



	Power Rating (kW)	Rated Output Current (A)	Rated Input Current (A)	Adaptive Motor (kW)	Brake Chopper	DC Reactor
GK900-4T0.75LB	0.75	2.5	3.5	0.75	●	○
GK900-4T1.5LB	1.5	3.8	5	1.5	●	○
GK900-4T2.2LB	2.2	5.5	6	2.2	●	○
GK900-4T3.7LB	3.7	8	9.3	3.7	●	○
GK900-4T5.5LB	5.5	11	12.3	5.5	●	○
GK900-4T7.5LB	7.5	17	19.3	7.5	●	○
GK900-4T11LB	11	23	27.8	11	●	○
GK900-4T15LB	15	30	32.8	15	●	○
GK900-4T18.5LB	18.5	37	44	18.5	●	○
GK900-4T22LB	22	45	50	22	●	○
GK900-4T30LB	30	58	62.8	30	●	○
GK900-4T37L(B)*	37	75	80	37	●	○
GK900-4T45L(B)*	45	88	93	45	●	○
GK900-4T55L(B)*	55	112	102	55	●	●
GK900-4T75L(B)*	75	139	133	75	●	●
GK900-4T90L(B)*	90	176	160	90	●	●
GK900-4T110L(B)*	110	210	192	110	●	●
GK900-4T132L	132	250	232	132	○	●
GK900-4T160L	160	304	285	160	○	●
GK900-4T185L	185	350	326	185	○	●
GK900-4T200L	200	380	354	200	○	●
GK900-4T220L	220	426	403	220	○	●
GK900-4T250L	250	465	441	250	○	●
GK900-4T280L	280	520	489	280	○	●
GK900-4T315L	315	585	566	315	○	●
GK900-4T355L	355	650	624	355	○	●
GK900-4T400L	400	725	699	400	○	●
GK900-4T450L	450	820	790	450	○	●

*Indicates that the built-in brake chopper is optional; e.g., GK900-4T37L(B): model GK900-4T37L without brake chopper, model GK900-4T37LB with brake chopper.

● Inbuilt

○ Externally mounted

● Inbuilt optional

○ None



	Power Rating (kW)	Rated Output Current (A)	Rated Input Current (A)	Adaptive Motor (kW)	Brake Chopper	DC Reactor
GK900-4T500L	500	860	828	500	○	⊙
GK900-4T560L	560	1020	980	560	○	⊙
GK900-4T630L	630	1140	1152	630	○	⊙
GK900-4T710L	710	1320	1287	710	○	⊙
GK900-4T800L	800	1500	1440	800	○	⊙
GK900-4T900L	900	1620	1744.2	900	○	⊙
GK900-4T1000L	1000	1720	1938.0	1000	○	⊙
GK900-4T1120L	1120	1980	2170.6	1120	○	⊙

*Indicates that the built-in brake chopper is optional; e.g., GK900-4T37L(B): model GK900-4T37L without brake chopper, model GK900-4T37LB with brake chopper.

⊙ Inbuilt

○ Externally mounted

⊙ Inbuilt optional

○ None