OWNER'S CERTIFICATE:

I HEREBY CERTIFY THAT I AM THE OWNER OF, OR AM INTERESTED IN, THE LAND INCLUDED WITHIN THE SUBDIVISION SHOWN ON THE ANNEXED MAP AND THAT I AM THE ONLY PERSON WHOSE CONSENT IS NECESSARY TO PASS A CLEAR TITLE TO SAID LAND. I CONSENT TO THE MAKING AND RECORDATION OF SAID MAP AND SUBDIVISION AS SHOWN WITHIN THE COLORED BORDER LINES.

CLARENCE L. JOHNSON

Johnson clarece

SHEETS 7 SHEET 1 OF

13,246 PARCEL MAP NO, COUNTY OF SANTA BARBARA, CALIFORNIA

BEING A PORTION OF RANCHO CANADA DE LOS PINOS (COLLEGE RANCH) IN THE COUNTY OF SANTA BARBARA, OF THE STATE OF CALIFORNIA, ACCORDING TO THE MAP THEREOF FILED IN RACK NO. 3 MAP 4, THE OFFICE OF THE COUNTY RECORDER OF SAID COUNTY.

Š Penfield Smith 111 EAST VICTORIA STREET POST OFFICE BOX 98 · SANTA

FEBRUARY 19

RECORDER'S CERTIFICATE:

8:00 ΑT FILED THIS **Z/S**† DAY OF **Ju/V** 1982, IN BOOK **30** OF PARCEL MAPS, AT PAGES 10 AND THE REQUEST OF PENFIELD & SMITH ENGINEERS, INC.

#8.00

THE FOLLOWING SIGNATURES OF EASEMENT HOLDERS HAVE BEEN OMITTED IN ACCORDANCE WITH SECTION 66436 (C) (1) OF THE GOVERNMENT CODE AS THEIR INTEREST CANNOT RIPEN INTO A FEE:

EASEMENT HOLDERS:

ASSOCIATED TELEPHONE COMPANY, LTD. PER DEEDS RECORDED FEBRUARY 21, 1950 AS INSTRUMENT NO. 2467 IN BOOK 901 PAGE 113 AND AUGUST 13, 1951 AS INSTRUMENT NO. 12015 IN BOOK 1009 PAGE 166, BOTH OF OFFICIAL RECORDS.

BY: Mary Rose Macdonald HOWARD C. MENZEL COUNTY CLERK-RECORDER, SANTA BARBARA COUNTY, CALIFORNIA

COUNTY SURVEYOR'S CERTIFICATE:

SUB Η Η Э THIS MAP CONFORMS WITH THE REQUIREMENTS DIVISION MAP ACT AND LOCAL ORDINANCE.

14,1982 DATE JUL

CHARLES F. WAGNER COUNTY SURVEYOR BY:

SURVEYOR'S CERTIFICATE:

⋖

ON FEBRUARY 19, 1982, BEFORE ME, THE UNDERSIGNED, NOTARY PUBLIC IN AND FOR SAID COUNTY AND STATE, PERSONALLY

S S

 $\cap \cap \cap$

COUNTY OF JANTA BARBARA STATE OF CALIFORNIA COUNTY OF

9

APPEARED CLARENCE L. JOHNSON KNOWN TO ME TO BE THE PERSON WHOSE NAME IS SUBSCRIBED TO THE WITHIN INSTRUMENT AND ACKNOWLEDGED THAT HE EXECUTED SAME AS OWNER.

REQUEST THE THIS MAP WAS PREPARED BY ME OR UNDER MY DIRECTION AND 18 BASED UPON A FIELD SURVEY IN CONFORMANCE WITH THE REQUIREMENTS OF THE SUBDIVISION MAP ACT AT

NOSNHOS CLARENCE FEBRUARY 1982. I HEREBY STATE THAT PARCEL MAP SUBSTANTIALLY CONFORMS TO THE APPROVED OR CONDITIONALLY APPROVED TENTATIVE MAP, IF ANY.

GRAHAM, HARL W. G

PRINT 20/84

*

MY COMMISSION EXPIRES_

GROOM

NOTARY PUBLIC IN AND FOR SAID COUNTY AND STATE

WITNESS MY HAND AND OFFICIAL SEAL

CONSTRUCTION REQUIREMENTS:

GOVERNMENT CODE. THE FOLLOWING CONSTRUCTION REQUIREMENTS ACCORDANCE WITH SECTION 66411.1 OF THE

COUNTY FIRE DEPARTMENT:

- A FIRE HYDRANT SHALL BE INSTALLED WITHIN 600 FEET DRIVING DISTANCE OF ALL STRUCTURES. THE HYDRANT (S) SHALL BE OF THE TYPE APPROVED BY THE SANTA BARBARA COUNTY FIRE DEPARTMENT, FIRE PROTECTION DIVISION, AND ACCEPTABLE BY THE WATER COMPANY OR DISTRICT SERVING THE PROPERTY.
- THE HYDRANT AND MAIN SUPPLYING SAME SHALL BE INSTALLED IN ACCORDANCE WITH THE STANDARDS ESTABLISHED BY THE INSURANCE SERVICES OFFICE AND THE AMERICAN WATER WORKS ASSOCIATION, AND SUPPLY A MINIMUM OF 750 GALLONS PERMINUTE UNDER NORMAL FLOW PRESSURE.
- COMPANY WATER THE EVENT THE PROPERTY IS NOT SERVED BY A W DISTRICT THE FOLLOWING SHALL BE APPLICABLE: N O 2.
- AN ELEVATED STORAGE TANK WITH AT LEAST 5,000 GALLON CAPACITY SHALL BE INSTALLED ON EACH PARCEL FOR FIRE PROTECTION. Ġ.
- A FEET SUCH IF STORAGE TANK IS OVER 250 FEET FROM STRUCTURE, A WATER MAIN SHALL BE INSTALLED, BROUGHT WITHIN 250 FORIVING DISTANCE FROM STRUCTURES, AND LOCATED IN SA MANNER THAT THE FIRE DEPARTMENT WILL BE ABLE TO CONNECT TO THE OUTLET. Θ
- 4 0 THE OUTLET ON STORAGE TANK SHALL BE A GATED VALVE, AT LEAST 18" ABOVE GRADE, AT LEAST 4" IN DIAMETER, WITH NATIONAL STANDARD FIRE DEPARTMENT THREAD, AND A CAP TPROTECT THE THREADS FROM DAMAGE. TANK TO BE MOUNTED ON A PERMANENT PAD. S
- IF STORAGE TANK IS LESS THAN 250 FEET DRIVING DISTANCE FROM STRUCTURES NO MAIN WILL BE REQUIRED. WATER TANK OR HYDRANT SHALL BE SERVICED BY AN ALL-WEATHER ROAD, 16 FEET IN WIDTH WHERE PRACTICAL, AND CAPABLE OF SUPPORTING A 16 TON FIRE VEHICLE. Ġ
- **B**E IF A MAIN IS INSTALLED FROM TANK TO STRUCTURE, IT SHALL 4" MINIMUM INSIDE DIAMETER TERMINATING WITH A 2-1/2" MINIMUM GATED VALVE AND OUTLET WITH NATIONAL STANDARD THREAD, AND A CAP INSTALLED TO PROTECT THE THREADS FROM DAMAGE. ш
- AUTO-AN Y FULL MET, AN WATER TANK SHALL BE MAINTAINED SUBSTANTIALLY TIMES. TO ASSURE THAT THIS REQUIREMENT IS M MATIC REFILLING SYSTEM MUST BE PROVIDED. Ľ.
 - ΒE CAN IF IT IS THE DESIRE OF THE APPLICANT, THE STORAGE CUMULATIVE IN A CENTRAL LOCATION WITH WATER MAINS HYDRANTS ATTACHED. G
- COMPLIANCE WITH THE ABOVE SHALL BE PRIOR TO ISSUANCE OF ANY BUILDING PERMIT OR CONDITIONAL USE PERMIT RELATING TO THIS PROPERTY. SUBSEQUENT REMOVAL OR ALTERATION OF THE TANK(S) OR APPURTENANCES THERETO IS A VIOLATION OF THE COUNTY FIRE CODE.
- ANY PRIVATE STREETS SHALL BE NAMED AND STREET SIGNS INSTALLED. BUILDING NUMBERS (MINIMUM 3") SHALL BE FROM THE STREET. 4
- STORED WATER SYSTEM MEET-LETTER, SUBMIT PLANS TO APPLICANT MAY SUBMIT PLANS FOR A ING THE SCOPE AND INTENT OF THIS THIS OFFICE. ٥.
- SYSTEMS SERVING EACH DWELLING TO BE INSTALLED PRIOR TO RECORDATION OR A SURETY BOND MAY BE OBTAINED GUARANTEEING INSTALLATION WITHIN ONE YEAR OF RECORDATION.
- FIRE TO BE A SMOKE DETECTOR APPROVED BY THE OFFICE OF THE STATE MARSHAL SHALL BE INSTALLED IN EACH UNIT. DETECTORS 'INSTALLED AS PER MANUFACTURERS INSTRUCTIONS.