

**Android API**

**Nathan Warner**



**Northern Illinois  
University**

Computer Science  
Northern Illinois University  
United States

## Contents

<b>1</b>	<b>Java Documentation</b>	<b>4</b>
1.1	Activity . . . . .	4
1.2	View . . . . .	20
1.3	ViewGroup . . . . .	32
1.4	ViewGroup.LayoutParams . . . . .	36
1.5	ViewGroup.MarginLayoutParams . . . . .	37
1.6	Color . . . . .	38
1.7	Context . . . . .	42
1.8	Configuration . . . . .	45
1.9	Resources . . . . .	51
1.10	DisplayMetrics . . . . .	55
1.11	Log . . . . .	58
1.12	WindowManager (Interface) . . . . .	60
1.13	Display . . . . .	64
1.14	ConstraintLayout . . . . .	66
1.15	ConstraintLayout.LayoutParams . . . . .	70
1.16	RelativeLayout . . . . .	74
1.17	RelativeLayout.LayoutParams . . . . .	77
1.18	LinearLayout . . . . .	78
1.19	LinearLayout.LayoutParams . . . . .	81
1.20	GridLayout . . . . .	82
1.21	GridLayout.LayoutParams . . . . .	86
1.22	GridLayout.Spec . . . . .	87
1.23	TableLayout . . . . .	88
1.24	TableLayout.LayoutParams . . . . .	90
1.25	TableRow . . . . .	91

1.26	FrameLayout . . . . .	92
1.27	FrameLayout.LayoutParams . . . . .	94
1.28	ListView . . . . .	95
1.29	TextView . . . . .	98
1.30	EditText . . . . .	112
1.31	InputType (Interface) . . . . .	113
1.32	Button . . . . .	116
1.33	ImageView . . . . .	117
1.34	ImageView.ScaleType (enum) . . . . .	120
1.35	ImageButton . . . . .	121
1.36	CompoundButton . . . . .	122
1.37	CheckBox . . . . .	124
1.38	RadioGroup . . . . .	125
1.39	RadioGroup.LayoutParams . . . . .	127
1.40	RadioButton . . . . .	128
1.41	AbsSpinner . . . . .	129
1.42	Spinner . . . . .	131
1.43	Progressbar . . . . .	133
1.44	AbsSeekBar . . . . .	137
1.45	SeekBar . . . . .	140
1.46	Drawable . . . . .	141
1.47	GradientDrawable . . . . .	145
1.48	Intent . . . . .	149
1.49	Animation . . . . .	152
1.50	AnimationSet . . . . .	155
1.51	AlphaAnimation . . . . .	157
1.52	RotateAnimation . . . . .	158
1.53	ScaleAnimation . . . . .	159
1.54	TranslateAnimation . . . . .	160
1.55	PreferenceManager . . . . .	161
1.56	SharedPreferences (interface) . . . . .	163
1.57	SharedPreferences.Editor (Interface) . . . . .	164
1.58	Menu (Interface) . . . . .	165

1.59	MenuItem (Interface) . . . . .	167
1.60	ContextMenu (interface) . . . . .	171
1.61	PopupMenu . . . . .	172
1.62	SubMenu (interface) . . . . .	173
1.63	MenuInflater . . . . .	174
1.64	Toast . . . . .	175
1.65	LayoutInflater (Abstract class) . . . . .	177
1.66	SQLiteDatabase . . . . .	179
1.67	Cursor (Interface) . . . . .	186
1.68	ScrollView . . . . .	189
1.69	HorizontalScrollView . . . . .	193

# Java Documentation

## 1.1 Activity

- Hierarchy

java.lang.Object → android.content.Context → android.content.ContextWrapper →  
android.view.ContextThemeWrapper → android.app.Activity

- Include

```
o android.app.Activity
```

- Constructors

```
o Activity()
```

- Public methods

- **void addContentView(View view, ViewGroup.LayoutParams params):** Add an additional content view to the activity.
- **void clearOverrideActivityTransition(int overrideType):** Clears the animations which are set from `overrideActivityTransition(int, int, int)`.
- **void closeContextMenu():** Programmatically closes the most recently opened context menu, if showing.
- **void closeOptionsMenu():** Programmatically closes the options menu.
- **PendingIntent createPendingResult(int requestCode, Intent data, int flags):** Create a new `PendingIntent` object which you can hand to others for them to use to send result data back to your `onActivityResult(int, int, Intent)` callback.
- **final void dismissDialog(int id):** This method was deprecated in API level 15. Use the new `DialogFragment` class with `FragmentManager` instead; this is also available on older platforms through the Android compatibility package.
- **final void dismissKeyboardShortcutsHelper():** Dismiss the Keyboard Shortcuts screen.
- **boolean dispatchGenericMotionEvent(MotionEvent ev):** Called to process generic motion events.
- **boolean dispatchKeyEvent(KeyEvent event):** Called to process key events.
- **boolean dispatchKeyShortcutEvent(KeyEvent event):** Called to process a key shortcut event.
- **boolean dispatchPopulateAccessibilityEvent(AccessibilityEvent event):** Called to process population of `AccessibilityEvents`.
- **boolean dispatchTouchEvent(MotionEvent ev):** Called to process touch screen events.
- **boolean dispatchTrackballEvent(MotionEvent ev):** Called to process trackball events.
- **void dump(String prefix, FileDescriptor fd, PrintWriter writer, String[] args):** Print the Activity's state into the given stream.

- **boolean enterPictureInPictureMode(PictureInPictureParams params):** Puts the activity in picture-in-picture mode if possible in the current system state.
- **void enterPictureInPictureMode():** Puts the activity in picture-in-picture mode if possible in the current system state.
- **<T extends View> T findViewById(int id):** Finds a view that was identified by the android:id XML attribute that was processed in onCreate(Bundle).
- **void finish():** Call this when your activity is done and should be closed.
- **void finishActivity(int requestCode):** Force finish another activity that you had previously started with startActivityForResult(Intent, int).
- **void finishActivityFromChild(Activity child, int requestCode):** This method was deprecated in API level 30. Use finishActivity(int) instead.
- **void finishAffinity():** Finish this activity as well as all activities immediately below it in the current task that have the same affinity.
- **void finishAfterTransition():** Reverses the Activity Scene entry Transition and triggers the calling Activity to reverse its exit Transition.
- **void finishAndRemoveTask():** Call this when your activity is done and should be closed and the task should be completely removed as a part of finishing the root activity of the task.
- **void finishFromChild(Activity child):** This method was deprecated in API level 30. Use finish() instead.
- **ActionBar getActionBar():** Retrieve a reference to this activity's ActionBar.
- **final Application getApplication():** Return the application that owns this activity.
- **ComponentCaller getCaller():** Returns the ComponentCaller instance of the app that started this activity.
- **ComponentName getCallingActivity():** Return the name of the activity that invoked this activity.
- **String getCallingPackage():** Return the name of the package that invoked this activity.
- **int getChangingConfigurations():** If this activity is being destroyed because it can not handle a configuration parameter being changed (and thus its onConfigurationChanged(android.content.res.Configuration) method is not being called), then you can use this method to discover the set of changes that have occurred while in the process of being destroyed.
- **ComponentName getComponentName():** Returns the complete component name of this activity.
- **Scene getContentScene():** Retrieve the Scene representing this window's current content.
- **TransitionManager getContentTransitionManager():** Retrieve the TransitionManager responsible for default transitions in this window.
- **ComponentCaller getCurrentCaller():** Returns the ComponentCaller instance of the app that re-launched this activity with a new intent via onNewIntent(Intent) or onActivityResult(int, int, Intent).
- **View getCurrentFocus():** Calls Window.getCurrentFocus() on the Window of this Activity to return the currently focused view.
- **FragmentManager getFragmentManager():** This method was deprecated in API level 28. Use FragmentActivity.getSupportFragmentManager()

- **ComponentCaller** `getInitialCaller()`: Returns the ComponentCaller instance of the app that initially launched this activity.
- **Intent** `getIntent()`: Returns the intent that started this activity.
- **Object** `getLastNonConfigurationInstance()`: Retrieve the non-configuration instance data that was previously returned by `onRetainNonConfigurationInstance()`.
- **String** `getLaunchedFromPackage()`: Returns the package name of the app that initially launched this activity.
- **int** `getLaunchedFromUid()`: Returns the uid of the app that initially launched this activity.
- **LayoutInflater** `getLayoutInflater()`: Convenience for calling `Window.getLayoutInflater()`.
- **LoaderManager** `getLoaderManager()`: This method was deprecated in API level 28. Use `FragmentManager.getSupportLoaderManager()`
- **String** `getLocalClassName()`: Returns class name for this activity with the package prefix removed.
- **int** `getMaxNumPictureInPictureActions()`: Return the number of actions that will be displayed in the picture-in-picture UI when the user interacts with the activity currently in picture-in-picture mode.
- **final MediaController** `getMediaController()`: Gets the controller which should be receiving media key and volume events while this activity is in the foreground.
- **MenuInflater** `getMenuInflater()`: Returns a MenuInflater with this context.
- **OnBackPressedDispatcher** `getOnBackPressedDispatcher()`: Returns the OnBackPressedDispatcher instance associated with the window that this activity is attached to.
- **final Activity** `getParent()`: This method was deprecated in API level 35. `ActivityGroup` is deprecated.
- **Intent** `getParentActivityIntent()`: Obtain an Intent that will launch an explicit target activity specified by this activity's logical parent.
- **SharedPreferences** `getPreferences(int mode)`: Retrieve a SharedPreferences object for accessing preferences that are private to this activity.
- **Uri** `getReferrer()`: Return information about who launched this activity.
- **int** `getRequestedOrientation()`: Returns the current requested orientation of the activity, which is either the orientation requested in the app manifest or the last orientation given to `setRequestedOrientation(int)`.
- **final SearchEvent** `getSearchEvent()`: During the `onSearchRequested()` callbacks, this function will return the SearchEvent that triggered the callback, if it exists.
- **final SplashScreen** `getSplashScreen()`: Get the interface that activity use to talk to the splash screen.
- **Object** `getSystemService(String name)`: Return the handle to a system-level service by name.
- **int** `getTaskId()`: Return the identifier of the task this activity is in.
- **final CharSequence** `getTitle()`:
- **final int** `getTitleColor()`:
- **VoiceInteractor** `getVoiceInteractor()`: Retrieve the active VoiceInteractor that the user is going through to interact with this activity.

- **final int getVolumeControlStream():** Gets the suggested audio stream whose volume should be changed by the hardware volume controls.
- **Window getWindow():** Retrieve the current Window for the activity.
- **WindowManager getWindowManager():** Retrieve the window manager for showing custom windows.
- **boolean hasWindowFocus():** Returns true if this activity's main window currently has window focus.
- **void invalidateOptionsMenu():** Declare that the options menu has changed, so should be recreated.
- **boolean isActivityTransitionRunning():** Returns whether there are any activity transitions currently running on this activity.
- **boolean isChangingConfigurations():** Check to see whether this activity is in the process of being destroyed in order to be recreated with a new configuration.
- **final boolean isChild():** This method was deprecated in API level 35. `ActivityGroup` is deprecated.
- **boolean isDestroyed():** Returns true if the final `onDestroy()` call has been made on the Activity, so this instance is now dead.
- **boolean isFinishing():** Check to see whether this activity is in the process of finishing, either because you called `finish()` on it or someone else has requested that it finished.
- **boolean isImmersive():** Bit indicating that this activity is "immersive" and should not be interrupted by notifications if possible.
- **boolean isInMultiWindowMode():** Returns true if the activity is currently in multi-window mode.
- **boolean isInPictureInPictureMode():** Returns true if the activity is currently in picture-in-picture mode.
- **boolean isLaunchedFromBubble():** Indicates whether this activity is launched from a bubble.
- **boolean isLocalVoiceInteractionSupported():** Queries whether the currently enabled voice interaction service supports returning a voice interactor for use by the activity.
- **boolean isTaskRoot():** Return whether this activity is the root of a task.
- **boolean isVoiceInteraction():** Check whether this activity is running as part of a voice interaction with the user.
- **boolean isVoiceInteractionRoot():** Like `isVoiceInteraction()`, but only returns true if this is also the root of a voice interaction.
- **final Cursor managedQuery(Uri uri, String[] projection, String selection, String[] selectionArgs, String sortOrder):** This method was deprecated in API level 15. Use `CursorLoader` instead.
- **boolean moveTaskToBack(boolean nonRoot):** Move the task containing this activity to the back of the activity stack.
- **boolean navigateUpTo(Intent upIntent):** Navigate from this activity to the activity specified by `upIntent`, finishing this activity in the process.
- **boolean navigateUpToFromChild(Activity child, Intent upIntent):** This method was deprecated in API level 30. Use `navigateUpTo(android.content.Intent)` instead.
- **void onActionModeFinished(ActionMode mode):** Notifies the activity that an action mode has finished.



- **void onActionModeStarted(ActionMode mode)**: Notifies the Activity that an action mode has been started.
- **void onActivityReenter(int resultCode, Intent data)**: Called when an activity you launched with an activity transition exposes this Activity through a returning activity transition, giving you the resultCode and any additional data from it.
- **void onActivityResult(int requestCode, int resultCode, Intent data, ComponentCaller caller)**: Same as onActivityResult(int, int, android.content.Intent), but with an extra parameter for the ComponentCaller instance associated with the app that sent the result.
- **void onAttachFragment(Fragment fragment)**: This method was deprecated in API level 28. Use FragmentActivity.onAttachFragment(androidx.fragment.app.Fragment)
- **void onAttachedToWindow()**: Called when the main window associated with the activity has been attached to the window manager.
- **void onBackPressed()**: This method was deprecated in API level 33. Use OnBackPressedCallback or androidx.activity.OnBackPressedCallback to handle back navigation instead.

Starting from Android 13 (API level 33), back event handling is moving to an ahead-of-time model and Activity.onBackPressed() and KeyEvent.KEYCODE\_BACK should not be used to handle back events (back gesture or back button click). Instead, an OnBackPressedCallback should be registered using Activity.getOnBackPressedDispatcher().registerOnBackPressedCallback(priority, callback).

- **void onConfigurationChanged(Configuration newConfig)**: Called by the system when the device configuration changes while your activity is running.
- **void onContentChanged()**: This hook is called whenever the content view of the screen changes (due to a call to Window setContentView or Window.addContentView).
- **boolean onContextItemSelected(MenuItem item)**: This hook is called whenever an item in a context menu is selected.
- **void onContextMenuClosed(Menu menu)**: This hook is called whenever the context menu is being closed (either by the user canceling the menu with the back/menu button, or when an item is selected).
- **void onCreate(Bundle savedInstanceState, PersistableBundle persistentState)**: Same as onCreate(android.os.Bundle) but called for those activities created with the attribute R.attr.persistableMode set to persistAcrossReboots.
- **void onCreateContextMenu(ContextMenu menu, View v, ContextMenu.ContextMenuInfo menuInfo)**: Called when a context menu for the view is about to be shown.
- **CharSequence onCreateDescription()**: Generate a new description for this activity.
- **void onCreateNavigateUpTaskStack(TaskStackBuilder builder)**: Define the synthetic task stack that will be generated during Up navigation from a different task.
- **boolean onCreateOptionsMenu(Menu menu)**: Initialize the contents of the Activity's standard options menu.
- **boolean onCreatePanelMenu(int featureId, Menu menu)**: Default implementation of Window.Callback.onCreatePanelMenu(int, Menu) for activities.

- **View onCreatePanelView(int featureId)**: Default implementation of Window.Callback.onCreatePanelView(int) for activities.
- **boolean onCreateThumbnail(Bitmap outBitmap, Canvas canvas)**: This method was deprecated in API level 28. Method doesn't do anything and will be removed in the future.
- **View onCreateView(View parent, String name, Context context, AttributeSet attrs)**: Standard implementation of LayoutInflater.Factory2.onCreateView(View, String, Context, AttributeSet) used when inflating with the LayoutInflater returned by Context.getSystemService(Class).
- **View onCreateView(String name, Context context, AttributeSet attrs)**: Standard implementation of LayoutInflater.Factory.onCreateView(String, Context, AttributeSet) used when inflating with the LayoutInflater returned by Context.getSystemService(Class).
- **void onDetachedFromWindow()**: Called when the main window associated with the activity has been detached from the window manager.
- **void onEnterAnimationComplete()**: Activities cannot draw during the period that their windows are animating in.
- **boolean onGenericMotionEvent(MotionEvent event)**: Called when a generic motion event was not handled by any of the views inside of the activity.
- **void onGetDirectActions(CancellationSignal cancellationSignal, Consumer<List<DirectAction>> callback)**: Returns the list of direct actions supported by the app.
- **boolean onKeyDown(int keyCode, KeyEvent event)**: Called when a key was pressed down and not handled by any of the views inside of the activity.
- **boolean onKeyLongPress(int keyCode, KeyEvent event)**: Default implementation of KeyEvent.Callback.onKeyLongPress(): always returns false (doesn't handle the event).
- **boolean onKeyMultiple(int keyCode, int repeatCount, KeyEvent event)**: Default implementation of KeyEvent.Callback.onKeyMultiple(): always returns false (doesn't handle the event).
- **boolean onKeyShortcut(int keyCode, KeyEvent event)**: Called when a key shortcut event is not handled by any of the views in the Activity.
- **boolean onKeyUp(int keyCode, KeyEvent event)**: Called when a key was released and not handled by any of the views inside of the activity.
- **void onLocalVoiceInteractionStarted()**: Callback to indicate that startLocalVoiceInteraction(android.os.Bundle) has resulted in a voice interaction session being started.
- **void onLocalVoiceInteractionStopped()**: Callback to indicate that the local voice interaction has stopped either because it was requested through a call to stopLocalVoiceInteraction() or because it was canceled by the user.
- **void onLowMemory()**: This is called when the overall system is running low on memory, and actively running processes should trim their memory usage.
- **boolean onMenuItemSelected(int featureId, MenuItem item)**: Default implementation of Window.Callback.onMenuItemSelected(int, MenuItem) for activities.
- **boolean onMenuOpened(int featureId, Menu menu)**: Called when a panel's menu is opened by the user.
- **void onMultiWindowModeChanged(boolean isInMultiWindowMode)**: This method was deprecated in API level 26. Use onMultiWindowModeChanged(boolean, android.content.res.Configuration) instead.

- **void onMultiWindowModeChanged(boolean isInMultiWindowMode, Configuration newConfig)**: Called by the system when the activity changes from fullscreen mode to multi-window mode and visa-versa.
- **boolean onNavigateUp()**: This method is called whenever the user chooses to navigate Up within your application’s activity hierarchy from the action bar.
- **boolean onNavigateUpFromChild(Activity child)**: This method was deprecated in API level 30. Use `onNavigateUp()` instead.
- **void onNewIntent(Intent intent, ComponentCaller caller)**: Same as `onNewIntent(android.content.Intent)`, but with an extra parameter for the `ComponentCaller` instance associated with the app that sent the intent.
- **boolean onOptionsItemSelected(MenuItem item)**: This hook is called whenever an item in your options menu is selected.
- **void onOptionsMenuClosed(Menu menu)**: This hook is called whenever the options menu is being closed (either by the user canceling the menu with the back/menu button, or when an item is selected).
- **void onPanelClosed(int featureId, Menu menu)**: Default implementation of `Window.Callback.onPanelClosed(int, Menu)` for activities.
- **void onPerformDirectAction(String actionId, Bundle arguments, CancellationSignal cancellationSignal, Consumer<Bundle> resultListener)**: This is called to perform an action previously defined by the app.
- **void onPictureInPictureModeChanged(boolean isInPictureInPictureMode, Configuration newConfig)**: Called by the system when the activity changes to and from picture-in-picture mode.
- **void onPictureInPictureModeChanged(boolean isInPictureInPictureMode)**: This method was deprecated in API level 26. Use `onPictureInPictureModeChanged(boolean, android.content.res.Configuration)` instead.
- **boolean onPictureInPictureRequested()**: This method is called by the system in various cases where picture in picture mode should be entered if supported.
- **void onPictureInPictureUiStateChanged(PictureInPictureUiState pipState)**: Called by the system when the activity is in PiP and has state changes.
- **void onPostCreate(Bundle savedInstanceState, PersistableBundle persistentState)**: This is the same as `onPostCreate(android.os.Bundle)` but is called for activities created with the attribute `R.attr.persistableMode` set to `persistAcrossReboots`.
- **void onPrepareNavigateUpTaskStack(TaskStackBuilder builder)**: Prepare the synthetic task stack that will be generated during Up navigation from a different task.
- **boolean onPrepareOptionsMenu(Menu menu)**: Prepare the Screen’s standard options menu to be displayed.
- **boolean onPreparePanel(int featureId, View view, Menu menu)**: Default implementation of `Window.Callback.onPreparePanel(int, View, Menu)` for activities.
- **void onProvideAssistContent(AssistContent outContent)**: This is called when the user is requesting an assist, to provide references to content related to the current activity.
- **void onProvideAssistData(Bundle data)**: This is called when the user is requesting an assist, to build a full `Intent.ACTION_ASSIST` Intent with all of the context of the current application.

- **void onProvideKeyboardShortcuts(List<KeyboardShortcutGroup> data, Menu menu, int deviceId):** Called when Keyboard Shortcuts are requested for the current window.
- **Uri onProvideReferrer():** Override to generate the desired referrer for the content currently being shown by the app.
- **void onRequestPermissionsResult(int requestCode, String[] permissions, int[] grantResults):** Callback for the result from requesting permissions.
- **void onRequestPermissionsResult(int requestCode, String[] permissions, int[] grantResults, int deviceId):** Callback for the result from requesting permissions.
- **void onRestoreInstanceState(Bundle savedInstanceState, PersistableBundle persistentState):** This is the same as `onRestoreInstanceState(android.os.Bundle)` but is called for activities created with the attribute `R.attr.persistableMode` set to `persistAcrossReboots`.
- **Object onRetainNonConfigurationInstance():** Called by the system, as part of destroying an activity due to a configuration change, when it is known that a new instance will immediately be created for the new configuration.
- **void onSaveInstanceState(Bundle outState, PersistableBundle outPersistentState):** This is the same as `onSaveInstanceState(Bundle)` but is called for activities created with the attribute `R.attr.persistableMode` set to `persistAcrossReboots`.
- **boolean onSearchRequested(SearchEvent searchEvent):** This hook is called when the user signals the desire to start a search.
- **boolean onSearchRequested():** Called when the user signals the desire to start a search.
- **void onStateNotSaved():** This method was deprecated in API level 29. Starting with `Build.VERSION_CODES.P` `onSaveInstanceState` is called after `onStop()`, so this hint isn't accurate anymore: you should consider your state not saved in between `onStart` and `onStop` callbacks inclusively.
- **void onTopResumedActivityChanged(boolean isTopResumedActivity):** Called when activity gets or loses the top resumed position in the system.
- **boolean onTouchEvent(MotionEvent event):** Called when a touch screen event was not handled by any of the views inside of the activity.
- **boolean onTrackballEvent(MotionEvent event):** Called when the trackball was moved and not handled by any of the views inside of the activity.
- **void onTrimMemory(int level):** Called when the operating system has determined that it is a good time for a process to trim unneeded memory from its process.
- **void onUserInteraction():** Called whenever a key, touch, or trackball event is dispatched to the activity.
- **void onVisibleBehindCanceled():** This method was deprecated in API level 26. This method's functionality is no longer supported as of `Build.VERSION_CODES.O` and will be removed in a future release.
- **void onWindowAttributesChanged(WindowManager.LayoutParams params):** This is called whenever the current window attributes change.
- **void onWindowFocusChanged(boolean hasFocus):** Called when the current Window of the activity gains or loses focus.
- **ActionMode onWindowStartingActionMode(ActionMode.Callback callback, int type):** Called when an action mode is being started for this window.

- **ActionMode onWindowStartingActionMode(ActionMode.Callback callback)**: Give the Activity a chance to control the UI for an action mode requested by the system.
- **void openContextMenu(View view)**: Programmatically opens the context menu for a particular view.
- **void openOptionsMenu()**: Programmatically opens the options menu.
- **void overrideActivityTransition(int overrideType, int enterAnim, int exitAnim, int backgroundColor)**: Customizes the animation and background color for activity transitions.
- **void overrideActivityTransition(int overrideType, int enterAnim, int exitAnim)**: Customizes the animation for activity transitions.
- **void overridePendingTransition(int enterAnim, int exitAnim)**: This method was deprecated in API level 34. Use `overrideActivityTransition(int, int, int)` instead.
- **void overridePendingTransition(int enterAnim, int exitAnim, int backgroundColor)**: This method was deprecated in API level 34. Use `overrideActivityTransition(int, int, int, int)` instead.
- **void postponeEnterTransition()**: Postpone the entering activity transition when Activity was started with `ActivityOptions.makeSceneTransitionAnimation(Activity, android.util.Pair[])`.
- **void recreate()**: Cause this Activity to be recreated with a new instance.
- **void registerActivityLifecycleCallbacks(Application.ActivityLifecycleCallbacks callback)**: Register an `Application.ActivityLifecycleCallbacks` instance that receives lifecycle callbacks for only this Activity.
- **void registerComponentCallbacks(ComponentCallbacks callback)**: Add a new `ComponentCallbacks` to the base application of the Context, which will be called at the same times as the `ComponentCallbacks` methods of activities and other components are called.
- **void registerForContextMenu(View view)**: Registers a context menu to be shown for the given view (multiple views can show the context menu).
- **void registerScreenCaptureCallback(Executor executor, Activity.ScreenCaptureCallback callback)**: Registers a screen capture callback for this activity.
- **boolean releaseInstance()**: Ask that the local app instance of this activity be released to free up its memory.
- **final void removeDialog(int id)**: This method was deprecated in API level 15. Use the new `DialogFragment` class with `FragmentManager` instead; this is also available on older platforms through the Android compatibility package.
- **void reportFullyDrawn()**: Report to the system that your app is now fully drawn, for diagnostic and optimization purposes.
- **DragAndDropPermissions requestDragAndDropPermissions(DragEvent event)**: Create `DragAndDropPermissions` object bound to this activity and controlling the access permissions for content URIs associated with the `DragEvent`.
- **void requestFullscreenMode(int request, OutcomeReceiver<Void, Throwable> approvalCallback)**: Request to put the activity into fullscreen.
- **final void requestOpenInBrowserEducation()**: Requests to show the 201cOpen in browser201d education.
- **final void requestPermissions(String[] permissions, int requestCode, int deviceId)**: Requests permissions to be granted to this application.

- **final void requestPermissions(String[] permissions, int requestCode):** Requests permissions to be granted to this application.
- **final void requestShowKeyboardShortcuts():** Request the Keyboard Shortcuts screen to show up.
- **boolean requestVisibleBehind(boolean visible):** This method was deprecated in API level 26. This method's functionality is no longer supported as of Build.VERSION\_CODES.O and will be removed in a future release.
- **final boolean requestWindowFeature(int featureId):** Enable extended window features.
- **final <T extends View> T requireViewById(int id):** Finds a view that was identified by the android:id XML attribute that was processed in onCreate(Bundle), or throws an IllegalArgumentException if the ID is invalid, or there is no matching view in the hierarchy.
- **final void runOnUiThread(Runnable action):** Runs the specified action on the UI thread.
- **void setActionBar(Toolbar toolbar):** Set a Toolbar to act as the ActionBar for this Activity window.
- **void setAllowCrossUidActivitySwitchFromBelow(boolean allowed):** Specifies whether the activities below this one in the task can also start other activities or finish the task.
- **void setContentTransitionManager(TransitionManager tm):** Set the TransitionManager to use for default transitions in this window.
- **void setContentView(View view, ViewGroup.LayoutParams params):** Set the activity content to an explicit view.
- **void setContentView(View view):** Set the activity content to an explicit view.
- **void setContentView(int layoutResID):** Set the activity content from a layout resource.
- **final void setDefaultKeyMode(int mode):** Select the default key handling for this activity.
- **void setEnterSharedElementCallback(SharedElementCallback callback):** When ActivityOptions.makeSceneTransitionAnimation(Activity, android.view.View, String) was used to start an Activity, callback will be called to handle shared elements on the launched Activity.
- **void setExitSharedElementCallback(SharedElementCallback callback):** When ActivityOptions.makeSceneTransitionAnimation(Activity, android.view.View, String) was used to start an Activity, callback will be called to handle shared elements on the launching Activity.
- **final void setFeatureDrawable(int featureId, Drawable drawable):** Convenience for calling Window.setFeatureDrawable(int, Drawable).
- **final void setFeatureDrawableAlpha(int featureId, int alpha):** Convenience for calling Window.setFeatureDrawableAlpha(int, int).
- **final void setFeatureDrawableResource(int featureId, int resId):** Convenience for calling Window.setFeatureDrawableResource(int, int).
- **final void setFeatureDrawableUri(int featureId, Uri uri):** Convenience for calling Window.setFeatureDrawableUri(int, Uri).
- **void setFinishOnTouchOutside(boolean finish):** Sets whether this activity is finished when touched outside its window's bounds.

- **void setImmersive(boolean i)**: Adjust the current immersive mode setting.
- **void setInheritShowWhenLocked(boolean inheritShowWhenLocked)**: Specifies whether this Activity should be shown on top of the lock screen whenever the lockscreen is up and this activity has another activity behind it with the showWhenLock attribute set.
- **void setIntent(Intent newIntent)**: Changes the intent returned by getIntent().
- **void setIntent(Intent newIntent, ComponentCaller newCaller)**: Changes the intent returned by getIntent(), and ComponentCaller returned by getCaller().
- **void setLocusContext(LocusId locusId, Bundle bundle)**: Sets the LocusId for this activity.
- **final void setMediaController(MediaController controller)**: Sets a MediaController to send media keys and volume changes to.
- **void setPictureInPictureParams(PictureInPictureParams params)**: Updates the properties of the picture-in-picture activity, or sets it to be used later when enterPictureInPictureMode() is called.
- **final void setProgress(int progress)**: This method was deprecated in API level 24. No longer supported starting in API 21.
- **final void setProgressBarIndeterminate(boolean indeterminate)**: This method was deprecated in API level 24. No longer supported starting in API 21.
- **final void setProgressBarIndeterminateVisibility(boolean visible)**: This method was deprecated in API level 24. No longer supported starting in API 21.
- **final void setProgressBarVisibility(boolean visible)**: This method was deprecated in API level 24. No longer supported starting in API 21.
- **void setRecentsScreenshotEnabled(boolean enabled)**: If set to false, this indicates to the system that it should never take a screenshot of the activity to be used as a representation in recents screen.
- **void setRequestedOrientation(int requestedOrientation)**: Change the desired orientation of this activity.
- **final void setResult(int resultCode, Intent data)**: Call this to set the result that your activity will return to its caller.
- **final void setResult(int resultCode)**: Call this to set the result that your activity will return to its caller.
- **final void setSecondaryProgress(int secondaryProgress)**: This method was deprecated in API level 24. No longer supported starting in API 21.
- **void setShouldDockBigOverlays(boolean shouldDockBigOverlays)**: Specifies a preference to dock big overlays like the expanded picture-in-picture on TV (see PictureInPictureParams.Builder.setExpandedAspectRatio).
- **void setShowWhenLocked(boolean showWhenLocked)**: Specifies whether an Activity should be shown on top of the lock screen whenever the lockscreen is up and the activity is resumed.
- **void setTaskDescription(ActivityManager.TaskDescription taskDescription)**: Sets information describing the task with this activity for presentation inside the Recents System UI.
- **void setTheme(int resid)**: Set the base theme for this context.
- **void setTitle(CharSequence title)**: Change the title associated with this activity.
- **void setTitle(int titleId)**: Change the title associated with this activity.

- **void setTitleColors(int textColor):** This method was deprecated in API level 21. Use actionBar styles instead.
- **boolean setTranslucent(boolean translucent):** Convert an activity, which particularly with `R.attr.windowIsTranslucent` or `R.attr.windowIsFloating` attribute, to a fullscreen opaque activity, or convert it from opaque back to translucent.
- **void setTurnScreenOn(boolean turnScreenOn):** Specifies whether the screen should be turned on when the Activity is resumed.
- **void setVisible(boolean visible):** Control whether this activity's main window is visible.
- **final void setVolumeControlStream(int streamType):** Suggests an audio stream whose volume should be changed by the hardware volume controls.
- **void setVrModeEnabled(boolean enabled, ComponentName requestedComponent):** Enable or disable virtual reality (VR) mode for this Activity.
- **boolean shouldDockBigOverlays():** Returns whether big overlays should be docked next to the activity as set by `setShouldDockBigOverlays(boolean)`.
- **boolean shouldShowRequestPermissionRationale(String permission):** Gets whether you should show UI with rationale before requesting a permission.
- **boolean shouldShowRequestPermissionRationale(String permission, int deviceId):** Gets whether you should show UI with rationale before requesting a permission.
- **boolean shouldUpRecreateTask(Intent targetIntent):** Returns true if the app should recreate the task when navigating 'up' from this activity by using `targetIntent`.
- **boolean showAssist(Bundle args):** Ask to have the current assistant shown to the user.
- **final boolean showDialog(int id, Bundle args):** This method was deprecated in API level 15. Use the new `DialogFragment` class with `FragmentManager` instead; this is also available on older platforms through the Android compatibility package.
- **final void showDialog(int id):** This method was deprecated in API level 15. Use the new `DialogFragment` class with `FragmentManager` instead; this is also available on older platforms through the Android compatibility package.
- **void showLockTaskEscapeMessage():** Shows the user the system defined message for telling the user how to exit lock task mode.
- **ActionMode startActionMode(ActionMode.Callback callback, int type):** Start an action mode of the given type.
- **ActionMode startActionMode(ActionMode.Callback callback):** Start an action mode of the default type `ActionMode.TYPE_PRIMARY`.
- **void startActivities(Intent[] intents, Bundle options):** Launch a new activity.
- **void startActivities(Intent[] intents):** Same as `startActivities(android.content.Intent[], android.os.Bundle)` with no options specified.
- **void startActivity(Intent intent):** Same as `startActivity(android.content.Intent, android.os.Bundle)` with no options specified.
- **void startActivity(Intent intent, Bundle options):** Launch a new activity.
- **void startActivityForResult(Intent intent, int requestCode):** Same as calling `startActivityForResult(android.content.Intent, int, android.os.Bundle)` with no options.



- **void startActivityForResult(Intent intent, int requestCode, Bundle options):** Launch an activity for which you would like a result when it finished.
- **void startActivityFromChild(Activity child, Intent intent, int requestCode):** This method was deprecated in API level 30. Use `androidx.fragment.app.FragmentActivity#startActivityFromFragment(androidx.fragment.app.Fragment, Intent, int)`
- **void startActivityFromChild(Activity child, Intent intent, int requestCode, Bundle options):** This method was deprecated in API level 30. Use `androidx.fragment.app.FragmentActivity#startActivityFromFragment(androidx.fragment.app.Fragment, Intent, int, Bundle)`
- **void startActivityFromFragment(Fragment fragment, Intent intent, int requestCode, Bundle options):** This method was deprecated in API level 28. Use `androidx.fragment.app.FragmentActivity#startActivityFromFragment(androidx.fragment.app.Fragment, Intent, int, Bundle)`
- **void startActivityFromFragment(Fragment fragment, Intent intent, int requestCode):** This method was deprecated in API level 28. Use `androidx.fragment.app.FragmentActivity#startActivityFromFragment(androidx.fragment.app.Fragment, Intent, int)`
- **boolean startActivityIfNeeded(Intent intent, int requestCode, Bundle options):** A special variation to launch an activity only if a new activity instance is needed to handle the given Intent.
- **boolean startActivityIfNeeded(Intent intent, int requestCode):** Same as calling `startActivityIfNeeded(android.content.Intent, int, android.os.Bundle)` with no options.
- **void startIntentSender(IntentSender intent, Intent fillInIntent, int flagsMask, int flagsValues, int extraFlags):** Same as calling `startIntentSender(android.content.IntentSender, android.content.Intent, int, int, int, android.os.Bundle)` with no options.
- **void startIntentSender(IntentSender intent, Intent fillInIntent, int flagsMask, int flagsValues, int extraFlags, Bundle options):** Like `startActivity(android.content.Intent, android.os.Bundle)`, but taking a `IntentSender` to start; see `startIntentSenderForResult(android.content.IntentSender, int, android.content.Intent, int, int, int, android.os.Bundle)` for more information.
- **void startIntentSenderForResult(IntentSender intent, int requestCode, Intent fillInIntent, int flagsMask, int flagsValues, int extraFlags):** Same as calling `startIntentSenderForResult(android.content.IntentSender, int, android.content.Intent, int, int, int, android.os.Bundle)` with no options.
- **void startIntentSenderForResult(IntentSender intent, int requestCode, Intent fillInIntent, int flagsMask, int flagsValues, int extraFlags, Bundle options):** Like `startActivityForResult(android.content.Intent, int)`, but allowing you to use a `IntentSender` to describe the activity to be started.
- **void startIntentSenderFromChild(Activity child, IntentSender intent, int requestCode, Intent fillInIntent, int flagsMask, int flagsValues, int extraFlags, Bundle options):** This method was deprecated in API level 30. Use `startIntentSenderForResult(android.content.IntentSender, int, android.content.Intent, int, int, int, android.os.Bundle)` instead.
- **void startIntentSenderFromChild(Activity child, IntentSender intent, int requestCode, Intent fillInIntent, int flagsMask, int flagsValues, int extraFlags):** This method was deprecated in API level 30. Use `startIntentSenderForResult(android.content.IntentSender, int, android.content.Intent, int, int, int)` instead.

- **void startLocalVoiceInteraction(Bundle privateOptions):** Starts a local voice interaction session.
- **void startLockTask():** Request to put this activity in a mode where the user is locked to a restricted set of applications.
- **void startManagingCursor(Cursor c):** This method was deprecated in API level 15. Use the new CursorLoader class with LoaderManager instead; this is also available on older platforms through the Android compatibility package.
- **boolean startNextMatchingActivity(Intent intent, Bundle options):** Special version of starting an activity, for use when you are replacing other activity components.
- **boolean startNextMatchingActivity(Intent intent):** Same as calling startNextMatchingActivity(android.content.Intent, android.os.Bundle) with no options.
- **void startPostponedEnterTransition():** Begin postponed transitions after postponeEnterTransition() was called.
- **void startSearch(String initialQuery, boolean selectInitialQuery, Bundle appSearchData, boolean globalSearch):** This hook is called to launch the search UI.
- **void stopLocalVoiceInteraction():** Request to terminate the current voice interaction that was previously started using startLocalVoiceInteraction(android.os.Bundle).
- **void stopLockTask():** Stop the current task from being locked.
- **void stopManagingCursor(Cursor c):** This method was deprecated in API level 15. Use the new CursorLoader class with LoaderManager instead; this is also available on older platforms through the Android compatibility package.
- **void takeKeyEvents(boolean get):** Request that key events come to this activity.
- **void triggerSearch(String query, Bundle appSearchData):** Similar to startSearch(String, boolean, Bundle, boolean), but actually fires off the search query after invoking the search dialog.
- **void unregisterActivityLifecycleCallbacks(Application.ActivityLifecycleCallbacks callback):** Unregister an Application.ActivityLifecycleCallbacks previously registered with registerActivityLifecycleCallbacks(ActivityLifecycleCallbacks).
- **void unregisterComponentCallbacks(ComponentCallbacks callback):** Remove a ComponentCallbacks object that was previously registered with registerComponentCallbacks(android.content.ComponentCallbacks).
- **void unregisterForContextMenu(View view):** Prevents a context menu to be shown for the given view.
- **void unregisterScreenCaptureCallback(Activity.ScreenCaptureCallback callback):** Unregisters a screen capture callback for this surface.

- **Protected methods**

- **void attachBaseContext(Context newBase):** Set the base context for this ContextWrapper.
- **void onActivityResult(int requestCode, int resultCode, Intent data):** Called when an activity you launched exits, giving you the requestCode you started it with, the resultCode it returned, and any additional data from it.

- **void onApplyThemeResource(Resources.Theme theme, int resid, boolean first):** Called by `setTheme(Theme)` and `getTheme()` to apply a theme resource to the current Theme object.
- **void onChildTitleChanged(Activity childActivity, CharSequence title):**
- **void onCreate(Bundle savedInstanceState):** Called when the activity is starting.
- **Dialog onCreateDialog(int id):** This method was deprecated in API level 15. Old no-arguments version of `onCreateDialog(int, android.os.Bundle)`.
- **Dialog onCreateDialog(int id, Bundle args):** This method was deprecated in API level 15. Use the new `DialogFragment` class with `FragmentManager` instead; this is also available on older platforms through the Android compatibility package.
- **void onDestroy():** Perform any final cleanup before an activity is destroyed.
- **void onNewIntent(Intent intent):** This is called for activities that set `launchMode` to "singleTop" in their package, or if a client used the `Intent.FLAG_ACTIVITY_SINGLE_TOP` flag when calling `startActivity(Intent)`.
- **void onPause():** Called as part of the activity lifecycle when the user no longer actively interacts with the activity, but it is still visible on screen.
- **void onPostCreate(Bundle savedInstanceState):** Called when activity start-up is complete (after `onStart()` and `onRestoreInstanceState(Bundle)` have been called).
- **void onPostResume():** Called when activity resume is complete (after `onResume()` has been called).
- **void onPrepareDialog(int id, Dialog dialog, Bundle args):** This method was deprecated in API level 15. Use the new `DialogFragment` class with `FragmentManager` instead; this is also available on older platforms through the Android compatibility package.
- **void onPrepareDialog(int id, Dialog dialog):** This method was deprecated in API level 15. Old no-arguments version of `onPrepareDialog(int, android.app.Dialog, android.os.Bundle)`.
- **void onRestart():** Called after `onStop()` when the current activity is being re-displayed to the user (the user has navigated back to it).
- **void onRestoreInstanceState(Bundle savedInstanceState):** This method is called after `onStart()` when the activity is being re-initialized from a previously saved state, given here in `savedInstanceState`.
- **void onResume():** Called after `onRestoreInstanceState(Bundle)`, `onRestart()`, or `onPause()`.
- **void onSaveInstanceState(Bundle outState):** Called to retrieve per-instance state from an activity before being killed so that the state can be restored in `onCreate(Bundle)` or `onRestoreInstanceState(Bundle)` (the `Bundle` populated by this method will be passed to both).
- **void onStart():** Called after `onCreate(Bundle)` — or after `onRestart()` when the activity had been stopped, but is now again being displayed to the user.
- **void onStop():** Called when you are no longer visible to the user.
- **void onTitleChanged(CharSequence title, int color):**
- **void onUserLeaveHint():** Called as part of the activity lifecycle when an activity is about to go into the background as the result of user choice.

- **Fields**

- **protected static final int[] FOCUSED\_STATE\_SET:**

- **Constants**

- **int DEFAULT\_KEYS\_DIALER:** Use with `setDefaultKeyMode(int)` to launch the dialer during default key handling.
- **int DEFAULT\_KEYS\_DISABLE:** Use with `setDefaultKeyMode(int)` to turn off default handling of keys.
- **int DEFAULT\_KEYS\_SEARCH\_GLOBAL:** Use with `setDefaultKeyMode(int)` to specify that unhandled keystrokes will start a global search (typically web search, but some platforms may define alternate methods for global search)

See `android.app.SearchManager` for more details.

- **int DEFAULT\_KEYS\_SEARCH\_LOCAL:** Use with `setDefaultKeyMode(int)` to specify that unhandled keystrokes will start an application-defined search.
- **int DEFAULT\_KEYS\_SHORTCUT:** Use with `setDefaultKeyMode(int)` to execute a menu shortcut in default key handling.
- **int FULLSCREEN\_MODE\_REQUEST\_ENTER:** Request type of `requestFullscreenMode(int, android.os.OutcomeReceiver)`, to request enter fullscreen mode from multi-window mode.
- **int FULLSCREEN\_MODE\_REQUEST\_EXIT:** Request type of `requestFullscreenMode(int, android.os.OutcomeReceiver)`, to request exiting the requested fullscreen mode and restore to the previous multi-window mode.
- **int OVERRIDE\_TRANSITION\_CLOSE:** Request type of `overrideActivityTransition(int, int, int)` or `overrideActivityTransition(int, int, int, int)`, to override the closing transition.
- **int OVERRIDE\_TRANSITION\_OPEN:** Request type of `overrideActivityTransition(int, int, int)` or `overrideActivityTransition(int, int, int, int)`, to override the opening transition.
- **int RESULT\_CANCELED:** Standard activity result: operation canceled.
- **int RESULT\_FIRST\_USER:** Start of user-defined activity results.
- **int RESULT\_OK:** Standard activity result: operation succeeded.

## 1.2 View

- Hierarchy

java.lang.Object → android.view.View

- Include

```
0  android.view.View
```

- Constructors

```
0  View(Context context)
1  View(Context context, AttributeSet attrs)
2  View(Context context, AttributeSet attrs, int defStyleAttr)
3  View(Context context, AttributeSet attrs, int defStyleAttr,
    ↪    int defStyleRes)
```

- Public methods (Only most important)

- **void setId(int id)**: Sets the unique identifier for the view.
- **void setVisibility(int visibility)**: Sets whether the view is visible, invisible, or gone.
- **int getVisibility()**: Returns the current visibility state.
- **void setEnabled(boolean enabled)**: Enables or disables user interaction.
- **boolean isEnabled()**: Returns whether the view is currently enabled.
- **void setFocusable(boolean focusable)**: Controls whether the view can gain focus.
- **void requestFocus()**: Requests focus for this view.
- **boolean hasFocus()**: Returns true if this view currently has focus.
- **void invalidate()**: Redraws the view on screen.
- **void requestLayout()**: Requests a new layout pass for this view.
- **void layout(int l, int t, int r, int b)**: Assigns size and position to the view.
- **void setOnClickListener(View.OnClickListener l)**: Sets a callback to handle click events.
- **void setOnLongClickListener(View.OnLongClickListener l)**: Sets a listener for long press events.
- **boolean performClick()**: Programmatically triggers the click listener.
- **boolean onTouchEvent(MotionEvent event)**: Handles touch interactions.
- **boolean onKeyDown(int keyCode, KeyEvent event)**: Called when a hardware key is pressed.
- **void onDraw(Canvas canvas)**: Called to render the view's visual content.
- **void measure(int widthMeasureSpec, int heightMeasureSpec)**: Determines the measured size of the view.
- **int getWidth() / int getHeight()**: Return the current dimensions of the view.
- **int getLeft() / getTop() / getRight() / getBottom()**: Return the view's position relative to its parent.

- **ViewGroup.LayoutParams** **getLayoutParams()**: Returns layout parameters assigned to this view.
- **void setLayoutParams(ViewGroup.LayoutParams params)**: Updates the layout parameters.
- **ViewPropertyAnimator** **animate()**: Starts an animation for view properties (translation, alpha, rotation, etc.).
- **void setAlpha(float alpha)**: Sets the transparency (0.0 = fully transparent, 1.0 = opaque).
- **void setTranslationX(float translationX)**: Moves the view horizontally relative to its position.
- **void setTranslationY(float translationY)**: Moves the view vertically relative to its position.
- **void setRotation(float rotation)**: Rotates the view around its pivot point.
- **void setScaleX(float scaleX)** / **setScaleY(float scaleY)**: Scales the view's size in X or Y direction.
- **void setClickable(boolean clickable)**: Enables or disables clickability.
- **void setLongClickable(boolean longClickable)**: Enables long-click behavior.
- **boolean isClickable()**: Returns whether the view handles clicks.
- **boolean isLongClickable()**: Returns whether the view handles long clicks.
- **void setPressed(boolean pressed)**: Sets the pressed state for visual feedback.
- **boolean isPressed()**: Returns whether the view is currently pressed.
- **void setContentDescription(CharSequence contentDescription)**: Sets a description for accessibility tools.
- **CharSequence** **getContentDescription()**: Returns the view's accessibility description.
- **void announceForAccessibility(CharSequence text)**: Announces a message for accessibility services.

- **Protected methods**

- **boolean awakenScrollBars(int startDelay, boolean invalidate)**: Trigger the scrollbars to draw.
- **boolean awakenScrollBars(int startDelay)**: Trigger the scrollbars to draw.
- **boolean awakenScrollBars()**: Trigger the scrollbars to draw.
- **int computeHorizontalScrollExtent()**: Compute the horizontal extent of the scrollbar thumb within its range.
- **int computeHorizontalScrollOffset()**: Compute the horizontal offset of the scrollbar thumb within its range.
- **int computeHorizontalScrollRange()**: Compute the horizontal scrollable range.
- **int computeVerticalScrollExtent()**: Compute the vertical extent of the scrollbar thumb within its range.
- **int computeVerticalScrollOffset()**: Compute the vertical offset of the scrollbar thumb within its range.
- **int computeVerticalScrollRange()**: Compute the vertical scrollable range.
- **void dispatchDraw(Canvas canvas)**: Called by **draw()** to draw child views.

- **boolean dispatchGenericFocusedEvent(MotionEvent event)**: Dispatch a generic motion event to the currently focused view.
- **boolean dispatchGenericPointerEvent(MotionEvent event)**: Dispatch a generic motion event to the view under the first pointer.
- **boolean dispatchHoverEvent(MotionEvent event)**: Dispatch a hover event.
- **void dispatchRestoreInstanceState(SparseArray<Parcelable> container)**: Restores the state for this view and its children.
- **void dispatchSaveInstanceState(SparseArray<Parcelable> container)**: Saves the state for this view and its children.
- **void dispatchSetActivated(boolean activated)**: Dispatches activation to all of this view’s children.
- **void dispatchSetPressed(boolean pressed)**: Dispatches pressed state to all of this view’s children.
- **void dispatchSetSelected(boolean selected)**: Dispatches selected state to all of this view’s children.
- **void dispatchVisibilityChanged(View changedView, int visibility)**: Propagates a visibility change down the hierarchy.
- **void drawableStateChanged()**: Called whenever the view’s state changes in a way that affects its drawables.
- **boolean fitSystemWindows(Rect insets)**: (Deprecated) Apply window insets to adjust for system decorations.
- **float getBottomFadingEdgeStrength()**: Returns the intensity of the bottom faded edge.
- **int getBottomPaddingOffset()**: Amount by which to extend the bottom fading region.
- **float getLeftFadingEdgeStrength()**: Returns the intensity of the left faded edge.
- **int getLeftPaddingOffset()**: Amount by which to extend the left fading region.
- **float getRightFadingEdgeStrength()**: Returns the intensity of the right faded edge.
- **int getRightPaddingOffset()**: Amount by which to extend the right fading region.
- **float getTopFadingEdgeStrength()**: Returns the intensity of the top faded edge.
- **int getTopPaddingOffset()**: Amount by which to extend the top fading region.
- **boolean isPaddingOffsetRequired()**: Returns true if this view draws inside its padding and requires offset support.
- **int getSuggestedMinimumHeight()**: Returns the suggested minimum height for this view.
- **int getSuggestedMinimumWidth()**: Returns the suggested minimum width for this view.
- **boolean overScrollBy(int deltaX, int deltaY, int scrollX, int scrollY, int scrollRangeX, int scrollRangeY, int maxOverScrollX, int maxOverScrollY, boolean isTouchEvent)**: Scrolls the view with standard over-scroll behavior.
- **void onOverScrolled(int scrollX, int scrollY, boolean clampedX, boolean clampedY)**: Responds to an over-scroll operation.

- **void onScrollChanged(int l, int t, int oldl, int oldt)**: Called when the view scrolls its own content.
- **void onAttachedToWindow()**: Called when the view is attached to a window.
- **void onDetachedFromWindow()**: Called when the view is detached from a window.
- **void onConfigurationChanged(Configuration newConfig)**: Called when the app configuration changes (e.g., orientation).
- **void onDisplayHint(int hint)**: Receives a hint about whether the view is displayed or not.
- **int getWindowAttachCount()**: Returns how many times this view has been attached to a window.
- **void onLayout(boolean changed, int left, int top, int right, int bottom)**: Called when assigning size and position to child views.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view's width and height.
- **final void setMeasuredDimension(int measuredWidth, int measuredHeight)**: Must be called in **onMeasure()** to store measured dimensions.
- **void onSizeChanged(int w, int h, int oldw, int oldh)**: Called when the size of this view changes during layout.
- **void onDraw(Canvas canvas)**: Implement this to perform custom drawing.
- **final void onDrawScrollBars(Canvas canvas)**: Draws horizontal and vertical scrollbars.
- **void onAnimationStart()**: Called when an animation starts.
- **void onAnimationEnd()**: Called when an animation ends.
- **boolean onSetAlpha(int alpha)**: Called when a transform involving alpha occurs.
- **void onCreateContextMenu(ContextMenu menu)**: Implement if the view contributes items to a context menu.
- **ContextMenu.ContextMenuInfo getMenuInfo()**: Returns extra info associated with the context menu.
- **int[] onCreateDrawableState(int extraSpace)**: Generates the new drawable state array for this view.
- **boolean verifyDrawable(Drawable who)**: Override if the view displays custom drawables; return true for those drawables.
- **static int[] mergeDrawableStates(int[] baseState, int[] additionalState)**: Merges additional drawable states into the base state.
- **void onFocusChanged(boolean gainFocus, int direction, Rect previouslyFocusedRect)**: Called when the focus state of this view changes.
- **void onVisibilityChanged(View changedView, int visibility)**: Called when the visibility of this view or its ancestor changes.
- **void onWindowVisibilityChanged(int visibility)**: Called when the containing window's visibility changes (GONE, INVISIBLE, or VISIBLE).
- **Parcelable onSaveInstanceState()**: Generates a representation of this view's internal state for later restoration.
- **void onRestoreInstanceState(Parcelable state)**: Restores the view's internal state from a saved instance.



- **void dispatchRestoreInstanceState(SparseArray<Parcelable> container):**  
Restores hierarchy state for this view and its children.
- **void dispatchSaveInstanceState(SparseArray<Parcelable> container):**  
Saves hierarchy state for this view and its children.

- **Fields**

- **public static final Property<View, Float> ALPHA:** A Property wrapper around the alpha functionality handled by the `View.setAlpha(float)` and `View.getAlpha()` methods.
- **public static final Property<View, Float> ROTATION:** A Property wrapper around the rotation functionality handled by `View.setRotation(float)` and `View.getRotation()`.
- **public static final Property<View, Float> ROTATION\_X:** A Property wrapper around the rotationX functionality handled by `View.setRotationX(float)` and `View.getRotationX()`.
- **public static final Property<View, Float> ROTATION\_Y:** A Property wrapper around the rotationY functionality handled by `View.setRotationY(float)` and `View.getRotationY()`.
- **public static final Property<View, Float> SCALE\_X:** A Property wrapper around the scaleX functionality handled by `View.setScaleX(float)` and `View.getScaleX()`.
- **public static final Property<View, Float> SCALE\_Y:** A Property wrapper around the scaleY functionality handled by `View.setScaleY(float)` and `View.getScaleY()`.
- **public static final Property<View, Float> TRANSLATION\_X:** A Property wrapper around the translationX functionality handled by `View.setTranslationX(float)` and `View.getTranslationX()`.
- **public static final Property<View, Float> TRANSLATION\_Y:** A Property wrapper around the translationY functionality handled by `View.setTranslationY(float)` and `View.getTranslationY()`.
- **public static final Property<View, Float> TRANSLATION\_Z:** A Property wrapper around the translationZ functionality handled by `View.setTranslationZ(float)` and `View.getTranslationZ()`.
- **public static final Property<View, Float> X:** A Property wrapper around the x-position handled by `View.setX(float)` and `View.getX()`.
- **public static final Property<View, Float> Y:** A Property wrapper around the y-position handled by `View.setY(float)` and `View.getY()`.
- **public static final Property<View, Float> Z:** A Property wrapper around the z-position handled by `View.setZ(float)` and `View.getZ()`.
- **protected static final int[] EMPTY\_STATE\_SET:** Indicates the view has no states set.
- **protected static final int[] ENABLED\_STATE\_SET:** Indicates the view is enabled.
- **protected static final int[] ENABLED\_FOCUSED\_STATE\_SET:** Indicates the view is enabled and has focus.
- **protected static final int[] ENABLED\_SELECTED\_STATE\_SET:** Indicates the view is enabled and selected.
- **protected static final int[] ENABLED\_FOCUSED\_SELECTED\_STATE\_SET:** Indicates the view is enabled, focused, and selected.

- **protected static final int[] ENABLED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is enabled and its window has focus.
- **protected static final int[] ENABLED\_FOCUSED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is enabled, focused, and its window has focus.
- **protected static final int[] ENABLED\_SELECTED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is enabled, selected, and its window has focus.
- **protected static final int[] ENABLED\_FOCUSED\_SELECTED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is enabled, focused, selected, and its window has focus.
- **protected static final int[] FOCUSED\_STATE\_SET:** Indicates the view is focused.
- **protected static final int[] SELECTED\_STATE\_SET:** Indicates the view is selected.
- **protected static final int[] WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view's window has focus.
- **protected static final int[] PRESSED\_STATE\_SET:** Indicates the view is pressed.
- **protected static final int[] PRESSED\_ENABLED\_STATE\_SET:** Indicates the view is pressed and enabled.
- **protected static final int[] PRESSED\_ENABLED\_FOCUSED\_STATE\_SET:** Indicates the view is pressed, enabled, and focused.
- **protected static final int[] PRESSED\_ENABLED\_SELECTED\_STATE\_SET:** Indicates the view is pressed, enabled, and selected.
- **protected static final int[] PRESSED\_ENABLED\_FOCUSED\_SELECTED\_STATE\_SET:** Indicates the view is pressed, enabled, focused, and selected.
- **protected static final int[] PRESSED\_FOCUSED\_STATE\_SET:** Indicates the view is pressed and focused.
- **protected static final int[] PRESSED\_SELECTED\_STATE\_SET:** Indicates the view is pressed and selected.
- **protected static final int[] FOCUSED\_SELECTED\_STATE\_SET:** Indicates the view is focused and selected.
- **protected static final int[] PRESSED\_ENABLED\_FOCUSED\_SELECTED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is pressed, enabled, focused, selected, and its window has the focus.
- **protected static final int[] PRESSED\_ENABLED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is pressed, enabled, and its window has focus.
- **protected static final int[] PRESSED\_FOCUSED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is pressed, focused, and its window has focus.
- **protected static final int[] PRESSED\_SELECTED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is pressed, selected, and its window has focus.
- **protected static final int[] SELECTED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is selected and its window has focus.

- **protected static final int[] FOCUSED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is focused and its window has focus.
- **protected static final int[] PRESSED\_FOCUSED\_SELECTED\_STATE\_SET:** Indicates the view is pressed, focused, and selected.
- **protected static final int[] PRESSED\_FOCUSED\_SELECTED\_WINDOW\_FOCUSED\_STATE\_SET:** Indicates the view is pressed, focused, selected, and its window has focus.

- **Constants**

- **int ACCESSIBILITY\_DATA\_SENSITIVE\_AUTO:** Automatically determine whether only accessibility tools may interact with this view.
- **int ACCESSIBILITY\_DATA\_SENSITIVE\_NO:** Allow interactions from all AccessibilityServices.
- **int ACCESSIBILITY\_DATA\_SENSITIVE\_YES:** Only allow interactions from AccessibilityServices marked as tools.
- **int ACCESSIBILITY\_LIVE\_REGION\_ASSERTIVE:** Announce changes immediately.
- **int ACCESSIBILITY\_LIVE\_REGION\_NONE:** Do not automatically announce changes.
- **int ACCESSIBILITY\_LIVE\_REGION\_POLITE:** Announce changes politely.
- **int AUTOFILL\_FLAG\_INCLUDE\_NOT\_IMPORTANT\_VIEWS:** Include not-important-for-autofill views in ViewStructure.
- **String AUTOFILL\_HINT\_CREDIT\_CARD\_EXPIRATION\_DATE:** Hint for credit card expiration date.
- **String AUTOFILL\_HINT\_CREDIT\_CARD\_EXPIRATION\_DAY:** Hint for credit card expiration day.
- **String AUTOFILL\_HINT\_CREDIT\_CARD\_EXPIRATION\_MONTH:** Hint for credit card expiration month.
- **String AUTOFILL\_HINT\_CREDIT\_CARD\_EXPIRATION\_YEAR:** Hint for credit card expiration year.
- **String AUTOFILL\_HINT\_CREDIT\_CARD\_NUMBER:** Hint for credit card number.
- **String AUTOFILL\_HINT\_CREDIT\_CARD\_SECURITY\_CODE:** Hint for credit card CVC/CVV.
- **String AUTOFILL\_HINT\_EMAIL\_ADDRESS:** Hint for email address.
- **String AUTOFILL\_HINT\_NAME:** Hint for real name.
- **String AUTOFILL\_HINT\_PASSWORD:** Hint for password.
- **String AUTOFILL\_HINT\_PHONE:** Hint for phone number.
- **String AUTOFILL\_HINT\_POSTAL\_ADDRESS:** Hint for postal address.
- **String AUTOFILL\_HINT\_POSTAL\_CODE:** Hint for postal/ZIP code.
- **String AUTOFILL\_HINT\_USERNAME:** Hint for username.
- **int AUTOFILL\_TYPE\_DATE:** Field is a date (millis since epoch).
- **int AUTOFILL\_TYPE\_LIST:** Field is a selection list (int index).
- **int AUTOFILL\_TYPE\_NONE:** Not autofillable.
- **int AUTOFILL\_TYPE\_TEXT:** Field is text.

- **int** **AUTOFILL\_TYPE\_TOGGLE**: Field is boolean/toggle.
- **int** **CONTENT\_SENSITIVITY\_AUTO**: Framework determines content sensitivity.
- **int** **CONTENT\_SENSITIVITY\_NOT\_SENSITIVE**: Content not sensitive.
- **int** **CONTENT\_SENSITIVITY\_SENSITIVE**: Content is sensitive.
- **int** **DRAG\_FLAG\_ACCESSIBILITY\_ACTION**: Drag initiated via accessibility action.
- **int** **DRAG\_FLAG\_GLOBAL**: Drag can cross window boundaries.
- **int** **DRAG\_FLAG\_GLOBAL\_PERSISTABLE\_URI\_PERMISSION**: Persist granted URI permissions across reboots.
- **int** **DRAG\_FLAG\_GLOBAL\_PREFIX\_URI\_PERMISSION**: URI permission applies to prefix matches.
- **int** **DRAG\_FLAG\_GLOBAL\_SAME\_APPLICATION**: Drag can cross windows within same app.
- **int** **DRAG\_FLAG\_GLOBAL\_URI\_READ**: Recipient may request read access to URIs.
- **int** **DRAG\_FLAG\_GLOBAL\_URI\_WRITE**: Recipient may request write access to URIs.
- **int** **DRAG\_FLAG\_HIDE\_CALLING\_TASK\_ON\_DRAG\_START**: Hide caller task during drag.
- **int** **DRAG\_FLAG\_OPAQUE**: Drag shadow is opaque.
- **int** **DRAG\_FLAG\_START\_INTENT\_SENDER\_ON\_UNHANDLED\_DRAG**: Delegate unhandled drag to system to start.
- **int** **DRAWING\_CACHE\_QUALITY\_AUTO**: *Deprecated*. Auto drawing cache quality.
- **int** **DRAWING\_CACHE\_QUALITY\_HIGH**: *Deprecated*. High drawing cache quality.
- **int** **DRAWING\_CACHE\_QUALITY\_LOW**: *Deprecated*. Low drawing cache quality.
- **int** **FIND\_VIEWS\_WITH\_CONTENT\_DESCRIPTION**: Find by content description.
- **int** **FIND\_VIEWS\_WITH\_TEXT**: Find by text.
- **int** **FOCUSABLE**: View wants keystrokes.
- **int** **FOCUSABLES\_ALL**: Add all focusables, regardless of touch mode.
- **int** **FOCUSABLES\_TOUCH\_MODE**: Add only focusables in touch mode.
- **int** **FOCUSABLE\_AUTO**: Determine focusability automatically.
- **int** **FOCUS\_BACKWARD**: Focus search backward.
- **int** **FOCUS\_DOWN**: Focus search down.
- **int** **FOCUS\_FORWARD**: Focus search forward.
- **int** **FOCUS\_LEFT**: Focus search left.
- **int** **FOCUS\_RIGHT**: Focus search right.
- **int** **FOCUS\_UP**: Focus search up.
- **int** **GONE**: View is hidden and takes no space.
- **int** **HAPTIC\_FEEDBACK\_ENABLED**: Enable haptic feedback.

- **int IMPORTANT\_FOR\_ACCESSIBILITY\_AUTO**: Determine importance for accessibility automatically.
- **int IMPORTANT\_FOR\_ACCESSIBILITY\_NO**: Not important for accessibility.
- **int IMPORTANT\_FOR\_ACCESSIBILITY\_NO\_HIDE\_DESCENDANTS**: Neither view nor descendants are important.
- **int IMPORTANT\_FOR\_ACCESSIBILITY\_YES**: Important for accessibility.
- **int IMPORTANT\_FOR\_AUTOFILL\_AUTO**: Determine importance for autofill automatically.
- **int IMPORTANT\_FOR\_AUTOFILL\_NO**: Not important for autofill; traverse children.
- **int IMPORTANT\_FOR\_AUTOFILL\_NO\_EXCLUDE\_DESCENDANTS**: Not important; do not traverse children.
- **int IMPORTANT\_FOR\_AUTOFILL\_YES**: Important; traverse children.
- **int IMPORTANT\_FOR\_AUTOFILL\_YES\_EXCLUDE\_DESCENDANTS**: Important; do not traverse children.
- **int IMPORTANT\_FOR\_CONTENT\_CAPTURE\_AUTO**: Determine importance for content capture automatically.
- **int IMPORTANT\_FOR\_CONTENT\_CAPTURE\_NO**: Not important; traverse children.
- **int IMPORTANT\_FOR\_CONTENT\_CAPTURE\_NO\_EXCLUDE\_DESCENDANTS**: Not important; exclude children.
- **int IMPORTANT\_FOR\_CONTENT\_CAPTURE\_YES**: Important; traverse children.
- **int IMPORTANT\_FOR\_CONTENT\_CAPTURE\_YES\_EXCLUDE\_DESCENDANTS**: Important; exclude children.
- **int INVISIBLE**: View is invisible but takes space.
- **int KEEP\_SCREEN\_ON**: Keep screen on while visible.
- **int LAYER\_TYPE\_HARDWARE**: Hardware layer.
- **int LAYER\_TYPE\_NONE**: No layer.
- **int LAYER\_TYPE\_SOFTWARE**: Software layer.
- **int LAYOUT\_DIRECTION\_INHERIT**: Inherit layout direction from parent.
- **int LAYOUT\_DIRECTION\_LOCALE**: Layout direction from locale script.
- **int LAYOUT\_DIRECTION\_LTR**: Left-to-right layout.
- **int LAYOUT\_DIRECTION\_RTL**: Right-to-left layout.
- **int MEASURED\_HEIGHT\_STATE\_SHIFT**: Bit shift to height state.
- **int MEASURED\_SIZE\_MASK**: Mask for measured size bits.
- **int MEASURED\_STATE\_MASK**: Mask for measured state bits.
- **int MEASURED\_STATE\_TOO\_SMALL**: Measured size is smaller than desired.
- **int NOT\_FOCUSABLE**: View does not want keystrokes.
- **int NO\_ID**: Marks a view with no ID.
- **int OVER\_SCROLL\_ALWAYS**: Always allow overscroll.

- **int OVER\_SCROLL\_IF\_CONTENT\_SCROLLS**: Allow overscroll only if content can scroll.
- **int OVER\_SCROLL\_NEVER**: Never allow overscroll.
- **int RECTANGLE\_ON\_SCREEN\_REQUEST\_SOURCE\_INPUT\_FOCUS**: Request due to input focus.
- **int RECTANGLE\_ON\_SCREEN\_REQUEST\_SOURCE\_SCROLL\_ONLY**: Request only to scroll, not tied to cursor/focus.
- **int RECTANGLE\_ON\_SCREEN\_REQUEST\_SOURCE\_TEXT\_CURSOR**: Request due to text cursor.
- **int RECTANGLE\_ON\_SCREEN\_REQUEST\_SOURCE\_UNDEFINED**: Request via legacy APIs (undefined source).
- **float REQUESTED\_FRAME\_RATE\_CATEGORY\_DEFAULT**: Preferred frame rate: default.
- **float REQUESTED\_FRAME\_RATE\_CATEGORY\_HIGH**: Preferred frame rate: high.
- **float REQUESTED\_FRAME\_RATE\_CATEGORY\_LOW**: Preferred frame rate: low.
- **float REQUESTED\_FRAME\_RATE\_CATEGORY\_NORMAL**: Preferred frame rate: normal.
- **float REQUESTED\_FRAME\_RATE\_CATEGORY\_NO\_PREFERENCE**: No frame rate preference.
- **int SCREEN\_STATE\_OFF**: Screen is off.
- **int SCREEN\_STATE\_ON**: Screen is on.
- **int SCROLLBARS\_INSIDE\_INSET**: Scrollbars inside padded area; increases padding.
- **int SCROLLBARS\_INSIDE\_OVERLAY**: Scrollbars inside content; no padding increase.
- **int SCROLLBARS\_OUTSIDE\_INSET**: Scrollbars at edge; increases padding.
- **int SCROLLBARS\_OUTSIDE\_OVERLAY**: Scrollbars at edge; no padding increase.
- **int SCROLLBAR\_POSITION\_DEFAULT**: Scrollbar at system default position.
- **int SCROLLBAR\_POSITION\_LEFT**: Scrollbar on left edge.
- **int SCROLLBAR\_POSITION\_RIGHT**: Scrollbar on right edge.
- **int SCROLL\_AXIS\_HORIZONTAL**: Horizontal scroll axis.
- **int SCROLL\_AXIS\_NONE**: No scroll axis.
- **int SCROLL\_AXIS\_VERTICAL**: Vertical scroll axis.
- **int SCROLL\_CAPTURE\_HINT\_AUTO**: Consider for scroll capture if scrollable.
- **int SCROLL\_CAPTURE\_HINT\_EXCLUDE**: Exclude this view from scroll capture.
- **int SCROLL\_CAPTURE\_HINT\_EXCLUDE\_DESCENDANTS**: Exclude descendants from scroll capture.
- **int SCROLL\_CAPTURE\_HINT\_INCLUDE**: Include this view for scroll capture.
- **int SCROLL\_INDICATOR\_BOTTOM**: Scroll indicator on bottom edge.

- **int SCROLL\_INDICATOR\_END**: Scroll indicator on end edge.
- **int SCROLL\_INDICATOR\_LEFT**: Scroll indicator on left edge.
- **int SCROLL\_INDICATOR\_RIGHT**: Scroll indicator on right edge.
- **int SCROLL\_INDICATOR\_START**: Scroll indicator on start edge.
- **int SCROLL\_INDICATOR\_TOP**: Scroll indicator on top edge.
- **int SOUND\_EFFECTS\_ENABLED**: Enable click/touch sound effects.
- **int STATUS\_BAR\_HIDDEN**: *Deprecated*. Use low profile instead.
- **int STATUS\_BAR\_VISIBLE**: *Deprecated*. Use **SYSTEM\_UI\_FLAG\_VISIBLE**.
- **int SYSTEM\_UI\_FLAG\_FULLSCREEN**: *Deprecated*. Use `WindowInsetsController.hide(Type)`.
- **int SYSTEM\_UI\_FLAG\_HIDE\_NAVIGATION**: *Deprecated*. Use `WindowInsetsController.hide(Type)`.
- **int SYSTEM\_UI\_FLAG\_IMMERSIVE**: *Deprecated*. Use default behavior.
- **int SYSTEM\_UI\_FLAG\_IMMERSIVE\_STICKY**: *Deprecated*. Use show-transient-bars-by-swipe behavior.
- **int SYSTEM\_UI\_FLAG\_LAYOUT\_FULLSCREEN**: *Deprecated*. See modern insets APIs.
- **int SYSTEM\_UI\_FLAG\_LAYOUT\_HIDE\_NAVIGATION**: *Deprecated*. See modern insets APIs.
- **int SYSTEM\_UI\_FLAG\_LAYOUT\_STABLE**: *Deprecated*. Use `WindowInsets.getInsetsIgnoringSystemBars()`.
- **int SYSTEM\_UI\_FLAG\_LIGHT\_NAVIGATION\_BAR**: *Deprecated*. Use appearance flags.
- **int SYSTEM\_UI\_FLAG\_LIGHT\_STATUS\_BAR**: *Deprecated*. Use appearance flags.
- **int SYSTEM\_UI\_FLAG\_LOW\_PROFILE**: *Deprecated*. Hide system bars instead.
- **int SYSTEM\_UI\_FLAG\_VISIBLE**: *Deprecated*. Use `WindowInsetsController.setVisible()`.
- **int SYSTEM\_UI\_LAYOUT\_FLAGS**: *Deprecated*. System UI layout flags deprecated.
- **int TEXT\_ALIGNMENT\_CENTER**: Center paragraph alignment.
- **int TEXT\_ALIGNMENT\_GRAVITY**: Default for root view (gravity).
- **int TEXT\_ALIGNMENT\_INHERIT**: Inherit text alignment.
- **int TEXT\_ALIGNMENT\_TEXT\_END**: Align to paragraph end.
- **int TEXT\_ALIGNMENT\_TEXT\_START**: Align to paragraph start.
- **int TEXT\_ALIGNMENT\_VIEW\_END**: Align to view end (RTL-aware).
- **int TEXT\_ALIGNMENT\_VIEW\_START**: Align to view start (RTL-aware).
- **int TEXT\_DIRECTION\_ANY\_RTL**: Any-RTL algorithm.
- **int TEXT\_DIRECTION\_FIRST\_STRONG**: First-strong algorithm.
- **int TEXT\_DIRECTION\_FIRST\_STRONG\_LTR**: First-strong, force LTR.
- **int TEXT\_DIRECTION\_FIRST\_STRONG\_RTL**: First-strong, force RTL.
- **int TEXT\_DIRECTION\_INHERIT**: Inherit text direction.
- **int TEXT\_DIRECTION\_LOCALE**: From system locale.

- **int TEXT\_DIRECTION\_LTR**: Force LTR.
- **int TEXT\_DIRECTION\_RTL**: Force RTL.
- **String VIEW\_LOG\_TAG**: Logging tag for this class.
- **int VISIBLE**: View is visible.



## 1.3 ViewGroup

- Hierarchy

java.lang.Object → android.view.View → android.view.ViewGroup

- Include

```
0  android.view.ViewGroup
```

- Constructors

```
0  ViewGroup(Context context)
1  ViewGroup(Context context, AttributeSet attrs)
2  ViewGroup(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  ViewGroup(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleAttrRes)
```

- Public methods

- **void addView(View child)**: Adds a child view to this ViewGroup.
- **void addView(View child, int index)**: Inserts a child view at a specific position.
- **void addView(View child, ViewGroup.LayoutParams params)**: Adds a child with explicit layout params.
- **void addView(View child, int index, ViewGroup.LayoutParams params)**: Inserts a child at a position with params.
- **void addView(View child, int width, int height)**: Adds a child using default params plus width/height.
- **void removeView(View view)**: Removes the specified child view.
- **void removeViewAt(int index)**: Removes the child at the given index.
- **void removeViews(int start, int count)**: Removes a range of children.
- **void removeAllViews()**: Removes all child views.
- **int getChildCount()**: Returns the number of children in this ViewGroup.
- **View getChildAt(int index)**: Returns the child at the specified index.
- **int indexOfChild(View child)**: Returns this child's index within the group.
- **void bringChildToFront(View child)**: Moves a child to the top of the Z-order.
- **boolean dispatchTouchEvent(MotionEvent ev)**: Dispatches touch events down the hierarchy.
- **boolean onInterceptTouchEvent(MotionEvent ev)**: Intercepts touch events before children (gesture handling).
- **void requestDisallowInterceptTouchEvent(boolean disallow)**: Child requests parent not to intercept touch.
- **final void layout(int l, int t, int r, int b)**: Assigns size/position to this view and descendants.

- **static int getChildMeasureSpec(int spec, int padding, int childDimension):** Computes a child's MeasureSpec.
- **ViewGroup.LayoutParams generateLayoutParams(AttributeSet attrs):** Creates layout params from XML.
- **void setClipToPadding(boolean clipToPadding):** Controls clipping of children within padding area.
- **void setClipChildren(boolean clipChildren):** Controls whether children are clipped to this ViewGroup's bounds.
- **int getDescendantFocusability() :** Gets how focus is handled among descendants.
- **void setDescendantFocusability(int focusability):** Sets focus behavior for descendants.
- **View getFocusedChild() :** Returns the currently focused child, if any.
- **View focusSearch(View focused, int direction):** Finds the next focusable view in a direction.
- **void requestChildFocus(View child, View focused):** Notifies parent that a child wants focus.
- **void setOnHierarchyChangeListener(ViewGroup.OnHierarchyChangeListener l):** Listens for child add/remove events.
- **void setLayoutTransition(LayoutTransition transition):** Animates child appearance/disappearance/changes.
- **void suppressLayout(boolean suppress):** Temporarily defers layout passes for batched changes.
- **void updateViewLayout(View view, ViewGroup.LayoutParams params):** Updates layout params for an existing child.

- **Protected methods**

- **boolean addViewInLayout(View child, int index, ViewGroup.LayoutParams params, boolean preventRequestLayout):** Adds a view during layout, optionally preventing a layout request.
- **boolean addViewInLayout(View child, int index, ViewGroup.LayoutParams params):** Adds a view during layout.
- **void attachLayoutAnimationParameters(View child, ViewGroup.LayoutParams params, int index, int count):** For subclasses to set layout animation parameters on the child.
- **void attachViewToParent(View child, int index, ViewGroup.LayoutParams params):** Attaches a view to this ViewGroup.
- **boolean canAnimate():** Returns whether this ViewGroup can animate its children after first layout.
- **boolean checkLayoutParams(ViewGroup.LayoutParams p):** Checks if the given LayoutParams are valid for this ViewGroup.
- **void cleanupLayoutState(View child):** Prevents the specified child from being laid out during the next layout pass.
- **void debug(int depth):** Outputs debug information about this view hierarchy.
- **void detachAllViewsFromParent():** Detaches all views from the parent.
- **void detachViewFromParent(int index):** Detaches the child at the given index from its parent.

- **void detachViewFromParent(View child):** Detaches the specified child from its parent.
- **void detachViewsFromParent(int start, int count):** Detaches a range of children from their parent.
- **void dispatchDraw(Canvas canvas):** Called by `draw` to draw the child views.
- **void dispatchFreezeSelfOnly(SparseArray<Parcelable> container):** Saves state only for this view (not its children).
- **boolean dispatchGenericFocusedEvent(MotionEvent event):** Dispatches a generic motion event to the currently focused view.
- **boolean dispatchGenericPointerEvent(MotionEvent event):** Dispatches a generic motion event to the view under the first pointer.
- **boolean dispatchHoverEvent(MotionEvent event):** Dispatches a hover event.
- **void dispatchRestoreInstanceState(SparseArray<Parcelable> container):** Restores state for this view and its children.
- **void dispatchSaveInstanceState(SparseArray<Parcelable> container):** Saves state for this view and its children.
- **void dispatchSetPressed(boolean pressed):** Propagates the pressed state to all children.
- **void dispatchThawSelfOnly(SparseArray<Parcelable> container):** Restores state only for this view (not its children).
- **void dispatchVisibilityChanged(View changedView, int visibility):** Dispatches visibility changes down the hierarchy.
- **boolean drawChild(Canvas canvas, View child, long drawingTime):** Draws a single child of this ViewGroup.
- **void drawableStateChanged():** Called when the view's state changes in a way that affects shown drawables.
- **ViewGroup.LayoutParams generateDefaultLayoutParams():** Returns a set of default layout parameters.
- **ViewGroup.LayoutParams generateLayoutParams(ViewGroup.LayoutParams p):** Returns a safe set of layout params based on the supplied params.
- **int getChildDrawingOrder(int childCount, int drawingPosition):** Maps drawing-order position to container position.
- **boolean getChildStaticTransformation(View child, Transformation t):** Sets `t` to the child's static transform if present; returns true if set.
- **boolean isChildrenDrawingOrderEnabled():** Returns whether children are drawn in the order from `getChildDrawingOrder`.
- **boolean isChildrenDrawnWithCacheEnabled():** Deprecated (API 23). Child caching forced by parents is ignored; use `View.setLayerType`.
- **void measureChild(View child, int parentWidthMeasureSpec, int parentHeightMeasureSpec):** Measures a child with this ViewGroup's specs and padding.
- **void measureChildWithMargins(View child, int parentWidthMeasureSpec, int widthUsed, int parentHeightMeasureSpec, int heightUsed):** Measures a child accounting for margins and used space.
- **void measureChildren(int widthMeasureSpec, int heightMeasureSpec):** Measures all children with the given specs and padding.

- **void onAttachedToWindow()** : Called when the view is attached to a window.
- **int[] onCreateDrawableState(int extraSpace)**: Generates the Drawable state for this view.
- **void onDetachedFromWindow()** : Called when the view is detached from a window.
- **abstract void onLayout(boolean changed, int l, int t, int r, int b)**: Assigns size and position to each child (subclasses must implement).
- **boolean onRequestFocusInDescendants(int direction, Rect previouslyFocusedRect)**: Requests focus on a suitable descendant.
- **void removeDetachedView(View child, boolean animate)**: Finishes removing a detached view, optionally with animation.
- **void setChildrenDrawingCacheEnabled(boolean enabled)**: Deprecated (API 28). View drawing cache largely obsolete with hardware acceleration; prefer **View.setLayerType** or **PixelCopy** for screenshots.
- **void setChildrenDrawingOrderEnabled(boolean enabled)**: Controls whether children are drawn using custom drawing order.
- **void setChildrenDrawnWithCacheEnabled(boolean enabled)**: Deprecated (API 23). Forcing child render caching is ignored; use **View.setLayerType**.
- **void setStaticTransformationsEnabled(boolean enabled)**: Enables static child transformations (invokes **getChildStaticTransformation** during draw).

- **Constants**

- **int CLIP\_TO\_PADDING\_MASK**: Clips to padding when both **FLAG\_CLIP\_TO\_PADDING** and **FLAG\_PADDING\_NOT\_NULL** are set.
- **int FOCUS\_AFTER\_DESCENDANTS**: The view receives focus only if none of its descendants request it.
- **int FOCUS\_BEFORE\_DESCENDANTS**: The view receives focus before any of its descendants.
- **int FOCUS\_BLOCK\_DESCENDANTS**: Prevents any descendants from receiving focus, even if they are focusable.
- **int LAYOUT\_MODE\_CLIP\_BOUNDS**: Layout mode constant that aligns layout to the view's clip bounds.
- **int LAYOUT\_MODE\_OPTICAL\_BOUNDS**: Layout mode constant that aligns layout to the view's optical bounds.
- **int PERSISTENT\_ALL\_CACHES**: *Deprecated in API 28*. Formerly kept all drawing caches (animation, scrolling, etc.). Superseded by hardware acceleration and **View.setLayerType(int, Paint)**.
- **int PERSISTENT\_ANIMATION\_CACHE**: *Deprecated in API 28*. Formerly kept only animation caches. Hardware acceleration now handles such effects efficiently.
- **int PERSISTENT\_NO\_CACHE**: *Deprecated in API 28*. Disabled view drawing caches. Replaced by hardware rendering mechanisms.
- **int PERSISTENT\_SCROLLING\_CACHE**: *Deprecated in API 28*. Formerly maintained caches for scrolling operations; hardware acceleration now replaces this feature.

## 1.4 ViewGroup.LayoutParams

- Hierarchy

java.lang.Object → android.view.ViewGroup.LayoutParams

- Include

```
0  android.view.ViewGroup.LayoutParams
```

- Constructors

```
0  LayoutParams(Context c, AttributeSet attrs)
1  LayoutParams(ViewGroup.LayoutParams source)
2  LayoutParams(int width, int height)
```

- Public methods

- **void resolveLayoutDirection(int layoutDirection):** Resolve layout parameters depending on the layout direction.

- Protected methods

- **void setBaseAttributes(TypedArray a, int widthAttr, int heightAttr):** Extracts the layout parameters from the supplied attributes.

- Fields

- **public int height:** Information about how tall the view wants to be.
- **public LayoutAnimationController.AnimationParameters layoutAnimationParameters:** Used to animate layouts.
- **public int width:** Information about how wide the view wants to be.

- Constants

- **int FILL\_PARENT:** Special value for the height or width requested by a View.
- **int MATCH\_PARENT:** Special value for the height or width requested by a View.
- **int WRAP\_CONTENT:** Special value for the height or width requested by a View.

## 1.5 ViewGroup.MarginLayoutParams

- Hierarchy

```
java.lang.Object → android.view.ViewGroup.LayoutParams →  
    android.view.ViewGroup.MarginLayoutParams
```

- Include

```
0  android.view.ViewGroup.MarginLayoutParams
```

- Constructors

```
0  MarginLayoutParams(Context c, AttributeSet attrs)  
1  MarginLayoutParams(ViewGroup.LayoutParams source)  
2  MarginLayoutParams(ViewGroup.MarginLayoutParams source)  
3  MarginLayoutParams(int width, int height)
```

- Public methods

- **int getLayoutDirection()**: Returns the layout direction.
- **int getMarginEnd()**: Returns the end margin in pixels.
- **int getMarginStart()**: Returns the start margin in pixels.
- **boolean isMarginRelative()**: Check if margins are relative.
- **void resolveLayoutDirection(int layoutDirection)**: This will be called by View.requestLayout().
- **void setLayoutDirection(int layoutDirection)**: Set the layout direction
- **void setMarginEnd(int end)**: Sets the relative end margin.
- **void setMarginStart(int start)**: Sets the relative start margin.
- **void setMargins(int left, int top, int right, int bottom)**: Sets the margins, in pixels.

- Fields

- **public int bottomMargin**: The bottom margin in pixels of the child.
- **public int leftMargin**: The left margin in pixels of the child.
- **public int rightMargin**: The right margin in pixels of the child.
- **public int topMargin**: The top margin in pixels of the child.

## 1.6 Color

- Hierarchy

java.lang.Object → android.graphics.Color

- Include

```
o android.graphics.Color
```

- Constructors

```
o Color()
```

- Public methods

- **static int HSVToColor(float[] hsv):** Convert HSV components to an ARGB color.
- **static int HSVToColor(int alpha, float[] hsv):** Convert HSV components to an ARGB color.
- **static void RGBToHSV(int red, int green, int blue, float[] hsv):** Convert RGB components to HSV.
- **static int alpha(int color):** Return the alpha component of a color int.
- **float alpha():** Returns the value of the alpha component in the range .
- **static float alpha(long color):** Returns the alpha component encoded in the specified color long.
- **static int argb(int alpha, int red, int green, int blue):** Return a color-int from alpha, red, green, blue components.
- **static int argb(float alpha, float red, float green, float blue):** Return a color-int from alpha, red, green, blue float components in the range .
- **static int blue(int color):** Return the blue component of a color int.
- **float blue():** Returns the value of the blue component in the range defined by this color's color space (see `ColorSpace.getMinValue(int)` and `ColorSpace.getMaxValue(int)`).
- **static float blue(long color):** Returns the blue component encoded in the specified color long.
- **static ColorSpace colorSpace(long color):** Returns the color space encoded in the specified color long.
- **static void colorToHSV(int color, float[] hsv):** Convert the ARGB color to its HSV components.
- **static long convert(long color, ColorSpace.Connector connector):** Converts the specified color long from a color space to another using the specified color space connector.
- **Color convert(ColorSpace colorSpace):** Converts this color from its color space to the specified color space.
- **static long convert(int color, ColorSpace colorSpace):** Converts the specified ARGB color int from the sRGB color space into the specified destination color space.

- **static long convert(float r, float g, float b, float a, ColorSpace source, ColorSpace destination)**: Converts the specified 3 component color from the source color space to the destination color space.
- **static long convert(float r, float g, float b, float a, ColorSpace.Connector connector)**: Converts the specified 3 component color from a color space to another using the specified color space connector.
- **static long convert(long color, ColorSpace colorSpace)**: Converts the specified color long from its color space into the specified destination color space.
- **boolean equals(Object o)**: Indicates whether some other object is "equal to" this one.
- **ColorSpace getColorSpace()**: Returns this color's color space.
- **float getComponent(int component)**: Returns the value of the specified component in the range defined by this color's color space (see `ColorSpace.getMinValue(int)` and `ColorSpace.getMaxValue(int)`).
- **int getComponentCount()**: Returns the number of components that form a color value according to this color space's color model, plus one extra component for alpha.
- **float[] getComponents()**: Returns this color's components as a new array.
- **float[] getComponents(float[] components)**: Copies this color's components in the supplied array.
- **ColorSpace.Model getModel()**: Returns the color model of this color.
- **static float green(long color)**: Returns the green component encoded in the specified color long.
- **float green()**: Returns the value of the green component in the range defined by this color's color space (see `ColorSpace.getMinValue(int)` and `ColorSpace.getMaxValue(int)`).
- **static int green(int color)**: Return the green component of a color int.
- **int hashCode()**: Returns a hash code value for the object.
- **static boolean isInColorSpace(long color, ColorSpace colorSpace)**: Indicates whether the specified color is in the specified color space.
- **boolean isSrgb()**: Indicates whether this color is in the sRGB color space.
- **static boolean isSrgb(long color)**: Indicates whether the specified color is in the sRGB color space.
- **static boolean isWideGamut(long color)**: Indicates whether the specified color is in a wide-gamut color space.
- **boolean isWideGamut()**: Indicates whether this color color is in a wide-gamut color space.
- **static float luminance(long color)**: Returns the relative luminance of a color.
- **static float luminance(int color)**: Returns the relative luminance of a color.
- **float luminance()**: Returns the relative luminance of this color.
- **static long pack(int color)**: Converts the specified ARGB color int to an RGBA color long in the sRGB color space.
- **static long pack(float red, float green, float blue, float alpha)**: Packs the sRGB color defined by the specified red, green, blue and alpha component values into an RGBA color long in the sRGB color space.



- **static long pack(float red, float green, float blue, float alpha, ColorSpace colorSpace)**: Packs the 3 component color defined by the specified red, green, blue and alpha component values into a color long in the specified color space.
- **static long pack(float red, float green, float blue)**: Packs the sRGB color defined by the specified red, green and blue component values into an RGBA color long in the sRGB color space.
- **long pack()**: Packs this color into a color long.
- **static int parseColor(String colorString)**: Parse the color string, and return the corresponding color-int.
- **float red()**: Returns the value of the red component in the range defined by this color's color space (see `ColorSpace.getMinValue(int)` and `ColorSpace.getMaxValue(int)`).
- **static float red(long color)**: Returns the red component encoded in the specified color long.
- **static int red(int color)**: Return the red component of a color int.
- **static int rgb(float red, float green, float blue)**: Return a color-int from red, green, blue float components in the range .
- **static int rgb(int red, int green, int blue)**: Return a color-int from red, green, blue components.
- **int toArgb()**: Converts this color to an ARGB color int.
- **static int toArgb(long color)**: Converts the specified color long to an ARGB color int.
- **String toString()**: Returns a string representation of the object.
- **static Color valueOf(float r, float g, float b)**: Creates a new opaque Color in the sRGB color space with the specified red, green and blue component values.
- **static Color valueOf(float r, float g, float b, float a)**: Creates a new Color in the sRGB color space with the specified red, green, blue and alpha component values.
- **static Color valueOf(int color)**: Creates a new Color instance from an ARGB color int.
- **static Color valueOf(float[] components, ColorSpace colorSpace)**: Creates a new Color in the specified color space with the specified component values.
- **static Color valueOf(long color)**: Creates a new Color instance from a color long.
- **static Color valueOf(float r, float g, float b, float a, ColorSpace colorSpace)**: Creates a new Color in the specified color space with the specified red, green, blue and alpha component values.

- **Constants**

- **int BLACK**:
- **int BLUE**:
- **int CYAN**:
- **int DKGRAY**:
- **int GRAY**:
- **int GREEN**:
- **int LTGRAY**:

- **int MAGENTA:**
- **int RED:**
- **int TRANSPARENT:**
- **int WHITE:**
- **int YELLOW:**

## 1.7 Context

- Hierarchy

java.lang.Object → android.content.Context

- Include

```
o android.content.Context
```

- Constructors

```
o Context()
```

- Public methods

- **Context** `getApplicationContext()`: Returns the global application context.
- **Resources** `getResources()`: Provides access to the app's resources (layouts, strings, drawables, etc.).
- **PackageManager** `getPackageManager()`: Returns a PackageManager for querying installed apps and permissions.
- **ContentResolver** `getContentResolver()`: Gives access to content providers (e.g., Contacts, MediaStore).
- **SharedPreferences** `getSharedPreferences(String name, int mode)`: Access or create a preferences file for storing key-value pairs.
- **File** `getFilesDir()`: Returns the app's private file storage directory.
- **File** `getCacheDir()`: Returns the app's private cache directory.
- **Drawable** `getDrawable(int id)`: Retrieves a drawable resource styled for the current theme.
- **int** `getColor(int id)`: Returns a color resource styled for the current theme.
- **String** `getString(int resId)`: Returns a localized string from resources.
- **String** `getString(int resId, Object... formatArgs)`: Returns a formatted localized string.
- **void** `startActivity(Intent intent)`: Launches a new activity.
- **ComponentName** `startService(Intent service)`: Starts a service.
- **boolean** `stopService(Intent service)`: Stops a running service.
- **boolean** `bindService(Intent service, ServiceConnection conn, int flags)`: Connects to a service for interaction.
- **void** `unbindService(ServiceConnection conn)`: Disconnects from a bound service.
- **void** `sendBroadcast(Intent intent)`: Sends a broadcast to all interested receivers.
- **Intent** `registerReceiver(BroadcastReceiver receiver, IntentFilter filter)`: Registers a broadcast receiver.
- **void** `unregisterReceiver(BroadcastReceiver receiver)`: Unregisters a previously registered receiver.

- **Object** `getSystemService(String name)`: Returns a handle to a system-level service (e.g., `LAYOUT_INFLATER_SERVICE`).
- **<T> T** `getSystemService(Class<T> serviceClass)`: Type-safe version of `getSystemService`.
- **Resources.Theme** `getTheme()`: Returns the current theme for styling and inflation.
- **TypedArray** `obtainStyledAttributes(int[] attrs)`: Retrieves styled attributes in the current theme.
- **FileInputStream** `openFileInput(String name)`: Opens a private file for reading.
- **FileOutputStream** `openFileOutput(String name, int mode)`: Opens a private file for writing.

- **Constants**

- **String** `ACTIVITY_SERVICE`: For `ActivityManager` (process/app state) via `getSystemService`.
- **String** `WINDOW_SERVICE`: For `WindowManager` (windows, display metrics).
- **String** `DISPLAY_SERVICE`: For `DisplayManager` (displays, modes).
- **String** `LAYOUT_INFLATER_SERVICE`: For `LayoutInflater` (inflate XML layouts).
- **String** `POWER_SERVICE`: For `PowerManager` (wake locks, power state).
- **String** `UI_MODE_SERVICE`: For `UiModeManager` (night mode, car/TV mode).
- **String** `CONNECTIVITY_SERVICE`: For `ConnectivityManager` (network state, requests).
- **String** `WIFI_SERVICE`: For `WifiManager` (Wi-Fi control).
- **String** `WIFI_P2P_SERVICE`: For `WifiP2pManager` (Wi-Fi Direct).
- **String** `TETHERING_SERVICE`: For `TetheringManager` (tethering APIs).
- **String** `USB_SERVICE`: For `UsbManager` (USB host/device).
- **String** `NFC_SERVICE`: For `NfcManager` (NFC features).
- **String** `VPN_MANAGEMENT_SERVICE`: For `VpnManager` (built-in VPN profiles).
- **String** `LOCATION_SERVICE`: For `LocationManager` (location providers).
- **String** `SENSOR_SERVICE`: For `SensorManager` (accelerometer, gyro, etc.).
- **String** `BLUETOOTH_SERVICE`: For `BluetoothManager` (Bluetooth stack).
- **String** `CAMERA_SERVICE`: For `CameraManager` (camera devices).
- **String** `AUDIO_SERVICE`: For `AudioManager` (volume, routing).
- **String** `NOTIFICATION_SERVICE`: For `NotificationManager` (post/cancel notifications).
- **String** `MEDIA_SESSION_SERVICE`: For `MediaSessionManager` (media controls).
- **String** `MEDIA_PROJECTION_SERVICE`: For `MediaProjectionManager` (screen capture).
- **String** `DOWNLOAD_SERVICE`: For `DownloadManager` (HTTP downloads).

- **String INPUT\_METHOD\_SERVICE**: For `InputMethodManager` (soft keyboard).
- **String CLIPBOARD\_SERVICE**: For `ClipboardManager` (global clipboard).
- **String KEYGUARD\_SERVICE**: For `KeyguardManager` (lock screen).
- **String BIOMETRIC\_SERVICE**: For `BiometricManager` (biometric auth).
- **String STORAGE\_SERVICE**: For `StorageManager` (volumes, storage ops).
- **String USER\_SERVICE**: For `userManager` (multi-user info).
- **String JOB\_SCHEDULER\_SERVICE**: For `JobScheduler` (deferrable background work).
- **String APP\_OPS\_SERVICE**: For `AppOpsManager` (app operation checks).
- **String VIBRATOR\_MANAGER\_SERVICE**: For `VibratorManager` (multi-vibrator control).
- **int MODE\_PRIVATE**: Default file mode for `openFileOutput`; file private to the app.
- **int MODE\_APPEND**: Append mode for `openFileOutput`.
- **int MODE\_ENABLE\_WRITE\_AHEAD\_LOGGING**: DB flag to enable WAL by default.
- **int MODE\_NO\_LOCALIZED\_COLLATORS**: DB flag to omit localized collators.
- **int RECEIVER\_EXPORTED**: `registerReceiver` flag — receiver accepts broadcasts from other apps.
- **int RECEIVER\_NOT\_EXPORTED**: `registerReceiver` flag — receiver is app-internal only.
- **int RECEIVER\_VISIBLE\_TO\_INSTANT\_APPS**: `registerReceiver` flag — visible to Instant Apps.
- **int BIND\_AUTO\_CREATE**: Auto-create service while bound.
- **int BIND\_NOT\_FOREGROUND**: Do not raise target service to foreground priority.
- **int BIND\_IMPORTANT**: Treat service as important to the client.
- **int BIND\_DEBUG\_UNBIND**: Include debugging help for unbind mismatches.
- **int BIND\_WAIVE\_PRIORITY**: Do not affect service process priority.

## 1.8 Configuration

- **Getting a Configuration object:** First, we get a Resources reference with `getResources()` from the activity class, then we can call `getConfiguration()` on that reference

```
o Configuration config = getResources().getConfiguration();
```

- **Hierarchy**

`java.lang.Object` → `android.content.res.Configuration`

- **Include**

```
o android.content.res.Configuration
```

- **Constructors**

```
o Configuration()
1 Configuration(Configuration o)
```

- **Public methods**

- **int compareTo(Configuration that):**
- **int describeContents():** Parcelable methods
- **int diff(Configuration delta):** Return a bit mask of the differences between this Configuration object and the given one.
- **boolean equals(Configuration that):**
- **boolean equals(Object that):** Indicates whether some other object is "equal to" this one.
- **static Configuration generateDelta(Configuration base, Configuration change):** Generate a delta Configuration between base and change.
- **int getGrammaticalGender():** Returns the user preference for the grammatical gender.
- **int getLayoutDirection():** Return the layout direction.
- **LocaleList getLocales():** Get the locale list.
- **int hashCode():** Returns a hash code value for the object.
- **boolean isLayoutSizeAtLeast(int size):** Check if the Configuration's current screenLayout is at least the given size.
- **boolean isNightModeActive():** Returns whether the configuration is in night mode
- **boolean isScreenHdr():** Return whether the screen has a high dynamic range.
- **boolean isScreenRound():** Return whether the screen has a round shape.
- **boolean isScreenWideColorGamut():** Return whether the screen has a wide color gamut and wide color gamut rendering is supported by this device.
- **static boolean needNewResources(int configChanges, int interestingChanges):** Determines if a new resource needs to be loaded from the bit set of configuration changes returned by `updateFrom(android.content.res.Configuration)`.

- **void readFromParcel(Parcel source):**
- **void setLayoutDirection(Locale loc):** Set the layout direction from a Locale.
- **void setLocale(Locale loc):** Set the locale list to a list of just one locale.
- **void setLocales(LocaleList locales):** Set the locale list.
- **void setTo(Configuration o):** Sets the fields in this object to those in the given Configuration.
- **void setToDefaults():** Set this object to the system defaults.
- **String toString():** Returns a string representation of the object.
- **int updateFrom(Configuration delta):** Copies the fields from delta into this Configuration object, keeping track of which ones have changed.
- **void writeToParcel(Parcel dest, int flags):** Flatten this object in to a Parcel.

- **Fields**

- **public static final Creator<Configuration> CREATOR:**
- **public int colorMode:** Bit mask of color capabilities of the screen.
- **public int densityDpi:** The target screen density being rendered to, corresponding to density resource qualifier.
- **public float fontScale:** Current user preference for the scaling factor for fonts, relative to the base density scaling.
- **public int fontWeightAdjustment:** Adjustment in text font weight.
- **public int hardKeyboardHidden:** A flag indicating whether the hard keyboard has been hidden.
- **public int keyboard:** The kind of keyboard attached to the device.
- **public int keyboardHidden:** A flag indicating whether any keyboard is available.
- **public Locale locale:** This field was deprecated in API level 24. Do not set or read this directly. Use `getLocales()` and `setLocales(android.os.LocaleList)`. If only the primary locale is needed, `getLocales().get(0)` is now the preferred accessor.
- **public int mcc:** IMSI MCC (Mobile Country Code), corresponding to mcc resource qualifier.
- **public int mnc:** IMSI MNC (Mobile Network Code), corresponding to mnc resource qualifier.
- **public int navigation:** The kind of navigation method available on the device.
- **public int navigationHidden:** A flag indicating whether any 5-way or DPAD navigation available.
- **public int orientation:** Overall orientation of the screen.
- **public int screenHeightDp:** The height of the available screen space in dp units.
- **public int screenWidthDp:** The width of the available screen space in dp units.
- **public int smallestScreenWidthDp:** The smallest screen size an application will see in normal operation.
- **public int touchscreen:** The kind of touch screen attached to the device.
- **public int uiMode:** Bit mask of the ui mode.

- **Constants**

- **int COLOR\_MODE\_HDR\_MASK**: Constant for colorMode: bits that encode the dynamic range of the screen.
- **int COLOR\_MODE\_HDR\_NO**: Constant for colorMode: a COLOR\_MODE\_HDR\_MASK value indicating that the screen is not HDR (low/standard dynamic range).
- **int COLOR\_MODE\_HDR\_SHIFT**: Constant for colorMode: bits shift to get the screen dynamic range.
- **int COLOR\_MODE\_HDR\_UNDEFINED**: Constant for colorMode: a COLOR\_MODE\_HDR\_MASK value indicating that it is unknown whether or not the screen is HDR.
- **int COLOR\_MODE\_HDR\_YES**: Constant for colorMode: a COLOR\_MODE\_HDR\_MASK value indicating that the screen is HDR (dynamic range).
- **int COLOR\_MODE\_UNDEFINED**: Constant for colorMode: a value indicating that the color mode is undefined
- **int COLOR\_MODE\_WIDE\_COLOR\_GAMUT\_MASK**: Constant for colorMode: bits that encode whether the screen is wide gamut.
- **int COLOR\_MODE\_WIDE\_COLOR\_GAMUT\_NO**: Constant for colorMode: a COLOR\_MODE\_WIDE\_COLOR\_GAMUT\_MASK value indicating that the screen is not wide gamut.
- **int COLOR\_MODE\_WIDE\_COLOR\_GAMUT\_UNDEFINED**: Constant for colorMode: a COLOR\_MODE\_WIDE\_COLOR\_GAMUT\_MASK value indicating that it is unknown whether or not the screen is wide gamut.
- **int COLOR\_MODE\_WIDE\_COLOR\_GAMUT\_YES**: Constant for colorMode: a COLOR\_MODE\_WIDE\_COLOR\_GAMUT\_MASK value indicating that the screen is wide gamut.
- **int DENSITY\_DPI\_UNDEFINED**: Default value for densityDpi indicating that no width has been specified.
- **int FONT\_WEIGHT\_ADJUSTMENT\_UNDEFINED**: An undefined fontWeightAdjustment.
- **int GRAMMATICAL\_GENDER\_FEMININE**: Constant for grammatical gender: to indicate the terms of address the user preferred in an application is feminine.
- **int GRAMMATICAL\_GENDER\_MASCULINE**: Constant for grammatical gender: to indicate the terms of address the user preferred in an application is masculine.
- **int GRAMMATICAL\_GENDER\_NEUTRAL**: Constant for grammatical gender: to indicate the terms of address the user preferred in an application is neuter.
- **int GRAMMATICAL\_GENDER\_NOT\_SPECIFIED**: Constant for grammatical gender: to indicate the user has not specified the terms of address for the application.
- **int HARDKEYBOARDHIDDEN\_NO**: Constant for hardKeyboardHidden, value corresponding to the physical keyboard being exposed.
- **int HARDKEYBOARDHIDDEN\_UNDEFINED**: Constant for hardKeyboardHidden: a value indicating that no value has been set.
- **int HARDKEYBOARDHIDDEN\_YES**: Constant for hardKeyboardHidden, value corresponding to the physical keyboard being hidden.



- **int KEYBOARDHIDDEN\_NO**: Constant for keyboardHidden, value corresponding to the keysexposed resource qualifier.
- **int KEYBOARDHIDDEN\_UNDEFINED**: Constant for keyboardHidden: a value indicating that no value has been set.
- **int KEYBOARDHIDDEN\_YES**: Constant for keyboardHidden, value corresponding to the keyshidden resource qualifier.
- **int KEYBOARD\_12KEY**: Constant for keyboard, value corresponding to the 12key resource qualifier.
- **int KEYBOARD\_NOKEYS**: Constant for keyboard, value corresponding to the nokeys resource qualifier.
- **int KEYBOARD\_QWERTY**: Constant for keyboard, value corresponding to the qwerty resource qualifier.
- **int KEYBOARD\_UNDEFINED**: Constant for keyboard: a value indicating that no value has been set.
- **int MNC\_ZERO**: Constant used to to represent MNC (Mobile Network Code) zero.
- **int NAVIGATIONHIDDEN\_NO**: Constant for navigationHidden, value corresponding to the navexposed resource qualifier.
- **int NAVIGATIONHIDDEN\_UNDEFINED**: Constant for navigationHidden: a value indicating that no value has been set.
- **int NAVIGATIONHIDDEN\_YES**: Constant for navigationHidden, value corresponding to the navhidden resource qualifier.
- **int NAVIGATION\_DPAD**: Constant for navigation, value corresponding to the dpad resource qualifier.
- **int NAVIGATION\_NONAV**: Constant for navigation, value corresponding to the nonav resource qualifier.
- **int NAVIGATION\_TRACKBALL**: Constant for navigation, value corresponding to the trackball resource qualifier.
- **int NAVIGATION\_UNDEFINED**: Constant for navigation: a value indicating that no value has been set.
- **int NAVIGATION\_WHEEL**: Constant for navigation, value corresponding to the wheel resource qualifier.
- **int ORIENTATION\_LANDSCAPE**: Constant for orientation, value corresponding to the land resource qualifier.
- **int ORIENTATION\_PORTRAIT**: Constant for orientation, value corresponding to the port resource qualifier.
- **int ORIENTATION\_SQUARE**: This constant was deprecated in API level 16. Not currently supported or used.
- **int ORIENTATION\_UNDEFINED**: Constant for orientation: a value indicating that no value has been set.
- **int SCREENLAYOUT\_LAYOUTDIR\_LTR**: Constant for screenLayout: a SCREENLAYOUT\_LAYOUTDIR\_MASK value indicating that a layout dir has been set to LTR.
- **int SCREENLAYOUT\_LAYOUTDIR\_MASK**: Constant for screenLayout: bits that encode the layout direction.
- **int SCREENLAYOUT\_LAYOUTDIR\_RTL**: Constant for screenLayout: a SCREENLAYOUT\_LAYOUTDIR\_MASK value indicating that a layout dir has been set to RTL.

- **int SCREENLAYOUT\_LAYOUTDIR\_SHIFT**: Constant for screenLayout: bits shift to get the layout direction.
- **int SCREENLAYOUT\_LAYOUTDIR\_UNDEFINED**: Constant for screenLayout: a SCREENLAYOUT\_LAYOUTDIR\_MASK value indicating that no layout dir has been set.
- **int SCREENLAYOUT\_LONG\_MASK**: Constant for screenLayout: bits that encode the aspect ratio.
- **int SCREENLAYOUT\_LONG\_NO**: Constant for screenLayout: a SCREENLAYOUT\_LONG\_MASK value that corresponds to the notlong resource qualifier.
- **int SCREENLAYOUT\_LONG\_UNDEFINED**: Constant for screenLayout: a SCREENLAYOUT\_LONG\_MASK value indicating that no size has been set.
- **int SCREENLAYOUT\_LONG\_YES**: Constant for screenLayout: a SCREENLAYOUT\_LONG\_MASK value that corresponds to the long resource qualifier.
- **int SCREENLAYOUT\_ROUND\_MASK**: Constant for screenLayout: bits that encode roundness of the screen.
- **int SCREENLAYOUT\_ROUND\_NO**: Constant for screenLayout: a SCREENLAYOUT\_ROUND\_MASK value indicating that the screen does not have a rounded shape.
- **int SCREENLAYOUT\_ROUND\_UNDEFINED**: Constant for screenLayout: a SCREENLAYOUT\_ROUND\_MASK value indicating that it is unknown whether or not the screen has a round shape.
- **int SCREENLAYOUT\_ROUND\_YES**: Constant for screenLayout: a SCREENLAYOUT\_ROUND\_MASK value indicating that the screen has a rounded shape.
- **int SCREENLAYOUT\_SIZE\_LARGE**: Constant for screenLayout: a SCREENLAYOUT\_SIZE\_MASK value indicating the screen is at least approximately 480x640 dp units, corresponds to the large resource qualifier.
- **int SCREENLAYOUT\_SIZE\_MASK**: Constant for screenLayout: bits that encode the size.
- **int SCREENLAYOUT\_SIZE\_NORMAL**: Constant for screenLayout: a SCREENLAYOUT\_SIZE\_MASK value indicating the screen is at least approximately 320x470 dp units, corresponds to the normal resource qualifier.
- **int SCREENLAYOUT\_SIZE\_SMALL**: Constant for screenLayout: a SCREENLAYOUT\_SIZE\_MASK value indicating the screen is at least approximately 320x426 dp units, corresponds to the small resource qualifier.
- **int SCREENLAYOUT\_SIZE\_UNDEFINED**: Constant for screenLayout: a SCREENLAYOUT\_SIZE\_MASK value indicating that no size has been set.
- **int SCREENLAYOUT\_SIZE\_XLARGE**: Constant for screenLayout: a SCREENLAYOUT\_SIZE\_MASK value indicating the screen is at least approximately 720x960 dp units, corresponds to the xlarge resource qualifier.
- **int SCREENLAYOUT\_UNDEFINED**: Constant for screenLayout: a value indicating that screenLayout is undefined
- **int SCREEN\_HEIGHT\_DP\_UNDEFINED**: Default value for screenHeightDp indicating that no width has been specified.
- **int SCREEN\_WIDTH\_DP\_UNDEFINED**: Default value for screenWidthDp indicating that no width has been specified.
- **int SMALLEST\_SCREEN\_WIDTH\_DP\_UNDEFINED**: Default value for smallestScreenWidthDp indicating that no width has been specified.

- **int TOUCHSCREEN\_FINGER**: Constant for touchscreen, value corresponding to the finger resource qualifier.
- **int TOUCHSCREEN\_NOTOUCH**: Constant for touchscreen, value corresponding to the notouch resource qualifier.
- **int TOUCHSCREEN\_STYLUS**: This constant was deprecated in API level 16. Not currently supported or used.
- **int TOUCHSCREEN\_UNDEFINED**: Constant for touchscreen: a value indicating that no value has been set.
- **int UI\_MODE\_NIGHT\_MASK**: Constant for uiMode: bits that encode the night mode.
- **int UI\_MODE\_NIGHT\_NO**: Constant for uiMode: a UI\_MODE\_NIGHT\_MASK value that corresponds to the notnight resource qualifier.
- **int UI\_MODE\_NIGHT\_UNDEFINED**: Constant for uiMode: a UI\_MODE\_NIGHT\_MASK value indicating that no mode type has been set.
- **int UI\_MODE\_NIGHT\_YES**: Constant for uiMode: a UI\_MODE\_NIGHT\_MASK value that corresponds to the night resource qualifier.
- **int UI\_MODE\_TYPE\_APPLIANCE**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value that corresponds to the appliance resource qualifier.
- **int UI\_MODE\_TYPE\_CAR**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value that corresponds to the car resource qualifier.
- **int UI\_MODE\_TYPE\_DESK**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value that corresponds to the desk resource qualifier.
- **int UI\_MODE\_TYPE\_MASK**: Constant for uiMode: bits that encode the mode type.
- **int UI\_MODE\_TYPE\_NORMAL**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value that corresponds to no UI mode resource qualifier specified.
- **int UI\_MODE\_TYPE\_TELEVISION**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value that corresponds to the television resource qualifier.
- **int UI\_MODE\_TYPE\_UNDEFINED**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value indicating that no mode type has been set.
- **int UI\_MODE\_TYPE\_VR\_HEADSET**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value that corresponds to the vrheadset resource qualifier.
- **int UI\_MODE\_TYPE\_WATCH**: Constant for uiMode: a UI\_MODE\_TYPE\_MASK value that corresponds to the watch resource qualifier.

## 1.9 Resources

- **Getting a resources object:** Inside the Activity class, we can call method `getResources()` from the Context class (from which class Activity inherits) to get a Resources reference for the application's package.

```
o Resources resources = getResources();
```

- **Hierarchy**

java.lang.Object → android.content.res.Resources

- **Include**

```
o android.content.res.Resources
```

- **Constructors**

```
o Resources(AssetManager assets, DisplayMetrics metrics,  
    ↪ Configuration config)
```

- **Public methods**

- **void addLoaders(ResourcesLoader... loaders):** Adds a loader to the list of loaders.
- **final void finishPreloading():** Called by zygote when it is done preloading resources, to change back to normal Resources operation.
- **final void flushLayoutCache():** Call this to remove all cached loaded layout resources from the Resources object.
- **XmlResourceParser getAnimation(int id):** Return an XmlResourceParser through which you can read an animation description for the given resource ID.
- **final AssetManager getAssets():** Retrieve underlying AssetManager storage for these resources.
- **static int getAttributeSetSourceResId(AttributeSet set):** Returns the resource ID of the resource that was used to create this AttributeSet.
- **boolean getBoolean(int id):** Return a boolean associated with a particular resource ID.
- **int getColor(int id):** This method was deprecated in API level 23. Use `getColor(int, android.content.res.Resources.Theme)` instead.
- **int getColor(int id, Resources.Theme theme):** Returns a themed color integer associated with a particular resource ID.
- **ColorStateList getColorStateList(int id, Resources.Theme theme):** Returns a themed color state list associated with a particular resource ID.
- **ColorStateList getColorStateList(int id):** This method was deprecated in API level 23. Use `getColorStateList(int, android.content.res.Resources.Theme)` instead.
- **Configuration getConfiguration():** Return the current configuration that is in effect for this resource object.

- **float** **getDimension(int id)**: Retrieve a dimensional for a particular resource ID.
- **int** **getDimensionPixelOffset(int id)**: Retrieve a dimensional for a particular resource ID for use as an offset in raw pixels.
- **int** **getDimensionPixelSize(int id)**: Retrieve a dimensional for a particular resource ID for use as a size in raw pixels.
- **DisplayMetrics** **getDisplayMetrics()**: Returns the current display metrics that are in effect for this resource object.
- **Drawable** **getDrawable(int id, Resources.Theme theme)**: Return a drawable object associated with a particular resource ID and styled for the specified theme.
- **Drawable** **getDrawable(int id)**: This method was deprecated in API level 22. Use `getDrawable(int, android.content.res.Resources.Theme)` instead.
- **Drawable** **getDrawableForDensity(int id, int density)**: This method was deprecated in API level 22. Use `getDrawableForDensity(int, int, android.content.res.Resources.Theme)` instead.
- **Drawable** **getDrawableForDensity(int id, int density, Resources.Theme theme)**: Return a drawable object associated with a particular resource ID for the given screen density in DPI and styled for the specified theme.
- **float** **getFloat(int id)**: Retrieve a floating-point value for a particular resource ID.
- **Typeface** **getFont(int id)**: Return the Typeface value associated with a particular resource ID.
- **float** **getFraction(int id, int base, int pbase)**: Retrieve a fractional unit for a particular resource ID.
- **int** **getIdentifier(String name, String defType, String defPackage)**: Return a resource identifier for the given resource name.
- **int[]** **getIntArray(int id)**: Return the int array associated with a particular resource ID.
- **int** **getInteger(int id)**: Return an integer associated with a particular resource ID.
- **XmlResourceParser** **getLayout(int id)**: Return an XmlResourceParser through which you can read a view layout description for the given resource ID.
- **Movie** **getMovie(int id)**: This method was deprecated in API level 29. Prefer `AnimatedImageDrawable`.
- **String** **getQuantityString(int id, int quantity, Object... formatArgs)**: Formats the string necessary for grammatically correct pluralization of the given resource ID for the given quantity, using the given arguments.
- **String** **getQuantityString(int id, int quantity)**: Returns the string necessary for grammatically correct pluralization of the given resource ID for the given quantity.
- **CharSequence** **getQuantityText(int id, int quantity)**: Returns the character sequence necessary for grammatically correct pluralization of the given resource ID for the given quantity.
- **String** **getResourceEntryName(int resid)**: Return the entry name for a given resource identifier.
- **String** **getResourceName(int resid)**: Return the full name for a given resource identifier.

- **String getResourcePackageName(int resid)**: Return the package name for a given resource identifier.
- **String getResourceTypeName(int resid)**: Return the type name for a given resource identifier.
- **String getString(int id)**: Return the string value associated with a particular resource ID. It will be stripped of any styled text information.
- **String getString(int id, Object... formatArgs)**: Return the string value associated with a particular resource ID, substituting the format arguments as defined in `Formatter` and `String.format(String, Object)`. It will be stripped of any styled text information.
- **String[] getStringArray(int id)**: Return the string array associated with a particular resource ID.
- **static Resources getSystem()**: Return a global shared `Resources` object that provides access to only system resources (no application resources), is not configured for the current screen (can not use dimension units, does not change based on orientation, etc), and is not affected by Runtime Resource Overlay.
- **CharSequence getText(int id, CharSequence def)**: Return the string value associated with a particular resource ID.
- **CharSequence getText(int id)**: Return the string value associated with a particular resource ID. The returned object will be a `String` if this is a plain string; it will be some other type of `CharSequence` if it is styled.
- **CharSequence[] getTextArray(int id)**: Return the styled text array associated with a particular resource ID.
- **void getValue(String name, TypedValue outValue, boolean resolveRefs)**: Return the raw data associated with a particular resource ID.
- **void getValue(int id, TypedValue outValue, boolean resolveRefs)**: Return the raw data associated with a particular resource ID.
- **void getValueForDensity(int id, int density, TypedValue outValue, boolean resolveRefs)**: Get the raw value associated with a resource with associated density.
- **XmlResourceParser getXml(int id)**: Return an `XmlResourceParser` through which you can read a generic XML resource for the given resource ID.
- **final Resources.Theme newTheme()**: Generate a new `Theme` object for this set of `Resources`.
- **TypedArray obtainAttributes(AttributeSet set, int[] attrs)**: Retrieve a set of basic attribute values from an `AttributeSet`, not performing styling of them using a theme and/or style resources.
- **TypedArray obtainTypedArray(int id)**: Return an array of heterogeneous values.
- **InputStream openRawResource(int id, TypedValue value)**: Open a data stream for reading a raw resource.
- **InputStream openRawResource(int id)**: Open a data stream for reading a raw resource.
- **AssetFileDescriptor openRawResourceFd(int id)**: Open a file descriptor for reading a raw resource.
- **void parseBundleExtra(String tagName, AttributeSet attrs, Bundle outBundle)**: Parse a name/value pair out of an XML tag holding that data.

- **void parseBundleExtras(XmlResourceParser parser, Bundle outBundle):** Parse a series of <extra> tags from an XML file.
  - **static void registerResourcePaths(String uniqueId, ApplicationInfo appInfo):** Register the resources paths of a package (e.g. a shared library).
  - **void removeLoaders(ResourcesLoader... loaders):** Removes loaders from the list of loaders.
  - **void updateConfiguration(Configuration config, DisplayMetrics metrics):** This method was deprecated in API level 25. See Context.createConfigurationContext(Configuration).
- **Constants**
    - **int ID\_NULL:** The null resource ID.

## 1.10 DisplayMetrics

- **Getting a DisplayMetrics object:** We get an instance using the `getDisplayMetrics()` method from the `Resource` class

```
◦ DisplayMetrics metrics = getResources().getDisplayMetrics();
```

- **Hierarchy**

`java.lang.Object` → `android.util.DisplayMetrics`

- **Include**

```
◦ android.util.DisplayMetrics
```

- **Constructors**

```
◦ DisplayMetrics()
```

- **Public methods**

- **boolean equals(DisplayMetrics other):** Returns true if these display metrics equal the other display metrics.
- **boolean equals(Object o):** Indicates whether some other object is "equal to" this one.
- **int hashCode():** Returns a hash code value for the object.
- **void setTo(DisplayMetrics o):**
- **void setToDefaults():**
- **String toString():** Returns a string representation of the object.

- **Fields**

- **public static final int DENSITY\_DEVICE\_STABLE:** The device's stable density.
- **public float density:** The logical density of the display.
- **public int densityDpi:** The screen density expressed as dots-per-inch.
- **public int heightPixels:** The absolute height of the available display size in pixels.
- **public float scaledDensity:** This field was deprecated in API level 34. this scalar factor is no longer accurate due to adaptive non-linear font scaling. Please use `TypedValue.applyDimension(int, float, DisplayMetrics)` or `TypedValue.deriveDimension(int, float, DisplayMetrics)` to convert between SP font sizes and pixels.
- **public int widthPixels:** The absolute width of the available display size in pixels.
- **public float xdpi:** The exact physical pixels per inch of the screen in the X dimension.



- **public float ydpi**: The exact physical pixels per inch of the screen in the Y dimension.

- **Constants**

- **int DENSITY\_140**: Intermediate density for screens that sit between DENSITY\_LOW (120dpi) and DENSITY\_MEDIUM (160dpi).
- **int DENSITY\_180**: Intermediate density for screens that sit between DENSITY\_MEDIUM (160dpi) and DENSITY\_HIGH (240dpi).
- **int DENSITY\_200**: Intermediate density for screens that sit between DENSITY\_MEDIUM (160dpi) and DENSITY\_HIGH (240dpi).
- **int DENSITY\_220**: Intermediate density for screens that sit between DENSITY\_MEDIUM (160dpi) and DENSITY\_HIGH (240dpi).
- **int DENSITY\_260**: Intermediate density for screens that sit between DENSITY\_HIGH (240dpi) and DENSITY\_XHIGH (320dpi).
- **int DENSITY\_280**: Intermediate density for screens that sit between DENSITY\_HIGH (240dpi) and DENSITY\_XHIGH (320dpi).
- **int DENSITY\_300**: Intermediate density for screens that sit between DENSITY\_HIGH (240dpi) and DENSITY\_XHIGH (320dpi).
- **int DENSITY\_340**: Intermediate density for screens that sit somewhere between DENSITY\_XHIGH (320 dpi) and DENSITY\_XXHIGH (480 dpi).
- **int DENSITY\_360**: Intermediate density for screens that sit somewhere between DENSITY\_XHIGH (320 dpi) and DENSITY\_XXHIGH (480 dpi).
- **int DENSITY\_390**: Intermediate density for screens that sit somewhere between DENSITY\_XHIGH (320 dpi) and DENSITY\_XXHIGH (480 dpi).
- **int DENSITY\_400**: Intermediate density for screens that sit somewhere between DENSITY\_XHIGH (320 dpi) and DENSITY\_XXHIGH (480 dpi).
- **int DENSITY\_420**: Intermediate density for screens that sit somewhere between DENSITY\_XHIGH (320 dpi) and DENSITY\_XXHIGH (480 dpi).
- **int DENSITY\_440**: Intermediate density for screens that sit somewhere between DENSITY\_XHIGH (320 dpi) and DENSITY\_XXHIGH (480 dpi).
- **int DENSITY\_450**: Intermediate density for screens that sit somewhere between DENSITY\_XHIGH (320 dpi) and DENSITY\_XXHIGH (480 dpi).
- **int DENSITY\_520**: Intermediate density for screens that sit somewhere between DENSITY\_XXHIGH (480 dpi) and DENSITY\_XXXHIGH (640 dpi).
- **int DENSITY\_560**: Intermediate density for screens that sit somewhere between DENSITY\_XXHIGH (480 dpi) and DENSITY\_XXXHIGH (640 dpi).
- **int DENSITY\_600**: Intermediate density for screens that sit somewhere between DENSITY\_XXHIGH (480 dpi) and DENSITY\_XXXHIGH (640 dpi).
- **int DENSITY\_DEFAULT**: The reference density used throughout the system.
- **int DENSITY\_HIGH**: Standard quantized DPI for high-density screens.
- **int DENSITY\_LOW**: Standard quantized DPI for low-density screens.
- **int DENSITY\_MEDIUM**: Standard quantized DPI for medium-density screens.
- **int DENSITY\_TV**: This is a secondary density, added for some common screen configurations.
- **int DENSITY\_XHIGH**: Standard quantized DPI for extra-high-density screens.

- **int DENSITY\_XXHIGH**: Standard quantized DPI for extra-extra-high-density screens.
- **int DENSITY\_XXXHIGH**: Standard quantized DPI for extra-extra-extra-high-density screens.

## 1.11 Log

- Hierarchy

java.lang.Object → android.util.Log

- Include

```
o android.util.Log
```

- Public methods

- **static int d(String tag, String msg, Throwable tr)**: Send a DEBUG log message and log the exception.
- **static int d(String tag, String msg)**: Send a DEBUG log message.
- **static int e(String tag, String msg)**: Send an ERROR log message.
- **static int e(String tag, String msg, Throwable tr)**: Send a ERROR log message and log the exception.
- **static String getStackTraceString(Throwable tr)**: Handy function to get a loggable stack trace from a Throwable

If any of the throwables in the cause chain is an `UnknownHostException`, this returns an empty string.

- **static int i(String tag, String msg, Throwable tr)**: Send a INFO log message and log the exception.
- **static int i(String tag, String msg)**: Send an INFO log message.
- **static boolean isLoggable(String tag, int level)**: Checks to see whether or not a log for the specified tag is loggable at the specified level.
- **static int println(int priority, String tag, String msg)**: Low-level logging call.
- **static int v(String tag, String msg)**: Send a VERBOSE log message.
- **static int v(String tag, String msg, Throwable tr)**: Send a VERBOSE log message and log the exception.
- **static int w(String tag, Throwable tr)**: Send a WARN log message and log the exception.
- **static int w(String tag, String msg, Throwable tr)**: Send a WARN log message and log the exception.
- **static int w(String tag, String msg)**: Send a WARN log message.
- **static int wtf(String tag, String msg)**: What a Terrible Failure: Report a condition that should never happen.
- **static int wtf(String tag, Throwable tr)**: What a Terrible Failure: Report an exception that should never happen.
- **static int wtf(String tag, String msg, Throwable tr)**: What a Terrible Failure: Report an exception that should never happen.

- Constants

- **int ASSERT**: Priority constant for the println method.
- **int DEBUG**: Priority constant for the println method; use Log.d.

- **int ERROR**: Priority constant for the println method; use Log.e.
- **int INFO**: Priority constant for the println method; use Log.i.
- **int VERBOSE**: Priority constant for the println method; use Log.v.
- **int WARN**: Priority constant for the println method; use Log.w.

## 1.12 WindowManager (Interface)

- **Getting WindowManagerObject:** We can get a WindowManager reference through the `.getWindowManager()` method in the activity class

```
o WindowManager wm = getWindowManager();
```

- **Signature**

```
o public interface WindowManager implements ViewManager
```

- **Include**

```
o android.view.WindowManager
```

- **Default methods**

- **default void addCrossWindowBlurEnabledListener(Consumer<Boolean> listener):** Adds a listener, which will be called when cross-window blurs are enabled/disabled at runtime.
- **default void addCrossWindowBlurEnabledListener(Executor executor, Consumer<Boolean> listener):** Adds a listener, which will be called when cross-window blurs are enabled/disabled at runtime.
- **default void addProposedRotationListener(Executor executor, IntConsumer listener):** Adds a listener to start monitoring the proposed rotation of the current associated context.
- **default int addScreenRecordingCallback(Executor executor, Consumer<Integer> callback):** Adds a screen recording callback.
- **default WindowMetrics getCurrentWindowMetrics():** Returns the WindowMetrics according to the current system state.
- **abstract Display getDefaultDisplay():** This method was deprecated in API level 30. Use `Context.getDisplay()` instead.
- **default WindowMetrics getMaximumWindowMetrics():** Returns the largest WindowMetrics an app may expect in the current system state.
- **default boolean isCrossWindowBlurEnabled():** Returns whether cross-window blur is currently enabled.
- **default InputTransferToken registerBatchedSurfaceControlInputReceiver(InputTransferToken hostInputTransferToken, SurfaceControl surfaceControl, Choreographer choreographer, SurfaceControlInputReceiver receiver):** Registers a SurfaceControlInputReceiver for a SurfaceControl that will receive batched input event.
- **default void registerTrustedPresentationListener(IBinder window, TrustedPresentationThresholds thresholds, Executor executor, Consumer<Boolean> listener):** Sets a callback to receive feedback about the presentation of a Window.

- **default InputTransferToken registerUnbatchedSurfaceControlInputReceiver(InputTransferToken hostInputTransferToken, SurfaceControl surfaceControl, Looper looper, SurfaceControlInputReceiver receiver):** Registers a SurfaceControlInputReceiver for a SurfaceControl that will receive every input event.
- **default void removeCrossWindowBlurEnabledListener(Consumer<Boolean> listener):** Removes a listener, previously added with addCrossWindowBlurEnabledListener(Executor, Consumer)
- **default void removeProposedRotationListener(IntConsumer listener):** Removes a listener, previously added with addProposedRotationListener(Executor, IntConsumer).
- **default void removeScreenRecordingCallback(Consumer<Integer> callback):** Removes a screen recording callback.
- **abstract void removeViewImmediate(View view):** Special variation of ViewManager.removeView(View) that immediately invokes the given view hierarchy's View.onDetachedFromWindow() methods before returning.
- **default boolean transferTouchEvent(InputTransferToken transferFromToken, InputTransferToken transferToToken):** Transfer the currently in progress touch gesture from the transferFromToken to the transferToToken.
- **default void unregisterSurfaceControlInputReceiver(SurfaceControl surfaceControl):** Unregisters and cleans up the registered SurfaceControlInputReceiver for the specified token.
- **default void unregisterTrustedPresentationListener(Consumer<Boolean> listener):** Removes a presentation listener associated with a window.

- **Constants**

- **int COMPAT\_SMALL\_COVER\_SCREEN\_OPT\_IN:** Value applicable for the PROPERTY\_COMPAT\_ALLOW\_SMALL\_COVER\_SCREEN property to provide a signal to the system that an application or its specific activities explicitly opt into being displayed on small cover screens on flippable style foldable devices that measure at least 1.5 inches up to 2.2 inches for the shorter dimension and at least 2.4 inches up to 3.4 inches for the longer dimension

Value is COMPAT\_SMALL\_COVER\_SCREEN\_OPT\_IN

- **String PROPERTY\_ACTIVITY\_EMBEDDING\_ALLOW\_SYSTEM\_OVERRIDE:** Application-level PackageManager.Property tag that specifies whether OEMs are permitted to provide activity embedding split-rule configurations on behalf of the app.
- **String PROPERTY\_ACTIVITY\_EMBEDDING\_SPLITS\_ENABLED:** Application level PackageManager.Property that an app can specify to inform the system that the app is activity embedding split feature enabled.
- **String PROPERTY\_CAMERA\_COMPAT\_ALLOW\_FORCE\_ROTATION:** Application level PackageManager.Property for an app to inform the system that the app should be excluded from the camera compatibility force rotation treatment.
- **String PROPERTY\_CAMERA\_COMPAT\_ALLOW\_REFRESH:** Application level PackageManager.Property for an app to inform the system that the app should be excluded from the activity "refresh" after the camera compatibility force rotation treatment.

- **String PROPERTY\_CAMERA\_COMPAT\_ALLOW\_SIMULATE\_REQUESTED\_ORIENTATION**: Application-level [PackageManager][android.content.pm.PackageManager.Property] tag that (when set to false) informs the system the app has opted out of the camera compatibility treatment for fixed-orientation apps, which simulates running on a portrait device, in the orientation requested by the app.
- **String PROPERTY\_CAMERA\_COMPAT\_ENABLE\_REFRESH\_VIA\_PAUSE**: Application level PackageManager.Property for an app to inform the system that the activity should be or shouldn't be "refreshed" after the camera compatibility force rotation treatment using "paused -> resumed" cycle rather than "stopped -> resumed".
- **String PROPERTY\_COMPAT\_ALLOW\_DISPLAY\_ORIENTATION\_OVERRIDE**: Application level PackageManager.Property for an app to inform the system that the app should be opted-out from the compatibility override that fixes display orientation to landscape natural orientation when an activity is fullscreen.
- **String PROPERTY\_COMPAT\_ALLOW\_IGNORE\_ORIENTATION\_REQUEST\_WHEN\_LOOP\_DETECTED**: Application level PackageManager.Property for an app to inform the system that the app can be opted-out from the compatibility treatment that avoids Activity#setRequestedOrientation() loops.
- **String PROPERTY\_COMPAT\_ALLOW\_MIN\_ASPECT\_RATIO\_OVERRIDE**: Application level PackageManager.Property for an app to inform the system that the app should be opted-out from the compatibility override that changes the min aspect ratio.
- **String PROPERTY\_COMPAT\_ALLOW\_ORIENTATION\_OVERRIDE**: Application level PackageManager.Property for an app to inform the system that the app should be excluded from the compatibility override for orientation set by the device manufacturer.
- **String PROPERTY\_COMPAT\_ALLOW\_RESIZEABLE\_ACTIVITY\_OVERRIDES**: Application level PackageManager.Property for an app to inform the system that the app should be opted-out from the compatibility overrides that change the resizability of the app.
- **String PROPERTY\_COMPAT\_ALLOW\_SANDBOXING\_VIEW\_BOUNDS\_APIS**: Application level PackageManager.Property for an app to inform the system that it needs to be opted-out from the compatibility treatment that sandboxes the View API.
- **String PROPERTY\_COMPAT\_ALLOW\_SMALL\_COVER\_SCREEN**: Application or Activity level PackageManager.Property to provide any preferences for showing all or specific Activities on small cover displays of foldable style devices.
- **String PROPERTY\_COMPAT\_ALLOW\_USER\_ASPECT\_RATIO\_FULLSCREEN\_OVERRIDE**: Application level PackageManager.Property tag that (when set to false) informs the system the app has opted out of the full-screen option of the user aspect ratio compatibility override settings.
- **String PROPERTY\_COMPAT\_ALLOW\_USER\_ASPECT\_RATIO\_OVERRIDE**: Application level PackageManager. Property tag that (when set to false) informs the system the app has opted out of the user-facing aspect ratio compatibility override.
- **String PROPERTY\_COMPAT\_ENABLE\_FAKE\_FOCUS**: Application level PackageManager.Property for an app to inform the system that the application can be opted-in or opted-out from the compatibility treatment that enables sending a fake focus event for unfocused resumed split-screen activities.

- **String PROPERTY\_COMPAT\_IGNORE\_REQUESTED\_ORIENTATION**: Application level PackageManager.Property for an app to inform the system that the app can be opted-in or opted-out from the compatibility treatment that avoids Activity#setRequestedOrientation() loops.
- **String PROPERTY\_SUPPORTS\_MULTI\_INSTANCE\_SYSTEM\_UI**: Activity or Application level PackageManager.Property for an app to declare that System UI should be shown for this app/component to allow it to be launched as multiple instances.
- **int SCREEN\_RECORDING\_STATE\_NOT\_VISIBLE**: Indicates the app that registered the callback is not visible in screen recording.
- **int SCREEN\_RECORDING\_STATE\_VISIBLE**: Indicates the app that registered the callback is visible in screen recording.



### 1.13 Display

- **Getting Display object:** We can get a Display object reference through the WindowManager object.

```
o Display display = getWindowManager().getDefaultDisplay();
```

- **Hierarchy**

java.lang.Object → android.view.Display

- **Include**

```
o android.view.Display
```

- **Public methods**

- **long getAppVsyncOffsetNanos():** Gets the app VSYNC offset, in nanoseconds.
- **void getCurrentSizeRange(Point outSmallestSize, Point outLargestSize):** Return the range of display sizes an application can expect to encounter under normal operation, as long as there is no physical change in screen size.
- **DisplayCutout getCutout():** Returns the DisplayCutout, or null if there is none.
- **DeviceInfo getDeviceInfo():** Returns the product-specific information about the display or the directly connected device on the display chain.
- **int getDisplayId():** Gets the display id.
- **int getFlags():** Returns a combination of flags that describe the capabilities of the display.
- **Display.HdrCapabilities getHdrCapabilities():** Returns the current display mode's HDR capabilities.
- **float getHdrSdrRatio():**
- **int getHeight():** This method was deprecated in API level 15. Use WindowMetrics.getBounds() instead.
- **float getHighestHdrSdrRatio():**
- **void getMetrics(DisplayMetrics outMetrics):** This method was deprecated in API level 30. Use WindowMetrics.getBounds() to get the dimensions of the application window. Use WindowMetrics.getDensity() to get the density of the application window.
- **Display.Mode getMode():** Returns the active mode of the display.
- **String getName():** Gets the name of the display.
- **int getOrientation():** This method was deprecated in API level 15. use getRotation()
- **OverlayProperties getOverlaySupport():** Returns the OverlayProperties of the display.
- **int getPixelFormat():** This method was deprecated in API level 17. This method is no longer supported. The result is always PixelFormat.RGBA\_8888.

- **ColorSpace getPreferredWideGamutColorSpace()**: Returns the preferred wide color space of the Display.
- **long getPresentationDeadlineNanos()**: This is how far in advance a buffer must be queued for presentation at a given time.
- **void getRealMetrics(DisplayMetrics outMetrics)**: This method was deprecated in API level 31. Use `WindowManager.getCurrentWindowMetrics()` to identify the current size of the activity window. UI-related work, such as choosing UI layouts, should rely upon `WindowMetrics.getBounds()`. Use `Configuration.densityDpi` to get the current density.
- **void getRealSize(Point outSize)**: This method was deprecated in API level 31. Use `WindowManager.getCurrentWindowMetrics()` to identify the current size of the activity window. UI-related work, such as choosing UI layouts, should rely upon `WindowMetrics.getBounds()`.
- **void getRectSize(Rect outSize)**: This method was deprecated in API level 30. Use `WindowMetrics.getBounds()` to get the dimensions of the application window.
- **float getRefreshRate()**: Gets the refresh rate of this display in frames per second.
- **int getRotation()**: Returns the rotation of the screen from its "natural" orientation.
- **RoundedCorner getRoundedCorner(int position)**: Returns the Rounded-Corner of the given position if there is one.
- **DisplayShape getShape()**: Returns the DisplayShape which is based on display coordinates.
- **void getSize(Point outSize)**: This method was deprecated in API level 30. Use `WindowMetrics` instead. Obtain a `WindowMetrics` instance by calling `WindowManager.getCurrentWindowMetrics()`, then call `WindowMetrics.getBounds()` to get the dimensions of the application window.
- **int getState()**: Gets the state of the display, such as whether it is on or off.
- **float getSuggestedFrameRate(int category)**: Gets the display-defined frame rate given a descriptive frame rate category.
- **Mode[] getSupportedModes()**: Gets the supported modes of this display, might include synthetic modes
- **float[] getSupportedRefreshRates()**: Get the supported refresh rates of this display in frames per second.
- **int getWidth()**: This method was deprecated in API level 15. Use `WindowMetrics.getBounds` instead.
- **boolean hasArrSupport()**: Returns whether display supports adaptive refresh rate or not.
- **boolean isHdr()**: Returns whether this display supports any HDR type.
- **boolean isHdrSdrRatioAvailable()**:
- **boolean isInternal()**: Check if this is a built-in display, i.e.
- **boolean isMinimalPostProcessingSupported()**: Returns true if the connected display can be switched into a mode with minimal post processing.
- **boolean isValid()**: Returns true if this display is still valid, false if the display has been removed.
- **boolean isWideColorGamut()**: Returns whether this display can be used to display wide color gamut content.

- **void registerHdrSdrRatioChangedListener(Executor executor, Consumer<Display> listener):** Registers a listener that will be invoked whenever the display's hdr/sdr ratio has changed.
- **String toString():** Returns a string representation of the object.
- **void unregisterHdrSdrRatioChangedListener(Consumer<Display> listener):**

- **Constants**

- **int DEFAULT\_DISPLAY:** The default Display id, which is the id of the primary display assuming there is one.
- **int FLAG\_PRESENTATION:** Display flag: Indicates that the display is a presentation display.
- **int FLAG\_PRIVATE:** Display flag: Indicates that the display is private.
- **int FLAG\_ROUND:** Display flag: Indicates that the display has a round shape.
- **int FLAG\_SECURE:** Display flag: Indicates that the display has a secure video output and supports compositing secure surfaces.
- **int FLAG\_SUPPORTS\_PROTECTED\_BUFFERS:** Display flag: Indicates that the display supports compositing content that is stored in protected graphics buffers.
- **int FRAME\_RATE\_CATEGORY\_HIGH:** High category determines the framework's recommended high frame rate.
- **int FRAME\_RATE\_CATEGORY\_NORMAL:** Normal category determines the framework's recommended normal frame rate.
- **int INVALID\_DISPLAY:** Invalid display id.
- **int STATE\_DOZE:** Display state: The display is dozing in a low power state; it is still on but is optimized for showing system-provided content while the device is non-interactive.
- **int STATE\_DOZE\_SUSPEND:** Display state: The display is dozing in a suspended low power state; it is still on but the CPU is not updating it.
- **int STATE\_OFF:** Display state: The display is off.
- **int STATE\_ON:** Display state: The display is on.
- **int STATE\_ON\_SUSPEND:** Display state: The display is in a suspended full power state; it is still on but the CPU is not updating it.
- **int STATE\_UNKNOWN:** Display state: The display state is unknown.
- **int STATE\_VR:** Display state: The display is on and optimized for VR mode.

## 1.14 ConstraintLayout

- **Hierarchy:**

java.lang.Object → android.view.View → android.view.ViewGroup →  
androidx.constraintlayout.widget.ConstraintLayout

- **Include:**

```
0 androidx.constraintlayout.widget.ConstraintLayout
```

- **Constructors:**

```
0 ConstraintLayout(@NonNull Context context)
1 ConstraintLayout(@NonNull Context context, @Nullable
  ↳ AttributeSet attrs)
2 ConstraintLayout(@NonNull Context context, @Nullable
  ↳ AttributeSet attrs, int defStyleAttr)
3
4 @TargetApi(value = Build.VERSION_CODES.LOLLIPOP)
5 ConstraintLayout(@NonNull Context context, @Nullable
  ↳ AttributeSet attrs, int defStyleAttr, int defStyleRes)
```

- **Public methods:**

- **void addValueModifier(ConstraintLayout.ValueModifier modifier):** Adds a ValueModifier to the ConstraintLayout.
- **void fillMetrics(Metrics metrics):** Populates the provided Metrics object with performance and measurement data.
- **void forceLayout():** Forces a layout pass, marking the layout as needing to be re-measured and re-laid out.
- **ConstraintLayout.LayoutParams generateLayoutParams(AttributeSet attrs):** Returns a new set of layout parameters based on the supplied attributes set.
- **Object getDesignInformation(int type, Object value):** Retrieves design-time information associated with the layout.
- **int getMaxHeight():** Returns the maximum height of this view.
- **int getMaxWidth():** Returns the maximum width of this view.
- **int getMinHeight():** Returns the minimum height of this view.
- **int getMinWidth():** Returns the minimum width of this view.
- **int getOptimizationLevel():** Returns the current optimization level for the layout resolution.
- **String getSceneString():** Returns a JSON5 string useful for debugging the constraints currently applied.
- **static SharedValues getSharedValues():** Returns the SharedValues instance, creating it if it does not already exist.
- **View getViewById(int id):** Returns the View corresponding to the given ID.
- **final ConstraintWidget getViewWidget(View view):** Returns the internal ConstraintWidget associated with a given view.

- **void loadLayoutDescription(int layoutDescription)**: Loads a layout description file from the application’s resources.
- **void onViewAdded(View view)**: Called when a child view is added to the layout.
- **void onViewRemoved(View view)**: Called when a child view is removed from the layout.
- **void requestLayout()**: Requests a re-layout of this view hierarchy.
- **void setConstraintSet(ConstraintSet set)**: Sets a **ConstraintSet** object to manage constraints.
- **void setDesignInformation(int type, Object value1, Object value2)**: Stores design-time information associated with the layout.
- **void setId(int id)**: Sets the ID for this view.
- **void setMaxHeight(int value)**: Sets the maximum height for this view.
- **void setMaxWidth(int value)**: Sets the maximum width for this view.
- **void setMinHeight(int value)**: Sets the minimum height for this view.
- **void setMinWidth(int value)**: Sets the minimum width for this view.
- **void setOnConstraintsChanged(ConstraintsChangeListener constraintsChangeListener)**: Registers a listener to be notified when constraints change.
- **void setOptimizationLevel(int level)**: Sets the optimization level for layout resolution.
- **void setState(int id, int screenWidth, int screenHeight)**: Sets the state of the **ConstraintLayout**, causing it to load a specific **ConstraintSet**.
- **boolean shouldDelayChildPressedState()**: Returns true if the pressed state should be delayed for children or descendants of this **ViewGroup**.

- **Protected methods:**

- **void applyConstraintsFromLayoutParams(boolean isInEditMode, View child, ConstraintWidget widget, ConstraintLayout.LayoutParams layoutParams, SparseArray<ConstraintWidget> idToWidget)**: Applies constraints from the given layout parameters to the specified **ConstraintWidget**.
- **boolean checkLayoutParams(ViewGroup.LayoutParams p)**: Determines whether the supplied layout parameters are valid for this layout.
- **void dispatchDraw(Canvas canvas)**: Called to draw the layout’s children onto the provided **Canvas**.
- **boolean dynamicUpdateConstraints(int widthMeasureSpec, int heightMeasureSpec)**: Can be overridden to change how **ValueModifiers** are used during dynamic updates of constraints.
- **ConstraintLayout.LayoutParams generateDefaultLayoutParams()**: Returns a set of default layout parameters for this **ConstraintLayout**.
- **ViewGroup.LayoutParams generateLayoutParams(ViewGroup.LayoutParams p)**: Returns a safe set of layout parameters based on the supplied parameters.
- **boolean isRtl()**: Returns **true** if the layout direction is right-to-left (RTL).
- **void onLayout(boolean changed, int left, int top, int right, int bottom)**: Called during layout to assign a size and position to each child.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the layout and its children to determine width and height.

- **void parseLayoutDescription(int id):** Called to handle layout descriptions; subclasses may override this method.
- **void resolveMeasuredDimension(int widthMeasureSpec, int heightMeasureSpec, int measuredWidth, int measuredHeight, boolean isWidthMeasuredTooSmall, boolean isHeightMeasuredTooSmall):** Handles setting the measured dimensions for the layout.
- **void resolveSystem(ConstraintWidgetContainer layout, int optimizationLevel, int widthMeasureSpec, int heightMeasureSpec):** Handles the measuring and constraint resolution of the layout.
- **void setSelfDimensionBehaviour(ConstraintWidgetContainer layout, int widthMode, int widthSize, int heightMode, int heightSize):** Configures the layout's own dimension behavior during constraint resolution.
- **Constants:**
  - **static final int DESIGN\_INFO\_ID = 0:**
  - **static final String VERSION = "ConstraintLayout-2.2.0-alpha04":**
- **Protected fields:**
  - **ConstraintLayoutStates mConstraintLayoutSpec:**
  - **boolean mDirtyHierarchy:**
  - **ConstraintWidgetContainer mLayoutWidget:**

## 1.15 ConstraintLayout.LayoutParams

- **Hierarchy:**

java.lang.Object → android.view.View → android.view.ViewGroup →  
androidx.constraintlayout.widget.ConstraintLayout

- **Include:**

```
0 androidx.constraintlayout.widget.ConstraintLayout
```

- **Constructors:**

```
0 LayoutParams(ViewGroup.LayoutParams params)
1 LayoutParams(Context c, AttributeSet attrs)
2 LayoutParams(int width, int height)
```

- **Public methods:**

- **String getConstraintTag():** Returns a tag that can be used to identify a view as being part of a constraint group.
- **ConstraintWidget getConstraintWidget():** Returns the underlying `ConstraintWidget` object associated with this layout parameter or view.
- **void reset():** Resets the associated `ConstraintWidget` to its default state.
- **void resolveLayoutDirection(int layoutDirection):** Resolves layout direction-dependent constraints such as start/end alignment.
- **void setWidgetDebugName(String text):** Sets a debug name for the `ConstraintWidget`, useful for diagnostics or logging.
- **void validate():** Validates the layout and ensures that all parameters and constraints are consistent.

- **Public fields:**

- **int baselineMargin:** The baseline margin.
- **int baselineToBaseline:** Constrains the baseline of a child to the baseline of a target child (contains the target child ID).
- **int baselineToBottom:** Constrains the baseline of a child to the bottom of a target child (contains the target child ID).
- **int baselineToTop:** Constrains the baseline of a child to the top of a target child (contains the target child ID).
- **int bottomToBottom:** Constrains the bottom side of a child to the bottom side of a target child (contains the target child ID).
- **int bottomToTop:** Constrains the bottom side of a child to the top side of a target child (contains the target child ID).
- **float circleAngle:** The angle used for a circular constraint.
- **int circleConstraint:** Constrains the center of a child to the center of a target child (contains the target child ID).
- **int circleRadius:** The radius used for a circular constraint.

- **boolean constrainedHeight**: Specifies if the vertical dimension is constrained when both top and bottom constraints are set and the dimension is not fixed.
- **boolean constrainedWidth**: Specifies if the horizontal dimension is constrained when both left and right constraints are set and the dimension is not fixed.
- **String constraintTag**: Defines a category of view to be used by helpers and MotionLayout.
- **String dimensionRatio**: The ratio information defining the aspect ratio of the view.
- **int editorAbsoluteX**: The design-time X coordinate (left position) of the child.
- **int editorAbsoluteY**: The design-time Y coordinate (top position) of the child.
- **int endToEnd**: Constrains the end side of a child to the end side of a target child (contains the target child ID).
- **int endToStart**: Constrains the end side of a child to the start side of a target child (contains the target child ID).
- **int goneBaselineMargin**: The baseline margin to use when the target is gone.
- **int goneBottomMargin**: The bottom margin to use when the target is gone.
- **int goneEndMargin**: The end margin to use when the target is gone.
- **int goneLeftMargin**: The left margin to use when the target is gone.
- **int goneRightMargin**: The right margin to use when the target is gone.
- **int goneStartMargin**: The start margin to use when the target is gone.
- **int goneTopMargin**: The top margin to use when the target is gone.
- **int guideBegin**: The distance of a guideline from the top or left edge of its parent.
- **int guideEnd**: The distance of a guideline from the bottom or right edge of its parent.
- **float guidePercent**: The ratio of the distance to the parent's sides.
- **boolean guidelineUseRtl**: Determines whether guideline position respects RTL layout direction.
- **boolean helped**: Indicates whether the view was modified by a helper.
- **float horizontalBias**: The ratio between two connections when left and right (or start and end) sides are constrained.
- **int horizontalChainStyle**: Defines how elements of a horizontal chain are positioned.
- **float horizontalWeight**: The child's weight used to distribute available horizontal space in a chain when using `MATCH_CONSTRAINT`.
- **int leftToLeft**: Constrains the left side of a child to the left side of a target child (contains the target child ID).
- **int leftToRight**: Constrains the left side of a child to the right side of a target child (contains the target child ID).
- **int matchConstraintDefaultHeight**: Defines how the widget's vertical dimension is handled when set to `MATCH_CONSTRAINT`.
- **int matchConstraintDefaultWidth**: Defines how the widget's horizontal dimension is handled when set to `MATCH_CONSTRAINT`.
- **int matchConstraintMaxHeight**: Specifies a maximum height for the widget.
- **int matchConstraintMaxWidth**: Specifies a maximum width for the widget.



- **int matchConstraintMinHeight**: Specifies a minimum height for the widget.
- **int matchConstraintMinWidth**: Specifies a minimum width for the widget.
- **float matchConstraintPercentHeight**: Specifies a percentage value when using the match-constraint percent mode for height.
- **float matchConstraintPercentWidth**: Specifies a percentage value when using the match-constraint percent mode for width.
- **int orientation**: The orientation of the layout (horizontal or vertical).
- **int rightToLeft**: Constrains the right side of a child to the left side of a target child (contains the target child ID).
- **int rightToRight**: Constrains the right side of a child to the right side of a target child (contains the target child ID).
- **int startToEnd**: Constrains the start side of a child to the end side of a target child (contains the target child ID).
- **int startToStart**: Constrains the start side of a child to the start side of a target child (contains the target child ID).
- **int topToBottom**: Constrains the top side of a child to the bottom side of a target child (contains the target child ID).
- **int topToTop**: Constrains the top side of a child to the top side of a target child (contains the target child ID).
- **float verticalBias**: The ratio between two connections when the top and bottom sides are constrained.
- **int verticalChainStyle**: Defines how elements of a vertical chain are positioned.
- **float verticalWeight**: The child's weight used to distribute available vertical space in a chain when using `MATCH_CONSTRAINT`.
- **int wrapBehaviorInParent**: Specifies how this view is considered during the parent's wrap computation:
  - \* `WRAP_BEHAVIOR_INCLUDED`: Included in both directions (default).
  - \* `WRAP_BEHAVIOR_HORIZONTAL_ONLY`: Included only horizontally.
  - \* `WRAP_BEHAVIOR_VERTICAL_ONLY`: Included only vertically.
  - \* `WRAP_BEHAVIOR_SKIPPED`: Excluded from wrap computation.

- **Constants:**

- **static final int BASELINE = 5**: The baseline of the text in a view.
- **static final int BOTTOM = 4**: The bottom side of a view.
- **static final int CHAIN\_PACKED = 2**: Chain packed style.
- **static final int CHAIN\_SPREAD = 0**: Chain spread style.
- **static final int CHAIN\_SPREAD\_INSIDE = 1**: Chain spread inside style.
- **static final int CIRCLE = 8**: Circle reference from a view.
- **static final int END = 7**: The right side of a view in left-to-right languages.
- **static final int GONE\_UNSET = -2147483648**: Defines an ID that is not set (default unset state).
- **static final int HORIZONTAL = 0**: The horizontal orientation.
- **static final int LEFT = 1**: The left side of a view.
- **static final int MATCH\_CONSTRAINT = 0**: Dimension will be controlled by constraints.

- **static final int MATCH\_CONSTRAINT\_PERCENT = 2:** Sets `matchConstraintDefault*` percent mode to be based on a percent of another dimension (usually the parent). Used for `matchConstraintDefaultWidth` and `matchConstraintDefaultHeight`.
- **static final int MATCH\_CONSTRAINT\_SPREAD = 0:** Sets `matchConstraintDefault*` to spread as much as possible within its constraints.
- **static final int MATCH\_CONSTRAINT\_WRAP = 1:** Sets `matchConstraintDefault*` to wrap content size.
- **static final int PARENT\_ID = 0:** References the ID of the parent layout.
- **static final int RIGHT = 2:** The right side of a view.
- **static final int START = 6:** The left side of a view in left-to-right languages.
- **static final int TOP = 3:** The top side of a view.
- **static final int UNSET = -1:** Defines an ID that is not set.
- **static final int VERTICAL = 1:** The vertical orientation.
- **static final int WRAP\_BEHAVIOR\_HORIZONTAL\_ONLY = 1:** Specifies that wrapping occurs only horizontally.
- **static final int WRAP\_BEHAVIOR\_INCLUDED = 0:** Specifies that wrapping includes both horizontal and vertical directions (default).
- **static final int WRAP\_BEHAVIOR\_SKIPPED = 3:** Specifies that the widget is excluded from wrap computation.
- **static final int WRAP\_BEHAVIOR\_VERTICAL\_ONLY = 2:** Specifies that wrapping occurs only vertically.

## 1.16 RelativeLayout

- **Hierarchy:**

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.RelativeLayout

- **Include:**

```
0  android.widget.RelativeLayout
```

- **Constructors:**

```
0  RelativeLayout(Context context)
1  RelativeLayout(Context context, AttributeSet attrs)
2  RelativeLayout(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  RelativeLayout(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleRes)
```

- **Public methods:**

- **RelativeLayout.LayoutParams generateLayoutParams(AttributeSet attrs):** Returns a new set of layout parameters based on the supplied attributes set.
- **CharSequence getAccessibilityClassName():** Return the class name of this object to be used for accessibility purposes.
- **int getBaseline():** Return the offset of the widget's text baseline from the widget's top boundary.
- **int getGravity():** Describes how the child views are positioned.
- **int getIgnoreGravity():** Get the ID of the View to be ignored by gravity.
- **void requestLayout():** Call this when something has changed that invalidates the layout of this view.
- **void setGravity(int gravity):** Describes how the child views are positioned.
- **void setHorizontalGravity(int horizontalGravity):** Sets the horizontal gravity of the layout.
- **void setIgnoreGravity(int viewId):** Defines which View is ignored when gravity is applied.
- **void setVerticalGravity(int verticalGravity):** Sets the vertical gravity of the layout.
- **boolean shouldDelayChildPressedState():** Returns true if the pressed state should be delayed for children or descendants of this ViewGroup.

- **Protected methods:**

- **boolean checkLayoutParams(ViewGroup.LayoutParams p):** Determines whether the supplied layout parameters are valid for this layout.
- **ViewGroup.LayoutParams generateDefaultLayoutParams():** Returns a set of layout parameters with a width of ViewGroup.LayoutParams.WRAP\_CONTENT, a height of ViewGroup.LayoutParams.WRAP\_CONTENT, and no spanning.

- **ViewGroup.LayoutParams generateLayoutParams(ViewGroup.LayoutParams lp)**: Returns a safe set of layout parameters based on the supplied layout parameters.
  - **void onLayout(boolean changed, int l, int t, int r, int b)**: Called from layout when this view should assign a size and position to each of its children.
  - **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its content to determine the measured width and height.
- **Constants:**
    - **int ABOVE**: Rule that aligns a child's bottom edge with another child's top edge.
    - **int ALIGN\_BASELINE**: Rule that aligns a child's baseline with another child's baseline.
    - **int ALIGN\_BOTTOM**: Rule that aligns a child's bottom edge with another child's bottom edge.
    - **int ALIGN\_END**: Rule that aligns a child's end edge with another child's end edge.
    - **int ALIGN\_LEFT**: Rule that aligns a child's left edge with another child's left edge.
    - **int ALIGN\_PARENT\_BOTTOM**: Rule that aligns the child's bottom edge with its `RelativeLayout` parent's bottom edge.
    - **int ALIGN\_PARENT\_END**: Rule that aligns the child's end edge with its `RelativeLayout` parent's end edge.
    - **int ALIGN\_PARENT\_LEFT**: Rule that aligns the child's left edge with its `RelativeLayout` parent's left edge.
    - **int ALIGN\_PARENT\_RIGHT**: Rule that aligns the child's right edge with its `RelativeLayout` parent's right edge.
    - **int ALIGN\_PARENT\_START**: Rule that aligns the child's start edge with its `RelativeLayout` parent's start edge.
    - **int ALIGN\_PARENT\_TOP**: Rule that aligns the child's top edge with its `RelativeLayout` parent's top edge.
    - **int ALIGN\_RIGHT**: Rule that aligns a child's right edge with another child's right edge.
    - **int ALIGN\_START**: Rule that aligns a child's start edge with another child's start edge.
    - **int ALIGN\_TOP**: Rule that aligns a child's top edge with another child's top edge.
    - **int BELOW**: Rule that aligns a child's top edge with another child's bottom edge.
    - **int CENTER\_HORIZONTAL**: Rule that centers the child horizontally with respect to the bounds of its `RelativeLayout` parent.
    - **int CENTER\_IN\_PARENT**: Rule that centers the child with respect to the bounds of its `RelativeLayout` parent.
    - **int CENTER\_VERTICAL**: Rule that centers the child vertically with respect to the bounds of its `RelativeLayout` parent.
    - **int END\_OF**: Rule that aligns a child's start edge with another child's end edge.

- **int LEFT\_OF**: Rule that aligns a child's right edge with another child's left edge.
- **int RIGHT\_OF**: Rule that aligns a child's left edge with another child's right edge.
- **int START\_OF**: Rule that aligns a child's end edge with another child's start edge.
- **int TRUE**: Constant used for layout rules that take a boolean value.

## 1.17 RelativeLayout.LayoutParams

- **Hierarchy:**

```
java.lang.Object → android.view.ViewGroup.LayoutParams →  
    android.view.ViewGroup.MarginLayoutParams →  
        android.widget.RelativeLayout.LayoutParams
```

- **Include**

```
0  android.widget.RelativeLayout.LayoutParams
```

- **Constructors:**

```
0  LayoutParams(Context c, AttributeSet attrs)  
1  LayoutParams(ViewGroup.LayoutParams source)  
2  LayoutParams(ViewGroup.MarginLayoutParams source)  
3  LayoutParams(RelativeLayout.LayoutParams source)  
4  LayoutParams(int w, int h)
```

- **Public methods:**

- **void addRule(int verb, int subject):** Adds a layout rule to be interpreted by the `RelativeLayout`, relative to another view.
- **void addRule(int verb):** Adds a layout rule to be interpreted by the `RelativeLayout`.
- **String debug(String output):** Returns a string representation of this set of layout parameters, typically used for debugging.
- **int getRule(int verb):** Returns the layout rule associated with a specific verb.
- **int[] getRules():** Retrieves a complete list of all supported rules, where each index represents a rule verb and each value represents the associated parameter (or `false` if not set).
- **void removeRule(int verb):** Removes a layout rule from interpretation by the `RelativeLayout`.
- **void resolveLayoutDirection(int layoutDirection):** Called by `View.requestLayout()` to resolve layout parameters that depend on layout direction (e.g., start/end alignment).

- **Fields:**

- **public boolean alignWithParent:** When true, uses the parent as the anchor if the anchor doesn't exist or if the anchor's visibility is `GONE`.

## 1.18 LinearLayout

- **Hierarchy:**

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.LinearLayout

- **Include**

```
0  android.widget.LinearLayout
```

- **Constructors:**

```
0  LinearLayout(Context context)
1  LinearLayout(Context context, AttributeSet attrs)
2  LinearLayout(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  LinearLayout(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleRes)
```

- **Public Methods:**

- **LinearLayout.LayoutParams generateLayoutParams(AttributeSet attrs):** Returns a new set of layout parameters based on the supplied attributes set.
- **CharSequence getAccessibilityClassName():** Return the class name of this object to be used for accessibility purposes.
- **int getBaseline():** Return the offset of the widget's text baseline from the widget's top boundary.
- **int getBaselineAlignedChildIndex():** Returns the index used for baseline alignment.
- **Drawable getDividerDrawable():** Returns the drawable used as a divider between child views.
- **int getDividerPadding():** Get the padding size used to inset dividers in pixels.
- **int getGravity():** Returns the current gravity.
- **int getOrientation():** Returns the current orientation.
- **int getShowDividers():** Returns how dividers are displayed between items.
- **float getWeightSum():** Returns the desired weights sum.
- **boolean isBaselineAligned():** Indicates whether widgets contained within this layout are aligned on their baseline or not.
- **boolean isMeasureWithLargestChildEnabled():** When true, all children with a weight will be considered having the minimum size of the largest child.
- **void onRtlPropertiesChanged(int layoutDirection):** Called when any RTL property (layout direction or text direction or text alignment) has been changed.
- **void setBaselineAligned(boolean baselineAligned):** Defines whether widgets contained in this layout are baseline-aligned or not.
- **void setBaselineAlignedChildIndex(int i):** Sets which child is used for baseline alignment.

- **void setDividerDrawable(Drawable divider)**: Set a drawable to be used as a divider between items.
- **void setDividerPadding(int padding)**: Set padding displayed on both ends of dividers.
- **void setGravity(int gravity)**: Describes how the child views are positioned.
- **void setHorizontalGravity(int horizontalGravity)**: Sets the horizontal gravity of the layout.
- **void setMeasureWithLargestChildEnabled(boolean enabled)**: When set to true, all children with a weight will be considered having the minimum size of the largest child.
- **void setOrientation(int orientation)**: Should the layout be a column or a row.
- **void setShowDividers(int showDividers)**: Set how dividers should be shown between items in this layout.
- **void setVerticalGravity(int verticalGravity)**: Sets the vertical gravity of the layout.
- **void setWeightSum(float weightSum)**: Defines the desired weights sum.
- **boolean shouldDelayChildPressedState()**: Return true if the pressed state should be delayed for children or descendants of this ViewGroup.

- **Protected Methods:**

- **boolean checkLayoutParams(ViewGroup.LayoutParams p)**: Determines whether the supplied layout parameters are valid for this layout.
- **LinearLayout.LayoutParams generateDefaultLayoutParams()**: Returns a set of layout parameters with a width of `ViewGroup.LayoutParams.MATCH_PARENT` and a height of `ViewGroup.LayoutParams.WRAP_CONTENT` when the layout's orientation is vertical.
- **LinearLayout.LayoutParams generateLayoutParams(ViewGroup.LayoutParams lp)**: Returns a safe set of layout parameters based on the supplied layout parameters.
- **void onDraw(Canvas canvas)**: Implement this method to perform custom drawing operations on the layout.
- **void onLayout(boolean changed, int l, int t, int r, int b)**: Called from layout when this view should assign a size and position to each of its children.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its content to determine the measured width and height.

- **Constants:**

- **int HORIZONTAL**: Constant indicating a horizontal orientation for the layout.
- **int SHOW\_DIVIDER\_BEGINNING**: Show a divider at the beginning of the group.
- **int SHOW\_DIVIDER\_END**: Show a divider at the end of the group.
- **int SHOW\_DIVIDER\_MIDDLE**: Show dividers between each item in the group.
- **int SHOW\_DIVIDER\_NONE**: Do not show any dividers.
- **int VERTICAL**: Constant indicating a vertical orientation for the layout.



## 1.19 LinearLayout.LayoutParams

- **Hierarchy:**

```
java.lang.Object → android.view.ViewGroup.LayoutParams →  
    android.view.ViewGroup.MarginLayoutParams →  
        android.widget.LinearLayout.LayoutParams
```

- **Include**

```
0  android.widget.LinearLayout.LayoutParams
```

- **Constructors:**

```
0  LayoutParams(Context c, AttributeSet attrs)  
1  LayoutParams(ViewGroup.LayoutParams p)  
2  LayoutParams(ViewGroup.MarginLayoutParams source)  
3  LayoutParams(LinearLayout.LayoutParams source)  
4  LayoutParams(int width, int height)  
5  LayoutParams(int width, int height, float weight)
```

- **Public methods:**

- **String debug(String output):**

- **Fields:**

- **public int gravity:** Gravity for the view associated with these LayoutParams.
- **public float weight:** Indicates how much of the extra space in the LinearLayout will be allocated to the view associated with these LayoutParams.

## 1.20 GridLayout

- **Hierarchy:**

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.GridLayout

- **Include:**

```
0  android.widget.GridLayout
```

- **Constructors**

```
0  GridLayout(Context context)
1  GridLayout(Context context, AttributeSet attrs)
2  GridLayout(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  GridLayout(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleRes)
```

- **Public methods**

- **GridLayout.LayoutParams generateLayoutParams(AttributeSet attrs):** Returns a new set of layout parameters based on the supplied attribute set.
- **CharSequence getAccessibilityClassName():** Returns the class name of this object to be used for accessibility purposes.
- **int getAlignmentMode():** Returns the current alignment mode used for positioning children within their grid cells.
- **int getColumnCount():** Returns the current number of columns.
- **int getOrientation():** Returns the current orientation (horizontal or vertical).
- **int getRowCount():** Returns the current number of rows.
- **boolean getUseDefaultMargins():** Returns whether this GridLayout will allocate default margins when none are defined in layout parameters.
- **boolean isColumnOrderPreserved():** Returns whether column boundaries are ordered by their grid indices.
- **boolean isRowOrderPreserved():** Returns whether row boundaries are ordered by their grid indices.
- **void onViewAdded(View child):** Called when a new child view is added to this ViewGroup.
- **void onViewRemoved(View child):** Called when a child view is removed from this ViewGroup.
- **void requestLayout():** Call this when something has changed that invalidates the layout of this view.
- **void setAlignmentMode(int alignmentMode):** Sets the alignment mode used for alignments between children of this container.
- **void setColumnCount(int columnCount):** Sets the total number of columns. Used to generate default column indices when none are specified.

- **void setColumnOrderPreserved(boolean columnOrderPreserved)**: When true, forces `GridLayout` to place column boundaries so their grid indices appear in ascending order.
- **void setOrientation(int orientation)**: Sets the layout's orientation. This controls:
  - \* The direction in which default row/column indices are generated when not specified.
  - \* Whether the grid is treated as row-major or column-major.
- **void setRowCount(int rowCount)**: Sets the total number of rows. Used to generate default row indices when none are specified.
- **void setRowOrderPreserved(boolean rowOrderPreserved)**: When true, forces `GridLayout` to place row boundaries in ascending order of their grid indices.
- **void setUseDefaultMargins(boolean useDefaultMargins)**: When true, `GridLayout` allocates default margins based on child visual characteristics.
- **static GridLayout.Spec spec(int start, float weight)**: Equivalent to `spec(start, 1, weight)`.
- **static GridLayout.Spec spec(int start)**: Returns a `Spec` where:
  - \* `span = [start, start + 1]`
  - \* To leave the start index undefined, use `UNDEFINED`.
- **static GridLayout.Spec spec(int start, int size, GridLayout.Alignment alignment, float weight)**: Returns a `Spec` where:
  - \* `span = [start, start + size]`
  - \* `alignment = alignment`
  - \* `weight = weight`
  - \* To leave the start index undefined, use `UNDEFINED`.
- **static GridLayout.Spec spec(int start, GridLayout.Alignment alignment, float weight)**: Equivalent to `spec(start, 1, alignment, weight)`.
- **static GridLayout.Spec spec(int start, int size, GridLayout.Alignment alignment)**: Equivalent to `spec(start, size, alignment, 0f)`.
- **static GridLayout.Spec spec(int start, GridLayout.Alignment alignment)**: Returns a `Spec` where:
  - \* `span = [start, start + 1]`
  - \* `alignment = alignment`
  - \* To leave the start index undefined, use `UNDEFINED`.
- **static GridLayout.Spec spec(int start, int size, float weight)**: Equivalent to `spec(start, size, default_alignment, weight)`, where `default_alignment` is defined in `GridLayout.LayoutParams`.
- **static GridLayout.Spec spec(int start, int size)**: Returns a `Spec` where:
  - \* `span = [start, start + size]`
  - \* To leave the start index undefined, use `UNDEFINED`.

- **Protected methods**

- **boolean checkLayoutParams(ViewGroup.LayoutParams p)**: Determines whether the supplied layout parameters are valid for this layout.
- **GridLayout.LayoutParams generateDefaultLayoutParams()**: Returns a set of default layout parameters used by this `GridLayout`.

- **GridLayout.LayoutParams generateLayoutParams(ViewGroup.LayoutParams lp)**: Returns a safe set of layout parameters based on the supplied layout parameters.
  - **void onLayout(boolean changed, int left, int top, int right, int bottom)**: Called during layout when this view should assign a size and position to each of its children.
  - **void onMeasure(int widthSpec, int heightSpec)**: Measures the view and its content to determine the measured width and height.
- **Fields**
    - **public static final GridLayout.Alignment BASELINE**: Indicates that a view should be aligned with the baselines of the other views in its cell group.
    - **public static final GridLayout.Alignment BOTTOM**: Indicates that a view should be aligned with the bottom edges of the other views in its cell group.
    - **public static final GridLayout.Alignment CENTER**: Indicates that a view should be centered with the other views in its cell group.
    - **public static final GridLayout.Alignment END**: Indicates that a view should be aligned with the end edges of the other views in its cell group.
    - **public static final GridLayout.Alignment FILL**: Indicates that a view should expand to fill the boundaries of its cell group.
    - **public static final GridLayout.Alignment LEFT**: Indicates that a view should be aligned with the left edges of the other views in its cell group.
    - **public static final GridLayout.Alignment RIGHT**: Indicates that a view should be aligned with the right edges of the other views in its cell group.
    - **public static final GridLayout.Alignment START**: Indicates that a view should be aligned with the start edges of the other views in its cell group.
    - **public static final GridLayout.Alignment TOP**: Indicates that a view should be aligned with the top edges of the other views in its cell group.
  - **Constants**
    - **int ALIGN\_BOUNDS**: Constant representing an `alignmentMode`. Child bounds are aligned within their grid cells.
    - **int ALIGN\_MARGINS**: Constant representing an `alignmentMode`. Child margins are aligned within their grid cells.
    - **int HORIZONTAL**: Constant representing a horizontal orientation for the layout.
    - **int UNDEFINED**: Constant used to indicate that a value is undefined.
    - **int VERTICAL**: Constant representing a vertical orientation for the layout.

## 1.21 GridLayout.LayoutParams

- **Hierarchy:**

```
java.lang.Object → android.view.ViewGroup.LayoutParams →  
    android.view.ViewGroup.MarginLayoutParams →  
        android.widget.GridLayout.LayoutParams
```

- **Include:**

```
0  android.widget.GridLayout.LayoutParams
```

- **Constructors:**

```
0  LayoutParams()  
1  LayoutParams(Context context, AttributeSet attrs)  
2  LayoutParams(ViewGroup.LayoutParams params)  
3  LayoutParams(ViewGroup.MarginLayoutParams params)  
4  LayoutParams(GridLayout.LayoutParams source)  
5  LayoutParams(GridLayout.Spec rowSpec, GridLayout.Spec  
    ↪ columnSpec)
```

**Note:** Values not defined in the attribute set take the default values defined in LayoutParams.

- **Public methods**

- **boolean equals(Object o):** Indicates whether some other object is "equal to" this one.
- **int hashCode():** Returns a hash code value for the object.
- **void setGravity(int gravity):** Describes how the child views are positioned.

- **Protected methods**

- **void setBaseAttributes(TypedArray attributes, int widthAttr, int heightAttr):** Extracts the layout parameters from the supplied attributes.

- **Fields**

- **public GridLayout.Spec columnSpec:** The spec that defines the horizontal characteristics of the cell group described by these layout parameters.
- **public GridLayout.Spec rowSpec:** The spec that defines the vertical characteristics of the cell group described by these layout parameters.

## 1.22 GridLayout.Spec

- Hierarchy

java.lang.Object → android.widget.GridLayout.Spec

- Include

```
0  android.widget.GridLayout.Spec
```

- Public methods

- **boolean equals(Object that):** Returns true if the class, alignment and span properties of this Spec and the supplied parameter are pairwise equal, false otherwise.
- **int hashCode():** Returns a hash code value for the object.

## 1.23 TableLayout

- **Hierarchy:**

```
java.lang.Object → android.view.View → android.view.ViewGroup →  
    android.widget.LinearLayout → android.widget.TableLayout
```

- **Include**

```
0  android.widget.TableLayout
```

- **Constructors**

```
0  TableLayout(Context context)  
1  TableLayout(Context context, AttributeSet attrs)
```

- **Public methods**

- **void addView(View child, int index):** Adds a child view at the specified index.
- **void addView(View child, ViewGroup.LayoutParams params):** Adds a child view with the specified layout parameters.
- **void addView(View child):** Adds a child view to the layout.
- **void addView(View child, int index, ViewGroup.LayoutParams params):** Adds a child view at the specified index with the given layout parameters.
- **TableLayout.LayoutParams generateLayoutParams(AttributeSet attrs):** Returns a new set of layout parameters based on the supplied attribute set.
- **CharSequence getAccessibilityClassName():** Returns the class name of this object to be used for accessibility purposes.
- **boolean isColumnCollapsed(int columnIndex):** Returns the collapsed state of the specified column.
- **boolean isColumnShrinkable(int columnIndex):** Returns whether the specified column is shrinkable.
- **boolean isColumnStretchable(int columnIndex):** Returns whether the specified column is stretchable.
- **boolean isShrinkAllColumns():** Indicates whether all columns in the table are shrinkable.
- **boolean isStretchAllColumns():** Indicates whether all columns in the table are stretchable.
- **void requestLayout():** Call this when something has changed that invalidates the layout of this view.
- **void setColumnCollapsed(int columnIndex, boolean isCollapsed):** Collapses or restores the specified column.
- **void setColumnShrinkable(int columnIndex, boolean isShrinkable):** Sets whether the specified column can shrink if necessary.
- **void setColumnStretchable(int columnIndex, boolean isStretchable):** Sets whether the specified column can stretch to fill available space.

- **void setOnHierarchyChangeListener(ViewGroup.OnHierarchyChangeListener listener)**: Registers a listener to be notified when a child view is added to or removed from this layout.
- **void setShrinkAllColumns(boolean shrinkAllColumns)**: Convenience method to mark all columns as shrinkable.
- **void setStretchAllColumns(boolean stretchAllColumns)**: Convenience method to mark all columns as stretchable.
- **Protected methods**
  - **boolean checkLayoutParams(ViewGroup.LayoutParams p)**: Determines whether the supplied layout parameters are valid for this layout.
  - **LinearLayout.LayoutParams generateDefaultLayoutParams()**: Returns a set of default layout parameters with a width of `ViewGroup.LayoutParams.MATCH_PARENT` and a height of `ViewGroup.LayoutParams.WRAP_CONTENT`.
  - **LinearLayout.LayoutParams generateLayoutParams(ViewGroup.LayoutParams p)**: Returns a safe set of layout parameters based on the supplied layout parameters.
  - **void onLayout(boolean changed, int l, int t, int r, int b)**: Called during layout when this view should assign a size and position to each of its children.
  - **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its content to determine the measured width and height.



## 1.24 TableLayout.LayoutParams

- Hierarchy

```
java.lang.Object → android.view.ViewGroup.LayoutParams →  
    android.view.ViewGroup.MarginLayoutParams →  
        android.widget.LinearLayout.LayoutParams →  
            android.widget.TableLayout.LayoutParams
```

- Include

```
0  android.widget.TableLayout.LayoutParams
```

- Constructors

```
0  LayoutParams()  
1  LayoutParams(Context c, AttributeSet attrs)  
2  LayoutParams(ViewGroup.LayoutParams p)  
3  LayoutParams(ViewGroup.MarginLayoutParams source)  
4  LayoutParams(int w, int h)  
5  LayoutParams(int w, int h, float initWeight)
```

- Protected methods

- **void setBaseAttributes(TypedArray a, int widthAttr, int heightAttr):**  
Fixes the row's width to ViewGroup.LayoutParams.MATCH\_PARENT; the row's height is fixed to ViewGroup.LayoutParams.WRAP\_CONTENT if no layout height is specified.

## 1.25 TableRow

- Hierarchy

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.LinearLayout → android.widget.TableRow

- Include

```
0  android.widget.TableRow
```

- Constructors

```
0  TableRow(Context context)
1  TableRow(Context context, AttributeSet attrs)
```

- Public methods

- **TableRow.LayoutParams generateLayoutParams(AttributeSet attrs):** Returns a new set of layout parameters based on the supplied attributes set.
- **CharSequence getAccessibilityClassName():** Return the class name of this object to be used for accessibility purposes.
- **View getChildAt(int i):**
- **int getChildCount():**
- **void setOnHierarchyChangeListener(ViewGroup.OnHierarchyChangeListener listener):** Register a callback to be invoked when a child is added to or removed from this view.

- Protected methods

- **boolean checkLayoutParams(ViewGroup.LayoutParams p):**
- **LinearLayout.LayoutParams generateDefaultLayoutParams():** Returns a set of layout parameters with a width of ViewGroup.LayoutParams.MATCH\_PARENT, a height of ViewGroup.LayoutParams.WRAP\_CONTENT and no spanning.
- **LinearLayout.LayoutParams generateLayoutParams(ViewGroup.LayoutParams p):** Returns a safe set of layout parameters based on the supplied layout params.
- **void onLayout(boolean changed, int l, int t, int r, int b):** Called from layout when this view should assign a size and position to each of its children.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec):** Measure the view and its content to determine the measured width and the measured height.

## 1.26 FrameLayout

- Hierarchy

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.FrameLayout

- Include

```
0  android.widget.FrameLayout
```

- Constructors

```
0  FrameLayout(Context context)
1  FrameLayout(Context context, AttributeSet attrs)
2  FrameLayout(Context context, AttributeSet attrs, int
    ↪  defStyleAttr, int defStyleRes)
3  FrameLayout(Context context, AttributeSet attrs, int
    ↪  defStyleAttr)
```

- Public methods

- **FrameLayout.LayoutParams generateLayoutParams(AttributeSet attrs)**: Returns a new set of layout parameters based on the supplied attribute set.
- **CharSequence getAccessibilityClassName()**: Returns the class name of this object to be used for accessibility purposes.
- **boolean getConsiderGoneChildrenWhenMeasuring()**: (*Deprecated in API level 15*) — Previously determined whether to include GONE children in measurement. Replaced by **getMeasureAllChildren()** for naming consistency.
- **boolean getMeasureAllChildren()**: Determines whether all children, or only those in the **VISIBLE** or **INVISIBLE** state, are considered during measurement.
- **void setForegroundGravity(int foregroundGravity)**: Describes how the foreground drawable is positioned within the layout.
- **void setMeasureAllChildren(boolean measureAll)**: Sets whether all children, or only visible ones, should be considered when measuring the layout.
- **boolean shouldDelayChildPressedState()**: Returns true if the pressed state should be delayed for children or descendants of this **ViewGroup**.

- Protected methods

- **boolean checkLayoutParams(ViewGroup.LayoutParams p)**: Determines whether the supplied layout parameters are valid for this layout.
- **FrameLayout.LayoutParams generateDefaultLayoutParams()**: Returns a set of default layout parameters with both width and height set to **ViewGroup.LayoutParams.MATCH\_PARENT**.
- **ViewGroup.LayoutParams generateLayoutParams(ViewGroup.LayoutParams lp)**: Returns a safe set of layout parameters based on the supplied layout parameters.
- **void onLayout(boolean changed, int left, int top, int right, int bottom)**: Called during layout when this view should assign a size and position to each of its children.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its content to determine the measured width and height.

## 1.27 `FrameLayout.LayoutParams`

- **Hierarchy**

```
java.lang.Object → android.view.ViewGroup.LayoutParams →  
    android.view.ViewGroup.MarginLayoutParams →  
        android.widget.FrameLayout.LayoutParams
```

- **Include**

```
0  android.widget.FrameLayout.LayoutParams
```

- **Constructors**

```
0  LayoutParams(Context c, AttributeSet attrs)  
1  LayoutParams(ViewGroup.LayoutParams source)  
2  LayoutParams(ViewGroup.MarginLayoutParams source)  
3  LayoutParams(FrameLayout.LayoutParams source)  
4  LayoutParams(int width, int height)  
5  LayoutParams(int width, int height, int gravity)
```

- **Fields**

- **public int gravity**: The gravity to apply with the View to which these layout parameters are associated.

- **Constants**

- **int UNSPECIFIED\_GRAVITY**: Value for gravity indicating that a gravity has not been explicitly specified.

## 1.28 ListView

- **Hierarchy:**

```
java.lang.Object → android.view.View → android.view.ViewGroup →  
    android.widget.AdapterView<android.widget.ListAdapter> →  
        android.widget.AbsListView → android.widget.ListView
```

- **Include**

```
0  android.widget.ListView
```

- **Constructors**

```
0  ListView(Context context)  
1  ListView(Context context, AttributeSet attrs)  
2  ListView(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr)  
3  ListView(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr, int defStyleRes)
```

- **Public methods**

- **void addFooterView(View v)**: Adds a fixed view to appear at the bottom of the list.
- **void addFooterView(View v, Object data, boolean isSelectable)**: Adds a fixed view to appear at the bottom of the list with optional data and selectable state.
- **void addHeaderView(View v, Object data, boolean isSelectable)**: Adds a fixed view to appear at the top of the list with optional data and selectable state.
- **void addHeaderView(View v)**: Adds a fixed view to appear at the top of the list.
- **boolean areFooterDividersEnabled()**: Returns whether footer dividers are currently enabled.
- **boolean areHeaderDividersEnabled()**: Returns whether header dividers are currently enabled.
- **boolean dispatchKeyEvent(KeyEvent event)**: Dispatches a key event to the next view on the focus path.
- **CharSequence getAccessibilityClassName()**: Returns the accessibility class name. A TYPE\_VIEW\_SCROLLED event should be sent whenever a scroll happens, even if position and child count remain unchanged.
- **ListAdapter getAdapter()**: Returns the adapter currently in use by this ListView.
- **long[] getCheckedItemIds()**: (*Deprecated in API 15*) — Use `AbsListView.getCheckedItemIds()` instead. Returns the IDs of the currently checked items.
- **Drawable getDivider()**: Returns the drawable that is drawn between each list item.
- **int getDividerHeight()**: Returns the height of the divider between list items.

- **int getFooterViewsCount()**: Returns the number of fixed footer views currently added.
- **int getHeaderViewsCount()**: Returns the number of fixed header views currently added.
- **boolean getItemsCanFocus()**: Returns whether list items can contain focusable elements.
- **int getMaxScrollAmount()**: Returns the maximum amount the list can scroll in response to arrow events.
- **Drawable getOverscrollFooter()**: Returns the drawable drawn below all list content when overscrolling.
- **Drawable getOverscrollHeader()**: Returns the drawable drawn above all list content when overscrolling.
- **boolean isOpaque()**: Indicates whether this view is opaque.
- **void onInitializeAccessibilityNodeInfoForItem(View view, int position, AccessibilityNodeInfo info)**: Initializes accessibility node info for a specific list item.
- **boolean onKeyDown(int keyCode, KeyEvent event)**: Default implementation handles key presses such as `KEYCODE_DPAD_CENTER` or `KEYCODE_ENTER` to trigger selection.
- **boolean onKeyMultiple(int keyCode, int repeatCount, KeyEvent event)**: Default implementation always returns false (does not handle multiple key events).
- **boolean onKeyUp(int keyCode, KeyEvent event)**: Default implementation handles key releases such as `KEYCODE_DPAD_CENTER`, `KEYCODE_ENTER`, or `KEYCODE_SPACE` to perform clicks.
- **boolean removeFooterView(View v)**: Removes a previously added footer view.
- **boolean removeHeaderView(View v)**: Removes a previously added header view.
- **boolean requestChildRectangleOnScreen(View child, Rect rect, boolean immediate)**: Called when a child requests that a specific rectangle within it be visible on the screen.
- **void setAdapter(ListAdapter adapter)**: Sets the adapter that provides the data and views for this `ListView`.
- **void setCacheColorHint(int color)**: When set to a nonzero value, indicates that the list is drawn on top of a solid, opaque background of that color.
- **void setDivider(Drawable divider)**: Sets the drawable that will be drawn between list items.
- **void setDividerHeight(int height)**: Sets the height of the divider drawn between list items.
- **void setFooterDividersEnabled(boolean footerDividersEnabled)**: Enables or disables drawing of dividers for footer views.
- **void setHeaderDividersEnabled(boolean headerDividersEnabled)**: Enables or disables drawing of dividers for header views.
- **void setItemsCanFocus(boolean itemsCanFocus)**: Indicates whether views created by the adapter can contain focusable items.
- **void setOverscrollFooter(Drawable footer)**: Sets the drawable to be drawn below all list content during overscroll.

- **void setOverscrollHeader(Drawable header)**: Sets the drawable to be drawn above all list content during overscroll.
- **void setRemoteViewsAdapter(Intent intent)**: Sets up this `ListView` to use a remote views adapter connected via a `RemoteViewsService`.
- **void setSelection(int position)**: Sets the currently selected item in the list.
- **void setSelectionAfterHeaderView()**: Sets the selection to the first list item following the header views.
- **void smoothScrollByOffset(int offset)**: Smoothly scrolls the list by the specified adapter position offset.
- **void smoothScrollToPosition(int position)**: Smoothly scrolls to the specified adapter position.

- **Protected methods**

- **boolean canAnimate()**: Indicates whether the view group can animate its children after the first layout pass.
- **void dispatchDraw(Canvas canvas)**: Called by the system's `draw()` method to render all child views within this layout.
- **boolean drawChild(Canvas canvas, View child, long drawingTime)**: Draws a single child view of this `ViewGroup` onto the provided `Canvas`.
- **void layoutChildren()**: Abstract method that subclasses must override to define how their child views are positioned and sized.
- **void onDetachedFromWindow()**: Called when the view is detached from its window, typically used to clean up resources or listeners.
- **void onFinishInflate()**: Called after a view and all its children have been inflated from XML to perform any final initialization.
- **void onFocusChanged(boolean gainFocus, int direction, Rect previouslyFocusedRect)**: Invoked when the view's focus state changes, providing the direction and previously focused rectangle.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its children to determine the overall measured width and height.
- **void onSizeChanged(int w, int h, int oldw, int oldh)**: Called during layout when the view's size changes, allowing for recalculation of layout-dependent properties.

## 1.29 TextView

- Hierarchy

java.lang.Object → android.view.View → android.widget.TextView

- Include

```
0 android.widget.TextView
```

- Constructors

```
0 TextView(Context context)
1 TextView(Context context, AttributeSet attrs)
2 TextView(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3 TextView(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleRes)
```

- Public methods

- **void addExtraDataToAccessibilityNodeInfo(AccessibilityNodeInfo info, String extraDataKey, Bundle arguments):** Adds extra data to an AccessibilityNodeInfo based on an explicit request for the additional data.
- **void addTextChangedListener(TextWatcher watcher):** Adds a TextWatcher whose methods are called whenever this TextView's text changes.
- **final void append(CharSequence text):** Appends text to the display buffer, upgrading to BufferType.EDITABLE if needed.
- **void append(CharSequence text, int start, int end):** Appends a slice of text to the display buffer, upgrading to BufferType.EDITABLE if needed.
- **void autofill(AutofillValue value):** Automatically fills this view's content with the provided value.
- **void beginBatchEdit():** Begins a batch edit session.
- **boolean bringPointIntoView(int offset):** Moves the character offset into view if needed.
- **boolean bringPointIntoView(int offset, boolean requestRectWithoutFocus):** Moves the insertion position at the given offset into the visible area.
- **void cancelLongPress():** Cancels a pending long press.
- **void clearComposingText():** Uses BaseInputConnection.removeComposingSpans() to clear IME composing state.
- **void computeScroll():** Requests the child to update mScrollX and mScrollY if necessary.
- **void debug(int depth):** Outputs debug information with the given depth.
- **boolean didTouchFocusSelect():** During a touch gesture, returns true iff initial touch moved focus to this view and changed selection.
- **void drawableHotspotChanged(float x, float y):** Propagates view hotspot changes to drawables/children.
- **void endBatchEdit():** Ends a batch edit session.



- **boolean extractText(ExtractedTextRequest request, ExtractedText outText)**: Extracts a portion of editable content into outText.
- **void findViewsWithText(ArrayList<View> outViews, CharSequence searched, int flags)**: Finds views containing the given text.
- **CharSequence getAccessibilityClassName()**: Returns the accessibility class name.
- **final int getAutoLinkMask()**: Gets the autolink mask.
- **int getAutoSizeMaxTextSize()**: Returns max auto-size text size.
- **int getAutoSizeMinTextSize()**: Returns min auto-size text size.
- **int getAutoSizeStepGranularity()**: Returns auto-size step granularity.
- **int[] getAutoSizeTextAvailableSizes()**: Returns available auto-size text sizes.
- **int getAutoSizeTextType()**: Returns the auto-size text type.
- **String[] getAutofillHints()**: Gets autofill hints for AutofillService.
- **int getAutofillType()**: Describes the autofill type for this view.
- **AutofillValue getAutofillValue()**: Returns current text as an AutofillValue.
- **int getBaseline()**: Returns the text baseline offset from the top.
- **int getBreakStrategy()**: Gets the paragraph line-break strategy.
- **int getCompoundDrawablePadding()**: Returns padding between compound drawables and text.
- **BlendMode getCompoundDrawableTintBlendMode()**: Returns the tint blend mode for compound drawables.
- **ColorStateList getCompoundDrawableTintList()**: Returns the tint list for compound drawables.
- **PorterDuff.Mode getCompoundDrawableTintMode()**: Returns the Porter-Duff tint mode for compound drawables.
- **Drawable[] getCompoundDrawables()**: Returns left, top, right, bottom drawables.
- **Drawable[] getCompoundDrawablesRelative()**: Returns start, top, end, bottom drawables.
- **int getCompoundPaddingBottom()**: Returns bottom padding plus drawable space.
- **int getCompoundPaddingEnd()**: Returns end padding plus drawable space.
- **int getCompoundPaddingLeft()**: Returns left padding plus drawable space.
- **int getCompoundPaddingRight()**: Returns right padding plus drawable space.
- **int getCompoundPaddingStart()**: Returns start padding plus drawable space.
- **int getCompoundPaddingTop()**: Returns top padding plus drawable space.
- **final int getCurrentHintTextColor()**: Returns current hint text color.
- **final int getCurrentTextColor()**: Returns current text color.
- **ActionMode.Callback getCustomInsertionActionModeCallback()**: Gets the custom insertion ActionMode callback.
- **ActionMode.Callback getCustomSelectionActionModeCallback()**: Gets the custom selection ActionMode callback.
- **Editable getEditableText()**: Returns the text as an Editable.
- **TextUtils.TruncateAt getEllipsize()**: Returns where long text is ellipsized.

- **CharSequence** **getError()**: Returns the current error message or **null**.
- **int** **getExtendedPaddingBottom()**: Returns extended bottom padding.
- **int** **getExtendedPaddingTop()**: Returns extended top padding.
- **InputFilter[]** **getFilters()**: Returns the list of input filters.
- **int** **getFirstBaselineToTopHeight()**: Distance from first baseline to top.
- **void** **getFocusedRect(Rect r)**: Fills **r** with the focus search rectangle.
- **int** **getFocusedSearchResultHighlightColor()**: Gets focused search result highlight color.
- **int** **getFocusedSearchResultIndex()**: Gets focused search result index.
- **String** **getFontFeatureSettings()**: Returns font feature settings.
- **String** **getFontVariationSettings()**: Returns font variation settings.
- **boolean** **getFreezesText()**: Whether full text is saved in icicles.
- **int** **getGravity()**: Returns horizontal/vertical text gravity.
- **int** **getHighlightColor()**: Returns selection highlight color.
- **Highlights** **getHighlights()**: Returns highlights.
- **CharSequence** **getHint()**: Returns the hint text.
- **final ColorStateList** **getHintTextColors()**: Returns hint text colors.
- **int** **getHyphenationFrequency()**: Gets automatic hyphenation frequency.
- **int** **getImeActionId()**: Gets IME action ID set via **setImeActionLabel**.
- **CharSequence** **getImeActionLabel()**: Gets IME action label.
- **LocaleList** **getImeHintLocales()**: Gets IME hint locales.
- **int** **getImeOptions()**: Gets IME options.
- **boolean** **getIncludeFontPadding()**: Whether extra ascent/descent padding is included.
- **Bundle** **getInputExtras(boolean create)**: Retrieves/creates input extras bundle.
- **int** **getInputType()**: Gets the editable content type.
- **int** **getJustificationMode()**: Gets text justification mode.
- **final KeyListener** **getKeyListener()**: Gets the current **KeyListener**.
- **int** **getLastBaselineToBottomHeight()**: Distance from last baseline to bottom.
- **final Layout** **getLayout()**: Gets the current text **Layout**.
- **float** **getLetterSpacing()**: Gets letter spacing (em).
- **int** **getLineBounds(int line, Rect bounds)**: Returns baseline for a line; optionally fills bounds.
- **int** **getLineBreakStyle()**: Gets line-break style.
- **int** **getLineBreakWordStyle()**: Gets line-break word style.
- **int** **getLineCount()**: Returns line count or 0 if layout not built.
- **int** **getLineHeight()**: Returns line height in pixels.
- **float** **getLineSpacingExtra()**: Returns extra line spacing.
- **float** **getLineSpacingMultiplier()**: Returns line spacing multiplier.
- **final ColorStateList** **getLinkTextColors()**: Returns link text colors.

- **final boolean** `getLinksClickable()`: Whether `LinkMovementMethod` is auto-set for links.
- **int** `getMarqueeRepeatLimit()`: Returns marquee repeat count.
- **int** `getMaxEms()`: Returns max width in ems, or -1.
- **int** `getMaxHeight()`: Returns max height in px, or -1.
- **int** `getMaxLines()`: Returns max lines, or -1.
- **int** `getMaxWidth()`: Returns max width in px, or -1.
- **int** `getMinEms()`: Returns min width in ems, or -1.
- **int** `getMinHeight()`: Returns min height in px, or -1.
- **int** `getMinLines()`: Returns min lines, or -1.
- **int** `getMinWidth()`: Returns min width in px, or -1.
- **Paint.FontMetrics** `getMinimumFontMetrics()`: Returns minimum font metrics used for line spacing.
- **final MovementMethod** `getMovementMethod()`: Gets the `MovementMethod`.
- **int** `getOffsetForPosition(float x, float y)`: Returns closest character offset to the given position.
- **TextPaint** `getPaint()`: Gets the `TextPaint`.
- **int** `getPaintFlags()`: Gets the current paint flags.
- **String** `getPrivateImeOptions()`: Gets private IME options.
- **int** `getSearchResultHighlightColor()`: Gets search result highlight color.
- **int[]** `getSearchResultHighlights()`: Gets current search result ranges.
- **int** `getSelectionEnd()`: Convenience for `Selection.getSelectionEnd()`.
- **int** `getSelectionStart()`: Convenience for `Selection.getSelectionStart()`.
- **int** `getShadowColor()`: Gets shadow color.
- **float** `getShadowDx()`: Gets shadow X offset.
- **float** `getShadowDy()`: Gets shadow Y offset.
- **float** `getShadowRadius()`: Gets shadow blur radius.
- **boolean** `getShiftDrawingOffsetForStartOverhang()`: True if shifting x-offset for start overhang.
- **final boolean** `getShowSoftInputOnFocus()`: Whether soft input shows on focus.
- **CharSequence** `getText()`: Returns the displayed text.
- **TextClassifier** `getTextClassifier()`: Returns the `TextClassifier`.
- **final ColorStateList** `getTextColors()`: Returns text colors by state.
- **Drawable** `getTextCursorDrawable()`: Returns the cursor drawable.
- **TextDirectionHeuristic** `getTextDirectionHeuristic()`: Returns resolved text direction heuristic.
- **Locale** `getTextLocale()`: Returns primary text `Locale`.
- **LocaleList** `getTextLocales()`: Returns text `LocaleList`.
- **PrecomputedText.Params** `getTextMetricsParams()`: Returns precomputed-text layout params.
- **float** `getTextScaleX()`: Returns horizontal text scale factor.
- **Drawable** `getTextSelectHandle()`: Returns selection handle drawable.

- **Drawable getTextSelectHandleLeft()**: Returns left selection handle drawable.
- **Drawable getTextSelectHandleRight()**: Returns right selection handle drawable.
- **float getTextSize()**: Returns text size (sp units).
- **int getTextSizeUnit()**: Returns the defined text size unit.
- **int getTotalPaddingBottom()**: Returns total bottom padding.
- **int getTotalPaddingEnd()**: Returns total end padding.
- **int getTotalPaddingLeft()**: Returns total left padding.
- **int getTotalPaddingRight()**: Returns total right padding.
- **int getTotalPaddingStart()**: Returns total start padding.
- **int getTotalPaddingTop()**: Returns total top padding.
- **final TransformationMethod getTransformationMethod()**: Returns the current text transformation method.
- **Typeface getTypeface()**: Returns the current **Typeface**.
- **URLSpan[] getUrls()**: Returns **URLSpans** attached to the text.
- **boolean getUseBoundsForWidth()**: True if bounding box width is used for line breaking/drawing.
- **boolean hasOverlappingRendering()**: Whether the view has overlapping rendering.
- **boolean hasSelection()**: True iff there is a nonzero-length selection.
- **void invalidateDrawable(Drawable drawable)**: Invalidates the given drawable.
- **boolean isAllCaps()**: Whether ALL CAPS transformation is applied.
- **boolean isAutoHandwritingEnabled()**: Whether automatic handwriting initiation is allowed.
- **boolean isCursorVisible()**: Whether the cursor is visible.
- **boolean isElegantTextHeight()**: Gets elegant height metrics flag.
- **boolean isFallbackLineSpacing()**: Whether fallback font ascent/descent is respected.
- **final boolean isHorizontallyScrollable()**: Whether text may be wider than the view.
- **boolean isInputMethodTarget()**: Whether this view is the current input method target.
- **boolean isLocalePreferredLineHeightForMinimumUsed()**: True if locale-preferred line height is used for minimum line height.
- **boolean isSingleLine()**: Whether text is constrained to a single scrolling line.
- **boolean isSuggestionsEnabled()**: Whether suggestions are enabled.
- **boolean isTextSelectable()**: Returns **textIsSelectable** state.
- **void jumpDrawablesToCurrentState()**: Calls **jumpToCurrentState()** on associated drawables.
- **int length()**: Returns the text length in characters.
- **boolean moveCursorToVisibleOffset()**: Moves cursor to a visible offset if needed.

- **void onBeginBatchEdit():** Called when a batch edit begins.
- **boolean onCheckIsTextEditor():** Whether this view is a text editor.
- **void onCommitCompletion(CompletionInfo text):** Called on IME completion.
- **void onCommitCorrection(CorrectionInfo info):** Called on IME auto-correction.
- **InputConnection onCreateInputConnection(EditorInfo outAttrs):** Creates an `InputConnection`.
- **void onCreateViewTranslationRequest(int[] supportedFormats, Consumer<ViewTranslationRequest> requestsCollector):** Collects view translation requests.
- **boolean onDragEvent(DragEvent event):** Handles drag events.
- **void onEditorAction(int actionCode):** Called for `performEditorAction()`.
- **void onEndBatchEdit():** Called when a batch edit ends.
- **boolean onGenericMotionEvent(MotionEvent event):** Handles generic motion events.
- **boolean onKeyDown(int keyCode, KeyEvent event):** Default handling for key down (e.g., `DPAD_CENTER/ENTER`).
- **boolean onKeyMultiple(int keyCode, int repeatCount, KeyEvent event):** Default returns false for multiple key events.
- **boolean onKeyPreIme(int keyCode, KeyEvent event):** Handles a key event before IME processes it.
- **boolean onKeyShortcut(int keyCode, KeyEvent event):** Called when key shortcut isn't handled.
- **boolean onKeyUp(int keyCode, KeyEvent event):** Default handling for key up (e.g., `DPAD_CENTER/ENTER/SPACE`).
- **boolean onPreDraw():** Called when the view tree is about to be drawn.
- **boolean onPrivateIMECommand(String action, Bundle data):** Handles private IME commands.
- **ContentInfo onReceiveContent(ContentInfo payload):** Default content reception.
- **PointerIcon onResolvePointerIcon(MotionEvent event, int pointerIndex):** Resolves pointer icon for the event.
- **void onRestoreInstanceState(Parcelable state):** Restores internal state from `Parcelable`.
- **void onRtlPropertiesChanged(int layoutDirection):** Called when RTL-related properties change.
- **Parcelable onSaveInstanceState():** Saves internal state to a `Parcelable`.
- **void onScreenStateChanged(int screenState):** Called when the screen state changes.
- **boolean onTextContextMenuItem(int id):** Handles a text context menu selection.
- **boolean onTouchEvent(MotionEvent event):** Handles pointer events.
- **boolean onTrackballEvent(MotionEvent event):** Handles trackball events.
- **void onVisibilityAggregated(boolean isVisible):** Called when user-visibility may change.

- **void onWindowFocusChanged(boolean hasWindowFocus):** Called when the containing window's focus changes.
- **boolean performLongClick():** Invokes `OnLongClickListener`, if defined.
- **void removeTextChangedListener(TextWatcher watcher):** Removes a `TextWatcher`.
- **void sendAccessibilityEventUnchecked(AccessibilityEvent event):** Sends an accessibility event without checking if accessibility is enabled.
- **void setAllCaps(boolean allCaps):** Transforms input to ALL CAPS display.
- **final void setAutoLinkMask(int mask):** Sets the autolink mask.
- **void setAutoSizeTextTypeUniformWithConfiguration(int autoSizeMinTextSize, int autoSizeMaxTextSize, int autoSizeStepGranularity, int unit):** Configures uniform auto-size text.
- **void setAutoSizeTextTypeUniformWithPresetSizes(int[] presetSizes, int unit):** Sets preset sizes for auto-size text.
- **void setAutoSizeTextTypeWithDefaults(int autoSizeTextType):** Enables default auto-size configuration.
- **void setBreakStrategy(int breakStrategy):** Sets paragraph break strategy.
- **void setCompoundDrawablePadding(int pad):** Sets padding between drawables and text.
- **void setCompoundDrawableTintBlendMode(BlendMode blendMode):** Sets blend mode for compound drawable tints.
- **void setCompoundDrawableTintList(ColorStateList tint):** Applies tint to compound drawables.
- **void setCompoundDrawableTintMode(PorterDuff.Mode tintMode):** Sets Porter-Duff blend mode for drawable tints.
- **void setCompoundDrawables(Drawable left, Drawable top, Drawable right, Drawable bottom):** Sets left/top/right/bottom drawables.
- **void setCompoundDrawablesRelative(Drawable start, Drawable top, Drawable end, Drawable bottom):** Sets start/top/end/bottom drawables.
- **void setCompoundDrawablesRelativeWithIntrinsicBounds(Drawable start, Drawable top, Drawable end, Drawable bottom):** Sets start/top/end/bottom drawables with intrinsic bounds.
- **void setCompoundDrawablesRelativeWithIntrinsicBounds(int start, int top, int end, int bottom):** Same as above with resource IDs.
- **void setCompoundDrawablesWithIntrinsicBounds(Drawable left, Drawable top, Drawable right, Drawable bottom):** Sets left/top/right/bottom drawables with intrinsic bounds.
- **void setCompoundDrawablesWithIntrinsicBounds(int left, int top, int right, int bottom):** Same as above with resource IDs.
- **void setCursorVisible(boolean visible):** Shows/hides the cursor.
- **void setCustomInsertionActionModeCallback(ActionMode.Callback actionModeCallback):** Sets custom insertion `ActionMode` callback.
- **void setCustomSelectionActionModeCallback(ActionMode.Callback actionModeCallback):** Sets custom selection `ActionMode` callback.
- **final void setEditableFactory(Editable.Factory factory):** Sets the `Editable.Factory`.
- **void setElegantTextHeight(boolean elegant):** Sets elegant height metrics flag.

- **void setEllipsize(TextUtils.TruncateAt where):** Enables ellipsizing of long words.
- **void setEms(int ems):** Sets exact width in ems.
- **void setEnabled(boolean enabled):** Enables/disables the view.
- **void setError(CharSequence error):** Shows an error icon and message popup.
- **void setError(CharSequence error, Drawable icon):** Shows a custom error icon and message popup.
- **void setExtractedText(ExtractedText text):** Applies extracted text to the view.
- **void setFallbackLineSpacing(boolean enabled):** Respects fallback font ascent/descent when enabled.
- **void setFilters(InputFilter[] filters):** Sets input filters for editable content.
- **void setFirstBaselineToTopHeight(int firstBaselineToTopHeight):** Adjusts top padding so first baseline is at the given distance from top.
- **void setFocusedSearchResultHighlightColor(int color):** Sets focused search result highlight color.
- **void setFocusedSearchResultIndex(int index):** Sets focused search result index.
- **void setFontFeatureSettings(String fontFeatureSettings):** Sets font feature settings.
- **boolean setFontVariationSettings(String fontVariationSettings):** Sets TrueType/OpenType variation settings.
- **void setFreezesText(boolean freezesText):** Controls saving full text on instance state.
- **void setGravity(int gravity):** Sets horizontal text alignment and vertical gravity.
- **void setHeight(int pixels):** Sets exact height in pixels.
- **void setHighlightColor(int color):** Sets selection highlight color.
- **void setHighlights(Highlights highlights):** Sets highlights.
- **final void setHint(CharSequence hint):** Sets hint text.
- **final void setHint(int resid):** Sets hint text from a resource.
- **final void setHintTextColor(ColorStateList colors):** Sets hint text colors.
- **final void setHintTextColor(int color):** Sets hint text color for all states.
- **void setHorizontallyScrolling(boolean whether):** Allows text to exceed view width.
- **void setHyphenationFrequency(int hyphenationFrequency):** Sets hyphenation frequency.
- **void setImeActionLabel(CharSequence label, int actionId):** Sets custom IME action label and ID.
- **void setImeHintLocales(LocaleList hintLocales):** Sets IME hint locales.
- **void setImeOptions(int imeOptions):** Sets editor type/IME options.
- **void setIncludeFontPadding(boolean includepad):** Toggles extra ascent/descent font padding.
- **void setInputExtras(int xmlResId):** Sets extra input data bundle from XML.

- **void setInputType(int type):** Sets the input content type.
- **void setJustificationMode(int justificationMode):** Sets text justification mode.
- **void setKeyListener(KeyListener input):** Sets the KeyListener.
- **void setLastBaselineToBottomHeight(int lastBaselineToBottomHeight):** Adjusts bottom padding so last baseline is at the given distance from bottom.
- **void setLetterSpacing(float letterSpacing):** Sets letter spacing (em).
- **void setLineBreakStyle(int lineBreakStyle):** Sets line-break style.
- **void setLineBreakWordStyle(int lineBreakWordStyle):** Sets line-break word style.
- **void setLineHeight(int unit, float lineHeight):** Sets explicit line height with unit.
- **void setLineHeight(int lineHeight):** Sets explicit line height (px).
- **void setLineSpacing(float add, float mult):** Sets line spacing extra and multiplier.
- **void setLines(int lines):** Sets exact line count.
- **final void setLinkTextColor(ColorStateList colors):** Sets link text colors.
- **final void setLinkTextColor(int color):** Sets link text color.
- **final void setLinksClickable(boolean whether):** Controls auto-setting of LinkMovementMethod.
- **void setLocalePreferredLineHeightForMinimumUsed(boolean flag):** Uses locale-preferred line height for minimum line height.
- **void setMarqueeRepeatLimit(int marqueeLimit):** Sets marquee repeat count.
- **void setMaxEms(int maxEms):** Sets maximum width in ems.
- **void setMaxHeight(int maxPixels):** Sets maximum height in px.
- **void setMaxLines(int maxLines):** Sets maximum number of lines.
- **void setMaxWidth(int maxPixels):** Sets maximum width in px.
- **void setMinEms(int minEms):** Sets minimum width in ems.
- **void setMinHeight(int minPixels):** Sets minimum height in px.
- **void setMinLines(int minLines):** Sets minimum number of lines.
- **void setMinWidth(int minPixels):** Sets minimum width in px.
- **void setMinimumFontMetrics(Paint.FontMetrics minimumFontMetrics):** Sets minimum font metrics for line spacing.
- **final void setMovementMethod(MovementMethod movement):** Sets the MovementMethod.
- **void setOnEditorActionListener(Text View.OnEditorActionListener l):** Sets a listener for editor actions.
- **void setPadding(int left, int top, int right, int bottom):** Sets absolute padding.
- **void setPaddingRelative(int start, int top, int end, int bottom):** Sets relative padding.
- **void setPaintFlags(int flags):** Sets paint flags and reflows text if changed.
- **void setPrivateImeOptions(String type):** Sets private IME options string.



- **void setRawInputType(int type)**: Directly sets the content type integer.
- **void setScroller(Scroller s)**: Sets the `Scroller` for scrolling animation.
- **void setSearchResultHighlightColor(int color)**: Sets search result highlight color.
- **void setSearchResultHighlights(int... ranges)**: Sets search result ranges (flattened).
- **void setSelectedOnFocus(boolean selectAllOnFocus)**: Selects all text when gaining focus.
- **void setSelected(boolean selected)**: Changes selection state of this view.
- **void setShadowLayer(float radius, float dx, float dy, int color)**: Applies a text shadow.
- **void setShiftDrawingOffsetForStartOverhang(boolean shiftDrawingOffsetForStartOverhang)**: Enables shifting x offset to show start overhang.
- **final void setShowSoftInputOnFocus(boolean show)**: Controls soft input visibility on focus.
- **void setSingleLine(boolean singleLine)**: Toggles single-line properties.
- **void setSingleLine()**: Sets single-line properties.
- **final void setSpannableFactory(Spannable.Factory factory)**: Sets the `Spannable.Factory`.
- **final void setText(int resid)**: Sets text from a string resource.
- **final void setText(CharSequence text)**: Sets the displayed text.
- **void setText(CharSequence text, TextView.BufferType type)**: Sets text and buffer type.
- **final void setText(int resid, TextView.BufferType type)**: Sets text from a resource with buffer type.
- **final void setText(char[] text, int start, int len)**: Displays a slice of a char array.
- **void setTextAppearance(Context context, int resId)**: *Deprecated API 23* — use `setTextAppearance(int)`.
- **void setTextAppearance(int resId)**: Sets the text appearance from a style resource.
- **void setTextClassifier(TextClassifier textClassifier)**: Sets the `TextClassifier`.
- **void setTextColor(int color)**: Sets text color for all states.
- **void setTextColor(ColorStateList colors)**: Sets text colors.
- **void setTextCursorDrawable(Drawable textCursorDrawable)**: Sets cursor drawable.
- **void setTextCursorDrawable(int textCursorDrawable)**: Sets cursor drawable by resource.
- **void setTextIsSelectable(boolean selectable)**: Toggles text selectability.
- **final void setTextKeepState(CharSequence text)**: Sets text while retaining cursor position.
- **final void setTextKeepState(CharSequence text, TextView.BufferType type)**: Sets text and buffer type while retaining cursor position.
- **void setTextLocale(Locale locale)**: Sets text `Locale` to a single-locale list.
- **void setTextLocales(LocaleList locales)**: Sets text `LocaleList`.

- **void setTextMetricsParams(PrecomputedText.Params params):** Applies text layout parameters.
- **void setTextScaleX(float size):** Sets horizontal text scale.
- **void setTextSelectHandle(int textSelectHandle):** Sets selection handle drawable (resource).
- **void setTextSelectHandle(Drawable textSelectHandle):** Sets selection handle drawable.
- **void setTextSelectHandleLeft(int textSelectHandleLeft):** Sets left selection handle (resource).
- **void setTextSelectHandleLeft(Drawable textSelectHandleLeft):** Sets left selection handle.
- **void setTextSelectHandleRight(Drawable textSelectHandleRight):** Sets right selection handle.
- **void setTextSelectHandleRight(int textSelectHandleRight):** Sets right selection handle (resource).
- **void setTextSize(int unit, float size):** Sets text size with unit.
- **void setTextSize(float size):** Sets text size in scaled pixels.
- **final void setTransformationMethod(TransformationMethod method):** Sets text transformation method.
- **void setTypeface(Typeface tf):** Sets the typeface.
- **void setTypeface(Typeface tf, int style):** Sets typeface and style (enables fake bold/italic if needed).
- **void setUseBoundsForWidth(boolean useBoundsForWidth):** Uses bounding-box width for line breaking/drawing.
- **void setWidth(int pixels):** Sets exact width in pixels.
- **boolean showContextMenu():** Shows the context menu.
- **boolean showContextMenu(float x, float y):** Shows the context menu anchored at the given coordinates.

- **Protected methods**

- **int computeHorizontalScrollRange():** Computes the horizontal range represented by the horizontal scrollbar.
- **int computeVerticalScrollExtent():** Computes the vertical extent of the scrollbar thumb within the total vertical range.
- **int computeVerticalScrollRange():** Computes the vertical range represented by the vertical scrollbar.
- **void drawableStateChanged():** Called when the view state changes in a way that affects any displayed drawables.
- **int getBottomPaddingOffset():** Returns the amount by which to extend the bottom fading region.
- **boolean getDefaultEditable():** Indicates whether the view has a default `KeyListener` even if not requested via XML.
- **MovementMethod getDefaultMovementMethod():** Returns the default `MovementMethod` for this view.
- **float getLeftFadingEdgeStrength():** Returns the intensity of the left faded edge.

- **int getLeftPaddingOffset()**: Returns the amount to extend the left fading region.
- **float getRightFadingEdgeStrength()**: Returns the intensity of the right faded edge.
- **int getRightPaddingOffset()**: Returns the amount to extend the right fading region.
- **int getTopPaddingOffset()**: Returns the amount to extend the top fading region.
- **boolean isPaddingOffsetRequired()**: True if the view draws inside padding and supports fading edge padding offsets.
- **void onAttachedToWindow()**: Called when the view is attached to a window.
- **void onConfigurationChanged(Configuration newConfig)**: Called when the device/app configuration changes.
- **void onCreateContextMenu(ContextMenu menu)**: Allows the view to add items to its context menu.
- **int[] onCreateDrawableState(int extraSpace)**: Generates a new drawable state array for this view.
- **void onDraw(Canvas canvas)**: Performs custom drawing for this view.
- **void onFocusChanged(boolean focused, int direction, Rect previouslyFocusedRect)**: Called when the view's focus state changes.
- **void onLayout(boolean changed, int left, int top, int right, int bottom)**: Assigns size and position to child views.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its content to determine width and height.
- **void onScrollChanged(int horiz, int vert, int oldHoriz, int oldVert)**: Called when the view scrolls its own contents.
- **void onSelectionChanged(int selStart, int selEnd)**: Called when the text selection changes.
- **void onTextChanged(CharSequence text, int start, int lengthBefore, int lengthAfter)**: Called when the text content changes.
- **void onVisibilityChanged(View changedView, int visibility)**: Called when visibility of this view or an ancestor changes.
- **boolean setFrame(int l, int t, int r, int b)**: Sets the view's frame; returns true if it changed.
- **boolean verifyDrawable(Drawable who)**: Returns true for any drawable that this view is displaying.

- **Constants**

- **int AUTO\_SIZE\_TEXT\_TYPE\_NONE**: The TextView does not auto-size text (default).
- **int AUTO\_SIZE\_TEXT\_TYPE\_UNIFORM**: The TextView scales text size both horizontally and vertically to fit within the container.
- **int FOCUSED\_SEARCH\_RESULT\_INDEX\_NONE**: A special index used for `setFocusedSearchResultIndex(int)` and `getFocusedSearchResultIndex()` indicating there is no focused search result.

## 1.30 EditText

- **Hierarchy**

java.lang.Object → android.view.View → android.widget.TextView →  
android.widget.EditText

- **Include**

```
0  android.widget.EditText
```

- **Constructors**

```
0  EditText(Context context)
1  EditText(Context context, AttributeSet attrs)
2  EditText(Context context, AttributeSet attrs, int
    ↪ defStyleAttr)
3  EditText(Context context, AttributeSet attrs, int
    ↪ defStyleAttr, int defStyleAttrRes)
```

- **Public methods**

- **void extendSelection(int index)**: Convenience method for `Selection.extendSelection`.
- **CharSequence getAccessibilityClassName()**: Returns the class name of this object to be used for accessibility purposes.
- **boolean getFreezesText()**: Returns whether this `TextView` includes its entire text contents in frozen icicles.
- **Editable getText()**: Returns the text that the `TextView` is displaying.
- **boolean isStyleShortcutEnabled()**: Returns true if style shortcuts are enabled, otherwise false.
- **boolean onKeyDown(int keyCode, KeyEvent event)**: Called on the focused view when a key shortcut event is not handled.
- **boolean onTextContextMenu(int id)**: Called when a context menu option for the text view is selected.
- **void selectAll()**: Convenience method for `Selection.selectAll`.
- **void setEllipsize(TextUtils.TruncateAt ellipsis)**: Specifies how overflowing text should be ellipsized instead of wrapped.
- **void setSelection(int index)**: Convenience method for `Selection.setSelection(Spannable, int)`.
- **void setSelection(int start, int stop)**: Convenience method for `Selection.setSelection(Spannable, int, int)`.
- **void setStyleShortcutsEnabled(boolean enabled)**: Enables style shortcuts such as `Ctrl+B` for bold.
- **void setText(CharSequence text, TextView.BufferType type)**: Sets the text to be displayed and the `TextView.BufferType`.

- **Protected methods**

- **boolean getDefaultEditable():** Subclasses override this to specify that they have a KeyListener by default even if not specifically called for in the XML options.
- **MovementMethod getDefaultMovementMethod():** Subclasses override this to specify a default movement method.

## 1.31 InputType (Interface)

- Signature

```
0 public interface InputType
```

- Include

```
0 android.text.InputType
```

- Constants

- **int TYPE\_CLASS\_DATETIME**: Class for dates and times.
- **int TYPE\_CLASS\_NUMBER**: Class for numeric text.
- **int TYPE\_CLASS\_PHONE**: Class for a phone number.
- **int TYPE\_CLASS\_TEXT**: Class for normal text.
- **int TYPE\_DATETIME\_VARIATION\_DATE**: Default variation of TYPE\_CLASS\_DATETIME: allows entering only a date.
- **int TYPE\_DATETIME\_VARIATION\_NORMAL**: Default variation of TYPE\_CLASS\_DATETIME: allows entering both a date and time.
- **int TYPE\_DATETIME\_VARIATION\_TIME**: Default variation of TYPE\_CLASS\_DATETIME: allows entering only a time.
- **int TYPE\_MASK\_CLASS**: Mask of bits that determine the overall class of text being given.
- **int TYPE\_MASK\_FLAGS**: Mask of bits that provide addition bit flags of options.
- **int TYPE\_MASK\_VARIATION**: Mask of bits that determine the variation of the base content class.
- **int TYPE\_NULL**: Special content type for when no explicit type has been specified.
- **int TYPE\_NUMBER\_FLAG\_DECIMAL**: Flag of TYPE\_CLASS\_NUMBER: the number is decimal, allowing a decimal point to provide fractional values.
- **int TYPE\_NUMBER\_FLAG\_SIGNED**: Flag of TYPE\_CLASS\_NUMBER: the number is signed, allowing a positive or negative sign at the start.
- **int TYPE\_NUMBER\_VARIATION\_NORMAL**: Default variation of TYPE\_CLASS\_NUMBER: plain normal numeric text.
- **int TYPE\_NUMBER\_VARIATION\_PASSWORD**: Variation of TYPE\_CLASS\_NUMBER: entering a numeric password.
- **int TYPE\_TEXT\_FLAG\_AUTO\_COMPLETE**: Flag for TYPE\_CLASS\_TEXT: the text editor (which means the application) is performing auto-completion of the text being entered based on its own semantics, which it will present to the user as they type.
- **int TYPE\_TEXT\_FLAG\_AUTO\_CORRECT**: Flag for TYPE\_CLASS\_TEXT: the user is entering free-form text that should have auto-correction applied to it.
- **int TYPE\_TEXT\_FLAG\_CAP\_CHARACTERS**: Flag for TYPE\_CLASS\_TEXT: capitalize all characters.

- **int TYPE\_TEXT\_FLAG\_CAP\_SENTENCES**: Flag for TYPE\_CLASS\_TEXT: capitalize the first character of each sentence.
- **int TYPE\_TEXT\_FLAG\_CAP\_WORDS**: Flag for TYPE\_CLASS\_TEXT: capitalize the first character of every word.
- **int TYPE\_TEXT\_FLAG\_ENABLE\_TEXT\_CONVERSION\_SUGGESTIONS**: Flag for TYPE\_CLASS\_TEXT: Let the IME know the text conversion suggestions are required by the application.
- **int TYPE\_TEXT\_FLAG\_IME\_MULTI\_LINE**: Flag for TYPE\_CLASS\_TEXT: the regular text view associated with this should not be multi-line, but when a fullscreen input method is providing text it should use multiple lines if it can.
- **int TYPE\_TEXT\_FLAG\_MULTI\_LINE**: Flag for TYPE\_CLASS\_TEXT: multiple lines of text can be entered into the field.
- **int TYPE\_TEXT\_FLAG\_NO\_SUGGESTIONS**: Flag for TYPE\_CLASS\_TEXT: the input method does not need to display any dictionary-based candidates.
- **int TYPE\_TEXT\_VARIATION\_EMAIL\_ADDRESS**: Variation of TYPE\_CLASS\_TEXT: entering an e-mail address.
- **int TYPE\_TEXT\_VARIATION\_EMAIL\_SUBJECT**: Variation of TYPE\_CLASS\_TEXT: entering the subject line of an e-mail.
- **int TYPE\_TEXT\_VARIATION\_FILTER**: Variation of TYPE\_CLASS\_TEXT: entering text to filter contents of a list etc.
- **int TYPE\_TEXT\_VARIATION\_LONG\_MESSAGE**: Variation of TYPE\_CLASS\_TEXT: entering the content of a long, possibly formal message such as the body of an e-mail.
- **int TYPE\_TEXT\_VARIATION\_NORMAL**: Default variation of TYPE\_CLASS\_TEXT: plain old normal text.
- **int TYPE\_TEXT\_VARIATION\_PASSWORD**: Variation of TYPE\_CLASS\_TEXT: entering a password.
- **int TYPE\_TEXT\_VARIATION\_PERSON\_NAME**: Variation of TYPE\_CLASS\_TEXT: entering the name of a person.
- **int TYPE\_TEXT\_VARIATION\_PHONETIC**: Variation of TYPE\_CLASS\_TEXT: entering text for phonetic pronunciation, such as a phonetic name field in contacts.
- **int TYPE\_TEXT\_VARIATION\_POSTAL\_ADDRESS**: Variation of TYPE\_CLASS\_TEXT: entering a postal mailing address.
- **int TYPE\_TEXT\_VARIATION\_SHORT\_MESSAGE**: Variation of TYPE\_CLASS\_TEXT: entering a short, possibly informal message such as an instant message or a text message.
- **int TYPE\_TEXT\_VARIATION\_URI**: Variation of TYPE\_CLASS\_TEXT: entering a URI.
- **int TYPE\_TEXT\_VARIATION\_VISIBLE\_PASSWORD**: Variation of TYPE\_CLASS\_TEXT: entering a password, which should be visible to the user.
- **int TYPE\_TEXT\_VARIATION\_WEB\_EDIT\_TEXT**: Variation of TYPE\_CLASS\_TEXT: entering text inside of a web form.
- **int TYPE\_TEXT\_VARIATION\_WEB\_EMAIL\_ADDRESS**: Variation of TYPE\_CLASS\_TEXT: entering e-mail address inside of a web form.
- **int TYPE\_TEXT\_VARIATION\_WEB\_PASSWORD**: Variation of TYPE\_CLASS\_TEXT: entering password inside of a web form.

## 1.32 Button

- Hierarchy

java.lang.Object → android.view.View → android.widget.TextView →  
android.widget.Button

- Include

```
0  android.widget.Button
```

- Constructors

```
0  Button(Context context)
1  Button(Context context, AttributeSet attrs)
2  Button(Context context, AttributeSet attrs, int defStyleAttr)
3  Button(Context context, AttributeSet attrs, int
    ↪  defStyleAttr, int defStyleRes)
```

- Public methods

- **CharSequence getAccessibilityClassName():** Return the class name of this object to be used for accessibility purposes.
- **PointerIcon onResolvePointerIcon(MotionEvent event, int pointerIndex):** Resolve the pointer icon that should be used for specified pointer in the motion event.



## 1.33 ImageView

- Hierarchy

java.lang.Object → android.view.View → android.widget.ImageView

- Include

```
0  android.widget.ImageView
```

- Constructors

```
0  ImageView(Context context)
1  ImageView(Context context, AttributeSet attrs)
2  ImageView(Context context, AttributeSet attrs, int
   ↪  defStyleAttr)
3  ImageView(Context context, AttributeSet attrs, int
   ↪  defStyleAttr, int defStyleAttrRes)
```

- Public methods

- **void animateTransform(Matrix matrix)**: Applies a temporary transformation matrix to the view's drawable when it is drawn.
- **final void clearColorFilter()**: Removes the image's **ColorFilter**.
- **void drawableHotspotChanged(float x, float y)**: Called whenever the view hotspot changes and needs to be propagated to drawables or child views managed by the view.
- **CharSequence getAccessibilityClassName()**: Returns the class name of this object to be used for accessibility purposes.
- **boolean getAdjustViewBounds()**: Returns true if the **ImageView** is adjusting its bounds to preserve the aspect ratio of its drawable.
- **int getBaseline()**: Returns the offset of the widget's text baseline from the widget's top boundary.
- **boolean getBaselineAlignBottom()**: Checks whether this view's baseline is considered the bottom of the view.
- **ColorFilter getColorFilter()**: Returns the active color filter for this **ImageView**.
- **boolean getCropToPadding()**: Returns whether this **ImageView** crops to its padding.
- **Drawable getDrawable()**: Gets the current drawable, or null if none has been assigned.
- **int getImageAlpha()**: Returns the alpha value applied to the drawable of this **ImageView**.
- **Matrix getImageMatrix()**: Returns the view's transformation matrix, if any.
- **BlendMode getImageTintBlendMode()**: Gets the blending mode used to apply the tint to the image drawable.
- **ColorStateList getImageTintList()**: Returns the current color tint list used for the image drawable.

- **PorterDuff.Mode getImageTintMode()**: Gets the blending mode used to apply the tint to the image drawable.
- **int getMaxHeight()**: Returns the maximum height of this view.
- **int getMaxWidth()**: Returns the maximum width of this view.
- **ImageView.ScaleType getScaleType()**: Returns the current scale type used to resize or move the image.
- **boolean hasOverlappingRendering()**: Returns whether this view has overlapping content.
- **void invalidateDrawable(Drawable dr)**: Invalidates the specified drawable.
- **boolean isOpaque()**: Indicates whether this view is opaque.
- **void jumpDrawablesToCurrentState()**: Calls `Drawable.jumpToCurrentState()` on all associated drawables.
- **int[] onCreateDrawableState(int extraSpace)**: Generates the new drawable state for this view.
- **void onRtlPropertiesChanged(int layoutDirection)**: Called when any RTL property (layout direction or text alignment) changes.
- **void onVisibilityAggregated(boolean isVisible)**: Called when the visibility of this view or one of its ancestors changes.
- **void setAdjustViewBounds(boolean adjustViewBounds)**: When true, adjusts the bounds to preserve the drawable’s aspect ratio.
- **void setAlpha(int alpha)**: *Deprecated in API 16.* Use `setImageAlpha(int)` instead.
- **void setBaseline(int baseline)**: Sets the offset of the widget’s text baseline from the widget’s top boundary.
- **void setBaselineAlignBottom(boolean aligned)**: Sets whether the baseline is considered the bottom of the view.
- **final void setColorFilter(int color, PorterDuff.Mode mode)**: Sets a tint color and mode for the image.
- **void setColorFilter(ColorFilter cf)**: Applies a custom color filter to the image.
- **final void setColorFilter(int color)**: Sets a tint color for the image.
- **void setCropToPadding(boolean cropToPadding)**: Sets whether this `ImageView` will crop its content to padding.
- **void setImageAlpha(int alpha)**: Sets the alpha transparency applied to the image.
- **void setImageBitmap(Bitmap bm)**: Sets a bitmap as the content of the `ImageView`.
- **void setImageDrawable(Drawable drawable)**: Sets a drawable as the content of the `ImageView`.
- **void setImageIcon(Icon icon)**: Sets an icon as the content of the `ImageView`.
- **void setImageLevel(int level)**: Sets the level for a `LevelListDrawable`.
- **void setImageMatrix(Matrix matrix)**: Applies a transformation matrix to the drawable.
- **void setImageResource(int resId)**: Sets a drawable resource as the content of the `ImageView`.

- **void setImageState(int[] state, boolean merge)**: Sets the drawable state for a `StateListDrawable`.
  - **void setImageTintBlendMode(BlendMode blendMode)**: Sets the blending mode for applying the tint.
  - **void setImageTintList(ColorStateList tint)**: Applies a tint list to the image drawable.
  - **void setImageTintMode(PorterDuff.Mode tintMode)**: Sets the blending mode for applying the tint.
  - **void setImageURI(Uri uri)**: Sets the content of this `ImageView` to the image located at the specified URI.
  - **void setMaxHeight(int maxHeight)**: Sets a maximum height for the view.
  - **void setMaxWidth(int maxWidth)**: Sets a maximum width for the view.
  - **void setScaleType(ImageView.ScaleType scaleType)**: Defines how the image should be resized or moved to fit the view bounds.
  - **void setSelected(boolean selected)**: Changes the selection state of this view.
  - **void setVisibility(int visibility)**: Sets the visibility state of this view.
- **Protected methods**
    - **void drawableStateChanged()**: Called whenever the state of the view changes in a way that affects the state of its drawables.
    - **void onAttachedToWindow()**: Called when the view is attached to a window.
    - **void onDetachedFromWindow()**: Called when the view is detached from a window.
    - **void onDraw(Canvas canvas)**: Implement this method to perform custom drawing for the view.
    - **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its content to determine the measured width and height.
    - **boolean setFrame(int l, int t, int r, int b)**: Assigns size and position to the view within its parent layout.
    - **boolean verifyDrawable(Drawable dr)**: Returns true if the view is displaying the given drawable; subclasses should override when managing their own drawables.

### 1.34 `ImageView.ScaleType` (enum)

- **Enum values**
  - **`ImageView.ScaleType CENTER`**: Center the image in the view, but perform no scaling.
  - **`ImageView.ScaleType CENTER_CROP`**: Scale the image uniformly (maintain the image's aspect ratio) so that both dimensions (width and height) of the image will be equal to or larger than the corresponding dimension of the view (minus padding).
  - **`ImageView.ScaleType CENTER_INSIDE`**: Scale the image uniformly (maintain the image's aspect ratio) so that both dimensions (width and height) of the image will be equal to or less than the corresponding dimension of the view (minus padding).
  - **`ImageView.ScaleType FIT_CENTER`**: Scale the image using `Matrix.ScaleToFit.CENTER`.
  - **`ImageView.ScaleType FIT_END`**: Scale the image using `Matrix.ScaleToFit.END`.
  - **`ImageView.ScaleType FIT_START`**: Scale the image using `Matrix.ScaleToFit.START`.
  - **`ImageView.ScaleType FIT_XY`**: Scale the image using `Matrix.ScaleToFit.FILL`.
  - **`ImageView.ScaleType MATRIX`**: Scale using the image matrix when drawing.
- **Public methods**
  - **`static ImageView.ScaleType valueOf(String name)`**:
  - **`static final ScaleType[] values()`**:

## 1.35 ImageButton

- **Hierarchy**

java.lang.Object → android.view.View → android.widget.ImageView →  
android.widget.ImageButton

- **Include**

```
0  android.widget.ImageButton
```

- **Constructors**

```
0  ImageButton(Context context)
1  ImageButton(Context context, AttributeSet attrs)
2  ImageButton(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  ImageButton(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleAttr)
```

- **Public methods**

- **CharSequence getAccessibilityClassName()**: Return the class name of this object to be used for accessibility purposes.
- **PointerIcon onResolvePointerIcon(MotionEvent event, int pointerIndex)**: Resolve the pointer icon that should be used for specified pointer in the motion event.

- **Protected methods**

- **boolean onSetAlpha(int alpha)**: Invoked if there is a Transform that involves alpha.

## 1.36 CompoundButton

- **Hierarchy**

java.lang.Object → android.view.View → android.widget.TextView →  
android.widget.Button → android.widget.CompoundButton

- **Include**

```
0  android.widget.CompoundButton
```

- **Constructors**

```
0  CompoundButton(Context context)
1  CompoundButton(Context context, AttributeSet attrs)
2  CompoundButton(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  CompoundButton(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleRes)
```

- **Public methods**

- **void autofill(AutofillValue value)**: Automatically fills the content of this view with the given autofill value.
- **void drawableHotspotChanged(float x, float y)**: Called when the view hotspot changes and must be propagated to drawables or child views.
- **CharSequence getAccessibilityClassName()**: Returns the class name of this object for accessibility purposes.
- **int getAutofillType()**: Describes the autofill type of this view, allowing an AutofillService to create an appropriate AutofillValue.
- **AutofillValue getAutofillValue()**: Returns the current text of this TextView for autofill purposes.
- **Drawable getButtonDrawable()**: Returns the button drawable associated with this compound button.
- **BlendMode getButtonTintBlendMode()**: Returns the blending mode used to apply the tint to the button drawable.
- **ColorStateList getButtonTintList()**: Returns the tint list applied to the button drawable.
- **PorterDuff.Mode getButtonTintMode()**: Returns the blending mode used to apply the tint to the button drawable.
- **int getCompoundPaddingLeft()**: Returns the left padding of the view, including space for the left drawable if present.
- **int getCompoundPaddingRight()**: Returns the right padding of the view, including space for the right drawable if present.
- **boolean isChecked()**: Returns the checked state of this button.
- **void jumpDrawablesToCurrentState()**: Calls `Drawable.jumpToCurrentState()` on all drawable objects associated with this view.
- **void onRestoreInstanceState(Parcelable state)**: Restores the internal state of the view from a previously saved state.

- **Parcelable onSaveInstanceState()**: Saves the internal state of the view for later restoration.
- **boolean performClick()**: Calls this view's **OnClickListener**, if one is defined.
- **void setButtonDrawable(int resId)**: Sets a drawable as the compound button image using its resource identifier.
- **void setButtonDrawable(Drawable drawable)**: Sets a drawable as the compound button image.
- **void setButtonIcon(Icon icon)**: Sets the button of this compound button to the specified icon.
- **void setButtonTintBlendMode(BlendMode tintMode)**: Sets the blending mode used to apply the tint specified by **setButtonTintList()**.
- **void setButtonTintList(ColorStateList tint)**: Applies a color tint to the button drawable.
- **void setButtonTintMode(PorterDuff.Mode tintMode)**: Specifies the blending mode used to apply the tint specified by **setButtonTintList()**.
- **void setChecked(boolean checked)**: Changes the checked state of this button.
- **void setOnCheckedChangeListener(CompoundButton.OnCheckedChangeListener listener)**: Registers a callback to be invoked when the checked state changes.
- **void setStateDescription(CharSequence stateDescription)**: Called when the view or subclass sets the state description for accessibility.
- **void toggle()**: Toggles the checked state of the button to the opposite of its current state.

- **Protected methods**

- **void drawableStateChanged()**: Called whenever the state of the view changes in a way that affects the state of its drawables.
- **int[] onCreateDrawableState(int extraSpace)**: Generates and returns the new drawable state array for this view, allocating extra space if needed.
- **void onDraw(Canvas canvas)**: Implement this method to perform custom drawing for the view.
- **boolean verifyDrawable(Drawable who)**: Returns true if the specified drawable is being displayed by this view; subclasses should override when managing their own drawables.

## 1.37 CheckBox

- **Hierarchy**

java.lang.Object → android.view.View → android.widget.TextView →  
android.widget.Button → android.widget.CompoundButton →  
android.widget.CheckBox

- **Include**

```
0  android.widget.CheckBox
```

- **Constructors**

```
0  CheckBox(Context context)
1  CheckBox(Context context, AttributeSet attrs)
2  CheckBox(Context context, AttributeSet attrs, int
   ↪  defStyleAttr)
3  CheckBox(Context context, AttributeSet attrs, int
   ↪  defStyleAttr, int defStyleAttrRes)
```

- **Public methods**

- **CharSequence getAccessibilityClassName()**: Return the class name of this object to be used for accessibility purposes.



## 1.38 RadioGroup

- Hierarchy

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.LinearLayout → android.widget.RadioGroup

- Include

```
0  android.widget.RadioGroup
```

- Constructors

```
0  RadioGroup(Context context)
1  RadioGroup(Context context, AttributeSet attrs)
```

- Public methods

- **void addView(View child, int index, ViewGroup.LayoutParams params):** Adds a child view with the specified layout parameters.
- **void autofill(AutofillValue value):** Automatically fills the content of this view with the value.
- **void check(int id):** Sets the selection to the radio button whose identifier is passed in parameter.
- **void clearCheck():** Clears the selection.
- **RadioGroup.LayoutParams generateLayoutParams(AttributeSet attrs):** Returns a new set of layout parameters based on the supplied attributes set.
- **CharSequence getAccessibilityClassName():** Return the class name of this object to be used for accessibility purposes.
- **int getAutofillType():** Describes the autofill type of this view, so an AutofillService can create the proper AutofillValue when autofilling the view.
- **AutofillValue getAutofillValue():** Gets the View's current autofill value.
- **int getCheckedRadioButtonId():** Returns the identifier of the selected radio button in this group.
- **void onInitializeAccessibilityNodeInfo(AccessibilityNodeInfo info):** Initializes an AccessibilityNodeInfo with information about this view.
- **void setOnCheckedChangeListener(RadioGroup.OnCheckedChangeListener listener):** Register a callback to be invoked when the checked radio button changes in this group.
- **void setOnHierarchyChangeListener(ViewGroup.OnHierarchyChangeListener listener):** Register a callback to be invoked when a child is added to or removed from this view.

- Protected methods

- **boolean checkLayoutParams(ViewGroup.LayoutParams p):**
- **LinearLayout.LayoutParams generateDefaultLayoutParams():** Returns a set of layout parameters with a width of ViewGroup.LayoutParams.MATCH\_PARENT and a height of ViewGroup.LayoutParams.WRAP\_CONTENT when the layout's orientation is VERTICAL.
- **void onFinishInflate():** Finalize inflating a view from XML.

## 1.39 RadioGroup.LayoutParams

- **Hierarchy:**

```
java.lang.Object → android.view.ViewGroup.LayoutParams →  
    android.view.ViewGroup.MarginLayoutParams →  
        android.widget.LinearLayout.LayoutParams →  
            android.widget.RadioGroup.LayoutParams
```

- **Include**

```
0  android.widget.RadioGroup.LayoutParams
```

- **constructors**

```
0  LayoutParams(Context c, AttributeSet attrs)  
1  LayoutParams(ViewGroup.LayoutParams p)  
2  LayoutParams(ViewGroup.MarginLayoutParams source)  
3  LayoutParams(int w, int h)  
4  LayoutParams(int w, int h, float initWeight)
```

- **Protected methods**

- **void setBaseAttributes(TypedArray a, int widthAttr, int heightAttr):**  
Fixes the child's width to ViewGroup.LayoutParams.WRAP\_CONTENT and the child's height to ViewGroup.LayoutParams.WRAP\_CONTENT when not specified in the XML file.

## 1.40 RadioButton

- **Hierarchy**

```
java.lang.Object → android.view.View → android.widget.TextView →  
    android.widget.Button → android.widget.CompoundButton →  
        android.widget.RadioButton
```

- **Include**

```
0  android.widget.RadioButton
```

- **Constructors**

```
0  Public constructors  
1  RadioButton(Context context)  
2  RadioButton(Context context, AttributeSet attrs)  
3  RadioButton(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr)  
4  RadioButton(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr, int defStyleRes)
```

- **Public methods**

- **CharSequence getAccessibilityClassName()**: Return the class name of this object to be used for accessibility purposes.
- **void onInitializeAccessibilityNodeInfo(AccessibilityNodeInfo info)**: Initializes an AccessibilityNodeInfo with information about this view.
- **void toggle()**: Change the checked state of the view to the inverse of its current state

If the radio button is already checked, this method will not toggle the radio button.

## 1.41 AbsSpinner

- Hierarchy

```
java.lang.Object → android.view.View → android.view.ViewGroup →  
    android.widget.AdapterView<android.widget.SpinnerAdapter> →  
        android.widget.AbsSpinner
```

- Include

```
0  android.widget.AbsSpinner
```

- Constructors

```
0  AbsSpinner(Context context)  
1  AbsSpinner(Context context, AttributeSet attrs)  
2  AbsSpinner(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr)  
3  AbsSpinner(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr, int defStyleRes)
```

- Public methods

- **void autofill(AutofillValue value)**: Automatically fills the content of this view with the value.
- **CharSequence getAccessibilityClassName()**: Return the class name of this object to be used for accessibility purposes.
- **SpinnerAdapter getAdapter()**: Returns the adapter currently associated with this widget.
- **int getAutofillType()**: Describes the autofill type of this view, so an AutofillService can create the proper AutofillValue when autofilling the view.
- **AutofillValue getAutofillValue()**: Gets the View's current autofill value.
- **int getCount()**:
- **View getSelectedView()**:
- **void onRestoreInstanceState(Parcelable state)**: Hook allowing a view to re-apply a representation of its internal state that had previously been generated by onSaveInstanceState().
- **Parcelable onSaveInstanceState()**: Hook allowing a view to generate a representation of its internal state that can later be used to create a new instance with that same state.
- **int pointToPosition(int x, int y)**: Maps a point to a position in the list.
- **void requestLayout()**: Override to prevent spamming ourselves with layout requests as we place views
- **void setAdapter(SpinnerAdapter adapter)**: The Adapter is used to provide the data which backs this Spinner.
- **void setSelection(int position, boolean animate)**: Jump directly to a specific item in the adapter data.

- **void setSelection(int position)**: Sets the currently selected item.
- **Protected methods**
  - **void dispatchRestoreInstanceState(SparseArray<Parcelable> container)**: Override to prevent thawing of any views created by the adapter.
  - **ViewGroup.LayoutParams generateDefaultLayoutParams()**: Returns a set of default layout parameters.
  - **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measure the view and its content to determine the measured width and the measured height.

## 1.42 Spinner

- Hierarchy

```
java.lang.Object → android.view.View → android.view.ViewGroup →  
    android.widget.AdapterView<android.widget.SpinnerAdapter> →  
        android.widget.AbsSpinner → android.widget.Spinner
```

- Include

```
0  android.widget.Spinner
```

- Constructors

```
0  Spinner(Context context)  
1  Spinner(Context context, AttributeSet attrs)  
2  Spinner(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr)  
3  Spinner(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr, int mode)  
4  Spinner(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr, int defStyleAttrRes, int mode)  
5  Spinner(Context context, AttributeSet attrs, int  
    ↪ defStyleAttr, int defStyleAttrRes, int mode, Resources.Theme  
    ↪ popupTheme)  
6  Spinner(Context context, int mode)
```

- Public methods

- **CharSequence** **getAccessibilityClassName()**: Returns the class name of this object to be used for accessibility purposes.
- **int** **getBaseline()**: Returns the offset of the widget's text baseline from the widget's top boundary.
- **int** **getDropDownHorizontalOffset()**: Returns the configured horizontal offset in pixels for the spinner's popup window of choices.
- **int** **getDropDownVerticalOffset()**: Returns the configured vertical offset in pixels for the spinner's popup window of choices.
- **int** **getDropDownWidth()**: Returns the configured width of the spinner's popup window of choices in pixels.
- **int** **getGravity()**: Describes how the selected item view is positioned within the spinner.
- **Drawable** **getPopupBackground()**: Returns the background drawable for the spinner's popup window of choices.
- **Context** **getPopupContext()**: Returns the context used to inflate the spinner's popup window.
- **CharSequence** **getPrompt()**: Returns the prompt text displayed when the spinner dialog is shown.
- **void** **onClick(DialogInterface dialog, int which)**: Invoked when a button in the dialog is clicked.

- **PointerIcon onResolvePointerIcon(MotionEvent event, int pointerIndex)**: Resolves the pointer icon that should be used for the specified pointer in the motion event.
- **void onRestoreInstanceState(Parcelable state)**: Restores the internal state of the spinner from a previously saved state.
- **Parcelable onSaveInstanceState()**: Saves the spinner’s current state for later restoration.
- **boolean onTouchEvent(MotionEvent event)**: Handles touch input events for the spinner.
- **boolean performClick()**: Calls this spinner’s `OnClickListener`, if one is defined.
- **void setAdapter(SpinnerAdapter adapter)**: Sets the `SpinnerAdapter` that provides the data backing this spinner.
- **void setDropDownHorizontalOffset(int pixels)**: Sets a horizontal offset in pixels for the spinner’s popup window of choices.
- **void setDropDownVerticalOffset(int pixels)**: Sets a vertical offset in pixels for the spinner’s popup window of choices.
- **void setDropDownWidth(int pixels)**: Sets the width of the spinner’s popup window of choices in pixels.
- **void setEnabled(boolean enabled)**: Sets the enabled state of this spinner.
- **void setGravity(int gravity)**: Defines how the selected item view is positioned within the spinner.
- **void setOnItemClickListener(AdapterView.OnItemClickListener l)**: No-op; spinners do not support item click events.
- **void setPopupBackgroundDrawable(Drawable background)**: Sets the background drawable for the spinner’s popup window of choices.
- **void setPopupBackgroundResource(int resId)**: Sets the background resource for the spinner’s popup window of choices.
- **void setPrompt(CharSequence prompt)**: Sets the prompt text to display when the dialog is shown.
- **void setPromptId(int promptId)**: Sets the prompt text to display when the dialog is shown using a resource ID.

- **Protected methods**

- **void onDetachedFromWindow()**: This is called when the view is detached from a window.
- **void onLayout(boolean changed, int l, int t, int r, int b)**: Called from layout when this view should assign a size and position to each of its children.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measure the view and its content to determine the measured width and the measured height.

- **Constants**

- **int MODE\_DIALOG**: Use a dialog window for selecting spinner options.
- **int MODE\_DROPDOWN**: Use a dropdown anchored to the Spinner for selecting spinner options.

## 1.43 Progressbar

- Hierarchy

java.lang.Object → android.view.View → android.widget.ProgressBar

- Include

```
0  android.widget.ProgressBar
```

- Constructors

```
0  ProgressBar(Context context)
1  ProgressBar(Context context, AttributeSet attrs)
2  ProgressBar(Context context, AttributeSet attrs, int
   ↳ defStyleAttr)
3  ProgressBar(Context context, AttributeSet attrs, int
   ↳ defStyleAttr, int defStyleRes)
```

- Public methods

- **void drawableHotspotChanged(float x, float y)**: Called whenever the view hotspot changes and must be propagated to drawables or child views.
- **CharSequence getAccessibilityClassName()**: Returns the class name of this object for accessibility purposes.
- **Drawable getCurrentDrawable()**: Returns the drawable currently used to draw the progress bar.
- **Drawable getIndeterminateDrawable()**: Returns the drawable used to draw the progress bar in indeterminate mode.
- **BlendMode getIndeterminateTintBlendMode()**: Returns the blending mode used to apply the tint to the indeterminate drawable, if specified.
- **ColorStateList getIndeterminateTintList()**: Returns the color tint list used for the indeterminate drawable.
- **PorterDuff.Mode getIndeterminateTintMode()**: Returns the blending mode used to apply the tint to the indeterminate drawable.
- **Interpolator getInterpolator()**: Gets the acceleration curve type for the indeterminate animation.
- **int getMax()**: Returns the upper limit of this progress bar's range.
- **int getMaxHeight()**: Returns the maximum height of the progress bar, in pixels.
- **int getMaxWidth()**: Returns the maximum width of the progress bar, in pixels.
- **int getMin()**: Returns the lower limit of this progress bar's range.
- **int getMinHeight()**: Returns the minimum height of the progress bar, in pixels.
- **int getMinWidth()**: Returns the minimum width of the progress bar, in pixels.
- **int getProgress()**: Returns the current progress level of the progress bar.
- **BlendMode getProgressBackgroundTintBlendMode()**: Returns the blending mode used to apply the tint to the progress background, if specified.



- **ColorStateList** **getProgressBackgroundTintList()**: Returns the tint list applied to the progress background, if specified.
- **PorterDuff.Mode** **getProgressBackgroundTintMode()**: Returns the blending mode used to apply the tint to the progress background.
- **Drawable** **getProgressDrawable()**: Returns the drawable used to draw the progress bar in progress mode.
- **BlendMode** **getProgressTintBlendMode()**: Returns the blending mode used to apply the tint to the progress drawable, if specified.
- **ColorStateList** **getProgressTintList()**: Returns the color tint list applied to the progress drawable.
- **PorterDuff.Mode** **getProgressTintMode()**: Returns the blending mode used to apply the tint to the progress drawable.
- **int** **getSecondaryProgress()**: Returns the current level of secondary progress.
- **BlendMode** **getSecondaryProgressTintBlendMode()**: Returns the blending mode used to apply the tint to the secondary progress drawable.
- **ColorStateList** **getSecondaryProgressTintList()**: Returns the color tint list applied to the secondary progress drawable.
- **PorterDuff.Mode** **getSecondaryProgressTintMode()**: Returns the blending mode used to apply the tint to the secondary progress drawable.
- **final void** **incrementProgressBy(int diff)**: Increases the primary progress by the specified amount.
- **final void** **incrementSecondaryProgressBy(int diff)**: Increases the secondary progress by the specified amount.
- **void** **invalidateDrawable(Drawable dr)**: Invalidates the specified drawable, forcing a redraw.
- **boolean** **isAnimating()**: Returns whether the progress bar is currently animating.
- **boolean** **isIndeterminate()**: Indicates whether this progress bar is in indeterminate mode.
- **void** **jumpDrawablesToCurrentState()**: Calls `Drawable.jumpToCurrentState()` on all associated drawables.
- **void** **onRestoreInstanceState(Parcelable state)**: Restores the internal state of the progress bar from a previously saved state.
- **Parcelable** **onSaveInstanceState()**: Saves the internal state of the progress bar for later restoration.
- **void** **onVisibilityAggregated(boolean isVisible)**: Called when the visibility of this view or its ancestors changes.
- **void** **postInvalidate()**: Schedules a redraw for the next event loop cycle.
- **void** **setIndeterminate(boolean indeterminate)**: Changes whether the progress bar is in indeterminate mode.
- **void** **setIndeterminateDrawable(Drawable d)**: Defines the drawable used to draw the progress bar in indeterminate mode.
- **void** **setIndeterminateDrawableTiled(Drawable d)**: Defines a tileable drawable used to draw the indeterminate progress bar.
- **void** **setIndeterminateTintBlendMode(BlendMode blendMode)**: Specifies the blending mode for applying the indeterminate tint.

- **void setIndeterminateTintList(ColorStateList tint):** Applies a color tint to the indeterminate drawable.
- **void setIndeterminateTintMode(PorterDuff.Mode tintMode):** Specifies the blending mode for applying the indeterminate tint.
- **void setInterpolator(Interpolator interpolator):** Sets the acceleration curve for the indeterminate animation.
- **void setInterpolator(Context context, int resID):** Sets the interpolator resource for the indeterminate animation.
- **void setMax(int max):** Sets the upper range of the progress bar.
- **void setMaxHeight(int maxHeight):** Sets the maximum height the progress bar can have.
- **void setMaxWidth(int maxWidth):** Sets the maximum width the progress bar can have.
- **void setMin(int min):** Sets the lower range of the progress bar.
- **void setMinHeight(int minHeight):** Sets the minimum height the progress bar can have.
- **void setMinWidth(int minWidth):** Sets the minimum width the progress bar can have.
- **void setProgress(int progress):** Sets the current progress value.
- **void setProgress(int progress, boolean animate):** Sets the current progress value, optionally animating the transition.
- **void setProgressBackgroundTintBlendMode(BlendMode blendMode):** Specifies the blending mode for the progress background tint.
- **void setProgressBackgroundTintList(ColorStateList tint):** Applies a tint to the progress background.
- **void setProgressBackgroundTintMode(PorterDuff.Mode tintMode):** Specifies the blending mode for the progress background tint.
- **void setProgressDrawable(Drawable d):** Defines the drawable used to draw the progress bar in progress mode.
- **void setProgressDrawableTiled(Drawable d):** Defines a tileable drawable for the progress bar in progress mode.
- **void setProgressTintBlendMode(BlendMode blendMode):** Specifies the blending mode for the progress indicator tint.
- **void setProgressTintList(ColorStateList tint):** Applies a tint to the progress indicator.
- **void setProgressTintMode(PorterDuff.Mode tintMode):** Specifies the blending mode for the progress indicator tint.
- **void setSecondaryProgress(int secondaryProgress):** Sets the current secondary progress value.
- **void setSecondaryProgressTintBlendMode(BlendMode blendMode):** Specifies the blending mode for the secondary progress tint.
- **void setSecondaryProgressTintList(ColorStateList tint):** Applies a tint to the secondary progress indicator.
- **void setSecondaryProgressTintMode(PorterDuff.Mode tintMode):** Specifies the blending mode for the secondary progress tint.
- **void setStateDescription(CharSequence stateDescription):** Called when an instance or subclass sets the state description.

- **Protected methods**
  - **void drawableStateChanged():** Called whenever the state of the view changes in a way that affects the state of its drawables.
  - **void onAttachedToWindow():** Called when the view is attached to a window.
  - **void onDetachedFromWindow():** Called when the view is detached from a window.
  - **void onDraw(Canvas canvas):** Implement this method to perform custom drawing for the view.
  - **void onMeasure(int widthMeasureSpec, int heightMeasureSpec):** Measures the view and its content to determine the measured width and height.
  - **void onSizeChanged(int w, int h, int oldw, int oldh):** Called during layout when the size of this view has changed.
  - **boolean verifyDrawable(Drawable who):** Returns true if the specified drawable is being displayed by this view; subclasses should override this when managing their own drawables.

## 1.44 AbsSeekBar

- Hierarchy

java.lang.Object → android.view.View → android.widget.ProgressBar →  
android.widget.AbsSeekBar

- Include

```
0  android.widget.AbsSeekBar
```

- Constructors

```
0  AbsSeekBar(Context context)
1  AbsSeekBar(Context context, AttributeSet attrs)
2  AbsSeekBar(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  AbsSeekBar(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleRes)
```

- Public methods

- **void drawableHotspotChanged(float x, float y)**: Called whenever the view hotspot changes and needs to be propagated to drawables or child views managed by the view.
- **CharSequence getAccessibilityClassName()**: Returns the class name of this object to be used for accessibility purposes.
- **int getKeyProgressIncrement()**: Returns the amount by which the progress changes when the user presses an arrow key.
- **boolean getSplitTrack()**: Returns whether the track is split by the thumb.
- **Drawable getThumb()**: Returns the drawable representing the scroll thumb — the component the user can drag to indicate progress.
- **int getThumbOffset()**: Returns the amount by which the thumb extends beyond the track.
- **BlendMode getThumbTintBlendMode()**: Returns the blending mode used to apply the tint to the thumb drawable, if specified.
- **ColorStateList getThumbTintList()**: Returns the tint color list applied to the thumb drawable, if specified.
- **PorterDuff.Mode getThumbTintMode()**: Returns the blending mode used to apply the tint to the thumb drawable, if specified.
- **Drawable getTickMark()**: Returns the drawable used as the tick mark for each progress position.
- **BlendMode getTickMarkTintBlendMode()**: Returns the blending mode used to apply the tint to the tick mark drawable, if specified.
- **ColorStateList getTickMarkTintList()**: Returns the tint color list applied to the tick mark drawable, if specified.
- **PorterDuff.Mode getTickMarkTintMode()**: Returns the blending mode used to apply the tint to the tick mark drawable, if specified.

- **void jumpDrawablesToCurrentState()**: Immediately updates all drawables associated with this view to their current state.
- **boolean onKeyDown(int keyCode, KeyEvent event)**: Handles key press events such as DPAD center or enter when the view is enabled and clickable.
- **void onRtlPropertiesChanged(int layoutDirection)**: Called when any RTL (right-to-left) layout property or alignment has changed.
- **boolean onTouchEvent(MotionEvent event)**: Handles touch or pointer events for user interaction.
- **void setKeyProgressIncrement(int increment)**: Sets the amount by which progress changes when the user presses arrow keys.
- **void setMax(int max)**: Sets the maximum value of the progress range.
- **void setMin(int min)**: Sets the minimum value of the progress range.
- **void setSplitTrack(boolean splitTrack)**: Specifies whether the track should be visually split by the thumb.
- **void setSystemGestureExclusionRects(List<Rect> rects)**: Defines regions within the view where system gestures should not be intercepted.
- **void setThumb(Drawable thumb)**: Sets the drawable used as the thumb in the progress meter.
- **void setThumbOffset(int thumbOffset)**: Sets the offset allowing the thumb to extend beyond the track.
- **void setThumbTintBlendMode(BlendMode blendMode)**: Defines the blending mode used when applying tint to the thumb drawable.
- **void setThumbTintList(ColorStateList tint)**: Applies a tint color list to the thumb drawable.
- **void setThumbTintMode(PorterDuff.Mode tintMode)**: Specifies the blending mode used with the thumb tint.
- **void setTickMark(Drawable tickMark)**: Sets the drawable used as a tick mark at each progress position.
- **void setTickMarkTintBlendMode(BlendMode blendMode)**: Specifies the blending mode used to apply tint to the tick mark drawable.
- **void setTickMarkTintList(ColorStateList tint)**: Applies a tint color list to the tick mark drawable.
- **void setTickMarkTintMode(PorterDuff.Mode tintMode)**: Specifies the blending mode used with the tick mark tint.

- **Protected methods**

- **void drawableStateChanged()**: Called whenever the state of the view changes in a way that affects the state of its drawables.
- **void onDraw(Canvas canvas)**: Implement this method to perform custom drawing operations for the view.
- **void onMeasure(int widthMeasureSpec, int heightMeasureSpec)**: Measures the view and its content to determine the measured width and height.
- **void onSizeChanged(int w, int h, int oldw, int oldh)**: Called during layout when the size of the view changes, providing both new and old dimensions.
- **boolean verifyDrawable(Drawable who)**: Returns true if the specified drawable is managed and displayed by this view; subclasses should override when handling custom drawables.

## 1.45 SeekBar

- **Hierarchy**

java.lang.Object → android.view.View → android.widget.ProgressBar →  
android.widget.AbsSeekBar → android.widget.SeekBar

- **Include**

```
0  android.widget.SeekBar
```

- **Constructors**

```
0  SeekBar(Context context)
1  SeekBar(Context context, AttributeSet attrs)
2  SeekBar(Context context, AttributeSet attrs, int
    ↪  defStyleAttr)
3  SeekBar(Context context, AttributeSet attrs, int
    ↪  defStyleAttr, int defStyleRes)
```

- **Public methods**

- **CharSequence getAccessibilityClassName()**: Return the class name of this object to be used for accessibility purposes.
- **void setOnSeekBarChangeListener(SeekBar.OnSeekBarChangeListener)**: Sets a listener to receive notifications of changes to the SeekBar's progress level.

## 1.46 Drawable

- Hierarchy

java.lang.Object → android.graphics.drawable.Drawable

- Include

```
o android.graphics.drawable.Drawable
```

- Constructors

```
o Drawable()
```

- Public methods

- **void applyTheme(Resources.Theme t)**: Applies the specified theme to this **Drawable** and its children.
- **boolean canApplyTheme()**: Returns true if this **Drawable** can apply a theme.
- **void clearColorFilter()**: Removes any color filter currently applied to the drawable.
- **final Rect copyBounds()**: Returns a copy of the drawable's bounds in a new **Rect** object.
- **final void copyBounds(Rect bounds)**: Copies the drawable's bounds into the specified **Rect**.
- **static Drawable createFromPath(String pathName)**: Creates a drawable from the specified file path name.
- **static Drawable createFromResourceStream(Resources res, TypedValue value, InputStream is, String srcName, BitmapFactory.Options opts)**: *Deprecated in API 28*. Creates a drawable from an input stream using the specified options.
- **static Drawable createFromResourceStream(Resources res, TypedValue value, InputStream is, String srcName)**: Creates a drawable from an input stream using the given resources and density information.
- **static Drawable createFromStream(InputStream is, String srcName)**: Creates a drawable from the specified input stream.
- **static Drawable createFromXml(Resources r, XmlPullParser parser)**: Creates a drawable from an XML document.
- **static Drawable createFromXml(Resources r, XmlPullParser parser, Resources.Theme theme)**: Creates a drawable from an XML document using the specified theme.
- **static Drawable createFromXmlInner(Resources r, XmlPullParser parser, AttributeSet attrs, Resources.Theme theme)**: Creates a drawable from within an XML document using an optional theme.
- **static Drawable createFromXmlInner(Resources r, XmlPullParser parser, AttributeSet attrs)**: Creates a drawable from within an XML document.
- **abstract void draw(Canvas canvas)**: Draws the drawable within its bounds, respecting alpha and color filters.

- **int** **getAlpha()**: Returns the current alpha value for the drawable.
- **final Rect** **getBounds()**: Returns the drawable’s bounding rectangle.
- **Drawable.Callback** **getCallback()**: Returns the current callback attached to this drawable.
- **int** **getChangingConfigurations()**: Returns a mask of configuration parameters that may change and require the drawable to be re-created.
- **ColorFilter** **getColorFilter()**: Returns the current color filter, or null if none is set.
- **Drawable.ConstantState** **getConstantState()**: Returns the constant state of this drawable, allowing shared state across instances.
- **Drawable** **getCurrent()**: Returns the current drawable in use, if the drawable supports multiple states.
- **Rect** **getDirtyBounds()**: Returns the drawable’s dirty bounds rectangle.
- **void** **getHotspotBounds(Rect outRect)**: Populates the provided **Rect** with the hotspot bounds.
- **int** **getIntrinsicHeight()**: Returns the drawable’s intrinsic (default) height.
- **int** **getIntrinsicWidth()**: Returns the drawable’s intrinsic (default) width.
- **int** **getLayoutDirection()**: Returns the resolved layout direction for this drawable.
- **final int** **getLevel()**: Returns the current drawable level.
- **int** **getMinimumHeight()**: Returns the minimum height suggested by this drawable.
- **int** **getMinimumWidth()**: Returns the minimum width suggested by this drawable.
- **abstract int** **getOpacity()**: *Deprecated in API 29.* Returns the drawable’s opacity mode.
- **Insets** **getOpticalInsets()**: Returns the optical insets for alignment during layout.
- **void** **getOutline(Outline outline)**: Populates the given **Outline** with the drawable’s shape for rendering effects such as shadows.
- **boolean** **getPadding(Rect padding)**: Fills the given **Rect** with content insets suggested by the drawable.
- **int[]** **getState()**: Returns the current state of the drawable as an array of state attributes.
- **Region** **getTransparentRegion()**: Returns a region representing areas of complete transparency.
- **boolean** **hasFocusStateSpecified()**: Returns true if the drawable explicitly specifies a focused state.
- **void** **inflate(Resources r, XmlPullParser parser, AttributeSet attrs, Resources.Theme theme)**: Inflates this drawable from XML, optionally styled by a theme.
- **void** **inflate(Resources r, XmlPullParser parser, AttributeSet attrs)**: Inflates this drawable from XML.
- **void** **invalidateSelf()**: Requests a redraw of the drawable using its current callback.
- **boolean** **isAutoMirrored()**: Returns whether the drawable automatically mirrors its image in RTL layouts.



- **boolean isFilterBitmap()**: Returns whether this drawable is filtering bitmaps when scaled or rotated.
- **boolean isProjected()**: Returns true if the drawable is projected.
- **boolean isStateful()**: Returns whether this drawable changes appearance based on its state.
- **final boolean isVisible()**: Returns true if the drawable is currently visible.
- **void jumpToCurrentState()**: Skips any active state transition animations and jumps directly to the current state.
- **Drawable mutate()**: Returns a mutable instance of this drawable that can be modified independently.
- **boolean onLayoutDirectionChanged(int layoutDirection)**: Called when the drawable’s layout direction changes.
- **static int resolveOpacity(int op1, int op2)**: Resolves and returns an appropriate opacity value from two input opacities.
- **void scheduleSelf(Runnable what, long when)**: Schedules the drawable to execute the given runnable at a specified time.
- **abstract void setAlpha(int alpha)**: Sets the drawable’s alpha value for transparency.
- **void setAutoMirrored(boolean mirrored)**: Sets whether this drawable automatically mirrors when layout direction is RTL.
- **void setBounds(int left, int top, int right, int bottom)**: Defines the bounding rectangle of the drawable.
- **void setBounds(Rect bounds)**: Sets the drawable’s bounds using the provided rectangle.
- **final void setCallback(Drawable.Callback cb)**: Binds a callback to the drawable for invalidation and scheduling.
- **void setChangingConfigurations(int configs)**: Specifies which configuration changes require the drawable to be recreated.
- **void setColorFilter(int color, PorterDuff.Mode mode)**: *Deprecated in API 29.* Use `setColorFilter(ColorFilter)` instead.
- **abstract void setColorFilter(ColorFilter colorFilter)**: Sets an optional color filter to modify how the drawable’s pixels are rendered.
- **void setDither(boolean dither)**: *Deprecated in API 23.* This property is ignored.
- **void setFilterBitmap(boolean filter)**: Enables or disables bilinear filtering for scaled or rotated bitmaps.
- **void setHotspot(float x, float y)**: Specifies the hotspot’s location within the drawable.
- **void setHotspotBounds(int left, int top, int right, int bottom)**: Defines the bounds for the hotspot within the drawable.
- **final boolean setLayoutDirection(int layoutDirection)**: Sets the layout direction for the drawable (LTR or RTL).
- **final boolean setLevel(int level)**: Sets the drawable’s current level, used by certain drawable types for animation or progress indication.
- **boolean setState(int[] stateSet)**: Sets the drawable’s current state using the given array of state attributes.
- **void setTint(int tintColor)**: Applies a single color tint to the drawable.

- **void setTintBlendMode(BlendMode blendMode)**: Specifies the blending mode used to apply the tint color.
- **void setTintList(ColorStateList tint)**: Applies a tint color list to the drawable for different states.
- **void setTintMode(PorterDuff.Mode tintMode)**: Specifies the blending mode used to apply the tint list.
- **boolean setVisible(boolean visible, boolean restart)**: Sets the drawable's visibility, optionally restarting animations.
- **void unscheduleSelf(Runnable what)**: Cancels any scheduled runnables associated with this drawable.

- **Protected methods**

- **void onBoundsChange(Rect bounds)**: Override this in your subclass to change appearance if you vary based on the bounds.
- **boolean onLevelChange(int level)**: Override this in your subclass to change appearance if you vary based on level.
- **boolean onStateChange(int[] state)**: Override this in your subclass to change appearance if you recognize the specified state.

## 1.47 GradientDrawable

- Hierarchy

java.lang.Object → android.graphics.drawable.Drawable →  
android.graphics.drawable.GradientDrawable

- Include

```
0 android.graphics.drawable.GradientDrawable
```

- Constructors

```
0 GradientDrawable()  
1 GradientDrawable(GradientDrawable.Orientation orientation,  
↪ int[] colors)
```

- Public methods

- **void applyTheme(Resources.Theme t)**: Applies the specified theme to this Drawable and its children.
- **boolean canApplyTheme()**: Returns true if this Drawable can apply a theme.
- **void draw(Canvas canvas)**: Draws the shape within its bounds, respecting alpha and color filter effects.
- **int getAlpha()**: Returns the current alpha value of the drawable.
- **int getChangingConfigurations()**: Returns a mask of configuration parameters that can change, requiring the drawable to be recreated.
- **ColorStateList getColor()**: Returns the color state list used to fill the shape, or null if it uses a gradient or no fill color.
- **ColorFilter getColorFilter()**: Returns the currently applied color filter, or null if none.
- **int[] getColors()**: Returns the colors used for the gradient fill, or null if not applicable.
- **Drawable.ConstantState getConstantState()**: Returns the constant state shared by this drawable.
- **float[] getCornerRadii()**: Returns the corner radii for all four corners.
- **float getCornerRadius()**: Returns the uniform corner radius set with **setCornerRadius(float)**.
- **float getGradientCenterX()**: Returns the X position of the gradient center as a fraction of the width.
- **float getGradientCenterY()**: Returns the Y position of the gradient center as a fraction of the height.
- **float getGradientRadius()**: Returns the gradient's radius in pixels.
- **int getGradientType()**: Returns the gradient type: **LINEAR\_GRADIENT**, **RADIAL\_GRADIENT**, or **SWEEP\_GRADIENT**.
- **int getInnerRadius()**: Returns the inner radius of the ring shape in pixels.
- **float getInnerRadiusRatio()**: Returns the inner radius of the ring as a ratio of the ring's width.

- **int** **getIntrinsicHeight()**: Returns the drawable’s intrinsic height.
- **int** **getIntrinsicWidth()**: Returns the drawable’s intrinsic width.
- **int** **getOpacity()**: *Deprecated*. No longer used for optimization.
- **Insets** **getOpticalInsets()**: Returns the suggested layout insets for alignment operations.
- **GradientDrawable.Orientation** **getOrientation()**: Returns the orientation of the gradient.
- **void** **getOutline(Outline outline)**: Populates the given **Outline** with the drawable’s shape outline.
- **boolean** **getPadding(Rect padding)**: Returns padding in the given **Rect**, as suggested by the drawable.
- **int** **getShape()**: Returns the shape type (**LINE**, **OVAL**, **RECTANGLE**, or **RING**).
- **int** **getThickness()**: Returns the ring’s thickness in pixels.
- **float** **getThicknessRatio()**: Returns the ring’s thickness as a ratio of its width.
- **boolean** **getUseLevel()**: Returns whether the drawable’s level property is used to scale the gradient.
- **boolean** **hasFocusStateSpecified()**: Returns true if the drawable explicitly defines a focused state.
- **void** **inflate(Resources r, XmlPullParser parser, AttributeSet attrs, Resources.Theme theme)**: Inflates the drawable from XML, optionally using a theme.
- **boolean** **isStateful()**: Returns true if the drawable changes appearance based on state.
- **Drawable** **mutate()**: Returns a mutable instance of this drawable that can be modified independently.
- **void** **setAlpha(int alpha)**: Sets the transparency level of the drawable.
- **void** **setColor(ColorStateList colorStateList)**: Changes the drawable to use a solid color state list instead of a gradient.
- **void** **setColor(int argb)**: Changes the drawable to use a single solid color.
- **void** **setColorFilter(ColorFilter colorFilter)**: Applies a color filter to the drawable.
- **void** **setColors(int[] colors, float[] offsets)**: Defines multiple colors and their relative positions in the gradient.
- **void** **setColors(int[] colors)**: Sets multiple colors for the gradient fill.
- **void** **setCornerRadii(float[] radii)**: Sets custom radii for each corner of the shape.
- **void** **setCornerRadius(float radius)**: Sets a uniform radius for all corners.
- **void** **setDither(boolean dither)**: *Deprecated*. Ignored property.
- **void** **setGradientCenter(float x, float y)**: Sets the center of the gradient as a fraction of width and height.
- **void** **setGradientRadius(float gradientRadius)**: Sets the gradient’s radius in pixels.
- **void** **setGradientType(int gradient)**: Defines the gradient type (**LINEAR**, **RADIAL**, or **SWEEP**).
- **void** **setInnerRadius(int innerRadius)**: Sets the inner radius of a ring shape.

- **void setInnerRadiusRatio(float innerRadiusRatio)**: Defines the ring’s inner radius as a ratio of its width.
- **void setOrientation(GradientDrawable.Orientation orientation)**: Sets the direction of the gradient.
- **void setPadding(int left, int top, int right, int bottom)**: Defines the padding of the shape.
- **void setShape(int shape)**: Sets the shape type (LINE, OVAL, RECTANGLE, RING).
- **void setSize(int width, int height)**: Defines the overall size of the shape.
- **void setStroke(int width, ColorStateList colorStateList)**: Sets stroke width and color using a color state list.
- **void setStroke(int width, ColorStateList colorStateList, float dashWidth, float dashGap)**: Sets stroke width, color, and dash pattern.
- **void setStroke(int width, int color, float dashWidth, float dashGap)**: Sets stroke width, solid color, and dash pattern.
- **void setStroke(int width, int color)**: Sets stroke width and solid color.
- **void setThickness(int thickness)**: Sets the thickness of the ring shape.
- **void setThicknessRatio(float thicknessRatio)**: Sets the ring thickness as a ratio of its width.
- **void setTintBlendMode(BlendMode blendMode)**: Specifies how tint color should be blended with the drawable.
- **void setTintList(ColorStateList tint)**: Applies a tint color list for different drawable states.
- **void setUseLevel(boolean useLevel)**: Configures whether the drawable’s level affects the gradient scaling.

- **Protected methods**

- **void onBoundsChange(Rect r)**: Override this in your subclass to change appearance if you vary based on the bounds.
- **boolean onLevelChange(int level)**: Override this in your subclass to change appearance if you vary based on level.
- **boolean onStateChange(int[] stateSet)**: Override this in your subclass to change appearance if you recognize the specified state.

- **Constants**

- **int ARC**: Shape is an arc.
- **int LINE**: Shape is a line
- **int LINEAR\_GRADIENT**: Gradient is linear (default.)
- **int OVAL**: Shape is an ellipse
- **int RADIAL\_GRADIENT**: Gradient is circular.
- **int RECTANGLE**: Shape is a rectangle, possibly with rounded corners
- **int RING**: Shape is a ring.
- **int SWEEP\_GRADIENT**: Gradient is a sweep.

## 1.48 Intent

- Hierarchy

java.lang.Object → android.content.Intent

- Include

```
0  android.content.Intent
```

- Constructors

```
0  Intent()
1  Intent(Context packageContext, Class<?> cls)
2  Intent(Intent o)
3  Intent(String action)
4  Intent(String action, Uri uri)
5  Intent(String action, Uri uri, Context packageContext,
   ↪ Class<?> cls)
```

- Public methods

- **setAction(String)**: Sets the action to perform (like ACTION\_VIEW, ACTION\_SEND).
- **getAction()**: Returns the currently set action.
- **setData(Uri)**: Sets a URI for the intent (like content to view/open).
- **getData()**: Gets the URI associated with the intent.
- **setType(String)**: Sets the MIME type of data (like "image/\*").
- **getType()**: Gets the MIME type.
- **setDataAndType(Uri, String)**: Sets both URI and MIME type at once.
- **addCategory(String)**: Adds a category (e.g. CATEGORY\_LAUNCHER).
- **removeCategory(String)**: Removes a category.
- **getCategories()**: Returns all categories added.
- **putExtra(String, T)**: (overloads) Stores data in the intent (String, int, ArrayList, etc.).
- **get\*Extra(...)**: (e.g., getStringExtra) Retrieves specific extra values.
- **getExtras()**: Gets entire Bundle of extras.
- **replaceExtras(Bundle)**: Replaces all extras.
- **removeExtra(String)**: Removes a specific extra.
- **setClass(Context, Class<?>)**: Directs the Intent to a specific Activity class (explicit intent).
- **setClassName(String, String)**: Sets a target component by package/class name.
- **setComponent(ComponentName)**: Specifies the component directly.
- **getComponent()**: Returns the component if explicitly set.
- **setPackage(String)**: Limits resolution to a specific package.

- **addFlags(int)**: Adds flags like `FLAG_ACTIVITY_NEW_TASK`, controlling launch behavior.
  - **setFlags(int)**: Replaces all existing flags.
  - **getFlags()**: Returns currently-set flags.
  - **resolveActivity(PackageManager)**: Checks if an intent can be handled by installed apps.
  - **toUri(int)**: Converts the intent to a URI string.
  - **filterEquals(Intent)**: Compares actions/data/categories/type but ignores extras.
  - **getScheme()**: Returns URI scheme (like "content", "http").
  - **getClipData()**: / **setClipData()** Used for advanced data transfers (drag-drop, multiple selections).
- **Fields**
    - **public static final Creator<Intent> CREATOR:**
- **Constants**
    - **ACTION\_MAIN**: Entry point Activity (launcher screen)
    - **ACTION\_VIEW**: Display data to the user (webpage, map, file)
    - **ACTION\_EDIT**: Edit existing data
    - **ACTION\_PICK**: Pick an item from data (gallery, contacts)
    - **ACTION\_GET\_CONTENT**: Allow the user to select a type of data (e.g., file picker)
    - **ACTION\_CHOOSER**: Show app-chooser dialog for an Intent
    - **ACTION\_SEND**: Share text, images, files
    - **ACTION\_SENDTO**: Send to a specific communication target (email, SMS)
    - **EXTRA\_TEXT**: Extra: text to send
    - **EXTRA\_SUBJECT**: Extra: email subject
    - **EXTRA\_STREAM**: Extra: send images/files
    - **EXTRA\_EMAIL**: Extra: receiver email addresses
    - **ACTION\_DIAL**: Open dialer with number prefilled
    - **ACTION\_CALL**: Directly place a call (requires permission)
    - **ACTION\_SENDSMS** / **ACTION\_VIEW**: with SMS URI Send SMS message
    - **EXTRA\_PHONE\_NUMBER**: Extra: phone number
    - **ACTION\_IMAGE\_CAPTURE**: Open camera app to take a picture
    - **ACTION\_VIDEO\_CAPTURE**: Record video
    - **EXTRA\_OUTPUT**: Where to save captured image/video
    - **ACTION\_SETTINGS**: Open device settings screen
    - **ACTION\_WIRELESS\_SETTINGS**: Wireless settings
    - **ACTION\_APPLICATION\_DETAILS\_SETTINGS**: App details settings (like uninstall/permissions page)
    - **FLAG\_ACTIVITY\_NEW\_TASK**: Start Activity in a new task (important for services)

- **FLAG\_ACTIVITY\_CLEAR\_TOP**: Clear Activities on top of target
- **FLAG\_ACTIVITY\_SINGLE\_TOP**: Reuse existing instance if already on top
- **ACTION\_AIRPLANE\_MODE\_CHANGED**: Airplane mode switch
- **ACTION\_BATTERY\_LOW**: Battery low warning
- **ACTION\_BOOT\_COMPLETED**: Device boot finished (permission required)



## 1.49 Animation

- Hierarchy

java.lang.Object → android.view.animation.Animation

- Include

```
0 android.view.animation.Animation
```

- Constructors

```
0 Animation()  
1 Animation(Context context, AttributeSet attrs)
```

- Public methods

- **cancel()**: Cancel the animation.
- **computeDurationHint()**: Compute a hint at how long the entire animation may last, in milliseconds.
- **getBackdropColor()**: Returns the background color to show behind the animating windows.
- **getBackgroundColor()**: *Deprecated in API level 30.* None of window animations are running with background color.
- **getDetachWallpaper()**: *Deprecated in API level 29.* All window animations are running with detached wallpaper.
- **getDuration()**: How long this animation should last.
- **getFillAfter()**: If fillAfter is true, this animation will apply its transformation after the end time.
- **getFillBefore()**: If fillBefore is true, this animation will apply its transformation before the start time.
- **getInterpolator()**: Gets the acceleration curve type for this animation.
- **getRepeatCount()**: Defines how many times the animation should repeat.
- **getRepeatMode()**: Defines what this animation should do when it reaches the end.
- **getShowBackdrop()**: If true, animation will show the backdrop behind window animations.
- **getStartOffset()**: When this animation should start relative to StartTime.
- **getStartTime()**: When this animation should start.
- **getTransformation(long, Transformation, float)**: Gets the transformation at a specified point in time.
- **getTransformation(long, Transformation)**: Gets the transformation at a specified point in time.
- **getZAdjustment()**: Returns the Z ordering mode while running the animation.
- **hasEnded()**: Indicates whether this animation has ended.
- **hasStarted()**: Indicates whether this animation has started.

- **initialize(int, int, int, int)**: Initialize animation with view and parent dimensions.
- **isFillEnabled()**: If true, animation applies the value of fillBefore.
- **isInitialized()**: Whether the animation has been initialized.
- **reset()**: Reset the initialization state of this animation.
- **restrictDuration(long)**: Ensure the duration is not longer than durationMillis.
- **scaleCurrentDuration(float)**: Scale the duration by the given factor.
- **setAnimationListener(Animation.AnimationListener)**: Bind an animation listener to this animation.
- **setBackdropColor(int)**: Set the backdrop color behind animating windows.
- **setBackgroundColor(int)**: *Deprecated in API level 30.*
- **setDetachWallpaper(boolean)**: *Deprecated in API level 29.*
- **setDuration(long)**: Set how long this animation should last.
- **setFillAfter(boolean)**: If true, the transformation persists after animation finishes.
- **setFillBefore(boolean)**: If true, apply transformation before animation start.
- **setFillEnabled(boolean)**: If true, animation applies the value of fillBefore.
- **setInterpolator(Interpolator)**: Sets the acceleration curve for the animation.
- **setInterpolator(Context, int)**: Sets acceleration curve using resources.
- **setRepeatCount(int)**: Sets how many times animation repeats.
- **setRepeatMode(int)**: Defines behavior when animation reaches the end.
- **setShowBackdrop(boolean)**: Enable backdrop animation behind windows.
- **setStartOffset(long)**: When animation should start relative to start time.
- **setStartTime(long)**: When animation should start.
- **setZAdjustment(int)**: Set Z ordering mode while running the animation.
- **start()**: Start the animation the first time getTransformation is invoked.
- **startNow()**: Start the animation at the current system time.
- **willChangeBounds()**: Indicates if animation affects bounds of animated view.
- **willChangeTransformationMatrix()**: Indicates if animation affects transformation matrix.

- **Protected methods**

- **applyTransformation(float interpolatedTime, Transformation t)**: Helper for getTransformation.
- **clone()**: Creates and returns a copy of this object.
- **ensureInterpolator()**: Guarantees that this animation has an interpolator.
- **finalize()**: Called by the garbage collector when there are no more references to the object.
- **getScaleFactor()**: Returns the scale factor set by the call to getTransformation.
- **resolveSize(int type, float value, int size, int parentSize)**: Convert size description to an actual dimension.

- **Constants**

- **applyTransformation(float interpolatedTime, Transformation t)**: Helper for getTransformation.

- **clone()**: Creates and returns a copy of this object.
- **ensureInterpolator()**: Guarantees that this animation has an interpolator.
- **finalize()**: Called by the garbage collector when there are no more references to the object.
- **getScaleFactor()**: Returns the scale factor set by the call to `getTransformation`.
- **resolveSize(int type, float value, int size, int parentSize)**: Convert size description to an actual dimension.

## 1.50 AnimationSet

- Hierarchy

java.lang.Object → android.view.animation.Animation →  
android.view.animation.AnimationSet

- Include

```
0  android.view.animation.AnimationSet
```

- Constructors

```
0  AnimationSet(Context context, AttributeSet attrs)
1  AnimationSet(boolean shareInterpolator)
```

- Public methods

- **addAnimation(Animation a)**: Add a child animation to this animation set.
- **computeDurationHint()**: Duration hint is the maximum duration hint of all child animations.
- **getAnimations()**: Returns the list of child animations.
- **getDuration()**: Duration is defined as the duration of the longest child animation.
- **getStartTime()**: When this animation should start.
- **getTransformation(long currentTime, Transformation t)**: Transformation is the concatenation of all component animations.
- **initialize(int width, int height, int parentWidth, int parentHeight)**: Initialize with the dimensions of the object and its parent.
- **reset()**: Reset the initialization state of this animation.
- **restrictDuration(long durationMillis)**: Ensure duration does not exceed durationMillis.
- **scaleCurrentDuration(float scale)**: Scale the duration by the specified factor.
- **setDuration(long durationMillis)**: Sets the duration for every child animation.
- **setFillAfter(boolean fillAfter)**: If true, transformation persists after animation ends.
- **setFillBefore(boolean fillBefore)**: If true, apply transformation before animation starts.
- **setRepeatMode(int repeatMode)**: Defines what happens when animation reaches the end.
- **setStartOffset(long startOffset)**: When this animation should start relative to start time.
- **setStartTime(long startTimeMillis)**: Sets start time for this animation and all child animations.
- **willChangeBounds()**: Indicates whether this animation affects bounds of the animated view.

- **willChangeTransformationMatrix()**: Indicates whether this animation affects the transformation matrix.
- **Protected methods**
  - **AnimationSet clone()**: Creates and returns a copy of this object.

## 1.51 AlphaAnimation

- **Hierarchy**

java.lang.Object → android.view.animation.Animation →  
android.view.animation.AlphaAnimation

- **Include**

```
0  android.view.animation.AlphaAnimation
```

- **Constructors**

```
0  AlphaAnimation(Context context, AttributeSet attrs)
1  AlphaAnimation(float fromAlpha, float toAlpha)
```

- **Public methods**

- **boolean willChangeBounds()**: Indicates whether or not this animation will affect the bounds of the animated view.
- **boolean willChangeTransformationMatrix()**: Indicates whether or not this animation will affect the transformation matrix.

- **Protected methods**

- **void applyTransformation(float interpolatedTime, Transformation t)**:  
Changes the alpha property of the supplied Transformation

## 1.52 RotateAnimation

- **Hierarchy**

java.lang.Object → android.view.animation.Animation →  
android.view.animation.RotateAnimation

- **Include**

```
0  android.view.animation.RotateAnimation
```

- **Constructors**

```
0  RotateAnimation(Context context, AttributeSet attrs)
1  RotateAnimation(float fromDegrees, float toDegrees)
2  RotateAnimation(float fromDegrees, float toDegrees, float
   ↪  pivotX, float pivotY)
3  RotateAnimation(float fromDegrees, float toDegrees, int
   ↪  pivotXType, float pivotXValue, int pivotYType, float
   ↪  pivotYValue)
```

- **Public methods**

- **void initialize(int width, int height, int parentWidth, int parentHeight):**  
Initialize this animation with the dimensions of the object being animated as well as the objects parents.

- **Protected methods**

- **void applyTransformation(float interpolatedTime, Transformation t):**  
Helper for getTransformation.

## 1.53 ScaleAnimation

- **Hierarchy**

java.lang.Object → android.view.animation.Animation →  
android.view.animation.ScaleAnimation

- **Include**

```
0  android.view.animation.ScaleAnimation
```

- **Constructors**

```
0  ScaleAnimation(Context context, AttributeSet attrs)
1  ScaleAnimation(float fromX, float toX, float fromY, float
   ↪ toY)
2  ScaleAnimation(float fromX, float toX, float fromY, float
   ↪ toY, float pivotX, float pivotY)
3  ScaleAnimation(float fromX, float toX, float fromY, float
   ↪ toY, int pivotXType, float pivotXValue, int pivotYType,
   ↪ float pivotYValue)
```

- **Public methods**

- **void initialize(int width, int height, int parentWidth, int parentHeight):**  
Initialize this animation with the dimensions of the object being animated as well as the objects parents.

- **Protected methods**

- **void applyTransformation(float interpolatedTime, Transformation t):**  
Helper for getTransformation.



## 1.54 TranslateAnimation

- Hierarchy

java.lang.Object → android.view.animation.Animation →  
android.view.animation.TranslateAnimation

- Include

```
0  android.view.animation.TranslateAnimation
```

- Constructors

```
0  TranslateAnimation(Context context, AttributeSet attrs)
1  TranslateAnimation(float fromXDelta, float toXDelta, float
   ↪ fromYDelta, float toYDelta)
2  TranslateAnimation(int fromXType, float fromXValue, int
   ↪ toXType, float toXValue, int fromYType, float
   ↪ fromYValue, int toYType, float toYValue)
```

- Public methods

- **void initialize(int width, int height, int parentWidth, int parentHeight):**  
Initialize this animation with the dimensions of the object being animated as well as the objects parents.

- Protected methods

- **void applyTransformation(float interpolatedTime, Transformation t):**  
Helper for getTransformation.

## 1.55 PreferenceManager

- Include:

```
o android.preference.PreferenceManager
```

- Nested interfaces

- **interface PreferenceManager.OnActivityDestroyListener**: This interface was deprecated in API level 29. Use the AndroidX Preference Library for consistent behavior across all devices. For more information on using the AndroidX Preference Library see Settings.
- **interface PreferenceManager.OnActivityResultListener**: This interface was deprecated in API level 29. Use the AndroidX Preference Library for consistent behavior across all devices. For more information on using the AndroidX Preference Library see Settings.
- **interface PreferenceManager.OnActivityStopListener**: This interface was deprecated in API level 29. Use the AndroidX Preference Library for consistent behavior across all devices. For more information on using the AndroidX Preference Library see Settings.

- Public methods

- **PreferenceScreen createPreferenceScreen(Context context)**:
- **Preference findPreference(CharSequence key)**: Finds a Preference based on its key.
- **static SharedPreferences getDefaultSharedPreferences(Context context)**: Gets a SharedPreferences instance that points to the default file that is used by the preference framework in the given context.
- **static String getDefaultSharedPreferencesName(Context context)**: Returns the name used for storing default shared preferences.
- **PreferenceDataStore getPreferenceDataStore()**: Returns the PreferenceDataStore associated with this manager or null if the default SharedPreferences are used instead.
- **SharedPreferences getSharedPreferences()**: Gets a SharedPreferences instance that preferences managed by this will use.
- **int getSharedPreferencesMode()**: Returns the current mode of the SharedPreferences file that preferences managed by this will use.
- **String getSharedPreferencesName()**: Returns the current name of the SharedPreferences file that preferences managed by this will use.
- **boolean isStorageDefault()**: Indicates if the storage location used internally by this class is the default provided by the hosting Context.
- **boolean isStorageDeviceProtected()**: Indicates if the storage location used internally by this class is backed by device-protected storage.
- **static void setDefaultValues(Context context, String sharedPreferencesName, int sharedPreferencesMode, int resId, boolean readAgain)**: Similar to `setDefaultValues(android.content.Context, int, boolean)` but allows the client to provide the filename and mode of the shared preferences file.
- **static void setDefaultValues(Context context, int resId, boolean readAgain)**: Sets the default values from an XML preference file by reading the values defined by each Preference item's `android:defaultValue` attribute.

- **void setPreferenceDataStore(PreferenceDataStore datastore):** Sets a PreferenceDataStore to be used by all Preferences associated with this manager that don't have a custom PreferenceDataStore assigned via Preference.setPreferenceDataStore(PreferenceDataStore).
  - **void setSharedPreferencesMode(int sharedPreferencesMode):** Sets the mode of the SharedPreferences file that preferences managed by this will use.
  - **void setSharedPreferencesName(String sharedPreferencesName):** Sets the name of the SharedPreferences file that preferences managed by this will use.
  - **void setStorageDefault():** Sets the storage location used internally by this class to be the default provided by the hosting Context.
  - **void setStorageDeviceProtected():** Explicitly set the storage location used internally by this class to be device-protected storage.
- **Constants**
    - **String KEY\_HAS\_SET\_DEFAULT\_VALUES:**
    - **String METADATA\_KEY\_PREFERENCES:** The Activity meta-data key for its XML preference hierarchy.

## 1.56 SharedPreferences (interface)

- Include

```
0  android.content.SharedPreferences
```

- Nested interfaces

- **interface SharedPreferences.Editor**: Interface used for modifying values in a SharedPreferences object.
- **interface SharedPreferences.OnSharedPreferenceChangeListener**: Interface definition for a callback to be invoked when a shared preference is changed.

- Abstract methods

- **abstract boolean contains(String key)**: Checks whether the preferences contains a preference.
- **abstract SharedPreferences.Editor edit()**: Create a new Editor for these preferences, through which you can make modifications to the data in the preferences and atomically commit those changes back to the SharedPreferences object.
- **abstract Map<String, ?> getAll()**: Retrieve all values from the preferences.
- **abstract boolean getBoolean(String key, boolean defValue)**: Retrieve a boolean value from the preferences.
- **abstract float getFloat(String key, float defValue)**: Retrieve a float value from the preferences.
- **abstract int getInt(String key, int defValue)**: Retrieve an int value from the preferences.
- **abstract long getLong(String key, long defValue)**: Retrieve a long value from the preferences.
- **abstract String getString(String key, String defValue)**: Retrieve a String value from the preferences.
- **abstract Set<String> getStringSet(String key, Set<String> defValues)**: Retrieve a set of String values from the preferences.
- **abstract void registerOnSharedPreferenceChangeListener(SharedPreferences.OnSharedPreferenceChangeListener listener)**: Registers a callback to be invoked when a change happens to a preference.
- **abstract void unregisterOnSharedPreferenceChangeListener(SharedPreferences.OnSharedPreferenceChangeListener listener)**: Unregisters a previous callback.

## 1.57 SharedPreferences.Editor (Interface)

- **Description:** Interface used for modifying values in a SharedPreferences object. All changes you make in an editor are batched, and not copied back to the original SharedPreferences until you call `commit()` or `apply()`
- **Abstract methods:**
  - **abstract void apply():** Commit your preferences changes back from this Editor to the SharedPreferences object it is editing.
  - **abstract SharedPreferences.Editor clear():** Mark in the editor to remove all values from the preferences.
  - **abstract boolean commit():** Commit your preferences changes back from this Editor to the SharedPreferences object it is editing.
  - **abstract SharedPreferences.Editor putBoolean(String key, boolean value):** Set a boolean value in the preferences editor, to be written back once `commit()` or `apply()` are called.
  - **abstract SharedPreferences.Editor putFloat(String key, float value):** Set a float value in the preferences editor, to be written back once `commit()` or `apply()` are called.
  - **abstract SharedPreferences.Editor putInt(String key, int value):** Set an int value in the preferences editor, to be written back once `commit()` or `apply()` are called.
  - **abstract SharedPreferences.Editor putLong(String key, long value):** Set a long value in the preferences editor, to be written back once `commit()` or `apply()` are called.
  - **abstract SharedPreferences.Editor putString(String key, String value):** Set a String value in the preferences editor, to be written back once `commit()` or `apply()` are called.
  - **abstract SharedPreferences.Editor putStringSet(String key, Set<String> values):** Set a set of String values in the preferences editor, to be written back once `commit()` or `apply()` is called.
  - **abstract SharedPreferences.Editor remove(String key):** Mark in the editor that a preference value should be removed, which will be done in the actual preferences once `commit()` is called.

## 1.58 Menu (Interface)

- Include

```
0  android.view.Menu
```

- Public abstract methods

- **abstract MenuItem add(int groupId, int itemId, int order, CharSequence title):** Add a new item to the menu.
- **abstract MenuItem add(int titleRes):** Add a new item to the menu.
- **abstract MenuItem add(CharSequence title):** Add a new item to the menu.
- **abstract MenuItem add(int groupId, int itemId, int order, int titleRes):** Variation on add(int, int, int, java.lang.CharSequence) that takes a string resource identifier instead of the string itself.
- **abstract int addIntentOptions(int groupId, int itemId, int order, ComponentName caller, Intent[] specifics, Intent intent, int flags, MenuItem[] outSpecificItems):** Add a group of menu items corresponding to actions that can be performed for a particular Intent.
- **abstract SubMenu addSubMenu(CharSequence title):** Add a new sub-menu to the menu.
- **abstract SubMenu addSubMenu(int groupId, int itemId, int order, int titleRes):** Variation on addSubMenu(int, int, int, java.lang.CharSequence) that takes a string resource identifier for the title instead of the string itself.
- **abstract SubMenu addSubMenu(int groupId, int itemId, int order, CharSequence title):** Add a new sub-menu to the menu.
- **abstract SubMenu addSubMenu(int titleRes):** Add a new sub-menu to the menu.
- **abstract void clear():** Remove all existing items from the menu, leaving it empty as if it had just been created.
- **abstract void close():** Closes the menu, if open.
- **abstract MenuItem findItem(int id):** Return the menu item with a particular identifier.
- **abstract MenuItem getItem(int index):** Gets the menu item at the given index.
- **abstract boolean hasVisibleItems():** Return whether the menu currently has item items that are visible.
- **abstract boolean isShortcutKey(int keyCode, KeyEvent event):** Is a keypress one of the defined shortcut keys for this window.
- **abstract boolean performIdentifierAction(int id, int flags):** Execute the menu item action associated with the given menu identifier.
- **abstract boolean performShortcut(int keyCode, KeyEvent event, int flags):** Execute the menu item action associated with the given shortcut character.
- **abstract void removeGroup(int groupId):** Remove all items in the given group.
- **abstract void removeItem(int id):** Remove the item with the given identifier.

- **abstract void setGroupCheckable(int group, boolean checkable, boolean exclusive):** Control whether a particular group of items can show a check mark.
- **default void setGroupDividerEnabled(boolean groupDividerEnabled):** Enable or disable the group dividers.
- **abstract void setGroupEnabled(int group, boolean enabled):** Enable or disable all menu items that are in the given group.
- **abstract void setGroupVisible(int group, boolean visible):** Show or hide all menu items that are in the given group.
- **abstract void setQwertyMode(boolean isQwerty):** Control whether the menu should be running in qwerty mode (alphabetic shortcuts) or 12-key mode (numeric shortcuts).
- **abstract int size():** Get the number of items in the menu.

- **Constants**

- **int CATEGORY\_ALTERNATIVE:** Category code for the order integer for items/groups that are alternative actions on the data that is currently displayed – or/add this with your base value.
- **int CATEGORY\_CONTAINER:** Category code for the order integer for items/groups that are part of a container – or/add this with your base value.
- **int CATEGORY\_SECONDARY:** Category code for the order integer for items/groups that are user-supplied secondary (infrequently used) options – or/add this with your base value.
- **int CATEGORY\_SYSTEM:** Category code for the order integer for items/groups that are provided by the system – or/add this with your base value.
- **int FIRST:** First value for group and item identifier integers.
- **int FLAG\_ALWAYS\_PERFORM\_CLOSE:** Flag for performShortcut(int, android.view.KeyEvent, int): if set, always close the menu after executing the shortcut.
- **int FLAG\_APPEND\_TO\_GROUP:** Flag for addIntentOptions(int, int, int, ComponentName, Intent, Intent, int, MenuItem): if set, do not automatically remove any existing menu items in the same group.
- **int FLAG\_PERFORM\_NO\_CLOSE:** Flag for performShortcut(int, KeyEvent, int): if set, do not close the menu after executing the shortcut.
- **int NONE:** Value to use for group and item identifier integers when you don't care about them.
- **int SUPPORTED\_MODIFIERS\_MASK:** A mask of all supported modifiers for MenuItem's keyboard shortcuts

## 1.59 MenuItem (Interface)

### – Include

```
0  android.view.MenuItem
```

### – Public abstract methods:

- \* **abstract boolean collapseActionView()**: Collapse the action view associated with this menu item.
- \* **abstract boolean expandActionView()**: Expand the action view associated with this menu item.
- \* **abstract ActionProvider getActionProvider()**: Gets the ActionProvider.
- \* **abstract View getActionView()**: Returns the currently set action view for this menu item.
- \* **default int getAlphabeticModifiers()**: Return the modifier for this menu item's alphabetic shortcut.
- \* **abstract char getAlphabeticShortcut()**: Return the char for this menu item's alphabetic shortcut.
- \* **default CharSequence getContentDescription()**: Retrieve the content description associated with this menu item.
- \* **abstract int getGroupId()**: Return the group identifier that this menu item is part of.
- \* **abstract Drawable getIcon()**: Returns the icon for this item as a Drawable (getting it from resources if it hasn't been loaded before).
- \* **default BlendMode getIconTintBlendMode()**: Returns the blending mode used to apply the tint to this item's icon, if specified.
- \* **default ColorStateList getIconTintList()**: default PorterDuff.Mode getIconTintMode()
- \* **abstract Intent getIntent()**: Return the Intent associated with this item.
- \* **abstract int getItemId()**: Return the identifier for this menu item.
- \* **abstract ContextMenu.ContextMenuInfo getMenuInfo()**: Gets the extra information linked to this menu item.
- \* **default int getNumericModifiers()**: Return the modifiers for this menu item's numeric (12-key) shortcut.
- \* **abstract char getNumericShortcut()**: Return the char for this menu item's numeric (12-key) shortcut.
- \* **abstract int getOrder()**: Return the category and order within the category of this item.
- \* **abstract SubMenu getSubMenu()**: Get the sub-menu to be invoked when this item is selected, if it has one.
- \* **abstract CharSequence getTitle()**: Retrieve the current title of the item.
- \* **abstract CharSequence getTitleCondensed()**: Retrieve the current condensed title of the item.
- \* **default CharSequence getTooltipText()**: Retrieve the tooltip text associated with this menu item.
- \* **abstract boolean hasSubMenu()**: Check whether this item has an associated sub-menu.
- \* **abstract boolean isActionViewExpanded()**: Returns true if this menu item's action view has been expanded.



- \* **abstract boolean isCheckedable():** Return whether the item can currently display a check mark.
- \* **abstract boolean isChecked():** Return whether the item is currently displaying a check mark.
- \* **abstract boolean isEnabled():** Return the enabled state of the menu item.
- \* **abstract boolean isVisible():** Return the visibility of the menu item.
- \* **abstract MenuItem setActionProvider(ActionProvider actionProvider):** Sets the ActionProvider responsible for creating an action view if the item is placed on the action bar.
- \* **abstract MenuItem setActionView(int resId):** Set an action view for this menu item.
- \* **abstract MenuItem setActionView(View view):** Set an action view for this menu item.
- \* **abstract MenuItem setAlphabeticShortcut(char alphaChar):** Change the alphabetic shortcut associated with this item.
- \* **default MenuItem setAlphabeticShortcut(char alphaChar, int alphaModifiers):** Change the alphabetic shortcut associated with this item.
- \* **abstract MenuItem setCheckable(boolean checkable):** Control whether this item can display a check mark.
- \* **abstract MenuItem setChecked(boolean checked):** Control whether this item is shown with a check mark.
- \* **default MenuItem setContentDescription(CharSequence contentDescription):** Change the content description associated with this menu item.
- \* **abstract MenuItem setEnabled(boolean enabled):** Sets whether the menu item is enabled.
- \* **abstract MenuItem setIcon(Drawable icon):** Change the icon associated with this item.
- \* **abstract MenuItem setIcon(int iconRes):** Change the icon associated with this item.
- \* **default MenuItem setIconTintBlendMode(BlendMode blendMode):** Specifies the blending mode used to apply the tint specified by setIconTintList(android.content.res.ColorStateList) to this item's icon.
- \* **default MenuItem setIconTintList(ColorStateList tint):** Applies a tint to this item's icon.
- \* **default MenuItem setIconTintMode(PorterDuff.Mode tintMode):** Specifies the blending mode used to apply the tint specified by setIconTintList(android.content.res.ColorStateList) to this item's icon.
- \* **abstract MenuItem setIntent(Intent intent):** Change the Intent associated with this item.
- \* **default MenuItem setNumericShortcut(char numericChar, int numericModifiers):** Change the numeric shortcut and modifiers associated with this item.
- \* **abstract MenuItem setNumericShortcut(char numericChar):** Change the numeric shortcut associated with this item.
- \* **abstract MenuItem setOnActionExpandListener(MenuItem.OnActionExpandListener listener):** Set an OnActionExpandListener on this menu item to be notified when the associated action view is expanded or collapsed.

- \* **abstract MenuItem setOnMenuItemClickListener(MenuItem.OnMenuItemClickListener menuItemClickListener):** Set a custom listener for invocation of this menu item.
- \* **abstract MenuItem setShortcut(char numericChar, char alphaChar):** Change both the numeric and alphabetic shortcut associated with this item.
- \* **default MenuItem setShortcut(char numericChar, char alphaChar, int numericModifiers, int alphaModifiers):** Change both the numeric and alphabetic shortcut associated with this item.
- \* **abstract void setShowAsAction(int actionEnum):** Sets how this item should display in the presence of an Action Bar.
- \* **abstract MenuItem setShowAsActionFlags(int actionEnum):** Sets how this item should display in the presence of an Action Bar.
- \* **abstract MenuItem setTitle(CharSequence title):** Change the title associated with this item.
- \* **abstract MenuItem setTitle(int title):** Change the title associated with this item.
- \* **abstract MenuItem setTitleCondensed(CharSequence title):** Change the condensed title associated with this item.
- \* **default MenuItem setTooltipText(CharSequence tooltipText):** Change the tooltip text associated with this menu item.
- \* **abstract MenuItem setVisible(boolean visible):** Sets the visibility of the menu item.

– **Constants**

- \* **int SHOW\_AS\_ACTION\_ALWAYS:** Always show this item as a button in an Action Bar.
- \* **int SHOW\_AS\_ACTION\_COLLAPSE\_ACTION\_VIEW:** This item's action view collapses to a normal menu item.
- \* **int SHOW\_AS\_ACTION\_IF\_ROOM:** Show this item as a button in an Action Bar if the system decides there is room for it.
- \* **int SHOW\_AS\_ACTION\_NEVER:** Never show this item as a button in an Action Bar.
- \* **int SHOW\_AS\_ACTION\_WITH\_TEXT:** When this item is in the action bar, always show it with a text label even if it also has an icon specified.

## 1.60 ContextMenu (interface)

- **Hierarchy**

android.view.Menu → android.view.ContextMenu

- **Include**

```
0  android.view.ContextMenu
```

- **Public abstract methods**

- \* **abstract void clearHeader():** Clears the header of the context menu.
- \* **abstract ContextMenu setHeaderIcon(int iconRes):** Sets the context menu header's icon to the icon given in iconRes resource id.
- \* **abstract ContextMenu setHeaderIcon(Drawable icon):** Sets the context menu header's icon to the icon given in icon Drawable.
- \* **abstract ContextMenu setHeaderTitle(int titleRes):** Sets the context menu header's title to the title given in titleRes resource identifier.
- \* **abstract ContextMenu setHeaderTitle(CharSequence title):** Sets the context menu header's title to the title given in title.
- \* **abstract ContextMenu setHeaderView(View view):** Sets the header of the context menu to the View given in view.

## 1.61 PopupMenu

### – Hierarchy

java.lang.Object → android.widget.PopupMenu

### – Include

```
0  android.widget.PopupMenu
```

### – Constructors

```
0  PopupMenu(Context context, View anchor)
1  PopupMenu(Context context, View anchor, int gravity)
2  PopupMenu(Context context, View anchor, int gravity,
    ↪ int popupStyleAttr, int popupStyleRes)
```

### – Public methods

- \* **void dismiss()**: Dismiss the menu popup.
- \* **View.OnTouchListener getDragToOpenListener()**: Returns an OnTouchListener that can be added to the anchor view to implement drag-to-open behavior.
- \* **int getGravity()**:
- \* **Menu getMenu()**: Returns the Menu associated with this popup.
- \* **MenuInflater getMenuInflater()**:
- \* **void inflate(int menuRes)**: Inflate a menu resource into this PopupMenu.
- \* **void setForceShowIcon(boolean forceShowIcon)**: Sets whether the popup menu's adapter is forced to show icons in the menu item views.
- \* **void setGravity(int gravity)**: Sets the gravity used to align the popup window to its anchor view.
- \* **void setOnDismissListener(PopupMenu.OnDismissListener listener)**: Sets a listener that will be notified when this menu is dismissed.
- \* **void setOnMenuItemClickListener(PopupMenu.OnMenuItemClickListener listener)**: Sets a listener that will be notified when the user selects an item from the menu.
- \* **void show()**: Show the menu popup anchored to the view specified during construction.

## 1.62 SubMenu (interface)

### – Signature

```
0 public interface SubMenu implements Menu
```

### – Include

```
0 android.view.SubMenu
```

### – Public abstract methods

- \* **abstract void clearHeader():** Clears the header of the submenu.
- \* **abstract MenuItem getItem():** Gets the MenuItem that represents this submenu in the parent menu.
- \* **abstract SubMenu setHeaderIcon(int iconRes):** Sets the submenu header's icon to the icon given in iconRes resource id.
- \* **abstract SubMenu setHeaderIcon(Drawable icon):** Sets the submenu header's icon to the icon given in icon Drawable.
- \* **abstract SubMenu setHeaderTitle(int titleRes):** Sets the submenu header's title to the title given in titleRes resource identifier.
- \* **abstract SubMenu setHeaderTitle(CharSequence title):** Sets the submenu header's title to the title given in title.
- \* **abstract SubMenu setHeaderView(View view):** Sets the header of the submenu to the View given in view.
- \* **abstract SubMenu setIcon(Drawable icon):** Change the icon associated with this submenu's item in its parent menu.
- \* **abstract SubMenu setIcon(int iconRes):** Change the icon associated with this submenu's item in its parent menu.

## 1.63 MenuInflater

- **Hierarchy**

java.lang.Object → android.view.MenuInflater

- **Include**

```
0  android.view.MenuInflater
```

- **Constructors**

```
0  MenuInflater(Context context)
```

- **Public methods**

- \* **void inflate(int menuRes, Menu menu):** Inflate a menu hierarchy from the specified XML resource.

## 1.64 Toast

### – Hierarchy

java.lang.Object → android.widget.Toast

### – Include

```
0  android.widget.Toast
```

### – Constructors

```
0  Toast(Context context)
```

### – Public methods

- \* **void addCallback(Toast.Callback callback)**: Adds a callback to be notified when the toast is shown or hidden.
- \* **void cancel()**: Close the view if it's showing, or don't show it if it isn't showing yet.
- \* **int getDuration()**: Return the duration.
- \* **int getGravity()**: Get the location at which the notification should appear on the screen.
- \* **float getHorizontalMargin()**: Return the horizontal margin.
- \* **float getVerticalMargin()**: Return the vertical margin.
- \* **View getView()**: This method was deprecated in API level 30. Custom toast views are deprecated. Apps can create a standard text toast with the `makeText(android.content.Context, java.lang.CharSequence, int)` method, or use a Snackbar when in the foreground. Starting from Android Build.VERSION\_CODES.R, apps targeting API level Build.VERSION\_CODES.R or higher that are in the background will not have custom toast views displayed.
- \* **int getXOffset()**: Return the X offset in pixels to apply to the gravity's location.
- \* **int getYOffset()**: Return the Y offset in pixels to apply to the gravity's location.
- \* **static Toast makeText(Context context, int resId, int duration)**: Make a standard toast that just contains text from a resource.
- \* **static Toast makeText(Context context, CharSequence text, int duration)**: Make a standard toast that just contains text.
- \* **void removeCallback(Toast.Callback callback)**: Removes a callback previously added with `addCallback(android.widget.Toast.Callback)`.
- \* **void setDuration(int duration)**: Set how long to show the view for.
- \* **void setGravity(int gravity, int xOffset, int yOffset)**: Set the location at which the notification should appear on the screen.
- \* **void setMargin(float horizontalMargin, float verticalMargin)**: Set the margins of the view.
- \* **void setText(int resId)**: Update the text in a Toast that was previously created using one of the `makeText()` methods.
- \* **void setText(CharSequence s)**: Update the text in a Toast that was previously created using one of the `makeText()` methods.

- \* **void setView(View view):** This method was deprecated in API level 30. Custom toast views are deprecated. Apps can create a standard text toast with the `makeText(android.content.Context, java.lang.CharSequence, int)` method, or use a Snackbar when in the foreground. Starting from Android Build.VERSION\_CODES.R, apps targeting API level Build.VERSION\_CODES.R or higher that are in the background will not have custom toast views displayed.
- \* **void show():** Show the view for the specified duration.

– **Constants**

- \* **int LENGTH\_LONG:** Show the view or text notification for a long period of time.
- \* **int LENGTH\_SHORT:** Show the view or text notification for a short period of time.



## 1.65 LayoutInflater (Abstract class)

### – Hierarchy

java.lang.Object → android.view.LayoutInflater

### – Include

```
0  android.view.LayoutInflater
```

### – Constructors (Protected)

```
0  LayoutInflater(Context context)
1  LayoutInflater(LayoutInflater original, Context
   ↪   newContext)
```

### – Public methods

- \* **abstract LayoutInflater cloneInContext(Context newContext)**: Create a copy of the existing LayoutInflater object, with the copy pointing to a different Context than the original.
- \* **final View onCreateView(Context viewContext, String name, String prefix, AttributeSet attrs)**: Low-level function for instantiating a view by name.
- \* **final View onCreateView(String name, String prefix, AttributeSet attrs)**: Low-level function for instantiating a view by name.
- \* **static LayoutInflater from(Context context)**: Obtains the LayoutInflater from the given context.
- \* **Context getContext()**: Return the context we are running in, for access to resources, class loader, etc.
- \* **final LayoutInflater.Factory getFactory()**: Return the current Factory (or null).
- \* **final LayoutInflater.Factory2 getFactory2()**: Return the current Factory2.
- \* **LayoutInflater.Filter getFilter()**:
- \* **View inflate(int resource, ViewGroup root)**: Inflate a new view hierarchy from the specified xml resource.
- \* **View inflate(XmlPullParser parser, ViewGroup root)**: Inflate a new view hierarchy from the specified xml node.
- \* **View inflate(XmlPullParser parser, ViewGroup root, boolean attachToRoot)**: Inflate a new view hierarchy from the specified XML node.
- \* **View inflate(int resource, ViewGroup root, boolean attachToRoot)**: Inflate a new view hierarchy from the specified xml resource.
- \* **View onCreateView(Context viewContext, View parent, String name, AttributeSet attrs)**: Version of onCreateView(android.view.View, java.lang.String, android.util.AttributeSet) that also takes the inflation context.
- \* **void setFactory(LayoutInflater.Factory factory)**: Attach a custom Factory interface for creating views while using this LayoutInflater.
- \* **void setFactory2(LayoutInflater.Factory2 factory)**: Like setFactory(Factory), but allows you to set a Factory2 interface.
- \* **void setFilter(LayoutInflater.Filter filter)**: Sets the Filter to by this LayoutInflater.

– **Protected methods**

- \* **View onCreateView(View parent, String name, AttributeSet attrs)**: Version of onCreateView(java.lang.String, android.util.AttributeSet) that also takes the future parent of the view being constructed.
- \* **View onCreateView(String name, AttributeSet attrs)**: This routine is responsible for creating the correct subclass of View given the xml element name.

## 1.66 SQLiteDatabase

### – Hierarchy

java.lang.Object → android.database.sqlite.SQLiteClosable →  
android.database.sqlite.SQLiteDatabase

### – Include

```
o  android.database.sqlite.SQLiteDatabase
```

### – Public methods

- \* **void beginTransaction():** Begins a transaction in EXCLUSIVE mode.
- \* **void beginTransactionNonExclusive():** Begins a transaction in IMMEDIATE mode.
- \* **void beginTransactionReadOnly():** Begins a transaction in DEFERRED mode, with the android-specific constraint that the transaction is read-only.
- \* **void beginTransactionWithListener(SQLiteTransactionListener transactionListener):** Begins a transaction in EXCLUSIVE mode.
- \* **void beginTransactionWithListenerNonExclusive(SQLiteTransactionListener transactionListener):** Begins a transaction in IMMEDIATE mode.
- \* **void beginTransactionWithListenerReadOnly(SQLiteTransactionListener transactionListener):** Begins a transaction in read-only mode with a SQLiteTransactionListener listener.
- \* **SQLiteStatement compileStatement(String sql):** Compiles an SQL statement into a reusable pre-compiled statement object.
- \* **static SQLiteDatabase create(SQLiteDatabase.CursorFactory factory):** Create a memory backed SQLite database.
- \* **static SQLiteDatabase createInMemory(SQLiteDatabase.OpenParams openParams):** Create a memory backed SQLite database.
- \* **SQLiteRawStatement createRawStatement(String sql):** Return a SQLiteRawStatement connected to the database.
- \* **int delete(String table, String whereClause, String[] whereArgs):** Convenience method for deleting rows in the database.
- \* **static boolean deleteDatabase(File file):** Deletes a database including its journal file and other auxiliary files that may have been created by the database engine.
- \* **void disableWriteAheadLogging():** This method disables the features enabled by enableWriteAheadLogging().
- \* **boolean enableWriteAheadLogging():** Write-ahead logging enables parallel execution of queries from multiple threads on the same database, and reduces the likelihood of stalling on filesystem syncs.
- \* **void endTransaction():** End a transaction.
- \* **void execPerConnectionSQL(String sql, Object[] bindArgs):** Execute the given SQL statement on all connections to this database.
- \* **void execSQL(String sql):** Execute a single SQL statement that is NOT a SELECT or any other SQL statement that returns data.
- \* **void execSQL(String sql, Object[] bindArgs):** Execute a single SQL statement that is NOT a SELECT/INSERT/UPDATE/DELETE.
- \* **static String findEditTable(String tables):** Finds the name of the first table, which is editable.

- \* **List<Pair<String, String>** **getAttachedDbs()**: Returns list of full path-names of all attached databases including the main database by executing 'pragma database\_list' on the database.
- \* **long getLastChangedRowCount()**: Return the number of database rows that were inserted, updated, or deleted by the most recent SQL statement within the current transaction.
- \* **long getLastInsertRowId()**: Return the "rowid" of the last row to be inserted on the current connection.
- \* **long getMaximumSize()**: Returns the maximum size the database may grow to.
- \* **long getPageSize()**: Returns the current database page size, in bytes.
- \* **String getPath()**: Gets the path to the database file.
- \* **Map<String, String> getSyncedTables()**: This method was deprecated in API level 15. This method no longer serves any useful purpose and has been deprecated.
- \* **long getTotalChangedRowCount()**: Return the total number of database rows that have been inserted, updated, or deleted on the current connection since it was created.
- \* **int getVersion()**: Gets the database version.
- \* **boolean inTransaction()**: Returns true if the current thread has a transaction pending.
- \* **long insert(String table, String nullColumnHack, ContentValues values)**: Convenience method for inserting a row into the database.
- \* **long insertOrThrow(String table, String nullColumnHack, ContentValues values)**: Convenience method for inserting a row into the database.
- \* **long insertWithOnConflict(String table, String nullColumnHack, ContentValues initialValues, int conflictAlgorithm)**: General method for inserting a row into the database.
- \* **boolean isDatabaseIntegrityOk()**: Runs 'pragma integrity\_check' on the given database (and all the attached databases) and returns true if the given database (and all its attached databases) pass integrity\_check, false otherwise.
- \* **boolean isDbLockedByCurrentThread()**: Returns true if the current thread is holding an active connection to the database.
- \* **boolean isDbLockedByOtherThreads()**: This method was deprecated in API level 16. Always returns false. Do not use this method.
- \* **boolean isOpen()**: Returns true if the database is currently open.
- \* **boolean isReadOnly()**: Returns true if the database is opened as read only.
- \* **boolean isWriteAheadLoggingEnabled()**: Returns true if write-ahead logging has been enabled for this database.
- \* **void markTableSyncable(String table, String deletedTable)**: This method was deprecated in API level 15. This method no longer serves any useful purpose and has been deprecated.
- \* **void markTableSyncable(String table, String foreignKey, String updateTable)**: This method was deprecated in API level 15. This method no longer serves any useful purpose and has been deprecated.
- \* **boolean needUpgrade(int newVersion)**: Returns true if the new version code is greater than the current database version.

- \* **static SQLiteDatabase openDatabase(String path, SQLiteDatabase.CursorFactory factory, int flags):** Open the database according to the flags OPEN\_READWRITE OPEN\_READONLY CREATE\_IF\_NECESSARY and/or NO\_LOCALIZED\_COLLATORS.
- \* **static SQLiteDatabase openDatabase(File path, SQLiteDatabase.OpenParams openParams):** Open the database according to the specified parameters
- \* **static SQLiteDatabase openDatabase(String path, SQLiteDatabase.CursorFactory factory, int flags, DatabaseErrorHandler errorHandler):** Open the database according to the flags OPEN\_READWRITE OPEN\_READONLY CREATE\_IF\_NECESSARY and/or NO\_LOCALIZED\_COLLATORS.
- \* **static SQLiteDatabase openOrCreateDatabase(File file, SQLiteDatabase.CursorFactory factory):** Equivalent to openDatabase(file.getPath(), factory, CREATE\_IF\_NECESSARY).
- \* **static SQLiteDatabase openOrCreateDatabase(String path, SQLiteDatabase.CursorFactory factory, DatabaseErrorHandler errorHandler):** Equivalent to openDatabase(path, factory, CREATE\_IF\_NECESSARY, errorHandler).
- \* **static SQLiteDatabase openOrCreateDatabase(String path, SQLiteDatabase.CursorFactory factory):** Equivalent to openDatabase(path, factory, CREATE\_IF\_NECESSARY).
- \* **Cursor query(boolean distinct, String table, String[] columns, String selection, String[] selectionArgs, String groupBy, String having, String orderBy, String limit):** Query the given URL, returning a Cursor over the result set.
- \* **Cursor query(String table, String[] columns, String selection, String[] selectionArgs, String groupBy, String having, String orderBy, String limit):** Query the given table, returning a Cursor over the result set.
- \* **Cursor query(boolean distinct, String table, String[] columns, String selection, String[] selectionArgs, String groupBy, String having, String orderBy, String limit, CancellationSignal cancellationSignal):** Query the given URL, returning a Cursor over the result set.
- \* **Cursor query(String table, String[] columns, String selection, String[] selectionArgs, String groupBy, String having, String orderBy):** Query the given table, returning a Cursor over the result set.
- \* **Cursor queryWithFactory(SQLiteDatabase.CursorFactory cursorFactory, boolean distinct, String table, String[] columns, String selection, String[] selectionArgs, String groupBy, String having, String orderBy, String limit, CancellationSignal cancellationSignal):** Query the given URL, returning a Cursor over the result set.
- \* **Cursor queryWithFactory(SQLiteDatabase.CursorFactory cursorFactory, boolean distinct, String table, String[] columns, String selection, String[] selectionArgs, String groupBy, String having, String orderBy, String limit):** Query the given URL, returning a Cursor over the result set.
- \* **Cursor rawQuery(String sql, String[] selectionArgs, CancellationSignal cancellationSignal):** Runs the provided SQL and returns a Cursor over the result set.
- \* **Cursor rawQuery(String sql, String[] selectionArgs):** Runs the provided SQL and returns a Cursor over the result set.
- \* **Cursor rawQueryWithFactory(SQLiteDatabase.CursorFactory cursorFactory, String sql, String[] selectionArgs, String editTable, Can-**

**cancellationSignal cancellationSignal**): Runs the provided SQL and returns a cursor over the result set.

- \* **Cursor rawQueryWithFactory(SQLiteDatabase.CursorFactory cursorFactory, String sql, String[] selectionArgs, String editTable)**: Runs the provided SQL and returns a cursor over the result set.
- \* **static int releaseMemory()**: Attempts to release memory that SQLite holds but does not require to operate properly.
- \* **long replace(String table, String nullColumnHack, ContentValues initialValues)**: Convenience method for replacing a row in the database.
- \* **long replaceOrThrow(String table, String nullColumnHack, ContentValues initialValues)**: Convenience method for replacing a row in the database.
- \* **void setCustomAggregateFunction(String functionName, BinaryOperator<String> aggregateFunction)**: Register a custom aggregate function that can be called from SQL expressions.
- \* **void setCustomScalarFunction(String functionName, UnaryOperator<String> scalarFunction)**: Register a custom scalar function that can be called from SQL expressions.
- \* **void setForeignKeyConstraintsEnabled(boolean enable)**: Sets whether foreign key constraints are enabled for the database.
- \* **void setLocale(Locale locale)**: Sets the locale for this database.
- \* **void setLockingEnabled(boolean lockingEnabled)**: This method was deprecated in API level 16. This method now does nothing. Do not use.
- \* **void setMaxSqlCacheSize(int cacheSize)**: Sets the maximum size of the prepared-statement cache for this database.
- \* **long setMaximumSize(long numBytes)**: Sets the maximum size the database will grow to.
- \* **void setPageSize(long numBytes)**: Sets the database page size.
- \* **void setTransactionSuccessful()**: Marks the current transaction as successful.
- \* **void setVersion(int version)**: Sets the database version.
- \* **String toString()**: Returns a string representation of the object.
- \* **int update(String table, ContentValues values, String whereClause, String[] whereArgs)**: Convenience method for updating rows in the database.
- \* **int updateWithOnConflict(String table, ContentValues values, String whereClause, String[] whereArgs, int conflictAlgorithm)**: Convenience method for updating rows in the database.
- \* **void validateSql(String sql, CancellationSignal cancellationSignal)**: Verifies that a SQL SELECT statement is valid by compiling it.
- \* **boolean yieldIfContended()**: This method was deprecated in API level 15. If the db is locked more than once (because of nested transactions) then the lock will not be yielded. Use `yieldIfContendedSafely` instead.
- \* **boolean yieldIfContendedSafely()**: Temporarily end the transaction to let other threads run.
- \* **boolean yieldIfContendedSafely(long sleepAfterYieldDelay)**: Temporarily end the transaction to let other threads run.

#### – Protected methods

- \* **void finalize()**: Called by the garbage collector on an object when garbage collection determines that there are no more references to the object.
- \* **void onAllReferencesReleased()**: Called when the last reference to the object was released by a call to `releaseReference()` or `close()`.

– Constants

- \* **int CONFLICT\_ABORT**: When a constraint violation occurs, no ROLLBACK is executed so changes from prior commands within the same transaction are preserved.
- \* **int CONFLICT\_FAIL**: When a constraint violation occurs, the command aborts with a return code SQLITE\_CONSTRAINT.
- \* **int CONFLICT\_IGNORE**: When a constraint violation occurs, the one row that contains the constraint violation is not inserted or changed.
- \* **int CONFLICT\_NONE**: Use the following when no conflict action is specified.
- \* **int CONFLICT\_REPLACE**: When a UNIQUE constraint violation occurs, the pre-existing rows that are causing the constraint violation are removed prior to inserting or updating the current row.
- \* **int CONFLICT\_ROLLBACK**: When a constraint violation occurs, an immediate ROLLBACK occurs, thus ending the current transaction, and the command aborts with a return code of SQLITE\_CONSTRAINT.
- \* **int CREATE\_IF\_NECESSARY**: Open flag: Flag for openDatabase(File, OpenParams) to create the database file if it does not already exist.
- \* **int ENABLE\_WRITE\_AHEAD\_LOGGING**: Open flag: Flag for openDatabase(File, OpenParams) to open the database file with write-ahead logging enabled by default.
- \* **String JOURNAL\_MODE\_DELETE**: The DELETE journaling mode is the normal behavior.
- \* **String JOURNAL\_MODE\_MEMORY**: The MEMORY journaling mode stores the rollback journal in volatile RAM.
- \* **String JOURNAL\_MODE\_OFF**: The OFF journaling mode disables the rollback journal completely.
- \* **String JOURNAL\_MODE\_PERSIST**: The PERSIST journaling mode prevents the rollback journal from being deleted at the end of each transaction.
- \* **String JOURNAL\_MODE\_TRUNCATE**: The TRUNCATE journaling mode commits transactions by truncating the rollback journal to zero-length instead of deleting it.
- \* **String JOURNAL\_MODE\_WAL**: The WAL journaling mode uses a write-ahead log instead of a rollback journal to implement transactions.
- \* **int MAX\_SQL\_CACHE\_SIZE**: Absolute max value that can be set by setMaxSqlCacheSize(int).
- \* **int NO\_LOCALIZED\_COLLATORS**: Open flag: Flag for openDatabase(File, OpenParams) to open the database without support for localized collators.
- \* **int OPEN\_READONLY**: Open flag: Flag for openDatabase(File, OpenParams) to open the database for reading only.
- \* **int OPEN\_READWRITE**: Open flag: Flag for openDatabase(File, OpenParams) to open the database for reading and writing. If the disk is full, this may fail even before you actually write anything.
- \* **int SQLITE\_MAX\_LIKE\_PATTERN\_LENGTH**: Maximum Length Of A LIKE Or GLOB Pattern The pattern matching algorithm used in the default LIKE and GLOB implementation of SQLite can exhibit  $O(N^2)$  performance (where  $N$  is the number of characters in the pattern) for certain pathological cases.
- \* **String SYNC\_MODE\_EXTRA**: The EXTRA sync mode is like FULL sync mode with the addition that the directory containing a rollback journal

is synced after that journal is unlinked to commit a transaction in DELETE journal mode.

- \* **String SYNC\_MODE\_FULL:** In FULL sync mode the SQLite database engine will use the xSync method of the VFS to ensure that all content is safely written to the disk surface prior to continuing.
- \* **String SYNC\_MODE\_NORMAL:** The NORMAL sync mode, the SQLite database engine will still sync at the most critical moments, but less often than in FULL mode.
- \* **String SYNC\_MODE\_OFF:** In OFF sync mode SQLite continues without syncing as soon as it has handed data off to the operating system.



## 1.67 Cursor (Interface)

### – Signature :

```
0 public interface Cursor implements Closeable
```

### – Include

```
0 android.database.Cursor
```

### – Public abstract methods

- \* **abstract void close():** Closes the Cursor, releasing all of its resources and making it completely invalid.
- \* **abstract void copyStringToBuffer(int columnIndex, CharArrayBuffer buffer):** Retrieves the requested column text and stores it in the buffer provided.
- \* **abstract void deactivate():** This method was deprecated in API level 16. Since `query()` is deprecated, so too is this.
- \* **abstract byte[] getBlob(int columnIndex):** Returns the value of the requested column as a byte array.
- \* **abstract int getColumnCount():** Return total number of columns
- \* **abstract int getColumnIndex(String columnName):** Returns the zero-based index for the given column name, or -1 if the column doesn't exist.
- \* **abstract int getColumnIndexOrThrow(String columnName):** Returns the zero-based index for the given column name, or throws `IllegalArgumentException` if the column doesn't exist.
- \* **abstract String getColumnName(int columnIndex):** Returns the column name at the given zero-based column index.
- \* **abstract String[] getColumnNames():** Returns a string array holding the names of all of the columns in the result set in the order in which they were listed in the result.
- \* **abstract int getCount():** Returns the numbers of rows in the cursor.
- \* **abstract double getDouble(int columnIndex):** Returns the value of the requested column as a double.
- \* **abstract Bundle getExtras():** Returns a bundle of extra values.
- \* **abstract float getFloat(int columnIndex):** Returns the value of the requested column as a float.
- \* **abstract int getInt(int columnIndex):** Returns the value of the requested column as an int.
- \* **abstract long getLong(int columnIndex):** Returns the value of the requested column as a long.
- \* **abstract Uri getNotificationUri():** Return the URI at which notifications of changes in this Cursor's data will be delivered, as previously set by `setNotificationUri(ContentResolver, Uri)`.
- \* **default List<Uri> getNotificationUris():** Return the URIs at which notifications of changes in this Cursor's data will be delivered, as previously set by `setNotificationUris(ContentResolver, List)`.
- \* **abstract int getPosition():** Returns the current position of the cursor in the row set.

- \* **abstract short getShort(int columnIndex):** Returns the value of the requested column as a short.
- \* **abstract String getString(int columnIndex):** Returns the value of the requested column as a String.
- \* **abstract int getType(int columnIndex):** Returns data type of the given column's value.
- \* **abstract boolean getWantsAllOnMoveCalls():** onMove() will only be called across processes if this method returns true.
- \* **abstract boolean isAfterLast():** Returns whether the cursor is pointing to the position after the last row.
- \* **abstract boolean isBeforeFirst():** Returns whether the cursor is pointing to the position before the first row.
- \* **abstract boolean isClosed():** return true if the cursor is closed
- \* **abstract boolean isFirst():** Returns whether the cursor is pointing to the first row.
- \* **abstract boolean isLast():** Returns whether the cursor is pointing to the last row.
- \* **abstract boolean isNull(int columnIndex):** Returns true if the value in the indicated column is null.
- \* **abstract boolean move(int offset):** Move the cursor by a relative amount, forward or backward, from the current position.
- \* **abstract boolean moveToFirst():** Move the cursor to the first row.
- \* **abstract boolean moveToLast():** Move the cursor to the last row.
- \* **abstract boolean moveToNext():** Move the cursor to the next row.
- \* **abstract boolean moveToPosition(int position):** Move the cursor to an absolute position.
- \* **abstract boolean moveToPrevious():** Move the cursor to the previous row.
- \* **abstract void registerContentObserver(ContentObserver observer):** Register an observer that is called when changes happen to the content backing this cursor.
- \* **abstract void registerDataSetObserver(DataSetObserver observer):** Register an observer that is called when changes happen to the contents of the this cursors data set, for example, when the data set is changed via query(), deactivate(), or close().
- \* **abstract boolean query():** This method was deprecated in API level 15. Don't use this. Just request a new cursor, so you can do this asynchronously and update your list view once the new cursor comes back.
- \* **abstract Bundle respond(Bundle extras):** This is an out-of-band way for the user of a cursor to communicate with the cursor.
- \* **abstract void setExtras(Bundle extras):** Sets a Bundle that will be returned by getExtras().
- \* **abstract void setNotificationUri(ContentResolver cr, Uri uri):** Register to watch a content URI for changes.
- \* **default void setNotificationUris(ContentResolver cr, List<Uri> uris):** Similar to setNotificationUri(android.content.ContentResolver, android.net.Uri), except this version allows to watch multiple content URIs for changes.
- \* **abstract void unregisterContentObserver(ContentObserver observer):** Unregister an observer that has previously been registered with this cursor via registerContentObserver(ContentObserver).

\* **abstract void unregisterDataSetObserver(DataSetObserver observer):**  
Unregister an observer that has previously been registered with this cursor  
via registerContentObserver(ContentObserver).

## 1.68 ScrollView

### – Hierarchy

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.FrameLayout → android.widget.ScrollView

### – Include

```
0  android.widget.ScrollView
```

### – Constructors

```
0  ScrollView(Context context)
1  ScrollView(Context context, AttributeSet attrs)
2  ScrollView(Context context, AttributeSet attrs, int
   ↪ defStyleAttr)
3  ScrollView(Context context, AttributeSet attrs, int
   ↪ defStyleAttr, int defStyleRes)
```

### – Public methods

- \* **void addView(View child, int index):** Adds a child view.
- \* **void addView(View child, ViewGroup.LayoutParams params):** Adds a child view with the specified layout parameters.
- \* **void addView(View child, int index, ViewGroup.LayoutParams params):** Adds a child view with the specified layout parameters.
- \* **void addView(View child):** Adds a child view.
- \* **boolean arrowScroll(int direction):** Handle scrolling in response to an up or down arrow click.
- \* **void computeScroll():** Called by a parent to request that a child update its values for mScrollX and mScrollY if necessary.
- \* **boolean dispatchKeyEvent(KeyEvent event):** Dispatch a key event to the next view on the focus path.
- \* **void draw(Canvas canvas):** Manually render this view (and all of its children) to the given Canvas.
- \* **boolean executeKeyEvent(KeyEvent event):** You can call this function yourself to have the scroll view perform scrolling from a key event, just as if the event had been dispatched to it by the view hierarchy.
- \* **void fling(int velocityY):** Fling the scroll view
- \* **boolean fullScroll(int direction):** Handles scrolling in response to a "home/end" shortcut press.
- \* **CharSequence getAccessibilityClassName():** Return the class name of this object to be used for accessibility purposes.
- \* **int getBottomEdgeEffectColor():** Returns the bottom edge effect color.
- \* **int getMaxScrollAmount():** int getTopEdgeEffectColor()
- \* **boolean isFillViewport():** Indicates whether this ScrollView's content is stretched to fill the viewport.
- \* **boolean isSmoothScrollingEnabled():**
- \* **boolean onGenericMotionEvent(MotionEvent event):** Implement this method to handle generic motion events.

- \* **boolean onInterceptTouchEvent(MotionEvent ev)**: Implement this method to intercept all touch screen motion events.
- \* **boolean onNestedFling(View target, float velocityX, float velocityY, boolean consumed)**: Request a fling from a nested scroll.
- \* **void onNestedScroll(View target, int dxConsumed, int dyConsumed, int dxUnconsumed, int dyUnconsumed)**: React to a nested scroll in progress.
- \* **void onNestedScrollAccepted(View child, View target, int axes)**: React to the successful claiming of a nested scroll operation.
- \* **boolean onStartNestedScroll(View child, View target, int nestedScrollAxes)**: React to a descendant view initiating a nestable scroll operation, claiming the nested scroll operation if appropriate.
- \* **void onStopNestedScroll(View target)**: React to a nested scroll operation ending.
- \* **boolean onTouchEvent(MotionEvent ev)**: Implement this method to handle pointer events.
- \* **boolean pageScroll(int direction)**: Handles scrolling in response to a "page up/down" shortcut press.
- \* **void requestChildFocus(View child, View focused)**: Called when a child of this parent wants focus
- \* **boolean requestChildRectangleOnScreen(View child, Rect rectangle, boolean immediate)**: Called when a child of this group wants a particular rectangle to be positioned onto the screen.
- \* **void requestDisallowInterceptTouchEvent(boolean disallowIntercept)**: Called when a child does not want this parent and its ancestors to intercept touch events with ViewGroup.onInterceptTouchEvent(MotionEvent).
- \* **void requestLayout()**: Call this when something has changed which has invalidated the layout of this view.
- \* **void scrollTo(int x, int y)**: Set the scrolled position of your view. This version also clamps the scrolling to the bounds of our child.
- \* **void scrollToDescendant(View child)**: Scrolls the view to the given child.
- \* **void setBottomEdgeEffectColor(int color)**: Sets the bottom edge effect color.
- \* **void setEdgeEffectColor(int color)**: Sets the edge effect color for both top and bottom edge effects.
- \* **void setFillViewport(boolean fillViewport)**: Indicates this ScrollView whether it should stretch its content height to fill the viewport or not.
- \* **void setSmoothScrollingEnabled(boolean smoothScrollingEnabled)**: Set whether arrow scrolling will animate its transition.
- \* **void setTopEdgeEffectColor(int color)**: Sets the top edge effect color.
- \* **boolean shouldDelayChildPressedState()**: Return true if the pressed state should be delayed for children or descendants of this ViewGroup.
- \* **final void smoothScrollBy(int dx, int dy)**: Like View.scrollBy, but scroll smoothly instead of immediately.
- \* **final void smoothScrollTo(int x, int y)**: Like scrollTo(int, int), but scroll smoothly instead of immediately.

– **Protected methods**

- \* **int computeScrollDeltaToGetChildRectOnScreen(Rect rect)**: Compute the amount to scroll in the Y direction in order to get a rectangle completely on the screen (or, if taller than the screen, at least the first screen size chunk of it).

- \* **int computeVerticalScrollOffset():** Compute the vertical offset of the vertical scrollbar's thumb within the horizontal range.
- \* **int computeVerticalScrollRange():** The scroll range of a scroll view is the overall height of all of its children.
- \* **float getBottomFadingEdgeStrength():** Returns the strength, or intensity, of the bottom faded edge.
- \* **float getTopFadingEdgeStrength():** Returns the strength, or intensity, of the top faded edge.
- \* **void measureChild(View child, int parentWidthMeasureSpec, int parentHeightMeasureSpec):** Ask one of the children of this view to measure itself, taking into account both the MeasureSpec requirements for this view and its padding.
- \* **void measureChildWithMargins(View child, int parentWidthMeasureSpec, int widthUsed, int parentHeightMeasureSpec, int heightUsed):** Ask one of the children of this view to measure itself, taking into account both the MeasureSpec requirements for this view and its padding and margins.
- \* **void onDetachedFromWindow():** This is called when the view is detached from a window.
- \* **void onLayout(boolean changed, int l, int t, int r, int b):** Called from layout when this view should assign a size and position to each of its children.
- \* **void onMeasure(int widthMeasureSpec, int heightMeasureSpec):** Measure the view and its content to determine the measured width and the measured height.
- \* **void onOverScrolled(int scrollX, int scrollY, boolean clampedX, boolean clampedY):** Called by overScrollBy(int, int, int, int, int, int, int, int, boolean) to respond to the results of an over-scroll operation.
- \* **boolean onRequestFocusInDescendants(int direction, Rect previouslyFocusedRect):** When looking for focus in children of a scroll view, need to be a little more careful not to give focus to something that is scrolled off screen.
- \* **void onRestoreInstanceState(Parcelable state):** Hook allowing a view to re-apply a representation of its internal state that had previously been generated by onSaveInstanceState().
- \* **Parcelable onSaveInstanceState():** Hook allowing a view to generate a representation of its internal state that can later be used to create a new instance with that same state.
- \* **void onSizeChanged(int w, int h, int oldw, int oldh):** This is called during layout when the size of this view has changed.

## 1.69 HorizontalScrollView

### – Hierarchy

java.lang.Object → android.view.View → android.view.ViewGroup →  
android.widget.FrameLayout → android.widget.HorizontalScrollView

### – Include

```
0  android.widget.HorizontalScrollView
```

### – Constructors

```
0  HorizontalScrollView(Context context)
1  HorizontalScrollView(Context context, AttributeSet
    ↪  attrs)
2  HorizontalScrollView(Context context, AttributeSet
    ↪  attrs, int defStyleAttr)
3  HorizontalScrollView(Context context, AttributeSet
    ↪  attrs, int defStyleAttr, int defStyleRes)
```

### – Public methods

- \* **void addView(View child, int index):** Adds a child view.
- \* **void addView(View child):** Adds a child view.
- \* **void addView(View child, ViewGroup.LayoutParams params):** Adds a child view with the specified layout parameters.
- \* **void addView(View child, int index, ViewGroup.LayoutParams params):** Adds a child view with the specified layout parameters.
- \* **boolean arrowScroll(int direction):** Handle scrolling in response to a left or right arrow click.
- \* **void computeScroll():** Called by a parent to request that a child update its values for mScrollX and mScrollY if necessary.
- \* **boolean dispatchKeyEvent(KeyEvent event):** Dispatch a key event to the next view on the focus path.
- \* **void draw(Canvas canvas):** Manually render this view (and all of its children) to the given Canvas.
- \* **boolean executeKeyEvent(KeyEvent event):** You can call this function yourself to have the scroll view perform scrolling from a key event, just as if the event had been dispatched to it by the view hierarchy.
- \* **void fling(int velocityX):** Fling the scroll view
- \* **boolean fullScroll(int direction):** Handles scrolling in response to a "home/end" shortcut press.
- \* **CharSequence getAccessibilityClassName():** Return the class name of this object to be used for accessibility purposes.
- \* **int getLeftEdgeEffectColor():** Returns the left edge effect color.
- \* **int getMaxScrollAmount():**
- \* **int getRightEdgeEffectColor():** Returns the right edge effect color.
- \* **boolean isFillViewport():** Indicates whether this HorizontalScrollView's content is stretched to fill the viewport.
- \* **boolean isSmoothScrollingEnabled():**

- \* **boolean onGenericMotionEvent(MotionEvent event)**: Implement this method to handle generic motion events.
- \* **boolean onInterceptTouchEvent(MotionEvent ev)**: Implement this method to intercept all touch screen motion events.
- \* **boolean onTouchEvent(MotionEvent ev)**: Implement this method to handle pointer events.
- \* **boolean pageScroll(int direction)**: Handles scrolling in response to a "page up/down" shortcut press.
- \* **void requestChildFocus(View child, View focused)**: Called when a child of this parent wants focus
- \* **boolean requestChildRectangleOnScreen(View child, Rect rectangle, boolean immediate)**: Called when a child of this group wants a particular rectangle to be positioned onto the screen.
- \* **void requestDisallowInterceptTouchEvent(boolean disallowIntercept)**: Called when a child does not want this parent and its ancestors to intercept touch events with ViewGroup.onInterceptTouchEvent(MotionEvent).
- \* **void requestLayout()**: Call this when something has changed which has invalidated the layout of this view.
- \* **void scrollTo(int x, int y)**: Set the scrolled position of your view. This version also clamps the scrolling to the bounds of our child.
- \* **void setEdgeEffectColor(int color)**: Sets the edge effect color for both left and right edge effects.
- \* **void setFillViewport(boolean fillViewport)**: Indicates this HorizontalScrollView whether it should stretch its content width to fill the viewport or not.
- \* **void setLeftEdgeEffectColor(int color)**: Sets the left edge effect color.
- \* **void setRightEdgeEffectColor(int color)**: Sets the right edge effect color.
- \* **void setSmoothScrollingEnabled(boolean smoothScrollingEnabled)**: Set whether arrow scrolling will animate its transition.
- \* **boolean shouldDelayChildPressedState()**: Return true if the pressed state should be delayed for children or descendants of this ViewGroup.
- \* **final void smoothScrollBy(int dx, int dy)**: Like View.scrollBy, but scroll smoothly instead of immediately.
- \* **final void smoothScrollTo(int x, int y)**: Like scrollTo(int, int), but scroll smoothly instead of immediately.

#### – Protected methods

- \* **int computeHorizontalScrollOffset()**: Compute the horizontal offset of the horizontal scrollbar's thumb within the horizontal range.
- \* **int computeHorizontalScrollRange()**: The scroll range of a scroll view is the overall width of all of its children.
- \* **int computeScrollDeltaToGetChildRectOnScreen(Rect rect)**: Compute the amount to scroll in the X direction in order to get a rectangle completely on the screen (or, if taller than the screen, at least the first screen size chunk of it).
- \* **float getLeftFadingEdgeStrength()**: Returns the strength, or intensity, of the left faded edge.
- \* **float getRightFadingEdgeStrength()**: Returns the strength, or intensity, of the right faded edge.



- \* **void measureChild(View child, int parentWidthMeasureSpec, int parentHeightMeasureSpec):** Ask one of the children of this view to measure itself, taking into account both the MeasureSpec requirements for this view and its padding.
- \* **void measureChildWithMargins(View child, int parentWidthMeasureSpec, int widthUsed, int parentHeightMeasureSpec, int heightUsed):** Ask one of the children of this view to measure itself, taking into account both the MeasureSpec requirements for this view and its padding and margins.
- \* **void onLayout(boolean changed, int l, int t, int r, int b):** Called from layout when this view should assign a size and position to each of its children.
- \* **void onMeasure(int widthMeasureSpec, int heightMeasureSpec):** Measure the view and its content to determine the measured width and the measured height.
- \* **void onOverScrolled(int scrollX, int scrollY, boolean clampedX, boolean clampedY):** Called by overScrollBy(int, int, int, int, int, int, int, int, boolean) to respond to the results of an over-scroll operation.
- \* **boolean onRequestFocusInDescendants(int direction, Rect previouslyFocusedRect):** When looking for focus in children of a scroll view, need to be a little more careful not to give focus to something that is scrolled off screen.
- \* **void onRestoreInstanceState(Parcelable state):** Hook allowing a view to re-apply a representation of its internal state that had previously been generated by onSaveInstanceState().
- \* **Parcelable onSaveInstanceState():** Hook allowing a view to generate a representation of its internal state that can later be used to create a new instance with that same state.
- \* **void onSizeChanged(int w, int h, int oldw, int oldh):** This is called during layout when the size of this view has changed.