

Quiz Answers
CS-330 Unix and Network Programming

Nathan Warner



**Northern Illinois
University**

Computer Science
Northern Illinois University
March 1, 2024
United States

Contents

1	Quiz 6: Awk	2
2	Quiz 7: Sed	3

Quiz 6: Awk

- Which function in awk is used to divide a string into pieces separated by the field separator and store the pieces in an array ?
 - split
- What is the meaning of the \$0 variable in awk ?
 - it holds the entire record
- awk reads input lines automatically
 - true
- Variables in awk are initialized how ?
 - to 0 or "" depending on context when first used
- Every awk program must use the BEGIN and END patterns.
 - false
- Which command line option allows to specify an awk program in a file ?
 - -f
- awk allows strings as array index.
 - true
- awk can use which character as field separator ?
 - any character
- In awk, strings printed with the "%20s" printf directive will always be left justified.
 - false
- What is the string concatenation operator in awk ?
 - the space character

Quiz 7: Sed

- In sed, the "i" command adds lines before the address
 - True
- In sed, when using a range address, the lines specified need not be consecutive.
 - False
- In sed, the dollar sign (\$) can be used as a single line address. What is its meaning?
 - the last line of input
- If the exclamation mark "!" is used after an sed address, then it will only search for obsolete lines.
 - False
- Which character is used to delimit the search and replacement components of the sed "s" command?
 - any, as long as all 3 are the same
- If sed is invoked as "sed -n" then it sorts its input numerically.
 - False
- The sed editor can be called from a shell script
 - True
- Which of the following utilities can be used to systematically process files?
 - all of the above
- Which of the following is NOT a valid address type for sed?
 - sublet address
- If no address is specified for the sed command then the command is applied to every input line.
 - true