

Cpp Nuances

Nathan Warner



**Northern Illinois
University**

Computer Science
Northern Illinois University
United States

Contents

1	Converting char to std::string	5
1.1	Constructor signature	5
1.2	Example	5
2	std::string::npos	6
2.1	Example	6
3	Narrowing	7
4	Aggregate types	8
4.1	Aggregate initialization	8
4.2	Narrowing is not allowed in aggregate-initialization from an initializer list .	9
4.3	implicit conversion using a single-argument constructor	9
5	Floating point literals	11
6	Size of structs and classes	12
6.1	Padding	13
7	When is trailing return type useful	14
7.1	Decltype on template parameters	14
7.2	Nested structs	14
8	Most vexing parse	15
9	Notes about copy constructors	16
10	Exceptions during a call to new	17
10.1	Exceptions during constructors	17

11	Notes about polymorphism	18
11.1	Polymorphism with arrays and slicing	19
11.1.1	Object Slicing	19
11.1.2	Polymorphism with arrays	20
11.2	Runtime polymorphism, dynamic dispatch, dynamic binding, and the vtable	21
11.2.1	Dynamic dispatch and dynamic binding	21
11.2.2	The Vtable	22
11.3	Can you call pure virtual methods	24
12	The existence of structs and classes	25
13	Note about heap allocated memory in vectors	26
14	Function that takes a const reference can accept rvalues	27
15	Notes about c++ casts	28
15.1	Static_cast	28
15.2	Dynamic_cast	28
15.2.1	When to Use Dynamic Casting	29
15.2.2	RTTI	29
15.3	const_cast	29
15.3.1	Modifying a non-const object that was passed as const	30
15.3.2	Removing const to use overloaded functions	30
15.4	reinterpret_cast	31
15.5	Why are c casts unsafe?	31
16	The compiler and functions	32
16.1	Important: compile time constant variables and memory (constant propa- gation/constant folding)	34
17	The introduction of the nullptr	35
17.1	Ambiguity in Overloaded Functions	35
17.2	Type safety	35
17.3	The type of nullptr	35
17.4	nullptr vs void*	36

18	Brace initialization vs Parenthesized Initialization	37
19	Are chars unsigned?	38
20	Size of types	39
21	Trivially copyable	40
22	POD types (Plain old data)	41
22.1	Trivial type	41
22.2	Standard layout	41
23	Notes about initialization	42
23.1	How many names does brace initialization have?	42
23.1.1	Uniform Initialization (General Term)	42
23.1.2	List Initialization	42
23.1.3	Aggregate Initialization	42
23.1.4	Value Initialization	42
23.1.5	Direct List Initialization	43
23.1.6	Copy List Initialization	43
23.1.7	Narrowing Prevention Initialization	43
23.1.8	Default Member Initialization	43
23.1.9	Copy list initialization and direct list initialization in aggregate types . . .	43
23.2	Other forms of initialization and their names	44
23.2.1	Direct Initialization	45
23.2.2	Copy Initialization	45
23.2.3	Default Initialization	45
24	Notes about destructors	46
24.1	Manual destructor calls	46
25	Notes about constructors	47
25.1	Value initialized vs default initialized	47
25.2	What exactly is =default	47
25.2.1	Non-POD fields	48

25.2.2	With copy constructors	48
25.2.3	Copy Assignment	49
25.2.4	Move constructor	49
25.2.5	Move Assignment	50
25.2.6	Destructor	50
25.2.7	Do you need to write them?	50
25.3	=delete	51
25.4	Rule of five	51
25.5	A confused compiler	51
25.6	Which constructor will be called	52
26	Notes about inheritance	54
26.1	Constructor chain	54
26.2	Destructor chain	54
27	Booleans under the hood: Adding two booleans	55
28	Type Promotion	56
28.1	Ranking	56
29	Notes about static	57
29.1	Static variables inside member functions	57
29.2	Using instances to call static methods	57
29.3	Can you make pure virtual methods static?	57
30	Trying to move const objects	58
31	Smart pointers in conjunction with raw ptrs	59
31.1	Shared_ptr with raw ptrs	59
31.2	Unique_ptr with raw ptrs	59
32	Calling delete on a nullptr	60

Converting char to std::string

Suppose we have a char variable, and we need to "convert" it to a string. To do this we use the string class constructor, which has two parameters, the size of the string to create, and the character to use as the fill.

1.1 Constructor signature

```
0 string(size_t n, char x)
```

1.2 Example

```
0 char c = 'a';  
1 string s(1,c);
```

std::string::npos

Concept 1: In C++, `std::string::npos` is a static member constant value with the greatest possible value for an element of type `size_t`. This value, when used as the length in string operations, typically represents "until the end of the string." It is often used in string manipulation functions to specify that the operation should proceed from the starting position to the end of the string, or until no more characters are found.

□

2.1 Example

```
0 string infix = buffer.substr(index + 2, string::npos);
```

`std::string::npos` is defined as the maximum value representable by the type `size_t`. This value is typically used to signify an error condition or a not-found condition when working with strings and other sequence types. However, when used as a length argument in methods like `std::string::substr`, it effectively becomes a directive to process characters until the end of the string. This is because any attempt to access beyond the end of the string would exceed the string's length, and the methods are designed to stop processing at that point.

Narrowing

Narrowing happens when:

- A value of a larger or more precise type is converted to a smaller or less precise type (e.g., double to int, int to char).
- A floating-point value is converted to an integer type.
- An integer value is converted to a smaller integer type (e.g., int to short) and does not fit within the destination type's range.

Aggregate types

Aggregate types in C++ are simple data structures that hold collections of values and have minimal additional behavior. They are essentially "plain old data" structures that are easy to initialize and manipulate. The term "aggregate" is formally defined by the C++ standard.

A class, struct, or union is considered an aggregate if it satisfies all of the following conditions:

1. No User-Defined Constructors: It must not have any explicitly declared constructors (including default, copy, or move constructors).
2. No Private or Protected Non-Static Data Members: All non-static data members must be public.
3. No Virtual Functions: It must not have any virtual functions.
4. No Base Classes: It must not inherit from another class or struct.
5. No Virtual Base Classes: It must not use virtual inheritance.

For example



4.1 Aggregate initialization

Aggregate initialization in C++ refers to a special form of initialization for aggregate types using an initializer list enclosed in {} braces. This allows you to directly specify values for the members of an aggregate type in the order they are declared.

Each member of the aggregate is initialized with the corresponding value provided in the initializer list. The order of values in the initializer list must match the declaration order of members in the aggregate.

If fewer values are provided in the initializer list than there are members in the aggregate, the remaining members are value-initialized (e.g., zero-initialized for fundamental types).

If the type is not an aggregate (e.g., has a user-defined constructor, private members, or virtual functions), aggregate initialization cannot be used.

```
0  struct S {  
1      int x,y;  
2  };  
3  
4  S s = {1,2};
```

Consider the next example,

```

0  struct S {
1      int x,y;
2
3      S(int x, int y) : x(x), y(y) {}
4  };
5
6  S s = {1,2}; // Works fine

```

Since the class *S* has a user-defined constructor, it is no longer an aggregate type.

Aggregate initialization is not applicable here. Instead, C++ checks for constructors that match the initializer list {1, 2}.

Since it found one, the compiler interprets it as calling the constructor *S*(int x, int y) with the arguments 1 and 2.

In modern C++ (C++11 and later), brace-enclosed initialization is often used for uniform initialization.

If a constructor is available that matches the initializer list, it is called.

4.2 Narrowing is not allowed in aggregate-initialization from an initializer list

The error "narrowing is not allowed in aggregate-initialization from an initializer list" occurs in C++ when you try to initialize an aggregate type (e.g., structs, arrays, or classes with no user-defined constructors) using values in an initializer list, but the values undergo an implicit narrowing conversion that could lose information or precision.

```

0  struct A {
1      int x;
2      float y;
3  };
4
5  A a = {1, 3.14}; // OK, no narrowing
6  A b = {1, 3.14f}; // OK, no narrowing (3.14f is a float literal)
7
8  A c = {1, 3.14}; // ERROR: narrowing from `double` to `float`

```

4.3 implicit conversion using a single-argument constructor

A constructor that takes one argument can be used for implicit conversion of that argument type to the class type.

```

0  struct s {
1      int x;
2      s(int value) : x(value) {} // Single-argument constructor
3  };
4  s s1 = 1;

```

The integer 1 is implicitly converted to an object of type s using the s(int value) constructor.

By default, a single-argument constructor allows implicit conversions. If you want to prevent implicit conversions and require explicit construction, you can use the explicit keyword

```

0  struct s {
1      int x;
2      explicit s(int value) : x(value) {}
3  };
4
5  int main() {
6      s s1 = 1; // ERROR: Explicit constructor prevents implicit
    ↪ conversion
7      s s2(1); // OK: Direct initialization
8  }

```

Floating point literals

Floating point literals in c++ will be of type double. For example,

```
o cout << typeid(4.09).name(); // d
```

Append *f* to the literal to make it a float

```
o cout << typeid(4.09f).name(); // d
```

Size of structs and classes

Consider the code

```
0  struct s { }  
1  cout << sizeof(s) << endl; // 1  
2  
3  s s1;  
4  cout << sizeof(s1) << endl; // 1
```

Notice that empty structs do not have a size of zero. Empty structs have a size of one byte.

A size of zero for a struct would mean that it occupies no memory. If multiple instances of such a struct are created, they would have no unique memory location to occupy. As a result, the compiler would assign the same memory address to all instances, which would violate fundamental rules of object-oriented programming in C++.

Furthermore, giving fields to the struct or class increases the size of that struct or class by size of the type.

```
0  struct s { int x; }  
1  cout << sizeof(s); // 4
```

Notice that the size is **not** 5. Creating functions and creating variables in those functions does not add to the size

```
0  struct s {  
1      void f() {  
2          int x;  
3      }  
4  }  
5  cout << sizeof(s); // 1
```

Creating structs inside structs and even adding fields to the inner structs does not increase the size

```
0  struct s {  
1      struct k { int x; };  
2  };  
3  
4  cout << sizeof(s); // 1  
5  cout << sizeof(s:k); // 4
```

Lastly, constructors and destructors do not increase the size.

It seems only fields increase the size.

6.1 Padding

Consider the following struct

```
0  struct s {  
1      char c; // 1 byte  
2      int x; // 4 bytes  
3  };  
4  cout << sizeof(s) << endl; // 8
```

Notice that we do not get a size of 5. In C++, padding is introduced by the compiler to ensure proper memory alignment of data members. This improves performance on most hardware architectures. The first member, char *c*, occupies 1 byte. The next member, int *x*, requires 4 bytes and should be aligned to a 4-byte boundary (on most systems). To achieve this alignment, 3 bytes of padding are added after *c* before *x* starts.

When is trailing return type useful

7.1 Decltype on template parameters

Suppose we had two template types T, U , and a function that accepts Ta, Ub . Suppose we wanted the return type to be the type of $T + U$, we could of course just write

```
0  template<typename T, typename U>
1  decltype(T{} + U{}) f(T a, U b) {
2      return a + b;
3  }
```

Or, we could utilize a trailing return

```
0  template<typename T, typename U>
1  auto f(T a, U b) -> decltype(a+b) {
2      return a + b;
3  }
```

7.2 Nested structs

Consider the code

```
0  struct A {
1      struct B {};
2
3      B f() const;
4  };
5
6  A::B A::f() const { }
```

Instead of having to use the scope resolution operator, we could use a trailing return type.

```
0  auto A::f() const -> B {
1
2  }
```

By using a trailing return type, we are essentially inside the scope of A by the time we specify the return type.

Most vexing parse

The most vexing parse is a phenomenon in C++ where a line of code that looks like a variable declaration is instead interpreted by the compiler as a function declaration. This often happens because of C++'s ambiguous grammar for declarations.

```
o std::string s(); // Treated as a function declaration
```

This will not be treated as a default constructed string by the C++ compiler, but instead as a function declaration. To fix this issue, we instead use brace initialization

```
o std::string s{} // A default string variable
```


Notes about copy constructors

The copy constructor in C++ typically takes a const reference (const T&) to ensure correctness and efficiency. If the copy constructor took its parameter by value, this would require making a copy of other before calling the constructor itself. But that copy itself would require calling the copy constructor, leading to infinite recursion until a stack overflow.

If the copy constructor took a non-const reference, this would not allow copying from const objects.

Since a copy operation should not modify the original object, using const ensures the copy constructor can be called for const objects.

Recall that functions (and methods) that take a const reference insure that the function can be called on both const objects and non-const objects. Functions that take non-const references can only accept non-const objects.

As a quick side note, since we are on the topic of const correctness, recall that constant member functions cannot call non-const member functions.

Exceptions during a call to new

When using raw pointers, an exception occurring after a new allocation leads to a resource leak if the allocated memory is not properly managed. This happens because new dynamically allocates memory on the heap, but if an exception interrupts execution before delete is called, the allocated memory remains unreachable and never freed.

To prevent this, use smart pointers (`std::unique_ptr` or `std::shared_ptr`), which automatically manage memory and clean up even if an exception occurs.

However, it is true that using `std::unique_ptr` and `std::shared_ptr` does not guarantee that there will be no resource leaks if they are not used properly. Specifically, passing new directly to their constructors can still lead to resource leaks in certain cases. This is why `std::make_unique` and `std::make_shared` are preferred

`make_shared` performs a single allocation that stores both the object and the control block together. If an exception occurs, no memory leak happens because allocation and ownership setup happen in one step.

Same is true for `make_unique`

10.1 Exceptions during constructors

If a call to new results in an exception, the object is never allocated. When you use new, the operator first tries to allocate memory by calling `operator new(size)`, which is similar to `malloc`.

If memory allocation is successful, the constructor of the object is called.

If there isn't enough memory, `operator new` will throw a `std::bad_alloc` exception (unless you use `nothrow new`, which returns `nullptr`)

If memory allocation succeeds but the constructor of the object throws an exception, the allocated memory is automatically freed, so there is no memory leak. If an exception is thrown in the constructor after memory has been allocated but before construction is complete, the C++ runtime ensures that the allocated memory is automatically freed. This is done by:

- Catching the exception inside the new operator.
- Calling `operator delete(ptr)` to deallocate the memory.

Notes about polymorphism

Consider the code

```
0  struct base {
1      virtual void print() const {
2          cout << "Base" << endl;
3      }
4
5      virtual ~base() {
6          cout << "Cleaned up base" << endl;
7      }
8  };
9  struct derived : base {
10     void print() const override {
11         cout << "Derived" << endl;
12     }
13
14     ~derived() {
15         cout << "Cleaned up derived" << endl;
16     }
17 };
18
19 void f(const base* o) {
20     o->print();
21 }
22
23 void f(const base& o) {
24     o.print();
25 }
26
27 derived d1;
28 base& b1 = d1;
29
30 f(b1);
31
32 base* d = new derived();
33 f(d);
34
35 delete d;
```

We get the output

```
0  Derived
1  Cleaned up derived
2  Cleaned up base
```

The reason both destructor messages ("Cleaned up derived" and "Cleaned up base") are printed when you call `delete d`; is due to polymorphic destruction.

The base class has a virtual destructor (virtual `~base()`). This ensures that when an object is deleted through a pointer to base, the destructor of the derived class will also be invoked before the base destructor.

`d` is deleted, and because base has a virtual destructor, the destructor call correctly cascades down the inheritance chain:

- First, `~derived()` runs and prints "Cleaned up derived".
- Then, `~base()` runs and prints "Cleaned up base".

If the destructor in base wasn't virtual, deleting a derived object through a `base*` pointer would cause undefined behavior (likely only `~base()` would be called, leading to memory leaks).

If base has fields (member variables), whether directly inherited by derived or not, the base destructor must be called to clean up those fields properly when a derived object is deleted.

11.1 Polymorphism with arrays and slicing

11.1.1 Object Slicing

Object slicing occurs when an object of a derived class is assigned to a variable of a base class type, causing the derived part of the object to be "sliced off", leaving only the base class portion.

Slicing occurs when

- A derived object is assigned to a base class object (not a pointer or reference).
- A derived object is stored in a container of base class objects (e.g., an array of base objects).

```
0  struct base {
1      int x{1};
2
3  };
4  struct derived : base {
5      int y{5};
6  };
7
8  base b = derived{};
9  // Error, no member named y in base
10 cout << b.x << endl << b.y;
```

11.1.2 Polymorphism with arrays

Consider the following code

```
0  struct base {
1      virtual void print() const {
2          cout << "Base" << endl;
3      }
4
5      virtual ~base() {
6          cout << "Cleaned up base" << endl;
7      }
8  };
9
10 struct derived : base {
11     void print() const override {
12         cout << "Derived" << endl;
13     }
14
15     ~derived() {
16         cout << "Cleaned up derived" << endl;
17     }
18 };
19
20 void f(const base& o) {
21     o.print();
22 }
23
24 auto main(int argc, const char* argv[]) -> int {
25     base* barr = new derived[5];
26
27     delete[] barr;
28
29     return EXIT_SUCCESS;
30 }
```

barr is declared as base*, but the memory actually holds derived objects. When delete[] barr; is called, C++ treats barr as an array of base objects, not derived objects. This breaks proper destructor calls, leading to undefined behavior.

Even though base has a virtual ~base(), the problem is not about virtual dispatch. Instead, it's about how C++ tracks array allocations.

The array of derived objects was allocated using new derived[5], but delete[] barr; doesn't have enough information to correctly call derived destructors.

When delete[] barr; is called, C++ sees a base* pointer and assumes it points to an array of base objects.

Instead we either,

```
0  derived* darr = new derived[n]
```

```

0  vector<unique_ptr<base>> v(5);
1  for (auto& item : v) {
2      item = make_unique<derived>();
3  }
4
5  // Or the standard approach
6  vector<base*> v2(5);
7  for (auto& item : v2) {
8      item = new derived();
9  }
10
11 for (auto& item : v2) {
12     delete item;
13 }

```

11.2 Runtime polymorphism, dynamic dispatch, dynamic binding, and the vtable

Runtime polymorphism in C++ is achieved through function overriding and is implemented using virtual functions in an inheritance hierarchy. It allows a derived class to provide a specific implementation of a function that is already defined in its base class.

11.2.1 Dynamic dispatch and dynamic binding

Dynamic dispatch is a mechanism where the function to be executed is determined at runtime, rather than at compile-time. This is a key feature of runtime polymorphism and is enabled by virtual functions in C++.

When a virtual function is declared in a base class and overridden in a derived class, C++ does not resolve function calls at compile-time.

Instead, when a function is called using a base class pointer/reference, C++ performs a runtime lookup to determine which function to execute.

This lookup is performed using the VTable (Virtual Table) and VPtr (Virtual Pointer) mechanism.

As a side note, the following will not work

```

0  struct foo {
1      constexpr virtual int print() const {
2          return 12;
3      }
4
5      virtual ~foo() {}
6  };
7
8  struct bar : foo {
9      constexpr int print() const override {
10         return 0;
11     }
12 };
13
14 foo* f = new bar{};
15 constexpr int x = f.print();

```

The issue is that since the print functions are determined and called at runtime, it cannot be a compile time constant expression. We get the error "The value of *f* is not usable in a constant expression"

Dynamic binding (also called late binding) is the underlying mechanism that allows dynamic dispatch to work. It refers to the process of determining which function implementation should be executed at runtime, rather than at compile time.

Binding refers to associating a function call with a function definition. Dynamic binding means this association happens at runtime, based on the actual type of the object.

Dynamic binding ensures that when a function is called on a base class pointer/reference, the correct overridden function from the derived class is invoked at runtime. Dynamic dispatch is the result of dynamic binding

11.2.2 The Vtable

C++ implements runtime polymorphism using a VTable (Virtual Table) and a VPtr (VPtr)

A VTable is a table of function pointers maintained per class. It stores pointers to the virtual functions defined in a class. Each class with virtual functions has a single VTable.

Each object of a class that has virtual functions contains a hidden pointer, called VPtr (Virtual Pointer). VPtr points to the VTable of that particular class.

During runtime, when a virtual function is called via a base class pointer, the VPtr is used to look up the correct function implementation in the VTable.

When the program starts, the compiler creates a VTable for every class that has virtual functions. Every object of such a class gets a hidden VPtr, which points to the corresponding VTable.

When a virtual function is called using a base class pointer, the call is resolved dynamically by checking the VTable.

The VTable (Virtual Table) is created at compile time, but the VPtr (Virtual Pointer) is assigned and used at runtime.

The VTable itself is constructed at compile time, meaning the compiler generates and lays out the function pointers in the table before the program runs.

The VPtr is assigned at runtime, when an object of the class is created.

Because having virtual functions in our struct / class requires this VPtr to be created, having virtual functions therefore will increase the size of the struct and the objects created by the size of a pointer (8 bytes on 64-bit systems or 4 bytes on 32-bit systems).

each class in the inheritance hierarchy that has at least one virtual function has its own vtable.

- A base class with virtual functions has a vtable that stores pointers to its virtual functions.
- A derived class that overrides any virtual functions gets its own vtable, which replaces the base class's function pointers with the derived class's implementations.
- The vtable is associated with a class, not individual objects.
- Each object of a class with virtual functions has a vptr (virtual table pointer) that points to the vtable of its actual type.

Consider the code

```
0  struct foo {
1      virtual void print() const {
2          cout << "Foo" << endl;
3      }
4
5      virtual ~foo() {}
6  };
7
8  struct bar : foo {
9      void print() const override {
10         cout << "Bar" << endl;
11     }
12 };
```

Since foo has virtual functions (print and the destructor), it will have a vtable.

Index	Function Pointer
0	foo::print()
1	foo::~~foo() (destructor)

Every instance of foo has a vptr (virtual table pointer) pointing to this table.

Since bar overrides print(), but still inherits the virtual destructor from foo, its vtable will have the overridden version of print().

Index	Function Pointer
0	bar::print()
1	foo::~~foo() (inherited destructor)

Each instance of bar will have its vptr pointing to vtable for bar.

```
0  int main() {  
1      foo* obj = new bar();  
2      obj->print(); // Calls bar::print() because vptr points to  
    ↪ bar's vtable  
3      delete obj;   // Calls foo::~foo() due to virtual destructor  
4  }
```

11.3 Can you call pure virtual methods

You cannot instantiate abstract classes. Thus, you cannot call pure virtual methods

The existence of structs and classes

Does a Struct Exist in Memory Before an Object is Created? Yes and No. It depends on what part of the struct you're referring to:

- **Struct Definition (Type Information) – Exists at Compile Time:** The struct itself is just a blueprint (like a class). It does not occupy memory on its own.

Only when you create an object of the struct does memory get allocated for its members.

- **VTable (for Virtual Functions) – Exists in Memory, Even Without Objects:** If the struct contains virtual functions, the compiler generates a VTable at compile time. The VTable itself is stored in static memory (not per object). Even if no object is created, the struct's VTable exists somewhere in memory.
- **Object Instances – Exist in Memory When Created:** When you instantiate an object of the struct, memory is allocated for that object's data members. If the struct has virtual functions, each object has a hidden VPtr (Virtual Pointer), which increases its size.

If *A* is a struct, why does `sizeof(A)` have a size even if no object is created? When you define a struct in C++, the compiler determines the size of its layout at compile time. This means that even if you don't create an object of the struct, `sizeof(A)` can still return a valid size.

The compiler does not assign fixed memory addresses to struct members. Instead, it determines the memory layout (size, alignment, and padding) at compile time. Actual memory addresses are assigned at runtime when an object is created.

Note about heap allocated memory in vectors

If your `std::vector` contains raw pointers (e.g., `std::vector<int*>`), the vector will only destroy the pointers themselves but not the dynamically allocated memory they point to. This will cause a memory leak if you don't manually delete each allocated object before the vector goes out of scope.

To avoid leaks, manually delete the elements before clearing the vector

Function that takes a const reference can accept rvalues

In C++, a function that takes a const reference can accept rvalues because const references extend the lifetime of temporary (rvalue) objects.

```
0  template <typename T>
1  void f(const T& x) {}
```

A const T& (a reference to a const object of type T) can bind to both lvalues and rvalues, because:

1. Lvalues are naturally bindable to references.
2. Rvalues (temporaries) can bind to const T& because:
 - The const qualifier guarantees that the temporary will not be modified.
 - C++ extends the lifetime of the temporary to match the lifetime of the reference.

```
0  const int& ref = 100; // OK: binds to temporary, lifetime
    ↪ extended
1  std::cout << ref << std::endl; // Prints 100
2
3  int& ref = 100; // ERROR: Cannot bind non-const lvalue reference
    ↪ to an rvalue
```

- If an lvalue is passed → T deduces to int&, making T&& collapse to int&.
- If an rvalue is passed → T deduces to int, making T&& remain int&&.

Notes about c++ casts

First, recall

- `static_cast` is used for safe and well-defined type conversions that are checked at compile-time.
- `dynamic_cast` is used only with polymorphic types (i.e., classes with at least one virtual function). It performs runtime type checking and is mainly used for safe downcasting.
- `const_cast` is used to add or remove `const` or `volatile` qualifiers from a variable. It is the only cast that can remove `const`, allowing modifications to otherwise constant data.
- `reinterpret_cast` is the most dangerous cast—it converts between completely unrelated types. It does not perform type checking and is used for low-level pointer manipulation.

15.1 `Static_cast`

When to Use `static_cast`:

- Converting between numeric types (e.g., `int` to `double`).
- Converting between pointers of related classes (e.g., upcasting in inheritance).
- Converting between explicitly defined conversion operators.

What It CANNOT Do:

- It does not check for validity at runtime.
- It cannot cast between unrelated types (use `reinterpret_cast` for that).
- It cannot remove `const` or `volatile` qualifiers (use `const_cast` for that).

15.2 `Dynamic_cast`

Dynamic casting in C++ is a feature provided by the language to safely convert pointers or references of base class types to pointers or references of derived class types at runtime. This is particularly useful in scenarios involving polymorphism, where you have a base class pointer or reference pointing to an object of a derived class, and you need to access derived class-specific members or methods.

Dynamic casting is used with pointers or references in class hierarchies that involve polymorphism (i.e., classes with at least one virtual function).

```
◦ dynamic_cast<new_type>(expression)
```

Dynamic casting performs a runtime check to ensure the cast is valid. If the cast is not possible, it returns `nullptr` for pointers or throws a `std::bad_cast` exception for references.

Dynamic casting relies on Run-Time Type Information (RTTI), which must be enabled in your compiler.

15.2.1 When to Use Dynamic Casting

- When you need to safely downcast in a polymorphic hierarchy.
- When you are unsure of the actual type of the object at runtime and need to check it.

Dynamic casting incurs a runtime overhead due to the type checking. It only works with polymorphic types (classes with at least one virtual function).

Overuse of dynamic casting can indicate a design flaw; prefer virtual functions and polymorphism where possible.

15.2.2 RTTI

RTTI stands for Run-Time Type Information. It is a feature in C++ that provides mechanisms to determine the type of an object at runtime. RTTI is particularly useful in scenarios involving polymorphism, where you need to identify the actual type of an object pointed to by a base class pointer or reference.

RTTI relies on metadata stored by the compiler for polymorphic types (classes with at least one virtual function). This metadata includes:

- A vtable (virtual table) for each polymorphic class, which contains pointers to its virtual functions.
- A `type_info` object for each class, which stores information about the class's type.

When you use `typeid` or `dynamic_cast`, the compiler generates code to access this metadata at runtime to determine the object's type.

15.3 `const_cast`

`const_cast` is only used to remove `const` or `volatile` qualifiers from a variable. It cannot be used to add `const`.

```
0  #include <iostream>
1
2  void modify(int* ptr) {
3      *ptr = 42;
4  }
5
6  int main() {
7      const int x = 10;
8
9      // Removing const
10     int* ptr = const_cast<int*>(&x);
11
12     modify(ptr); // Undefined behavior if `x` was originally a
    ↪ `const` object
13
14     std::cout << "x: " << x << std::endl; // This may not
    ↪ reflect the change due to UB
15 }
```

This is unsafe if `x` was originally declared as `const int x = 10;`, because modifying `x` leads to undefined behavior. However, if `x` was originally non-const and then cast to const, modifying it later using `const_cast` is safe.

If you want to add const, you should use

- Implicit conversion
- `static_cast`
- Declaring a const reference or pointer to a non-const object

```
0  int a = 5;
1  const int* ptr = &a; // Adding const implicitly
2  const int& ref = a;  // Adding const implicitly
```

`const_cast` is useful in a few specific cases where you need to work around const qualifiers safely.

15.3.1 Modifying a non-const object that was passed as const

If a function receives a const parameter but you know that the actual object is non-const, you can safely cast away const and modify it.

15.3.2 Removing const to use overloaded functions

Sometimes you have an overloaded function where one version accepts const and another modifies the object. `const_cast` allows selecting the modifying version when needed.

```
0  #include <iostream>
1
2  class Example {
3      public:
4      void print() {
5          std::cout << "Non-const print" << std::endl;
6      }
7
8      void print() const {
9          std::cout << "Const print" << std::endl;
10     }
11 };
12
13 void forceModify(const Example& obj) {
14     const_cast<Example&>(obj).print(); // Calls non-const
    ↪ version
15 }
16
17 int main() {
18     Example e;
19     forceModify(e); // Calls non-const print()
20 }
```

Note: Const cast is a runtime operation and does not perform any checks

15.4 reinterpret_cast

reinterpret_cast is a type of casting operator in C++ that is used to convert one pointer type to another, even if the types are entirely unrelated. It performs a low-level reinterpretation of the underlying binary representation of the data.

Note: reinterpret_cast is a runtime operation and does not perform any checks

15.5 Why are c casts unsafe?

C-style casting is unsafe and ambiguous because:

- It can perform multiple types of conversions at once, including:
 - static_cast
 - reinterpret_cast
 - const_cast
 - Even dynamic_cast (if a class has virtual functions)
- It lacks compile-time safety—you might unintentionally use an invalid cast.
- It is hard to search and debug since (Type) doesn't indicate what kind of conversion is being performed.

The compiler and functions

The compiler handles functions through several stages, from parsing the source code to generating machine code. Here's an overview of how the compiler deals with functions

1. **Parsing and Syntax Analysis:** The compiler reads the source code and identifies function declarations and definitions.

It checks the syntax of the function, such as the return type, function name, parameter list, and body.

2. **Semantic Analysis:** The compiler checks the meaning of the function, such as
 - Whether the function is declared before use (or has a prototype).
 - Whether the function parameters and return type match the function calls.
 - Whether the function body adheres to type rules (e.g., no invalid operations on types).
3. **Function Overloading Resolution:** If multiple functions with the same name exist (function overloading), the compiler determines which function to call based on the arguments provided.
4. **Code Generation:** The compiler generates intermediate or machine code for the function body.

It allocates memory for local variables and parameters.

It generates instructions for the function's logic, such as arithmetic operations, loops, and conditionals.

5. **Function Calls:** When a function is called, the compiler generates code to:
 - Push the arguments onto the stack (or pass them via registers, depending on the calling convention).
 - Transfer control to the function's code.
 - Save the return address so the program knows where to continue after the function finishes.
6. **Inlining (Optional):** If a function is marked with the inline keyword or the compiler determines it is beneficial, the compiler may replace the function call with the actual function body to avoid the overhead of a function call.
7. **Linkage:** If a function is declared in one translation unit (source file) and defined in another, the compiler ensures the function is properly linked.

The compiler generates symbols for functions, which the linker resolves during the linking phase.

8. **Optimization:** The compiler may optimize functions to improve performance, such as:
 - Removing unused code (dead code elimination).
 - Unrolling loops.
 - Inlining small functions.
 - Optimizing tail-recursive functions.

When a function is called, the compiler (and the runtime environment) manages memory for local variables in a specific way

Local variables in a function are typically stored in the stack, a region of memory that is managed automatically by the compiler and runtime environment.

When a function is called, the compiler allocates memory on the stack for all of its local variables.

This memory is only valid for the duration of the function call. Once the function returns, the memory is deallocated (freed).

Each function call creates a stack frame (also called an activation record), which contains:

- The function's local variables.
- The return address (where the program should continue after the function finishes).
- The function's parameters (if any).

The stack grows downward in memory, and each new function call adds a new stack frame on top of the previous one.

When a function returns, its stack frame is deallocated, and the memory becomes available for reuse.

If the same function is called again, a new stack frame is created, and the local variables are allocated in the same memory region (which may have been overwritten by other function calls in the meantime).

Local variables have automatic storage duration, meaning they are created when the function is called and destroyed when the function returns.

This means that the values of local variables are not preserved between function calls.

`constexpr` variables are treated differently because they are compile-time constants.

The compiler evaluates `constexpr` variables at compile time and replaces their uses with their computed values.

No memory is allocated for `constexpr` variables at runtime—they are essentially "baked into" the code.

If a local variable is declared `static`, it has static storage duration, meaning it is allocated memory once and persists across function calls.

Static local variables are not stored on the stack but in a separate region of memory (typically the data segment).

16.1 Important: compile time constant variables and memory (constant propagation/constant folding)

When the compiler encounters a compile-time constant (e.g., a `constexpr` variable), it evaluates the constant expression at compile time and replaces all uses of the variable with the computed value. This means:

- **No Memory Allocation for the Variable:** Since the value of the compile-time constant is known at compile time, the compiler does not allocate memory for the variable at runtime.

Instead, the variable is treated like a literal value (e.g., 10, 3.14, etc.), and its value is "baked into" the generated code wherever it is used.

- **Replacement of Uses:** The compiler replaces every occurrence of the compile-time constant variable with its computed value. This process is called constant propagation or constant folding.

The introduction of the nullptr

nullptr was introduced in C++11 to address several issues and improve type safety when dealing with null pointers. Prior to C++11, the standard way to represent a null pointer was to use the macro NULL, which is typically defined as 0 or ((void*)0) in C++. However, this approach had several drawbacks:

17.1 Ambiguity in Overloaded Functions

In C++, NULL is typically defined as 0, which is an integer. This can lead to ambiguity when overloading functions that take both integer and pointer arguments. For example

```
0 void foo(int);
1 void foo(char*);
2
3 foo(NULL); // Which foo is called? Ambiguous, as NULL is an
   ↪ integer.
```

nullptr resolves this ambiguity because it has its own type, std::nullptr_t, which is implicitly convertible to any pointer type but not to integral types. Thus:

```
0 foo(nullptr); // Unambiguously calls foo(char*)
```

17.2 Type safety

Using 0 or NULL for null pointers can lead to type safety issues because 0 is an integer literal, and it can be implicitly converted to other types, such as bool or int. This can result in unintended behavior or bugs.

nullptr is a keyword that explicitly represents a null pointer, and it cannot be implicitly converted to an integer. This makes the code more type-safe and less prone to errors.

17.3 The type of nullptr

nullptr is of type nullptr_t

```
0 auto ptr = nullptr // has type nullptr_t
```

17.4 `nullptr` vs `void*`

`nullptr` is used to explicitly indicate that a pointer does not point to any valid memory location.

It has its own type, `std::nullptr_t`, which is implicitly convertible to any pointer type (e.g., `int*`, `char*`, etc.) but not to other types like integers.

`void*` is a generic pointer type that can point to any data type.

Brace initialization vs Parenthesized Initialization

Brace initialization (also called uniform initialization or list initialization) was introduced in C++11 and has stricter rules compared to parenthesized initialization. Specifically, consider a uniform initialization of the form `type{expr}`

- **Prohibits narrowing conversions:** Brace initialization does not allow implicit narrowing conversions. If `expr` cannot be converted to `Type` without losing information (e.g., converting a double to an int), the compiler will emit an error.
- **Prevents most vexing parse:** Brace initialization avoids ambiguity with function declarations, which can occur with parenthesized initialization.
- **Calls constructors explicitly:** If `Type` has a constructor that takes an `std::initializer_list`, brace initialization will prefer that constructor.

If an `std::initializer_list` constructor exists, it will be chosen over other constructors, even if another constructor is a better match.

```
0  struct s {  
1      s(int x) {cout << "1" << endl;}  
2      s(initializer_list<int> x) {cout << "2" << endl;}  
3  };  
4  s s1{2}; // 2  
5  s s2(2); // 1
```

Parenthesized initialization (also called direct initialization) is more permissive and allows narrowing conversions. It behaves like a function call, where the compiler attempts to convert `expr` to `Type` using implicit conversions, even if narrowing occurs.

Note that parenthesized initialization does call constructors

Since c++20, direct initialization will work for aggregate types

struct lattice { int x, y; }; lattice p(10, 20); // OK since c++20

Are chars unsigned?

In C++, the char type is neither inherently signed nor unsigned. It's implementation-defined behavior.

- char, signed char, and unsigned char are distinct types.
- The default behavior of char depends on the compiler. Some compilers treat char as signed char, while others treat it as unsigned char.
- To ensure consistent behavior, use signed char or unsigned char explicitly.

Size of types

- **bool**: 1 Byte
- **char**: 1 Byte
- **short**: 2 Bytes
- **int**: 4 Bytes
- **long**: 4 or 8 bytes
- **long long**: 8 bytes
- **float**: 4 bytes
- **double**: 8 bytes
- **long double**: 16 bytes
- **string**: 32 bytes
- **Pointers**: 8 bytes

Note that the size of primitive types are usually implementation defined, and adding signed or unsigned does not change the size.

Also, references are the size of the type they refer to.

Trivially copyable

A trivially copyable type in C++ is a type that can be copied efficiently using `memcpy` or similar low-level operations without breaking its correctness. This means it does not require custom copy/move constructors or destructors.

A class or struct is trivially copyable if:

- Can be copied with `memcpy` without breaking program semantics.
- Has no user-defined copy/move constructors, assignment operators, or destructors.
- Only contains trivially copyable members.
- Does not have virtual functions or virtual base classes.

POD types (Plain old data)

POD (Plain Old Data) refers to a type in C++ that is simple, compatible with C structures, and has well-defined memory layouts. A POD type behaves like a C-style struct and lacks modern C++ features such as constructors, destructors, virtual functions, and non-trivial member functions.

A type is considered POD if:

- It is a trivial type (trivial constructor, destructor, copy/move operations).
- It is a standard-layout type (data layout matches C structs).

22.1 Trivial type

A type is trivial if:

- It has a trivial default constructor (compiler-generated, does nothing).
- It has a trivial copy/move constructor and assignment (member-wise copying).
- It has a trivial destructor (compiler-generated, does nothing).

22.2 Standard layout

A type is standard-layout if:

- It has no virtual functions or virtual base classes.
- It has only standard-layout base classes.
- All non-static data members have the same access control (public vs private matters).
- It does not inherit from multiple base classes with different access specifiers.

For a C++ structure (struct or class) to match a C struct's layout, it must

- Store its members in the same order as declared.
- Not have hidden padding or unexpected compiler transformations.
- Not have virtual functions or virtual base classes.
- Not use complex features like multiple inheritance.
- Use only standard-layout types for its members.

If a type is both trivial and standard-layout, it is POD.

Notes about initialization

23.1 How many names does brace initialization have?

23.1.1 Uniform Initialization (General Term)

Introduced in C++11, `{}` initialization is often referred to as uniform initialization because it provides a consistent syntax for initializing objects of any type.

Note that uniform initialization is an informal term

23.1.2 List Initialization

List initialization is the official term in the C++ standard for using `{}` to initialize objects.

23.1.3 Aggregate Initialization

When `{}` is used to initialize aggregates (structs, arrays, or classes with public members and no user-defined constructors), it's called aggregate initialization.

```
0  struct Point {  
1      int x, y;  
2  };  
3  Point p = {1, 2}; // Aggregate initialization
```

23.1.4 Value Initialization

If `{}` is used without any elements, it results in value initialization.

```
0  struct point {  
1      int x{},y{}; // Default value initialized  
2  };
```

Note that we can also do

```
0  struct point {  
1      int x,y  
2  };  
3  point p{}; // Construct p and default value initialize x,y
```

23.1.5 Direct List Initialization

When `{}` is used with a constructor that takes a list, it is called direct list initialization.

```
0 std::vector<int> v{1, 2, 3}; // Direct list initialization
```

23.1.6 Copy List Initialization

When `{}` is used on the right-hand side of an assignment or in variable initialization without explicit construction, it's called copy list initialization.

```
0 std::vector<int> v = {1, 2, 3}; // Copy list initialization
```

23.1.7 Narrowing Prevention Initialization

`{}` initialization prevents narrowing conversions, meaning it does not allow implicit type conversions that lose information.

```
0 int x = 3.5; // Allowed (implicit conversion)
1 int y{3.5}; // Error (narrowing conversion)
```

23.1.8 Default Member Initialization

`{}` can be used to initialize class members with default values.

```
0 struct Example {
1     int a = {}; // Value-initialized to 0
2 };
```

23.1.9 Copy list initialization and direct list initialization in aggregate types

We note that for an aggregate type, copy list initialization and direct list initialization behave the same

```
0 struct point {
1     int x,y
2 };
3 point p1 = {1,2};
4 point p1{1,2};
```

For aggregates, both `=` (copy list initialization) and `{}` (direct list initialization) behave identically because C++ applies aggregate initialization in both cases.

However, if point had a user-defined constructor, then they could behave differently.

If we defined a constructor that takes an `initializer_list`, both the above objects would call that constructor

```
0  struct point {
1      int x{},y{}; // Default value initialized
2
3      point(std::initializer_list<int> l) {
4          cout << "called init list " << endl;
5      }
6  };
7
8  point p1 = {1,2}; // called init list
9  point p2{1,2}; // called init list
```

Note that if we define a virtual method, our type becomes polymorphic and is no longer aggregate. Therefore, we cannot use either initialization above. Note however that c++ will still implicitly give us the default constructors, so the following will still work

```
0  struct point {
1      int x,y;
2
3      virtual void f();
4  };
5  point p1{1,2} // Error
6  point p2 = {1,2} // Error
7  point p3{};
```

In this case, we need to explicitly define our constructor

```
0  struct point {
1      int x,y;
2
3      point(int x, int y) : x(x), y(y) {}
4
5      virtual void f();
6  };
7  point p1{1,2}
8  point p2 = {1,2}
9  point p3{};
```

23.2 Other forms of initialization and their names

23.2.1 Direct Initialization

Uses the parenthesis () syntax

```
0  int x(10);    // Direct initialization
1  std::string s("hello");
```

Note that aggregate initialization logic will not work with this syntax

```
0  struct point{
1      int x,y
2  };
3  point p(1,2) // Error! Must define the constructor.
```

23.2.2 Copy Initialization

Uses assignment =

```
0  int x = 10;
```

Creates a temporary object and copies/moves it to initialize the variable. May involve implicit conversions. Calls copy constructor if the type has one.

23.2.3 Default Initialization

No explicit initializer

```
0  int x;        // Default initialization (uninitialized in local
    ↪ scope)
1  std::string s; // Calls default constructor (empty string)
```

Notes about constructors

24.1 Value initialized vs default initialized

Consider the code

```
0  struct s1 {  
1      string s{};  
2      int x{};  
3  };  
4  
5  struct s2 {  
6      string s;  
7      int x;  
8  };
```

Whats the difference? In s1, the members are explicitly initialized with {}

```
0  struct s1 {  
1      std::string s{}; // Initializes to an empty string  
2      int x{};        // Initializes to 0  
3  };
```

This ensures that when an instance of s1 is created, s will be initialized to an empty string (""), and x will be initialized to 0.

In s2, the members are not explicitly initialized:

```
0  struct s2 {  
1      std::string s; // Default constructor of std::string  
    ↪ initializes it to ""  
2      int x;        // Uninitialized, contains garbage value if  
    ↪ not explicitly set  
3  };
```

s is fine because std::string has a default constructor that initializes it to "".

x, however, remains uninitialized when a default-constructed object of s2 is created, leading to an indeterminate value.

24.2 What exactly is =default

the = default specifier is used to explicitly declare that a special member function should be automatically generated by the compiler with its default behavior.

```

0  struct s {
1      char c;
2      int x;
3
4      s() = default;
5  };

```

This declares a default constructor (`s()`) explicitly, but it tells the compiler to generate it using the default implementation.

By default, the compiler-generated constructor does not initialize member variables. So, this:

```

0  s() = default;

```

is equivalent to:

```

0  s() {} // Default constructor, does nothing

```

which means the members (`char c; int x;`) remain uninitialized when an object of `s` is created

24.2.1 Non-POD fields

=default construct (default constructor) calls default constructors of non-POD (plain-old-data) members.

```

0  struct S {
1      std::string str; // std::string has a default constructor
2      int x;
3
4      S() = default; // Compiler generates: S() {} (but calls
    ↪ std::string's constructor)
5  };

```

The `std::string` member is properly initialized (since `std::string` has a default constructor). The `int x` is uninitialized.

24.2.2 With copy constructors

```

0  struct S {
1      std::string str;
2      int x;
3
4      S() = default;
5      S(const S&) = default; // Compiler generates: S(const S&
    ↪ other) : str(other.str), x(other.x) {}
6  };

```


Generates a copy constructor that copies each member individually using their copy constructors.

24.2.3 Copy Assignment

Generates an assignment operator that copies each member individually.

```
0 struct S {  
1     std::string str;  
2     int x;  
3  
4     S& operator=(const S&) = default;  
5 };
```

Equivalent to

```
0 S& operator=(const S& other) {  
1     str = other.str; // Calls std::string's assignment operator  
2     x = other.x;     // Simply copies x  
3     return *this;  
4 }
```

24.2.4 Move constructor

Generates a move constructor that moves each member individually.

```
0 struct S {  
1     std::string str;  
2     int x;  
3  
4     S(S&&) = default; // Compiler generates: S(S&& other) :  
    ↪ str(std::move(other.str)), x(other.x) {}  
5 };
```

This allows efficient moving:

```
0 S obj1;  
1 S obj2 = std::move(obj1); // Moves `str`, but leaves `x` as a  
    ↪ copy
```

the move constructor does not "move" the int x. Instead, it simply copies x from the source. This is because int is a trivially copyable type, and moving it is no different from copying.

24.2.5 Move Assignment

Generates a move assignment operator that moves each member individually.

```
0 struct S {  
1     std::string str;  
2     int x;  
3  
4     S& operator=(S&&) = default;  
5 };
```

Equivalent to:

```
0 S& operator=(S&& other) {  
1     str = std::move(other.str); // Moves the string instead of  
    ↪ copying  
2     x = other.x; // Simply copies x (since int doesn't benefit  
    ↪ from move)  
3     return *this;  
4 }
```

24.2.6 Destructor

Generates a destructor that:

- Does nothing for fundamental types.
- Calls the destructors of member objects.

```
0 struct S {  
1     std::string str;  
2     int x;  
3  
4     ~S() = default; // Compiler generates: ~S() {} (but calls  
    ↪ std::string's destructor)  
5 };
```

24.2.7 Do you need to write them?

In C++, the compiler will automatically generate default implementations for special member functions only if they are needed and not explicitly declared.

However, if you declare any of them (without defining them), the compiler will not automatically generate them. This is where `= default` comes in—it explicitly tells the compiler to generate the default implementation.

24.3 =delete

=delete does the opposite of =default... It deletes the default implementation

24.4 Rule of five

In C++, the Rule of Five states that if you define or explicitly delete any of the following five special member functions, you should likely define or delete all five

- Destructor
- copy constructor
- copy assignment operator
- move constructor
- move assignment operator

```
0  struct s {  
1      string str{};  
2  
3      s(const s& other) {  
4          cout << "Copy constructor called" << endl;  
5          str = other.str;  
6      }  
7  };  
8  s s1;
```

In this case, we get an error. When you explicitly define a copy constructor in C++, the compiler does not automatically generate the default constructor for you. This is due to the Rule of Five

The C++ standard states that if you declare any of the above special member functions, the compiler will not generate a default constructor for you:

Once you define any of these functions, the compiler assumes you want full control over object creation and copying, so it does not provide the default constructor.

24.5 A confused compiler

Consider the code

```

0  struct point {
1      int x{};
2
3      point (int x) : x(x) {}
4
5      point(int&& other) {
6          cout << "called second" << endl;
7          x = other;
8      }
9  };
10 point p = 20; // Error

```

We get "error: conversion from 'int' to 'point' is ambiguous".

happens because there are multiple constructors that can accept an int, and the compiler doesn't know which one to pick.

- point(int) is a direct match for int.
- point(int&&) can accept an int as an rvalue reference.

The compiler does not know which one to pick, so it gives an error.

If we mark the first constructor explicit, we then prevent implicit conversion from int to point, and the second constructor will be the one called.

```

0  struct point {
1      int x{};
2
3      explicit point (int x) : x(x) {}
4
5      point(int&& other) {
6          cout << "called second" << endl;
7          x = other;
8      }
9  };
10 point p = 20;

```

24.6 Which constructor will be called

Suppose we have

```

0  struct point {
1      int x{};
2
3      point(const int& other) {
4          cout << "called first" << endl;
5          x = other;
6      }
7
8      point(int&& other) {
9          cout << "called second" << endl;
10         x = other;
11     }
12 };
13 point p = 20;

```

Which constructor gets called? The second constructor (`point(int&& other)`) is called in this case because the literal 20 is an rvalue.

We have two suitable constructors, and the compiler must determine which constructor to call.

The compiler deems the second as a better match than the first, because 20 is a pure rvalue. Note that if we removed the second constructor, the first would work. A constructor that takes a const reference can bind to both rvalues and lvalues.

Notes about inheritance

25.1 Constructor chain

In C++ inheritance, the constructor chain (or constructor delegation) refers to the sequence in which constructors of base and derived classes are called when an object of the derived class is created.

When an object of a derived class is created, the constructor of the base class runs before the constructor of the derived class.

If the base class has multiple levels, constructors are called in top-to-bottom order (from base to most derived).

If the base class does not have a user-defined constructor, the compiler provides a default constructor that is automatically invoked.

If the base class has a parameterized constructor, you must explicitly call it in the initializer list of the derived class.

25.2 Destructor chain

Destructors execute in reverse order of constructors (i.e., derived class destructor runs first, then base class destructor).

Booleans under the hood: Adding two booleans

In C++, `bool` is typically represented under the hood as an integral type, often stored as a single byte (char-sized) in memory. However, when used in expressions, `bool` values implicitly promote to `int`.

In C++, `bool` is effectively an integer type but only holds 0 (false) or 1 (true).

When used in an arithmetic expression, a `bool` value is promoted to an `int`.

This is part of the integral promotion rules in C++.

```
0  bool b1 = 1, b2 = 1;
1  cout << typeid(b1 + b2).name();
```

Type Promotion

Type promotion in C++ refers to the implicit conversion of smaller or lower-ranked types to larger or higher-ranked types in expressions. This ensures consistent operations without data loss.

- **Boolean Promotion:** `bool` converts to `int` (`false` \rightarrow 0, `true` \rightarrow 1) when used in arithmetic or bitwise operations.
- **Integral Promotion:** Types smaller than `int` (`char`, `short`, `bool`) promote to `int` if `int` can represent all values; otherwise, they promote to unsigned `int`.

If operands have different types, the one with the lower rank is converted to the higher-ranked type.

27.1 Ranking

`bool` \rightarrow `char/short` \rightarrow `int` \rightarrow `long` \rightarrow `long long` \rightarrow `float` \rightarrow `double` \rightarrow `long double`

Notes about static

28.1 Static variables inside member functions

Static variables inside member functions behave the same as static variables in regular functions

28.2 Using instances to call static methods

We note that we can use instances to call static methods using the dot notation

```
0  struct s{  
1      int x = 20;  
2      static void f() {  
3          cout << "static method" << endl;  
4      }  
5  };  
6  s::f();  
7  
8  s S;  
9  S.f();
```

28.3 Can you make pure virtual methods static?

No, you cannot

Trying to move const objects

Consider the code

```
0  struct s {  
1      string str{};  
2  
3      s() = default;  
4  
5      s(const string& other) {  
6          cout << "Copy constructor called" << endl;  
7          str = other;  
8      }  
9  
10     s(string&& other) {  
11         cout << "Move constructor called " << endl;  
12     }  
13 }  
14 };  
15 const string str = "Hello";  
16 s s1(std::move(str));
```

Something interesting happens, we get *"Copy constructor called"*. A constant object cannot be moved because moving modifies the source object.

The move constructor requires an argument of type `std::string&&` (a temporary, non-const string).

However, `std::move(str)` produces a const `std::string&&` (rvalue reference to const), which cannot be passed to the move constructor because the move constructor expects a non-const rvalue reference (`string&&`).

```
0  s(const string& other) {    // (1) Copy constructor  
1      cout << "Copy constructor called" << endl;  
2      str = other;  
3  }  
4  
5  s(string&& other) {         // (2) Move constructor  
6      cout << "Move constructor called" << endl;  
7  }
```

Since `std::move(str)` produces const `std::string&&`, it cannot bind to (2) `s(string&&)`, because the move constructor does not accept const.

Instead, `s(const string&)` (the copy constructor) is selected, because it can accept a const `std::string&`.

This is one reason why we have const in the copy constructor, if the copy constructors argument was not const, we would get an error trying to move the const object.

Smart pointers in conjunction with raw ptrs

30.1 Shared_ptr with raw ptrs

Consider the code

```
0  int x = 50;  
1  std::shared_ptr<int> ptr = std::make_shared<int>(50);
```

What happens if we do

```
0  int* ptr2 = &(*ptr);
```

Will it increase the reference count? No it does not

```
0  cout << ptr.use_count() << endl; // 1
```

30.2 Unique_ptr with raw ptrs

What if we do

```
0  std::unique_ptr<int> ptr = std::make_unique<int>(50);  
1  int* ptr2 = &(*ptr);
```

Does this even work? Yes, this works perfectly fine. `*ptr` dereferences the `std::unique_ptr<int>`, retrieving the integer it owns. `&(*ptr)` takes the address of that integer, effectively obtaining a raw pointer to the managed object.

If `ptr2` is used only within the scope where `ptr` exists and is valid, it's generally fine

If `ptr` is reset or goes out of scope, `ptr2` becomes a dangling pointer, leading to undefined behavior

Calling delete on a nullptr

Calling delete on a nullptr is perfectly safe and has no effect.

The delete operator first checks whether the pointer is nullptr. If the pointer is nullptr, delete does nothing and returns immediately.

This behavior ensures that you don't have to explicitly check for nullptr before calling delete.