

FreeRADIUS Configuration for the OpenRoaming

Rev. 20250522

1. Introduction

This document explains the minimum configuration of FreeRADIUS 3.x for setting up a RadSec endpoint [1] of the WBA OpenRoaming. This document aims to help operators obtain the first working environment but is not intended for providing official recommendations.

The configuration examples assume to use ver. 3.2.6 which is the latest stable one as of this writing (3.2.7 has an issue with RadSec). The source package is available at <https://freeradius.org/>. (Note: Ver. 3.0.25 and older must not be used because they suffer from instable RadSec connections.)

It is assumed that all other configurations of FreeRADIUS as a RADIUS IdP (Identity Provider), proxy, or both, have already be done. Only the additional configurations required for the OpenRoaming are described.

FreeRADIUS older than 3.2.1 needs an external RadSec proxy software that supports Dynamic Peer Discovery (DPD) feature required for OpenRoaming Access Network Provider (ANP). Hence, this document was written. A DPD support is available in FreeRADIUS 3.2.1 and newer [2].

Throughout the document, the locations of the configuration files are relative to the configuration directory of FreeRADIUS, normally located at /etc/raddb, unless otherwise indicated.

[1] “PKI RadSec End Entity Deployment Guidelines” (WBA Members Only)

[2] Dynamic Home Servers,
https://github.com/FreeRADIUS/freeradius-server/tree/v3.2.x/raddb/home_servers

2. Obtaining an OpenRoaming endpoint certificate and CA/I-CA certificates

Each operator directly connecting to the OpenRoaming network needs to receive an endpoint certificate package from a certificate issuer, WBA or its agent/broker. The package contains the following certificates. We assume that the operator acts as an IdP in this document.

- (1) A server (IdP) certificate (or a combined (IdP+ANP) certificate).
- (2) Root CA certificate (e.g. wba-root1.pem)
Root CA certificates can be found at <https://wballiance.com/openroaming/pki-repository/>
- (3) All I-CA (Intermediate CA) certificates, normally the issuer’s I-CA certificate and the policy certificate (e.g. wba-issuing1.pem and wba-policy1.pem).

These certificates should be in text format. In addition, the operator should retain the key file which was generated during the CSR creation [1] and its passphrase.

Suppose an operator “example.com” receives a certificate named as example.com.cer, which is a text file. The contents can be seen by a command line as follows.

```
$ openssl x509 -noout -text -in example.com.cer
```

A certificate chain file can be created by simply concatenating the operator’s certificate and the I-CA certificates.

```
$ cat example.com.cer wba-issuing1.pem wba-policy1.pem > cert-chain.pem
```

The content of the file looks like:

```
-----BEGIN CERTIFICATE-----
    <operator's certificate>
-----END CERTIFICATE-----
-----BEGIN CERTIFICATE-----
    <I-CA certificate (e.g. wba-issuing1.pem)>
-----END CERTIFICATE-----
-----BEGIN CERTIFICATE-----
    <I-CA certificate (e.g. wba-policy1.pem)>
-----END CERTIFICATE-----
```

Note, if the certificate and chain have been issued using WBA's Agent API, the responses may have been delivered to you using a JSON format. This means that the certificate and chain need to be reformatted back to a multi-line text format. Assuming your json certificate is in a file named "cert-json.pem", this can be achieved using the awk command:

```
$ awk '{gsub(/\n/, "\n")}'1 cert-json.pem > cert-text.pem
```

3. Configuring FreeRADIUS as the RadSec endpoint of OpenRoaming IdP (server)

1. Create a symbolic link if it does not exist in the sites-enabled directory.
(\$: regular user prompt, #: root command prompt)

```
$ sudo -s
# cd /etc/raddb
# ln -s sites-available/tls sites-enabled/tls
```

2. Open the tls file by a text editor and make sure that the following lines exist in the listen section.

```
ipaddr = *
port = 2083
type = auth+acct
proto = tcp
virtual_server = default
clients = radsec
```

3. In the "tls" section, set the key and certificate files (supposed they are in /etc/raddb/certs). The CA file wba-root.pem should contain both the legacy and new CA certificates. Please see section 4 for details. You may use the following command to create the file.

```
$ cat wba-root0.pem wba-root1.pem > wba-root.pem
```

```
private_key_password = <passphrase>
private_key_file = /etc/raddb/certs/example.com.key

certificate_file = /etc/raddb/certs/cert-chain.pem
ca_file = /etc/raddb/certs/wba-root.pem
```

4. Use the following format instead of ca_file if a CA directory is to be used instead of a CA file. This is useful if you want to trust multiple roots.

Both the legacy CA certificate (wba-root0.pem) and the new one (wba-root1.pem) should be put into the directly as individual files. Please see section 4 for details.

```
ca_path = /etc/raddb/certs
```

Then run “c_rehash” (part of openssl) to create symbolic links to each certificate.

```
# c_rehash /etc/raddb/certs
```

5. In the same “tls” section, add the following lines. It is important to enable TLS 1.3 explicitly in order to improve RadSec interoperability. (Without the ecdh_curve line, TLS 1.2 connection may fail.)

```
tls_min_version = “1.2”
```

```
tls_max_version = “1.3”
```

```
ecdh_curve = “”
```

6. In the “clients radsec” section, configuration for 127.0.0.1 (localhost) may already exist. Add the following lines below the configuration. The max_connections value may be tuned but the default value (16) is too small for large-scale deployment like OpenRoaming.

```
client OpenRoaming {
    ipaddr = *
    proto = tls
    secret = radsec
    add_cui = yes
    limit {
        max_connections = 0
    }
}
```

Set also the global parameter max_connections = 0 in the “listen { limit {” section.

A different client name, e.g., RadSec-OR, may be used. The name will appear in the radius.log file.

7. Configure the firewall to open 2083/tcp. For example, on Ubuntu use the command:

```
$ sudo ufw allow 2083
```

8. Restart the FreeRADIUS daemon (radiusd). Never use “reload,” which does not reflect configuration changes.

```
# systemctl restart radiusd
```

```
or
```

```
# service radiusd restart
```

9. Make FreeRADIUS start at boot time by running the following command:

```
# systemctl enable radiusd
```

10. Check that the TLS is configured correctly by using the openssl s_client command as follows from an external host. You should see the RadSec server certificate (IdP certificate).

```
$ openssl s_client -showcerts <ip address of RadSec server>:2083
```

Then, try the following as well. The ca-chain.pem file (= wbaorchain1.pem as of this writing) contains all the I-CA certificates and the Root CA certificate.

If you see no error and the openssl command keeps the connection for a while (> 30 sec), the RadSec endpoint is configured correctly. The command may exit immediately after successful connection in some cases.

```
$ openssl s_client -tls1_3 -quiet -connect <ip address of RadSec server>:2083 -cert example.com.cer -key example.com.key -cert_chain ca-chain.pem
```

```
$ openssl s_client -tls1_2 -quiet -connect <ip address of RadSec server>:2083 -cert example.com.cer -key example.com.key -cert_chain ca-chain.pem
```

Additional Notes: Some Linux distributions, such as Ubuntu, have different naming conventions.

1. FreeRADIUS configuration files may be located in /etc/freeradius/3.0 or /etc/freeradius instead of /etc/raddb .
2. The systemd service file for FreeRADIUS may be called freeradius.service. This means you will have to start and enable it by running “systemctl start freeradius” and “systemctl enable freeradius”, respectively.

4. Transition from the legacy Root CA to new Root

WBA OpenRoaming has introduced a new Root CA replacing the legacy CA in late 2024. All certificates are issued from the new trust anchor since Feb. 2025.

During the transition period, all operators (IdPs, ANPs, and hubs) need to set **both** the legacy CA certificate, **wba-root0** with “O=Cisco Systems, Inc.”, and the new CA certificate, **wba-root1** with “O=Wireless Broadband Alliance, Inc.”, on every RadSec endpoint.

These CA certificates can be found at <https://wballiance.com/openroaming/pki-repository/>

By adding the new CA certificate, IdPs will be able to accept connections from all peers having a new client certificate from the new trust anchor.

There may be some periods in which an ANP is still using an old client certificate while an IdP (or hub) is using a new server certificate. The ANP needs to have the new CA certificate to verify the new server certificate presented by the peer.

5. Configuration for proxy (ANP)

An external RadSec proxy software is required if you do not use the Dynamic Peer Discovery (DPD) feature of FreeRADIUS (>3.2.1). The Open Source Software (OSS) version of radsecproxy can be used for this purpose.

The source package is available at <https://radsecproxy.github.io/> .

Cisco Spaces Connector supports the OpenRoaming and can also be used as an external RadSec proxy with the DPD.

By using the following example in the proxy.conf file, all DEFAULT requests will be sent to the external proxy, e.g. the radsecproxy running on the same host, listening on the shifted ports 11812 (auth) and 11813 (acct). The secret should be fixed accordingly.

```
realm DEFAULT {
```

```

authhost = 127.0.0.1:11812
accthost = 127.0.0.1:11813
secret = testing123X
nostrip
}

```

6. Configuring FreeRADIUS to be compliant with the WRIX (informational)

To join the OpenRoaming, the RADIUS IdP and proxy need to be compliant with the WRIX.

Please refer to the WRIX documents for details.

On the ANP proxy, the Operator-Name attribute needs to be populated with the WBAID issued by the WBA or its agent. This setting is possible by inserting the following lines at the top in the “pre-proxy” section in the sites-enabled/default file, where “EXAMPLE:US” shows an example WBAID and “4” is the Namespace ID specifying the WBAID (RFC 5580).

```

update proxy-request{
    Operator-Name := "4EXAMPLE:US"
}

```

If you want to set Operator-Name only for outbound requests, the following code is useful. The “DEFAULT” corresponds to the “realm DEFAULT” at the end of the proxy.conf file. This prevents incoming Operator-Name from being modified for the other realms.

```

if ( control:Proxy-To-REALM == "DEFAULT" ) {
    update proxy-request{
        Operator-Name := "4EXAMPLE:US"
    }
}

```

7. Firewall configuration (informational)

Since there are many RadSec clients doing the DPD, the source addresses of these clients cannot be determined beforehand.

The RadSec endpoint of the OpenRoaming ANP needs to have 2083/tcp open to any hosts.

For your information, if firewalld with iptables is used in a Linux distribution, the configuration file /etc/firewalld/zones/public.xml would need to have an additional rule like:

```

<rule family="ipv4">
  <source address="0.0.0.0/0"/>
  <port port="2083" protocol="tcp"/>
  <accept/>
</rule>

```

8. RadSec interoperability in FreeRADIUS (informational)

It is important to enable TLS 1.3 explicitly as explained earlier.

Rev. 20200817 Hideaki Goto, Cityroam/eduroam	
Rev. 20200910 Hideaki Goto, Cityroam/eduroam	
Rev. 20210108 Hideaki Goto, Cityroam/eduroam	RadSec secret updated.
Rev. 20210323 Hideaki Goto, Cityroam/eduroam	Solved interoperability issue with ECC certs.
Rev. 20210524 Ryan Blossom, Single Digits	Added notes, ca_path
Rev. 20220107 Hideaki Goto, Cityroam/eduroam	Revised for clarity.
Rev. 20220505 Hideaki Goto, Cityroam/eduroam	Updated FreeRADIUS version.
Rev. 20230421 Hideaki Goto, Cityroam/eduroam	Fixed the issuer's name. Updated some descriptions.
Rev. 20230517 Mark Grayson, Cisco	Added JSON to TEXT format command and openssl test command.
Rev. 20230520 Hideaki Goto, Cityroam/eduroam	(merge & clean-up)
Rev. 20230524 Hideaki Goto, Cityroam/eduroam	Added a reference to the DPD in FreeRADIUS.
Rev. 20230714 Hideaki Goto, Cityroam/eduroam	WBAID is upper-case.
Rev. 20240409 Hideaki Goto, Cityroam/eduroam	Adds more example for setting Operator-Name.
Rev. 20240516 Hideaki Goto, Cityroam/eduroam	Improve TLS 1.2 interoperability. Add more test cases.
Rev. 20240721 Hideaki Goto, Cityroam/eduroam	Fix test commands.
Rev. 20240907 Hideaki Goto, Cityroam/eduroam	Add new trust anchor, preparing for the Root CA transition.
Rev. 20250306 Hideaki Goto, Cityroam/eduroam	Set max_connections parameter explicitly for stable operation avoiding a connection blocking problem. Update certificate file names.
Rev. 20250522 Hideaki Goto, Cityroam/eduroam	Fix the description about max_connections.