


Azure Functions timer trigger

02/27/2017 • 3 minutes to read • Contributors      [all](#)

In this article

[Timer trigger](#)

[Schedule examples](#)

[Trigger usage](#)

[Trigger sample](#)

[Next steps](#)

Timer

This article explains how to configure and code timer triggers in Azure Functions. Azure Functions has a timer trigger binding that lets you run your function code based on a defined schedule.

The timer trigger supports multi-instance scale-out. A single instance of a particular timer function is run across all instances.

This is reference information for Azure Functions developers. If you're new to Azure Functions, start with the following resources:

- [Create your first function.](#)
- [Azure Functions developer reference.](#)
- [C#, F#, Node, or Java](#) developer reference.
- [Azure Functions triggers and bindings concepts.](#)

Timer trigger

The timer trigger to a function uses the following JSON object in the `bindings` array of `function.json`:

JSON

 Copy

```
{
  "schedule": "<CRON expression - see below>",
  "name": "<Name of trigger parameter in function signature>",
  "type": "timerTrigger",
  "direction": "in"
}
```

The value of `schedule` is a [CRON expression](#) that includes these six fields:

```
{second} {minute} {hour} {day} {month} {day-of-week}
```

Note

Many of the cron expressions you find online omit the `{second}` field. If you copy from one of them, you need to adjust for the extra `{second}` field. For specific examples, see [Schedule examples](#) below.

The default time zone used with the CRON expressions is Coordinated Universal Time (UTC). To have your CRON expression based on another time zone, create a new app setting for your function app named `WEBSITE_TIME_ZONE`. Set the value to the name of the desired time zone as shown in the [Microsoft Time Zone Index](#).

For example, *Eastern Standard Time* is UTC-05:00. To have your timer trigger fire at 10:00 AM EST every day, use the following CRON expression that accounts for UTC time zone:

JSON

Copy

```
"schedule": "0 0 15 * * *",
```

Alternatively, you could add a new app setting for your function app named `WEBSITE_TIME_ZONE` and set the value to **Eastern Standard Time**. Then the following CRON expression could be used for 10:00 AM EST:

JSON

Copy

```
"schedule": "0 0 10 * * *",
```

Schedule examples

Here are some samples of CRON expressions you can use for the `schedule` property.


To trigger once every five minutes:

JSON


Copy

```
"schedule": "0 */5 * * * *
```

To trigger once at the top of every hour:

JSON	 Copy
<pre>"schedule": "0 0 * * * *",</pre>	

To trigger once every two hours:

JSON	 Copy
<pre>"schedule": "0 0 */2 * * *",</pre>	


To trigger once every hour from 9 AM to 5 PM:

JSON	 Copy
<pre>"schedule": "0 0 9-17 * * *",</pre>	

To trigger At 9:30 AM every day:


JSON	 Copy
<pre>"schedule": "0 30 9 * * *",</pre>	

To trigger At 9:30 AM every weekday:

JSON	 Copy
<pre>"schedule": "0 30 9 * * 1-5",</pre>	

Trigger usage

When a timer trigger function is invoked, the [timer object](#) is passed into the function. The following JSON is an example representation of the timer object.

JSON	 Copy
<pre>{ "Schedule": { }, "ScheduleStatus": { "Last": "2016-10-04T10:15:00.012699+00:00", "Next": "2016-10-04T10:20:00+00:00" }, }</pre>	

```
"IsPastDue":false  
}
```

Trigger sample

Suppose you have the following timer trigger in the `bindings` array of `function.json`:

JSON

 Copy

```
{  
  "schedule": "0 */5 * * * *",  
  "name": "myTimer",  
  "type": "timerTrigger",  
  "direction": "in"  
}
```

See the language-specific sample that reads the timer object to see whether it's running late.

- [C#](#)
- [F#](#)
- [Node.js](#)

Trigger sample in C#

C#

 Copy

```
public static void Run(TimerInfo myTimer, TraceWriter log)  
{  
    if(myTimer.IsPastDue)  
    {  
        log.Info("Timer is running late!");  
    }  
    log.Info($"C# Timer trigger function executed at: {DateTime.Now} ");  
}
```

Trigger sample in F#

F#

 Copy

```
let Run(myTimer: TimerInfo, log: TraceWriter ) =  
    if (myTimer.IsPastDue) then  
        log.Info("F# function is running late.")  
    let now = DateTime.Now.ToLongTimeString()  
    log.Info(sprintf "F# function executed at %s!" now)
```

Trigger sample in Node.js

JavaScript

 Copy

```
module.exports = function (context, myTimer) {  
    var timeStamp = new Date().toISOString();  
  
    if(myTimer.isPastDue)  
    {  
        context.log('Node.js is running late!');  
    }  
    context.log('Node.js timer trigger function ran!', timeStamp);  
  
    context.done();  
};
```

Next steps

For information about other bindings and triggers for Azure Functions, see [Azure Functions triggers and bindings developer reference](#).