mioty® Gateway AVA

Product Description

AVA is a bidirectional, low-cost gateway with the mioty Profiles EU0, EU1, EU2, US0 for usage in Europe and the US.

AVA is easy to install. The Gateway can be connected to your local network via Ethernet. It offers a web interface that gives overview and insights into all available mioty® traffic. It also contains rudimentary development implementations for mioty® application and service centers that allow you to configure your development sensors, decode their traffic, and forward their data via MQTT for easy evaluation. It is also possible to configure the gateway to connect to Application and Service Centers of your choice via BSSCI instead.

AVA sample kit available

- 1 AVA mioty® Gateway
- 1 MUNIA-M Indoor Humidity- and Temperature Sensor
- 1 ROBIN-M Outdoor Humidity- and Temperature Sensor

The sample kit is a perfect solution for testing the possibilities of the mioty® technology.

Order code:
AVA mioty® Gateway: A001-0090-001
AVA sample kit: A001-0105-001

Features:

- Input frequency range (EU): 868 – 870 MHz
- Input frequency range (US): 915 – 917 MHz
- Tx power: 14 dBm
- Sensitivity (EU1): < -135 dBm
- Input Voltage: 5 V DC (USB-C)
- Typical Input Current (EU1): aaprox. 900mA
- Typical Input Current (EU2): approx. 1200 mA
- Dimensions: 56 x 90 x 25 mm
- Weight: approx. 0,16 kg
- Temperature range: 0-35C°
- Humidity range: 20-80%

WEPTECH elektronik GmbH reserves the right to make changes to technical specifications or functions of the product without any notice. WEPTECH elektronik GmbH does not assume any responsibility for the use of the described products. All trademarks , registered trademarks and product names are the property of their owners.

Your partner in Engineering and EMS.