KingbaseES 错误码参考手册

金仓数据库管理系统 KingbaseES

文档版本：V9（V009R001C010）

发布日期：2025 年 12 月 3 日

中电科金仓（北京）科技股份有限公司

目　录

第 1 章　错误代码概述 1

第 2 章　Oracle 模式错误码 2

第 3 章　MySQL 模式错误码 16

第 4 章　SQLServer 模式错误码 30

版权声明 49

服务周期承诺 50

第1章　错误代码概述

遵循 SQL 标准对"SQLSTATE" 代码的习惯，KingbaseES 服务器发出的所有信息都将被赋予五位字符的错误代码。通常，想要知道发生了什么错误状况，应当查阅错误代码，而不是查看文本形式的错误消息。在 KingbaseES 的版本之间，错误代码不会轻易改变，也不会随着错误消息的本地化而改变。请注意部分（但不是全部）KingbaseES 生成的错误代码是由 SQL 标准定义的；部分标准没有定义的额外错误代码是由 KingbaseES 定义或者从其它数据库借用而来。

根据标准，错误代码的前两个字符表示错误类别，而后三个字符表示在该类别内的一种特定情况。因此，那些不能识别特定错误代码的应用仍然可以从错误类别中推断要做什么。

下述章节列出了 KingbaseES 不同兼容形态下定义的所有错误代码（其中部分代码目前实际上并未使用，但在 SQL 标准中有定义）。错误类别也在其中列出。每个错误类别都有一个“标准”错误代码，其后三个字符是 000 ，这个代码只用于那些属于该类别但是没有被赋予更特定代码的错误情况。

“情况名称”列中显示的内容是在 PL/SQL 中使用的。情况名称可以被写成大写或小写形式（注意 PL/SQL 不识别警告（与错误不同）情况名称，它们是类别 00、01 和 02）。

对于某些类型的错误，服务器会报告与错误相关的数据库对象（一个表、表列、数据类型或约束）的名称。例如，导致一个 unique_violation 错误的唯一约束的名称。这些名字被包含在错误报告消息的独立域中，这样应用就不必从可能是本地化可读的消息文本中抽取它们到 KingbaseES 位置，对于这个特性的完全覆盖只在 SQLSTATE 类别 23（完整性约束未被）的错误中存在，但是很可能会在未来进行扩展。

02-Oracle 兼容形态错误码 03-MySQL 兼容形态错误码 04-SQLServer 兼容形态错误码

第2章　Oracle 模式错误码

备注:

错误等级：S 为成功，W 为 Warning 警告，E 为 ERROR 错误。

表 2.1: Oracle 模式错误码

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
1000	warning	W	NUMBER scale > presion, and set presion = scale, (%d, %d)	number 标度 > 精度, 设置精度 = 标度 (%d, %d)
2000	no_data	W	variable or constant "%s" does not exists	变量或常量%s 不存在
8000	connection_exception	E	failed(rc:%d) to flush message(%d)	刷新消息 (rc:%d) 失败 (%d)
8003	connection_does_not_exist	E	connection not available	连接不可用
8006	connection_failure	E	errors communicating with the proxy	与代理通信错误
8001	sqlclient_unable_to _establish_sqlconnection	E	could not establish connection	无法建立连接
08P01	protocol_violation	E	incomplete message from client	从客户端过来的不完整信息
0A000	feature_not_supported	E	FETCH statement cannot return multiple rows	FETCH 语句无法返回多条记录
0L000	invalid_grantor	E	defaulting grantor to user ID %u	缺省将授权者身份给予用户 ID %u

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
0LP01	invalid_grant_operation	E	missing or invalid privilege	缺失或者无效权限
0P000	invalid_role_specification	E	could not translate name	不能翻译名称
0Z002	stacked_diagnostics_accessed _without_active_handle	E	GET STACKED DIAGNOSTICS cannot be used outside an exceptionhandler	GET STACKED DIAGNOSTICS 不能用于异常处理之外
20000	case_not_found	E	case not found	没有找到 CASE
21000	cardinality_violation	E	query ”%s” returned more than one row	查询”%s” 返回多条数据
22000	data_exception	E	the leading precision of the interval is too small: ”%d”	interval 值的前导精度太小：”%d”
2202E		E	typmod array must be type cstring[]	typmod 数组必须是 cstring[] 类型
2202E	array_subscript_error	E	wrong number of array subscripts	数组下标错误
22021	character_not_in_repertoire	E	invalid multibyte character for locale	无效的多字节字符, 对于 locale
22008	datetime_field_overflow	E	date/time field value out of range: ”%s”	日期/时间值超出范围: ”%s”
22008		E	timestamp out of range	时间戳超出范围
22012	division_by_zero	E	division by zero	除以零
22015	interval_field_overflow	E	interval field value out of range: ”%s”	间隔字段超出范围: ”%s”
2201E	invalid_argument_for _logarithm	E	cannot take logarithm of a negative number	无法取负数的对数
22014	invalid_argument_for_ntile _function	E	argument of ntile must be greater than zero	ntile 的参数必须大于零
22016	invalid_argument_for_nth _value_function	E	argument of nth_value must be greater than zero	nth_value 的参数必须大于零

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
2201F	invalid_argument_for_power_function	E	zero raised to a negative power is undefined	被提升到负乘方的最低点没有定义
2201G	invalid_argument_for_width_bucket_function	E	count must be greater than zero	count 必须大于 0
22007	invalid_datetime_format	E	invalid input syntax for type %s: "%s"	类型%s: "%s" 输入语法无效
22025	invalid_escape_sequence	E	invalid Unicode escape	无效的 Unicode 转义字符
22P06	nonstandard_use_of_escape_character	E	nonstandard use of escape in a string literal	在字符串常量中以不标准的方法使用转义字符
22023	invalid_parameter_value	E	Invalid input parameter	参数值无效
22013	invalid_preceding_or_following_size	E	frame starting offsetVal must not be negative	frame startoffsetval 不能为负
2201B	invalid_regular_expression	E	invalid regular expression: %s	无效的正则表达式: %s
2201W	invalid_row_count_in_limit_clause	E	%s must not be negative	%s 参数不能为负数
2201X	invalid_row_count_in_result_offset_clause	E	OFFSET must not be negative	OFFSET 后的值不能是负数
2202H	invalid_tablesample_argument	E	tablesample method %s requires %d argument, not %d	表采样方法%s 要求%d 个参数, 而不是%d 个
2202G	invalid_tablesample_repeat	E	TABLESAMPLE REPEATABLE parameter cannot be null	TABLESAMPLE REPEATABLE 参数不能为 null
22009	invalid_time_zone_displacement_value	E	time zone displacement out of range	时区位移超出范围
2200C	invalid_use_of_escape_character	E	SQL regular expression may not contain more than twoescape-double-quote separators	SQL 正则表达式不能包含两个以上的转义双引号分隔符
22004	null_value_not_allowed	E	dimension values cannot be null	维度值不能为空

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22003	numeric_value_out_of _range	E	integer out of range	整数超出范围
2200H	sequence_generator_limit _exceeded	E	nextval: over maximum value of sequence ”%s” (%s)	nextval: 超过序列”%s” 的最大值了 (%s)
22026	string_data_length _mismatch	E	bit string length %d does not match type bit(%d)	bit 字符串的长度 (%d) 与 bit 类型 (%d) 不匹配.
22001	string_data_right _truncation	E	value too long for type character varying(%d)	对于可变字符类型来说, 值太长了 (%d)
22011	substring_error	E	negative substring length not allowed	不允许子串长度为负数
22027	trim_error	E	trim set should have only one character	不允许多个字符的情况下删除字符集中只能有一个字符
2200F	zero_length_character _string	E	output cannot be empty string	输出不能有空字符串
22P02	invalid_text_representation	E	invalid input syntax for type %s: ”%s”	类型%s: ”%s” 输入语法无效
22P03	invalid_binary _representation	E	invalid length in external bit string	无效的外部位串长度
22P04	bad_copy_file_format	E	invalid COPY file header (missing flags)	无效的 COPY 文件头 (缺少标志)
22P05	untranslatable_character	E	unsupported Unicode escape sequence	不支持的 Unicode 转义序列
2200L	not_an_xml_document	E	not an XML document	不是一个 XML 文档
2200M	invalid_xml_document	E	could not parse XML document	不能解析 XML 文档
2200N	invalid_xml_content	E	invalid XML content	无效的 xml 内容
2200S	invalid_xml_comment	E	invalid XML comment	无效的 XML 注释
2200T	invalid_xml_processing _instruction	E	invalid XML processing instruction	无效的 XML 处理指令

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22030	duplicate_json_object_key_value	E	duplicate JSON object key value	重复的 JSON 键值
22032	invalid_json_text	E	at args %d,JSON syntax error.	在参数%d,JSON 语法错误.
22033	invalid_sql_json_subscript	E	jsonpath array subscript is out of bounds	jsonpath 数组下标越界
22034	more_than_one_sql_json_item	E	JSON path expression in JSON_QUERY should return singleton itemwithout wrapper	JSON_QUERY 中的 JSON 路径表达式应该返回一个没有包装器的单例项目
22035	no_sql_json_item	E	no SQL/JSON item	没有 SQL/JSON 项
22036	non_numeric_sql_json_item	E	jsonpath item method .%s() can only be applied to a string ornumeric value	jsonpath 成员方法.%s() 只能接收字符串或数字
22038	singleton_sql_json_item_required	E	single boolean result is expected	预期单个布尔结果
22039	sql_json_array_not_found	E	jsonpath wildcard array accessor can only be applied to anarray	jsonpath 通配符数组访问器只能应用于数组
2203A	sql_json_member_not_found	E	jsonpath member accessor can only be applied to an object	jsonpath 成员访问器只能应用于对象
2203B	sql_json_number_not_found	E	operand of unary jsonpath operator %s is not a numeric value	一元的 jsonpath 操作符%s 的操作数不是一个数值
2203C	sql_json_object_not_found	E	jsonpath wildcard member accessor can only be applied to anobject	jsonpath 通配符成员访问器只能应用于对象
2203F	sql_json_scalar_required	E	JSON path expression in JSON_VALUE should return singleton scalaritem	JSON_VALUE 中的 JSON 路径表达式应该返回一个标量项

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
23001	restrict_violation	E	The exclusion constraint does not support ALTER TABLE MODIFYCONSTRAINT ENABLE/DISABLE	排他约束不支持 ALTER TABLE MODIFY CONSTRAINT ENABLE/ DISABLE
23502	not_null_violation	E	null value in column ”%s” violates not-null constraint	在字段”%s” 中空值违反了非空约束
23503	foreign_key_violation	E	insert or update on table ” %s” violates foreign key constraint”%s”	在表”%s” 上执行插入或更新操作违反外键约束”%s”
23505	unique_violation	E	duplicate key value violates unique constraint ”%s”	重复键违反唯一约束”%s”
23514	check_violation	E	no partition of relation ”%s” found for row	没有为行找到关系”%s” 的分区
23P01	exclusion_violation	E	could not create exclusion constraint ”%s”	无法创建排他约束”%s”
24000	invalid_cursor_state	E	cursor %s has not open	游标%s 未打开
25000	invalid_transaction_state	E	cannot commit during a parallel operation	并行操作期间无法提交
25001	active_sql_transaction	E	cannot export a snap from a subtransaction	无法从子事务导出快照
25006	read_only_sql_transaction	E	cannot create temporary tables during recovery	不能在恢复过程中创建临时表
25P01	no_active_sql_transaction	E	can only be used in transaction blocks	只能在事务块中使用
25P02	in_failed_sql_transaction	E	current transaction is aborted, commands ignored until end oftransaction block	当前事务被终止, 事务块结束之前的查询被忽略
26000	invalid_sql_statement_name	E	Filename ”%s” is too long	文件”%s” 太长
27000	triggered_data_change _violation	E	tuple to be deleted was already modified by an operation triggeredby the current command	待删除元组值已经被当前命令触发的操作修改了

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
28000	invalid_authorization _specification	E	KB certificate authentication failed for user ”%s”	用户”%s” 的 KB 证书身份验证失败
28P01	invalid_password	E	password authentication failed for user ”%s”	用户”%s” Password 认证失败
28P02	weak_password	E	password is too weak!	密码太弱!
2BP01	dependent_objects_still _exist	E	cannot drop %s because %s requires it	无法删除%s, 因为%s 需要它
2D000	invalid_transaction _termination	E	invalid transaction termination	无效交易终止
2F005	function_executed_no _return_statement	E	control reached end of function without RETURN	控制流程到达函数的结束部分, 但是没有看到 RETURN
2F003	prohibited_sql_statement _attempted	E	password is required	密码是被要求的
34000	invalid_cursor_name	E	cursor ”%s” does not exist	游标”%s” 不存在
38000	external_routine_exception	E	uuid library failure: %d	uuid 库失败：%d
39004	null_value_not_allowed	E	null is not allowed in column ”%s”	列”%s” 中不允许为空
39P02	srf_protocol_violated	E	table-function protocol for materialize mode was not followed	没有跟随针对物化模式的表函数协议
39P03	event_trigger_protocol _violated	E	%s can only be called in a sql _drop event trigger function	%s 只能在 sql_drop 事件触发器函数中被调用
3B001	invalid_savepoint _specification	E	savepoint ”%s” does not exist	保存点”%s” 不存在
3F000	invalid_schema_name	E	cannot create private database link under public schema, pleasespecify public keyword or change the current schema	不能再公有模式下创建 databaselink, 请指定 public 关键字或者更改当前模式
40001	serialization_failure	E	could not serialize access due to concurrent update	由于同步更新而无法串行访问

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
40P01	deadlock_detected	E	deadlock detected	检测到死锁
42000	syntax_error_or_access _rule_violation	E	syntax error or access rule violation	语法错误或者违反接入规则
42601	syntax_error	E	conflicting or redundant options	选项冲突或过多
42501	insufficient_privilege	E	must be superuser to alter superusers	只有超级用户能修改超级用户
42803	grouping_error	E	aggregate function calls cannot be nested	不允许嵌套调用聚合函数
42P20	windowing_error	E	frame start cannot be UNBOUNDED FOLLOWING	框架的起始位置不能被执行 UNBOUNDED FOLLOWING 操作
42P19	invalid_recursion	E	recursive reference to query ”%s” must not appear more thanonce	对查询”%s” 的递归引用不能出现多次
42830	invalid_foreign_key	E	number of referencing and referenced columns for foreign keydisagree	外键的关联数和关联字段不一致
42602	invalid_name	E	invalid set label ”%s”	无效的设置标签”%s”
42622	name_too_long	E	the length of the ”%s” type is too long	”%s” 类型的长度太长
42939	reserved_name	E	role name ”%s” is reserved	角色名称”%s” 被保留了
42804	datatype_mismatch	E	cannot compare arrays of different element types	无法比较不同元素类型的数组
42P21	collation_mismatch	E	collation mismatch between implicit collations ”%s” and” %s”	排序名：”%s” 和”%s” 之间的排序规则不匹配
42P22	indeterminate_collation	E	could not determine which collation to use for string hashing	无法确定用于字符串哈希的排序规则
42809	wrong_object_type	E	type %s is not composite	类型%s 不是复合类型

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
428C9	generated_always	E	Cannot insert explicit value for identity column in table '%s'when	当 IDENTITY_INSERT 为 OFF 时, 不能往表'%s' 中 identity 列显示插入值
42P29	undefined_synonym	E	synonym %s.%s does not exist	同义词%s.%s 不存在
42P30	duplicate_synonym	E	synonym %s already exists	同义词%s 已经存在
42703	undefined_column	E	column "%s" of relation "%s" does not exist	关系"%$2s" 的"%$1s" 字段不存在
42883	undefined_function	E	function "%s" does not exist	函数%s 不存在
42P01	undefined_table	E	relation "%s.%s" does not exist	关系"%s.%s" 不存在
42P02	undefined_parameter	E	there is no parameter :%s	没有参数：%s
42704	undefined_object	E	language "%s" does not exist	language 对象"%s" 不存在
42701	duplicate_column	E	column "%s" appears twice in primary key constraint	主键约束中列"%s" 出现了两次
42P03	duplicate_cursor	E	cursor "%s" already in use	游标"%s" 已经被打开使用
42P04	duplicate_database	E	database "%s" already exists, skipping	数据库"%s" 已经存在, 跳过
42723	duplicate_function	E	function or procedure "%s" already exists	函数或过程"%s" 已存在
42P05	duplicate_prepared _statement	E	prepared statement "%s" already exists	预编译语句"%s" 已经存在
42P06	duplicate_schema	E	schema "%s" already exists	模式"%s" 已存在
42P07	duplicate_table	E	relation "%s" already exists	关系"%s" 已存在
42712	duplicate_alias	E	table name "%s" specified more than once	表名"%s" 指定了多次
42710	duplicate_object	E	type "%s" already exists	类型"%s" 已存在

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
42702	ambiguous_column	E	common column name ”%s” appears more than once in righttable	共同的字段名”%s” 在右边的表中出现了多次
42725	ambiguous_function	E	more than one function named ”%s”	”%s” 函数超过一个
42P08	ambiguous_parameter	E	user cannot join resource group %s	用户不能加入资源组%s
42P09	ambiguous_alias	E	table reference ”%s” is ambiguous	表关联”%s” 是不明确的
42P10	invalid_column_reference	E	Invalid column in the INSERT VALUES Clause	INSERT VALUES 子句中的列无效
42611	invalid_column_definition	E	column ”%s” inherits conflicting default values	列”%s” 继承与默认值冲突
42P11	invalid_cursor_definition	E	maximum open cursors exceeded	超出最大打开游标数
42P13	invalid_function_definition	E	cannot change mode of input parameter	无法更改输入参数的模式
42P15	invalid_schema_definition	E	CREATE specifies a schema (%s) different from the one being created(%s)	CREATE 指定的模式 (%s) 和将要创建的 (%s) 不同
42P16	invalid_table_definition	E	temporary tables cannot specify a schema name	临时表不能指定模式名
42P17	invalid_object_definition	E	table ”%s” is not a partitioned table	表”%s” 不是一个分区表
44000	with_check_option_violation	E	new row violates check option for view ”%s”	新行违反了视图”%s” 的检查选项
53000	insufficient_resources	E	out of file descriptors: %m; release and retry	超出文件描述符: %m; 释放再重试
53100	disk_full	E	could not extend file ”%s”: wrote only %d of %d bytes at block%u	无法扩展文件”%$1s”: 只能在块%$4u 上写%$3d 字节的%$2d
53200	out_of_memory	E	out of memory	内存溢出/内存用尽

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
53300	too_many_connections	E	sorry, too many clients already	对不起, 已经有太多的客户端
53400	configuration_limit_exceeded	E	temporary file size exceeds temp_file_limit (%dkB)	临时文件大小超过最大允许值 temp_file_limit(%dkB)
54000	program_limit_exceeded	E	too many INTO variables specified	在 INTO 后面指定了太多的变量
54001	statement_too_complex	E	too many grouping sets present (maximum 4096)	出现过多分组集合（最大 4096 个）
54011	too_many_columns	E	number of columns (%d) exceeds limit (%d)	字段个数 (%d) 超出限制 (%d)
54023	too_many_arguments	E	functions cannot have more than %d argument	函数的参数不能多于%d 个
55000	object_not_in_prerequisite _state	E	src_restrict must be loaded via shared_preload_libraries	src_restrict 必须通过 shared _preload_libraries 加载
55006	object_in_use	E	directory ”%s” already in use as a tablespace	目录”%s” 以一个表空间的形式正在使用
55P02	cant_change_runtime _param	E	parameter ”%s” cannot be changed	参数”%s” 不能被改变
55P03	lock_not_available	E	could not obtain lock on relation	无法在关系”%s.%s” 上获得锁
55P04	unsafe_new_enum_value _usage	E	unsafe use of new value ”%s” of enum type %s	不安全地使用”%s”, 该值是 enum 类型%s 上的一个新的成员值
57014	query_canceled	E	canceling statement due to user request	由于用户请求而正在取消查询
57P01	admin_shutdown	E	terminating logical replication worker due to administratorcommand	由于管理员命令而终止逻辑复制工作线程
57P02	crash_shutdown	E	terminating connection because of crash of another serverprocess	中断联接, 因为其它服务器进程崩溃

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
57P03	cannot_connect_now	E	the database system is in recovery mode	数据库系统在恢复模式中
57P04	database_dropped	E	terminating connection due to conflict with recovery	因为与恢复存在冲突终止连接
58000	system_error	E	could not get token information: error cod	无法获得令牌信息: 错误码
58030	io_error	E	could not read input file %m	无法读取输入文件%m
58P01	undefined_file	E	cannot create directory "%s": %m	无法创建目录"%s": %m
72000	snapshot_too_old	E	snapshot too old	快照太旧
F0001	lock_file_exists	E	lock file "%s" already exists	锁文件"%s" 已经存在.
HV000	fdw_error	E	OCINumberFromInt failed to convert integer to NUMBER	OCINumberFromInt 将 int 转换到 NUMBER 类型失败
HV005	fdw_column_name_not_found	E	system attribute "%s" can't be fetched from remote relation	不能从远端关系中获取系统属性"%s"
HV002	fdw_dynamic_parameter_value_needed	E	either filename or program is required for file_fdw foreigntables	file_fdw 外表需要文件名或程序
HV024	fdw_invalid_attribute_value	E	invalid value for option "%s"	无效的 option 值"%s"
HV004	fdw_invalid_data_type	E	column "%s" of foreign table "%s" cannot be converted to orfrom Oracle data type	外表"%s" 的列"%s" 不能和 oracle 数据类型互相映射
HV00D	fdw_invalid_option_name	E	invalid option "%s"	无效的选项"%s"
HV001	fdw_out_of_memory	E	out of memory	内存耗尽
HV00P	fdw_no_schemas	E	foreign-data wrapper "%s" does not support IMPORT FOREIGNSCHEMA	fdw "%s" 不支持 IMPORT FOREIGN SCHEMA 功能
HV00J	fdw_option_name_not_found	E	required option "%s" in foreign table "%s" missing	需要的 option "%s" 丢失, 无法访问外表"%s"

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
HV00Q	fdw_schema_not_found	E	remote schema ”%s” does not exist	远端模式名”%s” 不存在
HV00R	fdw_table_not_found	E	relation %s.%s does not exist	关系%s.%s 不存在
HV00L	fdw_unable_to_create_execution	E	RETURNING is not supported by this FDW	FDW 不支持 RETURNING 子句
HV00M	fdw_unable_to_create_reply	E	Internal oracle_fdw error: encountered unknown node type %d	内部 oracle_fdw 错误: 不支持处理无法识别的节点类型：%d
HV00N	fdw_unable_to_establish_connection	E	failed to connect to MySQL: %s	无法连接到 MySQL：%s
P0002	no_data_found	E	no data found	未找到数据
P0003	too_many_rows	E	query returned more than one row	查询返回多条记录
P0004	assert_failure	E	assertion failed	断言失败
P0005	self_is_null	E	method dispatch on NULL SELF argument is disallowed	不允许对 NULL SELF 参数进行方法调度
P0006	collection_is_null	E	reference to uninitialized collection	对未初始化集合的引用
P0007	subscript_outside_limit	E	subscript outside limit	集合类型下标超出限制
P0008	subscript_beyond_count	E	subscript beyond count	下标超出计数
P0013	sys_invalid_rowid	E	invalid input syntax for type %s: ”%s”	类型%s 的输入语法：”%s” 无效
P0014	rowtype_mismatch	E	The number of variables declared in the INTO list must match that ofselected columns.	变量个数和 INTO 列表的个数不匹配
P0306	record_invalid_operation	E	record type not support operation is null or is not null	记录类型不支持操作为空或为空
XX000	internal_error	E	resolvebindcpuliststr fail	解决绑定 CPU 列表失败

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
XX001	data_corrupted	E	checksum error occurred	发生校验和错误
XX002	index_corrupted	E	index ”%s” contains unexpected zero page at block %u	索引”%s” 在块%u 上包含未期望的零页
F1000	tablespace_is_offline	E	Tablespace(%s) you specify in offline mode, does not allow alteroperation!	在脱机模式下指定的表空间（%s）不允许更改操作！
F1001	tablespace_is_readonly	E	Tablespace(%s) you specify is not in read write mode, does not allowswitch to read only mode!	您指定的表空间（%s）未处于读写模式, 不允许切换到只读模式！
F1002	tablespace_is_write	E	Tablespace(%s) you specify is not in read only mode, does not allowswitch to read write mode!	您指定的表空间（%s）未处于只读模式, 不允许切换到读写模式！
F1003	tablespace_operation _notsupport	E	System tablespace’s mode cannot be changed!	系统表空间的模式无法更改！

第3章　MySQL 模式错误码

备注:

错误等级：S 为成功，W 为 Warning 警告，E 为 ERROR 错误。

表 3.1: MySQL 模式错误码

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
1000	warning	W	NUMBER scale > presion, and set presion = scale, (%d, %d)	number 标度 > 精度, 设置精度 = 标度 (%d, %d)
2000	no_data	W	variable or constant ”%s” does not exists	变量或常量”%s” 不存在
8000	connection_exception	E	failed(rc:%d) to flush message(%d)	刷新消息 (rc:%d) 失败 (%d)
8003	connection_does_not_exist	E	connection not available	连接不可用
8006	connection_failure	E	errors communicating with the proxy	与代理通信错误
8001	sqlclient_unable_to _establish_sqlconnection	E	could not establish connection	无法建立连接
08P01	protocol_violation	E	incomplete message from client	从客户端过来的不完整信息
0A000	feature_not_supported	E	FETCH statement cannot return multiple rows	FETCH 语句无法返回多条记录

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
0L000	invalid_grantor	E	defaulting grantor to user ID %u	缺省将授权者身份给予用户 ID %u
0LP01	invalid_grant_operation	E	missing or invalid privilege	缺失或者无效权限
0P000	invalid_role_specification	E	could not translate name	不能翻译名称
0Z002	stacked_diagnostics_accessed _without_active_handle	E	GET STACKED DIAGNOSTICS cannot be used outside an exceptionhandler	GET STACKED DIAGNOSTICS 不能用于异常处理之外
20000	case_not_found	E	case not found	没有找到 CASE
21000	cardinality_violation	E	query ”%s” returned more than one row	查询”%s” 返回多条数据
22000	data_exception	E	the leading precision of the interval is too small: ”%d”	interval 值的前导精度太小：” %d”
2202E		E	typmod array must be type cstring[]	typmod 数组必须是 cstring[] 类型
2202E	array_subscript_error	E	wrong number of array subscripts	数组下标错误
22021	character_not_in_repertoire	E	invalid multibyte character for locale	无效的多字节字符, 对于 locale
22008	datetime_field_overflow	E	date/time field value out of range: ”%s”	日期/时间值超出范围: ”%s”
22008		E	timestamp out of range	时间戳超出范围
22012	division_by_zero	E	division by zero	除以零
22015	interval_field_overflow	E	interval field value out of range: ”%s”	间隔字段超出范围: ”%s”
2201E	invalid_argument_for _logarithm	E	cannot take logarithm of a negative number	无法取负数的对数
22014	invalid_argument_for_ntile _function	E	argument of ntile must be greater than zero	ntile 的参数必须大于零

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22016	invalid_argument_for_nth_value_function	E	argument of nth_value must be greater than zero	nth_value 的参数必须大于零
2201F	invalid_argument_for_power_function	E	zero raised to a negative power is undefined	被提升到负乘方的最低点没有定义
2201G	invalid_argument_for_width_bucket_function	E	count must be greater than zero	count 必须大于 0
22007	invalid_datetime_format	E	invalid input syntax for type %s: "%s"	类型%s: "%s" 输入语法无效
22025	invalid_escape_sequence	E	invalid Unicode escape	无效的 Unicode 转义字符
22P06	nonstandard_use_of_escape_character	E	nonstandard use of escape in a string literal	在字符串常量中以不标准的方法使用转义字符
22023	invalid_parameter_value	E	Invalid input parameter	参数值无效
22013	invalid_preceding_or_following_size	E	frame starting offsetVal must not be negative	frame startoffsetval 不能为负
2201B	invalid_regular_expression	E	invalid regular expression: %s	无效的正则表达式: %s
2201W	invalid_row_count_in_limit_clause	E	%s must not be negative	%s 参数不能为负数
2201X	invalid_row_count_in_result_offset_clause	E	OFFSET must not be negative	OFFSET 后的值不能是负数
2202H	invalid_tablesample_argument	E	tablesample method %s requires %d argument, not %d	表采样方法%s 要求%d 个参数, 而不是%d 个
2202G	invalid_tablesample_repeat	E	TABLESAMPLE REPEATABLE parameter cannot be null	TABLESAMPLE REPEATABLE 参数不能为 null
22009	invalid_time_zone_displacement_value	E	time zone displacement out of range	时区位移超出范围
2200C	invalid_use_of_escape_character	E	SQL regular expression may not contain more than twoescape-double-quote separators	SQL 正则表达式不能包含两个以上的转义双引号分隔符

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22004	null_value_not_allowed	E	dimension values cannot be null	维度值不能为空
22003	numeric_value_out_of _range	E	integer out of range	整数超出范围
2200H	sequence_generator_limit _exceeded	E	nextval: over maximum value of sequence ”%s” (%s)	nextval: 超过序列”%s” 的最大值了 (%s)
22026	string_data_length _mismatch	E	bit string length %d does not match type bit(%d)	bit 字符串的长度 (%d) 与 bit 类型 (%d) 不匹配.
22001	string_data_right _truncation	E	value too long for type character varying(%d)	对于可变字符类型来说, 值太长了 (%d)
22011	substring_error	E	negative substring length not allowed	不允许子串长度为负数
22027	trim_error	E	trim set should have only one character	不允许多个字符的情况下删除字符集中只能有一个字符
2200F	zero_length_character _string	E	output cannot be empty string	输出不能有空字符串
22P02	invalid_text_representation	E	invalid input syntax for type %s: ”%s”	类型%s: ”%s” 输入语法无效
22P03	invalid_binary _representation	E	invalid length in external bit string	无效的外部位串长度
22P04	bad_copy_file_format	E	invalid COPY file header (missing flags)	无效的 COPY 文件头 (缺少标志)
22P05	untranslatable_character	E	unsupported Unicode escape sequence	不支持的 Unicode 转义序列
2200L	not_an_xml_document	E	not an XML document	不是一个 XML 文档
2200M	invalid_xml_document	E	could not parse XML document	不能解析 XML 文档
2200N	invalid_xml_content	E	invalid XML content	无效的 xml 内容
2200S	invalid_xml_comment	E	invalid XML comment	无效的 XML 注释
2200T	invalid_xml_processing _instruction	E	invalid XML processing instruction	无效的 XML 处理指令

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22030	duplicate_json_object_key_value	E	duplicate JSON object key value	重复的 JSON 键值
22032	invalid_json_text	E	at args %d,JSON syntax error.	在参数%d,JSON 语法错误.
22033	invalid_sql_json_subscript	E	jsonpath array subscript is out of bounds	jsonpath 数组下标越界
22034	more_than_one_sql_json_item	E	JSON path expression in JSON_QUERY should return singleton itemwithout wrapper	JSON_QUERY 中的 JSON 路径表达式应该返回一个没有包装器的单例项目
22035	no_sql_json_item	E	no SQL/JSON item	没有 SQL/JSON 项
22036	non_numeric_sql_json_item	E	jsonpath item method .%s() can only be applied to a string ornumeric value	jsonpath 成员方法.%s() 只能接收字符串或数字
22038	singleton_sql_json_item_required	E	single boolean result is expected	预期单个布尔结果
22039	sql_json_array_not_found	E	jsonpath wildcard array accessor can only be applied to anarray	jsonpath 通配符数组访问器只能应用于数组
2203A	sql_json_member_not_found	E	jsonpath member accessor can only be applied to an object	jsonpath 成员访问器只能应用于对象
2203B	sql_json_number_not_found	E	operand of unary jsonpath operator %s is not a numeric value	一元的 jsonpath 操作符%s 的操作数不是一个数值
2203C	sql_json_object_not_found	E	jsonpath wildcard member accessor can only be applied to anobject	jsonpath 通配符成员访问器只能应用于对象
2203F	sql_json_scalar_required	E	JSON path expression in JSON_VALUE should return singleton scalaritem	JSON_VALUE 中的 JSON 路径表达式应该返回一个标量项

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
23001	restrict_violation	E	The exclusion constraint does not support ALTER TABLE MODIFYCONSTRAINT ENABLE/DISABLE	排他约束不支持 ALTER TABLE MODIFY CONSTRAINT ENABLE/ DISABLE
23502	not_null_violation	E	null value in column ”%s” violates not-null constraint	在字段”%s” 中空值违反了非空约束
23503	foreign_key_violation	E	insert or update on table ” %s” violates foreign key constraint”%s”	在表”%s” 上执行插入或更新操作违反外键约束”%s”
23505	unique_violation	E	duplicate key value violates unique constraint ”%s”	重复键违反唯一约束”%s”
23514	check_violation	E	no partition of relation ”%s” found for row	没有为行找到关系”%s” 的分区
23P01	exclusion_violation	E	could not create exclusion constraint ”%s”	无法创建排他约束”%s”
24000	invalid_cursor_state	E	cursor %s has not open	游标%s 未打开
25000	invalid_transaction_state	E	cannot commit during a parallel operation	并行操作期间无法提交
25001	active_sql_transaction	E	cannot export a snap from a subtransaction	无法从子事务导出快照
25006	read_only_sql_transaction	E	cannot create temporary tables during recovery	不能在恢复过程中创建临时表
25P01	no_active_sql_transaction	E	can only be used in transaction blocks	只能在事务块中使用
25P02	in_failed_sql_transaction	E	current transaction is aborted, commands ignored until end oftransaction block	当前事务被终止, 事务块结束之前的查询被忽略
26000	invalid_sql_statement_name	E	Filename ”%s” is too long	文件”%s” 太长
27000	triggered_data_change _violation	E	tuple to be deleted was already modified by an operation triggeredby the current command	待删除元组值已经被当前命令触发的操作修改了

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
28000	invalid_authorization _specification	E	KB certificate authentication failed for user ”%s”	用户”%s” 的 KB 证书身份验证失败
28P01	invalid_password	E	password authentication failed for user ”%s”	用户”%s” Password 认证失败
28P02	weak_password	E	password is too weak!	密码太弱!
2BP01	dependent_objects_still _exist	E	cannot drop %s because %s requires it	无法删除%s, 因为%s 需要它
2D000	invalid_transaction _termination	E	invalid transaction termination	无效交易终止
2F005	function_executed_no _return_statement	E	control reached end of function without RETURN	控制流程到达函数的结束部分, 但是没有看到 RETURN
2F003	prohibited_sql_statement _attempted	E	password is required	密码是被要求的
34000	invalid_cursor_name	E	cursor ”%s” does not exist	游标”%s” 不存在
38000	external_routine_exception	E	uuid library failure: %d	uuid 库失败：%d
39004	null_value_not_allowed	E	null is not allowed in column ”%s”	列”%s” 中不允许为空
39P02	srf_protocol_violated	E	table-function protocol for materialize mode was not followed	没有跟随针对物化模式的表函数协议
39P03	event_trigger_protocol _violated	E	%s can only be called in a sql _drop event trigger function	%s 只能在 sql_drop 事件触发器函数中被调用
3B001	invalid_savepoint _specification	E	savepoint ”%s” does not exist	保存点”%s” 不存在
3F000	invalid_schema_name	E	cannot create private database link under public schema, pleasespecify public keyword or change the current schema	不能再公有模式下创建 databaselink, 请指定 public 关键字或者更改当前模式
40001	serialization_failure	E	could not serialize access due to concurrent update	由于同步更新而无法串行访问

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
40P01	deadlock_detected	E	deadlock detected	检测到死锁
42000	syntax_error_or_access _rule_violation	E	syntax error or access rule violation	语法错误或者违反接入规则
42601	syntax_error	E	conflicting or redundant options	选项冲突或过多
42501	insufficient_privilege	E	must be superuser to alter superusers	只有超级用户能修改超级用户
42803	grouping_error	E	aggregate function calls cannot be nested	不允许嵌套调用聚合函数
42P20	windowing_error	E	frame start cannot be UNBOUNDED FOLLOWING	框架的起始位置不能被执行 UNBOUNDED FOLLOWING 操作
42P19	invalid_recursion	E	recursive reference to query ”%s” must not appear more thanonce	对查询”%s” 的递归引用不能出现多次
42830	invalid_foreign_key	E	number of referencing and referenced columns for foreign keydisagree	外键的关联数和关联字段不一致
42602	invalid_name	E	invalid set label ”%s”	无效的设置标签”%s”
42622	name_too_long	E	the length of the ”%s” type is too long	”%s” 类型的长度太长
42939	reserved_name	E	role name ”%s” is reserved	角色名称”%s” 被保留了
42804	datatype_mismatch	E	cannot compare arrays of different element types	无法比较不同元素类型的数组
42P21	collation_mismatch	E	collation mismatch between implicit collations ”%s” and” %s”	排序名：”%s” 和”%s” 之间的排序规则不匹配
42P22	indeterminate_collation	E	could not determine which collation to use for string hashing	无法确定用于字符串哈希的排序规则
42809	wrong_object_type	E	type %s is not composite	类型%s 不是复合类型

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
428C9	generated_always	E	Cannot insert explicit value for identity column in table '%s'when	当 IDENTITY_INSERT 为 OFF 时, 不能往表'%s' 中 identity 列显示插入值
42P29	undefined_synonym	E	synonym %s.%s does not exist	同义词%s.%s 不存在
42P30	duplicate_synonym	E	synonym %s already exists	同义词%s 已经存在
42703	undefined_column	E	column "%s" of relation "%s" does not exist	关系"%$2s" 的"%$1s" 字段不存在
42883	undefined_function	E	function "%s" does not exist	函数"%s" 不存在
42P01	undefined_table	E	relation "%s.%s" does not exist	关系"%s.%s" 不存在
42P02	undefined_parameter	E	there is no parameter :%s	没有参数：%s
42704	undefined_object	E	language "%s" does not exist	language 对象"%s" 不存在
42701	duplicate_column	E	column "%s" appears twice in primary key constraint	主键约束中列"%s" 出现了两次
42P03	duplicate_cursor	E	cursor "%s" already in use	游标"%s" 已经被打开使用
42P04	duplicate_database	E	database "%s" already exists, skipping	数据库"%s" 已经存在, 跳过
42723	duplicate_function	E	function or procedure "%s" already exists	函数或过程"%s" 已存在
42P05	duplicate_prepared _statement	E	prepared statement "%s" already exists	预编译语句"%s" 已经存在
42P06	duplicate_schema	E	schema "%s" already exists	模式"%s" 已存在
42P07	duplicate_table	E	relation "%s" already exists	关系"%s" 已存在
42712	duplicate_alias	E	table name "%s" specified more than once	表名"%s" 指定了多次
42710	duplicate_object	E	type "%s" already exists	类型"%s" 已存在

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
42702	ambiguous_column	E	common column name ”%s” appears more than once in righttable	共同的字段名”%s” 在右边的表中出现了多次
42725	ambiguous_function	E	more than one function named ”%s”	”%s” 函数超过一个
42P08	ambiguous_parameter	E	user cannot join resource group %s.	用户不能加入资源组%s
42P09	ambiguous_alias	E	table reference ”%s” is ambiguous	表关联”%s” 是不明确的
42P10	invalid_column_reference	E	Invalid column in the INSERT VALUES Clause	INSERT VALUES 子句中的列无效
42611	invalid_column_definition	E	column ”%s” inherits conflicting default values	列”%s” 继承与默认值冲突
42P11	invalid_cursor_definition	E	maximum open cursors exceeded	超出最大打开游标数
42P13	invalid_function_definition	E	cannot change mode of input parameter	无法更改输入参数的模式
42P15	invalid_schema_definition	E	CREATE specifies a schema (%s) different from the one being created(%s)	CREATE 指定的模式 (%s) 和将要创建的 (%s) 不同
42P16	invalid_table_definition	E	temporary tables cannot specify a schema name	临时表不能指定模式名
42P17	invalid_object_definition	E	table ”%s” is not a partitioned table	表”%s” 不是一个分区表
44000	with_check_option_violation	E	new row violates check option for view ”%s”	新行违反了视图”%s” 的检查选项
53000	insufficient_resources	E	out of file descriptors: %m; release and retry	超出文件描述符: %m; 释放再重试
53100	disk_full	E	could not extend file ”%s”: wrote only %d of %d bytes at block%u	无法扩展文件”%$1s”: 只能在块%$4u 上写%$3d 字节的%$2d
53200	out_of_memory	E	out of memory	内存溢出/内存用尽

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
53300	too_many_connections	E	sorry, too many clients already	对不起, 已经有太多的客户端
53400	configuration_limit_exceeded	E	temporary file size exceeds temp_file_limit (%dkB)	临时文件大小超过最大允许值 temp_file_limit(%dkB)
54000	program_limit_exceeded	E	too many INTO variables specified	在 INTO 后面指定了太多的变量
54001	statement_too_complex	E	too many grouping sets present (maximum 4096)	出现过多分组集合（最大 4096 个）
54011	too_many_columns	E	number of columns (%d) exceeds limit (%d)	字段个数 (%d) 超出限制 (%d)
54023	too_many_arguments	E	functions cannot have more than %d argument	函数的参数不能多于%d 个
55000	object_not_in_prerequisite _state	E	src_restrict must be loaded via shared_preload_libraries	src_restrict 必须通过 shared _preload_libraries 加载
55006	object_in_use	E	directory ”%s” already in use as a tablespace	目录”%s” 以一个表空间的形式正在使用
55P02	cant_change_runtime _param	E	parameter ”%s” cannot be changed	参数”%s” 不能被改变
55P03	lock_not_available	E	could not obtain lock on relation ”%s.%s”	无法在关系”%s.%s” 上获得锁
55P04	unsafe_new_enum_value _usage	E	unsafe use of new value ”%s” of enum type %s	不安全地使用”%s”, 该值是 enum 类型%s 上的一个新的成员值
57014	query_canceled	E	canceling statement due to user request	由于用户请求而正在取消查询
57P01	admin_shutdown	E	terminating logical replication worker due to administratorcommand	由于管理员命令而终止逻辑复制工作线程
57P02	crash_shutdown	E	terminating connection because of crash of another serverprocess	中断联接, 因为其它服务器进程崩溃

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
57P03	cannot_connect_now	E	the database system is in recovery mode	数据库系统在恢复模式中
57P04	database_dropped	E	terminating connection due to conflict with recovery	因为与恢复存在冲突终止连接
58000	system_error	E	could not get token information: error cod	无法获得令牌信息: 错误码
58030	io_error	E	could not read input file %m	无法读取输入文件%m
58P01	undefined_file	E	cannot create directory "%s": %m	无法创建目录"%s": %m
72000	snapshot_too_old	E	snapshot too old	快照太旧
F0001	lock_file_exists	E	lock file "%s" already exists	锁文件"%s" 已经存在.
HV000	fdw_error	E	OCINumberFromInt failed to convert integer to NUMBER	OCINumberFromInt 将 int 转换到 NUMBER 类型失败
HV005	fdw_column_name_not_found	E	system attribute "%s" can't be fetched from remote relation	不能从远端关系中获取系统属性"%s"
HV002	fdw_dynamic_parameter_value_needed	E	either filename or program is required for file_fdw foreigntables	file_fdw 外表需要文件名或程序
HV024	fdw_invalid_attribute_value	E	invalid value for option "%s"	无效的 option 值"%s"
HV004	fdw_invalid_data_type	E	column "%s" of foreign table "%s" cannot be converted to orfrom Oracle data type	外表%s 的列%s 不能和 oracle 数据类型互相映射
HV00D	fdw_invalid_option_name	E	invalid option "%s"	无效的选项"%s"
HV001	fdw_out_of_memory	E	out of memory	内存耗尽
HV00P	fdw_no_schemas	E	foreign-data wrapper "%s" does not support IMPORT FOREIGNSCHEMA	fdw "%s" 不支持 IMPORT FOREIGN SCHEMA 功能
HV00J	fdw_option_name_not_found	E	required option "%s" in foreign table "%s" missing	需要的 option "%s" 丢失, 无法访问外表"%s"

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
HV00Q	fdw_schema_not_found	E	remote schema ”%s” does not exist	远端模式名”%s” 不存在
HV00R	fdw_table_not_found	E	relation %s.%s does not exist	关系%s.%s 不存在
HV00L	fdw_unable_to_create_execution	E	RETURNING is not supported by this FDW	FDW 不支持 RETURNING 子句
HV00M	fdw_unable_to_create_reply	E	Internal oracle_fdw error: encountered unknown node type %d.	内部 oracle_fdw 错误: 不支持处理无法识别的节点类型：%d
HV00N	fdw_unable_to_establish_connection	E	failed to connect to MySQL: %s	无法连接到 MySQL：%s
P0002	no_data_found	E	no data found	未找到数据
P0003	too_many_rows	E	query returned more than one row	查询返回多条记录
P0004	assert_failure	E	assertion failed	断言失败
P0005	self_is_null	E	method dispatch on NULL SELF argument is disallowed	不允许对 NULL SELF 参数进行方法调度
P0006	collection_is_null	E	reference to uninitialized collection	对未初始化集合的引用
P0007	subscript_outside_limit	E	subscript outside limit	集合类型下标超出限制
P0008	subscript_beyond_count	E	subscript beyond count	下标超出计数
P0013	sys_invalid_rowid	E	invalid input syntax for type %s: ”%s”	类型%s 的输入语法”%s” 无效
P0014	rowtype_mismatch	E	The number of variables declared in the INTO list must match that of selected columns.	变量个数和 INTO 列表的个数不匹配
P0306	record_invalid_operation	E	record type not support operation is null or is not null	记录类型不支持操作为空或为空
XX000	internal_error	E	resolvebindcpuliststr fail.	解决绑定 CPU 列表失败.

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
XX001	data_corrupted	E	checksum error occurred	发生校验和错误
XX002	index_corrupted	E	index ”%s” contains unexpected zero page at block %u	索引”%s” 在块%u 上包含未期望的零页
F1000	tablespace_is_offline	E	Tablespace(%s) you specify in offline mode, does not allow alteroperation!	在脱机模式下指定的表空间（%s）不允许更改操作！
F1001	tablespace_is_readonly	E	Tablespace(%s) you specify is not in read write mode, does not allowswitch to read only mode!	您指定的表空间（%s）未处于读写模式, 不允许切换到只读模式！
F1002	tablespace_is_write	E	Tablespace(%s) you specify is not in read only mode, does not allowswitch to read write mode!	您指定的表空间（%s）未处于只读模式, 不允许切换到读写模式！
F1003	tablespace_operation _notsupport	E	System tablespace’s mode cannot be changed!	系统表空间的模式无法更改！
0Z003	invalid_condition_number	E	Invalid condition number	无效的 CONDITION 值

第4章　SQLServer 模式错误码

备注:

错误等级：S 为成功，W 为 Warning 警告，E 为 ERROR 错误。

表 4.1: SQLServer 模式错误码

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
00000	successful_completion	S		
01000	warning	W	NUMBER scale > presion, and set presion = scale, (%d, %d)	number 标度 > 精度, 设置精度 = 标度 (%d, %d)
0100C	dynamic_result_sets _returned	W		
01008	implicit_zero_bit_padding	W		
01003	null_value_eliminated_in _set_function	W		
01007	privilege_not_granted	W		
01006	privilege_not_revoked	W		
01004	string_data_right _truncation	W		
01P01	deprecated_feature	W		
02000	no_data	W	variable or constant ”%s” does not exists	变量或常量%s 不存在

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
02001	no_additional_dynamic _result_sets_returne	W		
03000	sql_statement_not_yet_ _complete	E		
08000	connection_exception	E	failed(rc:%d) to flush message(%d)	刷新消息 (rc:%d) 失败 (%d)
08003	connection_does_not_exist	E	connection not available	连接不可用
08006	connection_failure	E	errors communicating with the proxy	与代理通信错误
08001	sqlclient_unable_to _establish_sqlconnection	E	could not establish connection	无法建立连接
08004	sqlserver_rejected _establishment_of _sqlconnection	E		
08007	transaction_resolution_ _unknown	E		
08P01	protocol_violation	E	incomplete message from client	从客户端过来的不完整信息
09000	triggered_action_exception	E		
0A000	feature_not_supported	E	FETCH statement cannot return multiple rows	FETCH 语句无法返回多条记录
0B000	invalid_transaction _initiation	E		
0F000	locator_exception	E		
0F001	invalid_locator_specification	E		
0L000	invalid_grantor	E	defaulting grantor to user ID %u	缺省将授权者身份给予用户 ID %u
0LP01	invalid_grant_operation	E	missing or invalid privilege	缺失或者无效权限
0P000	invalid_role_specification	E	could not translate name	不能翻译名称

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
0Z000	diagnostics_exception	E	目前已经废弃	
0Z002	stacked_diagnostics_accessed_without_active_handler	E	GET STACKED DIAGNOSTICS cannot be used outside an exceptionhandler	GET STACKED DIAGNOSTICS 不能用于异常处理之外
20000	case_not_found	E	case not found	没有找到 CASE
21000	cardinality_violation	E	query ”%s” returned more than one row	查询”%s” 返回多条数据
22000	data_exception	E	the leading precision of the interval is too small: ”%d”	interval 值的前导精度太小：”%d”
2202E		E	typmod array must be type cstring[]	typmod 数组必须是 cstring[] 类型
2202E	array_subscript_error	E	typmod array must be type cstring[]	typmod 数组必须是 cstring[] 类型
22021	character_not_in_repertoire	E	invalid multibyte character for locale	无效的多字节字符, 对于 locale
22008	datetime_field_overflow	E	date/time field value out of range: ”%s”	日期/时间值超出范围: ”%s”
22008		E	date/time field value out of range: ”%s”	日期/时间值超出范围: ”%s”
22012	division_by_zero	E	division by zero	除以零
22005	error_in_assignment	E		
2200B	escape_character_conflict	E		
22022	indicator_overflow	E		
22015	interval_field_overflow	E	interval field value out of range: ”%s”	间隔字段超出范围: ”%s”
2201E	invalid_argument_for_logarithm	E	cannot take logarithm of a negative number	无法取负数的对数
22014	invalid_argument_for_ntile_function	E	argument of ntile must be greater than zero	ntile 的参数必须大于零

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22016	invalid_argument_for_nth_value_function	E	argument of nth_value must be greater than zero	nth_value 的参数必须大于零
2201F	invalid_argument_for_power_function	E	zero raised to a negative power is undefined	被提升到负乘方的最低点没有定义
2201G	invalid_argument_for_width_bucket_function	E	count must be greater than zero	count 必须大于 0
22018	invalid_character_value_for_cast	E		
22007	invalid_datetime_format	E	invalid input syntax for type %s: "%s"	类型%s: "%s" 输入语法无效
22019	invalid_escape_character	E		
2200D	invalid_escape_octet	E		
22025	invalid_escape_sequence	E	invalid Unicode escape	无效的 Unicode 转义字符
22P06	nonstandard_use_of_escape_character	E	nonstandard use of escape in a string literal	在字符串常量中以不标准的方法使用转义字符
22010	invalid_indicator_parameter_value	E		
22023	invalid_parameter_value	E	Invalid input parameter	参数值无效
22013	invalid_preceding_or_following_size	E	frame starting offsetVal must not be negative	frame startoffsetval 不能为负
2201B	invalid_regular_expression	E	invalid regular expression: %s	无效的正则表达式: %s
2201W	invalid_row_count_in_limit_clause	E	%s must not be negative	%s 参数不能为负数
2201X	invalid_row_count_in_result_offset_clause	E	OFFSET must not be negative	OFFSET 后的值不能是负数
2202H	invalid_tablesample_argument	E	tablesample method %s requires %d argument, not %d	表采样方法%s 要求%d 个参数, 而不是%d 个

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
2202G	invalid_tablesample_repeat	E	TABLESAMPLE REPEATABLE parameter cannot be null	TABLESAMPLE REPEATABLE 参数不能为 null
22009	invalid_time_zone _displacement_value	E	time zone displacement out of range	时区位移超出范围
2200C	invalid_use_of_escape _character	E	SQL regular expression may not contain more than twoescape-double-quote separators	SQL 正则表达式不能包含两个以上的转义双引号分隔符
2200G	most_specific_type _mismatch	E		
22004	null_value_not_allowed	E	dimension values cannot be null	维度值不能为空
22002	null_value_no_indicator _parameter	E		
22003	numeric_value_out_of _range	E	integer out of range	整数超出范围
2200H	sequence_generator_limit _exceeded	E	nextval: over maximum value of sequence ”%s” (%s)	nextval: 超过序列”%s” 的最大值了 (%s)
22026	string_data_length _mismatch	E	bit string length %d does not match type bit(%d)	bit 字符串的长度 (%d) 与 bit 类型 (%d) 不匹配.
22001	string_data_right _truncation	E	value too long for type character varying(%d)	对于可变字符类型来说, 值太长了 (%d)
22011	substring_error	E	negative substring length not allowed	不允许子串长度为负数
22027	trim_error	E	trim set should have only one character	不允许多个字符的情况下删除字符集中只能有一个字符
22024	unterminated_c_string	E		
2200F	zero_length_character _string	E	output cannot be empty string	输出不能有空字符串
22P01	floating_point_exception	E		

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22P02	invalid_text_representation	E	invalid input syntax for type %s: "%s"	类型%s: "%s" 输入语法无效
22P03	invalid_binary _representation	E	invalid length in external bit string	无效的外部位串长度
22P04	bad_copy_file_format	E	invalid COPY file header (missing flags)	无效的 COPY 文件头 (缺少标志)
22P05	untranslatable_character	E	unsupported Unicode escape sequence	不支持的 Unicode 转义序列
2200L	not_an_xml_document	E	not an XML document	不是一个 XML 文档
2200M	invalid_xml_document	E	could not parse XML document	不能解析 XML 文档
2200N	invalid_xml_content	E	invalid XML content	无效的 xml 内容
2200S	invalid_xml_comment	E	invalid XML comment	无效的 XML 注释
2200T	invalid_xml_processing _instruction	E	invalid XML processing instruction	无效的 XML 处理指令
22030	duplicate_json_object_key _value	E	duplicate JSON object key value	重复的 JSON 键值
22032	invalid_json_text	E	at args %d,JSON syntax error.	在参数%d,JSON 语法错误.
22033	invalid_sql_json_subscript	E	jsonpath array subscript is out of bounds	jsonpath 数组下标越界
22034	more_than_one_sql_json _item	E	JSON path expression in JSON_QUERY should return singleton itemwithout wrapper	JSON_QUERY 中的 JSON 路径表达式应该返回一个没有包装器的单例项目
22035	no_sql_json_item	E	no SQL/JSON item	没有 SQL/JSON 项
22036	non_numeric_sql_json_item	E	jsonpath item method .%s() can only be applied to a string ornumeric value	jsonpath 成员方法.%s() 只能接收字符串或数字
22037	non_unique_keys_in_a _json_object	E		

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
22038	singleton_sql_json_item _required	E	single boolean result is expected	预期单个布尔结果
22039	sql_json_array_not_found	E	jsonpath wildcard array accessor can only be applied to anarray	jsonpath 通配符数组访问器只能应用于数组
2203A	sql_json_member_not _found	E	jsonpath member accessor can only be applied to an object	jsonpath 成员访问器只能应用于对象
2203B	sql_json_number_not _found	E	operand of unary jsonpath operator %s is not a numeric value	一元的 jsonpath 操作符%s 的操作数不是一个数值
2203C	sql_json_object_not_found	E	jsonpath wildcard member accessor can only be applied to anobject	jsonpath 通配符成员访问器只能应用于对象
2203D	too_many_json_array _elements	E		
2203E	too_many_json_object _members	E		
2203F	sql_json_scalar_required	E	JSON path expression in JSON_VALUE should return singleton scalaritem	JSON_VALUE 中的 JSON 路径表达式应该返回一个标量项
23000	integrity_constraint _violation	E		
23001	restrict_violation	E	The exclusion constraint does not support ALTER TABLE MODIFYCONSTRAINT ENABLE/DISABLE	排他约束不支持 ALTER TABLE MODIFY CONSTRAINT ENABLE/ DISABLE
23502	not_null_violation	E	null value in column ”%s” violates not-null constraint	在字段”%s” 中空值违反了非空约束
23503	foreign_key_violation	E	insert or update on table ” %s” violates foreign key constraint”%s”	在表”%s” 上执行插入或更新操作违反外键约束”%s”
23505	unique_violation	E	duplicate key value violates unique constraint ”%s”	重复键违反唯一约束”%s”

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
23514	check_violation	E	no partition of relation ”%s” found for row	没有为行找到关系”%s” 的分区
23P01	exclusion_violation	E	could not create exclusion constraint ”%s”	无法创建排他约束”%s”
24000	invalid_cursor_state	E	cursor %s has not open	游标%s 未打开
25000	invalid_transaction_state	E	cannot commit during a parallel operation	并行操作期间无法提交
25001	active_sql_transaction	E	cannot export a snap from a subtransaction	无法从子事务导出快照
25002	branch_transaction_already _active	E		
25008	held_cursor_requires_same _isolation_level	E		
25003	inappropriate_access_mode _for_branch_transaction	E		
25004	inappropriate_isolation_level _for_branch_transaction	E		
25005	no_active_sql_transaction _for_branch_transaction	E		
25006	read_only_sql_transaction	E	cannot create temporary tables during recovery	不能在恢复过程中创建临时表
25007	schema_and_data _statement_mixing_not _supported	E		
25P01	no_active_sql_transaction	E	can only be used in transaction blocks	只能在事务块中使用
25P02	in_failed_sql_transaction	E	current transaction is aborted, commands ignored until end oftransaction block	当前事务被终止, 事务块结束之前的查询被忽略
25P03	idle_in_transaction_session _timeout	E		
25P04	client_idle_timeout	E		

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
26000	invalid_sql_statement_name	E	Filename ”%s” is too long	文件”%s” 太长
27000	triggered_data_change _violation	E	tuple to be deleted was already modified by an operation triggeredby the current command	待删除元组值已经被当前命令触发的操作修改了
28000	invalid_authorization _specification	E	KB certificate authentication failed for user ”%s”	用户”%s” 的 KB 证书身份验证失败
28P01	invalid_password	E	password authentication failed for user ”%s”	用户”%s” Password 认证失败
28P02	weak_password	E	password is too weak!	密码太弱!
2B000	dependent_privilege _descriptors_still_exist	E	dependent privilege descriptors still exist	依然存在依赖的权限描述
2BP01	dependent_objects_still _exist	E	cannot drop %s because %s requires it	无法删除%s 因为%s 需要它
2D000	invalid_transaction _termination	E	invalid transaction termination	无效交易终止
2F000	sql_routine_exception	E		
2F005	function_executed_no _return_statement	E	control reached end of function without RETURN	控制流程到达函数的结束部分, 但是没有看到 RETURN
2F002	modifying_sql_data_not _permitted	E		
2F003	prohibited_sql_statement _attempted	E	password is required	密码是被要求的
2F004	reading_sql_data_not _permitted	E		
34000	invalid_cursor_name	E	cursor ”%s” does not exist	游标”%s” 不存在
38000	external_routine_exception	E	uuid library failure: %d	uuid 库失败：%d
38001	containing_sql_not _permitted	E		

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
38002	modifying_sql_data_not_permitted	E		
38003	prohibited_sql_statement_attempted	E		
38004	reading_sql_data_not_permitted	E		
39000	external_routine_invocation_exception	E		
39001	invalid_sqlstate_returned	E		
39004	null_value_not_allowed	E	null is not allowed in column ”%s”	列”%s” 中不允许为空
39P01	trigger_protocol_violated	E		
39P02	srf_protocol_violated	E	table-function protocol for materialize mode was not followed	没有跟随针对物化模式的表函数协议
39P03	event_trigger_protocol_violated	E	%s can only be called in a sql_drop event trigger function	%s 只能在 sql_drop 事件触发器函数中被调用
3B000	savepoint_exception	E		
3B001	invalid_savepoint_specification	E	savepoint ”%s” does not exist	保存点”%s” 不存在
3F000	invalid_schema_name	E	missing or invalid synonym identifier the current default schema ispublic	同义词标识符丢失或无效，当前默认模式为 public
40000	transaction_rollback	E		
40002	transaction_integrity_constraint_violation	E		
40001	serialization_failure	E	could not serialize access due to concurrent update	由于同步更新而无法串行访问
40003	statement_completion_unknown	E		

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
40P01	deadlock_detected	E	deadlock detected	检测到死锁
42601	syntax_error	E	conflicting or redundant options	选项冲突或过多
42501	insufficient_privilege	E	must be superuser to alter superusers	只有超级用户能修改超级用户
42846	cannot_coerce	E		
42803	grouping_error	E	aggregate function calls cannot be nested	不允许嵌套调用聚合函数
42P20	windowing_error	E	frame start cannot be UNBOUNDED FOLLOWING	框架的起始位置不能被执行 UNBOUNDED FOLLOWING 操作.
42P19	invalid_recursion	E	recursive reference to query ”%s” must not appear more thanonce	对查询”%s” 的递归引用不能出现多次
42830	invalid_foreign_key	E	number of referencing and referenced columns for foreign keydisagree	外键的关联数和关联字段不一致
42602	invalid_name	E	invalid set label ”%s”	无效的设置标签”%s”
42622	name_too_long	E	the length of the ”%s” type is too long	”%s” 类型的长度太长
42939	reserved_name	E	role name ”%s” is reserved	角色名称”%s” 被保留了
42804	datatype_mismatch	E	cannot compare arrays of different element types	无法比较不同元素类型的数组
42P18	indeterminate_datatype	E		
42P21	collation_mismatch	E	collation mismatch between implicit collations ”%s” and” %s”	排序名：”%s” 和”%s” 之间的排序规则不匹配
42P22	indeterminate_collation	E	could not determine which collation to use for string hashing	无法确定用于字符串哈希的排序规则

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
42809	wrong_object_type	E	type %s is not composite	类型%s 不是复合类型
428C9	generated_always	E	Cannot insert explicit value for identity column in table '%s'when	当 IDENTITY_INSERT 为 OFF 时, 不能往表'%s' 中 identity 列显示插入值
42P29	undefined_synonym	E	synonym %s.%s does not exist	同义词%s.%s 不存在
42P30	duplicate_synonym	E	synonym %s already exists	同义词%s 已经存在
42703	undefined_column	E	column "%s" of relation "%s" does not exist	关系""%2$s"" 的""%1$s"" 字段不存在
34000	invalid_cursor_name	E	cursor "%s" does not exist	游标"%s" 不存在
3D000	invalid_catalog_name	E		
42883	undefined_function	E	function "%s" does not exist	函数"%s" 不存在
26000		E	Filename "%s" is too long	文件"%s" 太长
3F000		E	cannot create private database link under public schema,pleasespecify public keyword or change the current schema	不能再公有模式下创建 databaselink, 请指定 public 关键字或者更改当前模式
42P01	undefined_table	E	relation "%s.%s" does not exist	关系"%s.%s" 不存在
42P02	undefined_parameter	E	there is no parameter :%s	没有参数：%s
42704	undefined_object	E	language "%s" does not exist	language 对象"%s" 不存在
42701	duplicate_column	E	column "%s" appears twice in primary key constraint	主键约束中列"%s" 出现了两次
42P03	duplicate_cursor	E	cursor "%s" already in use	游标"%s" 已经被打开使用
42P04	duplicate_database	E	database "%s" already exists, skipping	数据库"%s" 已经存在, 跳过
42723	duplicate_function	E	function or procedure "%s" already exists	函数或过程"%s" 已存在

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
42P05	duplicate_prepared _statement	E	prepared statement ”%s” already exists	预编译语句”%s” 已经存在
42P06	duplicate_schema	E	schema ”%s” already exists	模式”%s” 已存在
42P07	duplicate_table	E	relation ”%s” already exists	关系”%s” 已存在
42712	duplicate_alias	E	table name ”%s” specified more than once	表名”%s” 指定了多次
42710	duplicate_object	E	type ”%s” already exists	类型”%s” 已存在
42702	ambiguous_column	E	common column name ”%s” appears more than once in righttable	共同的字段名”%s” 在右边的表中出现了多次
42725	ambiguous_function	E	more than one function named ”%s”	”%s” 函数超过一个
42P08	ambiguous_parameter	E	user cannot join resource group %s.	用户不能加入资源组%s
42P09	ambiguous_alias	E	table reference ”%s” is ambiguous	表关联”%s” 是不明确的
42P10	invalid_column_reference	E	Invalid column in the INSERT VALUES Clause	INSERT VALUES 子句中的列无效
42611	invalid_column_definition	E	column ”%s” inherits conflicting default values	列”%s” 继承与默认值冲突
42P11	invalid_cursor_definition	E	maximum open cursors exceeded	超出最大打开游标数
42P12	invalid_database_definition	E		
42P13	invalid_function_definition	E	cannot change mode of input parameter	无法更改输入参数的模式
42P14	invalid_prepared_statement _definition	E		
42P15	invalid_schema_definition	E	CREATE specifies a schema (%s) different from the one being created(%s)	CREATE 指定的模式 (%s) 和将要创建的 (%s) 不同

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
42P16	invalid_table_definition	E	temporary tables cannot specify a schema name	临时表不能指定模式名
42P17	invalid_object_definition	E	table ”%s” is not a partitioned table	表”%s” 不是一个分区表
44000	with_check_option_violation	E	new row violates check option for view ”%s”	新行数据违反了视图”%s” 的检查项
53000	insufficient_resources	E	out of file descriptors: %m; release and retry	超出文件描述符: %m; 释放再重试
53100	disk_full	E	could not extend file ”%s”: wrote only %d of %d bytes at block%u	无法扩展文件””%1$s””: 只能在块%4$u 上写%3$d 字节的%2$d
53200	out_of_memory	E	out of memory	内存溢出/内存用尽
53300	too_many_connections	E	sorry, too many clients already	对不起, 已经有太多的客户端
53400	configuration_limit_exceeded	E	temporary file size exceeds temp_file_limit (%dkB)	临时文件大小超过最大允许值 temp_file_limit(%dkB)
54000	program_limit_exceeded	E	too many INTO variables specified	在 INTO 后面指定了太多的变量
54001	statement_too_complex	E	too many grouping sets present (maximum 4096)	出现过多分组集合（最大 4096 个）
54011	too_many_columns	E	number of columns (%d) exceeds limit (%d)	字段个数 (%d) 超出限制 (%d)
54023	too_many_arguments	E	functions cannot have more than %d argument	函数的参数不能多于%d 个
55000	object_not_in_prerequisite _state	E	Views ”%s” containing WITH READ ONLY are not automaticallyupdatable.	只读视图”%s” 不支持自动更新
55006	object_in_use	E	directory ”%s” already in use as a tablespace	目录”%s” 以一个表空间的形式正在使用
55P02	cant_change_runtime _param	E	parameter ”%s” cannot be changed	参数%s 不能被改变

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
55P03	lock_not_available	E	could not obtain lock on relation	无法在关系”%s.%s” 上获得锁
55P04	unsafe_new_enum_value _usage	E	unsafe use of new value ”%s” of enum type %s	不安全地使用”%s”, 该值是 enum 类型%s 上的一个新的成员值
57000	operator_intervention	E		
57014	query_canceled	E	canceling statement due to user request	由于用户请求而正在取消查询
57P01	admin_shutdown	E	terminating logical replication worker due to administratorcommand	由于管理员命令而终止逻辑复制工作线程
57P02	crash_shutdown	E	terminating connection because of crash of another serverprocess	中断联接, 因为其它服务器进程崩溃
57P03	cannot_connect_now	E	the database system is in recovery mode	数据库系统在恢复模式中
57P04	database_dropped	E	terminating connection due to conflict with recovery	因为与恢复存在冲突终止连接
58000	system_error	E	could not get token information: error cod	无法获得令牌信息: 错误码
58030	io_error	E	could not read input file %m	无法读取输入文件%m
58P01	undefined_file	E	cannot create directory ”%s”: %m	无法创建目录”%s”: %m
58P02	duplicate_file	E		
72000	snapshot_too_old	E	snapshot too old	快照太旧
F0000	config_file_error	E		
F0001	lock_file_exists	E	lock file ”%s” already exists	锁文件”%s” 已经存在.
HV000	fdw_error	E	OCINumberFromInt failed to convert integer to NUMBER	OCINumberFromInt 将 int 转换到 NUMBER 类型失败

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
HV005	fdw_column_name_not_found	E	system attribute ”%s” can’t be fetched from remote relation	不能从远端关系中获取系统属性”%s”
HV002	fdw_dynamic_parameter_value_needed	E	either filename or program is required for file_fdw foreigntables	file_fdw 外表需要文件名或程序
HV010	fdw_function_sequence_error	E		
HV021	fdw_inconsistent_descriptor_information	E		
HV024	fdw_invalid_attribute_value	E	invalid value for option ”%s”	无效的 option 值”%s”
HV007	fdw_invalid_column_name	E		
HV008	fdw_invalid_column_number	E		
HV004	fdw_invalid_data_type	E	column ”%s” of foreign table ”%s” cannot be converted to orfrom Oracle data type	外表”%s” 的列”%s” 不能和 oracle 数据类型互相映射
HV006	fdw_invalid_data_type_descriptors	E		
HV091	fdw_invalid_descriptor_field_identifier	E		
HV00B	fdw_invalid_handle	E		
HV00C	fdw_invalid_option_index	E		
HV00D	fdw_invalid_option_name	E	invalid option ”%s”	无效的选项”%s”
HV090	fdw_invalid_string_length_or_buffer_length	E		
HV00A	fdw_invalid_string_format	E		
HV009	fdw_invalid_use_of_null_pointer	E		

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
HV014	fdw_too_many_handles	E		
HV001	fdw_out_of_memory	E	out of memory	内存耗尽
HV00P	fdw_no_schemas	E	foreign-data wrapper ”%s” does not support IMPORT FOREIGNSCHEMA	fdw ”%s” 不支持 IMPORT FOREIGN SCHEMA 功能
HV00J	fdw_option_name_not _found	E	required option ”%s” in foreign table ”%s” missing	需要的 option ”%s” 丢失, 无法访问外表”%s”
HV00K	fdw_reply_handle	E		
HV00Q	fdw_schema_not_found	E	remote schema ”%s” does not exist	远端模式名”%s” 不存在
HV00R	fdw_table_not_found	E	relation %s.%s does not exist	关系%s.%s 不存在
HV00L	fdw_unable_to_create _execution	E	RETURNING is not supported by this FDW	FDW 不支持 RETURNING 子句
HV00M	fdw_unable_to_create _reply	E	Internal oracle_fdw error: encountered unknown node type %d.	内部 oracle_fdw 错误: 不支持处理无法识别的节点类型：%d
HV00N	fdw_unable_to_establish _connection	E	failed to connect to MySQL: %s	无法连接到 MySQL：%s
P0000	plpgsql_error	E		
P0001	raise_exception	E		
P0002	no_data_found	E	no data found	未找到数据
P0003	too_many_rows	E	query returned more than one row	查询返回多条记录
P0004	assert_failure	E	assertion failed	断言失败
P0005	self_is_null	E	method dispatch on NULL SELF argument is disallowed	不允许对 NULL SELF 参数进行方法调度
P0006	collection_is_null	E	reference to uninitialized collection	对未初始化集合的引用
P0007	subscript_outside_limit	E	subscript outside limit	集合类型下标超出限制

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
P0008	subscript_beyond_count	E	subscript beyond count	下标超出计数
P0009	malformed_wrap_input	E		
P0010	timeout_on_resource	E		
P0011	not_logged_on	E		
P0012	login_denied	E		
P0013	sys_invalid_rowid	E	invalid input syntax for type %s: ”%s”	类型%s 的输入语法无效
P0014	rowtype_mismatch	E	The number of variables declared in the INTO list must match that ofselected columns.	变量个数和 INTO 列表的个数不匹配
P0015	access_into_null	E		
P0016	no_data_needed	E		
P0182	value_error	E		
P0306	record_invalid_operation	E	record type not support operation is null or is not null	记录类型不支持操作为空或为空
P0999	user_defined_exception	E		
XX000	internal_error	E	resolvebindcpuliststr fail.	解决绑定 CPU 列表失败.
XX001	data_corrupted	E	checksum error occurred	发生校验和错误
XX002	index_corrupted	E	index ”%s” contains unexpected zero page at block %u	索引”%s” 在块%u 上包含未期望的零页
EE000	encryption_engine	E		
F1000	tablespace_is_offline	E	Tablespace(%s) you specify in offline mode, does not allow alteroperation!	在脱机模式下指定的表空间（%s）不允许更改操作！

-续表-

错误码	错误码描述	错误等级	错误内容 (英文)	错误内容 (中文)
F1001	tablespace_is_readonly	E	Tablespace(%s) you specify is not in read write mode, does not allowswitch to read only mode!	您指定的表空间（%s）未处于读写模式, 不允许切换到只读模式！
F1002	tablespace_is_write	E	Tablespace(%s) you specify is not in read only mode, does not allowswitch to read write mode!	您指定的表空间（%s）未处于只读模式, 不允许切换到读写模式！
F1003	tablespace_operation _notsupport	E	System tablespace's mode cannot be changed!	系统表空间的模式无法更改！

版权声明

中电科金仓（北京）科技股份有限公司（简称：电科金仓）版权所有，并保留对本手册及本声明的一切权利。

未得到电科金仓的书面许可，任何人不得以任何方式或形式对本手册内的任何部分进行复制、摘录、备份、修改、传播、翻译成其他语言、将其全部或部分用于商业用途。

免责声明

本手册内容依据现有信息制作，由于产品版本升级或其他原因，其内容有可能变更。电科金仓保留在没有任何通知或者提示的情况下对手册内容进行修改的权利。

本手册仅作为使用指导，电科金仓在编写本手册时已尽力保证其内容准确可靠，但并不确保手册内容完全没有错误或遗漏，本手册中的所有信息也不构成任何明示或暗示的担保。

技术支持

- 电科金仓官方网站：http://www.kingbase.com.cn/
- 电科金仓文档中心：http://help.kingbase.com.cn/
- 全国服务热线：400-601-1188
- 电科金仓技术支持与反馈信箱：support@kingbase.com.cn

服务周期承诺

由于市场需求在不断变化，技术创新和发展的进程不断加剧，产品的版本更迭不可避免。电科金仓对于产品版本生命周期的有效管理，有助于您提前规划项目，更好地从产品服务终止上过渡。

表 2: KingbaseES 产品生命周期里程碑

关键里程碑点	定义
产品发布日期	产品正式发布版本，即 GA（general availability）版本的发布日期。
停止销售日期	正式停止销售的日期，版本停止接受订单日。该日之后，产品将不再销售。
停止功能升级日期	在该日期之后，不再提供新特性和新硬件支持。但依旧提供错误修复、安全修复、功能维护等服务。
停止功能维护日期	在该日期之后，不再维护功能，修复问题。但依旧提供安全修复等服务
停止安全维护日期	在该日期之后，不再发布补丁版本修复中高风险漏洞，仅提供有限的支持。
产品服务终止日期	停止提供产品服务和支持的日期。包括软件维护版本，缺陷修复，以及针对该产品的所有服务支持（包括服务热线和远程/现场支持）。

服务周期策略

金仓数据库管理系统 KingbaseES 产品确保以下的服务周期：

1）产品自发布之日起至产品停止功能升级（包含新特性、新硬件支持）之日止不少于 5 年。

2）产品停止功能升级之日起至产品停止功能维护（主要包括问题修复）之日止不少于 4 年。

3）产品功能维护停止之日起至产品停止安全维护（包括中高风险漏洞修复）之日止不少于 2 年。

针对金仓数据库管理系统 KingbaseES V9 产品（发布日期：2022 年 7 月 15 日），其具体服务周期安排如下：

- 产品销售日期：以产品销售合同所约定日期为准。
- 停止升级日期：自产品销售日期起计算，满 5 年之日止。
- 服务终止日期：自产品销售日期起计算，满 11 年之日止。

服务终止策略

金仓数据库管理系统 KingbaseES 产品确保在销售后，至少提供 6 年的服务支持。

备注:

电科金仓将会综合各方因素来确定产品服务终止日期。并将在实际产品服务终止日期之前至少 90 天，通过公开方式宣布产品服务终止日期。