External API Documentation

Download Documentation

Comprehensive guide for integrating with Race Odds Pro APIs

API Overview

Base URL

```
https://oddspro.com.au/api/external/
```

Available Endpoints

- GET `/top-favs` - Top favorite runners
- GET `/leaderboard` - Bookmaker performance stats
- GET `/race/:raceId` - Detailed race information
- GET `/meeting/:meetingId` - Detailed meeting information
- GET `/movers` - Top price shortenings with filtering
- GET `/movers/track/:track` - Track-specific movers
- GET `/drifters` - Top price drifters (price increases)
- GET `/meetings` - All meetings with races
- GET `/results` - All race results with filtering

Additional Endpoints

- GET `/api/races/:id/results` - Single race results with finishing positions

Response Format

All endpoints return JSON with standardized structure:

```
{
  "data": [...],
  "meta": {
    "total": 10,
    "filters": {...}
```

```
  }
}
```

/top-favs Endpoint

Get shortest-priced favorites across all bookmakers

Parameters

`type`	optional	T, H, G, all
`location`	optional	domestic, international, all
`date`	optional	YYYY-MM-DD
`track`	optional	Track name filter
`limit`	optional	Number (default: 10)

Example Request

```
https://oddspro.com.au/api/external/top-favs?
type=T&track=Flemington&limit=5
```

Test Endpoint

INFO

Discovering Race and Meeting IDs

Learn how to find race and meeting IDs for the detail endpoints

Finding Race IDs

1. **Top Favorites:** Each favorite includes a `raceId` field
2. **Meeting Details:** Each race includes an `id` field
3. **Discovery API:** Use `/api/meetings` for all race IDs

Finding Meeting IDs

1. Discovery API: Use `/api/meetings` for all meeting IDs

2. Top Favorites: Each favorite includes meeting information

Discovery Flow Example

```
1. GET /api/meetings → Get all meetings and race IDs
2. GET /api/external/race/[raceId] → Get specific race details
3. GET /api/external/meeting/[meetingId] → Get all races in meeting
```

Test Discovery API Copy Discovery URL

/race/:raceId Endpoint

Get detailed information for a specific race including all runners and their top 3 odds

Parameters

`raceId`	required	Numeric race ID

Example Request

```
https://oddspro.com.au/api/external/race/123456
```

Test Endpoint

/meeting/:meetingId Endpoint

Get all races for a specific meeting with detailed runner information and odds

Parameters

`meetingId`	required	Numeric meeting ID

Example Request

```
https://oddspro.com.au/api/external/meeting/789
```

Test Endpoint

/leaderboard Endpoint

Get bookmaker performance statistics

Parameters

`type`	optional	T, H, G, all
`location`	optional	domestic, international, all
`date`	optional	YYYY-MM-DD

Example Request

```
https://oddspro.com.au/api/external/leaderboard?type=T
```

Test Endpoint

/movers Endpoint

Get top price shortenings (runners with the largest percentage price drops)

Parameters

`type`	optional	T, H, G, all
`location`	optional	domestic, international, all
`track`	optional	Filter by track name (e.g., "Flemington")
`maxOdds`	optional	Maximum current odds (e.g., 10 for $10)
`limit`	optional	Number of results (default: 10)
`date`	optional	YYYY-MM-DD (default:

today)

Response Format

Returns runners with significant price shortenings (5%+ minimum)

```
{
  "data": [
    {
      "runnerId": 123456,
      "runnerName": "Fast Horse",
      "track": "Flemington",
      "raceNumber": 5,
      "raceName": "Melbourne Cup",
      "movementPercentage": 25.5,
      "currentBestOdds": 8.50,
      "firstPrice": 11.00,
      "topOdds": [
        {
          "bookmaker": "sportsbet",
          "price": 8.50,
          "displayName": "Sportsbet"
        }
      ]
    }
  ],
  "meta": {
    "total": 10,
    "filters": { "type": "T", "maxOdds": 20 }
  }
}
```

Example Requests

```
https://oddspro.com.au/api/external/movers?limit=5
```

```
https://oddspro.com.au/api/external/movers?type=T&maxOdds=10&limit=3
```

Test Endpoint

/movers/track/:track Endpoint

Get movers for a specific racing track

Path Parameter

`track`	required	Track name (e.g., "Flemington", "Randwick")

Query Parameters

`type`	optional	T, H, G, all
`maxOdds`	optional	Maximum current odds
`limit`	optional	Number of results (default: 10)

Example Request

```
https://oddspro.com.au/api/external/movers/track/Flemington?limit=5
```

Test Endpoint

/drifters Endpoint

Get runners with significant price increases (drifting odds)

Parameters

`type`	optional	T, H, G, all
`location`	optional	domestic, international, all
`track`	optional	Filter by track name
`maxOdds`	optional	Maximum current odds (e.g., 10)
`minMovement`	optional	Minimum drift % (default: 5)
`limit`	optional	Number of results (default: 10)

Example Request

```
https://oddspro.com.au/api/external/drifters?type=T&limit=5
```

Test Endpoint

/meetings Endpoint

Get all upcoming meetings with race information

Parameters

`type`	optional	T, H, G, all
`location`	optional	domestic, international, all
`date`	optional	YYYY-MM-DD (default: today)

Response Format

Returns all meetings with race details, runners, and bookmaker markets

```
{
  "data": [
    {
      "id": 123,
      "track": "Flemington",
      "location": "VIC",
      "type": "T",
      "races": [
        {
          "id": 456,
          "name": "Melbourne Cup",
          "number": 7,
          "startTime": "2025-11-03T03:00:00Z",
          "runners": [...]
        }
      ]
    }
  ]
}
```

Example Request

```
https://oddspro.com.au/api/external/meetings?
type=T&location=domestic
```

Test Endpoint

/results Endpoint

Get all race results for a specific day with filtering options

Parameters

`date`	optional	YYYY-MM-DD (default: today)
`type`	optional	T, H, G, all
`location`	optional	domestic, international, all
`track`	optional	Filter by track name
`limit`	optional	Number of results (default: all)

Response Format

Returns all races with official results and runner details

```
{
  "data": [
    {
      "raceId": 123456,
      "raceName": "Melbourne Cup",
      "raceNumber": 7,
      "startTime": "2025-01-08T03:00:00Z",
      "distance": 3200,
      "status": "finished",
      "meeting": {
        "track": "Flemington",
        "location": "VIC",
        "type": "T"
      },
      "results": [
        {
          "position": 1,
          "runnerNumber": 4,
          "runnerName": "Winner",
          "trainerName": "John Smith",
          "riderName": "Jane Doe"
        }
      ],
      "rawResults": [[4], [7], [2]]
    }
  ],
  "meta": {
    "total": 15,
    "totalAvailable": 15,
    "filters": {
```

```
      "date": "2025-01-08",
      "type": "all",
      "location": "all"
    }
  }
}
```

Example Request

```
https://oddspro.com.au/api/external/results?date=2025-01-08&type=T&location=domestic
```

Test Endpoint

Note: This endpoint only returns races that have finished and have official results. Use filtering parameters to narrow down to specific meetings or race types.

/api/races/:id/results Endpoint

Get official race results for a single race (not under /external)

Parameters

`id`	required	Numeric race ID

Response Format

Returns formatted results with finishing positions and runner details

```
{
  "raceId": 123456,
  "raceName": "Melbourne Cup",
  "raceNumber": 7,
  "status": "finished",
  "startTime": "2025-11-03T03:00:00Z",
  "meeting": {
    "track": "Flemington",
    "location": "VIC",
    "type": "T"
  },
  "results": [
    {
      "position": 1,
      "runnerNumber": 4,
      "runnerName": "Winner",
      "runnerDetails": {
```

```
        "trainerName": "John Smith",
        "riderName": "Jane Doe"
      }
    }
  ],
  "rawResults": [[4], [7], [2], [1]]
}
```

Example Request

```
https://oddspro.com.au/api/races/123456/results
```

Test Endpoint

Note: This endpoint only returns data for races that have finished and have official results. Returns 404 for upcoming or in-progress races.

/tracks Endpoint

Get simple list of track names with location filtering

GET `/api/external/tracks`

Parameters

`code` (optional): Race type code (T, R, G)

`date` (optional): Date in YYYY-MM-DD format

`location` (optional): Location filter:

- AUS, `AUSTRALIA`, `DOMESTIC` - Australian tracks only
- `INT`, `INTERNATIONAL` - International tracks only
- State/country codes: NSW, VIC, QLD, WA, SA, TAS, NT, ACT, USA, GBR, NZL, etc.

Response

```
{
  "date": "2025-07-08",
  "code": "T",
  "location": "AUS",
  "tracks": ["Flemington", "Randwick", "Eagle Farm", ...]
```

```
}
```

Example Request

```
https://oddspro.com.au/api/external/tracks?code=T&location=AUS
```

Test Endpoint

Tip: Use this endpoint for autocomplete or track selection UIs. Returns just track names for a cleaner response.

Authentication & Limits

Access and usage information

Authentication

No authentication required for public endpoints

Rate Limiting

- Recommended: 100 requests per minute per IP
- Consider API key-based access for higher limits
- Contact support for enterprise rate limits

Data Freshness

- Updated every 5 minutes via BetWatch integration
- Live race scheduling changes reflected immediately
- Real-time odds from active bookmakers

Code Examples

Ready-to-use code snippets for integration

JavaScript Python PHP cURL

```
// Fetch top favorites
async function getTopFavs(type = 'all', location = 'all', limit
  const params = new URLSearchParams({ type, location, limit })
  const response = await fetch('https://oddspro.com.au/api/exte
  return response.json();
}

// Fetch leaderboard
async function getLeaderboard(type = 'all', location = 'all') {
  const params = new URLSearchParams({ type, location });
  const response = await fetch('https://oddspro.com.au/api/exte
  return response.json();
}

// Usage example
const favorites = await getTopFavs('T', 'domestic', 5);
console.log(favorites.data);
```