COMP3411 Week 08 Tutorial

Yifan He

z5173587@unsw.edu.au

https://github.com/hharryyf/COMP3411-24T1-tutoring

Propositional Logic

- $\bullet \ \phi = p \mid \phi \land \phi \mid \phi \lor \phi \mid \neg \phi \mid \phi \Longrightarrow \phi \mid \phi \Longleftrightarrow \phi$
- Semantic definition:
 - $\phi = p$ is true iff p is true
 - $\phi = \neg \phi'$ is true iff ϕ' is false
 - $\phi = \phi_1 \wedge \phi_2$ is true iff both ϕ_1 and ϕ_2 are true
 - $\phi = \phi_1 \vee \phi_2$ is true iff either ϕ_1 or ϕ_2 is true
 - $\phi_1 \Longrightarrow \phi_2$ can be written as $\neg \phi_1 \lor \phi_2$
 - $\phi_1 \Longleftrightarrow \phi_2$ is the same as $(\phi_1 \Longrightarrow \phi_2) \land (\phi_2 \Longrightarrow \phi_1)$

Conjunctive Normal Form

- A literal is a variable p or its negation $\neg p$
- A clause is a disjunction (v) of literals
- A propositional formula is CNF iff it is a conjunction (∧) of clauses

Conjunctive Normal Form

- A literal is a variable p or its negation $\neg p$
- A clause is a disjunction (v) of literals
- A propositional formula is CNF iff it is a conjunction (∧) of clauses

Satisfiability ($KB \models \alpha$)

- Model: a satisfiability assignment for KB
- Valid: true in all models
- Satisfiable: true in some models
- Unsatisfiable: true in no models

Propositional logic remark

- $m{\phi}$ is satisfiable iff there is some assignment that satisfies $m{\phi}$
- SAT is NP-complete

Propositional logic remark

- ullet ϕ is satisfiable iff there is some assignment that satisfies ϕ
- SAT is NP-complete

Resolution

- A method of checking satisfiability
- Sound and complete
 - Convert ϕ to CNF (can be done in linear time)
 - $C_1, C_2 \in \phi$ such that $l \in C_1$ and $\neg l \in C_2$
 - $\phi = \phi \land ((C_1 \lor I) \lor (C_2 \lor \neg I))$ • Example: $(x_1 \lor x_2) \land (x_3 \lor \neg x_2)$
 - $(x_1 \vee x_2) \wedge (x_3 \vee \neg x_2) \wedge (x_1 \vee x_3)$
 - ullet ϕ is unsatisfiable iff empty clause is derivable

- Valid, satisfiable, or neither using truth tables or inference rules. For those that are satisfiable, list all the models that satisfy them.
- $(Smoke \Rightarrow Fire) \Rightarrow ((Smoke \land Heat) \Rightarrow Fire)$

- Valid, satisfiable, or neither using truth tables or inference rules. For those that are satisfiable, list all the models that satisfy them.
- $(Smoke \Rightarrow Fire) \Rightarrow ((Smoke \land Heat) \Rightarrow Fire)$
 - $(\neg Smoke \lor Fire) \Longrightarrow ((Smoke \land Heat) \Longrightarrow Fire)$

- Valid, satisfiable, or neither using truth tables or inference rules. For those that are satisfiable, list all the models that satisfy them.
- $(Smoke \Rightarrow Fire) \Rightarrow ((Smoke \land Heat) \Rightarrow Fire)$
 - $(\neg Smoke \lor Fire) \Longrightarrow ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(\neg(\neg Smoke \lor Fire)) \lor ((Smoke \land Heat) \Longrightarrow Fire)$

- Valid, satisfiable, or neither using truth tables or inference rules. For those that are satisfiable, list all the models that satisfy them.
- $(Smoke \Rightarrow Fire) \Rightarrow ((Smoke \land Heat) \Rightarrow Fire)$
 - $(\neg Smoke \lor Fire) \Longrightarrow ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(\neg(\neg Smoke \lor Fire)) \lor ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(Smoke \land \neg Fire) \lor ((Smoke \land Heat) \Longrightarrow Fire)$

- Valid, satisfiable, or neither using truth tables or inference rules. For those that are satisfiable, list all the models that satisfy them.
- $(Smoke \Rightarrow Fire) \Rightarrow ((Smoke \land Heat) \Rightarrow Fire)$
 - $(\neg Smoke \lor Fire) \Longrightarrow ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(\neg(\neg Smoke \lor Fire)) \lor ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(Smoke \land \neg Fire) \lor ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(Smoke \land \neg Fire) \lor ((\neg (Smoke \land Heat)) \lor Fire)$

- Valid, satisfiable, or neither using truth tables or inference rules. For those that are satisfiable, list all the models that satisfy them.
- $(Smoke \Rightarrow Fire) \Rightarrow ((Smoke \land Heat) \Rightarrow Fire)$
 - $(\neg Smoke \lor Fire) \Longrightarrow ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(\neg(\neg Smoke \lor Fire)) \lor ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(Smoke \land \neg Fire) \lor ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(Smoke \land \neg Fire) \lor ((\neg (Smoke \land Heat)) \lor Fire)$
 - $(Smoke \land \neg Fire) \lor (\neg Smoke \lor \neg Heat \lor Fire)$

- Valid, satisfiable, or neither using truth tables or inference rules. For those that are satisfiable, list all the models that satisfy them.
- $(Smoke \Rightarrow Fire) \Rightarrow ((Smoke \land Heat) \Rightarrow Fire)$
 - $(\neg Smoke \lor Fire) \Longrightarrow ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(\neg(\neg Smoke \lor Fire)) \lor ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(Smoke \land \neg Fire) \lor ((Smoke \land Heat) \Longrightarrow Fire)$
 - $(Smoke \land \neg Fire) \lor ((\neg (Smoke \land Heat)) \lor Fire)$
 - $(Smoke \land \neg Fire) \lor (\neg Smoke \lor \neg Heat \lor Fire)$
 - (Smoke ∨ ¬Smoke ∨ ¬Heat ∨ Fire) ∧ (¬Fire ∨ ¬Smoke ∨ ¬Heat ∨ Fire)
 - Valid

• $(Big \land Dumb) \lor \neg Dumb$

- (Big ∧ Dumb) ∨ ¬Dumb
 - $(Big \lor \neg Dumb) \land (Dumb \lor \neg Dumb)$

- $(Big \land Dumb) \lor \neg Dumb$
 - $(Big \lor \neg Dumb) \land (Dumb \lor \neg Dumb)$
 - Big ∨ ¬Dumb
 - Satisfiable

- $(Big \land Dumb) \lor \neg Dumb$
 - $(Big \lor \neg Dumb) \land (Dumb \lor \neg Dumb)$
 - Big ∨ ¬Dumb
 - Satisfiable
 - {*Big*} {*Big*, *Dumb*} {}

If the unicorn in mythical, then it is immortal, but if it is not mythical, then it is mortal and a mammal. If the unicorn in either immortal or a mammal, then it is horned. The unicorn is magical if it is horned.

If the unicorn in mythical, then it is immortal, but if it is not mythical, then it is mortal and a mammal. If the unicorn in either immortal or a mammal, then it is horned. The unicorn is magical if it is horned.

Encoding

If the unicorn in mythical, then it is immortal, but if it is not mythical, then it is mortal and a mammal. If the unicorn in either immortal or a mammal, then it is horned. The unicorn is magical if it is horned.

Encoding

Variables: mythical, mortal, mamal, magical, horned

 \bigcirc mythical $\Rightarrow \neg$ mortal

If the unicorn in mythical, then it is immortal, but if it is not mythical, then it is mortal and a mammal. If the unicorn in either immortal or a mammal, then it is horned. The unicorn is magical if it is horned.

Encoding

- mythical ⇒ ¬mortal

If the unicorn in mythical, then it is immortal, but if it is not mythical, then it is mortal and a mammal. If the unicorn in either immortal or a mammal, then it is horned. The unicorn is magical if it is horned.

Encoding

- mythical ⇒ ¬mortal
- \bigcirc (¬mortal v mammal) \Longrightarrow horned

If the unicorn in mythical, then it is immortal, but if it is not mythical, then it is mortal and a mammal. If the unicorn in either immortal or a mammal, then it is horned. The unicorn is magical if it is horned.

Encoding

- mythical ⇒ ¬mortal
- (¬mortal ∨ mammal) ⇒ horned
- horned ⇒ magical

 \bigcirc mythical $\Longrightarrow \neg$ mortal

- \bigcirc mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal

- \bigcirc mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal

- \bigcirc mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal
- - mythical ∨ (mortal ∧ mammal)
 - (mythical ∨ mortal) ∧ (mythical ∨ mammal)

- \bigcirc mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal
- \bigcirc ¬mythical \Longrightarrow (mortal \land mammal)
 - mythical ∨ (mortal ∧ mammal)
 - (mythical ∨ mortal) ∧ (mythical ∨ mammal)

- \bigcirc mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal
- - mythical ∨ (mortal ∧ mammal)
 - (mythical ∨ mortal) ∧ (mythical ∨ mammal)
- \bigcirc (¬mortal \lor mammal) \Longrightarrow horned
 - $(\neg(\neg mortal \lor mammal)) \lor horned$
 - (mortal ∧ ¬mammal) ∨ horned
 - $(mortal \lor horned) \land (\neg mammal \lor horned)$

- lacktriangledown mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal
- - mythical ∨ (mortal ∧ mammal)
 - (mythical ∨ mortal) ∧ (mythical ∨ mammal)
- \bigcirc (¬mortal \lor mammal) \Longrightarrow horned
 - $(\neg(\neg mortal \lor mammal)) \lor horned$
 - (mortal ∧ ¬mammal) ∨ horned
 - (mortal ∨ horned) ∧ (¬mammal ∨ horned)
- horned ⇒ magical

- \bigcirc mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal
- - mythical ∨ (mortal ∧ mammal)
 - (mythical ∨ mortal) ∧ (mythical ∨ mammal)
- \bigcirc (¬mortal \lor mammal) \Longrightarrow horned
 - (¬(¬mortal ∨ mammal)) ∨ horned
 - (mortal ∧ ¬mammal) ∨ horned
 - $(mortal \lor horned) \land (\neg mammal \lor horned)$
- horned ⇒ magical
 - ¬horned ∨ magical

- \bigcirc mythical $\Longrightarrow \neg$ mortal
 - ¬mythical ∨ ¬mortal
- - mythical ∨ (mortal ∧ mammal)
 - (mythical ∨ mortal) ∧ (mythical ∨ mammal)
- \bigcirc (¬mortal \lor mammal) \Longrightarrow horned
 - $(\neg(\neg mortal \lor mammal)) \lor horned$
 - (mortal ∧ ¬mammal) ∨ horned
 - $(mortal \lor horned) \land (\neg mammal \lor horned)$
- horned ⇒ magical
 - ¬horned ∨ magical

(¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧ (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧ (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ⊨ horned

- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧ (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧ (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ⊨ horned
- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned is UNSAT

(¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned ∧ ¬mammal

- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned ∧ ¬mammal
- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned ∧ ¬mammal ∧ mythical

- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned ∧ ¬mammal
- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned ∧ ¬mammal ∧ mythical
- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned ∧ ¬mammal ∧ mythical ∧ mortal

(¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧ (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧ (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧ ¬horned ∧ ¬mammal ∧ mythical ∧mortal ∧ ¬mythical

- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧ (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧ (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧ ¬horned ∧ ¬mammal ∧ mythical ∧mortal ∧ ¬mythical
- (¬mythical ∨ ¬mortal) ∧ (mythical ∨ mortal) ∧
 (mythical ∨ mammal) ∧ (mortal ∨ horned) ∧
 (¬mammal ∨ horned) ∧ (¬horned ∨ magical) ∧
 ¬horned ∧ ¬mammal ∧
 mythical ∧ mortal ∧ ¬mythical

Encoding (we know horned is true)

- lacktriangledown mythical $\Longrightarrow \neg$ mortal
- ullet $(\neg mortal \lor mammal) \Longrightarrow horned$
- horned ⇒ magical
 - Write out all models, is magical/mythical always true?

Encoding (we know horned is true)

- ullet mythical $\Longrightarrow \neg$ mortal
- ullet $(\neg mortal \lor mammal) \Longrightarrow horned$
- horned ⇒ magical
 - Write out all models, is magical/mythical always true?
 - By rule (4), we know magical must be true

Encoding (we know horned is true)

- \bigcirc mythical $\Longrightarrow \neg$ mortal

- lacktriangledown horned \Longrightarrow magical
 - Write out all models, is magical/mythical always true?
 - By rule (4), we know *magical* must be true
 - We only need to consider the truth value of mythical, mortal, and mammal
 - We just use a truth table

Encoding (we know *horned* and *magical* are true)

- \bigcirc mythical $\Longrightarrow \neg$ mortal

Encoding (we know *horned* and *magical* are true)

- \bigcirc mythical $\Longrightarrow \neg$ mortal

mythical	mortal	mammal	(1)	(2)
T	Т	T	F	-
T	T	F	F	-
Т	F	Т	Т	Т
T	F	F	Т	Т
F	T	Т	Т	Т
F	T	F	Т	F
F	F	Т	Т	F
F	F	F	Т	F

Encoding (we know *horned* and *magical* are true)

- \bigcirc mythical $\Longrightarrow \neg$ mortal

mythical	mortal	mammal	(1)	(2)
T	Т	T	F	-
Т	T	F	F	-
T	F	Т	Т	Т
T	F	F	Т	Т
F	T	Т	Т	Т
F	T	F	Т	F
F	F	Т	Т	F
F	F	F	Т	F

- {horned, magic, myth, mammal}
- {horned, magic, myth}
- {horned, magic, mortal, mammal} no mythical!

Hint on assignment 3

9-board tic-tac-toe

- You are playing tic-tac-toe on a 9x9 "sudoku" board, it has 3x3 subboard of size 3x3.
- The first step is made by the x player randomly.
 Then, two players take turns to put pieces on the board.
- If a player plays at the *i*-th cell on the *j*-th subboard. The next player must make a move on the *i*-th subboard.
- Game ends if one player has a 3 in a row/column/diagonal.
- Game ends in a draw if someone cannot make a move.

Hint on assignment 3

Algorithms

- Two player zero-sum turn-taking game
- Monte Carlo Tree Search (MCTS) + UCT
 - Works very well in games that a heuristic evaluation function is hard to come up with
 - I recommend you try this approach if you know MCTS
- Alpha-beta pruning with heuristic function

Hint on assignment 3

Important components of alpha-beta search

- Efficient data structure for the board
 - Update a move, undo a move
 - Knows the termination of a game
 - Knows who wins
 - Evaluate how "good" a position is
 - Sometimes this is critical
 - You can increase the searching depth with good DS
- Gradually increase the searching depth as the game progress
- A well designed heuristic function for middle game positions
- Health warning with Python! Too slow!

Alpha-beta pruning algorithm Review

- alphabeta(state, $\alpha = -\infty$, $\beta = \infty$, depth)
 - If *state* is terminal or *depth* = 0, return: heuristic score of the *max* player
 - 2 If it is the turn of max
 - For each next state of state
 - $\alpha = max(\alpha, alphabeta(next, \alpha, \beta, depth 1))$
 - If $\alpha \ge \beta$ return α
 - \bigcirc return α
 - If it is the turn of min
 - For each next state of state
 - $\beta = min(\beta, alphabeta(next, \alpha, \beta, depth 1))$
 - If $\alpha \ge \beta$ return β
 - return β

A heuristic function to start with

- $Score = \sum_{i=1}^{9} eval(subboard(i))$
 - eval(subboard(i)) = 1000000 if x has 3 in a line
 - eval(subboard(i)) = -1000000 if o has 3 in a line
 - eval(subboard(i)) = 0 if the subboard is full
 - eval(subboard(i))+ = 1000 if x has one 2 in a line
 - eval(subboard(i)) = 1000 if o has one 2 in a line
 - eval(subboard(i)) + = 100 if x has one 1 in a line
 - eval(subboard(i)) = 100 if o has one 1 in a line

		Х
	0	
Χ	0	

• Score = -1000 + 3 * 100 - 2 * 100 = -900