

# Randomized Quicksort

(CLRS textbook: chapter 7)



# Randomized Quicksort Algorithm (High-Level Description)



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .





# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)
- ▶ By comparing  $p$  to every other key in  $S$ , **split** the set  $S$  into two subsets:



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)
- ▶ By comparing  $p$  to every other key in  $S$ , **split** the set  $S$  into two subsets:
  - ▶  $S_{<} = \{s \in S \mid s < p\}$



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)
- ▶ By comparing  $p$  to every other key in  $S$ , **split** the set  $S$  into two subsets:
  - ▶  $S_{<} = \{s \in S \mid s < p\}$
  - ▶  $S_{>} = \{s \in S \mid s > p\}$



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)
- ▶ By comparing  $p$  to every other key in  $S$ , **split** the set  $S$  into two subsets:
  - ▶  $S_{<} = \{s \in S \mid s < p\}$
  - ▶  $S_{>} = \{s \in S \mid s > p\}$

(doing this for  $|S| = n$  takes  $n - 1$  key comparisons)



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)
- ▶ By comparing  $p$  to every other key in  $S$ , **split** the set  $S$  into two subsets:
  - ▶  $S_{<} = \{s \in S \mid s < p\}$
  - ▶  $S_{>} = \{s \in S \mid s > p\}$

(doing this for  $|S| = n$  takes  $n - 1$  key comparisons)

- ▶ **RQS( $S_{<}$ )**;



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)
- ▶ By comparing  $p$  to every other key in  $S$ , **split** the set  $S$  into two subsets:
  - ▶  $S_{<} = \{s \in S \mid s < p\}$
  - ▶  $S_{>} = \{s \in S \mid s > p\}$

(doing this for  $|S| = n$  takes  $n - 1$  key comparisons)

- ▶ **RQS( $S_{<}$ )**; output  $p$  ;



# Randomized Quicksort Algorithm (High-Level Description)

**Input:** Set  $S$  of  $n$  distinct keys

**Output:** The keys of  $S$  in increasing order

**RQS( $S$ )** (\* recursive, divide-and-conquer algorithm \*)

- ▶ If  $S$  is empty then return.
- ▶ If  $|S| = 1$  then output the key in  $S$  and return.
- ▶ Select a key  $p$  (called a “pivot”) **uniformly at random** from  $S$ .  
(each key of  $S$  is equally likely to be selected as pivot.)
- ▶ By comparing  $p$  to every other key in  $S$ , **split** the set  $S$  into two subsets:
  - ▶  $S_{<} = \{s \in S \mid s < p\}$
  - ▶  $S_{>} = \{s \in S \mid s > p\}$

(doing this for  $|S| = n$  takes  $n - 1$  key comparisons)

- ▶  $RQS(S_{<})$ ; output  $p$  ;  $RQS(S_{>})$





Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, 4, 6, 5}

**2, 8, 7, 1, 3, 4, 6, 5**



Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, 4, 6, 5}

**2, 8, 7, 1, 3, 4, 6, 5**



Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, 4, 6, 5}

2, 8, 7, 1, 3, 4, 6, 5




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, 4, 6, 5}

2, 8, 7, 1, 3, 4, 6, 5


4




Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on  $S = \{2, 8, 7, 1, 3, 4, 6, 5\}$



Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on  $S = \{2, 8, 7, 1, 3, 4, 6, 5\}$







Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on  $S = \{2, 8, 7, 1, 3, 4, 6, 5\}$




Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, **3**, **4**, 6, 5}



Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on  $S = \{2, 8, 7, 1, 3, 4, 6, 5\}$







Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on  $S = \{2, 8, 7, 1, 3, 4, 6, 5\}$




Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}







Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2**


Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3**




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3**




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




**1, 2, 3, 4**

Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




**1, 2, 3, 4**

Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




**1, 2, 3, 4**

Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




**1, 2, 3, 4**

Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4**


Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4, 5**




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4, 5, 6**




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4, 5, 6**




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




**1, 2, 3, 4, 5, 6**

Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}




**1, 2, 3, 4, 5, 6**

Example execution of **RQS** on **S** = {2, 8, 7, 1, 3, 4, 6, 5}



**1, 2, 3, 4, 5, 6**


Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4, 5, 6, 7**




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4, 5, 6, 7, 8**




Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4, 5, 6, 7, 8**



Example execution of **RQS** on **S** = {**2**, 8, 7, 1, 3, **4**, 6, 5}



**1, 2, 3, 4, 5, 6, 7, 8**





# Basic Observations

In every  $RQS(S)$  execution:



# Basic Observations

In every  $RQS(S)$  execution:

- ▶ Two keys are compared **only if** one of them is selected as a **pivot**.



# Basic Observations

In every  $RQS(S)$  execution:

- ▶ Two keys are compared **only if** one of them is selected as a **pivot**.
- ▶ Two keys are compared **at most once**.



# Basic Observations

In every  $RQS(S)$  execution:

- ▶ Two keys are compared **only if** one of them is selected as a **pivot**.
- ▶ Two keys are compared **at most once**.
- ▶ If two keys are “split apart” in different sets by a pivot (like 2 and 7 are split apart by pivot 4) then they are **never** compared.



# Complexity Analysis of Randomized Quicksort

- **Fix** some input  $S$  with  $n$  *distinct* keys.



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$



# Complexity Analysis of Randomized Quicksort

- ▶ Fix some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?





# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1)$$



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1) + (n - 2)$$



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1) + (n - 2) + \dots + 2 + 1$$



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1) + (n - 2) + \dots + 2 + 1 = \frac{n(n - 1)}{2}$$



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1) + (n - 2) + \dots + 2 + 1 = \frac{n(n - 1)}{2} \text{ i.e., } \Theta(n^2)$$



# Complexity Analysis of Randomized Quicksort

- ▶ Fix some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1) + (n - 2) + \dots + 2 + 1 = \frac{n(n - 1)}{2} \text{ i.e., } \Theta(n^2)$$

- ▶ What is the **expected** (“average”) value of  $C$ ?



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1) + (n - 2) + \dots + 2 + 1 = \frac{n(n - 1)}{2} \text{ i.e., } \Theta(n^2)$$

- ▶ What is the **expected** (“average”) value of  $C$ ?  
(over all the possible **random pivot selections** by  $RQS(S)$ )



# Complexity Analysis of Randomized Quicksort

- ▶ **Fix** some input  $S$  with  $n$  *distinct* keys.
- ▶ Run  $RQS(S)$
- ▶ Let  $C$  = number of key comparisons done by  $RQS(S)$
- ▶ What is the **worst-case** value of  $C$ ?

$$C = (n - 1) + (n - 2) + \dots + 2 + 1 = \frac{n(n - 1)}{2} \text{ i.e., } \Theta(n^2)$$

- ▶ What is the **expected** (“average”) value of  $C$ ?  
(over all the possible **random pivot selections** by  $RQS(S)$ )
- ▶ More precisely: what is  $E(C)$ ?





# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order



# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$



# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$
- ▶ Note that  $RQS(S)$  compares  $z_i$  and  $z_j$  **at most once** (and only if, at some point, it selects  $z_i$  or  $z_j$  as a pivot)



# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$
- ▶ Note that  $RQS(S)$  compares  $z_i$  and  $z_j$  **at most once** (and only if, at some point, it selects  $z_i$  or  $z_j$  as a pivot)

$$\text{Let } c_{ij} = \begin{cases} 1 & RQS(S) \text{ compares } z_i \text{ and } z_j \end{cases}$$



# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$
- ▶ Note that  $RQS(S)$  compares  $z_i$  and  $z_j$  **at most once** (and only if, at some point, it selects  $z_i$  or  $z_j$  as a pivot)

$$\text{Let } c_{ij} = \begin{cases} 1 & RQS(S) \text{ compares } z_i \text{ and } z_j \\ 0 & \text{otherwise} \end{cases}$$



# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$
- ▶ Note that  $RQS(S)$  compares  $z_i$  and  $z_j$  **at most once** (and only if, at some point, it selects  $z_i$  or  $z_j$  as a pivot)

$$\text{Let } c_{ij} = \begin{cases} 1 & RQS(S) \text{ compares } z_i \text{ and } z_j \\ 0 & \text{otherwise} \end{cases}$$

This is an **indicator random variable**



# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$
- ▶ Note that  $RQS(S)$  compares  $z_i$  and  $z_j$  **at most once** (and only if, at some point, it selects  $z_i$  or  $z_j$  as a pivot)

$$\text{Let } c_{ij} = \begin{cases} 1 & RQS(S) \text{ compares } z_i \text{ and } z_j \\ 0 & \text{otherwise} \end{cases}$$

This is an **indicator random variable**

- ▶ The **total** number of key comparisons done by  $RQS(S)$  is:



# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$
- ▶ Note that  $RQS(S)$  compares  $z_i$  and  $z_j$  **at most once** (and only if, at some point, it selects  $z_i$  or  $z_j$  as a pivot)

$$\text{Let } c_{ij} = \begin{cases} 1 & RQS(S) \text{ compares } z_i \text{ and } z_j \\ 0 & \text{otherwise} \end{cases}$$

This is an **indicator random variable**

- ▶ The **total** number of key comparisons done by  $RQS(S)$  is:

$$C = \sum_{1 \leq i < j \leq n} c_{ij}$$





# Complexity Analysis of Randomized Quicksort

- ▶ Let  $z_1 < z_2 < \dots < z_i < \dots < z_j < \dots < z_n$  be the keys of  $S$  in ascending order
- ▶ Run  $RQS(S)$
- ▶ Note that  $RQS(S)$  compares  $z_i$  and  $z_j$  **at most once** (and only if, at some point, it selects  $z_i$  or  $z_j$  as a pivot)

$$\text{Let } c_{ij} = \begin{cases} 1 & RQS(S) \text{ compares } z_i \text{ and } z_j \\ 0 & \text{otherwise} \end{cases}$$

This is an **indicator random variable**

- ▶ The **total** number of key comparisons done by  $RQS(S)$  is:

$$C = \sum_{1 \leq i < j \leq n} c_{ij}$$

- ▶ We want to compute  $E(C)$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$E(c_{ij}) =$$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$E(c_{ij}) = 1 \cdot \Pr[c_{ij} = 1]$$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$E(c_{ij}) = 1 \cdot \Pr[c_{ij} = 1] + 0 \cdot \Pr[c_{ij} = 0]$$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$\begin{aligned} E(c_{ij}) &= 1 \cdot \Pr[c_{ij} = 1] + 0 \cdot \Pr[c_{ij} = 0] \\ &= \Pr[c_{ij} = 1] \end{aligned}$$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$\begin{aligned} E(c_{ij}) &= 1 \cdot \Pr[c_{ij} = 1] + 0 \cdot \Pr[c_{ij} = 0] \\ &= \Pr[c_{ij} = 1] \\ &= \Pr[z_i \text{ and } z_j \text{ are compared}] \end{aligned}$$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$\begin{aligned} E(c_{ij}) &= 1 \cdot \Pr[c_{ij} = 1] + 0 \cdot \Pr[c_{ij} = 0] \\ &= \Pr[c_{ij} = 1] \\ &= \Pr[z_i \text{ and } z_j \text{ are compared}] \end{aligned}$$

$$E(C) = E\left(\sum_{1 \leq i < j \leq n} c_{ij}\right)$$





# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$\begin{aligned} E(c_{ij}) &= 1 \cdot \Pr[c_{ij} = 1] + 0 \cdot \Pr[c_{ij} = 0] \\ &= \Pr[c_{ij} = 1] \\ &= \Pr[z_i \text{ and } z_j \text{ are compared}] \end{aligned}$$

$$\begin{aligned} E(C) &= E\left(\sum_{1 \leq i < j \leq n} c_{ij}\right) \\ &= \sum_{1 \leq i < j \leq n} E(c_{ij}) \quad \text{by linearity of expectations} \end{aligned}$$



# Complexity Analysis of Randomized Quicksort

Number of comparisons done by  $RQS(S)$ :  $C = \sum_{1 \leq i < j \leq n} c_{ij}$

To compute  $E(C)$ , we first compute  $E(c_{ij})$ :

$$\begin{aligned} E(c_{ij}) &= 1 \cdot \Pr[c_{ij} = 1] + 0 \cdot \Pr[c_{ij} = 0] \\ &= \Pr[c_{ij} = 1] \\ &= \Pr[z_i \text{ and } z_j \text{ are compared}] \end{aligned}$$

$$\begin{aligned} E(C) &= E\left(\sum_{1 \leq i < j \leq n} c_{ij}\right) \\ &= \sum_{1 \leq i < j \leq n} E(c_{ij}) \quad \text{by linearity of expectations} \\ &= \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}] \end{aligned}$$



# Complexity Analysis of Randomized Quicksort

- We just proved:

**Lemma:**  $E(C) = \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}]$



# Complexity Analysis of Randomized Quicksort

- ▶ We just proved:

**Lemma:**  $E(C) = \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}]$

- ▶ We will later prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$



# Complexity Analysis of Randomized Quicksort

- ▶ We just proved:

**Lemma:**  $E(C) = \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}]$

- ▶ We will later prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

- ▶ By combining these two lemmas:

$$E(C) = \sum_{1 \leq i < j \leq n} \frac{2}{j-i+1}$$



# Complexity Analysis of Randomized Quicksort

- ▶ We just proved:

**Lemma:**  $E(C) = \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}]$

- ▶ We will later prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

- ▶ By combining these two lemmas:

$$E(C) = \sum_{1 \leq i < j \leq n} \frac{2}{j-i+1} = \dots \leq 2n(1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n})$$



# Complexity Analysis of Randomized Quicksort

- ▶ We just proved:

**Lemma:**  $E(C) = \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}]$

- ▶ We will later prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

- ▶ By combining these two lemmas:

$$E(C) = \sum_{1 \leq i < j \leq n} \frac{2}{j-i+1} = \dots \leq 2n(1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n})$$

- ▶ It is known that  $H_n = 1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n}$  is  $O(\log n)$ .



# Complexity Analysis of Randomized Quicksort

- ▶ We just proved:

**Lemma:**  $E(C) = \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}]$

- ▶ We will later prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

- ▶ By combining these two lemmas:

$$E(C) = \sum_{1 \leq i < j \leq n} \frac{2}{j-i+1} = \dots \leq 2n(1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n})$$

- ▶ It is known that  $H_n = 1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n}$  is  $O(\log n)$ .

[In fact, for  $n \geq 2$ ,  $H_n \leq (\log_e n) + 1$ .]





# Complexity Analysis of Randomized Quicksort

- ▶ We just proved:

**Lemma:**  $E(C) = \sum_{1 \leq i < j \leq n} \Pr[z_i \text{ and } z_j \text{ are compared}]$

- ▶ We will later prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

- ▶ By combining these two lemmas:

$$E(C) = \sum_{1 \leq i < j \leq n} \frac{2}{j-i+1} = \dots \leq 2n(1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n})$$

- ▶ It is known that  $H_n = 1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{n}$  is  $O(\log n)$ .

[In fact, for  $n \geq 2$ ,  $H_n \leq (\log_e n) + 1$ .]

- ▶ Therefore:

**Theorem:**  $E(C)$  is  $O(n \log n)$



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] =$



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{n}$

Since  $z_1$  and  $z_n$  are the **smallest** and **largest** element in  $S$ ,



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{n}$

Since  $z_1$  and  $z_n$  are the **smallest** and **largest** element in  $S$ , they will be compared by  $RQS(S)$  **if and only if** the first pivot that  $RQS(S)$  selects among the  $n$  elements of  $S$  is



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{n}$

Since  $z_1$  and  $z_n$  are the **smallest** and **largest** element in  $S$ , they will be compared by  $RQS(S)$  **if and only if** the first pivot that  $RQS(S)$  selects among the  $n$  elements of  $S$  is  $z_1$  or  $z_n$ .



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{n}$

Since  $z_1$  and  $z_n$  are the **smallest** and **largest** element in  $S$ , they will be compared by  $RQS(S)$  **if and only if** the first pivot that  $RQS(S)$  selects among the  $n$  elements of  $S$  is  $z_1$  or  $z_n$ .

Note that  $j - i + 1 = n$ , so the lemma is correct in this case!



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- ▶ For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{n}$

Since  $z_1$  and  $z_n$  are the **smallest** and **largest** element in  $S$ , they will be compared by  $RQS(S)$  **if and only if** the first pivot that  $RQS(S)$  selects among the  $n$  elements of  $S$  is  $z_1$  or  $z_n$ .

Note that  $j - i + 1 = n$ , so the lemma is correct in this case!

In our example:  $n = 8$ ,  $z_1 = 1$  and  $z_n = 8$ , and  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{8} = \frac{1}{4}$ .

- ▶ For any  $i$  and  $j = i + 1$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] =$





# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- ▶ For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{n}$

Since  $z_1$  and  $z_n$  are the **smallest** and **largest** element in  $S$ , they will be compared by  $RQS(S)$  **if and only if** the first pivot that  $RQS(S)$  selects among the  $n$  elements of  $S$  is  $z_1$  or  $z_n$ .

Note that  $j - i + 1 = n$ , so the lemma is correct in this case!

In our example:  $n = 8$ ,  $z_1 = 1$  and  $z_n = 8$ , and  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{8} = \frac{1}{4}$ .

- ▶ For any  $i$  and  $j = i + 1$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = 1!$



# Complexity Analysis of Randomized Quicksort

It now remains to prove:

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

Some intuition first:

- For  $i = 1$  and  $j = n$ ,  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{n}$

Since  $z_1$  and  $z_n$  are the **smallest** and **largest** element in  $S$ , they will be compared by  $RQS(S)$  **if and only if** the first pivot that  $RQS(S)$  selects among the  $n$  elements of  $S$  is  $z_1$  or  $z_n$ .

Note that  $j - i + 1 = n$ , so the lemma is correct in this case!

In our example:  $n = 8$ ,  $z_1 = 1$  and  $z_n = 8$ , and  $\Pr[z_1 \text{ and } z_n \text{ are compared}] = \frac{2}{8} = \frac{1}{4}$ .

- For any  $i$  and  $j = i + 1$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = 1!$   
(do you see why?)



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

►  $|Z_{ij}| =$



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

►  $|Z_{ij}| = j - i + 1$ .



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- ▶  $|Z_{ij}| = j - i + 1$ .
- ▶ Initially,  $Z_{ij}$  is entirely contained in (the set of keys)  $S$ .



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- ▶  $|Z_{ij}| = j - i + 1$ .
- ▶ Initially,  $Z_{ij}$  is entirely contained in (the set of keys)  $S$ .
- ▶  $RQS(S)$  keeps selecting pivots and uses them to **split**  $S$  into smaller and smaller subsets until it gets subsets of size one or zero.





# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- ▶  $|Z_{ij}| = j - i + 1$ .
- ▶ Initially,  $Z_{ij}$  is entirely contained in (the set of keys)  $S$ .
- ▶  $RQS(S)$  keeps selecting pivots and uses them to **split**  $S$  into smaller and smaller subsets until it gets subsets of size one or zero.
- ▶ As long as  $RQS(S)$  selects pivots that are **not** in  $Z_{ij}$ , then  $Z_{ij}$  remains contained in one of the subsets formed by the pivots,



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- ▶  $|Z_{ij}| = j - i + 1$ .
- ▶ Initially,  $Z_{ij}$  is entirely contained in (the set of keys)  $S$ .
- ▶  $RQS(S)$  keeps selecting pivots and uses them to **split**  $S$  into smaller and smaller subsets until it gets subsets of size one or zero.
- ▶ As long as  $RQS(S)$  selects pivots that are **not** in  $Z_{ij}$ , then  $Z_{ij}$  remains contained in one of the subsets formed by the pivots, and  **$z_i$  and  $z_j$  remain uncomparated.**



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- ▶  $|Z_{ij}| = j - i + 1$ .
- ▶ Initially,  $Z_{ij}$  is entirely contained in (the set of keys)  $S$ .
- ▶  $RQS(S)$  keeps selecting pivots and uses them to **split**  $S$  into smaller and smaller subsets until it gets subsets of size one or zero.
- ▶ As long as  $RQS(S)$  selects pivots that are **not** in  $Z_{ij}$ , then  $Z_{ij}$  remains contained in one of the subsets formed by the pivots, and  **$z_i$  and  $z_j$  remain uncomparated**.
- ▶ At some point,  $RQS(S)$  **must** select a pivot  **$p$  in  $Z_{ij}$** , because it must split  $Z_{ij}$  into smaller sets.



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Consider the set of keys  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$

- ▶  $|Z_{ij}| = j - i + 1$ .
- ▶ Initially,  $Z_{ij}$  is entirely contained in (the set of keys)  $S$ .
- ▶  $RQS(S)$  keeps selecting pivots and uses them to **split**  $S$  into smaller and smaller subsets until it gets subsets of size one or zero.
- ▶ As long as  $RQS(S)$  selects pivots that are **not** in  $Z_{ij}$ , then  $Z_{ij}$  remains contained in one of the subsets formed by the pivots, and  **$z_i$  and  $z_j$  remain uncomparing**.
- ▶ At some point,  $RQS(S)$  **must** select a pivot  **$p$  in  $Z_{ij}$** , because it must split  $Z_{ij}$  into smaller sets.
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  **$p$  in  $Z_{ij}$** .



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

► ...

► Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**





# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then  $z_i$  and  $z_j$  **are compared**.



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then  $z_i$  and  $z_j$  **are compared**.
- ▶ So:

$$\Pr[z_i \text{ and } z_j \text{ are compared}] = \Pr[p = z_i \text{ or } p = z_j]$$



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then  $z_i$  and  $z_j$  **are compared**.
- ▶ So:

$$\Pr[z_i \text{ and } z_j \text{ are compared}] = \Pr[p = z_i \text{ or } p = z_j \mid p \in Z_{ij}]$$



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then  $z_i$  and  $z_j$  **are compared**.
- ▶ So:

$$\begin{aligned}\Pr[z_i \text{ and } z_j \text{ are compared}] &= \Pr[p = z_i \text{ or } p = z_j \mid p \in Z_{ij}] \\ &= \frac{2}{j - i + 1}\end{aligned}$$



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then  $z_i$  and  $z_j$  **are compared**.
- ▶ So:

$$\begin{aligned}\Pr[z_i \text{ and } z_j \text{ are compared}] &= \Pr[p = z_i \text{ or } p = z_j \mid p \in Z_{ij}] \\ &= \frac{2}{j - i + 1}\end{aligned}$$

The last equality holds because:

(1)  $|Z_{ij}| = j - i + 1$



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then  $z_i$  and  $z_j$  **are compared**.
- ▶ So:

$$\begin{aligned}\Pr[z_i \text{ and } z_j \text{ are compared}] &= \Pr[p = z_i \text{ or } p = z_j \mid p \in Z_{ij}] \\ &= \frac{2}{j - i + 1}\end{aligned}$$

The last equality holds because:

(1)  $|Z_{ij}| = j - i + 1$ , and (2) each key in  $Z_{ij}$  is equally likely to be the selected pivot  $p \in Z_{ij}$ .



# Complexity Analysis of Randomized Quicksort

**Lemma:** For  $i < j$ ,  $\Pr[z_i \text{ and } z_j \text{ are compared}] = \frac{2}{j-i+1}$

**Proof:** Let  $Z_{ij} = \{z_i, z_{i+1}, \dots, z_j\}$ .  $|Z_{ij}| = j - i + 1$

- ▶ ...
- ▶ Consider the **first time**  $RQS(S)$  selects a pivot  $p$  in  $Z_{ij}$ .
- ▶ There are 2 possible cases:
  1. If  $z_i < p < z_j$  then  $z_i$  and  $z_j$  **are never compared**
  2. If  $p = z_i$  or  $p = z_j$  then  $z_i$  and  $z_j$  **are compared**.
- ▶ So:

$$\begin{aligned}\Pr[z_i \text{ and } z_j \text{ are compared}] &= \Pr[p = z_i \text{ or } p = z_j \mid p \in Z_{ij}] \\ &= \frac{2}{j - i + 1}\end{aligned}$$

The last equality holds because:

(1)  $|Z_{ij}| = j - i + 1$ , and (2) each key in  $Z_{ij}$  is equally likely to be the selected pivot  $p \in Z_{ij}$ .

Note: The exact argument uses conditional probabilities.

