

# Bloom Filters

Burton Howard Bloom [1970]

Course Website: Bloom Filters Survey by A. Broder and M. Mitzenmacher



# Bloom Filter

- Space-efficient “Probabilistic Dictionary”



# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set **S**



# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set **S**
- Operations:



# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set **S**
- Operations:

**BF\_Insert(x) :  $S \leftarrow S \cup \{x\}$**



# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set **S**
- Operations:

**BF\_Insert(x) :**  $S \leftarrow S \cup \{x\}$


**BF\_Search(x) :**



# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set **S**
- Operations:

**BF\_Insert(x) :  $S \leftarrow S \cup \{x\}$**


**BF\_Search(x) :**  “No”



# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set  $S$
- Operations:

**BF\_Insert( $x$ )** :  $S \leftarrow S \cup \{x\}$

**BF\_Search( $x$ )** :  “No”  $\Rightarrow x \notin S$





# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set  $S$
- Operations:

**BF\_Insert( $x$ )** :  $S \leftarrow S \cup \{x\}$

**BF\_Search( $x$ )** :

↘

↘

“No”

“Probably Yes”

$\Rightarrow x \notin S$




# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set  $S$
- Operations:

**BF\_Insert( $x$ )** :  $S \leftarrow S \cup \{x\}$

**BF\_Search( $x$ )** :



“No”

“Probably Yes”

$\Rightarrow x \notin S$

$\Rightarrow$  “Probably” in  $x \in S$




# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set  $S$
- Operations:

**BF\_Insert( $x$ )** :  $S \leftarrow S \cup \{x\}$

**BF\_Search( $x$ )** :



“No”

$\Rightarrow x \notin S$

“Probably Yes”

$\Rightarrow$  “Probably” in  $x \in S$   
(but perhaps not!)




# Bloom Filter

- Space-efficient “Probabilistic Dictionary”
- Maintain the “fingerprints” of the elements of a set  $S$
- Operations:

**BF\_Insert( $x$ )** :  $S \leftarrow S \cup \{x\}$

**BF\_Search( $x$ )** :



“No”

$\Rightarrow x \notin S$

“Probably Yes”

$\Rightarrow$  “Probably” in  $x \in S$   
(but perhaps not!)



# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not



# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set S of malicious URLs - say 10 Million URLs



# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)



# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500 \text{ MB}$  total)
  - Don't want to store huge file on user side!





# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.



# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500 \text{ MB}$  total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :



# Example Application: Malicious URLs


- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500 \text{ MB}$  total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :

**BF\_Search(URL)**



# Example Application: Malicious URLs


- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set **S** of malicious URLs - say 10 Million URLs ( $S \approx 500 \text{ MB}$  total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of **S** on the user side.
- To check if a URL is in **S** :

**BF\_Search(URL)**  "No"



# Example Application: Malicious URLs


- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :

**BF\_Search(URL)**  "No"  $\Rightarrow \text{URL} \notin S$



# Example Application: Malicious URLs


- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :

**BF\_Search(URL)**  "No"  $\Rightarrow$  URL  $\notin S$   
visit the website




# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :



# Example Application: Malicious URLs


- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :






# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :



# Example Application: Malicious URLs

- A web browser wants to check if an URL entered by an user is malicious or not
- Huge set  $S$  of malicious URLs - say 10 Million URLs ( $S \approx 500$  MB total)
  - Don't want to store huge file on user side!
- Store only a Bloom Filter of  $S$  on the user side.
- To check if a URL is in  $S$  :



- Can accomplish this using a BF of size  $\approx 10$  MB, with False Positive rate just 2%




# Bloom Filter




# Bloom Filter

- Array **BF**[0 ...  $m-1$ ] of  $m$  bits, initially all 0's




# Bloom Filter

- Array **BF**[0 ...  $m-1$ ] of  $m$  bits, initially all 0's
- $t$  independent hash functions  $h_1, h_2, \dots, h_t$




# Bloom Filter

- Array **BF**[0 ...  $m-1$ ] of  $m$  bits, initially all 0's
- $t$  independent hash functions  $h_1, h_2, \dots, h_t$   
 $h_i : U \rightarrow \{0, 1, \dots, m-1\}$



# Bloom Filter

- Array **BF**[0 ...  $m-1$ ] of  $m$  bits, initially all 0's
- $t$  independent hash functions  $h_1, h_2, \dots, h_t$   
 $h_i : U \rightarrow \{0, 1, \dots, m-1\}$   
 $h_i$  satisfying **SUHA**



# Bloom Filter

- Array **BF**[0 ...  $m-1$ ] of  $m$  bits, initially all 0's
- $t$  independent hash functions  $h_1, h_2, \dots, h_t$   
 $h_i : U \rightarrow \{0, 1, \dots, m-1\}$   
 $h_i$  satisfying **SUHA**

**SUHA:** Every element is equally likely to hash into any of the  $m$  slots of **BF**, independent of where the other elements have hashed to.

BF	
0	0
0	1
0	
0	.
0	.
0	.
0	
0	$m - 1$





Example **BF[0 ... 7]** with  $t = 2$ :  $h_1$  and  $h_2$

BF	
0	0
0	1
0	2
0	3
0	4
0	5
0	6
0	7

Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS

BF	
0	0
0	1
0	2
0	3
0	4
0	5
0	6
0	7

Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$

BF	
0	0
0	1
0	2
0	3
0	4
0	5
0	6
0	7

Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS

$BF\_Insert(x_1)$




Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS

$BF\_Insert(x_1)$


$BF\_Insert(x_2)$




Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS

$BF\_Insert(x_1)$




$BF\_Insert(x_2)$




Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS

$BF\_Insert(x_1)$



$BF\_Insert(x_2)$







Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS

$BF\_Insert(x_1)$



$BF\_Insert(x_2)$




$BF\_Insert(x_3)$


Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$




$BF\_Insert(x_3)$




Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$




$BF\_Insert(x_3)$




Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$



$BF\_Insert(x_3)$




SEARCHES


Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$



$BF\_Insert(x_3)$



SEARCHES

$BF\_Search(x) =$

Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$


INSERTS

$BF\_Insert(x_1)$

$BF\_Insert(x_2)$


$BF\_Insert(x_3)$

**BF**



SEARCHES


$BF\_Search(x) =$




Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$




$BF\_Insert(x_3)$



SEARCHES


$BF\_Search(x) =$




Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$




$BF\_Insert(x_3)$



SEARCHES

$BF\_Search(x) = \text{"No"}$







Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$



$BF\_Insert(x_3)$



SEARCHES


$BF\_Search(x) = \text{"No"}$

$\Rightarrow x \notin x_1, x_2, x_3$


Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$



$BF\_Insert(x_3)$



SEARCHES


$BF\_Search(x) = \text{"No"}$   
 $\Rightarrow x \notin x_1, x_2, x_3$

$BF\_Search(x') =$


Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$




$BF\_Insert(x_3)$



SEARCHES

$BF\_Search(x) = \text{"No"}$   
 $\Rightarrow x \notin \{x_1, x_2, x_3\}$



$BF\_Search(x') =$


Example  $BF[0 \dots 7]$  with  $t = 2$ :  $h_1$  and  $h_2$

INSERTS

$BF\_Insert(x_1)$

$BF\_Insert(x_2)$

$BF\_Insert(x_3)$



SEARCHES


$BF\_Search(x) = \text{"No"}$   
 $\Rightarrow x \notin \{x_1, x_2, x_3\}$

$BF\_Search(x') =$


Example  $BF[0 \dots 7]$  with  $t = 2: h_1$  and  $h_2$

INSERTS


$BF\_Insert(x_1)$



$BF\_Insert(x_2)$




$BF\_Insert(x_3)$




SEARCHES

$BF\_Search(x) = \text{"No"}$

$\Rightarrow x \notin x_1, x_2, x_3$




$BF\_Search(x') = \text{"Prob. Yes"}$



Example  $BF[0 \dots 7]$  with  $t = 2: h_1$  and  $h_2$

INSERTS

$BF\_Insert(x_1)$



$BF\_Insert(x_2)$

$BF\_Insert(x_3)$

SEARCHES

$BF\_Search(x) = \text{"No"}$

$\Rightarrow x \notin x_1, x_2, x_3$

$BF\_Search(x') = \text{"Prob. Yes"}$

False Positive !



“Fingerprint” of  $x$  are the indices  $h_1(x), h_2(x), \dots, h_t(x)$



“Fingerprint” of  $x$  are the indices  $h_1(x), h_2(x), \dots, h_t(x)$

**BF\_Insert( $x$ )**      [Insert the “fingerprint” of  $x$  in **BF**]





“Fingerprint” of  $x$  are the indices  $h_1(x), h_2(x), \dots, h_t(x)$

**BF\_Insert( $x$ )**      [Insert the “fingerprint” of  $x$  in **BF**]

for  $i = 1$  to  $t$  :

**BF**[ $h_i(x)$ ] = 1



“Fingerprint” of  $x$  are the indices  $h_1(x), h_2(x), \dots, h_t(x)$

**BF\_Insert( $x$ )**      [Insert the “fingerprint” of  $x$  in **BF**]

for  $i = 1$  to  $t$  :

**BF**[ $h_i(x)$ ] = 1

**BF\_Search( $x$ )**      [Search for “fingerprint” of  $x$  in **BF**]



“Fingerprint” of  $x$  are the indices  $h_1(x), h_2(x), \dots, h_t(x)$

**BF\_Insert( $x$ )**      [Insert the “fingerprint” of  $x$  in **BF**]

for  $i = 1$  to  $t$  :

**BF**[ $h_i(x)$ ] = 1

**BF\_Search( $x$ )**      [Search for “fingerprint” of  $x$  in **BF**]

for  $i = 1$  to  $t$  :

    if **BF**[ $h_i(x)$ ] = 0 then return “No”



“Fingerprint” of  $x$  are the indices  $h_1(x), h_2(x), \dots, h_t(x)$

**BF\_Insert( $x$ )**      [Insert the “fingerprint” of  $x$  in **BF**]

for  $i = 1$  to  $t$  :

**BF**[ $h_i(x)$ ] = 1

**BF\_Search( $x$ )**      [Search for “fingerprint” of  $x$  in **BF**]

for  $i = 1$  to  $t$  :

    if **BF**[ $h_i(x)$ ] = 0 then return “No”

return “Probably Yes”



# Probability of False Positive



# Probability of False Positive

Setup:

- Insert  $x_1, x_2, \dots, x_n$  into an empty  $\text{BF}[0 \dots m-1]$  with  $t$  independent hash functions  $h_1, h_2, \dots, h_t$  each satisfying SUHA.



# Probability of False Positive

Setup:

- Insert  $x_1, x_2, \dots, x_n$  into an empty  $\text{BF}[0 \dots m-1]$  with  $t$  independent hash functions  $h_1, h_2, \dots, h_t$  each satisfying SUHA.
- Do  $\text{BF\_Search}(x)$  for  $x \notin x_1, x_2, \dots, x_n$



# Probability of False Positive

Setup:

- Insert  $x_1, x_2, \dots, x_n$  into an empty  $\text{BF}[0 \dots m-1]$  with  $t$  independent hash functions  $h_1, h_2, \dots, h_t$  each satisfying SUHA.
- Do  $\text{BF\_Search}(x)$  for  $x \notin x_1, x_2, \dots, x_n$

We would like to compute:

- $\text{Pr}[\text{false positive}]$





# Probability of False Positive

Setup:

- Insert  $x_1, x_2, \dots, x_n$  into an empty  $\text{BF}[0 \dots m-1]$  with  $t$  independent hash functions  $h_1, h_2, \dots, h_t$  each satisfying SUHA.
- Do  $\text{BF\_Search}(x)$  for  $x \notin x_1, x_2, \dots, x_n$

We would like to compute:

- $\Pr[\text{false positive}] = \Pr [\text{BF\_Search}(x) = \text{“Probably Yes”}]$



# Probability of False Positive

Setup:

- Insert  $x_1, x_2, \dots, x_n$  into an empty  $\text{BF}[0 \dots m-1]$  with  $t$  independent hash functions  $h_1, h_2, \dots, h_t$  each satisfying SUHA.
- Do  $\text{BF\_Search}(x)$  for  $x \notin x_1, x_2, \dots, x_n$

We would like to compute:

- $\Pr[\text{false positive}] = \Pr[\text{BF\_Search}(x) = \text{"Probably Yes"}]$

We first compute:

- For an arbitrary index  $i$  of  $\text{BF}$ ,  $\Pr[\text{BF}[i] = 0]$  after inserting  $x_1, x_2, \dots, x_n$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] =$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = \Pr\left[\bigcap_{k=1}^n \bigcap_{j=1}^t h_j(x_k) \neq i\right]$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = \Pr\left[\bigcap_{k=1}^n \bigcap_{j=1}^t h_j(x_k) \neq i\right]$$

By SUHA and  
independence of  $h_i$ s :  
these events are  
mutually  
independent!



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = \Pr\left[\bigcap_{k=1}^n \bigcap_{j=1}^t h_j(x_k) \neq i\right]$$

$$= \prod_{k=1}^n \prod_{j=1}^t \Pr[h_j(x_k) \neq i]$$

By SUHA and  
independence of  $h_i$ s :  
these events are  
mutually  
independent!



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = \Pr\left[\bigcap_{k=1}^n \bigcap_{j=1}^t h_j(x_k) \neq i\right]$$

$$= \prod_{k=1}^n \prod_{j=1}^t \underbrace{\Pr[h_j(x_k) \neq i]}_{1 - 1/m}$$

Because of  
SUHA !





# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = \Pr\left[\bigcap_{k=1}^n \bigcap_{j=1}^t h_j(x_k) \neq i\right]$$

$$= \prod_{k=1}^n \prod_{j=1}^t \underbrace{\Pr[h_j(x_k) \neq i]}_{1 - 1/m}$$

Because of  
SUHA !

$$= (1 - 1/m)^{nt}$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = (1 - 1/m)^n$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = (1 - 1/m)^n \quad \left[ 1 - y \approx e^{-y} \quad (\text{for small } y = 1/m) \right]$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\begin{aligned} \Pr[\mathbf{BF}[i] = 0] &= (1 - 1/m)^{nt} && [1 - y \approx e^{-y} \quad (\text{for small } y = 1/m)] \\ &\approx (e^{-1/m})^{nt} \end{aligned}$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\begin{aligned}\Pr[\mathbf{BF}[i] = 0] &= (1 - 1/m)^{nt} && [1 - y \approx e^{-y} \quad (\text{for small } y = 1/m)] \\ &\approx (e^{-1/m})^{nt} = e^{-nt/m}\end{aligned}$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = (1 - 1/m)^{nt} \quad \left[ 1 - y \approx e^{-y} \quad (\text{for small } y = 1/m) \right]$$

$$\approx (e^{-1/m})^{nt} = e^{-nt/m}$$

$$\Pr[\mathbf{BF}[i] = 1] =$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = (1 - 1/m)^{nt} \quad \left[ 1 - y \approx e^{-y} \quad (\text{for small } y = 1/m) \right]$$

$$\approx (e^{-1/m})^{nt} = e^{-nt/m}$$

$$\Pr[\mathbf{BF}[i] = 1] = 1 - \Pr[\mathbf{BF}[i] = 0]$$



# Probability of False Positive

Consider an arbitrary index  $i$  of the **BF**

After inserting  $x_1, x_2, \dots, x_n$ ,

$$\Pr[\mathbf{BF}[i] = 0] = (1 - 1/m)^{nt} \quad \left[ 1 - y \approx e^{-y} \quad (\text{for small } y = 1/m) \right]$$

$$\approx (e^{-1/m})^{nt} = e^{-nt/m}$$

$$\Pr[\mathbf{BF}[i] = 1] = 1 - \Pr[\mathbf{BF}[i] = 0]$$

$$\approx 1 - e^{-nt/m}$$





# Probability of False Positive

**Lemma 1:** After inserting  $x_1, x_2, \dots, x_n$  into a **BF** of size  $m$  with  $t$  hash functions,



# Probability of False Positive

**Lemma 1:** After inserting  $x_1, x_2, \dots, x_n$  into a **BF** of size  $m$  with  $t$  hash functions, for every index  $i$ ,  $\Pr[\mathbf{BF}[i] = 1] \approx 1 - e^{-nt/m}$



# Probability of False Positive

**Lemma 1:** After inserting  $x_1, x_2, \dots, x_n$  into a **BF** of size  $m$  with  $t$  hash functions, for every index  $i$ ,  $\Pr[\mathbf{BF}[i] = 1] \approx \underbrace{1 - e^{-nt/m}}_q$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(\mathbf{x}) = \text{"Probably Yes"}]$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$$\begin{aligned}\text{Pr}[\text{false positive}] &= \text{Pr} [\mathbf{BF\_Search}(\mathbf{x}) = \text{"Probably Yes"}] \\ &= \text{Pr}[\mathbf{BF}[h_1(\mathbf{x})] = 1]\end{aligned}$$



# Probability of a False Positive

Do **BF\_Search**(**x**) for **x**  $\notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(\mathbf{x}) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(\mathbf{x})] = 1 \cap \mathbf{BF}[h_2(\mathbf{x})] = 1]$$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(x) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(x) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$



Not independent !



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(x) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$

$$\approx \Pr[\mathbf{BF}[h_1(x)] = 1] \cdot \Pr[\mathbf{BF}[h_2(x)] = 1] \cdot \dots \cdot \Pr[\mathbf{BF}[h_t(x)] = 1]$$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(x) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$

$$\approx \Pr[\underbrace{\mathbf{BF}[h_1(x)] = 1}_{i_1}] \cdot \Pr[\underbrace{\mathbf{BF}[h_2(x)] = 1}_{i_2}] \cdot \dots \cdot \Pr[\underbrace{\mathbf{BF}[h_t(x)] = 1}_{i_t}]$$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\text{Pr}[\text{false positive}] = \text{Pr} [\mathbf{BF\_Search}(\mathbf{x}) = \text{"Probably Yes"}]$

$$= \text{Pr}[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$

$$\approx \text{Pr}[\mathbf{BF}[i_1] = 1] \cdot \text{Pr}[\mathbf{BF}[i_2] = 1] \cdot \dots \cdot \text{Pr}[\mathbf{BF}[i_t] = 1]$$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(x) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$

$$\approx \underbrace{\Pr[\mathbf{BF}[i_1] = 1]}_q \cdot \underbrace{\Pr[\mathbf{BF}[i_2] = 1]}_q \cdot \dots \cdot \underbrace{\Pr[\mathbf{BF}[i_t] = 1]}_q$$

By Lemma 1 !



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(\mathbf{x}) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$

$$\approx \underbrace{\Pr[\mathbf{BF}[i_1] = 1]}_q \cdot \underbrace{\Pr[\mathbf{BF}[i_2] = 1]}_q \cdot \dots \cdot \underbrace{\Pr[\mathbf{BF}[i_t] = 1]}_q$$

By Lemma 1 !

$$\approx q^t$$



# Probability of a False Positive

Do **BF\_Search**(**x**) for  $x \notin x_1, x_2, \dots, x_n$

$\Pr[\text{false positive}] = \Pr [\mathbf{BF\_Search}(\mathbf{x}) = \text{"Probably Yes"}]$

$$= \Pr[\mathbf{BF}[h_1(x)] = 1 \cap \mathbf{BF}[h_2(x)] = 1 \cap \dots \cap \mathbf{BF}[h_t(x)] = 1]$$

$$\approx \underbrace{\Pr[\mathbf{BF}[i_1] = 1]}_q \cdot \underbrace{\Pr[\mathbf{BF}[i_2] = 1]}_q \cdot \dots \cdot \underbrace{\Pr[\mathbf{BF}[i_t] = 1]}_q$$

By Lemma 1 !

$$\approx q^t = \left(1 - e^{-nt/m}\right)^t$$



# Probability of a False Positive

$$\Pr[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$



# Probability of a False Positive

$$\Pr[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$

$$\frac{m}{n}$$





# Probability of a False Positive

$$\Pr[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$


$\frac{m}{n}$

# of elements




# Probability of a False Positive

$$\text{Pr}[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$



# Probability of a False Positive

$$\Pr[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$



# Probability of a False Positive

$$\Pr[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$

$$\frac{m}{n} \text{ (\# of bits per element)}$$



# Probability of a False Positive

$$\Pr[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$

Fix the ratio  $\frac{m}{n}$  (# of bits per element)



# Probability of a False Positive

$$\text{Pr}[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$

Fix the ratio  $\frac{m}{n}$  (# of bits per element)

Find  $t$  (i.e. # of hash functions) which **minimizes**  $\text{Pr}[\text{false positive}]$



# Probability of a False Positive

$$\text{Pr}[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$

Fix the ratio  $\frac{m}{n}$  (# of bits per element)

Find  $t$  (i.e. # of hash functions) which **minimizes**  $\text{Pr}[\text{false positive}]$

Find derivative of  $\left(1 - e^{-nt/m}\right)^t$  w.r.t  $t$  and set it to **0**



# Probability of a False Positive

$$\text{Pr}[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t$$

Fix the ratio  $\frac{m}{n}$  (# of bits per element)

Find  $t$  (i.e. # of hash functions) which **minimizes**  $\text{Pr}[\text{false positive}]$

$$\text{Optimal } t = (\log_e 2) \frac{m}{n} = 0.69 \frac{m}{n}$$





# Probability of a False Positive

$$\Pr[\text{false positive}] \approx \left(1 - e^{-nt/m}\right)^t = 0.62^{\frac{m}{n}}$$

with optimal  $t$

Fix the ratio  $\frac{m}{n}$  (# of bits per element)

Find  $t$  (i.e. # of hash functions) which **minimizes**  $\Pr[\text{false positive}]$

$$\text{Optimal } t = (\log_e 2) \frac{m}{n} = 0.69 \frac{m}{n}$$



# Example

- Want a Bloom Filter for a set **S** of **n = 10 Million** URLs



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL



# Example

- Want a Bloom Filter for a set **S** of **n = 10 Million** URLs

Much less than space required to store 1 full URL

- Can allocate **8 bits** per URL



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m$



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m = 8n = 8 * 10$  Million bits  $\approx 10$  MB



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m = 8n = 8 * 10 \text{ Million bits} \approx 10 \text{ MB}$

The  $t$  that minimizes  $\text{Pr}[\text{false positive}]$  is:





# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m = 8n = 8 * 10$  Million bits  $\approx 10$  MB

The  $t$  that minimizes  $\Pr[\text{false positive}]$  is:

$$t \approx 0.69 \frac{m}{n}$$

hash functions



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m = 8n = 8 * 10$  Million bits  $\approx 10$  MB

The  $t$  that minimizes  $\Pr[\text{false positive}]$  is:

$$t \approx 0.69 \frac{m}{n} = 0.69 * 8 = 5.52 \text{ hash functions}$$



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m = 8n = 8 * 10$  Million bits  $\approx 10$  MB

The  $t$  that minimizes  $\Pr[\text{false positive}]$  is:

$$t \approx 0.69 \frac{m}{n} = 0.69 * 8 = 5.52 \text{ hash functions}$$

With this  $t$ ,  $\Pr[\text{false positive}] \approx 0.62^{\frac{m}{n}}$



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m = 8n = 8 * 10$  Million bits  $\approx 10$  MB

The  $t$  that minimizes  $\Pr[\text{false positive}]$  is:

$$t \approx 0.69 \frac{m}{n} = 0.69 * 8 = 5.52 \text{ hash functions}$$

With this  $t$ ,  $\Pr[\text{false positive}] \approx 0.62^{\frac{m}{n}} = 0.62^8$



# Example

- Want a Bloom Filter for a set  $S$  of  $n = 10$  Million URLs
- Can allocate 8 bits per URL

Size of BF =  $m = 8n = 8 * 10$  Million bits  $\approx 10$  MB

The  $t$  that minimizes  $\Pr[\text{false positive}]$  is:

$$t \approx 0.69 \frac{m}{n} = 0.69 * 8 = 5.52 \text{ hash functions}$$

With this  $t$ ,  $\Pr[\text{false positive}] \approx 0.62^{\frac{m}{n}} = 0.62^8 \approx 2 \% !!$

