Max-Heaps

Abstract Data Type:

- Describes an object and its operations

Abstract Data Type:

- Describes an object and its operations

Data Structure:

- Some **specific implementation** of an Abstract Data Type

Abstract Data Type:

- Describes an object and its operations

Data Structure:

- Some **specific implementation** of an Abstract Data Type

Example of an Abstract Data Type: Priority Queues

Priority Queues

- Object : Set S of elements with “keys” (“priority”) that can be compared

Priority Queues

- Object : Set S of elements with “keys” (“priority”) that can be compared

- Operations:

Priority Queues

- Object : Set S of elements with “keys” (“priority”) that can be compared

- Operations:
  - **Insert(**S, x**):** Insert element x in S

Priority Queues

- Object : Set S of elements with “keys” (“priority”) that can be compared

- Operations:
  - **Insert(**S, x**):** Insert element x in S
  - **Max(**S**):** Returns an element of highest priority in S

Priority Queues

- Object : Set S of elements with “keys” (“priority”) that can be compared

- Operations:
  - **Insert(**S, x**):** Insert element x in S
  - **Max(**S**):** Returns an element of highest priority in S
  - **Extract_Max(**S**):** returns Max(S) and removes it from S.

An Application of Priority Queue

The OS can use a Priority Queue to maintain a set S of jobs and schedule them according to their priorities:

- When a new job x arrives, the OS does **Insert**(S,x).
- When a processor becomes available to execute a job, the OS does

  Extract_Max(S**)**

Simple Data Structures for implementing a Priority Queue

Worst Case Time For	Insert	Extract_Max
Unordered Linked List		

Simple Data Structures for implementing a Priority Queue

Worst Case Time For	Insert	Extract_Max
Unordered Linked List	**Θ(1)**	

Simple Data Structures for implementing a Priority Queue

Worst Case Time For	Insert	Extract_Max
Unordered Linked List	**$\Theta(1)$**	**$\Theta(n)$**

Simple Data Structures for implementing a Priority Queue

Worst Case Time For	Insert	Extract_Max
Unordered Linked List	**Θ(1)**	**Θ(n)**
Ordered Linked List		

Simple Data Structures for implementing a Priority Queue

Worst Case Time For	Insert	Extract_Max
Unordered Linked List	**$\Theta(1)$**	**$\Theta(n)$**
Ordered Linked List		**$\Theta(1)$**

Simple Data Structures for implementing a Priority Queue

Worst Case Time For	Insert	Extract_Max
Unordered Linked List	**$\Theta(1)$**	**$\Theta(n)$**
Ordered Linked List	**$\Theta(n)$**	**$\Theta(1)$**

Simple Data Structures for implementing a Priority Queue

Worst Case Time For	Insert	Extract_Max
Unordered Linked List	**$\Theta(1)$**	**$\Theta(n)$**
Ordered Linked List	**$\Theta(n)$**	**$\Theta(1)$**

Goal: Data Structure that does each operation in $\Theta(\log n)$ time

Max-Heaps

Visualizing Max-Heaps

Elements of Max-Heap are stored in a Complete Binary Tree.

Complete Binary Tree (CBT)



Complete Binary Tree (CBT)

- A Binary Tree



Complete Binary Tree (CBT)

- A Binary Tree
- Every level L, except maybe the bottom level, has 2^L nodes.



Complete Binary Tree (CBT)

- A Binary Tree
- Every level L, except maybe the bottom level, has 2^L nodes.
- All the nodes in the bottom level are as far to the left as possible.



Is this a Complete Binary Tree?



Is this a Complete Binary Tree? **No!**



Is this a Complete Binary Tree?



Is this a Complete Binary Tree?

No!



Height of a Tree



Height of a Tree

Number of **edges** in the longest path from root to any leaf.



Height of a Tree

Number of **edges** in the longest path from root to any leaf.

Height: 3



FACT: Height of a CBT with n nodes is $\lfloor \log_2 n \rfloor$



FACT: Height of a CBT with n nodes is $\lfloor \log_2 n \rfloor$



Here n = 9, and height = $\lfloor \log_2 9 \rfloor = 3$

Max-Heap: The n elements of a Max-Heap are stored in a CBT with n nodes such that the following property holds.

Max-Heap Property: Priority of each node >= Priority of its children

Example of a Max-Heap

$S = \{3, 4, 5, 7, 7, 9, 9, 12, 17\}$

(for simplicity, we identify each element with its priority)

Example of a Max-Heap

$S = \{3, 4, 5, 7, 7, 9, 9, 12, 17\}$



Example of a Max-Heap

S = {3, 4, 5, 7, 7, 9, 9, 12, 17}



Example of a Max-Heap

$S = \{3, 4, 5, 7, 7, 9, 9, 12, 17\}$

Heap of S is not unique !



Example of a Max-Heap

$S = \{3, 4, 5, 7, 7, 9, 9, 12, 17\}$

Heap of S is not unique !



Array Representation of a Heap



A:

Index 1 2 3 4 5 6 7 8 9



A:

17								

Index 1 2 3 4 5 6 7 8 9



A:	17	9							
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12						
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12	7					
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12	7	7				
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12	7	7	9			
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12	7	7	9	5		
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12	7	7	9	5	3	
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12	7	7	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9



A:	17	9	12	7	7	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9





Index 1 2 3 4 5 6 7 8 9





Left Child of A[i] is at A[2i]

Right Child of A[i] is at A[2i+1]

A:	17	9	12	7	7	9	5	3	4
Index	1	2	3	4	5	6	7	8	9



A:	17	9	12	7	7	9	5	3	4
Index	1	2	3	4	5	6	7	8	9







A:	17	9	12	7	7	9	5	3	4
Index	1	2	3	4	5	6	7	8	9







Parent of A[i] is A[⌊i/2⌋]



Efficient navigation in the tree

- Left Child of **A[i]** is at **A[2i]**
- Right Child of **A[i]** is at **A[2i+1]**
- Parent of **A[i]** is **A[$\lfloor$i/2$\rfloor$]**

Heap Operations

We will implement the following operations:

- **Insert(A, x)**
- **Max(A)**
- **Extract_Max(A)**

We will implement the following operations:

- **Insert(A, x)**
- **Max(A)**
- **Extract_Max(A)**

<u>High-Level idea for operations:</u>

We will implement the following operations:

- **Insert(A, x)**
- **Max(A)**
- **Extract_Max(A)**

<u>High-Level idea for operations:</u>

1) Maintain the CBT shape

We will implement the following operations:

- **Insert(A, x)**
- **Max(A)**
- **Extract_Max(A)**

<u>High-Level idea for operations:</u>

1) Maintain the CBT shape

2) Maintain the Max-Heap property

Insert(A, x)

Insert(A, 13)



A:	17	9	12	7	7	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9

Insert(A, 13)



A:	17	9	12	7	7	9	5	3	4	
Index	1	2	3	4	5	6	7	8	9	10

A.Heapsize = 10

Insert(A, 13)



	1	2	3	4	5	6	7	8	9	10
A:	17	9	12	7	7	9	5	3	4	13

A.Heapsize = 10

Insert(A, 13)



This is a CBT, but Max-Heap Property has been violated.

A:	17	9	12	7	7	9	5	3	4	13
Index	1	2	3	4	5	6	7	8	9	10

A.Heapsize = 10

Insert(A, 13)





Insert(A, 13)



A:	17	9	12	7	13	9	5	3	4	7
Index	1	2	3	4	5	6	7	8	9	10

A.Heapsize = 10

Insert(A, 13)





Insert(A, 13)



A:	17	13	12	7	9	9	5	3	4	7
Index	1	2	3	4	5	6	7	8	9	10

A.Heapsize = 10

Insert(A, 13)



Max-Heap Property has been restored!

A:

17	13	12	7	9	9	5	3	4	7
1	2	3	4	5	6	7	8	9	10

Index

A.Heapsize = 10

Insert(A, x)

1. Put x at the bottom left of the tree:

   Increment A.heapsize and set A[A.heapsize] = x

2. Percolate x up the tree:

   While priority of x > priority of its parent

   Swap x with parent

Insert(A, x)

1. Put x at the bottom left of the tree:

   Increment A.heapsize and set A[A.heapsize] = x

2. Percolate x up the tree:

   While x is not root AND priority of x > priority of its parent

   Swap x with parent

Insert(A, x)

1. Put x at the bottom left of the tree:

   Increment A.heapsize and set A[A.heapsize] = x

Maintains CBT shape

2. Percolate x up the tree:

   While x is not root AND priority of x > priority of its parent

   Swap x with parent

Maintains Max-Heap property

What is the Worst-Case Complexity of **Insert(A,x)** ?

What is the Worst-Case Complexity of **Insert(A,x)** ?

O(log n)

What is the Worst-Case Complexity of **Insert(A,x)** ?

O(log n)

For **every** input A,x of size n, the algorithm takes **at most** c_1. log n steps.

What is the Worst-Case Complexity of **Insert(A,x)** ?

$O(\log n)$

For **every** input A,x of size n, the algorithm takes **at most** $c_1 . \log n$ steps.

$\Omega(\log n)$

What is the Worst-Case Complexity of **Insert(A,x)** ?

$O(\log n)$

For **every** input A,x of size n, the algorithm takes **at most** c_1. log n steps.

$\Omega(\log n)$

For **some** input A,x of size n, the algorithm takes **at least** c_2. log n steps.

What is the Worst-Case Complexity of **Insert(A,x)** ?

$O(\log n)$

For **every** input A,x of size n, the algorithm takes **at most** c_1. log n steps.

$\Omega(\log n)$

For **some** input A,x of size n, the algorithm takes **at least** c_2. log n steps.

Priority of x is > Priority of root

What is the Worst-Case Complexity of **Insert(A,x)** ?



$O(\log n)$

For **every** input A,x of size n, the algorithm takes **at most** c_1. log n steps.

$\Omega(\log n)$

For **some** input A,x of size n, the algorithm takes **at least** c_2. log n steps.

Max(A)

Max(A):

Return A[1]

Max(A):

Return A[1]

Max(A):

Return A[1]

Worst-Case Time Complexity is $\Theta(1)$

Extract_Max(A)

Extract_Max(A)



A:	17	13	12	7	9	9	5	3	4	7
Index	1	2	3	4	5	6	7	8	9	10

A.Heapsize = 10

Extract_Max(A)



A:		13	12	7	9	9	5	3	4	7
Index	1	2	3	4	5	6	7	8	9	10

A.Heapsize = 10

Extract_Max(A)





Extract_Max(A)



A:	7	13	12	7	9	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9

Extract_Max(A)



This is a CBT, but Max-Heap Property has been violated.

A:	7	13	12	7	9	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9

Extract_Max(A)



This is a CBT, but Max-Heap Property has been violated.

A:	7	13	12	7	9	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9

Extract_Max(A)





A.Heapsize = 9

Extract_Max(A)



A:	13	7	12	7	9	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9

Extract_Max(A)





Extract_Max(A)



A:	13	9	12	7	7	9	5	3	4
Index	1	2	3	4	5	6	7	8	9

A.Heapsize = 9

Extract_Max(A)



Max-Heap Property has been restored!

A:

13	9	12	7	7	9	5	3	4
1	2	3	4	5	6	7	8	9

Index

A.Heapsize = 9

Extract_Max(A)

1. Return the root A[1].

2. Remove the returned element from the heap:

    Set A[1] = A[A.heapsize] and decrement A.heapsize

3. Drip the element in A[1] down the tree:

    Let x be the element in A[1]

    While priority of some child of x > priority of x

        Swap x with the highest-priority child of x

Extract_Max(A)

1. Return the root A[1].

2. Remove the returned element from the heap:

   Set A[1] = A[A.heapsize] and decrement A.heapsize

3. Drip the element in A[1] down the tree:

   Let x be the element in A[1]

   While x is not a leaf AND priority of some child of x > priority of x

   Swap x with the highest-priority child of x

Extract_Max(A)

1. Return the root A[1].

2. Remove the returned element from the heap:

   Set A[1] = A[A.heapsize] and decrement A.heapsize

3. Drip the element in A[1] down the tree:

   Let x be the element in A[1]

   While x is not a leaf AND priority of some child of x > priority of x

      Swap x with the highest-priority child of x

Index of x <= [n/2]

Extract_Max(A)

1. Return the root A[1].

2. Remove the returned element from the heap:

   Set A[1] = A[A.heapsize] and decrement A.heapsize

3. Drip the element in A[1] down the tree:

   Let x be the element in A[1]

   While x is not a leaf AND priority of some child of x > priority of x

   Swap x with the highest-priority child of x

Maintains CBT shape

Maintains Max-Heap property

Index of x <= ⌊n/2⌋

What is the Worst-Case Complexity of **Extract_Max(A)** ?

What is the Worst-Case Complexity of **Extract_Max(A)** ?

$\Theta(\log n)$ **BOTH**

$O(\log n)$

For **every** input A of size n, the algorithm takes **at most** c_1. log n steps.

$\Omega(\log n)$

For **some** input A of size n, the algorithm takes **at least** c_2. log n steps.

What is the Worst-Case Complexity of **Extract_Max(A)** ?

$\Theta(\log n)$ — BOTH — $O(\log n)$ and $\Omega(\log n)$

$O(\log n)$

For **every** input A of size n, the algorithm takes **at most** c_1. log n steps.

$\Omega(\log n)$

For **some** input A of size n, the algorithm takes **at least** c_2. log n steps.

A[A.heapsize] has the smallest priority

Application: HeapSort

To sort an Array A of n elements:

Application: HeapSort

To sort an Array A of n elements:

- Make a heap out of the elements of A

Application: HeapSort

To sort an Array A of n elements:

- Make a heap out of the elements of A

How do you do this?

Application: HeapSort

To sort an Array A of n elements:

- Make a heap out of the elements of A

This can be done in $\Theta(n)$ time !

Application: HeapSort

To sort an Array A of n elements:

- Make a heap out of the elements of A

This can be done in $\Theta(n)$ time !

- **Extract_Max(A)** n times [Each one takes $\Theta(\log n)$ time]

Application: HeapSort

To sort an Array A of n elements:

- Make a heap out of the elements of A

This can be done in $\Theta(n)$ time !

- **Extract_Max(A)** n times [Each one takes $\Theta(\log n)$ time]

Worst-Case time complexity is $\Theta(n \log n)$

Application: HeapSort

To sort an Array A of n elements:

- Make a heap out of the elements of A

This can be done in $\Theta(n)$ time !

- **Extract_Max(A)** n times [Each one takes $\Theta(\log n)$ time]

Worst-Case time complexity is $\Theta(n \log n)$

This sorting can be done “in-place” in A (Refer CLRS Section 6.4)