

Binomial Heaps

© 2019 by Jay Balasundaram and Sam Toueg. This document may not be posted on the internet without the written permission of the copyright owners.



Abstract Data Types

Abstract Data Types		Insert	Min	Extract_Min	Union
Mergeable Priority Queues		✓	✓	✓	✓



Data Structures

Abstract Data Types	Data Structures	Insert	Min	Extract_Min	Union
Mergeable Priority Queues	Min Binomial Heap	$O(\log n)$	$O(\log n)$	$O(\log n)$	$O(\log n)$




Binomial Trees

B_k tree: defined recursively


$k = 0$

$B_0 :$




$k >= 1$

$B_k :$



Binomial Tree B_k




Binomial Forest F_n of size n

Sequence of B_k trees with *strictly decreasing k's* and a total of n nodes.




Example: Binomial Forest F_7 of $n = 7$ nodes

$$n = 7 = <1\ 1\ 1>_2 = 2^2 + 2^1 + 2^0$$



Example: Binomial Forest F_9 of $n = 9$ nodes

$$n = 9 = <1\ 0\ 0\ 1>_2 = 2^3 + 2^0$$




A **Min Binomial Heap** of n elements is a **Binomial Forest** F_n such that

1. Each node of F_n stores one element
2. Each B_k tree of F_n is Min-Heap ordered



Min Binomial Heap of size $n = 13 = < 1101 >_2$



Binomial Heap Operations

© 2019 by Jay Balasundaram and Sam Toueg. This document may not be posted
on the internet without the written permission of the copyright owners.



Must implement the following operations:

- **Union(T, Q)**
- **Insert(T, x)**
- **Min(T)**
- **Extract_Min(T)**



High Level Ideas

© 2019 by Jay Balasundaram and Sam Toueg. This document may not be posted on the internet without the written permission of the copyright owners.



High Level Ideas


Lemma 1: Can merge **two** min heap-ordered B_k trees into a **single** min heap-ordered B_{k+1} tree with just **one** key-comparison.



High Level Ideas

Lemma 1: Can merge **two** min heap-ordered B_k trees into a **single** min heap-ordered B_{k+1} tree with just **one** key-comparison.


Proof: To merge



High Level Ideas

Lemma 1: Can merge **two** min heap-ordered B_k trees into a **single** min heap-ordered B_{k+1} tree with just **one** key-comparison.


Proof: To merge, if $x \leq y$



High Level Ideas

Lemma 1: Can merge **two** min heap-ordered B_k trees into a **single** min heap-ordered B_{k+1} tree with just **one** key-comparison.

Proof: To merge, if $x \leq y$



High Level Ideas


Lemma 2: Deleting **the root** of a min heap-ordered B_k tree gives a **min binomial heap**.



High Level Ideas

Lemma 2: Deleting **the root** of a min heap-ordered B_k tree gives a **min binomial heap**.


Proof: Deleting the root of min heap-ordered B_k tree.



High Level Ideas

Lemma 2: Deleting **the root** of a min heap-ordered B_k tree gives a **min binomial heap**.


Proof: Deleting the root of min heap-ordered B_k tree.



High Level Ideas

Lemma 2: Deleting **the root** of a min heap-ordered B_k tree gives a **min binomial heap**.


Proof: Deleting the root of min heap-ordered B_k tree.



$$S \leftarrow \text{Union}(\tau, Q)$$


$S \leftarrow \text{Union}(T, Q)$


T is a Binomial Heap of size $n = 3 = < 1 1>_2$



$S \leftarrow \text{Union}(T, Q)$

T is a Binomial Heap of size $n = 3 = < 1 1>_2$


Q is a Binomial Heap of size $n = 7 = < 1 1 1>_2$



$S \leftarrow \text{Union}(T, Q)$

T is a Binomial Heap of size $n = 3 = < 1 1>_2$


Q is a Binomial Heap of size $n = 7 = < 1 1 1>_2$



$S \leftarrow \text{Union}(T, Q)$

T is a Binomial Heap of size $n = 3 = <1\ 1>_2$


Q is a Binomial Heap of size $n = 7 = <1\ 1\ 1>_2$



$S \leftarrow \text{Union}(T, Q)$

T is a Binomial Heap of size $n = 3 = <1\ 1>_2$


Q is a Binomial Heap of size $n = 7 = <1\ 1\ 1>_2$



$S \leftarrow \text{Union}(T, Q)$

T is a Binomial Heap of size $n = 3 = <1\ 1>_2$


Q is a Binomial Heap of size $n = 7 = <1\ 1\ 1>_2$



$S \leftarrow \text{Union}(T, Q)$

T is a Binomial Heap of size $n = 3 = <1\ 1>_2$

Q is a Binomial Heap of size $n = 7 = <1\ 1\ 1>_2$




How many new edges were added?



$S \leftarrow \text{Union}(T, Q)$

T is a Binomial Heap of size $n = 3 = <1\ 1>_2$

Q is a Binomial Heap of size $n = 7 = <1\ 1\ 1>_2$



How many new edges were added?





2
4



3


: T












Carry



(3) : T

+

(6)


: Q

X : S






Carry





MERGE



3 : T
+
6 : Q

X : S






Carry



(3) : T




(6) : Q



X : S



MERGE



Carry

(3) : T


+

(6) : Q


X : S




Carry




3 : T
+
6 : Q



X






X





X : S





Carry



X

(3) : T
+
(6) : Q

X

: S

3 new edges
3 key-comparisons



Worst-Case Complexity of Union(T, Q)

Say $|T| \leq n$ and $|Q| \leq n$ (i.e. each contains at most n elements)



Worst-Case Complexity of Union(T, Q)

Say $|T| \leq n$ and $|Q| \leq n$ (i.e. each contains at most n elements)

\Rightarrow Each of T, Q have $O(\log n)$ B_k trees.



Worst-Case Complexity of $\text{Union}(T, Q)$

Say $|T| \leq n$ and $|Q| \leq n$ (i.e. each contains at most n elements)

- ⇒ Each of T, Q have $O(\log n)$ B_k trees.
- ⇒ **$\text{Union}(T, Q)$** takes at most $O(\log n)$ key-comparisons




$$S \leftarrow \text{Insert}(T, x)$$


$S \leftarrow \text{Insert}(T, x)$

$S \leftarrow \text{Union}(T, \{x\})$



$$S \leftarrow \text{Insert}(T, x)$$
$$S \leftarrow \text{Union}(T, \{x\})$$


Trivial Binomial
Heap containing
just x



$$S \leftarrow \text{Insert}(T, x)$$
$$S \leftarrow \text{Union}(T, \{x\})$$

Trivial Binomial
Heap containing
just x

If $|T| \leq n$, **Insert**(T, x) takes at most $O(\log n)$ key-comparisons



Min(T)

© 2019 by Jay Balasundaram and Sam Toueg. This document may not be posted
on the internet without the written permission of the copyright owners.



$\text{Min}(T)$

Scan the roots of the B_k trees of T and return the smallest key.



$\text{Min}(T)$

Scan the roots of the B_k trees of T and return the smallest key.

If $|T| \leq n$, $\text{Min}(T)$ takes at most $O(\log n)$ key-comparisons




Extract_Min(T)




Extract_Min(T)

$T :$




Extract_Min(T)

$T :$





Extract_Min(T)




Extract_Min(T)

Binomial Heap $S = B_3 - \{1\}$




Extract_Min(T)

Binomial Heap $S = B_3 - \{1\}$




Binomial Heap $U = T - B_3$




Extract_Min(T)

Binomial Heap $S = B_3 - \{1\}$



Binomial Heap $U = T - B_3$



Now do: $T \leftarrow \text{Union}(U, S)$

Extract_Min(T)

- Do $\text{Min}(T)$ to locate the smallest element – Say it is the root of B_i

$$\textcolor{red}{U} = T - B_i$$



Extract_Min(T)

- Do $\text{Min}(T)$ to locate the smallest element – Say it is the root of B_i

$$\mathbf{U} = T - B_i$$

- Delete root of B_i . By Lemma 2, we get a Binomial Heap S , where

$$\mathbf{S} = B_i - (\text{root of } B_i)$$



Extract_Min(T)

- Do $\text{Min}(T)$ to locate the smallest element – Say it is the root of B_i

$$\textcolor{red}{U} = T - B_i$$

- Delete root of B_i . By Lemma 2, we get a Binomial Heap S , where

$$\textcolor{red}{S} = B_i - (\text{root of } B_i)$$

- $T \leftarrow \text{Union}(\textcolor{red}{U}, \textcolor{red}{S})$



Extract_Min(T)

- Do $\text{Min}(T)$ to locate the smallest element – Say it is the root of B_i

$$U = T - B_i$$

- Delete root of B_i . By Lemma 2, we get a Binomial Heap S , where

$$S = B_i - (\text{root of } B_i)$$

- $T \leftarrow \text{Union}(U, S)$

If $|T| \leq n$, Extract_Min(T) takes at most $O(\log n)$ key-comparisons



A couple more operations

- Given **pointer to a node x** in a Binomial Heap T , you can do:



A couple more operations

- Given **pointer to a node x** in a Binomial Heap T , you can do:

Decrease_Key(T, x, k): Decrease the key at node x to k .



A couple more operations

- Given **pointer to a node x** in a Binomial Heap T , you can do:

Decrease_Key(T, x, k): Decrease the key at node x to k .

Remove(T, x): Remove the key at node x .



A couple more operations

- Given **pointer to a node x** in a Binomial Heap T , you can do:

Decrease_Key(T, x, k): Decrease the key at node x to k .

Remove(T, x): Remove the key at node x .

Both in
 $O(\log n)$ time



A couple more operations

- Given **pointer to a node x** in a Binomial Heap T , you can do:

Decrease_Key(T, x, k): Decrease the key at node x to k .

Remove(T, x): Remove the key at node x .

Both in
 $O(\log n)$ time

- How do you do **Increase_Key(T, x, k)** ?



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?

Insert(T, x_1) , Insert(T, x_2) , . . . , Insert(T, x_k)



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?

$\text{Insert}(T, x_1)$, $\text{Insert}(T, x_2)$, . . . , $\text{Insert}(T, x_k)$

$O(\log n)$



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?

$\text{Insert}(T, x_1)$, $\text{Insert}(T, x_2)$, . . . , $\text{Insert}(T, x_k)$

$O(\log n)$ $O(\log(n + 1))$



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?

$\text{Insert}(T, x_1)$, $\text{Insert}(T, x_2)$, , $\text{Insert}(T, x_k)$

$O(\log n)$ $O(\log(n + 1))$ $O(\log(n + k))$



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?

$\text{Insert}(T, x_1)$, $\text{Insert}(T, x_2)$, , $\text{Insert}(T, x_k)$

$O(\log n)$ $O(\log(n + 1))$ $O(\log(n + k))$

- Total: $O(k \log(n + k))$



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?

$\text{Insert}(T, x_1)$, $\text{Insert}(T, x_2)$, , $\text{Insert}(T, x_k)$

$O(\log n)$ $O(\log(n + 1))$ $O(\log(n + k))$

- Total: $O(k \log(n + k))$
- Is the cost of k successive inserts actually lower?



Cost of k successive inserts

- T : Binomial Heap with n elements.
- Cost of k successive inserts into T ?

$\text{Insert}(T, x_1)$, $\text{Insert}(T, x_2)$, , $\text{Insert}(T, x_k)$

$O(\log n)$ $O(\log(n + 1))$ $O(\log(n + k))$

- Total: $O(k \log(n + k))$
- Is the cost of k successive inserts actually lower? Yes!



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ x_1 \\ \hline \end{array} \quad \begin{array}{r} 1 \ 1 \ 0 \ 1 \ 1 \\ \\ \\ \\ \hline \end{array}$$



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ x_1 \\ \hline \end{array}$$

1
1 1 0 1 1
1
0



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ x_1 \\ \hline \end{array}$$

1 1
1 1 0 1 1
+
x_1

0 0



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ X_1 \\ \hline \end{array} \quad \begin{array}{r} 1 \ 1 \\ \hline 1 \ 1 \ 0 \ 1 \ 1 \\ \hline 1 \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$$



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ X_1 \\ \hline \end{array} \quad \begin{array}{r} 1 \ 1 \\ \hline 1 \ 1 \ 0 \ 1 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$$

Cost : 2



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ X_1 \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array} \quad \begin{array}{r} T \\ + \\ X_2 \\ \hline 1 \ 1 \ 1 \ 0 \ 1 \end{array}$$

Cost : 2



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ X_1 \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$$

Cost : 2

A binary addition diagram showing the sum of T and X₁. The binary number T is 11011. The binary number X₁ is 1. The sum is 11100. The diagram shows the addition column by column from right to left. The first column (least significant) has a carry of 1. The second column has a carry of 1. The third column has a carry of 1. The fourth column has a carry of 1. The fifth column (most significant) has a carry of 1. Red numbers 1 1 are placed above the first two columns to indicate the carries.

$$\begin{array}{r} T \\ + \\ X_2 \\ \hline 1 \ 1 \ 1 \ 0 \ 1 \end{array}$$

Cost : 0

A binary addition diagram showing the sum of T and X₂. The binary number T is 11011. The binary number X₂ is 1. The sum is 11101. The diagram shows the addition column by column from right to left. The first column (least significant) has a carry of 1. The second column has a carry of 1. The third column has a carry of 1. The fourth column has a carry of 1. The fifth column (most significant) has a carry of 1. Red numbers 1 1 are placed above the first two columns to indicate the carries.



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$$\begin{array}{r} T \\ + \\ X_1 \\ \hline 1 & 1 & 0 & 1 & 1 \\ & 1 \\ \hline 1 & 1 & 1 & 0 & 0 \\ \text{Cost : } 2 \end{array}$$

$$\begin{array}{r} T \\ + \\ X_2 \\ \hline 1 & 1 & 1 & 0 & 0 \\ & 1 \\ \hline 1 & 1 & 1 & 0 & 1 \\ \text{Cost : } 0 \end{array}$$

$$\begin{array}{r} T \\ + \\ X_3 \\ \hline 1 & 1 & 1 & 0 & 1 \\ & 1 \\ \hline \end{array}$$



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

T + x_1	T + x_2	T + x_3
$\begin{array}{r} 1 \ 1 \\ 1 \ 1 \ 0 \ 1 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$ Cost : 2	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 0 \end{array}$



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

T + x_1	T + x_2	T + x_3
$\begin{array}{r} 1 \ 1 \\ 1 \ 1 \ 0 \ 1 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$ Cost : 2	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 0 \end{array}$ Cost : 1



Example: Say $|T| = 27 = <11011>_2$ $T = < B_4 \ B_3 \ B_1 \ B_0 >$

T + x_1	T + x_2	T + x_3	T + x_4
$1 \ 1 \ 0 \ 1 \ 1$ 1 $1 \ 1 \ 1 \ 0 \ 0$ Cost : 2	$1 \ 1 \ 1 \ 0 \ 0$ 1 $1 \ 1 \ 1 \ 0 \ 1$ Cost : 0	$1 \ 1 \ 1 \ 0 \ 1$ 1 $1 \ 1 \ 1 \ 1 \ 0$ Cost : 1	$1 \ 1 \ 1 \ 1 \ 0$ 1



Example: Say $|T| = 27 = <11011>_2$ $T = < B_4 \ B_3 \ B_1 \ B_0 >$

T + x_1	T + x_2	T + x_3	T + x_4
$1 \ 1 \ 0 \ 1 \ 1$ 1 $1 \ 1 \ 1 \ 0 \ 0$	$1 \ 1 \ 1 \ 0 \ 0$ 1 $1 \ 1 \ 1 \ 0 \ 1$	$1 \ 1 \ 1 \ 0 \ 1$ 1 $1 \ 1 \ 1 \ 1 \ 0$	$1 \ 1 \ 1 \ 1 \ 0$ 1 $1 \ 1 \ 1 \ 1 \ 1$
Cost : 2	Cost : 0	Cost : 1	



Example: Say $|T| = 27 = <11011>_2$ $T = < B_4 \ B_3 \ B_1 \ B_0 >$

T + x_1	T + x_2	T + x_3	T + x_4
$1 \ 1 \ 0 \ 1 \ 1$ 1 $1 \ 1 \ 1 \ 0 \ 0$ Cost : 2	$1 \ 1 \ 1 \ 0 \ 0$ 1 $1 \ 1 \ 1 \ 0 \ 1$ Cost : 0	$1 \ 1 \ 1 \ 0 \ 1$ 1 $1 \ 1 \ 1 \ 1 \ 0$ Cost : 1	$1 \ 1 \ 1 \ 1 \ 0$ 1 $1 \ 1 \ 1 \ 1 \ 1$ Cost : 0



Example: Say $|T| = 27 = <11011>_2$ $T = < B_4 \ B_3 \ B_1 \ B_0 >$

T	$1 \ 1 \ 0 \ 1 \ 1$	T	$1 \ 1 \ 1 \ 0 \ 0$	T	$1 \ 1 \ 1 \ 0 \ 1$	T	$1 \ 1 \ 1 \ 1 \ 0$	T	$1 \ 1 \ 1 \ 1 \ 1$
$+$		$+$		$+$		$+$		$+$	
x_1	1	x_2	1	x_3	1	x_4	1	x_5	1
	$1 \ 1 \ 1 \ 0 \ 0$		$1 \ 1 \ 1 \ 0 \ 1$		$1 \ 1 \ 1 \ 1 \ 0$		$1 \ 1 \ 1 \ 1 \ 1$		
Cost : 2		Cost : 0		Cost : 1		Cost : 0			

Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

T $+$ x_1	T $+$ x_2	T $+$ x_3	T $+$ x_4	T $+$ x_5
$\begin{array}{r} 1 \ 1 \\ 1 \ 1 \ 0 \ 1 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$ Cost : 2	$\begin{array}{r} 1 \ 1 \ 1 \\ 1 \ 1 \ 1 \ 0 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 0 \end{array}$ Cost : 1	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ \hline 1 \ 0 \ 0 \ 0 \ 0 \end{array}$
$\begin{array}{r} 1 \ 1 \\ 1 \ 1 \ 0 \ 1 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$ Cost : 2	$\begin{array}{r} 1 \ 1 \ 1 \\ 1 \ 1 \ 1 \ 0 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 0 \end{array}$ Cost : 1	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ \hline 1 \ 0 \ 0 \ 0 \ 0 \end{array}$

Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

T $+$ x_1	T $+$ x_2	T $+$ x_3	T $+$ x_4	T $+$ x_5
$\begin{array}{r} 1 \ 1 \\ 1 \ 1 \ 0 \ 1 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 0 \end{array}$ Cost : 2	$\begin{array}{r} 1 \ 1 \ 1 \\ 1 \ 1 \ 1 \ 0 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 0 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 0 \end{array}$ Cost : 1	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 1 \end{array}$ Cost : 0	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ \hline 1 \ 0 \ 0 \ 0 \ 0 \end{array}$ Cost : 5
$\begin{array}{r} 1 \ 1 \\ 1 \ 1 \ 0 \ 1 \ 1 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 0 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \end{array}$ $\begin{array}{r} 1 \ 0 \ 0 \ 0 \ 0 \end{array}$	$\begin{array}{r} 1 \ 1 \ 1 \\ 1 \ 1 \ 1 \ 0 \ 0 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \end{array}$	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 0 \end{array}$	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ \hline 1 \ 1 \ 1 \ 1 \ 1 \end{array}$	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ \hline 1 \ 0 \ 0 \ 0 \ 0 \end{array}$

Example: Say $|T| = 27 = <11011>_2$ $T = < B_4 \ B_3 \ B_1 \ B_0 >$

T $+$ x_1	T $+$ x_2	T $+$ x_3	T $+$ x_4	T $+$ x_5
$\begin{array}{r} 1 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 0 \ 1 \ 1$ 1	$\begin{array}{r} 1 \ 1 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 0 \ 0$ 1	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 0 \ 1$ 1	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 1 \ 0$ 1	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 1 \ 1 \ 1$ 1
$1 \ 1 \ 1 \ 0 \ 0$ Cost : 2	$1 \ 1 \ 1 \ 0 \ 1$ Cost : 0	$1 \ 1 \ 1 \ 1 \ 0$ Cost : 1	$1 \ 1 \ 1 \ 1 \ 1$ Cost : 0	$1 \ 0 \ 0 \ 0 \ 0 \ 0$ Cost : 5

- Total for 5 insertions: $2 + 0 + 1 + 0 + 5 = 8$ key-comparisons (not 5×5).



Example: Say $|T| = 27 = <11011>_2$ $T = < B_4 \ B_3 \ B_1 \ B_0 >$

T $+$ x_1	T $+$ x_2	T $+$ x_3	T $+$ x_4	T $+$ x_5
$\begin{array}{r} 1 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 0 \ 1 \ 1$ 1	$\begin{array}{r} 1 \ 1 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 0 \ 0$ 1	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 0 \ 1$ 1	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 1 \ 0$ 1	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ 1 \end{array}$ $1 \ 1 \ 1 \ 1 \ 1 \ 1$ 1
$1 \ 1 \ 1 \ 0 \ 0$ Cost : 2	$1 \ 1 \ 1 \ 0 \ 1$ Cost : 0	$1 \ 1 \ 1 \ 1 \ 0$ Cost : 1	$1 \ 1 \ 1 \ 1 \ 1$ Cost : 0	$1 \ 0 \ 0 \ 0 \ 0 \ 0$ Cost : 5

- Total for 5 insertions: $2 + 0 + 1 + 0 + 5 = 8$ key-comparisons (not 5×5).
- Initially: T has $27 - \alpha(27) = 27 - 4 = 23$ edges



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

$\begin{array}{r} T \\ + \\ x_1 \end{array}$ $\begin{array}{r} 1 & 1 & 0 & 1 & 1 \\ + & & & & \\ 1 & 1 & 1 & 0 & 0 \end{array}$ Cost : 2	$\begin{array}{r} T \\ + \\ x_2 \end{array}$ $\begin{array}{r} 1 & 1 & 1 & 0 & 0 \\ + & & & & \\ 1 & 1 & 1 & 0 & 1 \end{array}$ Cost : 0	$\begin{array}{r} T \\ + \\ x_3 \end{array}$ $\begin{array}{r} 1 & 1 & 1 & 0 & 1 \\ + & & & & \\ 1 & 1 & 1 & 1 & 0 \end{array}$ Cost : 1	$\begin{array}{r} T \\ + \\ x_4 \end{array}$ $\begin{array}{r} 1 & 1 & 1 & 1 & 0 \\ + & & & & \\ 1 & 1 & 1 & 1 & 1 \end{array}$ Cost : 0	$\begin{array}{r} T \\ + \\ x_5 \end{array}$ $\begin{array}{r} 1 & 1 & 1 & 1 & 1 \\ + & & & & \\ 1 & 0 & 0 & 0 & 0 \end{array}$ Cost : 5
---	---	---	---	---

- Total for 5 insertions: $2 + 0 + 1 + 0 + 5 = 8$ key-comparisons (not 5×5).
- Initially: T has $27 - \alpha(27) = 27 - 4 = 23$ edges
- After 5 insertions: T has $32 - \alpha(32) = 32 - 1 = 31$ edges



Example: Say $|T| = 27 = \langle 11011 \rangle_2$ $T = \langle B_4 \ B_3 \ B_1 \ B_0 \rangle$

T $+$ x_1	T $+$ x_2	T $+$ x_3	T $+$ x_4	T $+$ x_5
$\begin{array}{r} 1 \ 1 \\ + \\ 1 \end{array}$ \hline $1 \ 1 \ 1 \ 0 \ 0$	$\begin{array}{r} 1 \ 1 \ 1 \\ + \\ 1 \end{array}$ \hline $1 \ 1 \ 1 \ 0 \ 1$	$\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ 1 \end{array}$ \hline $1 \ 1 \ 1 \ 1 \ 0$	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ 1 \end{array}$ \hline $1 \ 1 \ 1 \ 1 \ 1$	$\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ 1 \end{array}$ \hline $1 \ 0 \ 0 \ 0 \ 0$
Cost : 2	Cost : 0	Cost : 1	Cost : 0	Cost : 5

- Total for 5 insertions: $2 + 0 + 1 + 0 + 5 = 8$ key-comparisons (not 5×5).
- Initially: T has $27 - \alpha(27) = 27 - 4 = 23$ edges
- After 5 insertions: T has $32 - \alpha(32) = 32 - 1 = 31$ edges
- The 5 insertions added: $31 - 23 = 8$ new edges.



Example: Say $|T| = 27 = <11011>_2$ $T = < B_4 \ B_3 \ B_1 \ B_0 >$

$\begin{array}{r} T \\ + \\ X_1 \end{array}$ $\begin{array}{r} 1 \ 1 \\ 1 \ 1 \ 0 \ 1 \ 1 \\ + \\ 1 \end{array}$ $\hline 1 \ 1 \ 1 \ 0 \ 0$ Cost : 2	$\begin{array}{r} T \\ + \\ X_2 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \\ 1 \ 1 \ 1 \ 0 \ 0 \\ + \\ 1 \end{array}$ $\hline 1 \ 1 \ 1 \ 0 \ 1$ Cost : 0	$\begin{array}{r} T \\ + \\ X_3 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 0 \ 1 \\ 1 \ 1 \ 1 \ 1 \ 0 \ 1 \\ + \\ 1 \end{array}$ $\hline 1 \ 1 \ 1 \ 1 \ 0$ Cost : 1	$\begin{array}{r} T \\ + \\ X_4 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 0 \\ 1 \ 1 \ 1 \ 1 \ 1 \ 0 \\ + \\ 1 \end{array}$ $\hline 1 \ 1 \ 1 \ 1 \ 1 \ 1$ Cost : 0	$\begin{array}{r} T \\ + \\ X_5 \end{array}$ $\begin{array}{r} 1 \ 1 \ 1 \ 1 \ 1 \ 1 \\ 1 \ 1 \ 1 \ 1 \ 1 \ 1 \ 1 \\ + \\ 1 \end{array}$ $\hline 1 \ 0 \ 0 \ 0 \ 0 \ 0$ Cost : 5
--	--	--	--	--

- Total for 5 insertions: $2 + 0 + 1 + 0 + 5 = 8$ key-comparisons (not 5×5).
- Initially: T has $27 - \alpha(27) = 27 - 4 = 23$ edges
- After 5 insertions: T has $32 - \alpha(32) = 32 - 1 = 31$ edges
- The 5 insertions added: $31 - 23 = 8$ new edges.
- **8 new edges = 8 key-comparisons**



Total Cost of k successive inserts
into a Binomial Heap with n nodes ?



Total Cost of k successive inserts
into a Binomial Heap with n nodes ?

total cost is at most $O(k \log(n + k))$ key-comparisons



Total Cost of k successive inserts
into a Binomial Heap with n nodes ?

Claim: If $k > \log_2 n$, total cost is at most

key-comparisons



Total Cost of k successive inserts
into a Binomial Heap with n nodes ?

Claim: If $k > \log_2 n$, total cost is at most $2k$ key-comparisons



Total Cost of k successive inserts
into a Binomial Heap with n nodes ?

Claim: If $k > \log_2 n$, total cost is at most $2k$ key-comparisons

Proof: Do A2 – Q6 ☺



Total Cost of k successive inserts
into a Binomial Heap with n nodes ?

Claim: If $k > \log_2 n$, total cost is at most $2k$ key-comparisons

Proof: Do A2 – Q6 ☺

⇒ Average cost per insert is ≤ 2 key-comparisons !

