PHYS 143 – Mechanics and Thermal Physics

Vectors

How do we describe, combine and calculate with quantities that have both magnitude and direction?

Hope Donglo

Office 24, Department of Physics, University of Ghana

Course information

- **Text:** Young and Freedman, *University Physics* (15th ed.). Copies in the Physics Department Library and Balme Library. Read the book on your own as well.
- **Sakai** (`sakai.ug.edu.gh`): slides, problem sheets, announcements, office hours. Log in this week.
- **Attendance** is required; ten absences without a UG physician's note bars you from the final exam.
- **Homework** must be your own work; you may not copy it, wholly or partly, from any source. Asking lecturers, TAs and classmates for help at any reasonable time is encouraged.

Everything else

Venues, times, TA names and the assessment breakdown are on Sakai. Extra material, practice questions and the Reference deck for each lecture: hhdonglo.github.io/phys143.html.

This week: the central question and the thread

CORE

Central question

How do we describe, combine and calculate with quantities that have both magnitude *and* direction?

By the end of this week, you should be able to:

1. Represent, add and subtract vectors graphically.
2. Resolve vectors into components and reconstruct their magnitude and direction.
3. Add vectors using components and unit-vector notation, and find the unit vector of any vector.
4. Calculate and interpret dot and cross products.

The thread of the week

Vectors give us a way to represent quantities with magnitude and direction. **Graphs build understanding; components give us a systematic way to calculate.**

1 UNDERSTAND: why do we need vectors?
2 CALCULATE: how do we calculate accurately?
3 EXTEND: what can two vectors construct?

Reading: Young and Freedman, Chapter 1, §1.7–1.10. **Slide labels:** **CORE** you should be able to do this; **PRACTICE** use it to develop the skill; **REFERENCE** keep it for later use.


Opening problem

You leave the Balme Library and walk **1 km north**, then **2 km east**.

Where are you now, relative to where you started?

Predict first


- Are you 3 km from the starting point?
- Is a single number a complete answer?
- In approximately what direction should the answer point?



We solve this once we can add vectors at 90°.

But what if... we cannot yet solve this completely. Before solving it, here is the method we will use throughout physics: **IDENTIFY, SET UP, EXECUTE, EVALUATE**.

How we solve every problem this semester



IDENTIFY

Read the problem carefully.
Identify the target: what is needed?
Identify the principles of physics required.

SET UP

Sketch a diagram.
Choose coordinates.
Predict the approximate size and direction.
Look for the appropriate equation.

EXECUTE

State the explanation; do the calculation, noting what is missing from what is given.
Carry units; keep track of signs.

EVALUATE

Go over your solution; step back from the paperwork.
Are the units, size and direction right?
Does it make physical sense?

But what if... the method needs quantities to work with. What do "how much" and "which way" mean exactly? → **magnitude and direction**.

Given: the values from the question, with units, and the unknown.

Sketch: a diagram with the axes, angles and known vectors.

IDENTIFY: the target, and the physics (which rule).

SET UP: axes, assumptions, your *prediction*, and the equation *in symbols*.

EXECUTE: *substitute* with units on its own line; then **one step per line**; a boxed answer.

EVALUATE: units, sign, size, direction, a limiting case or an independent check.

A short model

Given: $A = 10.0\,\text{m}$, $\theta = 30.0^\circ$ (from $+x$).
Equation (6): $A_x = A\cos\theta$
Substitute: $A_x = (10.0\,\text{m})(\cos 30.0^\circ)$
Solve: $A_x = (10.0\,\text{m})(0.8660)$
$\boxed{A_x = 8.66\,\text{m}}$
Evaluate: positive, and less than A, as predicted.

Algebra between the substitution and the answer may be skipped on a slide; the lines above never are.

Contact 1: Understand

Why do we need vectors?

Magnitude and direction





Magnitude: how much?

Define: the **size** of a quantity: a number with units, such as $5\,\mathrm{m}$, $70\,\mathrm{kg}$, $15\,\mathrm{m/s}$. Never negative. A bag is $5\,\mathrm{m}$ away: which point?

Direction: which way?

Define: the **orientation** of a quantity relative to a reference: a compass word, or an angle (in degrees or radians) from a reference direction.

Rule: a complete answer to "where?"

State: magnitude *and* direction: $5\,\mathrm{m}$ at $40°$ north of east. **Explain:** magnitude alone fits every point on a circle of radius $5\,\mathrm{m}$; the direction picks one.

But what if... do all quantities need a direction? Mass is $70\,\mathrm{kg}$ whichever way you face. Some need both, some only a size: **scalars and vectors**.

Scalar

State (Young): a scalar quantity is **described completely by a numerical value and appropriate units**, where applicable.

Define: scalars may or may not have units (a count has none; mass has kg). They combine by ordinary arithmetic. e.g. mass, time, temperature, distance, speed, energy.

Vector

State (Young): a vector quantity **requires both magnitude and direction**.

Define: the magnitude (a scalar, in the units of the quantity) and the direction (from a reference direction). Vectors combine by the rules of vector addition. e.g. displacement, velocity, acceleration, force.

Explain: keep these distinct

The magnitude of a vector is a **scalar** and is **never negative**. A vector is not described by a single number: "$15\,\mathrm{m/s}$" is a speed; "$15\,\mathrm{m/s}$ north" is a velocity.

Notation: vector and magnitude

$$\vec{\boldsymbol{A}} = \text{the vector}$$

$$A = |\vec{\boldsymbol{A}}| = \text{magnitude of the vector}$$

Define: a vector is printed bold with an arrow ($\vec{\boldsymbol{A}}$) and handwritten with an arrow ($\vec{A}$). A is its magnitude, a non-negative number in the units of the quantity.

Convention used all week

In $\vec{\boldsymbol{A}} \cdot \vec{\boldsymbol{B}} = AB\cos\phi$, A and B are magnitudes.
A_x is a **number**; $A_x\hat{\boldsymbol{\imath}}$ is a **vector**.

Explain: the arrow says "this is a vector"; dropping it, as in A, means "only the size". Mixing the two is the commonest notation error in this course.

Concept check: scalar or vector?

PRACTICE

Decide for each, then compare with your neighbour

(a) $15\,\mathrm{m/s}$
(b) $15\,\mathrm{m/s}$ north
(c) distance walked, $3\,\mathrm{km}$
(d) displacement, $3\,\mathrm{km}$ east
(e) temperature, $30^{\circ}\mathrm{C}$
(f) a force of $20\,\mathrm{N}$ downwards
(g) $-5\,\mathrm{J}$ of energy
(h) mass, $70\,\mathrm{kg}$

Concept check: scalar or vector?

PRACTICE

Decide for each, then compare with your neighbour

(a) $15\,\mathrm{m/s}$
(b) $15\,\mathrm{m/s}$ north
(c) distance walked, $3\,\mathrm{km}$
(d) displacement, $3\,\mathrm{km}$ east
(e) temperature, $30^{\circ}\mathrm{C}$
(f) a force of $20\,\mathrm{N}$ downwards
(g) $-5\,\mathrm{J}$ of energy
(h) mass, $70\,\mathrm{kg}$

Answers

Scalars: (a) speed, (c) distance, (e), (g), (h). Vectors: (b) velocity, (d) displacement, (f) force. **A negative number is not automatically a vector:** $-5\,\mathrm{J}$ is a scalar.

Concept check: scalar or vector?

PRACTICE

Decide for each, then compare with your neighbour

(a) $15\,\mathrm{m/s}$
(b) $15\,\mathrm{m/s}$ north
(c) distance walked, $3\,\mathrm{km}$
(d) displacement, $3\,\mathrm{km}$ east
(e) temperature, $30^{\circ}\mathrm{C}$
(f) a force of $20\,\mathrm{N}$ downwards
(g) $-5\,\mathrm{J}$ of energy
(h) mass, $70\,\mathrm{kg}$

Answers

Scalars: (a) speed, (c) distance, (e), (g), (h). Vectors: (b) velocity, (d) displacement, (f) force. **A negative number is not automatically a vector:** $-5\,\mathrm{J}$ is a scalar.


Which one needs a direction?

A trotro driver says "I am $3\,\mathrm{km}$ from Madina". Is that enough to find the trotro? What is missing? **Distance** is a scalar; **displacement** is a vector (next slide).

But what if... how do we describe a change of position as a vector? → **displacement**.

Displacement: a vector from start to finish

CORE



Rule: displacement (Young)

State: the displacement of a body is the vector from its initial position P_1 to its final position P_2. It depends only on P_1 and P_2, **not on the path taken**.

Define: magnitude: the straight-line distance P_1P_2, in metres; direction: from P_1 towards P_2.
Explain: the distance travelled is the path length, a scalar that can only grow; displacement is zero for a round trip.


Predict

You walk once round a $400\,\mathrm{m}$ track and stop where you started. What is the distance? What is the displacement?

But what if... how do we name, draw and compare vectors? → **representing a vector**.

Displacement: a vector from start to finish

CORE



Rule: displacement (Young)

State: the displacement of a body is the vector from its initial position P_1 to its final position P_2. It depends only on P_1 and P_2, **not on the path taken**.


Define: magnitude: the straight-line distance P_1P_2, in metres; direction: from P_1 towards P_2.
Explain: the distance travelled is the path length, a scalar that can only grow; displacement is zero for a round trip.

Predict

You walk once round a $400\,\mathrm{m}$ track and stop where you started. What is the distance? What is the displacement? **Distance $400\,\mathrm{m}$; displacement $\vec{0}$.**

But what if... how do we name, draw and compare vectors? → **representing a vector**.

Representing a vector



Rule: equal and opposite vectors

State: two vectors are **equal** if they have the same magnitude and the same direction, wherever they are drawn; only magnitude and direction matter.
$-\vec{\boldsymbol{A}}$ has the same magnitude as $\vec{\boldsymbol{A}}$ and the opposite direction.

Rule: multiplying by a scalar

$c\vec{\boldsymbol{A}}$ has magnitude $|c|A$.
$c > 0$: the direction is unchanged ($2\vec{\boldsymbol{A}}$).
$c < 0$: the direction is reversed ($-\vec{\boldsymbol{A}}$, $-2\vec{\boldsymbol{A}}$).

Define: a vector is drawn as an arrow (a ray): its length is the magnitude. **Explain:** antiparallel vectors of equal size are negatives of each other.

But what if... two displacements follow one another, as in the opening problem. What single displacement results? → **graphical addition**.

Predict first

If $\vec{A}$ and $\vec{B}$ are swapped, does the resultant change?



(a) $\vec{A}$ first, then $\vec{B}$ (b) $\vec{B}$ first, then $\vec{A}$ (c) tails together

Adding two vectors: three equivalent ways

Predict first

If $\vec{A}$ and $\vec{B}$ are swapped, does the resultant change?



Rule: head to tail, (a) and (b)

State: put the tail of the second vector at the head of the first. The resultant $\vec{R}$ runs from the first tail to the last head. $\vec{A} + \vec{B} = \vec{B} + \vec{A}$ (commutative).

Rule: parallelogram, (c)


State: draw both tails at one point. $\vec{R}$ is the *diagonal* from that point of the parallelogram built on $\vec{A}$ and $\vec{B}$.


Define: the **resultant** $\vec{R} = \vec{A} + \vec{B}$ is the single vector with the same effect as $\vec{A}$ then $\vec{B}$. **Explain:** the three constructions give the same $\vec{R}$.

But what if... three vectors, not two? Does the grouping matter?

Three or more vectors: the order does not matter

CORE





Rule: associative law


State: $(\vec{A}+\vec{B})+\vec{C}=\vec{A}+(\vec{B}+\vec{C})=\vec{B}+(\vec{A}+\vec{C})$: group or order the vectors in any way and the resultant $\vec{R}$ has the same magnitude and direction.


Define: $\vec{R}$ is the resultant of all three, from the first tail to the last head. **Explain:** add two, then add the third to that sum; every route ends at the same head. (A numerical check follows in Contact 2.)

But what if... we want to undo an addition? First, how big is $\vec{R}$ in the simplest case, along one line.

Predict first: sketch $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ east, and $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ west. Predict each resultant.

Predict first: sketch $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ east, and $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ west. Predict each resultant.







Rules: parallel, antiparallel, and the bounds on R

(1) Parallel: $|\vec{\boldsymbol{R}}| = A + B$, the largest. **Antiparallel:** $|\vec{\boldsymbol{R}}| = |A - B|$, along the *larger* vector, the smallest. In general $|A - B| \leq |\vec{\boldsymbol{A}} + \vec{\boldsymbol{B}}| \leq A + B$: for $3\,\mathrm{m}$ and $4\,\mathrm{m}$, $1\,\mathrm{m} \leq R \leq 7\,\mathrm{m}$. **Magnitudes do not simply add.**

Predict first: sketch $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ east, and $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ west. Predict each resultant.





Rules: parallel, antiparallel, and the bounds on R


(1) Parallel: $|\vec{\boldsymbol{R}}| = A + B$, the largest. **Antiparallel:** $|\vec{\boldsymbol{R}}| = |A - B|$, along the *larger* vector, the smallest. In general $|A - B| \leq |\vec{\boldsymbol{A}} + \vec{\boldsymbol{B}}| \leq A + B$: for $3\,\mathrm{m}$ and $4\,\mathrm{m}$, $1\,\mathrm{m} \leq R \leq 7\,\mathrm{m}$. **Magnitudes do not simply add.**


Your turn

Aayalolo mate walks $4.5\,\mathrm{km}$ east, then (i) $1.5\,\mathrm{km}$ east, (ii) $6.0\,\mathrm{km}$ west. Predict, then find $\vec{\boldsymbol{R}}$.

But what if... we want to undo an addition? $\rightarrow$ **subtraction**.

Predict first: sketch $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ east, and $5\,\mathrm{m}$ east then $3\,\mathrm{m}$ west. Predict each resultant.





Rules: parallel, antiparallel, and the bounds on R

(1) Parallel: $|\vec{\boldsymbol{R}}| = A + B$, the largest. **Antiparallel:** $|\vec{\boldsymbol{R}}| = |A - B|$, along the *larger* vector, the smallest. In general $|A - B| \leq |\vec{\boldsymbol{A}} + \vec{\boldsymbol{B}}| \leq A + B$: for $3\,\mathrm{m}$ and $4\,\mathrm{m}$, $1\,\mathrm{m} \leq R \leq 7\,\mathrm{m}$. **Magnitudes do not simply add.**

Your turn

Aayalolo mate walks $4.5\,\mathrm{km}$ east, then (i) $1.5\,\mathrm{km}$ east, (ii) $6.0\,\mathrm{km}$ west. Predict, then find $\vec{\boldsymbol{R}}$. (i) $6.0\,\mathrm{km}$ east; (ii) $1.5\,\mathrm{km}$ west


But what if... we want to undo an addition? → **subtraction**.

Rule: subtraction

(2) $\vec{A} - \vec{B} = \vec{A} + (-\vec{B})$

Reverse $\vec{B}$, then add head to tail.

Define: $\vec{A} - \vec{B}$ is the vector that, added to $\vec{B}$, gives $\vec{A}$. **Explain:** drawn from a shared tail, it runs from the head of $\vec{B}$ to the head of $\vec{A}$.



Connect: Lecture 2

Change in velocity $\Delta\vec{v} = \vec{v}_2 - \vec{v}_1$, hence acceleration.


But what if... we need numbers, not drawings? A drawing is only as accurate as the ruler. Calculate, starting at $90°$.

Predict first

A student walks $5.0\,\mathrm{m}$ east, then $12\,\mathrm{m}$ north across a courtyard. Is the displacement $17\,\mathrm{m}$? Predict its size and direction.

Predict first

A student walks $5.0\,\mathrm{m}$ east, then $12\,\mathrm{m}$ north across a courtyard. Is the displacement $17\,\mathrm{m}$? Predict its size and direction.




Head to tail, the legs meet at 90°: a **right triangle**.
Prediction: $12 < R < 17\,\mathrm{m}$, leaning north.

Rule: perpendicular vectors

(3) $R = \sqrt{A^2 + B^2}, \quad \theta = \tan^{-1}(B/A)$
Define: A, B the leg magnitudes; R the resultant (the hypotenuse); θ the angle between $\vec{\boldsymbol{R}}$ and $\vec{\boldsymbol{A}}$.

Predict first

A student walks $5.0\,\mathrm{m}$ east, then $12\,\mathrm{m}$ north across a courtyard. Is the displacement $17\,\mathrm{m}$? Predict its size and direction.



Head to tail, the legs meet at 90°: a **right triangle**.
Prediction: $12 < R < 17\,\mathrm{m}$, leaning north.

Rule: perpendicular vectors

(3) $R = \sqrt{A^2 + B^2}, \quad \theta = \tan^{-1}(B/A)$
Define: A, B the leg magnitudes; R the resultant (the hypotenuse); θ the angle between $\vec{\boldsymbol{R}}$ and $\vec{\boldsymbol{A}}$.


$R = \sqrt{5.0^2 + 12^2} = 13\,\mathrm{m}, \quad \theta = \tan^{-1}(12/5.0) = 67^\circ$ north of east. ✓$(12 < 13 < 17)$
Explain: valid *only* at 90°.

But what if... does it work when the legs are not at 90°? First, solve the opening problem.

Example 1 (Young Ex. 1.5)

You leave the Balme Library and walk $1.00\,\mathrm{km}$ north, then $2.00\,\mathrm{km}$ east. Find your final displacement from the start: magnitude and direction.

eg. a walk from the Balme Library, University of Ghana, Legon




Predict first

Is R more or less than $3\,\mathrm{km}$? Closer to north or to east?

Example 1: the opening problem, solution (1): identify and set up

CORE



Key idea

Perpendicular legs make a right triangle: Pythagoras gives the size and the tangent gives the angle.

IDENTIFY

Given: $A = 1.00\,\text{km}$ (north), $B = 2.00\,\text{km}$ (east), legs at $90°$. Find: R and the direction.


SET UP

Head to tail; the legs form a right triangle, so Rule (3): $R = \sqrt{A^2 + B^2}$, $\tan\theta = B/A$ (θ from north).

Prediction: $2 < R < 3\,\text{km}$, closer to east.

Example 1: the opening problem, solution (2): execute and evaluate

CORE



EXECUTE

Write the rule. $R = \sqrt{A^2 + B^2}$

Substitute with units. $R = \sqrt{(1.00\,\text{km})^2 + (2.00\,\text{km})^2}$

Square and add. $R = \sqrt{1.00 + 4.00}\,\text{km} = \sqrt{5.00}\,\text{km}$

Take the root. $\boxed{R = 2.24\,\text{km}}$


Write the angle rule. $\tan\theta = \dfrac{B}{A}$

Substitute. $\tan\theta = \dfrac{2.00\,\text{km}}{1.00\,\text{km}} = 2.00$ (units cancel)

Inverse tangent. $\theta = \tan^{-1}(2.00)$ $\boxed{\theta = 63.4^\circ \text{ east of north}}$

Example 1: the opening problem, solution (2): execute and evaluate

CORE



EXECUTE

Write the rule. $R = \sqrt{A^2 + B^2}$

Substitute with units. $R = \sqrt{(1.00\,\text{km})^2 + (2.00\,\text{km})^2}$

Square and add. $R = \sqrt{1.00 + 4.00}\,\text{km} = \sqrt{5.00}\,\text{km}$

Take the root. $\boxed{R = 2.24\,\text{km}}$


Write the angle rule. $\tan\theta = \dfrac{B}{A}$

Substitute. $\tan\theta = \dfrac{2.00\,\text{km}}{1.00\,\text{km}} = 2.00$ (units cancel)

Inverse tangent. $\theta = \tan^{-1}(2.00)$ $\boxed{\theta = 63.4^\circ \text{ east of north}}$

EVALUATE

Units km; $2 < R < 3\,\text{km}$ and nearer east, as predicted; $R < 1.00 + 2.00$: magnitudes did not add.



side a is opposite angle α, etc.

Rule: cosine rule, find a side

(4) $a^2 = b^2 + c^2 - 2bc\cos\alpha$

For two vectors, $R^2 = A^2 + B^2 - 2AB\cos\gamma$, with γ the internal angle opposite $\vec{\boldsymbol{R}}$.


Rule: sine rule, find an angle

(5) $\dfrac{a}{\sin\alpha} = \dfrac{b}{\sin\beta} = \dfrac{c}{\sin\gamma}$

Define: a, b, c are the sides; α, β, γ the angles opposite them. **Explain:** mathematical tools for any triangle, used here without derivation. If $\alpha = 90°$, (4) becomes Pythagoras (3).

Example 2: a trotro


A trotro travels $3.00\,\mathrm{km}$ east along the main road, then $2.00\,\mathrm{km}$ at 60° north of east along a feeder road. Find the resultant displacement. *Predict first:* is Pythagoras allowed? Is R nearer 5 or $3\,\mathrm{km}$?



eg. a trotro route from Madina Station, Accra

Example 2: a trotro

A trotro travels $3.00\,\mathrm{km}$ east along the main road, then $2.00\,\mathrm{km}$ at 60° north of east along a feeder road. Find the resultant displacement. *Predict first:* is Pythagoras allowed? Is R nearer 5 or $3\,\mathrm{km}$?




eg. a trotro route from Madina Station, Accra

No right angle: the *internal* angle between the legs is $\gamma = 180^\circ - 60^\circ = 120^\circ$. Pythagoras would give $3.61\,\mathrm{km}$, but the second leg alone carries the trotro $2.00\cos 60^\circ = 1.00\,\mathrm{km}$ further east, so $R \geq 4.00\,\mathrm{km}$: $3.61\,\mathrm{km}$ is impossible. Use the cosine rule (4).

But what if... we apply Pythagoras to a leg at 60°? It gives $\sqrt{3.00^2 + 2.00^2} = 3.61\,\mathrm{km}$, yet $R \geq 4.00\,\mathrm{km}$.

Example 2: a trotro, solution (1): identify and set up

CORE



Key idea

The head-to-tail angle between the legs is $120°$, not $60°$, so Pythagoras fails; use the cosine rule with the angle opposite $\vec{R}$.


IDENTIFY

Given: $A = 3.00\,\text{km}$ east, $B = 2.00\,\text{km}$ at $60°$ north of east. Find: R and the direction α above east.

SET UP

Internal angle opposite $\vec{R}$: $\gamma = 180° - 60° = 120°$. Rules (4) then (5).

Prediction: $3 < R < 5\,\text{km}$, small α above east.



EXECUTE

Write the cosine rule (4). $R^2 = A^2 + B^2 - 2AB\cos\gamma$

Substitute with units.

$$R^2 = (3.00\,\text{km})^2 + (2.00\,\text{km})^2 - 2(3.00\,\text{km})(2.00\,\text{km})\cos 120^\circ$$

Evaluate each term ($\cos 120^\circ = -0.500$).


$$R^2 = 9.00 + 4.00 + 6.00\,\text{km}^2$$

Add, then take the root. $R^2 = 19.0\,\text{km}^2$ $\boxed{R = 4.36\,\text{km}}$

Write the sine rule (5). $\dfrac{\sin\alpha}{B} = \dfrac{\sin\gamma}{R}$, so $\sin\alpha = \dfrac{B\sin\gamma}{R}$

Substitute. $\sin\alpha = \dfrac{(2.00\,\text{km})\sin 120^\circ}{4.36\,\text{km}} = 0.397$

Inverse sine. $\boxed{\alpha = 23.4^\circ \text{ north of east}}$



EXECUTE

Write the cosine rule (4). $R^2 = A^2 + B^2 - 2AB\cos\gamma$

Substitute with units.

$R^2 = (3.00\,\text{km})^2 + (2.00\,\text{km})^2 - 2(3.00\,\text{km})(2.00\,\text{km})\cos 120^\circ$

Evaluate each term ($\cos 120^\circ = -0.500$).

$R^2 = 9.00 + 4.00 + 6.00\,\text{km}^2$

Add, then take the root. $R^2 = 19.0\,\text{km}^2$ $\boxed{R = 4.36\,\text{km}}$

Write the sine rule (5). $\dfrac{\sin\alpha}{B} = \dfrac{\sin\gamma}{R}$, so $\sin\alpha = \dfrac{B\sin\gamma}{R}$

Substitute. $\sin\alpha = \dfrac{(2.00\,\text{km})\sin 120^\circ}{4.36\,\text{km}} = 0.397$

Inverse sine. $\boxed{\alpha = 23.4^\circ \text{ north of east}}$

EVALUATE

$3 < R < 5\,\text{km}$ and $R \geq 4.00\,\text{km}$, as predicted; $0 < \alpha < 60^\circ$, matching the sketch.

Question

A delivery rider makes four legs: 2.1 km at 20° N of E, 3.4 km at 35° W of N, 1.8 km S, 2.6 km at 10° S of W. Where does the rider end up?

- Graphical methods give physical understanding . . .
- . . . but scale drawings have limited precision,
- and each extra leg needs another triangle, with its own cosine and sine rule.

The transition to Contact 2

Triangle methods work, but become cumbersome. Components give a systematic numerical method for any number of vectors.

Common mistakes and the correct habit

Mistake	Instead
Giving the magnitude a sign: $\lvert\vec{\boldsymbol{A}}\rvert < 0$.	The magnitude is never negative; the minus sign belongs to the direction.
Adding magnitudes: $\lvert\vec{\boldsymbol{A}} + \vec{\boldsymbol{B}}\rvert = \lvert\vec{\boldsymbol{A}}\rvert + \lvert\vec{\boldsymbol{B}}\rvert$.	Add head to tail; then $\lvert A - B\rvert \leq \lvert\vec{\boldsymbol{A}} + \vec{\boldsymbol{B}}\rvert \leq A + B$.
Calling any negative number a vector ($-5\,\mathrm{J}$).	Ask whether a direction is needed: energy is a scalar.
Using Pythagoras when the angle is not 90°.	Find the internal angle, then the cosine and sine rules.
Reading "30° north of east" from north.	Start from the first named direction and turn toward the second.
Confusing distance with displacement.	Displacement is final minus initial; distance is the path length.

Contact 2: Calculate

How do we calculate with vectors accurately?

Graphs build understanding; components let us calculate

Where we are: we can represent vectors and add them graphically and with triangles. **How do we calculate with any number of vectors, at any angles, accurately?**

Graphical methods

Show what is happening; good for sketches and checks; limited accuracy, awkward for many vectors.

Components


Turn vectors into ordinary numbers; any number of vectors, any accuracy; the same in 3D.

The method of the week

Graphs give geometric understanding; components provide a systematic way to calculate accurately. RESOLVE → COMBINE → RECONSTRUCT: sketch first, predict, calculate, then check.

But what if... we describe a vector by how much of it lies along each axis? What is that "how much"? → **components**.

What is a component?




State. A 2D vector can be built from an x component and a y component. **Define.** A **component** is the part of a vector along one chosen axis: A_x is **how much of $\vec{A}$ lies along x**; A_y, **how much along y**; units of the vector. **Explain.** A projection on the axis; it depends on the axes chosen.

Scalar numbers, not vectors

A_x **is a number** (positive, negative or zero); **the component vector is** $A_x\hat{\boldsymbol{\imath}}$, so $\vec{\boldsymbol{A}} = A_x\hat{\boldsymbol{\imath}} + A_y\hat{\boldsymbol{\jmath}}$.

But what if... we know only the magnitude A and the angle θ? How do we get A_x and A_y? $\rightarrow$ **resolving**.



Rule: resolving (2D)

(6) $A_x = A\cos\theta, \qquad A_y = A\sin\theta$


Apply when θ is from $+x$ toward $+y$.

Define: $A = |\vec{A}|$; θ from $+x$ (degrees); A_x, A_y numbers in the units of $\vec{A}$. **Explain:** A_x is *adjacent* to θ ($\cos\theta = A_x/A$), A_y *opposite* ($\sin\theta = A_y/A$).

Predict first

For $\theta = 150°$, are A_x, A_y positive or negative?

But what if... the vector points left or down, as at $150°$? Then $\cos\theta$ or $\sin\theta$ is negative. → **signs and quadrants**.



Before using equations, ask: does the vector point **right or left**? Does it point **up or down**?

Sign rule

quadrant	I	II	III	IV
A_x	>0	<0	<0	>0
A_y	>0	>0	<0	<0

Permanent rule

Sketch → predict signs → calculate

The calculator never replaces the sketch.


But what if... the angle is given from another axis, such as $37°$ from $+y$ or $45°$ below $+x$? Then $A\cos\theta$ and $A\sin\theta$ swap roles. → **resolving carefully**.

Example 3

A force of $12.0\,\mathrm{N}$ acts on a wooden stool at $\theta = 150^\circ$ (counter-clockwise from $+x$). Find F_x and F_y.


Sketch → predict signs → calculate

Right or left? Up or down? So what signs do you expect?



Example 3: components of a force, solution (1): identify and set up

CORE



Key idea

θ is measured from $+x$, so the signs of $\cos\theta$ and $\sin\theta$ carry the quadrant: sketch first.


IDENTIFY

Given: $F = 12.0\,\text{N}$, $\theta = 150°$ from $+x$. Find: F_x, F_y.

SET UP

Rule (6): $F_x = F\cos\theta, \quad F_y = F\sin\theta.$

Quadrant II, so predict $F_x < 0$, $F_y > 0$, each smaller than $12.0\,\text{N}$.



EXECUTE

Write rule (6) for F_x. $F_x = F\cos\theta$

Substitute with units. $F_x = (12.0\,\mathrm{N})\cos 150^\circ$

Cosine is negative in quadrant II. $F_x = (12.0\,\mathrm{N})(-0.8660)$

$$\boxed{F_x = -10.4\,\mathrm{N}}$$

Write rule (6) for F_y. $F_y = F\sin\theta$


Substitute with units. $F_y = (12.0\,\mathrm{N})\sin 150^\circ$

Sine is positive in quadrant II. $F_y = (12.0\,\mathrm{N})(0.5000)$

$$\boxed{F_y = +6.00\,\mathrm{N}}$$

Example 3: components of a force, solution (2): execute and evaluate

CORE



EXECUTE

Write rule (6) for F_x. $F_x = F\cos\theta$

Substitute with units. $F_x = (12.0\,\text{N})\cos 150^\circ$

Cosine is negative in quadrant II. $F_x = (12.0\,\text{N})(-0.8660)$

$$\boxed{F_x = -10.4\,\text{N}}$$

Write rule (6) for F_y. $F_y = F\sin\theta$

Substitute with units. $F_y = (12.0\,\text{N})\sin 150^\circ$

Sine is positive in quadrant II. $F_y = (12.0\,\text{N})(0.5000)$

$$\boxed{F_y = +6.00\,\text{N}}$$

EVALUATE

Signs and sizes as predicted. Check: $\sqrt{(10.4)^2 + (6.00)^2}\,\text{N} = \sqrt{108 + 36.0}\,\text{N} = 12.0\,\text{N}$, the given magnitude. ✓


Example 4 (Young Ex. 1.6)

Find the x- and y-components of the displacements $\vec{D}$ and $\vec{E}$.

(a) $|\vec{D}| = 3.00\,\mathrm{m}$ of a football; $\alpha = 45.0^\circ$ below $+x$.

(b) $|\vec{E}| = 4.50\,\mathrm{m}$; $\beta = 37.0^\circ$ from the $+y$ axis, with tilted axes.

eg. a football match at the Accra Sports Stadium



Predict first

Name the axis each angle is measured from. Which of $\sin$, $\cos$ goes with which component? Signs?

Sketch → predict signs → calculate.

Example 4: angles measured from other axes, solution

PRACTICE

IDENTIFY and SET UP: rule (6), $A_x = A\cos\theta$, $A_y = A\sin\theta$, holds only for θ from $+x$; otherwise ask: *adjacent* $\to \cos$, *opposite* $\to \sin$. Predict: $D_x > 0$, $D_y < 0$; $E_x > 0$, $E_y > 0$ (tilted axes).

Example 4: angles measured from other axes, solution

PRACTICE

IDENTIFY and SET UP: rule (6), $A_x = A\cos\theta$, $A_y = A\sin\theta$, holds only for θ from $+x$; otherwise ask: *adjacent* $\to$ cos, *opposite* $\to$ sin. Predict: $D_x > 0$, $D_y < 0$; $E_x > 0$, $E_y > 0$ (tilted axes).

(a) Given: $D = 3.00\,\text{m}$, $\alpha = 45.0^\circ$ below $+x$, so $\theta = -45.0^\circ$.

Equation (6): $D_x = D\cos\theta, \quad D_y = D\sin\theta$

Substitute: $D_x = (3.00\,\text{m})\cos(-45.0^\circ)$

$D_y = (3.00\,\text{m})\sin(-45.0^\circ)$

Solve: $D_x = (3.00\,\text{m})(0.7071)$

$\boxed{D_x = +2.12\,\text{m}}$

$D_y = (3.00\,\text{m})(-0.7071) \quad \boxed{D_y = -2.12\,\text{m}}$

(b) Given: $E = 4.50\,\text{m}$, $\beta = 37.0^\circ$ from $+y$.

Equation: E_y is *adjacent* to β, E_x is *opposite*: $E_y = E\cos\beta, \quad E_x = E\sin\beta$

Substitute: $E_x = (4.50\,\text{m})\sin 37.0^\circ$

$E_y = (4.50\,\text{m})\cos 37.0^\circ$

Solve: $E_x = (4.50\,\text{m})(0.6018) \quad \boxed{E_x = +2.71\,\text{m}}$

$E_y = (4.50\,\text{m})(0.7986) \quad \boxed{E_y = +3.59\,\text{m}}$

Example 4: angles measured from other axes, solution

PRACTICE

IDENTIFY and SET UP: rule (6), $A_x = A\cos\theta$, $A_y = A\sin\theta$, holds only for θ from $+x$; otherwise ask: *adjacent* $\to$ cos, *opposite* $\to$ sin. Predict: $D_x > 0$, $D_y < 0$; $E_x > 0$, $E_y > 0$ (tilted axes).

(a) Given: $D = 3.00\,\text{m}$, $\alpha = 45.0^\circ$ below $+x$, so $\theta = -45.0^\circ$.

Equation (6): $D_x = D\cos\theta, \quad D_y = D\sin\theta$

Substitute: $D_x = (3.00\,\text{m})\cos(-45.0^\circ)$

$D_y = (3.00\,\text{m})\sin(-45.0^\circ)$

Solve: $D_x = (3.00\,\text{m})(0.7071)$

$\boxed{D_x = +2.12\,\text{m}}$

$D_y = (3.00\,\text{m})(-0.7071) \quad \boxed{D_y = -2.12\,\text{m}}$

(b) Given: $E = 4.50\,\text{m}$, $\beta = 37.0^\circ$ from $+y$.

Equation: E_y is *adjacent* to β, E_x is *opposite*: $E_y = E\cos\beta, \quad E_x = E\sin\beta$

Substitute: $E_x = (4.50\,\text{m})\sin 37.0^\circ$

$E_y = (4.50\,\text{m})\cos 37.0^\circ$


Solve: $E_x = (4.50\,\text{m})(0.6018) \quad \boxed{E_x = +2.71\,\text{m}}$

$E_y = (4.50\,\text{m})(0.7986) \quad \boxed{E_y = +3.59\,\text{m}}$

EVALUATE: signs as predicted. Check: $\sqrt{2.12^2 + 2.12^2} = 3.00\,\text{m}$ and $\sqrt{2.71^2 + 3.59^2} = 4.50\,\text{m}$, the given magnitudes. ✓ $A\cos\theta$, $A\sin\theta$ **hold only for** θ **from** $+x$.

But what if... given A_x and A_y, find A and θ? A calculator gives the same $\tan^{-1}$ for two vectors that point opposite ways. $\to$ **reconstructing**.

Two equivalent descriptions of one vector




Key idea

Magnitude/direction and components are two equivalent ways of describing the same vector. Going from components back to magnitude and direction is **reconstructing**.

Predict first

$\vec{P} = (-2,\ 2)$ and $\vec{Q} = (2,\ -2)$. Both have $A_y/A_x = -1$, and a calculator gives $\tan^{-1}(-1) = -45°$ for both. Same direction?

Define: $\tan\theta = A_y/A_x$, so $\theta = \tan^{-1}(A_y/A_x)$ is a number the calculator returns between $-90°$ and $+90°$ only. **Explain:** two opposite vectors have the same ratio A_y/A_x, so the ratio alone cannot give the direction.



Rule: reconstructing a vector

(7) Magnitude: $A = \sqrt{A_x^2 + A_y^2}$.
Quadrant: from the signs of A_x, A_y.
Reference angle:
$\theta_{\text{ref}} = \tan^{-1} |A_y/A_x|$.
Direction: I: θ_{ref}; II: $180^\circ - \theta_{\text{ref}}$; III: $180^\circ + \theta_{\text{ref}}$; IV: $360^\circ - \theta_{\text{ref}}$.

CHECK: the direction agrees with the sketch. **Extension:** $\text{atan2}(A_y, A_x)$ builds in both signs; use it after quadrant reasoning. **WATCH OUT:** the same A_y/A_x can mean different directions. **Quadrant first.**

$\vec{\boldsymbol{P}} = (-2, 2)$: left and up, quadrant II.
$\theta_{\text{ref}} = \tan^{-1}(2/2) = 45^\circ$

$$\theta_P = 180^\circ - 45^\circ = \mathbf{135}^\circ$$

Rule: reconstructing a vector

(7) Magnitude: $A = \sqrt{A_x^2 + A_y^2}$.
Quadrant: from the signs of A_x, A_y.
Reference angle:
$\theta_{\text{ref}} = \tan^{-1}|A_y/A_x|$.
Direction: I: θ_{ref}; II: $180^\circ - \theta_{\text{ref}}$; III: $180^\circ + \theta_{\text{ref}}$; IV: $360^\circ - \theta_{\text{ref}}$.

CHECK: the direction agrees with the sketch. **Extension:** $\text{atan2}(A_y, A_x)$ builds in both signs; use it after quadrant reasoning. **WATCH OUT:** the same A_y/A_x can mean different directions. **Quadrant first.**

$\vec{P} = (-2, 2)$: left and up, quadrant II.
$\theta_{\text{ref}} = \tan^{-1}(2/2) = 45^\circ$

$$\theta_P = 180^\circ - 45^\circ = \mathbf{135}^\circ$$

$\vec{Q} = (2, -2)$: right and down, quadrant IV.
$\theta_{\text{ref}} = 45^\circ$

$$\theta_Q = 360^\circ - 45^\circ = \mathbf{315}^\circ \ (= -45^\circ)$$

Rule: reconstructing a vector

(7) Magnitude: $A = \sqrt{A_x^2 + A_y^2}$.
Quadrant: from the signs of A_x, A_y.
Reference angle:
$\theta_{\text{ref}} = \tan^{-1}|A_y/A_x|$.
Direction: I: θ_{ref}; II: $180^\circ - \theta_{\text{ref}}$; III: $180^\circ + \theta_{\text{ref}}$; IV: $360^\circ - \theta_{\text{ref}}$.

CHECK: the direction agrees with the sketch.
Extension: $\text{atan2}(A_y, A_x)$ builds in both signs; use it after quadrant reasoning. **WATCH OUT:** the same A_y/A_x can mean different directions. **Quadrant first.**

$\vec{P} = (-2, 2)$: left and up, quadrant II.
$\theta_{\text{ref}} = \tan^{-1}(2/2) = 45^\circ$

$$\theta_P = 180^\circ - 45^\circ = \mathbf{135}^\circ$$

$\vec{Q} = (2, -2)$: right and down, quadrant IV.
$\theta_{\text{ref}} = 45^\circ$

$$\theta_Q = 360^\circ - 45^\circ = \mathbf{315}^\circ \ (= -45^\circ)$$

Your turn: $A_x = -3.0\,\text{m}$, $A_y = -4.0\,\text{m}$. Find A and θ.

But what if... there are several vectors? How do their components combine? → **adding vectors**.

Rule: reconstructing a vector

(7) Magnitude: $A = \sqrt{A_x^2 + A_y^2}$.
Quadrant: from the signs of A_x, A_y.
Reference angle:
$\theta_{\text{ref}} = \tan^{-1}|A_y/A_x|$.
Direction: I: θ_{ref}; II: $180^\circ - \theta_{\text{ref}}$; III: $180^\circ + \theta_{\text{ref}}$; IV: $360^\circ - \theta_{\text{ref}}$.

CHECK: the direction agrees with the sketch. **Extension:** $\text{atan2}(A_y, A_x)$ builds in both signs; use it after quadrant reasoning. **WATCH OUT:** the same A_y/A_x can mean different directions. **Quadrant first.**

$\vec{P} = (-2, 2)$: left and up, quadrant II.
$\theta_{\text{ref}} = \tan^{-1}(2/2) = 45^\circ$

$$\theta_P = 180^\circ - 45^\circ = \mathbf{135}^\circ$$


$\vec{Q} = (2, -2)$: right and down, quadrant IV.
$\theta_{\text{ref}} = 45^\circ$

$$\theta_Q = 360^\circ - 45^\circ = \mathbf{315}^\circ \ (= -45^\circ)$$

Your turn: $A_x = -3.0\,\text{m}$, $A_y = -4.0\,\text{m}$. Find A and θ. $A = \sqrt{(-3.0)^2 + (-4.0)^2} = 5.0\,\text{m}$; quadrant III; $\theta_{\text{ref}} = \tan^{-1}(4/3) = 53.1^\circ$; $\theta = 180^\circ + 53.1^\circ = 233.1^\circ$ ✓

But what if... there are several vectors? How do their components combine? → **adding vectors**.

Adding vectors with components



Question: how do the components of $\vec{R} = \vec{A} + \vec{B} + \cdots$ relate to theirs?

Rule: adding vectors by components

(8) $$R_x = \sum A_x, \quad R_y = \sum A_y$$

Define: R_x is the sum of all the x-components (in 3D also R_z). **Explain:** components are signed lengths along one axis, so they simply add.

The central skill: RESOLVE → COMBINE → RECONSTRUCT

RESOLVE each vector (a table helps), **COMBINE** like components, **RECONSTRUCT** the magnitude and direction of $\vec{R}$. **Sketch → predict signs → calculate**. **CHECK:** the quadrant agrees with the sketch, and $R \leq$ the sum of the magnitudes.

But what if... the vectors are given as magnitudes and compass directions? → **a multiple-vector problem**.

Example 5 (Young Ex. 1.7)

A student on a campus orienteering run makes three displacements:


$\vec{A}$: $72.4\,\mathrm{m}$, $32.0°$ **east of north**
$\vec{B}$: $57.3\,\mathrm{m}$, $36.0°$ **south of west**
$\vec{C}$: $17.8\,\mathrm{m}$ **south**

Find the resultant $\vec{R}$: magnitude and direction.

eg. the University of Ghana, Legon campus


Predict first

From the sketch: roughly how far, and in which quadrant?



Example 5: three displacements, solution (1): identify and set up

CORE



Key idea

Convert every angle to one measured from $+x$ so that the same Rule (6) works for all three vectors.


IDENTIFY

Given: $A = 72.4\,\text{m}$ (32.0° E of N); $B = 57.3\,\text{m}$ (36.0° S of W); $C = 17.8\,\text{m}$ (S). Find: $\vec{\boldsymbol{R}}$.

SET UP

x east, y north. Angles from $+x$:
$\theta_A = 90.0^\circ - 32.0^\circ = 58.0^\circ$,
$\theta_B = 180.0^\circ + 36.0^\circ = 216.0^\circ$, $\theta_C = 270.0^\circ$.

Rules (6) and (8). Prediction: R much less than the sum of lengths; left and up (quadrant II).




EXECUTE: resolve each vector

Write rule (6). $A_x = A\cos\theta_A$, $A_y = A\sin\theta_A$; same for $\vec{\boldsymbol{B}}$, $\vec{\boldsymbol{C}}$.

Substitute with units, one vector per line.

$$A_x = (72.4\,\text{m})\cos 58.0^\circ = (72.4)(0.5299)\,\text{m} = +38.37\,\text{m}$$
$$A_y = (72.4\,\text{m})\sin 58.0^\circ = (72.4)(0.8480)\,\text{m} = +61.40\,\text{m}$$
$$B_x = (57.3\,\text{m})\cos 216.0^\circ = (57.3)(-0.8090)\,\text{m} = -46.36\,\text{m}$$
$$B_y = (57.3\,\text{m})\sin 216.0^\circ = (57.3)(-0.5878)\,\text{m} = -33.68\,\text{m}$$
$$C_x = (17.8\,\text{m})\cos 270.0^\circ = 0,$$
$$C_y = (17.8\,\text{m})\sin 270.0^\circ = -17.80\,\text{m}$$



Key idea

Components add as signed numbers; the quadrant comes from the signs of R_x, R_y, not from the calculator.

EXECUTE: combine

Write rule (8). $R_x = A_x + B_x + C_x$, $R_y = A_y + B_y + C_y$


Add the x-components. $R_x = 38.37\,\text{m} - 46.36\,\text{m} + 0$

$\boxed{R_x = -7.99\,\text{m}}$

Add the y-components.

$R_y = 61.40\,\text{m} - 33.68\,\text{m} - 17.80\,\text{m}$ $\boxed{R_y = +9.92\,\text{m}}$

Read the quadrant from the signs. $R_x < 0$, $R_y > 0$: quadrant II, as predicted.



EXECUTE: reconstruct

Write rule (7). $R = \sqrt{R_x^2 + R_y^2}, \quad \theta_{\text{ref}} = \tan^{-1} \dfrac{|R_y|}{|R_x|}$

Substitute. $R = \sqrt{(-7.99\,\text{m})^2 + (9.92\,\text{m})^2}$


Square and add. $R = \sqrt{63.8 + 98.4}\,\text{m} = \sqrt{162.2}\,\text{m}$

$\boxed{R = 12.7\,\text{m}}$

Reference angle. $\theta_{\text{ref}} = \tan^{-1} \dfrac{9.92\,\text{m}}{7.99\,\text{m}} = 51.1^\circ$

Direction from $+x$ in quadrant II. $\theta = 180^\circ - 51.1^\circ = 129^\circ$

$\boxed{\text{i.e. } 39^\circ \text{ west of north}}$



EXECUTE: reconstruct

Write rule (7). $R = \sqrt{R_x^2 + R_y^2}, \quad \theta_{\text{ref}} = \tan^{-1} \dfrac{|R_y|}{|R_x|}$

Substitute. $R = \sqrt{(-7.99\,\text{m})^2 + (9.92\,\text{m})^2}$

Square and add. $R = \sqrt{63.8 + 98.4}\,\text{m} = \sqrt{162.2}\,\text{m}$

$\boxed{R = 12.7\,\text{m}}$

Reference angle. $\theta_{\text{ref}} = \tan^{-1} \dfrac{9.92\,\text{m}}{7.99\,\text{m}} = 51.1^\circ$

Direction from $+x$ in quadrant II. $\theta = 180^\circ - 51.1^\circ = 129^\circ$

$\boxed{\text{i.e. } 39^\circ \text{ west of north}}$

EVALUATE


Units m; quadrant II as sketched;
$R = 12.7\,\text{m} \leq 72.4 + 57.3 + 17.8 = 147.5\,\text{m}$, the sum of the magnitudes, because $\vec{\boldsymbol{B}}$ largely cancels $\vec{\boldsymbol{A}}$. ✓

But what if... writing components in words is long? → **unit vectors**.

Unit vectors $\hat{\imath}, \hat{\jmath}, \hat{k}$

State: vectors of magnitude 1, with no units, along the standard directions: $\hat{\imath}$ along $+x$, $\hat{\jmath}$ along $+y$, $\hat{k}$ along $+z$. **Direction only.**

$$\textbf{(9)} \quad \vec{A} = A_x\hat{\imath} + A_y\hat{\jmath} + A_z\hat{k}$$



Define: A_x, A_y, A_z are numbers in the units of $\vec{A}$.
Explain: a compact way to write components *together with their directions*.

Number or vector?


A_x, A_y, A_z are **numbers**; $A_x\hat{\imath}$, $A_y\hat{\jmath}$, $A_z\hat{k}$ are **component vectors**.

Rule: 3D

Right-handed axes: curl the fingers from $+x$ to $+y$, the thumb points along $+z$.

$$A = \sqrt{A_x^2 + A_y^2 + A_z^2}$$

Direction angles in 3D are extended material (supplement).




Example 6 (Young Ex. 1.8)

$\vec{D} = (6.00\hat{\imath} + 3.00\hat{\jmath} - 1.00\hat{k})\,\text{m}$ and $\vec{E} = (4.00\hat{\imath} - 5.00\hat{\jmath} + 8.00\hat{k})\,\text{m}$. Find $\vec{F} = 2\vec{D} - \vec{E}$ and its magnitude.

Key idea

Add or subtract like components; the unit vectors just label the axis, and $|\vec{F}|$ uses all three squared.




Key idea

Add or subtract like components; the unit vectors just label the axis, and $|\vec{F}|$ uses all three squared.

Example 6 (Young Ex. 1.8)

$\vec{D} = (6.00\hat{\imath} + 3.00\hat{\jmath} - 1.00\hat{k})\,\text{m}$ and $\vec{E} = (4.00\hat{\imath} - 5.00\hat{\jmath} + 8.00\hat{k})\,\text{m}$. Find $\vec{F} = 2\vec{D} - \vec{E}$ and its magnitude.

IDENTIFY Given: $\vec{D}$, $\vec{E}$ as above. Find: $\vec{F}$ and F. **SET UP** Collect like terms, Rule (8): $F_x = 2D_x - E_x$, and likewise for y, z; then magnitude in 3D. Predict: $F_y > 0$ since $D_y > 0$ and $E_y < 0$.



EXECUTE

Write the rule. $F_x = 2D_x - E_x$, and likewise for y, z

Substitute x. $F_x = 2(6.00\,\text{m}) - 4.00\,\text{m} = 8.00\,\text{m}$

Substitute y.

$F_y = 2(3.00\,\text{m}) - (-5.00\,\text{m}) = 6.00 + 5.00 = 11.00\,\text{m}$

Substitute z.


$F_z = 2(-1.00\,\text{m}) - 8.00\,\text{m} = -2.00 - 8.00 = -10.00\,\text{m}$

Assemble. $\boxed{\vec{\boldsymbol{F}} = (8.00\hat{\boldsymbol{\imath}} + 11.00\hat{\boldsymbol{\jmath}} - 10.00\hat{\boldsymbol{k}})\,\text{m}}$

Write rule (9). $F = \sqrt{F_x^2 + F_y^2 + F_z^2}$

Square and add. $F = \sqrt{64.0 + 121 + 100}\,\text{m} = \sqrt{285}\,\text{m}$

$\boxed{F = 16.9\,\text{m}}$



EXECUTE

Write the rule. $F_x = 2D_x - E_x$, and likewise for y, z

Substitute x. $F_x = 2(6.00\,\text{m}) - 4.00\,\text{m} = 8.00\,\text{m}$

Substitute y.

$F_y = 2(3.00\,\text{m}) - (-5.00\,\text{m}) = 6.00 + 5.00 = 11.00\,\text{m}$

Substitute z.

$F_z = 2(-1.00\,\text{m}) - 8.00\,\text{m} = -2.00 - 8.00 = -10.00\,\text{m}$

Assemble. $\boxed{\vec{\boldsymbol{F}} = (8.00\hat{\boldsymbol{\imath}} + 11.00\hat{\boldsymbol{\jmath}} - 10.00\hat{\boldsymbol{k}})\,\text{m}}$

Write rule (9). $F = \sqrt{F_x^2 + F_y^2 + F_z^2}$

Square and add. $F = \sqrt{64.0 + 121 + 100}\,\text{m} = \sqrt{285}\,\text{m}$

$\boxed{F = 16.9\,\text{m}}$

EVALUATE $F_y > 0$ as predicted; $3.3\,\text{m} \le F \le 23.8\,\text{m}$ ($|2D| \mp E$). ✓

Your turn: adding three vectors in unit-vector form

Your turn

$\vec{\boldsymbol{A}} = (4\hat{\boldsymbol{\imath}} - 5\hat{\boldsymbol{\jmath}} + 7\hat{\boldsymbol{k}})\,\mathrm{m}$, $\vec{\boldsymbol{B}} = (\hat{\boldsymbol{\imath}} - 3\hat{\boldsymbol{\jmath}} + 5\hat{\boldsymbol{k}})\,\mathrm{m}$, $\vec{\boldsymbol{C}} = (\hat{\boldsymbol{\imath}} + \hat{\boldsymbol{\jmath}} - 2\hat{\boldsymbol{k}})\,\mathrm{m}$. Find $\vec{\boldsymbol{A}} + \vec{\boldsymbol{B}} + \vec{\boldsymbol{C}}$ and its magnitude. Then add in a different order.

Predict first

Which component of the sum is the largest? Does the order of addition matter?

Your turn

$\vec{A} = (4\hat{\imath} - 5\hat{\jmath} + 7\hat{k})\,\mathrm{m}$, $\vec{B} = (\hat{\imath} - 3\hat{\jmath} + 5\hat{k})\,\mathrm{m}$, $\vec{C} = (\hat{\imath} + \hat{\jmath} - 2\hat{k})\,\mathrm{m}$. Find $\vec{A} + \vec{B} + \vec{C}$ and its magnitude. Then add in a different order.


Predict first

Which component of the sum is the largest? Does the order of addition matter?

Substitute: $R_x = 4 + 1 + 1, \quad R_y = -5 - 3 + 1, \quad R_z = 7 + 5 - 2$ (m)

Solve: $\boxed{\vec{R} = (6\hat{\imath} - 7\hat{\jmath} + 10\hat{k})\,\mathrm{m}}$; $\quad R = \sqrt{6^2 + (-7)^2 + 10^2}\,\mathrm{m} = \sqrt{185}\,\mathrm{m} = 13.6\,\mathrm{m}$

Evaluate: the same answer in any order, as the associative law (Contact 1) requires. ✓



Rule: the unit vector of a vector

(10) $\hat{\boldsymbol{A}} = \dfrac{\vec{\boldsymbol{A}}}{A}$ (divide every component by the magnitude), and conversely $\vec{\boldsymbol{A}} = A\,\hat{\boldsymbol{A}}$.


Define: $\hat{\boldsymbol{A}}$ has $|\hat{\boldsymbol{A}}| = 1$, no units, and the same direction as $\vec{\boldsymbol{A}}$; $A = |\vec{\boldsymbol{A}}|$. **Explain:** dividing by a positive scalar changes the length, not the direction; so $\hat{\boldsymbol{A}}$ records the direction alone and A the size.

Predict first

For $\vec{\boldsymbol{A}} = (3.00\hat{\boldsymbol{\imath}} - 2.00\hat{\boldsymbol{\jmath}})\,\mathrm{m}$: are the components of $\hat{\boldsymbol{A}}$ bigger or smaller than 1? Which signs? Which quadrant?

But what if... does the rule give the right numbers? → **a worked example**.

Example 7: the unit vector of a vector




Example 7

$\vec{A} = (3.00\hat{i} - 2.00\hat{j})$ m. Find $\hat{A}$ and verify it.

Key idea

Dividing by A keeps the direction and removes the units, so $|\hat{A}| = 1$.

Example 7: the unit vector of a vector




Example 7

$\vec{\boldsymbol{A}} = (3.00\hat{\boldsymbol{\imath}} - 2.00\hat{\boldsymbol{\jmath}})\,\mathrm{m}$. Find $\hat{\boldsymbol{A}}$ and verify it.

IDENTIFY Given: $A_x = 3.00\,\mathrm{m}$, $A_y = -2.00\,\mathrm{m}$. Find: $\hat{\boldsymbol{A}}$. **SET UP** Rule (10); predict components between -1 and 1, $+$ for x, $-$ for y, quadrant IV.

Key idea

Dividing by A keeps the direction and removes the units, so $|\hat{\boldsymbol{A}}| = 1$.



EXECUTE

Write rule (9). $A = \sqrt{A_x^2 + A_y^2}$

Substitute and add.


$$A = \sqrt{(3.00\,\text{m})^2 + (-2.00\,\text{m})^2} = \sqrt{13.0}\,\text{m} = 3.61\,\text{m}$$

Write rule (10). $\hat{\boldsymbol{A}} = \vec{\boldsymbol{A}}/A$

Divide each component. $\hat{\boldsymbol{A}} = \dfrac{3.00\,\text{m}}{3.61\,\text{m}}\hat{\boldsymbol{\imath}} + \dfrac{-2.00\,\text{m}}{3.61\,\text{m}}\hat{\boldsymbol{\jmath}}$

Evaluate (units cancel). $\boxed{\hat{\boldsymbol{A}} = 0.832\hat{\boldsymbol{\imath}} - 0.555\hat{\boldsymbol{\jmath}}}$

Example 7: solution



EXECUTE

Write rule (9). $A = \sqrt{A_x^2 + A_y^2}$

Substitute and add.

$$A = \sqrt{(3.00\,\text{m})^2 + (-2.00\,\text{m})^2} = \sqrt{13.0}\,\text{m} = 3.61\,\text{m}$$

Write rule (10). $\hat{\boldsymbol{A}} = \vec{\boldsymbol{A}}/A$

Divide each component. $\hat{\boldsymbol{A}} = \dfrac{3.00\,\text{m}}{3.61\,\text{m}}\hat{\boldsymbol{\imath}} + \dfrac{-2.00\,\text{m}}{3.61\,\text{m}}\hat{\boldsymbol{\jmath}}$

Evaluate (units cancel). $\boxed{\hat{\boldsymbol{A}} = 0.832\hat{\boldsymbol{\imath}} - 0.555\hat{\boldsymbol{\jmath}}}$

EVALUATE

$|\hat{\boldsymbol{A}}| = \sqrt{0.832^2 + 0.555^2} = 1.00$ (exactly $\frac{9}{13} + \frac{4}{13} = 1$); the units cancel; $\tan^{-1}(-2/3) = -33.7°$, quadrant IV, as predicted. ✓

Common mistakes and the correct habit

Mistake	Instead
Trusting $\tan^{-1}$ for the direction.	Quadrant first from the signs, then the reference angle.
Using $A\cos\theta$, $A\sin\theta$ when θ is not from $+x$.	Ask adjacent or opposite, and take the signs from the sketch.
Adding magnitudes instead of components.	Resolve, combine, reconstruct.
Calculating before predicting the signs.	Sketch, predict the signs, then calculate.
Mixing scalar components with component vectors.	A_x is a number; $A_x\hat{\boldsymbol{\imath}}$ is the vector.
Calculator in the wrong angle mode.	Check degrees against radians before every trigonometric step.

Lecture 2: motion

Projectile motion: the x- and y-motions are treated separately, using $v_x = v\cos\theta$ and $v_y = v\sin\theta$.

Lecture 3: forces

Newton's second law is applied component by component, $\sum F_x = ma_x$ and $\sum F_y = ma_y$, with axes along and perpendicular to a slope.

Beyond mechanics

Electric and magnetic fields and every other vector quantity are added by components in exactly the same way.

Physical meaning

Resolve, combine, reconstruct is a skill you will use every week of this course.

Contact 3: Extend

How do vector products describe physical quantities?

From combining vectors to constructing quantities

So far, we have used vectors to represent and combine physical quantities. We now ask a new question: **what useful physical quantities can we construct from two vectors?**

From combining vectors to constructing quantities

So far, we have used vectors to represent and combine physical quantities. We now ask a new question: **what useful physical quantities can we construct from two vectors?**

Pulling a crate

How much of the pull acts **along the motion**?

pulling a crate $\rightarrow$ **dot product** $\rightarrow$ *work*

vector $\cdot$ vector $\rightarrow$ **scalar**

Turning a door

The effect depends on where and which way you push, and has an **axis**.


turning a door $\rightarrow$ **cross product** $\rightarrow$ *torque*

vector $\times$ vector $\rightarrow$ **vector**


Vector multiplication is carried out in two ways: the scalar ("dot") product and the vector ("cross") product. We first understand what each product means geometrically, then learn how to calculate it.

Question

How much of one vector lies along the direction of another?



$\vec{A}\cdot\vec{B} = A\,(B\cos\phi)$




$\vec{A}\cdot\vec{B} = B\,(A\cos\phi)$


Define. The part of $\vec{B}$ along $\vec{A}$ is its **projection** $B\cos\phi$; where **for dot and cross products, ϕ is the angle between the vectors when placed tail-to-tail**, $0^\circ \leq \phi \leq 180^\circ$.

Question

How much of one vector lies along the direction of another?



$\vec{A}\cdot\vec{B} = A\,(B\cos\phi)$



$\vec{A}\cdot\vec{B} = B\,(A\cos\phi)$

Define. The part of $\vec{B}$ along $\vec{A}$ is its **projection** $B\cos\phi$; where **for dot and cross products, ϕ is the angle between the vectors when placed tail-to-tail**, $0^\circ \le \phi \le 180^\circ$.


Definition: dot product

$$\textbf{(11)}\quad \vec{A}\cdot\vec{B} = AB\cos\phi$$

Explain. vector · vector → **scalar**; A, B the magnitudes; units multiply: $\mathrm{m}\cdot\mathrm{m} = \mathrm{m}^2$. Equivalently $A(B\cos\phi) = B(A\cos\phi)$: the magnitude of one vector times the component of the other along it.

Sign of the dot product, and which angle is ϕ


CORE



(a) $\phi = 50°$ (b) $\phi = 90°$ (c) $\phi = 140°$

Predict first

For each pair: is $\vec{A} \cdot \vec{B}$ positive, zero, or negative?



(a) $\phi = 50°$ (b) $\phi = 90°$ (c) $\phi = 140°$

Predict first

For each pair: is $\vec{A} \cdot \vec{B}$ positive, zero, or negative?

Rule: sign of the dot product

$$\phi < 90° \Rightarrow \vec{A} \cdot \vec{B} > 0; \qquad \phi = 90° \Rightarrow \vec{A} \cdot \vec{B} = 0; \qquad \phi > 90° \Rightarrow \vec{A} \cdot \vec{B} < 0$$

Which angle?

ϕ **is the angle between the vectors placed tail to tail.** Do not use the internal angle of a head-to-head triangle: for the trotro legs of Example 2, $\phi = 60°$ but $\gamma = 120°$.

Question

What are $\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\imath}}$ and $\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\jmath}}$?

Question

What are $\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\imath}}$ and $\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\jmath}}$?

Rule: unit-vector dot products

$$\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\imath}} = \hat{\boldsymbol{\jmath}} \cdot \hat{\boldsymbol{\jmath}} = \hat{\boldsymbol{k}} \cdot \hat{\boldsymbol{k}} = 1, \qquad \hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\jmath}} = \hat{\boldsymbol{\jmath}} \cdot \hat{\boldsymbol{k}} = \hat{\boldsymbol{k}} \cdot \hat{\boldsymbol{\imath}} = 0$$

Dot product from components

Question

What are $\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\imath}}$ and $\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\jmath}}$?

Rule: unit-vector dot products

$$\hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\imath}} = \hat{\boldsymbol{\jmath}} \cdot \hat{\boldsymbol{\jmath}} = \hat{\boldsymbol{k}} \cdot \hat{\boldsymbol{k}} = 1, \qquad \hat{\boldsymbol{\imath}} \cdot \hat{\boldsymbol{\jmath}} = \hat{\boldsymbol{\jmath}} \cdot \hat{\boldsymbol{k}} = \hat{\boldsymbol{k}} \cdot \hat{\boldsymbol{\imath}} = 0$$

Expanding the product of the two component sums, only like terms survive:

Rule: dot product from components

(12) $\vec{\boldsymbol{A}} \cdot \vec{\boldsymbol{B}} = A_x B_x + A_y B_y + A_z B_z$

Define: $A_x, \ldots, B_z$ are components. **Explain:** (11) uses angles, (12) uses components; both give one scalar.

Connect: work, Lecture 4


$W = \vec{\boldsymbol{F}} \cdot \vec{\boldsymbol{s}}$: a constant force $\vec{\boldsymbol{F}}$ acting through a displacement $\vec{\boldsymbol{s}}$. Studied fully in Lecture 4.


Example 8 (after Young Ex. 1.9)

$|\vec{A}| = 7.50\,\mathrm{m}$ at $53.0°$ and $|\vec{B}| = 5.00\,\mathrm{m}$ at $130.0°$, both from $+x$. Find $\vec{A} \cdot \vec{B}$.

Predict first

Is ϕ less than or more than $90°$? So what sign? Larger or smaller than $AB = 37.5\,\mathrm{m}^2$?





Key idea

ϕ is measured tail to tail; its size sets the sign of $\vec{A} \cdot \vec{B}$.

IDENTIFY


Given: $A = 7.50\,\text{m}$ at $53.0°$; $B = 5.00\,\text{m}$ at $130.0°$. Find: $\vec{A} \cdot \vec{B}$.

SET UP

Rule (11): $\vec{A} \cdot \vec{B} = AB\cos\phi$. Tail-to-tail angle: $\phi = 130.0° - 53.0° = 77.0°$.

Prediction: $\phi < 90°$, so positive, and below $AB = 37.5\,\text{m}^2$.

PRACTICE



EXECUTE


Write rule (11). $\vec{A} \cdot \vec{B} = AB \cos\phi$

Substitute with units. $\vec{A} \cdot \vec{B} = (7.50\,\mathrm{m})(5.00\,\mathrm{m}) \cos 77.0^\circ$

Multiply the magnitudes. $\vec{A} \cdot \vec{B} = (37.5\,\mathrm{m}^2) \cos 77.0^\circ$

Evaluate the cosine. $\vec{A} \cdot \vec{B} = (37.5\,\mathrm{m}^2)(0.2250)$

$$\boxed{\vec{A} \cdot \vec{B} = 8.44\,\mathrm{m}^2}$$



EXECUTE

Write rule (11). $\vec{A} \cdot \vec{B} = AB\cos\phi$

Substitute with units. $\vec{A} \cdot \vec{B} = (7.50\,\mathrm{m})(5.00\,\mathrm{m})\cos 77.0^\circ$

Multiply the magnitudes. $\vec{A} \cdot \vec{B} = (37.5\,\mathrm{m}^2)\cos 77.0^\circ$

Evaluate the cosine. $\vec{A} \cdot \vec{B} = (37.5\,\mathrm{m}^2)(0.2250)$

$$\boxed{\vec{A} \cdot \vec{B} = 8.44\,\mathrm{m}^2}$$

EVALUATE

Positive since $\phi < 90^\circ$, and less than $37.5\,\mathrm{m}^2$, as predicted; units are m^2 (a product of units), not m.


Reuse: ϕ is a tail-to-tail angle, not an internal triangle angle.

Example 9


Two vectors are given by $\vec{A} = \hat{i} + 9\hat{j} + 2\hat{k}$ and $\vec{B} = -5\hat{i} + \hat{j} - \hat{k}$. Find $\vec{A} \cdot \vec{B}$ and the angle ϕ between them.

Predict first

$\vec{A}$ points mostly along $+y$, $\vec{B}$ mostly along $-x$. Predict: is ϕ near 0°, 90° or 180°?



schematic: tail to tail, ϕ is close to 90°



schematic: tail to tail, ϕ is close to 90°

Key idea

Rule (11) solved for $\cos\phi$ turns two vectors into an angle.


IDENTIFY

Given: $\vec{\boldsymbol{A}} = (1,\ 9,\ 2)$, $\vec{\boldsymbol{B}} = (-5,\ 1,\ -1)$. Find: $\vec{\boldsymbol{A}} \cdot \vec{\boldsymbol{B}}$ and the angle ϕ.

SET UP

Rule (12): $\vec{\boldsymbol{A}} \cdot \vec{\boldsymbol{B}} = A_x B_x + A_y B_y + A_z B_z$. Rule (11) solved for the angle: $\cos\phi = \dfrac{\vec{\boldsymbol{A}} \cdot \vec{\boldsymbol{B}}}{AB}$.

Prediction: ϕ near 90° ($\vec{\boldsymbol{A}}$ mostly $+y$, $\vec{\boldsymbol{B}}$ mostly $-x$).



schematic: tail to tail, ϕ is close to 90°

Key idea

Rule (11) solved for $\cos\phi$ turns two vectors into an angle.

IDENTIFY

Given: $\vec{A} = (1, 9, 2)$, $\vec{B} = (-5, 1, -1)$. Find: $\vec{A} \cdot \vec{B}$ and the angle ϕ.

SET UP

Rule (12): $\vec{A} \cdot \vec{B} = A_x B_x + A_y B_y + A_z B_z$. Rule (11) solved for the angle: $\cos\phi = \dfrac{\vec{A} \cdot \vec{B}}{AB}$.

Prediction: ϕ near 90° ($\vec{A}$ mostly $+y$, $\vec{B}$ mostly $-x$).


EXECUTE: the dot product

Write rule (12). $\vec{A} \cdot \vec{B} = A_x B_x + A_y B_y + A_z B_z$

Substitute the components.

$= (1)(-5) + (9)(1) + (2)(-1)$

Multiply each pair, then add. $= -5 + 9 - 2$ $\boxed{\vec{A} \cdot \vec{B} = 2}$



schematic: tail to tail,
ϕ is close to $90°$

EXECUTE: the magnitudes

Write rule (9). $A = \sqrt{A_x^2 + A_y^2 + A_z^2}$

Substitute and add. $A = \sqrt{1^2 + 9^2 + 2^2} = \sqrt{86}$


$A = 9.27$

Same for $\vec{B}$. $B = \sqrt{(-5)^2 + 1^2 + (-1)^2} = \sqrt{27}$

$B = 5.20$

Key idea

A small $\cos\phi$ means ϕ is just under $90°$, as predicted.




EXECUTE: the angle

Write the rule. $\cos\phi = \dfrac{\vec{A}\cdot\vec{B}}{AB}$

Substitute. $\cos\phi = \dfrac{2}{(9.27)(5.20)} = \dfrac{2}{48.2} = 0.0415$

Inverse cosine. $\phi = \cos^{-1}(0.0415)$ $\boxed{\phi = 87.6^\circ}$



EXECUTE: the angle

Write the rule. $\cos\phi = \dfrac{\vec{A}\cdot\vec{B}}{AB}$

Substitute. $\cos\phi = \dfrac{2}{(9.27)(5.20)} = \dfrac{2}{48.2} = 0.0415$

Inverse cosine. $\phi = \cos^{-1}(0.0415)$ $\boxed{\phi = 87.6^\circ}$

EVALUATE

A small positive dot product gives an angle just under 90°, as predicted.

Independent check in Example 11: $|\vec{A}\times\vec{B}| = AB\sin\phi$.

Reuse: magnitude (9), dot product (11) and (12).

But what if... a push perpendicular to a door's lever arm gives $\vec{r}\cdot\vec{F} = 0$, yet turns it most? $\rightarrow$ **cross product**.

Question

How can two vectors produce a *third* vector?


Question

How can two vectors produce a *third* vector?

Definition: cross product

- **(13)** Magnitude: $|\vec{A} \times \vec{B}| = AB \sin \phi$ (area of the parallelogram)
- Direction: perpendicular to the plane of $\vec{A}$ and $\vec{B}$, given by the **right-hand rule**

Define: ϕ the tail-to-tail angle, $0° \leq \phi \leq 180°$; the result is a **vector**, in the product of the units. **Explain:** zero for parallel vectors, largest for perpendicular ones. Right-hand rule: next slide.



Right-hand rule


For $\vec{A} \times \vec{B}$:

1. Place $\vec{A}$ and $\vec{B}$ tail to tail.
2. Point the fingers of the right hand along $\vec{A}$.
3. Curl the fingers toward $\vec{B}$ through the smaller angle.
4. The thumb gives the direction of $\vec{A} \times \vec{B}$.

Order matters

$\vec{A} \times \vec{B} = -(\vec{B} \times \vec{A})$. Swapping the vectors reverses the direction (same magnitude).

Special cases: parallel or antiparallel ($\phi = 0°, 180°$): $\vec{A} \times \vec{B} = \vec{0}$, in particular $\vec{A} \times \vec{A} = \vec{0}$. Perpendicular: $|\vec{A} \times \vec{B}| = AB$, the largest possible.



Rule: unit-vector cross products

Cyclic order $\hat{\imath} \to \hat{\jmath} \to \hat{k} \to \hat{\imath}$ gives $+$; reversed order gives $-$:

$\hat{\imath} \times \hat{\jmath} = \hat{k}, \quad \hat{\jmath} \times \hat{k} = \hat{\imath}, \quad \hat{k} \times \hat{\imath} = \hat{\jmath}$

$\hat{\jmath} \times \hat{\imath} = -\hat{k}, \quad \hat{k} \times \hat{\jmath} = -\hat{\imath}, \quad \hat{\imath} \times \hat{k} = -\hat{\jmath}$

$\hat{\imath} \times \hat{\imath} = \hat{\jmath} \times \hat{\jmath} = \hat{k} \times \hat{k} = \vec{\mathbf{0}}$


Explain: each unit vector is perpendicular to the others, so $\sin\phi = 1$ for unlike pairs and 0 for like pairs; the sign comes from the right-hand rule.

Rule: cross product from components

$$\textbf{(14)} \quad \vec{A} \times \vec{B} = \begin{vmatrix} \hat{\imath} & \hat{\jmath} & \hat{k} \\ A_x & A_y & A_z \\ B_x & B_y & B_z \end{vmatrix}$$

$$\begin{aligned} =&(A_y B_z - A_z B_y)\hat{\imath} \\ &+ (A_z B_x - A_x B_z)\hat{\jmath} \\ &+ (A_x B_y - A_y B_x)\hat{k} \end{aligned}$$

Define: the determinant is a memory aid: expand along the top row; the $\hat{\jmath}$ term carries a minus sign, which is why $(A_z B_x - A_x B_z)$ is written reversed.
Explain: (14) follows from the table on the left.




Key idea

The thumb points where the fingers curl from $\vec{A}$ to $\vec{B}$; $\sin\phi < 1$ keeps $|\vec{A} \times \vec{B}| < AB$.

Example 10 (Young Ex. 1.11)

$\vec{A}$ has magnitude 6 units and points along $+x$. $\vec{B}$ has magnitude 4 units and lies in the xy-plane at $30°$ to $+x$. Find $\vec{A} \times \vec{B}$. *Predict: which way will it point?*



Key idea


The thumb points where the fingers curl from $\vec{A}$ to $\vec{B}$; $\sin\phi < 1$ keeps $|\vec{A} \times \vec{B}| < AB$.

Example 10 (Young Ex. 1.11)

$\vec{A}$ has magnitude 6 units and points along $+x$. $\vec{B}$ has magnitude 4 units and lies in the xy-plane at $30°$ to $+x$. Find $\vec{A} \times \vec{B}$. *Predict: which way will it point?*

IDENTIFY Given: $A = 6$, $B = 4$, $\phi = 30°$. Find: $|\vec{A} \times \vec{B}|$ and its direction. **SET UP** Rule (13); right-hand rule, fingers along $\vec{A}$ ($+x$), curl towards $\vec{B}$ (towards $+y$): predict $+z$.

Example 10: solution



EXECUTE


Write rule (13). $|\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}}| = AB \sin \phi$

Substitute. $|\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}}| = (6)(4) \sin 30^\circ$

Evaluate. $= (24)(0.500) = 12$

Direction by the right-hand rule. fingers along $+x$, curl toward $+y$, thumb along $+z$

Result. $\boxed{\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}} = 12\,\hat{\boldsymbol{k}}}$



EXECUTE

Write rule (13). $|\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}}| = AB \sin\phi$


Substitute. $|\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}}| = (6)(4) \sin 30^\circ$

Evaluate. $= (24)(0.500) = 12$

Direction by the right-hand rule. fingers along $+x$, curl toward $+y$, thumb along $+z$

Result. $\boxed{\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}} = 12\,\hat{\boldsymbol{k}}}$

EVALUATE Check by components: $\vec{\boldsymbol{A}} = 6\hat{\boldsymbol{\imath}}$, $\vec{\boldsymbol{B}} = 3.46\hat{\boldsymbol{\imath}} + 2\hat{\boldsymbol{\jmath}}$; the $\hat{\boldsymbol{k}}$ term of (14): $A_x B_y - A_y B_x = (6)(2) - (0)(3.46) = 12$. ✓
$12 < AB = 24$, as $\sin 30^\circ < 1$.




Example 11

$\vec{A} = \hat{\imath} + 9\hat{\jmath} + 2\hat{k}$ and $\vec{B} = -5\hat{\imath} + \hat{\jmath} - \hat{k}$. Find $\vec{A} \times \vec{B}$, and check it is perpendicular to both. *Predict: the largest possible magnitude is* $AB = 48.1$.

Key idea

$\vec{A} \times \vec{B}$ is perpendicular to both inputs, so its dot product with each is zero: an independent check.




Key idea

$\vec{A} \times \vec{B}$ is perpendicular to both inputs, so its dot product with each is zero: an independent check.

Example 11

$\vec{A} = \hat{\imath} + 9\hat{\jmath} + 2\hat{k}$ and $\vec{B} = -5\hat{\imath} + \hat{\jmath} - \hat{k}$. Find $\vec{A} \times \vec{B}$, and check it is perpendicular to both. *Predict: the largest possible magnitude is* $AB = 48.1$.

IDENTIFY Given: $\vec{A} = (1, 9, 2)$, $\vec{B} = (-5, 1, -1)$. **SET UP** Rule (14), component by component.



EXECUTE

Write rule (14), one component per line.


$$\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}} = (A_y B_z - A_z B_y)\hat{\boldsymbol{\imath}} + (A_z B_x - A_x B_z)\hat{\boldsymbol{\jmath}} + (A_x B_y - A_y B_x)\hat{\boldsymbol{k}}$$

x: $A_y B_z - A_z B_y = (9)(-1) - (2)(1) = -9 - 2 = -11$

y: $A_z B_x - A_x B_z = (2)(-5) - (1)(-1) = -10 + 1 = -9$

z: $A_x B_y - A_y B_x = (1)(1) - (9)(-5) = 1 + 45 = 46$

Assemble. $\boxed{\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}} = -11\hat{\boldsymbol{\imath}} - 9\hat{\boldsymbol{\jmath}} + 46\hat{\boldsymbol{k}}}$



EXECUTE

Write rule (14), one component per line.

$\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}} = (A_y B_z - A_z B_y)\hat{\boldsymbol{\imath}} + (A_z B_x - A_x B_z)\hat{\boldsymbol{\jmath}} + (A_x B_y - A_y B_x)\hat{\boldsymbol{k}}$

x: $A_y B_z - A_z B_y = (9)(-1) - (2)(1) = -9 - 2 = -11$

y: $A_z B_x - A_x B_z = (2)(-5) - (1)(-1) = -10 + 1 = -9$

z: $A_x B_y - A_y B_x = (1)(1) - (9)(-5) = 1 + 45 = 46$

Assemble. $\boxed{\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}} = -11\hat{\boldsymbol{\imath}} - 9\hat{\boldsymbol{\jmath}} + 46\hat{\boldsymbol{k}}}$

EVALUATE

$(\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}}) \cdot \vec{\boldsymbol{A}} = (-11)(1) + (-9)(9) + (46)(2) = 0,$

$(\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}}) \cdot \vec{\boldsymbol{B}} = (-11)(-5) + (-9)(1) + (46)(-1) = 0.$ ✓

Size: $\sqrt{121 + 81 + 2116} = 48.1 = AB \sin\phi$, $\phi = 87.6°$ (Example 9). ✓

Dot product and cross product compared

Dot product

$$\vec{A} \cdot \vec{B} = AB \cos \phi$$

- Result: a **scalar**
- Zero when the vectors are perpendicular
- Maximum magnitude when the vectors are parallel or antiparallel

Cross product

$$|\vec{A} \times \vec{B}| = AB \sin \phi$$

- Result: a **vector**
- Zero when the vectors are parallel or antiparallel
- Maximum magnitude when the vectors are perpendicular

The angle ϕ in both products

ϕ is **the angle between the vectors when placed tail-to-tail**, $0° \leq \phi \leq 180°$. **Do not use the internal angle of a head-to-tail vector triangle as** ϕ, such as the $\gamma = 120°$ in the trotro problem.

Connect: torque, Lecture 8 (CORE)

$\vec{\tau} = \vec{r} \times \vec{F}$, with $|\vec{\tau}| = rF\sin\phi$: a force $\vec{F}$ applied at position $\vec{r}$ from a pivot. The direction comes from the right-hand rule; the order matters; $\tau = 0$ if $\vec{F} \parallel \vec{r}$ and is largest if $\vec{F} \perp \vec{r}$.

Practice example: a spanner

A spanner is pivoted at one end; $F = 30\,\mathrm{N}$ acts at $r = 0.50\,\mathrm{m}$ from the pivot at $60°$ to $\vec{r}$ (in the page). **Predict:** is τ larger or smaller than $rF = 15\,\mathrm{N\,m}$?

eg. a mechanic at Suame Magazine, Kumasi

But what if... a problem uses several of these ideas at once: adding, resolving, dot and cross products? Which tool, and when? → **integrated applications**.

Connect: torque, Lecture 8 (CORE)

$\vec{\tau} = \vec{r} \times \vec{F}$, with $|\vec{\tau}| = rF\sin\phi$: a force $\vec{F}$ applied at position $\vec{r}$ from a pivot. The direction comes from the right-hand rule; the order matters; $\tau = 0$ if $\vec{F} \parallel \vec{r}$ and is largest if $\vec{F} \perp \vec{r}$.

Practice example: a spanner

A spanner is pivoted at one end; $F = 30\,\mathrm{N}$ acts at $r = 0.50\,\mathrm{m}$ from the pivot at $60°$ to $\vec{r}$ (in the page). **Predict:** is τ larger or smaller than $rF = 15\,\mathrm{N\,m}$?
$\tau = rF\sin\phi = (0.50)(30)\sin 60° = 13.0\,\mathrm{N\,m}$, less than 15; thumb out of the page, $+z$. ✓

eg. a mechanic at Suame Magazine, Kumasi

But what if... a problem uses several of these ideas at once: adding, resolving, dot and cross products? Which tool, and when? → **integrated applications**.


Example 12: integrated application

A porter pulls a crate of tomatoes across a level concrete floor with a rope. The rope force is $50.0\,\mathrm{N}$ at 30.0° north of east. The crate moves $3.00\,\mathrm{m}$ east, then $4.00\,\mathrm{m}$ north.

(a) Find the crate's displacement $\vec{s}$.
(b) Find the work done by the rope force, $W = \vec{F} \cdot \vec{s}$.
(c) The same force acts at $\vec{r} = (0.800\hat{i} + 0.600\hat{j})\,\mathrm{m}$ from a pivot. Find the torque $\vec{\tau} = \vec{r} \times \vec{F}$.


Predict first

Sketch first. Which vector tool does each part need, and why? Is $W > 0$? Does $\vec{\tau}$ point along $+z$ or $-z$?



top view; $F = 50.0$ N; z points out of the page

eg. goods moved at Makola Market, Accra



top view; $F = 50.0$ N; z points out of the page

Key idea

Adding vectors uses components; a scalar from two vectors is the dot product, a vector is the cross product.


IDENTIFY

Given: $F = 50.0\,\mathrm{N}$ at 30.0° N of E; legs $3.00\,\mathrm{m}$ E and $4.00\,\mathrm{m}$ N; $\vec{r} = (0.800\hat{\imath} + 0.600\hat{\jmath})\,\mathrm{m}$. Find: $\vec{s}$, W, $\vec{\tau}$.

(a) add vectors → components (8). (b) a scalar from two vectors → dot product (12). (c) a vector from two vectors → cross product (14).

SET UP

x east, y north, z up. Predict: $\phi < 90^\circ$ so $W > 0$; $\vec{r}$ is steeper than $\vec{F}$, so turning from $\vec{r}$ to $\vec{F}$ is clockwise: $\vec{\tau}$ along $-z$.



top view; $F = 50.0$ N; z points out of the page

Key idea

Adding vectors uses components; a scalar from two vectors is the dot product, a vector is the cross product.

IDENTIFY

Given: $F = 50.0\,\text{N}$ at $30.0°$ N of E; legs $3.00\,\text{m}$ E and $4.00\,\text{m}$ N; $\vec{r} = (0.800\hat{\imath} + 0.600\hat{\jmath})\,\text{m}$. Find: $\vec{s}$, W, $\vec{\tau}$.

(a) add vectors → components (8). (b) a scalar from two vectors → dot product (12). (c) a vector from two vectors → cross product (14).

SET UP

x east, y north, z up. Predict: $\phi < 90°$ so $W > 0$; $\vec{r}$ is steeper than $\vec{F}$, so turning from $\vec{r}$ to $\vec{F}$ is clockwise: $\vec{\tau}$ along $-z$.

EXECUTE (a)

Add the legs (8). $s_x = 3.00\,\text{m}$, $s_y = 4.00\,\text{m}$

$$\boxed{\vec{s} = (3.00\hat{\imath} + 4.00\hat{\jmath})\,\text{m}}$$


Magnitude (7). $s = \sqrt{(3.00)^2 + (4.00)^2}\,\text{m} = 5.00\,\text{m}$

Direction. $\theta = \tan^{-1}\dfrac{4.00}{3.00} = 53.1°$ north of east

Resolve the force (6). $F_x = (50.0\,\text{N})\cos 30.0° = 43.3\,\text{N}$

$F_y = (50.0\,\text{N})\sin 30.0° = 25.0\,\text{N}$

Reuse: (6) resolving, (8) adding.



top view; $F = 50.0$ N; z points out of the page

EXECUTE (b): work

Write rule (12). $W = F_x s_x + F_y s_y$

Substitute. $W = (43.3\,\text{N})(3.00\,\text{m}) + (25.0\,\text{N})(4.00\,\text{m})$

Multiply, then add. $W = 129.9\,\text{J} + 100.0\,\text{J}$ $\boxed{W = 230\,\text{J}}$

EXECUTE (c): torque

Both vectors lie in the xy-plane, so only the $\hat{k}$ term of (14) survives. $\tau_z = r_x F_y - r_y F_x$


Substitute. $\tau_z = (0.800\,\text{m})(25.0\,\text{N}) - (0.600\,\text{m})(43.3\,\text{N})$

Multiply, then subtract. $\tau_z = 20.0\,\text{N m} - 26.0\,\text{N m}$

$\boxed{\vec{\boldsymbol{\tau}} = -5.98\,\hat{\boldsymbol{k}}\,\text{N m}}$

Key idea

Work uses the part of $\vec{\boldsymbol{F}}$ along $\vec{\boldsymbol{s}}$ (dot); torque uses the part perpendicular to $\vec{\boldsymbol{r}}$ (cross, right-hand rule).



top view; $F = 50.0$ N; z points out of the page

Key idea

Work uses the part of $\vec{F}$ along $\vec{s}$ (dot); torque uses the part perpendicular to $\vec{r}$ (cross, right-hand rule).

EXECUTE (b): work

Write rule (12). $W = F_x s_x + F_y s_y$

Substitute. $W = (43.3\,\text{N})(3.00\,\text{m}) + (25.0\,\text{N})(4.00\,\text{m})$

Multiply, then add. $W = 129.9\,\text{J} + 100.0\,\text{J}$ $\boxed{W = 230\,\text{J}}$

EXECUTE (c): torque

Both vectors lie in the xy-plane, so only the $\hat{k}$ term of (14) survives. $\tau_z = r_x F_y - r_y F_x$

Substitute. $\tau_z = (0.800\,\text{m})(25.0\,\text{N}) - (0.600\,\text{m})(43.3\,\text{N})$

Multiply, then subtract. $\tau_z = 20.0\,\text{N m} - 26.0\,\text{N m}$

$\boxed{\vec{\tau} = -5.98\,\hat{k}\,\text{N m}}$

EVALUATE

Work: $\phi = 53.1° - 30.0° = 23.1°$, so $Fs\cos\phi = (50.0)(5.00)\cos 23.1° = 230\,\text{J}$ ✓; $W > 0$ as predicted.

Torque: $r = 1.00\,\text{m}$ at $36.9°$, $\phi = 36.9° - 30.0° = 6.9°$, so $rF\sin\phi = (1.00)(50.0)\sin 6.9° = 6.0\,\text{N m}$ ✓


Right-hand rule from $\vec{r}$ $(36.9°)$ to $\vec{F}$ $(30.0°)$: clockwise seen from above, so $-z$ ✓

Common mistakes and the correct habit

Mistake	Instead
Using the internal triangle angle in $\vec{A} \cdot \vec{B}$ or $\vec{A} \times \vec{B}$.	ϕ is the angle tail to tail, $0^\circ \leq \phi \leq 180^\circ$.
Writing a dot product as a vector, or a cross product as a number.	Dot gives a scalar; cross gives a vector.
Forgetting that $\vec{A} \times \vec{B} = -\vec{B} \times \vec{A}$.	Use the right-hand rule and keep the order.
Swapping $\cos$ and $\sin$ between the two products.	Test with the special cases: perpendicular and parallel.
A wrong sign on the $\hat{\jmath}$ term of the cross product.	Use the determinant, then check $(\vec{A} \times \vec{B}) \cdot \vec{A} = 0$.
Taking $\hat{\imath} \cdot \hat{\jmath} = 1$.	Like unit vectors give 1, unlike give 0.

Week 1 concept map

CORE



What you should remember

Key ideas

- **A vector is a mathematical object used to represent a physical quantity; its components depend on the axes chosen.**
- A_x is a number; $A_x\hat{\imath}$ is the component vector.
- Displacement depends only on the end points, not on the path.
- Magnitudes do not simply add: $|A - B| \leq |\vec{\boldsymbol{A}} + \vec{\boldsymbol{B}}| \leq A + B$.
- **Graphs give geometric understanding; components provide a systematic way to calculate accurately.**
- Magnitude/direction and components describe the same vector; find the quadrant before the angle.
- **The dot product measures the component of one vector along another; the cross product produces a vector perpendicular to both input vectors.** Their magnitudes are $AB\cos\phi$ and $AB\sin\phi$, respectively.
- Habit: sketch, predict, calculate, evaluate.

Reference tools: where to look

Equations, procedures: the next slides (master toolkit, core equations).

Reference deck: the seven specialised toolkits, equation anatomy, vocabulary, extra examples and practice.

Common mistakes: the last slide of each contact.

MASTER TOOLKIT – For a general vector problem

1. **IDENTIFY** What is being asked?
2. **SKETCH** Draw the physical situation.
3. **CHOOSE AXES** Select useful perpendicular coordinates.
4. **PREDICT** Estimate signs, quadrant, size and direction.
5. **RESOLVE** Convert vectors into components if necessary.
6. **COMBINE** Perform the required vector operation.
7. **RECONSTRUCT** Find magnitude and direction if required.
8. **EVALUATE** Check units, signs, quadrant, magnitude, direction and physical reasonableness.

If the result disagrees with the sketch or prediction, investigate before accepting the answer. The seven specialised toolkits are in the Reference deck.

Inside the course framework

IDENTIFY (step 1): what is being asked?
SET UP (steps 2–4): sketch, choose axes, predict.
EXECUTE (steps 5–7): resolve, combine, reconstruct.
EVALUATE (step 8): check the result.

Reference tools: core equations

Idea	No.	Equation	Conditions and units
Along a line	(1)	$R = A + B$ or $R = \lvert A - B\rvert$; $\lvert A - B\rvert \le R \le A + B$	one line only
Subtraction	(2)	$\vec{\boldsymbol{A}} - \vec{\boldsymbol{B}} = \vec{\boldsymbol{A}} + (-\vec{\boldsymbol{B}})$	same units
Perpendicular	(3)	$R = \sqrt{A^2 + B^2}, \quad \tan\theta = B/A$	90° between the vectors
Cosine rule	(4)	$R^2 = A^2 + B^2 - 2AB\cos\gamma$	γ: internal angle opposite R
Sine rule	(5)	$\dfrac{a}{\sin\alpha} = \dfrac{b}{\sin\beta} = \dfrac{c}{\sin\gamma}$	sides and opposite angles
Components	(6)	$A_x = A\cos\theta, \quad A_y = A\sin\theta$	θ from $+x$; units of $\vec{\boldsymbol{A}}$
Magnitude, direction	(7)	$A = \sqrt{A_x^2 + A_y^2}, \quad \theta_{\text{ref}} = \tan^{-1}\lvert A_y/A_x\rvert$	place by quadrant
Addition	(8)	$R_x = \sum A_x, \quad R_y = \sum A_y$	same units for all terms
Unit-vector form	(9)	$\vec{\boldsymbol{A}} = A_x\hat{\boldsymbol{\imath}} + A_y\hat{\boldsymbol{\jmath}} + A_z\hat{\boldsymbol{k}}$	$A = \sqrt{A_x^2 + A_y^2 + A_z^2}$; $\hat{\imath}, \hat{\jmath}, \hat{\boldsymbol{k}}$ no units
Unit vector of $\vec{\boldsymbol{A}}$	(10)	$\hat{\boldsymbol{A}} = \vec{\boldsymbol{A}}/A, \quad \vec{\boldsymbol{A}} = A\hat{\boldsymbol{A}}$	$\lvert\hat{\boldsymbol{A}}\rvert = 1$, no units
Dot product	(11)	$\vec{\boldsymbol{A}} \cdot \vec{\boldsymbol{B}} = AB\cos\phi$	scalar; product of units
Dot, components	(12)	$A_xB_x + A_yB_y + A_zB_z$	same scalar
Cross product	(13)	$\lvert\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}}\rvert = AB\sin\phi$	vector; right-hand rule
Cross, components	(14)	$(A_yB_z - A_zB_y)\hat{\boldsymbol{\imath}} + (A_zB_x - A_xB_z)\hat{\boldsymbol{\jmath}} + (A_xB_y - A_yB_x)\hat{\boldsymbol{k}}$	$\vec{\boldsymbol{A}} \times \vec{\boldsymbol{B}} = -\vec{\boldsymbol{B}} \times \vec{\boldsymbol{A}}$

Checklist: can I . . . CORE

- ☐ distinguish a scalar from a vector?
- ☐ add and subtract vectors graphically?
- ☐ resolve a vector with the correct signs?
- ☐ determine the direction of a vector, including its correct quadrant?
- ☐ add several vectors by components?
- ☐ write a vector with $\hat{\boldsymbol{\imath}}, \hat{\boldsymbol{\jmath}}, \hat{\boldsymbol{k}}$?
- ☐ use IDENTIFY → SET UP → EXECUTE → EVALUATE?
- ☐ calculate a dot product and interpret its sign?
- ☐ calculate a cross product and determine its direction?
- ☐ explain when each product is zero?

Next

Problem sheet 1: extra component, resultant, dot and cross problems, plus challenge problems. The Reference deck holds the supporting material cut from the live lecture; the supplementary notes cover linear independence and direction angles in 3D (extension).