


## Intermediate representations

---



front end produce an intermediate representation(IR) for the program

optimizer transforms the code in IR form into an equivalent program that may run more efficiently.

back end transforms the code in IR form into native code for the target machine

The IR encodes knowledge that the compiler has derived about the source program.

## Intermediate representation

---

Why use an intermediate representation?

1. break the compiler into manageable pieces  
good software engineering technique
2. allow a complete pass before code is emitted  
lets compiler consider more than one option
3. simplifies retargeting to new host  
isolates back end from front end
4. simplifies handling of “poly-architecture” problem  
 $m$  lang's,  $n$  targets  $\Rightarrow m + n$  components(myth)
5. enables machine-independent optimization  
general techniques, multiple passes

An intermediate representation is a compile-time data structure

## Intermediate representation

---

### Important IR properties

- ease of generation
- ease of manipulation
- cost of manipulation
- level of abstraction
- freedom of expression
- size of typical procedure
- original or derivative

Subtle design decisions in the IR have far reaching effects on the speed and effectiveness of the compiler.

Level of exposed detail is a crucial consideration.

## Intermediate representation

---

Representations talked about in the literature include:

- abstract syntax trees(AST)
- linear (operator) form of tree
- directed acyclic graphs(DAG)
- control flow graph(CFG)
- program dependence graph(PDG)
- static single assignment form(SSA)
- stack code
- three address code or quadruples
- hybrid combination

## Intermediate representations

---

Broadly speaking, IRs fall into three categories:

### Structural

- structural IRs are graphically oriented
- examples: trees, directed acyclic graphs
- heavily used in source to source translators
- nodes, edges tend to be large

### Linear

- pseudo-code for some abstract machine
- large variation in level of abstraction
- simple, compact data structures
- easier to rearrange


### Hybrid

- combination of graphs and linear code
- attempt to take best of each
- examples: control flow graph

## Abstract syntax tree

---

An abstract syntax tree (AST) is the procedure's parse tree with the nodes for most non-terminal symbols removed.




This represents "x - 2 \* y"

For ease of manipulation, can use a linearized (operator) form of the tree.

x 2 y \* - in postfix form.

## Directed acyclic graph

A directed acyclic graph(DAG) is an AST with a unique node for each value.



$x \leftarrow 2 * y + \sin(2 * x)$

$z \leftarrow x / 2$

## Control flow graph

---


The control flow graph (CFG) models the transfers of control in the procedure.

- nodes in the graph are basic blocks  
maximal-length straight-line blocks of code
- edges in the graph represent control flow  
loops, if-then-else, case, goto

Example

```
if (x = y)
    then s1
    else s2
s3
```

becomes





## Stack machine code

---

Several stack-based computers have been built

Compilers can directly generate stack code

Example

$x - 2 * y$

becomes

push x

push 2

push y

multiply

subtract

Advantages

- compact form
- introduced names are implicit, not explicit
- simple to generate and execute code

B5500, B1700, P-code, BCPL, RPN calculators

Bytecodes are becoming popular (again)

## Three address code

---

Three address code is a term used to describe a variety of representations.

In general, they allow statements of the form:

$$x \leftarrow y \text{ op } z$$

with a single operator and, at most, three names.

Simple form of expression

$$x - 2 * y$$

becomes

$$t1 \leftarrow 2 * y$$

$$t2 \leftarrow x - t1$$

Advantages

- compact form(direct mapping)
- names for intermediate values

Can include forms of prefix or postfix code

## Three address code

---

Typical statement types include:

1. assignments –  $x \leftarrow y \text{ op } z$
2. assignments –  $x \leftarrow \text{op } y$
3. assignments –  $x \leftarrow y[i]$
4. assignments –  $x \leftarrow y$
5. branches – goto L
6. conditional branches – if x relop y goto L
7. procedure calls – param x and call p
8. address and pointer assignments

## Three address code

---

Until recently, compile-time space was a serious issue

- machines had small memories
- compiler touches space it allocates

Compact forms of three address code

- quadruples
- triples
- indirect triples

Major tradeoff is compactness versus ease of manipulation

Today, speed(and locality) may be more important

## Three address code

---

### Quadruples

$x - 2 * y$				
(1)	load	t1	y	
(2)	loadi	t2	2	
(3)	mult	t3	t2	t1
(4)	load	t4	x	
(5)	sub	t5	t4	t2

- simple record structure with four fields
- easy of reorder
- explicit names

## Thress address code

---

### Triples

$x - 2 * y$				
(1)	load	y		
(2)	loadi	2		
(3)	mult	(1)	(2)	
(4)	load	x		
(5)	sub	(4)	(3)	

- use table index as implicit name
- requires only three fields in record
- harder to reorder

## Three address code

---

### Indirect Triples

$x - 2 * y$					
	stmt		op	arg1	arg2
(1)	(100)	(100)	load	y	
(2)	(101)	(101)	loadi	2	
(3)	(102)	(102)	mult	(100)	(101)
(4)	(103)	(103)	load	x	
(5)	(104)	(104)	sub	(103)	(102)

- list of 1<sup>st</sup> triple in statement
- simplifies moving statements
- more space than triples
- implicit name space management

## Other hybrids

---

An attempt to get the best of both worlds

- graphs where they work
- linear codes where it pays

Unfortunately, there appears to be little agreement about where to use each kind of IR to best advantage.

For example:

- PCC and F77 directly emit assembly code for control flow, but build and pass around expression trees for expressions.
- Many systems use a control flow graph with three address code for each basic block
- Source-to-source translators typically use AST and dependence graph



## Intermediate representation

---

But this isn't the whole story.

Symbol table:

- identifiers, procedures
- size, type, location
- lexical nesting depth

Constant table:

- representation, type
- storage class, offset(s)

Storage map:

- storage layout
- overlap information
- (virtual) register assignments

## Advice

---

- Many kinds of IR are used in practice
- Best choice depends on application
- There is no widespread agreement on this subject
- A compiler may need several different IRs
- Choose IR with right level of detail
- Keep manipulation costs in mind