

PROGRAMOWANIE OBIEKTOWE

Projekt

Wydział Informatyki i Telekomunikacji	Kierunek: Informatyka Techniczna
Grupa zajęciowa (np. Pn7:30):Czw 13:15	Semestr: 2025/26 LATO
Nazwisko i Imię:Filip Klich	Nr indeksu:293446
Nazwisko i Imię:Michał Sikora	Nr indeksu:292845
Nazwisko i Imię:	Nr indeksu:
Nr. grupy projektowej:3	
Prowadzący: mgr inż. Karol Puchała	

TEMAT:

„Objectively Worse Doom”

OCENA:

PUNKTY:

Data:

1. Spis narzędzi użytych przy tworzeniu projektu

- GCC 16.1.1 2026.04.30, w tym g++
- POSIXowy shell (**bash**)
- Coreutils, a dokładniej:
 - **find**
 - **echo**
 - **mkdir**
 - **rm**
 - **cat**
 - **[** (do sprawdzania kompatybilności)
 - **stat** (do sprawdzania kompatybilności)
 - **basename** (do sprawdzania kompatybilności)
 - **head** (do sprawdzania kompatybilności)
 - **mktemp** (do sprawdzania kompatybilności)
- GNU **sed**
- **lsof** (do sprawdzania kompatybilności)
- **objcopy**
- GNU **make**
- **expect** (do testów)
- **libasound** (ALSA)
- **glibc**

Dodatkowo:

- format object fileów to **elf64-x84-64**
- kernel z DRM/KMS oraz evdev

2. Założenia i opis funkcjonalny programu

2.1 Opis założeń

Projekt ma na celu stworzenie w pełni funkcjonalnej, minimalistycznej gry typu retro FPS. Wszystkie kluczowe elementy mechaniki gry (potwory, broń) są projektowane z wykorzystaniem polimorfizmu, dziedziczenia i kompozycji, tak aby kod był czytelny i rozszerzalny.

- Gra jest w pełni obiektowa - każdy byt w świecie gry (potwór, broń, pocisk, gracz) jest instancją odpowiedniej klasy lub interfejsu.
- Polimorfizm jest używany jako główny mechanizm rozróżniania zachowania (różne typy potworów i pocisków).
- Gra działa w czasie rzeczywistym (pętla gry z update'ami i renderowaniem).
- Celem gry jest zabicie bossa.
- Prosta grafika imitująca 3d, podobna do Castle Wolfenstein 3d, ale napisana od zera

2.2 Opis funkcjonalny

2.2.1 Ogólna koncepcja rozgrywki

Gracz wciela się w przeniesionego do innego świata mieszkańca Japonii. Jego celem jest pokonanie armii króla demonów atakującego królestwo Aliud Regnum Mundi. Zadaniem jest przetrwanie i eliminacja wszystkich demonów oraz ich króla. Gracz może poruszać się, strzelać i zmieniać broń.

2.2.2 System potworów

Wszystkie potwory dziedziczą po wspólnej klasie abstrakcyjnej. Dzięki polimorfizmowi każdy typ zachowuje się inaczej, ale jest traktowany przez silnik gry w identyczny sposób.

2.2.2.1 Dostępne typy potworów

- **Podstawowy słaby** - najprostszy przeciwnik, mała ilość HP, atak w zwarcu
- **Słaby ranged** - tutorialowy przeciwnik strzelający
- **Assault shooter** - strzela seriami, średni zasięg
- **Sniper** - strzela rzadko, ale bardzo celnie i z dużej odległości
- **Duży gruby** - duża ilość HP, wolny, zadaje duże obrażenia w zwarcu
- **Mały szybki** - mały, bardzo szybki, bardzo mała ilość HP
- **All-rounder** - przeciwnik dobry zarówno w CQC, jak i w dystansie
- **Magic** - utility ale dla przeciwników
- **Elite Tank** - bardzo trudny przeciwnik do zabicia
- **Elite Szybki** - bardzo szybki przeciwnik który szarżuje
- **Boss**

2.2.3 System broni

Gracz może nosić wiele broni, zaimplementowanych polimorfizmem.

2.2.3.1 Dostępne bronie

- **M1911** - pistolet podstawowy, szybki słaby ogień pojedynczy
- **Pistolet maszynowy** - szybkostrzelny, niskie obrażenia od trafienia
- **Karabin** - zrównoważona broń średniego dystansu
- **Sniper rifle** - bardzo wysokie obrażenia, wolne przeładowanie
- **Plasma gun** - strzela dużymi, powolnymi pociskami energetycznymi
- **Shotgun** - strzela wiązką śrutu (kilka pocisków naraz)
- **Katana** - broń biała, nie zużywa amunicji

2.2.4 System pocisków

Wszystkie pociski dziedziczą po klasie abstrakcyjnej `Projectile`


2.2.4.1 Typy pocisków

- **Pocisk zwyczajny** - klasyczny raycast
- **Plasma** - nie raycast, duże obrażenia, pocisk porusza się wolno
- **Slug** - wiele małych pocisków jednocześnie, nie raycast
- **Granat** - nie raycast, obrażenia obszarowe

2.2.5 Dodatkowe mechaniki

- System zdrowia i pancerza
- Proste pickupy
- Status effecty
- Efekty podpalenia i spowolnienia

3. Klasy



input/evdev/backend.h

```
#pragma once
#include <vector>
#include <bitset>
#include <linux/input.h>
#include "input/input-backend.h"

namespace input {
    namespace evdev {
        class backend : public input::input_backend {
        private:
            /* a single open evdev file */
            struct device_node {
                int fd;
                bool is_keyboard;
                bool is_mouse;
            };

            /* all open files */
            std::vector<device_node> devices;
            /* currently pressed keys */
            std::bitset<KEY_CNT> key_map;
            /* current mouse state */
            mouse_state mouse;

            /* last absolute state for EV_ABS */
            int last_abs_x;
            int last_abs_y;

            /* epoll file descriptor for reading only changed files */
            int epoll_fd;

            /* emulated-to-native map */
            uint16_t map_to_native(key k) const;
            /* probe all evdev devices */
            void probe_devices();
            /* probe a single evdev device */
            void probe_device(std::string const& dev_name);
            /* process a single struct input_event from evdev files */
            void process_event(struct input_event const& ev);

        public:
            /* constructor */
            backend();
            /* destructor */
            ~backend() override;

            /* update internal state */
            void update() override;
            /* read key from internal state */
            bool is_key_down(key k) const override;
            /* read internal mouse state */
            mouse_state get_mouse_state() const override;
            /* reset internal mouse state */
            void reset_mouse_state(int nx, int ny) override;
        };
    }
}
```

}
}

input/input-backend.h

```
#pragma once

#include <stdint>

namespace input {
    /* recognized key map */
    enum class key {
        unknown = 0,
        a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z,
        n0, n1, n2, n3, n4, n5, n6, n7, n8, n9,
        f1, f2, f3, f4, f5, f6, f7, f8, f9, f10, f11, f12,
        esc, tab, caps_lock, l_shift, l_ctrl, l_meta, l_alt, space, r_alt, r_meta,
        r_ctrl, r_shift, enter, backspace,
        print_screen, scroll_lock, pause, insert, home, page_up, del, end, page_down,
        up, down, left, right,
        backtick, hyphen, equals, open_bracket, close_bracket, backslash, semicolon,
        quote, comma, period, slash,
        num_lock, kp_slash, kp_asterisk, kp_minus, kp_plus, kp_enter, kp_dot, kp0, kp1,
        kp2, kp3, kp4, kp5, kp6, kp7, kp8, kp9
    };

    /* recognized mouse state */
    struct mouse_state {
        int x, y;
        bool left, right, middle;
    };

    class input_backend {
    protected:
        /* bad flag, as in eg. std::filesystem::* */
        bool bad;
    public:
        /* constructor */
        input_backend();
        /* virtual destructor */
        virtual ~input_backend() = default;

        /* pure virtual "tick" method */
        virtual void update() = 0;
        /* pure virtual read from state */
        virtual bool is_key_down(key k) const = 0;
        /* pure virtual read from state */
        virtual mouse_state get_mouse_state() const = 0;
        /* pure virtual reset state */
        virtual void reset_mouse_state(int nx = 0, int ny = 0) = 0;
        /* virtual getter (we forgot about this one), as in std::filesystem */
        virtual bool is_bad() const;

        /* char-to-keymap helper */
        static key to_key(char c);
    };
}
```

rendering/drm-kms/crtc.h

```
#pragma once

#include <cstdint>
#include "device-context.h"
#include "mode.h"

namespace rendering {
    namespace drm_kms {
        class crtc {
            /* device owner */
            device_context const& dev;
            /* kernel CRTC id */
            std::uint32_t crtc_id;

        public:
            /* constructor */
            crtc(device_context const& d, uint32_t id);

            /* DRM_IOCTL_MODE_SETCRTC wrapper */
            bool set_config(uint32_t fb_id, uint32_t conn_id, mode const& m);

            /* DRM_IOCTL_MODE_PAGE_FLIP wrapper */
            bool page_flip(uint32_t fb_id) const;
        };
    }
}
```

rendering/drm-kms/framebuffer.h

```
#pragma once

#include <stdint>
#include <stddef>
#include "device-context.h"
#include "mode.h"

namespace rendering {
    namespace drm_kms {
        class crtc;
        class connector;
        class backend;

        class framebuffer {
            /* device owner */
            device_context const& dev;
            /* kernel framebuffer handle */
            uint32_t handle;

            /* kernel framebuffer id */
            uint32_t fb_id;
            /* mmap-ped memory pointer */
            uint32_t* mmio_ptr;
            /* mmap-ped memory size */
            size_t size;
            /* framebuffer pitch */
            uint32_t pitch;

        public:
            /* constructor */
            framebuffer(device_context const& d, uint32_t width, uint32_t height,
                bool *const success = nullptr);
            /* destructor */
            ~framebuffer();

            /* blit */
            void copy_from(uint32_t const* src, size_t pixel_count) const;

            /* page flip */
            bool flip_onto(crtc const& c) const;

            /* apply config to CRTC */
            bool apply_config(crtc &c, std::uint32_t const connector_id,
                mode const& m) const;

            friend connector;
            friend backend;
        };
    }
}
```

rendering/drm-kms/mode.h

```
#pragma once

#include <drm/drm.h>
#include "rendering/rendering-mode.h"

namespace rendering {
    namespace drm_kms {
        class mode : public rendering::rendering_mode {
            /* kernel drm_mode_modeinfo struct */
            struct drm_mode_modeinfo kernel_mode;

        public:

            /* constructor */
            mode(struct drm_mode_modeinfo const& info);
            /* destructor override with default */
            ~mode() override = default;

            /* CRTC creation request for ioctl */
            struct drm_mode_crtc create_crtc_req(std::uint32_t const crtc_id,
                std::uint32_t const fb_id, std::uint32_t const *const conn_id) const;

            /* componentized-like interface override */
            unsigned int operator()(util::component_tag<"x_res">) const override;
            /* componentized-like interface override */
            unsigned int operator()(util::component_tag<"y_res">) const override;
            /* componentized-like interface override */
            unsigned int operator()(util::component_tag<"refresh_hz">) const override;
            /* componentized-like interface override */
            bool operator()(util::component_tag<"has_vsync">) const override;
        };
    }
}
```

rendering/drm-kms/connector.h

```
#pragma once

#include <vector>
#include <memory>
#include <cstdint>
#include "device-context.h"
#include "mode.h"

namespace rendering {
    namespace drm_kms {
        class crtc;
        class framebuffer;

        class connector {
            /* device owner */
            device_context const& dev;
            /* kernel connector id */
            uint32_t connector_id;
            /* kernel encoder id */
            uint32_t encoder_id;

        public:
            /* constructor */
            connector(device_context const& d, uint32_t id, bool* const success = nullptr);

            /* returns std::vector of available modes for a particular connector */
            std::vector<std::unique_ptr<mode const>> probe_modes();

            /* config for ioctl */
            bool apply_config(crtc& c, framebuffer const& fb, mode const& m) const;
        };
    }
}
```


rendering/drm-kms/device-context.h

```
#pragma once

#include <string>

namespace rendering {
    namespace drm_kms {
        class device_context {
            /* dri file descriptor */
            int fd;

        public:

            /* constructor */
            explicit device_context(std::string const& path);
            /* destructor */
            ~device_context();

            /* error checking */
            bool is_valid() const;
            /* sys/ioctl.h ::ioctl wrapper */
            int ioctl(unsigned long request, void* arg) const;
            /* sys/mman.h ::mmap wrapper */
            void *mmap(void *addr, size_t len, int prot, int flags, off_t off) const;
        };
    }
}
```

rendering/drm-kms/backend.h

```
#pragma once

#include <memory>
#include <vector>
#include <drm/drm.h>

#include "rendering/rendering-backend.h"
#include "device-context.h"
#include "framebuffer.h"
#include "connector.h"
#include "crtc.h"

namespace rendering {
    namespace drm_kms {
        class backend : public rendering::rendering_backend {
        protected:
            /* opened /dev/dri device */
            std::unique_ptr<device_context> dev;
            /* currently active connector */
            std::unique_ptr<connector> active_connector;
            /* currently active crtc */
            std::unique_ptr<crtc> active_crtc;
            /* error checking */
            bool is_bad;

            /* double-buffering */
            std::unique_ptr<framebuffer> buffers[2];
            /* currently active buffers index */
            int front_buffer_index;
            /* shadow buffer */
            std::vector<uint32_t> shadow;

            /* currently chosen mode */
            std::unique_ptr<mode const> current_mode;

            /* framebuffer id for tty VT driver */
            uint32_t original_fb_id = 0;
            /* connector id for tty VT driver */
            uint32_t original_connector_id = 0;
            /* mode for tty VT driver */
            struct drm_mode_modeinfo original_mode = {};
            /* whether or not original VT state was preserved */
            bool has_original_state = false;

        public:
            /* constructor */
            backend();
            /* destructor override */
            ~backend() override;

            /* backend + fd aggregate */
            bool bad() const override;
            /* componentized-like interface override */
            virtual std::vector<std::unique_ptr<rendering_mode const>>
                operator()(util::component_tag<"modes">) override;
```

```

    /* virtual method override */
    void push_mode(std::unique_ptr<rendering_mode const> pushed_mode) override;
    /* componentized-like interface override */
    unsigned int operator()(util::component_tag<"width">) override;
    /* componentized-like interface override */
    unsigned int operator()(util::component_tag<"height">) override;
    /* componentized-like interface override */
    unsigned int operator()(util::component_tag<"pitch">) override;
    /* componentized-like interface override */
    std::uint32_t *operator()(util::component_tag<"mmio">) override;
    /* virtual method override */
    void wait_for_vsync() override;
    /* virtual method override */
    void flush() override;
};
}
}

```

rendering/renderer-2d.h

```
#pragma once
```

```
#include "rendering-backend.h"
#include "assets/asset-manager.h"
#include "assets/texture.h"
#include <string_view>
#include <cstdint>
#include <algorithm>
```

```
namespace rendering {
    class renderer_2d {
        /* chosen backend */
        rendering_backend &target;
        /* asset mgr ref */
        assets::asset_manager const& tex_manager;
        /* chosen 16x16 font atlas */
        assets::texture const& font_texture;

    public:
        /* constructor */
        renderer_2d(rendering_backend &tgt, assets::asset_manager const& tm,
            assets::texture const& font_tex);

        /* blit texture onto backend */
        void draw_texture(assets::texture const& tex, int x, int y, int w, int h) const;

        /* draw parts of font atlas onto backend, forming a string */
        void draw_text(std::string_view text, int x, int y, int char_w,
            int char_h, std::uint32_t const color) const;

        /* draw rectangle with alpha */
        void draw_rect(int x, int y, int w, int h, std::uint32_t color) const;
    };
}
```

rendering/lighting.h

```
#pragma once

#include <cstdint>

namespace rendering {
    class lighting {
        /* dynamic lighting minimum distance */
        static constexpr float dl_start = 64.0f;
        /* dynamic lighting units per length */
        static constexpr float dl_density = 0.25f;

    public:

        /* calculate light level from sector light and z */
        __attribute__((always_inline)) static inline int
        calculate(std::uint8_t const sector_light_level, float const depth) {
            if(depth > dl_start) {
                int corrected_light = sector_light_level - (depth - dl_start) * dl_density;
                if(corrected_light < 0) corrected_light = 0;
                return corrected_light;
            } else {
                return sector_light_level;
            }
        }

        /* apply lighting to color using SWAR */
        __attribute__((always_inline)) static inline std::uint32_t
        apply(std::uint32_t const orig, int light) {
            std::uint32_t swar_rb = orig & 0x00ff00ff;
            std::uint32_t swar_g = orig & 0x0000ff00;

            swar_rb = ((swar_rb * light) >> 8) & 0x00ff00ff;
            swar_g = ((swar_g * light) >> 8) & 0x0000ff00;

            return swar_rb | swar_g;
        }
    };
}
```

rendering/frd.h

```
#pragma once

#include <cstdint>
#include <vector>
#include "math/vec2.h"

namespace rendering {
    struct frame_rendering_data {
        /* camera position */
        math::vec2 cam_pos;
        /* camera height and angle */
        float cam_height, cam_angle;
        /* screen width and height */
        unsigned int sw, sh;
        /* half of screen width */
        float half_sw;
        /* backend pitch */
        unsigned int pitch;
        /* backend framebuffer */
        std::uint32_t *__restrict mmio;
        /* fov scale */
        float fov_scale;
        /* 1 / fov_scale */
        float inv_fov_scale;
        /* cosine and sine of camera angle */
        float cos_cam_angle, sin_cam_angle;

        /* euclidian distance correction factor */
        std::vector<float> const* euclidian_dist_factor;
    };
}
```

rendering/sprite.h

```
#pragma once

#include "math/vec2.h"
#include "assets/ids.h"
#include "util/componentized.h"

namespace rendering {
    class software_renderer;
    class vissprite;

    class sprite : public util::componentized<sprite> {
    protected:

        /* sprite position */
        [[=util::ref_component_field{}]] math::vec2 pos;
        /* sprite height */
        [[=util::ref_component_field{}]] float z_pos;
        /* sprite angle */
        [[=util::ref_component_field{}]] float angle;
        /* sprite texture */
        assets::texture_id tex_id;
        /* texture scaling factor */
        float inherent_scale;
        /* flash time */
        float hit_flash = 0.0f;

    public:

        /* constructor */
        sprite(math::vec2 const p, float const z,
              assets::texture_id const tex, float const is);
        //sprite();
        /* virtual destructor */
        virtual ~sprite() = default;

        friend util::componentized<sprite>;
        friend software_renderer;
        friend vissprite;
    };
}
```

rendering/rendering-backend.h

```
#pragma once

#include <vector>
#include <memory>
#include <cstdint>
#include <cstdint>

#include "util/componentized.h"
#include "rendering-mode.h"

namespace rendering {
    class rendering_backend {
    public:

        /* virtual aggregator */
        virtual bool bad() const = 0;
        /* componentized-like API for mode acquisition */
        virtual std::vector<std::unique_ptr<rendering_mode const>>
            operator()(util::component_tag<"modes">) = 0;
        /* mode setting */
        virtual void push_mode(std::unique_ptr<rendering_mode const> mode) = 0;
        /* componentized-like API */
        virtual unsigned int operator()(util::component_tag<"width">) = 0;
        /* componentized-like API */
        virtual unsigned int operator()(util::component_tag<"height">) = 0;
        /* componentized-like API */
        virtual unsigned int operator()(util::component_tag<"pitch">) = 0;
        /* componentized-like API */
        virtual std::uint32_t *operator()(util::component_tag<"mmio">) = 0;
        /* wait for hardware vsync, if current mode supports it */
        virtual void wait_for_vsync() = 0;
        /* flush to display */
        virtual void flush() = 0;

        /* virtual destructor */
        virtual ~rendering_backend() = default;
    };
}
```


rendering/rendering-mode.h

```
#pragma once

#include "util/componentized.h"

namespace rendering {
    class rendering_mode : public util::componentized<rendering_mode> {
    public:
        /* virtual destructor */
        virtual ~rendering_mode() = default;

        /* componentized-like API */
        virtual unsigned int operator()(util::component_tag<"x_res">) const = 0;
        /* componentized-like API */
        virtual unsigned int operator()(util::component_tag<"y_res">) const = 0;
        /* componentized-like API */
        virtual unsigned int operator()(util::component_tag<"refresh_hz">) const = 0;
        /* componentized-like API */
        virtual bool operator()(util::component_tag<"has_vsync">) const = 0;

        friend util::componentized<rendering_mode>;
    };
}
```

rendering/software-renderer.h

```
#pragma once

#include "rendering-backend.h"
#include "frd.h"
#include "visplane.h"
#include "vissprite.h"
#include "assets/asset-manager.h"
#include "geometry/linedef.h"
#include "geometry/bsp-node.h"
#include "geometry/map-data.h"
#include "math/vec2.h"
#include <vector>
#include <cstdint>

namespace rendering {
    class software_renderer {
        /* chosen backend */
        rendering_backend &target;
        /* texture mgr reference */
        assets::asset_manager const& tex_manager;
        /* map reference */
        geometry::map_data const& current_map;

        /* near clipping plane distance */
        static constexpr float near_z = 0.1f;

        /* upper clip array */
        std::vector<int> upper_clip;
        /* lower clip array */
        std::vector<int> lower_clip;
        /* rendered visplanes */
        std::vector<visplane> visplanes;
        /* rendered vissprites */
        std::vector<vissprite> vissprites;

        /* euclidian distance correction */
        std::vector<float> euclidian_dist_factor;

        /* recursively render a BSP node */
        void render_bsp_node(util::indexed_storage<geometry::bsp_node>::id_t
            node_id, frame_rendering_data const& frd);
        /* render a linedef */
        void project_and_draw_linedef(geometry::linedef line,
            frame_rendering_data const& frd);
        /* render a wall linedef */
        void draw_solid_wall_span(float proj_x1, float proj_x2, float z1,
            float z2, float u1, float u2, geometry::linedef const& line,
            frame_rendering_data const& frd);
        /* render a portal linedef */
        void draw_portal_wall_span(float proj_x1, float proj_x2, float z1,
            float z2, float u1, float u2, geometry::linedef const& line,
            frame_rendering_data const& frd);
        /* render all visplanes */
        void render_visplanes(frame_rendering_data const& frd);
        /* queue a vissprite to be rendered */
    };
}
```

```

    void add_vissprite(sprite *const s, std::uint8_t light,
                      frame_rendering_data const& frd);
    /* render all vissprites */
    void render_vissprites(frame_rendering_data const& frd);
    /* whether or not a BSP should be culled based on its bounding box */
    bool is_box_visible(geometry::bsp_node::bounding_box const& box,
                       frame_rendering_data const& frd);

public:
    /* constructor */
    software_renderer(rendering_backend &tgt, assets::asset_manager const& tm, geometry::map_data

    /* render whole bsp tree */
    void render_bsp(math::vec2 const cam_pos, float const cam_height, float cam_angle, float fov

};
}

```

rendering/vissprite.h

```
#pragma once

#include <stdint>
#include <vector>

#include "assets/asset-manager.h"
#include "sprite.h"

namespace rendering {
    struct frame_rendering_data;

    class vissprite {
        /* z */
        float depth;
        /* clamped screen position */
        int cx1, cx2;
        /* projected position, sprite scale */
        float proj_x, scale;
        /* projected height */
        float z_pos;
        /* sprite texture id */
        assets::texture_id tex_id;
        /* sector light level */
        std::uint8_t light_level;
        /* damage flash */
        bool flash_red;

        /* upper clip array at vissprite queue time */
        std::vector<int> upper_clip;
        /* lower clip array at vissprite queue time */
        std::vector<int> lower_clip;

    public:

        /* constructor */
        vissprite(sprite const& sprite, float const z, int const clamped_x1,
            int const clamped_x2, float const px, float const sc,
            std::uint8_t const light, std::vector<int> const& uc,
            std::vector<int> const& lc);

        /* sort for painters algorithm */
        static void pa_sort(std::vector<vissprite> &vec);

        /* render onto backend */
        void render(assets::asset_manager const& tex_manager,
            frame_rendering_data const& frd) const;
    };
}
```

rendering/visplane.h

```
#pragma once

#include <cstdint>
#include <vector>

#include "assets/asset-manager.h"
#include "assets/ids.h"

namespace rendering {
    struct frame_rendering_data;

    class visplane {
        /* visplane height */
        float height;
        /* visplane texture */
        assets::texture_id tex_id;
        /* sector light */
        std::uint8_t light_level;
        /* visplane x span */
        int min_x, max_x;
        /* visplane bounding functions */
        std::vector<int> top, bottom;

    public:

        /* constructor */
        visplane(unsigned int const sw, float const h,
            assets::texture_id const tid, std::uint8_t const light);

        /* add column to a visplane vector, either by extending an existing visplane */
        /* or by creating a new one */
        static void add_column(std::vector<visplane>& pool, int x,
            int y_start, int y_end, unsigned int sw, float flat_height,
            assets::texture_id tex_id, std::uint8_t light_level);

        /* render a visplane */
        void render(assets::asset_manager const& tex_manager,
            frame_rendering_data const& frd) const;
    };
}
```

math/ray2.h

```
#pragma once

#include "vec2.h"
#include "segment.h"

namespace math {
    class ray2 {
    public:
        /* ray end */
        vec2 end;
        /* ray direction */
        vec2 direction;

        /* constructor */
        constexpr ray2(vec2 const e, vec2 const d);

        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
            operator==(ray2 const other) const;
        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
            operator!=(ray2 const other) const;

        /* rotate ray by angle */
        static ray2 const rotate(ray2 const ray, float const angle);

        /* ray intersects a segment */
        bool intersects(segment const seg, vec2 &hit_point, float &distance,
            float &seg_len) const;
    };
}

/* constexpr inline definitions */
constexpr math::ray2::ray2(vec2 const e, vec2 const d) : end(e), direction(d) {}

__attribute__((always_inline)) constexpr inline bool
math::ray2::operator==(ray2 const other) const {
    return end == other.end && direction == other.direction;
}

__attribute__((always_inline)) constexpr inline bool
math::ray2::operator!=(ray2 const other) const {
    return !(*this == other);
}
```

math/segment.h

```
#pragma once

#include "vec2.h"
#include "util/componentized.h"

namespace math {
    class segment : public util::componentized<segment> {
        /* segment points */
        [=util::component_field{}]] vec2 point0, point1;

    public:

        /* constructor */
        constexpr segment(vec2 const p0, vec2 const p1);

        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
            operator==(segment const other) const;
        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
            operator!=(segment const other) const;

        /* segment angle */
        float angle() const;
        /* segment midpoint */
        constexpr vec2 const midpoint() const;
        /* segment length */
        float len() const;
        /* segment square length */
        float sqr_len() const;

        friend util::componentized<segment>;
    };
}

/* constexpr inline definitions */
constexpr math::segment::segment(vec2 const p0, vec2 const p1) : point0(p0), point1(p1) {}

constexpr math::vec2 const math::segment::midpoint() const {
    return (point0 + point1) / 2.0f;
}

__attribute__((always_inline)) constexpr inline bool
math::segment::operator==(segment const other) const {
    return point0 == other.point0 && point1 == other.point1;
}

__attribute__((always_inline)) constexpr inline bool
math::segment::operator!=(segment const other) const {
    return !(*this == other);
}
}
```

math/vec3.h

```
#pragma once

#include "util/componentized.h"
#include "vec2.h"

namespace math {
    class vec3 : public util::componentized<vec3> {
        /* vector components */
        [=util::ref_component_field{}] float x;
        /* vector components */
        [=util::ref_component_field{}] float y;
        /* vector components */
        [=util::ref_component_field{}] float z;
    public:

        /* constructor from 3 floats */
        constexpr inline vec3(float const X = 0, float const Y = 0,
                               float const Z = 0);
        /* constructor from a vec2 and height */
        constexpr inline vec3(vec2 const flat, float const Z = 0);

        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3 const
            operator+(vec3 const other) const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3 const
            operator-(vec3 const other) const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3 const
            operator-() const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3 const
            operator*(float const scalar) const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3 const
            operator/(float const scalar) const;

        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3
            &operator+=(vec3 const other);
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3
            &operator-=(vec3 const other);
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3
            &operator*=(float const scalar);
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec3
            &operator/=(float const scalar);

        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
            operator==(vec3 const other) const;
        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
```



```

        operator!=(vec3 const other) const;

    /* dot product of 2 vec3s */
    static constexpr float dot_product(vec3 const first, vec3 const second);
    /* cross product of 2 vec3s */
    static constexpr vec3 const cross_product(vec3 const first, vec3 const second);

    /* vector length */
    constexpr float len() const;
    /* vector square length */
    constexpr float sqr_len() const;
    /* normalized vector */
    constexpr vec3 const normalized() const;

    friend util::componentized<vec3>;
};

/* constexpr inline definitions */
constexpr inline
math::vec3::vec3(float const X, float const Y, float const Z) : x(X), y(Y), z(Z) {}

constexpr inline
math::vec3::vec3(vec2 const flat, float const Z) : x(flat("x"_f)), y(flat("y"_f)), z(Z) {}

__attribute__((always_inline)) constexpr inline math::vec3 const
math::vec3::operator+(vec3 const other) const {
    return vec3(x + other.x, y + other.y, z + other.z);
}

__attribute__((always_inline)) constexpr inline math::vec3 const
math::vec3::operator-(vec3 const other) const {
    return vec3(x - other.x, y - other.y, z - other.z);
}

__attribute__((always_inline)) constexpr inline math::vec3 const
math::vec3::operator-() const {
    return vec3(-x, -y, -z);
}

__attribute__((always_inline)) constexpr inline math::vec3 const
math::vec3::operator*(float const scalar) const {
    return vec3(x * scalar, y * scalar, z * scalar);
}

__attribute__((always_inline)) constexpr inline math::vec3 const
math::vec3::operator/(float const scalar) const {
    return vec3(x / scalar, y / scalar, z / scalar);
}

__attribute__((always_inline)) constexpr inline math::vec3 &
math::vec3::operator+=(vec3 const other) {
    x += other.x; y += other.y; z += other.z;
    return *this;
}

__attribute__((always_inline)) constexpr inline math::vec3 &
math::vec3::operator-=(vec3 const other) {

```

```

    x -= other.x; y -= other.y; z -= other.z;
    return *this;
}

__attribute__((always_inline)) constexpr inline math::vec3 &
math::vec3::operator*=(float const scalar) {
    x *= scalar; y *= scalar; z *= scalar;
    return *this;
}

__attribute__((always_inline)) constexpr inline math::vec3 &
math::vec3::operator/=(float const scalar) {
    x /= scalar; y /= scalar; z /= scalar;
    return *this;
}

__attribute__((always_inline)) constexpr inline bool
math::vec3::operator==(vec3 const other) const {
    return x == other.x && y == other.y && z == other.z;
}

__attribute__((always_inline)) constexpr inline bool
math::vec3::operator!=(vec3 const other) const {
    return !(*this == other);
}

constexpr float math::vec3::dot_product(vec3 const first, vec3 const second) {
    return first.x * second.x + first.y * second.y + first.z * second.z;
}

constexpr math::vec3 const math::vec3::cross_product(vec3 const first, vec3 const second) {
    return vec3(
        first.y * second.z - first.z * second.y,
        first.z * second.x - first.x * second.z,
        first.x * second.y - first.y * second.x
    );
}

```

math/vec2.h

```
#pragma once
#include "util/componentized.h"

namespace math {
    class vec3;

    class vec2 : public util::componentized<vec2> {
        /* vector components */
        [=util::ref_component_field{}] float x;
        /* vector components */
        [=util::ref_component_field{}] float y;

    public:

        /* constructor from 2 floats */
        constexpr inline vec2(float const X = 0, float const Y = 0);
        /* constructor from a vec3, discarding z */
        vec2(vec3 const& vec);

        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            operator+(vec2 const other) const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            operator-(vec2 const other) const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            operator-() const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            operator*(float const scalar) const;
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            operator/(float const scalar) const;

        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            &operator+=(vec2 const other);
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            &operator-=(vec2 const other);
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            &operator*=(float const scalar);
        /* algebraic operators */
        __attribute__((always_inline)) constexpr inline vec2
            &operator/=(float const scalar);

        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
            operator==(vec2 const other) const;
        /* comparison operators */
        __attribute__((always_inline)) constexpr inline bool
            operator!=(vec2 const other) const;
    };
}
```

```

    /* dot product of 2 vec2s */
    static float dot_product(vec2 const first, vec2 const second);
    /* cross product of 2 vec2s */
    static float cross_product(vec2 const first, vec2 const second);

    /* vector length */
    float len() const;
    /* vector square length */
    float sqr_len() const;
    /* normalized vector */
    vec2 const normalized() const;
    /* a vector perpendicular to a given one */
    vec2 const perpendicular() const;
    /* vector argument */
    float angle() const;

    /* angle between 2 vectors */
    static float angle_between(vec2 const first, vec2 const second);
    /* vector rotation */
    static vec2 const rotate(vec2 const vec, float const angle);
    /* optimized vector rotation */
    static vec2 const rotate_with_known_trig(vec2 const vec,
        float const cos, float const sin);

    friend util::componentized<vec2>;
};

/* constexpr inline definitions */
constexpr inline
math::vec2::vec2(float const X, float const Y) : x(X), y(Y) {}

__attribute__((always_inline)) constexpr inline math::vec2
math::vec2::operator+(vec2 const other) const {
    return vec2(x + other.x, y + other.y);
}

__attribute__((always_inline)) constexpr inline math::vec2
math::vec2::operator-(vec2 const other) const {
    return vec2(x - other.x, y - other.y);
}

__attribute__((always_inline)) constexpr inline math::vec2
math::vec2::operator-() const {
    return vec2(-x, -y);
}

__attribute__((always_inline)) constexpr inline math::vec2
math::vec2::operator*(float const scalar) const {
    return vec2(x * scalar, y * scalar);
}

__attribute__((always_inline)) constexpr inline math::vec2
math::vec2::operator/(float const scalar) const {
    return vec2(x / scalar, y / scalar);
}

__attribute__((always_inline)) constexpr inline math::vec2&

```

```

math::vec2::operator+=(vec2 const other) {
    x += other.x;
    y += other.y;
    return *this;
}

__attribute__((always_inline)) constexpr inline math::vec2&
math::vec2::operator-=(vec2 const other) {
    x -= other.x;
    y -= other.y;
    return *this;
}

__attribute__((always_inline)) constexpr inline math::vec2&
math::vec2::operator*=(float const scalar) {
    x *= scalar;
    y *= scalar;
    return *this;
}

__attribute__((always_inline)) constexpr inline math::vec2&
math::vec2::operator/=(float const scalar) {
    x /= scalar;
    y /= scalar;
    return *this;
}

__attribute__((always_inline)) constexpr inline bool
math::vec2::operator==(vec2 const other) const {
    return x == other.x && y == other.y;
}

__attribute__((always_inline)) constexpr inline bool
math::vec2::operator!=(vec2 const other) const {
    return !(*this == other);
}

```

util/file-resource.h

```
#pragma once
#define FILE_RESOURCE_H

#include <vector>
#include "resource.h"

namespace util {
    class file_resource : public resource {
        /* mapped file */
        std::vector<std::byte> file_data;

    public:
        /* constructor */
        explicit file_resource(std::vector<std::byte> data);
        /* destructor override with default */
        ~file_resource() override = default;

        /* componentized-like API */
        void const* operator()(component_tag<"beginning">) const override;
        /* componentized-like API */
        void const* operator()(component_tag<"end">) const override;
        /* componentized-like API */
        std::size_t operator()(component_tag<"size">) const override;
    };
}
```

util/resource.h

```
#pragma once
#define RESOURCE_H

#include <cstddef>
#include "util/componentized.h"

namespace util {
    class resource {
    public:
        /* virtual destructor */
        virtual ~resource() = default;

        /* componentized-like API */
        virtual void const* operator()(component_tag<"beginning">) const = 0;
        /* componentized-like API */
        virtual void const* operator()(component_tag<"end">) const = 0;
        /* componentized-like API */
        virtual std::size_t operator()(component_tag<"size">) const = 0;
    };
}
```

util/binary-resource.h

```
#pragma once
#define BINARY_RESOURCE_H

#include "resource.h"

namespace util {
    class binary_resource : public resource {
        /* ptr to the beginning of baked binary date */
        void const* begin_ptr;
        /* ptr to the end of baked binary date */
        void const* end_ptr;
        /* size of baked binary date */
        std::size_t byte_size;

    public:

        /* constructor */
        binary_resource(void const* begin, void const* end);
        /* destructor */
        ~binary_resource() override = default;

        /* componentized-like API */
        void const* operator()(component_tag<"beginning">) const override;
        /* componentized-like API */
        void const* operator()(component_tag<"end">) const override;
        /* componentized-like API */
        std::size_t operator()(component_tag<"size">) const override;
    };
}
```


util/componentized.h

```
#pragma once
#define COMPONENTIZED_H

#include <concepts>
#include <meta>
#include <iostream>
#include <string_view>
#include <vector>

namespace util {
    /* c++26 meta annotation */
    struct component_field {};
    /* c++26 meta annotation */
    struct ref_component_field {};

    /* char array for any string size */
    template<std::size_t N>
    struct fixed_string {
        char data[N];
        /* constructor */
        constexpr fixed_string(char const (&s)[N]) {
            for (std::size_t i = 0; i < N; ++i) data[i] = s[i];
        }
        /* convert to std::string_view explicitly */
        constexpr std::string_view view() const { return {data, N - 1}; }
    };

    /* template metaprogramming argument struct */
    template<fixed_string field>
    struct component_tag {};

    template <typename T>
    class componentized {
        /* get a std::meta::info of a field with annotation, or {} if not found */
        template <fixed_string field, typename A>
        constexpr static std::meta::info get_tagged_member() {
            auto ctx = std::meta::access_context::current();
            auto members = std::meta::nonstatic_data_members_of(^T, ctx);

            for (auto m : members) {
                if (std::meta::identifier_of(m) == field.view()) {
                    auto attrs = std::meta::annotations_of(m);
                    for (auto attr : attrs) {
                        if (std::meta::type_of(attr) == ^A) {
                            return m;
                        }
                    }
                }
            }
            return {};
        }

    public:
        /* auto& operator() for ref_component_field only */
        template<fixed_string field>
```

```

requires (get_tagged_member<field, ref_component_field const>() != std::meta::info{})
auto& operator()(component_tag<field>) {
    constexpr auto target = get_tagged_member<field, ref_component_field const>();
    return static_cast<T *>(this)->[:target:];
}

/* auto const& operator() for ref_component_field or component_field */
template<fixed_string field>
requires
    ( (get_tagged_member<field, component_field const>() != std::meta::info{}) ||
      (get_tagged_member<field, ref_component_field const>() != std::meta::info{}) )
auto const& operator()(component_tag<field>) const {
    constexpr auto target = []{
        auto tgt = get_tagged_member<field, component_field const>();
        if(tgt != std::meta::info{}) return tgt;
        return get_tagged_member<field, ref_component_field const>();
    }();
    return static_cast<T const *>(this)->[:target:];
}

};

/* usage:
* class test : public util::componentized<test> {
*     [[=util::ref_component_field{}]] int hp;
*     [[=util::component_field{}]] int max_hp;
*
*     float secret;
*
*     [[=util::component_field{}]] float speed;
*
*     friend class componentized<test>;
* };
*
* int main() {
*     test d(100, 5.5f);
*
*     std::cout << "Initial HP: " << d("hp"_f) << std::endl;
*     d("hp"_f) = 150;
*     std::cout << "Updated HP: " << d("hp"_f) << std::endl;
*     std::cout << "Speed: " << d("speed"_f) << std::endl;
* }
*/

}

/* operator""_f for the "hp"_f notation */
/* must be global */
template<util::fixed_string field>
constexpr util::component_tag<field> operator""_f() {
    return {};
}

```

util/resource-loader.h

```
#pragma once

/* auto-generated file with all declarations */
#include "res.h"

#include <string>
#include <string_view>
#include <unordered_map>
#include <mutex>
#include <shared_mutex>
#include <memory>

#if __has_include(<meta>)
#include <meta>
#endif

#include "resource.h"
#include "binary-resource.h"
#include "file-resource.h"

namespace util {
    class resource_loader {
        /* resource name to pointer cache */
        std::unordered_map<std::string, void*> symbol_cache;
        /* resource name to resource cache */
        std::unordered_map<std::string, std::unique_ptr<resource>> resource_cache;
        /* cache mutex for writing */
        mutable std::shared_mutex cache_mutex;

        /* try to load from cache */
        void* lookup_binary(std::string_view resource_name);
        /* load a resource file */
        std::unique_ptr<resource> load_file(std::string_view resource_name) const;
        /* lookup baked resource via dlsym */
        resource* lookup_resource_runtime(std::string_view resource_name);

        /* turn resource name into symbol name */
        constexpr std::string make_symbol_name(std::string_view resource_name) const;

    public:
        /* count members of the res namespace */
        static constexpr std::size_t count_res_members();

        /* templated array to hold res namespace members */
        template <std::size_t N>
        struct info_array {
            std::meta::info data[N > 0 ? N : 1];
        };

        /* lookup all members of the res namespace */
        template <std::size_t N>
        static constexpr info_array<N> get_res_members_array();

        /* create resource from reflection */
        constexpr resource const* get_by_symbol_reflection(std::string_view symbol_name) const;
    };
}
```

```

#endif

public:
    /* constructor */
    resource_loader() = default;
    /* destructor */
    ~resource_loader() = default;

    resource_loader(resource_loader const&) = delete;
    resource_loader& operator=(resource_loader const&) = delete;

    /* get resource by name */
    constexpr resource* lookup_resource(std::string_view resource_name);
};

/* constexpr function definitions */
constexpr std::string resource_loader::make_symbol_name(std::string_view resource_name) const {
    std::string sym = "_binary_res_";
    sym.reserve(sym.size() + resource_name.size());

    for (char ch : resource_name) {
        unsigned char c = static_cast<unsigned char>(ch);
        if ((c >= 'a' && c <= 'z') || (c >= 'A' && c <= 'Z') || (c >= '0' && c <= '9')) {
            sym += ch;
        } else {
            sym += '_';
        }
    }
    return sym;
}

#if __has_include(<meta>)
constexpr std::size_t resource_loader::count_res_members() {
    std::size_t count = 0;
    for (auto m : std::meta::members_of(^res_symbols, std::meta::access_context::current())) {
        if (std::meta::has_identifier(m)) {
            if (std::string_view(std::meta::identifier_of(m)).starts_with("_binary_res_")) {
                ++count;
            }
        }
    }
    return count;
}

template <std::size_t N>
constexpr resource_loader::info_array<N> resource_loader::get_res_members_array() {
    resource_loader::info_array<N> arr{};
    std::size_t idx = 0;
    for (auto m : std::meta::members_of(^res_symbols, std::meta::access_context::current())) {
        if (std::meta::has_identifier(m)) {
            if (std::string_view(std::meta::identifier_of(m)).starts_with("_binary_res_")) {
                if (idx < N) {
                    arr.data[idx++] = m;
                }
            }
        }
    }
    return arr;
}

```

```

    }

    constexpr resource const* resource_loader::get_by_symbol_reflection(std::string_view symbol_name)
    {
        if constexpr {
            #if __has_include(<meta>)
                static constexpr std::size_t num_members = count_res_members();
                static constexpr auto members_arr = get_res_members_array<num_members>();

                if (!symbol_name.ends_with("_start")) {
                    return nullptr;
                }
                std::string end_name(symbol_name.substr(0, symbol_name.size() - 6));
                end_name += "_end";

                unsigned char const* begin_sym = nullptr;
                unsigned char const* end_sym = nullptr;

                /* TODO: work around a gcc 16.1.1 20260430 bug */
                #pragma GCC diagnostic push
                #pragma GCC diagnostic ignored "-Wshadow"
                template for (constexpr auto m : members_arr.data) {
                    if constexpr (std::meta::has_identifier(m)) {
                        constexpr std::string_view name = std::meta::identifier_of(m);
                        if (name == symbol_name) {
                            begin_sym = [&m];
                        } else if (name == end_name) {
                            end_sym = [&m];
                        }
                    }
                }
                #pragma GCC diagnostic pop

                if (begin_sym && end_sym) {
                    return std::define_static_object(
                        binary_resource(
                            static_cast<void const*>(begin_sym),
                            static_cast<void const*>(end_sym)));
                }
            #endif
            return nullptr;
        } else {
            /* not constexpr, abort */
            return nullptr;
        }
    }

    constexpr resource* resource_loader::lookup_resource(std::string_view resource_name) {
        if constexpr {
            std::string begin_name = make_symbol_name(std::string(resource_name) + "_start");

            return const_cast<resource*>(get_by_symbol_reflection(begin_name));
        } else {
            return lookup_resource_runtime(resource_name);
        }
    }
}
#endif
}

```

util/indexed-storage.h

```
#pragma once

#include <vector>
#include <cstdint>
#include <cstdint>
#include <cassert>
#include <utility>
#include <iterator>

namespace util {
    template<typename T>
    class indexed_storage {
    public:
        /* element identifier type */
        typedef std::uint32_t id_t;

        /* sentinel identifier */
        static constexpr id_t nullid = 0;

        /* iterator entry */
        struct entry {
            id_t id;
            T& value;
        };

        /* const iterator entry */
        struct const_entry {
            id_t id;
            T const& value;
        };

        class iterator {
        private:
            /* bound indexed_storage */
            indexed_storage* storage;
            /* current index */
            size_t index;
            /* constructor */
            iterator(indexed_storage* st, size_t idx) : storage(st), index(idx) {}
            friend class indexed_storage<T>;
        public:
            /* c++ semantics */
            using iterator_category = std::forward_iterator_tag;
            /* c++ semantics */
            using value_type = entry;
            /* c++ semantics */
            using difference_type = std::ptrdiff_t;
            /* c++ semantics */
            using pointer = entry*;
            /* c++ semantics */
            using reference = entry;

            /* constructor */
            iterator() : storage(nullptr), index(0) {}

            /* access operator */
```

```

    entry operator*() const {
        return {storage->lookup[index], storage->objects[index]};
    }

    /* iteration */
    iterator& operator++() { ++index; return *this; }
    /* iteration */
    iterator operator++(int) { iterator tmp = *this; ++(*this); return tmp; }
    /* iteration */
    iterator& operator--() { --index; return *this; }
    /* iteration */
    iterator operator--(int) { iterator tmp = *this; --(*this); return tmp; }

    /* comparison operators */
    bool operator==(iterator const& other) const { return index == other.index; }
    /* comparison operators */
    bool operator!=(iterator const& other) const { return index != other.index; }
};

class const_iterator {
private:
    /* bound indexed_storage */
    indexed_storage const* storage;
    /* current index */
    size_t index;
    /* constructor */
    const_iterator(indexed_storage const* st, size_t idx) : storage(st), index(idx) {}
    friend class indexed_storage<T>;
public:
    /* c++ semantics */
    using iterator_category = std::forward_iterator_tag;
    /* c++ semantics */
    using value_type = const_entry;
    /* c++ semantics */
    using difference_type = std::ptrdiff_t;
    /* c++ semantics */
    using pointer = const_entry*;
    /* c++ semantics */
    using reference = const_entry;

    /* constructor */
    const_iterator() : storage(nullptr), index(0) {}

    /* access operator */
    const_entry operator*() const {
        return {storage->lookup[index], storage->objects[index]};
    }

    /* iteration */
    const_iterator& operator++() { ++index; return *this; }
    /* iteration */
    const_iterator operator++(int) { const_iterator tmp = *this; ++(*this); return tmp; }
    /* iteration */
    const_iterator& operator--() { --index; return *this; }
    /* iteration */
    const_iterator operator--(int) { const_iterator tmp = *this; --(*this); return tmp; }

    /* comparison operators */

```

```

        bool operator==(const_iterator const& other) const { return index == other.index; }
        /* comparison operators */
        bool operator!=(const_iterator const& other) const { return index != other.index; }
    };

protected:
    /* vector of held objects */
    std::vector<T> objects;
    /* index to id lookup */
    std::vector<id_t> lookup;
    /* id to index lookup */
    std::vector<size_t> reverse;

    /* next available id */
    id_t next_id = 1;

private:
    /* init from predefined objects */
    void init_from_objects() {
        size_t n = objects.size();
        lookup.reserve(n);
        reverse.reserve(n + 1);

        reverse.push_back(0);

        for (size_t i = 0; i < n; ++i) {
            id_t new_id = next_id++;
            lookup.push_back(new_id);
            reverse.push_back(i);
        }
    }

public:
    /* constructor */
    indexed_storage() {
        reverse.push_back(0);
    }

    /* constructor from a T vector */
    explicit indexed_storage(std::vector<T> const& initial_objects)
        : objects(initial_objects) {
        init_from_objects();
    }

    /* constructor from a T vector using move semantics */
    explicit indexed_storage(std::vector<T>&& initial_objects) noexcept
        : objects(std::move(initial_objects)) {
        init_from_objects();
    }

    /* current size */
    id_t size() const { return static_cast<id_t>(objects.size()); }

    /* add element */
    id_t add(T const& object) {
        id_t new_id = next_id++;

        if (new_id >= reverse.size()) {

```



```

        reverse.resize(new_id + 1, 0);
    }

    reverse[new_id] = objects.size();
    objects.push_back(object);
    lookup.push_back(new_id);

    return new_id;
}

/* add element with move semantics */
id_t add(T&& object) {
    id_t new_id = next_id++;

    if (new_id >= reverse.size()) {
        reverse.resize(new_id + 1, 0);
    }

    reverse[new_id] = objects.size();
    objects.push_back(std::move(object));
    lookup.push_back(new_id);

    return new_id;
}

/* remove an element */
void remove(id_t id) {
    if (id == nullid || id >= reverse.size() ||
        (reverse[id] == 0 && (objects.empty() || lookup[0] != id))) {
        return;
    }

    size_t index_to_remove = reverse[id];
    size_t last_index = objects.size() - 1;

    if (index_to_remove != last_index) {
        T& last_obj = objects.back();
        id_t last_id = lookup.back();

        objects[index_to_remove] = std::move(last_obj);
        lookup[index_to_remove] = last_id;

        reverse[last_id] = index_to_remove;
    }

    objects.pop_back();
    lookup.pop_back();
    reverse[id] = 0;
}

/* access an element */
T& operator[](id_t id) {
    assert(id != nullid && id < reverse.size() && reverse[id] < objects.size());
    return objects[reverse[id]];
}

/* access an element */
T const& operator[](id_t id) const {

```

```

        assert(id != nullid && id < reverse.size() && reverse[id] < objects.size());
        return objects[reverse[id]];
    }

    /* iteration */
    iterator begin() { return iterator(this, 0); }
    /* iteration */
    iterator end() { return iterator(this, objects.size()); }

    /* iteration */
    const_iterator begin() const { return const_iterator(this, 0); }
    /* iteration */
    const_iterator end() const { return const_iterator(this, objects.size()); }

    /* iteration */
    const_iterator cbegin() const { return const_iterator(this, 0); }
    /* iteration */
    const_iterator cend() const { return const_iterator(this, objects.size()); }

    /* remove via an iterator */
    iterator erase(iterator it) {
        if (it != end()) {
            remove((*it).id);
        }
        return it;
    }

    /* remove via a const iterator */
    const_iterator erase(const_iterator it) {
        if (it != cend()) {
            const_cast<indexed_storage*>(this)->remove((*it).id);
        }
        return it;
    }

    /* contains a specific id */
    bool contains(id_t id) const {
        return id != nullid && id < reverse.size() &&
            (reverse[id] != 0 || (!objects.empty() && lookup[0] == id));
    }
};
}

```

game/game.h

```
#pragma once

#include <vector>
#include <memory>

#include "util/resource-loader.h"
#include "assets/asset-manager.h"
#include "input/input-backend.h"
#include "rendering/rendering-backend.h"
#include "audio/audio-backend.h"
#include "geometry/map-data.h"
#include "engine/world.h"
#include "audio/audio-mixer.h"
#include "rendering/renderer-2d.h"
#include "rendering/software-renderer.h"
#include "entities/player.h"

namespace game {
    class game {
        /* used resource loader */
        util::resource_loader rl;
        /* used asset manager */
        assets::asset_manager am;
        /* used input backend */
        std::unique_ptr<input::input_backend> input;
        /* used rendering backend */
        std::unique_ptr<rendering::rendering_backend> rb;
        /* used audio backend */
        std::unique_ptr<audio::audio_backend> ab;
        /* map */
        geometry::map_data md;
        /* audio mixer */
        audio::audio_mixer mix;
        /* 2d renderer (eg. for HUD) */
        rendering::renderer_2d r2d;
        /* 3d renderer */
        rendering::software_renderer sr;
        /* world */
        engine::world w;
        /* player pointer */
        entities::player* player_ptr;

        /* player fov */
        float fov;

        /* display a star wars like text scroll */
        void text_scroll(std::vector<std::string> const& text, assets::audio_clip_id const aid);
        /* display a text scroll from a resource */
        void ts_from_resource(std::string const& res_name, assets::audio_clip_id const aid);
        /* display the opening */
        void opening();
        /* display the ending */
        void ending();
        /* display the credits */
        void credits();
    };
}
```

```
        /* show the main menu */
        void show_main_menu();
        /* show the options menu */
        void show_options();
        /* game loop */
        void loop();
        /* overlay the hud */
        void draw_hud();
    public:
        /* constructor */
        game();
        /* run game */
        void run();
};
```

geometry/subsector.h

```
#pragma once

#include "util/resource.h"
#include "util/indexed-storage.h"
#include "rendering/sprite.h"
#include <vector>

namespace rendering {
    class software_renderer;
}

namespace geometry {
    class linedef;

    class subsector {
        /* lines belonging to a subsector */
        std::vector<util::indexed_storage<linedef>::id_t> lines;
        /* sprites belonging to a subsector */
        std::vector<rendering::sprite*> sprites;

    public:

        /* constructor */
        subsector() = default;
        /* constructor */
        subsector(std::vector<util::indexed_storage<linedef>::id_t> l);

        /* load subsectors from a binary */
        static std::vector<subsector> load_from_bin(util::resource const& res);

        /* remove a sprite from a subsector */
        void remove_sprite(rendering::sprite* spr);
        /* add a sprite to a subsector */
        void add_sprite(rendering::sprite* spr);

        friend rendering::software_renderer;
    };
}
```

geometry/sector.h

```
#pragma once

#include "assets/asset-manager.h"
#include "util/resource.h"
#include <vector>
#include <cstdint>

namespace rendering {
    class software_renderer;
}

namespace geometry {
    class sector {
        /* sector floor */
        float floor_height;
        /* ceiling floor */
        float ceiling_height;
        /* sector floor texture */
        assets::texture_id floor_tex;
        /* ceiling floor texture */
        assets::texture_id ceiling_tex;
        /* sector lighting */
        std::uint8_t light_level;

    public:

        /* constructor */
        sector(float fh, float ch, assets::texture_id ft, assets::texture_id ct, std::uint8_t light)

        /* load sectors from a binary */
        static std::vector<sector> load_from_bin(util::resource const& res);

        friend rendering::software_renderer;
    };
}
```

geometry/monster-spawn.h

```
#pragma once

#include <vector>
#include <cstdint>
#include "math/vec2.h"
#include "util/resource.h"
#include "util/componentized.h"
#include "entities/monster-factory.h"

namespace geometry {
    class monster_spawn : public util::componentized<monster_spawn> {
        std::uint32_t type;
        [[=util::component_field{}}]] math::vec2 pos;
        float z;

        friend class util::componentized<monster_spawn>;

    public:
        monster_spawn(std::uint32_t t, math::vec2 p, float height);

        static std::vector<monster_spawn> load_from_bin(util::resource const& res);

        friend std::unique_ptr<entities::monster> entities::make_monster(geometry::monster_spawn const& spawn);
    };
}
```

geometry/sidedef.h

```
#pragma once

#include "assets/ids.h"
#include "util/resource.h"
#include "util/indexed-storage.h"
#include <vector>

namespace rendering {
    class software_renderer;
}

namespace geometry {
    class sector;

    class sidedef {
        /* sector the sidedef is facing */
        util::indexed_storage<sector>::id_t facing_sector;
        /* portal upper texture */
        assets::texture_id upper_tex;
        /* wall texture */
        assets::texture_id middle_tex;
        /* portal lower texture */
        assets::texture_id lower_tex;

    public:

        /* constructor */
        sidedef(util::indexed_storage<sector>::id_t sector, assets::texture_id ut, assets::texture_i

        /* load subsectors from a binary */
        static std::vector<sidedef> load_from_bin(util::resource const& res);

        friend rendering::software_renderer;
    };
}
```


geometry/bsp-node.h

```
#pragma once

#include "math/vec2.h"
#include "util/indexed-storage.h"
#include "util/resource.h"
#include <vector>

namespace rendering {
    class software_renderer;
}

namespace geometry {
    class bsp_node {
    public:
        /* BSP node bounding box */
        struct bounding_box {
            float top, bottom, left, right;
        };

    private:

        /* partitioning line definition */
        math::vec2 pl_coord, pl_dir;
        /* front/back node bounding boxes */
        bounding_box front_box, back_box;
        /* front/back node ids */
        util::indexed_storage<bsp_node>::id_t front, back;
        /* leaf (subsector) bitmask */
        static constexpr util::indexed_storage<bsp_node>::id_t leaf_flag
            = 1 << (sizeof(util::indexed_storage<bsp_node>::id_t) * 8 - 1);

    public:

        /* is the front node a subsector */
        __attribute__((always_inline)) inline constexpr bool is_front_leaf() const;
        /* is the back node a subsector */
        __attribute__((always_inline)) inline constexpr bool is_back_leaf() const;
        /* the id of the front node */
        __attribute__((always_inline)) inline constexpr
            util::indexed_storage<bsp_node>::id_t get_front_index() const;
        /* the id of the back node */
        __attribute__((always_inline)) inline constexpr
            util::indexed_storage<bsp_node>::id_t get_back_index() const;

        /* on which side of the partitioning line does a point lie */
        bool is_pt_front_side(math::vec2 const& point) const;

        /* constructor */
        bsp_node(math::vec2 const pc, math::vec2 const pd, bounding_box const fb,
            bounding_box const bb, util::indexed_storage<bsp_node>::id_t f,
            util::indexed_storage<bsp_node>::id_t b);
        /* load subsectors from a binary */
        static std::vector<bsp_node> const load_from_bin(util::resource const& res);

        /* is any id a subsector */
    };
}
```

```

__attribute__((always_inline)) static inline constexpr bool
    is_leaf(util::indexed_storage<bsp_node>::id_t const id);
/* literal id of a node from a possibly bitmasked one */
__attribute__((always_inline)) static inline constexpr
    util::indexed_storage<bsp_node>::id_t
    get_id(util::indexed_storage<bsp_node>::id_t const raw);

    friend rendering::software_renderer;
};

__attribute__((always_inline)) inline constexpr bool geometry::bsp_node::is_front_leaf() const {
    return is_leaf(front);
}

__attribute__((always_inline)) inline constexpr bool geometry::bsp_node::is_back_leaf() const {
    return is_leaf(back);
}

__attribute__((always_inline)) inline constexpr util::indexed_storage<geometry::bsp_node>::id_t geom
    return get_id(front);
}

__attribute__((always_inline)) inline constexpr util::indexed_storage<geometry::bsp_node>::id_t geom
    return get_id(back);
}

__attribute__((always_inline)) inline constexpr bool geometry::bsp_node::is_leaf(util::indexed_stora
    return id & geometry::bsp_node::leaf_flag;
}

__attribute__((always_inline)) inline constexpr util::indexed_storage<geometry::bsp_node>::id_t geom
    return raw & ~geometry::bsp_node::leaf_flag;
}

```

geometry/linedef.h

```
#pragma once

#include "math/segment.h"
#include "util/resource.h"
#include "util/indexed-storage.h"
#include "util/componentized.h"
#include <vector>

namespace rendering {
    class software_renderer;
}

namespace geometry {
    class sidedef;

    class linedef : public util::componentized<linedef> {
        /* line segment */
        [=util::component_field{}] math::segment seg;

        /* front sidedef */
        util::indexed_storage<sidedef>::id_t front;
        /* back sidedef */
        util::indexed_storage<sidedef>::id_t back;

    public:

        /* constructor */
        linedef(math::vec2 const p0, math::vec2 const p1,
            util::indexed_storage<sidedef>::id_t const f,
            util::indexed_storage<sidedef>::id_t const b);

        /* load subsectors from a binary */
        static std::vector<linedef> load_from_bin(util::resource const& res);

        /* is it a wall */
        __attribute__((always_inline)) constexpr inline bool is_wall() const;
        /* is it a portal */
        __attribute__((always_inline)) constexpr inline bool is_portal() const;
        /* line direction */
        __attribute__((always_inline)) constexpr inline math::vec2 dir() const;
        /* line length */
        __attribute__((always_inline)) constexpr inline float len() const;

        friend util::componentized<linedef>;
        friend rendering::software_renderer;
    };
}

__attribute__((always_inline)) constexpr inline bool geometry::linedef::is_wall() const {
    return back == util::indexed_storage<sidedef>::nullid;
}

__attribute__((always_inline)) constexpr inline bool geometry::linedef::is_portal() const {
    return !is_wall();
}
```

```
}

__attribute__((always_inline)) constexpr inline math::vec2 geometry::linedef::dir() const {
    return (seg("point1"_f) - seg("point0"_f)).normalized();
}

__attribute__((always_inline)) constexpr inline float geometry::linedef::len() const {
    return seg.len();
}
```

geometry/pickup-spawn.h

```
#pragma once

#include <vector>
#include <cstdint>
#include <memory>
#include "math/vec2.h"
#include "util/resource.h"
#include "util/componentized.h"
#include "world_objects/pickup.h"
#include "assets/asset-manager.h"

namespace entities { class player; }
namespace audio { class audio_mixer; }
namespace engine { class world; }
namespace geometry { class pickup_spawn; }
namespace world_object {
    std::unique_ptr<world_object::pickup> make_pickup(geometry::pickup_spawn const& ps, entities::pl
}

namespace geometry {
    class pickup_spawn : public util::componentized<pickup_spawn> {
        std::uint32_t type;
        std::uint32_t subtype;
        [[=util::component_field{}]] math::vec2 pos;
        float z;

        friend class util::componentized<pickup_spawn>;

    public:
        pickup_spawn(std::uint32_t t, std::uint32_t st, math::vec2 p, float height);

        static std::vector<pickup_spawn> load_from_bin(util::resource const& res);

        friend std::unique_ptr<world_object::pickup> world_object::make_pickup(pickup_spawn const& p
    };
}
```

geometry/map-data.h

```
#pragma once

#include "sector.h"
#include "sidedef.h"
#include "linedef.h"
#include "subsector.h"
#include "bsp-node.h"
#include "monster-spawn.h"
#include "pickup-spawn.h"
#include "rendering/sprite.h"
#include "util/indexed-storage.h"
#include "util/componentized.h"

namespace rendering {
    class software_renderer;
}

namespace game {
    class game;
}

namespace geometry {
    class map_data : public util::componentized<map_data> {
        /* all sectors */
        util::indexed_storage<sector> sectors;
        /* all sidedefs */
        util::indexed_storage<sidedef> sidedefs;
        /* all linedefs */
        [[=util::component_field{}}} util::indexed_storage<linedef> linedefs;
        /* all subsectors */
        [[=util::ref_component_field{}}} util::indexed_storage<subsector> subsectors;
        /* BSP tree */
        util::indexed_storage<bsp_node> nodes;
        /* all monster spawns */
        std::vector<monster_spawn> monster_spawns;
        /* all pickup spawns */
        std::vector<pickup_spawn> pickup_spawns;

        /* root BSP node */
        [[=util::component_field{}}} util::indexed_storage<bsp_node>::id_t root_node_id;

    public:

        /* subsector from point */
        util::indexed_storage<subsector>::id_t get_subsector_id(math::vec2 const& pt) const;

        /* move sprite to a new position */
        void move_to(rendering::sprite* spr, math::vec2 const& new_pos);

        /* load from binaries */
        static map_data load_from_bin(util::resource const& sectors_res,
            util::resource const& sidedefs_res, util::resource const& linedefs_res,
            util::resource const& subsectors_res, util::resource const& nodes_res,
            util::resource const& monsters_res, util::resource const& pickups_res);
    };
}
```

```
    friend util::componentized<map_data>;  
    friend rendering::software_renderer;  
    friend game::game;  
};  
}
```

assets/ids.h

```
#pragma once
```

```
#include <cstdint>
```

```
namespace assets {  
    typedef std::int32_t texture_id;  
    typedef std::int32_t menu_id;  
    typedef std::int32_t audio_clip_id;  
}
```


assets/audio-clip.h

```
#pragma once
#define AUDIO_CLIP_H

#include <vector>
#include <cstdint>
#include "util/resource.h"
#include "util/componentized.h"
#include "audio/audio-backend.h"

namespace assets {
    class audio_clip : public util::componentized<audio_clip> {
        /* constructor */
        audio_clip(std::vector<std::uint8_t> const &data, audio::audio_format const &fmt);

        /* PCM data to play */
        [[=util::component_field{}]] std::vector<std::uint8_t> pcm_data;
        /* supported format */
        [[=util::component_field{}]] audio::audio_format format;
        /* length in frames */
        [[=util::component_field{}]] unsigned long total_frames;

    public:
        /* load from a binary */
        static audio_clip const load_from_bin(util::resource const &res);

        friend util::componentized<audio_clip>;
    };
}
```

assets/menu.h

```
#pragma once

#include <vector>
#include <string>
#include <string_view>
#include <functional>

#include "util/resource.h"
#include "util/resource-loader.h"
#include "texture.h"
#include "menu-element.h"
#include "input/input-backend.h"
#include "ids.h"

namespace rendering {
    class rendering_backend;
    class renderer_2d;
}

namespace assets {
    class menu {
        /* constructor */
        menu(std::vector<menu_element> els, texture_id const b);

        /* menu elements */
        std::vector<menu_element> elements;
        /* menu background */
        texture_id const bg;

    public:
        /* load from binaries */
        static menu load_from_bin(util::resource_loader &resld, util::resource const &res);

        /* conditionally replace format strings with values within elements */
        /* usage: */
        /* menu.set_formatter_for("{name}", [&](std::string_view tmpl) { */
        /*     std::string s(tmpl); */
        /*     for (std::size_t p; (p = s.find("{name}")) != std::string::npos;) */
        /*         s.replace(p, 7, player_name); */
        /*     return s; */
        /* }); */
        void selective_formatter(std::string_view key_filter,
                                std::function<std::string(std::string_view)> fn);

        /* add a formatter to all elements */
        void formatter_all(std::function<std::string(std::string_view)> fn);

        /* display a menu */
        int display(rendering::renderer_2d const &r2d, rendering::rendering_backend &rb,
                    input::input_backend &in, std::vector<texture> const& ui_tx) const;
    };
}
```

assets/menu-element.h

```
#pragma once

#include <vector>
#include <string>
#include <functional>

#include "util/componentized.h"
#include "util/resource.h"
#include "texture.h"
#include "ids.h"

namespace rendering {
    class renderer_2d;
}

namespace input {
    struct mouse_state;
}

namespace assets {
    class menu_element {
        /* constructor */
        menu_element(int f, float bx, float by, float ex, float ey,
            texture_id const b, std::string s, int cw, int ch, std::uint8_t r,
            std::uint8_t g, std::uint8_t b_col, float rlm);

        /* function within a menu */
        int function;
        /* dimentions relative to screen size */
        float const begin_x, begin_y, end_x, end_y;
        /* element background */
        texture_id const bg;
        /* element text */
        std::string fmt_template;
        /* set formatter */
        std::function<std::string(std::string_view)> formatter;
        /* character dimentions in pixels */
        int char_w, char_h;
        /* text color */
        std::uint8_t col_r, col_g, col_b;
        /* left margin, relative to element width */
        float relative_left_margin;

        /* run template through formatter */
        std::string resolve_text() const;
        /* pack r, g, b into color */
        std::uint32_t text_color() const;
        /* set a formatter */
        void selective_fmt(std::string_view key_filter,
            std::function<std::string(std::string_view)> fn);
        /* render an element */
        int render(rendering::renderer_2d const &r2d, std::vector<texture> const& ui_tx,
            int sw, int sh, input::mouse_state const &ms) const;

    public:
```

```
    /* load from a binary */  
    static menu_element load_from_bin(util::resource const &res);  
  
    friend class menu;  
};  
}
```

assets/asset-manager.h

```
#pragma once

#include <vector>
#include <string>
#include <string_view>

#include "util/resource.h"
#include "util/resource-loader.h"
#include "asset-pack.h"
#include "input/input-backend.h"
#include "ids.h"

namespace rendering {
    class renderer_2d;
    class rendering_backend;
}

namespace assets {
    class asset_manager {
        /* resource loader reference */
        util::resource_loader &rl;
        /* all loaded asset packs */
        std::vector<asset_pack> asset_packs;
        /* current asset pack */
        unsigned int cur_set;

        /* constructor */
        asset_manager(util::resource_loader &resld, std::vector<asset_pack> packs);

    public:
        /* load all assets */
        static asset_manager load(util::resource_loader &resld);

        /* next asset pack */
        void cycle_set();

        /* lookup textures */
        texture const& wall_tx_by_id(texture_id const id) const;
        /* lookup textures */
        texture const& sprite_tx_by_id(texture_id const id) const;
        /* lookup textures */
        texture const& flat_tx_by_id(texture_id const id) const;
        /* lookup textures */
        texture const& ui_tx_by_id(texture_id const id) const;
        /* lookup a menu */
        menu &menu_by_id(menu_id const id);
        /* lookup an audio clip */
        audio_clip const& audio_clip_by_id(audio_clip_id const id) const;

        /* display a menu */
        int display_menu(menu_id const id, rendering::renderer_2d const& r2d,
            rendering::rendering_backend &rb, input::input_backend &in);
    };
}
```

assets/texture.h

```
#pragma once

#include <vector>
#include <cstdint>
#include <cstdint>

#include "util/resource.h"
#include "util/componentized.h"

namespace assets {
    class texture : public util::componentized<texture> {
        /* constructor */
        texture(std::vector<std::uint32_t> const &t, std::uint32_t const w,
                std::uint32_t const h, bool const transparent = false);

        /* pixel array */
        [=util::component_field{}] std::vector<std::uint32_t> pixels;
        /* texture dimentions */
        [=util::component_field{}] std::uint32_t width, height;

        /* whether or not the texture has transparency */
        [=util::component_field{}] bool has_transparency;

    public:
        /* load from a binary */
        static texture const load_from_bin(util::resource const &res);

        friend util::componentized<texture>;
    };
}
```

assets/asset-pack.h

```
#pragma once

#include <vector>
#include <cstdint>
#include <string_view>
#include <unordered_map>

#include "util/resource.h"
#include "util/resource-loader.h"
#include "texture.h"
#include "menu-element.h"
#include "menu.h"
#include "audio-clip.h"
#include "ids.h"

namespace assets {
    class asset_pack {
        /* all textures */
        std::vector<texture> wall_textures;
        /* all textures */
        std::vector<texture> sprite_textures;
        /* all textures */
        std::vector<texture> flat_textures;
        /* all textures */
        std::vector<texture> ui_textures;
        /* all menus */
        std::vector<menu> menus;
        /* all audio clips */
        std::vector<audio_clip> audio_clips;

        /* constructor */
        asset_pack(std::vector<texture> walls, std::vector<texture> sprites,
            std::vector<texture> flats, std::vector<texture> ui,
            std::vector<menu> ms, std::vector<audio_clip> clips);

        /* load textures from a meta file */
        static std::vector<texture> tx_from_meta(util::resource_loader &resld,
            std::string_view meta_path);
        /* load menus from a meta file */
        static std::vector<menu> menus_from_meta(util::resource_loader &resld,
            std::string_view meta_path);
        /* load audio clips from a meta file */
        static std::vector<audio_clip> clips_from_meta(util::resource_loader &resld,
            std::string_view meta_path);
        /* parse keys in a declaration meta file */
        static std::unordered_map<std::string, std::string>
            parse_meta_keys(std::string const& content);

    public:
        /* load from a binary */
        static asset_pack load(util::resource_loader &resld,
            std::string_view pack_meta_path);

        /* lookup textures */
    };
}
```

```

texture const& wall_tx_by_id(texture_id const id) const;
/* lookup textures */
texture const& sprite_tx_by_id(texture_id const id) const;
/* lookup textures */
texture const& flat_tx_by_id(texture_id const id) const;
/* lookup textures */
texture const& ui_tx_by_id(texture_id const id) const;
/* lookup a menu */
menu &menu_by_id(menu_id const id);
/* lookup an audio clip */
audio_clip const& audio_clip_by_id(audio_clip_id const id) const;

/* display a menu */
int display_menu(menu_id const id, rendering::renderer_2d const& r2d,
    rendering::rendering_backend &rb, input::input_backend &in);
};
}

```


systems/health_systems.h

```
#pragma once

#include <vector>
#include <memory>
#include <algorithm>

#include "combat/status-effect.h"
#include "util/indexed-storage.h"
#include "util/componentized.h"

namespace engine {class actor;}

namespace systems {
    class health_system : public util::componentized<health_system> {
        [=util::component_field{}] float current_hp;
        [=util::component_field{}] float max_hp;
        [=util::component_field{}] float armor;
        [=util::component_field{}] float max_armor;

        [=util::component_field{}] std::vector<std::unique_ptr<combat::status_effect>> active_effects;

        friend class util::componentized<health_system>;

    public:
        health_system(float hp, float max, float arm, float max_arm);

        void apply_damage(float amount);
        void apply_heal(float amount);
        void apply_shield(float amount);
        void apply_true_damage(float amount);

        void add_effect(std::unique_ptr<combat::status_effect> effect, engine::actor& owner);
        void process_effects(float dt, engine::actor& owner);

        bool is_dead() const;
    };
}
```

audio/alsa/backend.h

```
#pragma once

#include <alsa/asoundlib.h>
#include "audio/audio-backend.h"

namespace audio {
    namespace alsa {
        class backend : public audio::audio_backend {
        private:
            /* error check */
            bool is_bad;

            /* also pcm */
            snd_pcm_t* pcm_handle;
            /* supported format */
            audio_format fmt;
            /* supported is currently paused */
            bool paused;

            /* convert to alsa */
            snd_pcm_format_t to_alsa_format(unsigned int bits) const;

            /* configure hardware */
            bool configure_hw_params();

        public:
            /* constructor */
            backend();
            /* destructor */
            ~backend() override;

            /* set a new format */
            bool open(audio_format const& format) override;
            /* stop */
            void close() override;
            /* send pcm data */
            long write(void const* data, unsigned long frames) override;
            /* drain the pcm buffer */
            void drain() override;
            /* pause audio */
            void pause() override;
            /* resume audio */
            void resume() override;
            /* componentized-like api */
            audio_format operator()(util::component_tag<"current_format">) const override;
            /* error checking */
            bool bad() const override;
        };
    }
}
```

audio/audio-mixer.h

```
#pragma once
#define AUDIO_MIXER_H

#include "audio-backend.h"
#include "assets/audio-clip.h"
#include <vector>

namespace audio {

    class audio_mixer {
    private:
        /* one of mixed sounds */
        struct playing_sound {
            assets::audio_clip const* clip;
            unsigned long current_frame;
        };

        /* backend ref */
        audio_backend &target;
        /* supported format */
        audio_format mix_format;
        /* all currently playing sounds */
        std::vector<playing_sound> active_sounds;

    public:
        /* constructor */
        explicit audio_mixer(audio_backend &tgt, audio_format const& fmt);

        /* queue a sound */
        void play(assets::audio_clip const& clip);

        /* stop all sounds */
        void stop_all();

        /* play audio */
        void step(unsigned long frames_to_mix);

        /* are there no sounds playing */
        bool is_silent() const;
    };
}
```

audio/audio-backend.h

```
#pragma once

#include <cstddef>
#include <stdint>
#include <string>
#include <vector>

#include "util/componentized.h"

namespace audio {

    /* supported format struct */
    struct audio_format {
        unsigned int sample_rate;
        unsigned int channels;
        unsigned int bits_per_sample;
    };

    class audio_backend {
    public:
        /* virtual destructor */
        virtual ~audio_backend() = default;

        /* set a new format */
        virtual bool open(audio_format const& fmt) = 0;
        /* stop */
        virtual void close() = 0;
        /* send pcm data */
        virtual long write(void const* data, unsigned long frames) = 0;
        /* drain the pcm buffer */
        virtual void drain() = 0;

        /* pause audio */
        virtual void pause() = 0;
        /* resume audio */
        virtual void resume() = 0;
        /* componentized-like api */
        virtual audio_format operator()(util::component_tag<"current_format">) const = 0;
        /* error checking */
        virtual bool bad() const = 0;
    };
}
```

engine/actor.h

```
#pragma once

#include "renderable-entity.h"
#include "systems/health_systems.h"
#include "util/componentized.h"

namespace combat { class charmed; class slowed; }

namespace engine {

    enum class faction {
        player,
        enemy,
        neutral
    };

    class actor : public renderable_entity, public util::componentized<actor> {
    public:
        using util::componentized<actor>::operator();
        using rendering::sprite::operator();
    protected:
        /* current actor health */
        [=util::component_field{}] systems::health_system health;
        /* movement */
        float movement_speed;
        /* player / enemy / neither */
        faction team;

        friend class util::componentized<actor>;
        friend class combat::charmed;
        friend class combat::slowed;
        friend class projectile;

    public:
        /* constructor */
        actor(math::vec2 const p, float const z, assets::texture_id const tex,
            float const is, float const hp, float const shield,
            float const move_speed, faction const this_team);

        /* take damage */
        virtual void take_damage(float const dmg);
        /* take damage passing through shield */
        virtual void take_true_damage(float const dmg);
        /* heal */
        virtual void heal(float const amount);
        /* restore shield */
        virtual void add_shield(float const amount);
        /* apply an affect */
        virtual void add_effect(std::unique_ptr<combat::status_effect> effect);

        /* whether or not the actor is dead */
        bool is_dead() const;

        /* entity tick */
        virtual void update(float dt) override;
```

```
}  
};
```

engine/entity.h

```
#pragma once

namespace engine {
    class entity {
    public:
        /* tick an entity */
        virtual void update(float const dt) = 0;
        /* virtual destructor */
        virtual ~entity() = default;
    };
}
```

engine/projectile.h

```
#pragma once

#include "renderable-entity.h"
#include "actor.h"
#include "world.h"
#include "math/vec2.h"
#include "combat/status-effect.h"
#include <memory>
#include <functional>

namespace geometry { class map_data; }
namespace combat { namespace weapons { class projectile_firing_mode; } }
namespace entities { class monster; class monster_boss; }

namespace engine {

    class projectile : public renderable_entity {
        friend class combat::weapons::projectile_firing_mode;
        friend class entities::monster;
        friend class entities::monster_boss;
    protected:
        math::vec2 direction;
        float speed;
        float damage;
        float lifetime;
        float hit_radius;
        faction team;
        std::function<std::unique_ptr<combat::status_effect>()> on_hit_effect;

        world* world_ref = nullptr;
        geometry::map_data* map_ref = nullptr;
        util::indexed_storage<std::unique_ptr<entity>>::id_t self_id = 0;

    public:
        projectile(math::vec2 pos, float z, assets::texture_id tex, float scale,
                   math::vec2 dir, float spd, float dmg, float life,
                   faction f, float radius = 8.0f);

        void update(float dt) override;
    };
}
```


engine/world.h

```
#pragma once
#include <vector>
#include <memory>

#include "util/indexed-storage.h"
#include "entity.h"

namespace engine {
    class world {
    private:
        /* all entities */
        util::indexed_storage<std::unique_ptr<entity>> entities;
        /* entities to be removed at the end of a tick */
        std::vector<util::indexed_storage<std::unique_ptr<entity>>::id_t>
            deleted_entities;

    public:

        /* constructor */
        world();

        world(const world&) = delete;
        world& operator=(const world&) = delete;

        /* tick all entities */
        void update(float const dt);

        /* get an entity */
        entity& operator[](
            util::indexed_storage<std::unique_ptr<entity>>::id_t const id);
        /* get an entity */
        entity const& operator[](
            util::indexed_storage<std::unique_ptr<entity>>::id_t const id) const;
        /* all entities */
        util::indexed_storage<std::unique_ptr<entity>> const& get_entities() const;

        /* add an entity */
        util::indexed_storage<std::unique_ptr<entity>>::id_t
            register_entity(std::unique_ptr<entity> e);

        /* delete an entity */
        void delete_entity(
            util::indexed_storage<std::unique_ptr<entity>>::id_t const id);

        /* entity ptr (can be NULL) */
        entity* entity_from_id(
            util::indexed_storage<std::unique_ptr<entity>>::id_t const id) const;
    };
}
```

engine/renderable-entity.h

```
#pragma once
#include "entity.h"
#include "rendering/sprite.h"

namespace engine {
    class renderable_entity : public entity, public rendering::sprite {
    public:
        /* constructor */
        renderable_entity(math::vec2 const p, float const z, assets::texture_id const tex, float const is)
            : entity(), rendering::sprite(p, z, tex, is) {}

        //renderable_entity() : rendering::sprite() {}

        /* virtual destructor */
        virtual ~renderable_entity() = default;
    };
}
```

world_objects/pickup-factory.h

```
#pragma once

#include <memory>
#include <cstdint>
#include "math/vec2.h"
#include "world_objects/pickup.h"

namespace geometry {
    class map_data;
    class pickup_spawn;
}

namespace engine { class world; }
namespace entities { class player; }
namespace audio { class audio_mixer; }
namespace assets { class asset_manager; }

namespace world_object {
    std::unique_ptr<pickup> make_pickup(geometry::pickup_spawn const& ps, entities::player& player,
}
```

world_objects/pickup.h

```
#pragma once

#include "engine/renderable-entity.h"
#include "math/vec2.h"
#include "util/indexed-storage.h"
#include "geometry/subsector.h"

namespace entities { class player; }
namespace geometry { class map_data; }

namespace world_object {

    class pickup : public engine::renderable_entity {
        float pickup_radius;
        entities::player& player_ref;
        geometry::map_data& map_ref;
        util::indexed_storage<geometry::subsector>::id_t subsector_id;
        bool consumed = false;

    public:
        pickup(math::vec2 pos, float z, assets::texture_id tex,
            entities::player& p, geometry::map_data& md,
            util::indexed_storage<geometry::subsector>::id_t sub_id,
            float radius = 20.0f, float scale = 1.0f);

        void update(float dt) override;
        bool is_consumed() const;

        virtual void on_pickup(entities::player& p) = 0;
        virtual ~pickup() = default;
    };
}
```

world_objects/weapon-pickup.h

```
#pragma once

#include <memory>
#include "pickup.h"

namespace combat { namespace weapons { class weapon; } }

namespace world_object {

    class weapon_pickup : public pickup {
        std::unique_ptr<combat::weapons::weapon> provided_weapon;
        int slot;
    public:
        weapon_pickup(math::vec2 pos, float z, assets::texture_id tex,
            std::unique_ptr<combat::weapons::weapon> w, int weapon_slot,
            entities::player& p, geometry::map_data& md,
            util::indexed_storage<geometry::subsector>::id_t sub_id,
            float radius = 25.0f, float scale = 0.4f);
        void on_pickup(entities::player& p) override;
    };

}
```

world_objects/armor-pickup.h

```
#pragma once
```

```
#include "pickup.h"
```

```
namespace world_object {
```

```
    class armor_pickup : public pickup {
```

```
        float armor_amount;
```

```
    public:
```

```
        armor_pickup(math::vec2 pos, float z, assets::texture_id tex,
```

```
                    float amount, entities::player& p,
```

```
                    geometry::map_data& md,
```

```
                    util::indexed_storage<geometry::subsector>::id_t sub_id,
```

```
                    float radius = 20.0f);
```

```
        void on_pickup(entities::player& p) override;
```

```
    };
```

```
}
```

world_objects/health-pickup.h

```
#pragma once

#include "pickup.h"

namespace world_object {

    class health_pickup : public pickup {
        float heal_amount;
    public:
        health_pickup(math::vec2 pos, float z, assets::texture_id tex,
            float amount, entities::player& p,
            geometry::map_data& md,
            util::indexed_storage<geometry::subsector>::id_t sub_id,
            float radius = 20.0f);
        void on_pickup(entities::player& p) override;
    };

}
```

world_objects/ammo-pickup.h

```
#pragma once

#include "pickup.h"
#include "entities/player.h"

namespace world_object {

    template<typename WeaponT>
    class ammo_pickup : public pickup {
        int amount;
    public:
        ammo_pickup(math::vec2 position, float z, assets::texture_id tex,
                    int amt, entities::player& pl,
                    geometry::map_data& md,
                    util::indexed_storage<geometry::subsector>::id_t sub_id,
                    float radius = 20.0f)
            : pickup(position, z, tex, pl, md, sub_id, radius), amount(amt) {}

        void on_pickup(entities::player& p) override {
            p.resupply<WeaponT>(amount);
        }
    };

}
```


combat/burning.h

```
#pragma once

#include "status-effect.h"

namespace combat
{
    class burning : public status_effect {
    public:
        burning(float const dur, unsigned int intens);

        void affect(engine::actor& target) override;
    };
}
```

combat/charmed.h

```
#pragma once

#include "status-effect.h"

namespace combat
{
    class charmed : public status_effect {
    public:
        charmed(float const dur, unsigned int intens);

        void on_apply(engine::actor& target) override;
        void on_expire(engine::actor& target) override;
    };
}
```

combat/slowed.h

```
#pragma once

#include "status-effect.h"

namespace combat
{
    class slowed : public status_effect {
    public:
        slowed(float const dur, unsigned int intens);

        void on_apply(engine::actor& target) override;
        void on_expire(engine::actor& target) override;
    };
}
```

combat/weapons/firing-mode.h

```
#pragma once

#include "math/vec2.h"

namespace combat {
    namespace weapons {
        class firing_mode {
        public:
            virtual void spawn_bullet(math::vec2 pos, float angle, float damage) = 0;
            virtual ~firing_mode() = default;
        };
    }
}
```

combat/weapons/smg.h

```
#pragma once
#include "weapon.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace combat {
    namespace weapons {
        class smg : public weapon {
        public:
            explicit smg(geometry::map_data const& map,
                        engine::world const& world,
                        audio::audio_mixer& mix,
                        assets::asset_manager const& am);
        };
    }
}
```

combat/weapons/projectile-firing-mode.h

```
#pragma once

#include "firing-mode.h"
#include "engine/actor.h"
#include "assets/ids.h"

namespace engine { class world; }
namespace geometry { class map_data; }

namespace combat {
    namespace weapons {

        class projectile_firing_mode : public firing_mode {
            engine::world& world_ref;
            geometry::map_data& map_ref;
            engine::faction team;
            assets::texture_id projectile_tex;
            float projectile_speed;
            float projectile_lifetime;
            float projectile_scale;

        public:
            projectile_firing_mode(engine::world& w, geometry::map_data& md,
                                   engine::faction f,
                                   assets::texture_id tex, float spd,
                                   float lifetime = 5.0f, float scale = 0.5f);

            void spawn_bullet(math::vec2 pos, float angle, float damage) override;
        };
    }
}
```

combat/weapons/katana.h

```
#pragma once
#include "weapon.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace combat {
    namespace weapons {
        class katana : public weapon {
        public:
            katana(geometry::map_data const& map, engine::world const& world,
                  audio::audio_mixer& mix, assets::asset_manager const& am);

            bool can_fire() const override;
            void fire(math::vec2 pos, float angle) override;
            void reload() override;
        };
    }
}
```

combat/weapons/hitscan-firing-mode.h

```
#pragma once

#include "firing-mode.h"
#include "geometry/map-data.h"
#include "engine/actor.h"

namespace engine { class world; }

namespace combat {
    namespace weapons {
        class hitscan_firing_mode : public firing_mode {
            geometry::map_data const& map;
            engine::world const& world_ref;
            float max_range;
            float hit_radius;

        public:
            hitscan_firing_mode(geometry::map_data const& map,
                               engine::world const& world,
                               float range = 8192.0f,
                               float radius = 32.0f);

            void spawn_bullet(math::vec2 pos, float angle, float damage) override;
        };
    }
}
```


combat/weapons/pistol.h

```
#pragma once
#include "weapon.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace combat {
    namespace weapons {
        class pistol : public weapon {
        public:
            explicit pistol(geometry::map_data const& map,
                           engine::world const& world,
                           audio::audio_mixer& mix,
                           assets::asset_manager const& am);
        };
    }
}
```

combat/weapons/shotgun.h

```
#pragma once
#include "weapon.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace combat {
    namespace weapons {
        class shotgun : public weapon {
        public:
            static constexpr int    pellet_count = 8;
            static constexpr float spread        = 0.2618f;

            explicit shotgun(geometry::map_data const& map,
                            engine::world const& world,
                            audio::audio_mixer& mix,
                            assets::asset_manager const& am);
            void fire(math::vec2 pos, float angle) override;
        };
    }
}
```

combat/weapons/rifle.h

```
#pragma once
#include "weapon.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace combat {
    namespace weapons {
        class rifle : public weapon {
        public:
            explicit rifle(geometry::map_data const& map,
                           engine::world const& world,
                           audio::audio_mixer& mix,
                           assets::asset_manager const& am);
        };
    }
}
```

combat/weapons/weapon.h

```
#pragma once

#include <memory>

#include "math/vec2.h"
#include "firing-mode.h"
#include "assets/ids.h"
#include "util/componentized.h"

namespace audio { class audio_mixer; }
namespace assets { class asset_manager; }

namespace combat
{
    namespace weapons {
        class weapon : public util::componentized<weapon> {
            friend class util::componentized<weapon>;
        protected:
            std::unique_ptr<firing_mode> ammo;
            [[=util::component_field{}]] int ammo_count;
            int max_ammo;
            [[=util::component_field{}]] int reserve_mags;
            float fire_rate;
            float last_shot_time;
            float damage;
            audio::audio_mixer& mixer;
            assets::asset_manager const& assets;
            assets::audio_clip_id fire_sound_id;
            assets::audio_clip_id reload_sound_id;
            [[=util::component_field{}]] float reload_duration;
            [[=util::component_field{}]] float reload_timer;
            [[=util::component_field{}]] bool reloading;

            void finish_reload();
        public:
            virtual bool can_fire() const;
            void tick(float dt);
            void resupply(int amount);

            virtual void fire(math::vec2 pos, float angle);
            virtual void reload();
            virtual ~weapon() = default;
        protected:
            weapon(std::unique_ptr<firing_mode> firing, int max, float rate, float dmg,
                int reserve,
                audio::audio_mixer& mix,
                assets::asset_manager const& am,
                assets::audio_clip_id fire_snd = -1,
                assets::audio_clip_id reload_snd = -1,
                float reload_dur = 1.5f);
    };
}
}
```

combat/weapons/sniper-rifle.h

```
#pragma once
#include "weapon.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace combat {
    namespace weapons {
        class sniper_rifle : public weapon {
        public:
            explicit sniper_rifle(geometry::map_data const& map,
                                engine::world const& world,
                                audio::audio_mixer& mix,
                                assets::asset_manager const& am);
        };
    }
}
```

combat/weapons/plasma-gun.h

```
#pragma once
#include "weapon.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace combat {
    namespace weapons {
        class plasma_gun : public weapon {
        public:
            explicit plasma_gun(geometry::map_data& map,
                               engine::world& world,
                               audio::audio_mixer& mix,
                               assets::asset_manager const& am);
        };
    }
}
```

combat/status-effect.h

```
#pragma once

#include "math/vec2.h"

namespace engine {class actor;}

namespace combat
{
    class status_effect {
    protected:
        float duration;
        unsigned int intensity;
        float tick_interval;
        float tick_timer;
    public:
        status_effect(float const dur, float tick_inter, unsigned int intens);

        virtual void on_apply(engine::actor&);
        virtual void on_expire(engine::actor&);
        virtual void affect(engine::actor&);
        virtual ~status_effect() = default;

        bool tick(float dt);
        bool is_expired() const;
    };
}
```

entities/monster-factory.h

```
#pragma once

#include <memory>
#include <cstdint>
#include "math/vec2.h"
#include "entities/monster.h"

namespace engine { class world; }

namespace geometry {
    class monster_spawn;
    class map_data;
}

namespace entities {
    std::unique_ptr<monster> make_monster(geometry::monster_spawn const& ms, engine::actor& target,
}
```


entities/slug-projectile.h

```
#pragma once

#include "engine/projectile.h"

namespace entities {

    class slug_projectile : public engine::projectile {
    public:
        using projectile::projectile;
    };

}
```

entities/monsters/monster-magic.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_magic : public monster {
```

```
        float charge_time;
```

```
        float charge_timer;
```

```
        bool is_charging;
```

```
        float post_fire_cooldown;
```

```
        float sidestep_timer;
```

```
        float sidestep_sign;
```

```
    public:
```

```
        monster_magic(math::vec2 const p, float const z, engine::actor& target, geometry::map_data&
```

```
        void update(float dt) override;
```

```
};
```

```
}
```

entities/monsters/monster-elite-swift.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_elite_swift : public monster {
```

```
        float charge_speed;
```

```
        bool is_charging;
```

```
        float charge_timer;
```

```
        float charge_cd;
```

```
        float circle_angle;
```

```
        float circle_radius;
```

```
    public:
```

```
        monster_elite_swift(math::vec2 const p, float const z, engine::actor& target, geometry::map_
```

```
        void update(float dt) override;
```

```
};
```

```
}
```

entities/monsters/monster-basic.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_basic : public monster {  
    public:
```

```
        monster_basic(math::vec2 const p, float const z, engine::actor& target, geometry::map_data& map_data)
```

```
        void update(float dt) override;
```

```
    };
```

```
}
```

entities/monsters/monster-trapper.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_trapper : public monster {
```

```
        int    max_traps;
```

```
        int    traps_placed;
```

```
        float  trap_timer;
```

```
        float  trap_interval;
```

```
        float  wander_timer;
```

```
        float  wander_sign;
```

```
    public:
```

```
        monster_trapper(math::vec2 const p, float const z, engine::actor& target, geometry::map_data
```

```
        void update(float dt) override;
```

```
};
```

```
}
```

entities/monsters/monster-duzy-gruby.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_Duzy_Gruby : public monster {  
    public:
```

```
        monster_Duzy_Gruby(math::vec2 const p, float const z, engine::actor& target, geometry::map_d
```

```
        void update(float dt) override;
```

```
    };
```

```
}
```

entities/monsters/monster-spawner.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_spawner : public monster {
```

```
        int    max_spawns;
```

```
        int    current_spawns;
```

```
        float  spawn_interval;
```

```
        float  spawn_timer;
```

```
    public:
```

```
        monster_spawner(math::vec2 const p, float const z, engine::actor& target, geometry::map_data
```

```
        void update(float dt) override;
```

```
};
```

```
}
```

entities/monsters/monster-maly-szybki.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_Maly_Szybki : public monster {
```

```
        bool is_dashing;
```

```
        float dash_timer;
```

```
        float dash_cooldown;
```

```
    public:
```

```
        monster_Maly_Szybki(math::vec2 const p, float const z, engine::actor& target, geometry::map_
```

```
        void update(float dt) override;
```

```
};
```

```
}
```


entities/monsters/monster-elite-tank.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_elite_tank : public monster {
```

```
        bool  melee_mode;
```

```
        float melee_threshold;
```

```
        float heavy_timer;
```

```
        float heavy_cd;
```

```
    public:
```

```
        monster_elite_tank(math::vec2 const p, float const z, engine::actor& target, geometry::map_d
```

```
        void update(float dt) override;
```

```
};
```

```
}
```

entities/monsters/monster-ranged.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_ranged : public monster {
```

```
        float preferred_dist;
```

```
    public:
```

```
        monster_ranged(math::vec2 const p, float const z, engine::actor& target, geometry::map_data&
```

```
        void update(float dt) override;
```

```
    };
```

```
}
```

entities/monsters/monster-all-rounder.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_all_rounder : public monster {  
        bool   melee_mode;  
        float  melee_threshold;
```

```
    public:
```

```
        monster_all_rounder(math::vec2 const p, float const z, engine::actor& target, geometry::map_  
        void update(float dt) override;
```

```
    };
```

```
}
```

entities/monsters/monster-assault.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_assault : public monster {
```

```
        int    burst_size;
```

```
        float  burst_interval;
```

```
        int    burst_remaining;
```

```
        float  burst_timer;
```

```
        float  burst_cooldown;
```

```
        float  strafe_sign;
```

```
        float  strafe_timer;
```

```
    public:
```

```
        monster_assault(math::vec2 const p, float const z, engine::actor& target, geometry::map_data
```

```
        void update(float dt) override;
```

```
};
```

```
}
```

entities/monsters/monster-boss.h

```
#pragma once

#include "entities/monster.h"
#include "engine/world.h"
#include "geometry/map-data.h"
#include <vector>

namespace entities {

    class monster_boss : public monster {
        // phase tracking
        int current_phase = 1;
        float max_hp_val;

        // ranged: 4 hitscans with slow
        float ranged_cooldown = 0.0f;
        static constexpr float ranged_cd_max = 3.0f;
        static constexpr int projectile_count = 4;
        static constexpr float projectile_spread = 0.15f;

        // melee: burning
        // uses base attack_cooldown / attack_cd_max

        // charge (phase 2+3)
        bool is_charging = false;
        float charge_timer = 0.0f;
        float charge_cooldown = 0.0f;
        float post_charge_stun = 0.0f;
        math::vec2 charge_dir{0.0f, 0.0f};
        static constexpr float charge_speed_mult = 5.0f;
        static constexpr float charge_duration = 1.2f;
        static constexpr float charge_cd_max = 6.0f;
        static constexpr float stun_duration = 2.0f;

        // channel (phase 3)
        bool is_channeling = false;
        float channel_timer = 0.0f;
        float flash_timer = 0.0f;
        bool phase3_debuffed = false;

        // spawned minions tracking
        std::vector<util::indexed_storage<std::unique_ptr<engine::entity>>::id_t> minion_ids;

        // combat stance
        bool wants_melee = false;
        float stance_timer = 10.0f;

        geometry::map_data& boss_map_ref;

        float hp_ratio() const;
        void update_phase();
        void phase1_ai(float dt, float dist);
        void phase2_ai(float dt, float dist);
        void phase3_ai(float dt, float dist);
        void ranged_attack_slow();
    };
}
```

```
void melee_attack_burn();
void start_charge();
void update_charge(float dt);
void start_channel();
bool minions_alive() const;

public:
    monster_boss(math::vec2 const p, float const z, engine::actor& target, geometry::map_data& m

    bool channeling() const;
    float flash_phase() const;

    void update(float dt) override;
};

}
```

entities/monsters/monster-sniper.h

```
#pragma once
```

```
#include "entities/monster.h"
```

```
namespace entities {
```

```
    class monster_sniper : public monster {  
        float shoot_interval;  
        float aim_timer;
```

```
    public:
```

```
        monster_sniper(math::vec2 const p, float const z, engine::actor& target, geometry::map_data&  
        void update(float dt) override;
```

```
    };
```

```
}
```

entities/plasma-projectile.h

```
#pragma once

#include "engine/projectile.h"

namespace entities {

    class plasma_projectile : public engine::projectile {
    public:
        using projectile::projectile;
    };

}
```


entities/player.h

```
#pragma once

#include <vector>
#include <memory>

#include "engine/actor.h"
#include "math/vec2.h"
#include "combat/weapons/weapon.h"
#include "util/componentized.h"

namespace geometry { class map_data; }
namespace engine { class world; }

namespace entities {
    class player : public engine::actor, public util::componentized<player> {
    public:
        using util::componentized<player>::operator();
        using engine::actor::operator();

    protected:
        [[=util::component_field{}]] std::vector<std::unique_ptr<combat::weapons::weapon>> weapons;
        float sensitivity;
        [[=util::component_field{}]] int current_weapon_index;
        geometry::map_data* map_ref = nullptr;
        engine::world* world_ref = nullptr;
        float collision_radius = 16.0f;
        float walk_speed;
        float sprint_speed;

        friend class util::componentized<player>;

    public:

        player(math::vec2 const p, float const z, assets::texture_id const tex, float const is, float const fr);

        void equip(int slot, std::unique_ptr<combat::weapons::weapon> wpn);

        void update(float dt) override;
        void move(math::vec2 direction);
        void rotate(float yaw);
        void shoot();
        void reload();
        void switch_weapons(int index);
        void start_sprint();
        void stop_sprint();

        template<typename WeaponT>
        bool resupply(int amount) {
            for (auto& w : weapons) {
                if (!w) continue;
                if (dynamic_cast<WeaponT*>(&*w)) {
                    w->resupply(amount);
                    return true;
                }
            }
        }
    }
}
```

```
        return false;
    }
};
}
```

entities/monster.h

```
#pragma once

#include "engine/actor.h"
#include "assets/ids.h"

namespace engine { class world; }
namespace geometry { class map_data; }

namespace entities {
    class monster : public engine::actor {
    protected:
        engine::actor& target;
        geometry::map_data& map_ref;
        engine::world& world_ref;
        float attack_cooldown;
        float attack_range;
        float detection_radius;
        float attack_damage;
        float attack_cd_max;
        float collision_radius = 16.0f;

        bool has_target() const;
        float dist_to_target() const;
        math::vec2 dir_to_target() const;
        void apply_wall_collision(math::vec2& new_pos) const;
        void move_toward_target(float speed, float dt);
        void move_away_from_target(float speed, float dt);
        void strafe(float speed, float dt);
        void melee_attack(float damage);
        void ranged_attack(float damage, assets::texture_id tex, float speed);

    public:

        monster(math::vec2 const p, float const z, assets::texture_id const tex, float const is, flo

        void update(float dt) override;
    };
}
```

4. Schematy blokowe własnych funkcji C++

fml

5

5.1 Opis poruszania sie

5.2 Wymagania techniczne

5.3 Uwagi instalacyjne

UWAGA: \$ i # jak w man 1 bash

5.3.1 Kompilacja programu

Aby skompilowac program, nalezy postepowac wedlug nastepujacych instrukcji:

1. Uzyc \$: `git clone https://github.com/hhsNel/oop-project` lub w inny sposob zdobyc kod zdrojowy programu, a nastepnie wejsc w jego katalog
2. Usunac potencjalne pliki ktore zostaly z poprzedniej kompilacji za pomoca \$: `make clean`
3. Zbudowac program za pomoca \$: `make`

UWAGA: Punkty 2. i 3. mozna polaczyc w jedno: \$: `make clean all`

5.3.2 Instalacja programu

Aby zainstalowac program, nalezy postepowac wedlug nastepujacych instrukcji:

1. przekopiowac zbudowany plik za pomoca #: `install isekai-doom /usr/local/bin -m 755`

UWAGA: Jezeli niedostepny jest `install`, mozna uzyc #: `cp isekai-doom /usr/local/bin && chown /usr/local/bin/isekai-doom root:root && chmod 755 /usr/local/bin/isekai-doom`

6

7

8