How Should We Read ViT Attention Maps? A Fast-Weight Perspective


Hongbo Huang
Student ID: 50026755

Abstract

How should a vision transformer's attention map be read as image evidence? Using the fast-weight representation, we distinguish three assumptions about patch scores: image specificity, spatial correspondence and output contribution. We test each with a matched control on frozen models. Index-based relocation reduced all three deep-layer scores, while value weighting improved foreground and ClickMe alignment in supervised DeiT. On Oxford-IIIT Pet, an exploratory CLS-only readout in DeiT-S ranked patches more consistently with the change in class margin after their contributions to the final classification token were removed. Aggregating all queries gave better foreground localisation on the same images.

1 Introduction

A background patch can attract strong attention in a vision transformer [8, 11]. A map of received attention sums the weights assigned to each source token. In a deep layer, that token has already exchanged information with other positions. Even a strongly attended token can send a small vector to a query. Both observations complicate the familiar reading of a bright patch as important input.



Reading a bright patch

Image specificity. How much of its score recurs across images?

Spatial correspondence. What links the token's grid position to its input evidence?

Output contribution. How large a value does the token send to the receiving query?

Figure 1: A head as a fast-weight network for one image. Keys and transformed values are its weights. Received attention sums softmax activations over queries and heads and places each sum at its source slot.

How do these reading choices shape what a map explains? Using the fast-weight representation [31] (Fig. 1), we make three contributions.

(1) We use the fast-weight representation to separate recurring spatial structure, token position and the magnitude contributed to a query.
(2) We test each change in readout against a matched control on three frozen checkpoints.
(3) We show that index-based relocation degrades deep-layer rankings and that restricting the receiving query can improve agreement with an intervention while worsening localisation.

Preprint.

2 Related work

From attention to a readable unit. Vision transformers mix patch tokens by attention [13]. Fast-weight memory lets a network write temporary weights [28]. Linear attention admits such an interpretation [27], and softmax attention has connections to Hopfield memory [26]. We use MiTA's two-layer representation of softmax attention [31] to identify choices made when displaying a frozen model's activations.

From a token to an image region. Contextualised language tokens retain identity information [7], and ViT representations retain spatial information [25]. Registers change the computation that produces high-norm tokens [11, 18], and no-op heads offer one account of outliers [6]. We instead vary how the same tokens are placed and weighted on a grid. Rollout, relevance propagation and gradient weighting trace information across layers [1, 9, 10]. Prior norm analyses incorporate transformed values [19, 36]. GlobEnc, ALTI and TokenTM also track transformations across layers [15, 22, 34]. Our local comparisons isolate the spatial assignment of value lengths and the choice of receiving query.

Which output is explained? The explanatory value of attention depends on the test [17, 32]. CAM targets a class [35], while Value Zeroing measures contextual mixing in language encoders [23]. Ayyar et al. [3] evaluate filtered attention with human gaze and perturbations. We hold the layer and images fixed and intervene on the final classification-token (CLS) pathway. Evaluation depends on parameters, supervision and occlusion [2, 5, 30]. The centre bias found in CNNs was largely absent in the ViTs tested by Kuang et al. [20]. We measure recurring structure in each checkpoint.

3 Methods for reading a frozen attention head

For query i, source j and head h, let $z_j^h = W_O^h v_j^h$ be the transformed value. For query and key dimension d and affine projections, the output before residual addition is

$$o_i = b_O + \sum_{h,j} a_{ij}^h z_j^h, \qquad a_{ij}^h = \mathrm{softmax}_j(q_i^{h\top} k_j^h / \sqrt{d}). \tag{1}$$

For a fixed image, $k_j^h/\sqrt{d}$ and z_j^h act as the input and output weights of a two-layer network in q_i^h. Received attention (R0) assigns $s_j = \sum_{h,i} a_{ij}^h$ to patch slot j. It sums over all queries, including CLS, and reports the 196 patch scores. Following work that measures the properties of hidden units [4], we define a diagnostic and a controlled change in readout for each assumption.

Image specificity (C1). A bright slot may reflect a recurring spatial pattern. We estimate how much spatial variance a held-out mean map explains and subtract that map from each image's scores. Subtracting a centred Gaussian scaled to the mean map's spatial standard deviation controls for a radial prior.

Spatial correspondence (C2). A patch slot contains contextual information. We train a linear probe to decode each token's grid index and redistribute s_j by its predicted position probabilities. A blur matched in mean squared displacement tests whether redistribution adds anything beyond smoothing. Index accuracy measures recoverable position information. The input origin of a token's content remains unknown.

Output contribution (C3). Activation omits the length and direction of the vector sent to a query. We measure the share of attention on patches with block-input norm above three times the image median. C3 weights each activation by its transformed-value length, $c_j = \sum_{h,i} a_{ij}^h \|z_j^h\|_2$. Its control simply zeros received attention on the high-norm patches. C3 uses no threshold. For a single query–source pair,

$$\Big\| \sum_h a_{ij}^h z_j^h \Big\|_2 \le \sum_h a_{ij}^h \|z_j^h\|_2.$$

The left side retains cancellation between heads. C3 sums the right side over queries. Both measures are local to the attention branch. Neither includes residuals, MLPs or subsequent token mixing.

4 Experiments on three reading assumptions




Figure 2: Each column pairs a diagnostic (a–c) with a change in readout (d–f). Panel (a) shows the pooled share of spatial variance explained by the held-out mean map. Panels (b,c) show mean index-decoding accuracy and mean attention share on high-norm patches. Curves have 95% intervals on ImageNet-S (a,c) or 2,000 held-out images (b). Shading marks layers 9–12. In (d–f), horizontal position is the modified readout minus R0 (circle) or its matched control (diamond) on each alignment metric. Bars are unadjusted paired 95% image-bootstrap intervals. Filled markers indicate an interval excluding zero and an absolute mean difference of at least 0.02. The link between diagnostic and benefit is assessed post hoc.

Design and decision rule. We evaluated frozen DeiT-S/B [29] and DINO ViT-S/16 [8], summing maps across layers 9–12 unless specified. On ImageNet-S [16] (12,419 images, with 12,150 valid enrichment scores per DeiT and 12,144 for DINO), enrichment compares the foreground rate among top-ranked patches with the rate at the same radii. On ClickMe [14, 21] (17,408 images), alignment is the own-image minus other-image correlation with human maps (Spearman). Deletion integrates least- minus most-important-first top-1 retention on 2,000 images. Another 4,000 ImageNet images [12] were split equally for probe training and calibration. A higher or lower verdict requires a paired 95% bootstrap interval excluding zero and an absolute mean difference of at least 0.02 (0.05 for deletion). Other differences are termed comparable, including imprecise estimates. Primary contrasts compared each change with its matched control and the combined readout with R0. Individual contrasts with R0 were descriptive except for R1.

What changes under matched controls? The deep mean map was mostly radial (App. B). Index decoding weakened with depth, and late high-norm attention concentrated in the supervised models (Fig. 2b,c). Mean subtraction's sole gain over R0, on DINO ClickMe, was comparable to Gaussian subtraction. In DeiT-B it beat the Gaussian on all three metrics but yielded no gain over R0. Deep probe relocation lowered all nine model–metric scores relative to R0 and underperformed matched blur in DeiT-S and DINO (Table B.3; App. C). In supervised DeiT-S/B, value weighting improved enrichment by 0.038/0.065 and ClickMe alignment by 0.033/0.058 over R0. Three of the four gains also cleared the high-norm control. The fourth, DeiT-B ClickMe, was 0.017 above control. Top-1 deletion gains of 0.017/0.029 fell below the registered 0.05 margin.

Registered predictions. R1 held in all nine tests: deep C3 in DINO was comparable to R0 on all three metrics, as was early C2 (layers 1–4) on both alignment metrics in all three models. R2 predicted four supervised alignment gains from combining C3, C2 and C1. One score was higher, one comparable and two lower (*partly holds*). R3 held: neither a test-time register nor the released MiTA model exceeded DeiT-S on either alignment metric under the decision rule. MiTA also differs in training and preprocessing. App. A documents the pilots and registration; App. D shows fixed-seed examples.

5 Two exploratory tests of what a readout explains

Where do the value lengths matter? C3 improved spatial alignment in supervised DeiT. To test whether each image's arrangement of lengths matters, we used frozen DeiT-S on 384 hash-selected Oxford-IIIT Pet test images [24]. We kept each recipient's attention and value lengths, then assigned its sorted lengths to positions ranked by a paired donor image within each layer and head. A within-ring shuffle retained the radial distribution. A third control kept the lengths at their own positions and replaced each head's received attention with its spatial mean.

Table 1: Spatial assignment of value lengths in DeiT-S (layers 9–12). All rows use the same 383 pet crops with foreground and background. The difference column gives reading minus C3 for same-ring enrichment, with paired 95% image-bootstrap intervals. AUROC ranks patches across radii.

Reading	Enrichment	Difference from C3 [95% CI]	AUROC
Received attention (R0)	0.141	−0.019 [−0.023, −0.015]	0.788
Projected value norm (C3)	0.160	—	0.817
Donor-image positions	0.137	−0.022 [−0.026, −0.019]	0.787
Within-ring permutation	0.138	−0.021 [−0.025, −0.018]	0.793
Value norm only	0.120	−0.040 [−0.048, −0.032]	0.757
Unprojected value norm	0.163	0.004 [0.003, 0.005]	0.822
Norm after summing heads	0.156	−0.003 [−0.005, −0.002]	0.809

Donor assignment and within-ring shuffling reduced enrichment by 0.022 and 0.021 (Table 1). Resampling donor pairs gave a C3 advantage of 0.022 [0.019, 0.026]. Removing spatial variation in attention also reduced enrichment. Both the recipient's spatial assignment of lengths and its patch-specific attention weights improved this readout. Unprojected lengths gave slightly higher enrichment, so the output projection adds no measured advantage here.

Which receiving query matters? On 128 of the pet images we removed one source patch's value term at a time from the last CLS attention output, holding attention fixed. We recomputed the remaining block and classifier, then ranked all 196 patches by the absolute change in the original top-two logit margin. Restricting C3 to the CLS query improved its within-image rank correlation with this intervention by 0.041 [0.026, 0.057]. After seeing that result, we scored the same layer-12 rankings against the masks. The same query restriction reduced both enrichment and AUROC (Table 2). The paired 95% interval for the AUROC change was $[-0.110, -0.074]$.

Table 2: Classifier sensitivity and foreground alignment for layer-12 readouts on the same 128 images. Rows give mean per-image scores. The last row gives paired differences. Margin Spearman compares the readout with the measured patch effects on the CLS pathway. Net magnitude takes the norm after summing head vectors, allowing them to cancel.

Layer-12 readout	Margin Spearman	Enrichment	AUROC
All queries, attention	0.696	0.117	0.754
All queries, sum of magnitudes	0.705	0.127	0.769
CLS, attention	0.730	0.081	0.666
CLS, sum of magnitudes	0.747	0.095	0.678
CLS, net magnitude	0.756	0.098	0.678
CLS minus all queries (sum of magnitudes)	+0.041	−0.033	−0.091

6 Discussion and conclusion

The fast-weight view separates the token slot displayed on the grid, the activation assigned to it and the vector sent to a particular query. Testing those choices on frozen models shows that decodable position alone is a poor basis for relocating deep scores and that the choice of query can favour different targets. On the same pet images, aggregating all queries gave better foreground localisation, while the CLS-only ranking agreed more closely with the measured effects on the final CLS pathway. The matched intervention covers one checkpoint and one image domain. Human maps and object masks also reflect what annotators were asked to identify. Removing a contextualised value measures its effect at that layer, while tracing its evidence to input pixels remains open.

References

[1] Samira Abnar and Willem Zuidema. Quantifying Attention Flow in Transformers. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 4190–4197, 2020. doi: 10.18653/v1/2020.acl-main.385.

[2] Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity Checks for Saliency Maps. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 31, 2018.

[3] Meghna P. Ayyar, Jenny Benois-Pineau, and Akka Zemmari. There is More to Attention: Statistical Filtering Enhances Explanations in Vision Transformers. In *Pattern Recognition. ICPR 2026*, volume 16816 of *Lecture Notes in Computer Science*, pages 591–605. Springer, 2027. doi: 10.1007/978-3-032-31666-0_39.

[4] David Bau, Bolei Zhou, Aditya Khosla, Aude Oliva, and Antonio Torralba. Network Dissection: Quantifying Interpretability of Deep Visual Representations. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6541–6549, 2017.

[5] Stefan Blücher, Johanna Vielhaben, and Nils Strodthoff. Decoupling Pixel Flipping and Occlusion Strategy for Consistent XAI Benchmarks. *Transactions on Machine Learning Research (TMLR)*, 2024.

[6] Yelysei Bondarenko, Markus Nagel, and Tijmen Blankevoort. Quantizable Transformers: Removing Outliers by Helping Attention Heads Do Nothing. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36, pages 75067–75096, 2023. doi: 10.52202/075280-3282.

[7] Gino Brunner, Yang Liu, Damián Pascual, Oliver Richter, Massimiliano Ciaramita, and Roger Wattenhofer. On Identifiability in Transformers. In *International Conference on Learning Representations (ICLR)*, 2020.

[8] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging Properties in Self-Supervised Vision Transformers. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 9650–9660, 2021.

[9] Hila Chefer, Shir Gur, and Lior Wolf. Transformer Interpretability Beyond Attention Visualization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 782–791, 2021.

[10] Hila Chefer, Shir Gur, and Lior Wolf. Generic Attention-model Explainability for Interpreting Bi-Modal and Encoder-Decoder Transformers. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 397–406, 2021.

[11] Timothée Darcet, Maxime Oquab, Julien Mairal, and Piotr Bojanowski. Vision Transformers Need Registers. In *International Conference on Learning Representations (ICLR)*, 2024.

[12] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

[13] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale. In *International Conference on Learning Representations (ICLR)*, 2021.

[14] Thomas Fel, Ivan Felipe, Drew Linsley, and Thomas Serre. Harmonizing the object recognition strategies of deep neural networks with humans. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 35, 2022. doi: 10.52202/068431-0685.

[15] Javier Ferrando, Gerard I. Gállego, and Marta R. Costa-jussà. Measuring the Mixing of Contextual Information in the Transformer. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 8698–8714, 2022. doi: 10.18653/v1/2022.emnlp-main.595. URL https://aclanthology.org/2022.emnlp-main.595/.

[16] Shanghua Gao, Zhong-Yu Li, Ming-Hsuan Yang, Ming-Ming Cheng, Junwei Han, and Philip Torr. Large-Scale Unsupervised Semantic Segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(6):7457–7476, 2023. doi: 10.1109/TPAMI.2022.3218275.

[17] Sarthak Jain and Byron C. Wallace. Attention is not Explanation. In *Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, pages 3543–3556, 2019. doi: 10.18653/v1/N19-1357.

[18] Nick Jiang, Amil Dravid, Alexei A. Efros, and Yossi Gandelsman. Vision Transformers Don't Need Trained Registers. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 38, 2025. doi: 10.52202/085713-1891.

[19] Goro Kobayashi, Tatsuki Kuribayashi, Sho Yokoi, and Kentaro Inui. Attention is Not Only a Weight: Analyzing Transformers with Vector Norms. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7057–7075, 2020. doi: 10.18653/v1/2020.emnlp-main.574.

[20] Keying Kuang, Iain Carmichael, and Elizabeth Purdom. When Random Saliency Looks Trained: Architectural Center Bias in CNN Interpretability. In *International Conference on Machine Learning (ICML)*,

volume 306 of *Proceedings of Machine Learning Research*, pages 61236–61266, 2026.

[21] Drew Linsley, Dan Shiebler, Sven Eberhardt, and Thomas Serre. Learning what and where to attend. In *International Conference on Learning Representations (ICLR)*, 2019.

[22] Ali Modarressi, Mohsen Fayyaz, Yadollah Yaghoobzadeh, and Mohammad Taher Pilehvar. GlobEnc: Quantifying Global Token Attribution by Incorporating the Whole Encoder Layer in Transformers. In *Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, pages 258–271, 2022. doi: 10.18653/v1/2022.naacl-main.19. URL https://aclanthology.org/2022.naacl-main.19/.

[23] Hosein Mohebbi, Willem Zuidema, Grzegorz Chrupała, and Afra Alishahi. Quantifying Context Mixing in Transformers. In *Conference of the European Chapter of the Association for Computational Linguistics (EACL)*, pages 3378–3400, 2023. doi: 10.18653/v1/2023.eacl-main.245.

[24] Omkar M. Parkhi, Andrea Vedaldi, Andrew Zisserman, and C. V. Jawahar. Cats and Dogs. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3498–3505, 2012. doi: 10.1109/CVPR.2012.6248092.

[25] Maithra Raghu, Thomas Unterthiner, Simon Kornblith, Chiyuan Zhang, and Alexey Dosovitskiy. Do Vision Transformers See Like Convolutional Neural Networks? In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 34, 2021.

[26] Hubert Ramsauer, Bernhard Schäfl, Johannes Lehner, Philipp Seidl, Michael Widrich, Lukas Gruber, Markus Holzleitner, Thomas Adler, David Kreil, Michael K. Kopp, Günter Klambauer, Johannes Brandstetter, and Sepp Hochreiter. Hopfield networks is all you need. In *International Conference on Learning Representations (ICLR)*, 2021.

[27] Imanol Schlag, Kazuki Irie, and Jürgen Schmidhuber. Linear Transformers Are Secretly Fast Weight Programmers. In *International Conference on Machine Learning (ICML)*, volume 139 of *Proceedings of Machine Learning Research*, pages 9355–9366, 2021.

[28] Jürgen Schmidhuber. Learning to Control Fast-Weight Memories: An Alternative to Dynamic Recurrent Networks. *Neural Computation*, 4(1):131–139, 1992. doi: 10.1162/neco.1992.4.1.131.

[29] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning (ICML)*, volume 139 of *Proceedings of Machine Learning Research*, pages 10347–10357, 2021.

[30] Matthew Walmer, Saksham Suri, Kamal Gupta, and Abhinav Shrivastava. Teaching Matters: Investigating the Role of Supervision in Vision Transformers. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7486–7496, 2023.

[31] Qishuai Wen, Zhiyuan Huang, Xianghan Meng, Wei He, and Chun-Guang Li. Mixture-of-top-k attention: Efficient attention via scalable fast weights. arXiv:2602.01219v6, 2026.

[32] Sarah Wiegreffe and Yuval Pinter. Attention is not not Explanation. In *Conference on Empirical Methods in Natural Language Processing (EMNLP-IJCNLP)*, pages 11–20, 2019. doi: 10.18653/v1/D19-1002.

[33] Ross Wightman. PyTorch Image Models. GitHub repository, https://github.com/huggingface/pytorch-image-models, 2019.

[34] Junyi Wu, Bin Duan, Weitai Kang, Hao Tang, and Yan Yan. Token Transformation Matters: Towards Faithful Post-hoc Explanation for Vision Transformer. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10926–10935, 2024.

[35] Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning Deep Features for Discriminative Localization. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2921–2929, 2016.

[36] Hongbo Zhu, Theodor Wulff, Rahul Singh Maharjan, Jinpei Han, and Angelo Cangelosi. Noise-Free Explanation for Driving Action Prediction. In *European Conference on Artificial Intelligence (ECAI)*, volume 392 of *Frontiers in Artificial Intelligence and Applications*, pages 451–458, 2024. doi: 10.3233/FAIA240520.

A Experimental details

Models. All models are frozen ViTs with 16×16 patches on 224×224 inputs, taken from timm [33]. *DeiT-S and DeiT-B* [29]: `deit_small_patch16_224.fb_in1k` and `deit_base_patch16_224.fb_in1k` (resize to 248, centre crop 224: a crop ratio of 0.9). *DINO ViT-S/16* [8]: `vit_small_patch16_224.dino` with the official DINO linear head (resize to 256, centre crop 224: a crop ratio of 0.875). *DeiT-S with a test-time register* [18]: the activations of eight feed-forward units in layers 4 and 5 are moved to one added register token, which is left out of every map, like CLS. The units were selected on 500 ImageNet-S images, where they reduce the number of high-norm patch tokens (counted per layer) by 92.75% and keep 99.0% of the predictions; on the other 11,919 images the reduction is 91.5%, and ImageNet accuracy stays at 79.8%. For DeiT-B the same search found no such units (44.9% reduction with 32 units), so we report the register for DeiT-S only. *Top-k training*: the DeiT-S checkpoint released with MiTA [31] (25 summary slots, $k = 25$), with its own preprocessing (crop ratio 0.875). It differs from our DeiT-S in training and preprocessing, so its row in Table B.1 is not a controlled comparison; its deletion score is undefined because its summary slots pool fixed regions of the full grid. Both model-side changes are tested at size S only; in a preliminary comparison with an earlier protocol, top-k training scored 0.011 lower in object enrichment than its baseline at size S but 0.037 higher at size Tiny, so the result should not be read beyond DeiT-S.

Attention conventions. With x the block input after its first layer norm, projections include the checkpoint's biases:

$$q_i^h = W_Q^h x_i + b_Q^h, \quad k_j^h = W_K^h x_j + b_K^h, \quad v_j^h = W_V^h x_j + b_V^h.$$

Equation 1 includes the output bias b_O and describes the attention branch before residual addition, with dropout inactive at evaluation. W_O^h is the head's slice of the output projection. C3 assigns the per-head vector magnitudes to patches; the shared output bias is not assigned to any patch. The fixed-image two-layer representation uses the coupled softmax activation, rather than an elementwise nonlinearity.

Data. *Execution test*: 5,000 randomly drawn ImageNet validation images [12]. *ImageNet-S* [16]: all 12,419 validation images with segmentation masks; stored enrichment is finite for 12,150 (12,144 for DINO). Historical records include all-foreground grids scored zero. Appendix E gives the cohort sensitivity check. Deletion uses a fixed random subset of 2,000. *ClickMe* [14, 21]: the 17,408-image validation split released with Harmonization (17 `val-*.tfrecords` shards). This split name does not identify the original ImageNet split of each image. Images are resized from 256×256 to 224×224 without cropping; heatmaps are resized to 64×64, blurred with a 10×10 Gaussian ($\sigma = 10$), then resized to 224×224 (bilinear interpolation). *Held-out set*: 4,000 ImageNet validation images excluded from map-quality and execution evaluation; 2,000 train probes and 2,000 provide mean maps, probe-test accuracies and blur calibration. Our near-duplicate check matched 2 of 4,002 candidate ImageNet validation images to ClickMe records; this does not establish every ClickMe image's training-set membership. Possible overlap with model training images limits generalisation claims.

Diagnostics. All three are computed per layer. *Specificity*: with $\bar{s}$ the mean received-attention map of the held-out images and Var_j the variance over the 196 patches of one image, the share explained is $1 - \sum_x \mathrm{Var}_j(s - \bar{s}) \,/\, \sum_x \mathrm{Var}_j(s)$, summed over the ImageNet-S images x. *Location*: the top-1 accuracy of the linear position probe on the 196 patch tokens of each of 2,000 held-out images. *Contribution*: the share of received attention on high-norm tokens, on the ImageNet-S images. The high-norm threshold (three times the median, defined below) is an operational definition fixed before the experiments; we did not test other thresholds. The correction itself uses no threshold.

Corrections and matched controls. Scores are computed per layer and summed over layers 9–12 without per-layer rescaling, except for the C1 control's calibration described below. Queries include all 197 tokens; maps contain 196 patches. Negative C1 scores are retained for ranking, without clipping. *Mean-map subtraction* computes $\sum_\ell (s_\ell - \bar{s}_\ell)$ using the 2,000 calibration images. With $S = \sum_\ell s_\ell$ and $\bar{S} = \sum_\ell \bar{s}_\ell$, its control is $S - G\,\mathrm{sd}_j(\bar{S})/\,\mathrm{sd}_j(G)$, where G is a centred isotropic Gaussian ($\sigma = 3.5$ patches). Calibration thus uses the *summed* mean map. *Probe relocation* computes $r_p = \sum_j s_j P_\ell(p \mid x_j)$, preserving total score. One linear 196-way classifier per model/layer is

trained on standardised tokens after the first layer norm: cross-entropy, Adam, learning rate 0.01, 30 epochs, token minibatches of 4,096, seed 0. Feature means/standard deviations use only the 2,000 training images; standard deviations are floored at 10^{-6}. Its Gaussian control is a row-normalised kernel $K_{jp} \propto \exp(-\|p-j\|^2/(2\sigma_\ell^2))$. The width (0.7–2.9 patches) matches

$$D_\ell = \frac{1}{2000N} \sum_{x,j,p} P_\ell(p \mid x_j)\|p-j\|^2$$

on calibration images, using uniform averaging over source patch indices. Matching uses uniform source indices. ClickMe uses the same crop-trained probe and blur on resized full images, introducing a potential geometry mismatch. *Contribution weighting* computes $c_j = \sum_{h,i} a_{ij}^h \|W_O^h v_j^h\|_2$, a sum of per-head norm-weighted terms related to Kobayashi et al. [19]. Summing magnitudes before aggregating across heads omits cross-head cancellation; residual addition, subsequent normalisation and later-layer computation are outside this score. The control zeros received attention at high-norm patches: block-input norm greater than three times the image's median patch norm, using the midpoint median. C3 itself has no high-norm threshold. *All three corrections*: contribution weighting, probe relocation, then subtraction of the held-out mean of the resulting map, per layer before summation.

Metrics. *Same-ring object enrichment.* A patch is valid if it contains at least one non-ignored pixel, and is an object patch if at least half of its non-ignored pixels belong to the image's class mask. We select as many top-scoring patches as there are object patches. For every ring of patches at the same distance from the grid centre, we take the object rate among its selected patches minus that among all its patches, and average over rings, weighted by their selected patches. Invalid patches are excluded from selection and ring baselines. Ties are broken with the fixed seeded perturbation used in the original runs. A purely radial map scores zero in expectation over tie-breaking. *Image-specific ClickMe alignment.* The map is upsampled to 224×224 and correlated (Spearman, over pixels) with the image's own human map; we subtract its correlation with the previous image's human map within each batch (`roll(1)`; batch size 64). For an image-independent map, these differences average to zero over the paired set because the control permutes the same human maps; individual-image differences need not be zero. This removes fixed-prior alignment on average, without guaranteeing invariance to a prior mixed into an image-dependent map. *Deletion score.* Patches are ranked once by the original map. At removal budgets $0, 1, 2, 4, 8, 16, 32, 64, 98, 147$, we record the binary indicator that the original top-1 prediction is preserved. Tokens are dropped after positional embedding; CLS and any register remain. We use an SRG-style LIF–MIF area difference [5], adapting the value function from class probability to top-1 preservation. Areas use trapezoidal integration over removed-patch fraction $b/196$, from 0 to $147/196$. *Validity of the metrics.* A random map, a centred Gaussian and the mean map all score within 0.004 of zero on enrichment and on ClickMe alignment (the two image-independent maps have exactly zero mean on the latter, up to numerical precision); on deletion the centred Gaussian scores 0.110, 0.099 and 0.140 (DeiT-S, DeiT-B, DINO ViT-S), which is why every correction is compared with a matched control. *Statistics.* One value per image; paired image-bootstrap with 1,000 resamples, seed 0 and 95% percentile intervals. A difference is *higher* (*h*) or *lower* (*l*) if its interval excludes zero and its absolute mean reaches 0.02 (0.05 for deletion), and *comparable* (*c*) otherwise. The comparable category also covers imprecise differences. Intervals are unadjusted for multiple comparisons. Resampling holds checkpoints, probes and the within-batch ClickMe pairing fixed, excluding uncertainty from training, probe fitting or alternative pairings. Because the control reuses human maps within each batch, ClickMe score rows are not independent pairings.

GAE reference. The gradient-based reference [10] targets the unmodified model's predicted top-1 logit and uses all 12 attention layers. Starting with $R = I$, each layer updates $R \leftarrow R + \mathrm{mean}_h[(\nabla_{A^h} f_c \odot A^h)_+]R$, then takes the final CLS-to-patch row. It is class-specific and spans all layers, whereas R0/C1–C3 are class-agnostic and sum layers 9–12. Its scores provide descriptive context rather than a matched single-component ablation.

Registered predictions. The protocol was frozen before formal runs, after smoke tests on 32–64 images and earlier exploratory observations documented in `docs/preregistration.md`. Historical P4/P3/P6 map to R1/R2/R3; definitions, margins and verdicts are unchanged. R2 has three possible outcomes: holds (4/4 higher), partly holds (1–3) and does not hold (0). Primary contrasts

were the combination versus R0 and each correction versus its matched control, without a registered direction for the latter. Other correction–R0 contrasts are descriptive, except R1's registered negative controls. Prior execution/diagnostic results had been seen, making the last two rows of Table A.1 replications. Diagnosis–benefit interpretation and supplementary mechanism analyses are post hoc.

Table A.1: Registered predictions and outcomes (centre-controlled metrics: enrichment and ClickMe alignment).

	Prediction	Outcome
R1	Contribution weighting is comparable to received attention in DINO ViT-S on all three metrics	holds (3 of 3 cells)
R1	Relocation at layers 1–4 is comparable to received attention on the centre-controlled metrics in all models	holds (6 of 6 cells)
R2	All three corrections together are higher than received attention on the centre-controlled metrics in DeiT-S and DeiT-B	partly holds (1 higher: DeiT-B ClickMe; 1 comparable; 2 lower)
R3	Neither model-side change is higher than DeiT-S received attention on the centre-controlled metrics	holds (4 of 4 cells)
–	Execution agreement rises with k and exceeds that of random sets at every k	holds in all models
–	Probe accuracy falls with depth; the share of attention on high-norm tokens peaks in layers 6–12 of the supervised models and is below 1% in every layer of DINO ViT-S	holds in all models

Compute and code. The original experiments used approximately 19 NVIDIA L4 GPU hours. The paper repository provides the registered protocol, configurations and fixed splits in `docs/preregistration.md`, `configs/` and `data/splits/`. The exploratory protocols, scripts and individual scores are in `experiments/`. The README gives separate commands for rebuilding the displayed results and running inference.

B Additional results

These results support the framework at different levels: execution and parameter sensitivity check internal dependence, while paired comparisons and supplementary analyses assess spatial alignment, deletion sensitivity and proposed interpretations.

Table B.1: Complete scores for the original tests, layers 9–12 unless indicated. Arrows mark higher/lower scores versus received attention (DeiT-S for model-side rows). Diamonds indicate higher scores than the matched control. Bold indicates higher than both. Untagged tested cells are comparable. GAE uses gradients and all 12 layers. Dashes indicate unavailable comparisons.

	DeiT-S			DeiT-B			DINO ViT-S		
Reading	Enr.	Click.	Del.	Enr.	Click.	Del.	Enr.	Click.	Del.
Received attention	0.140	0.157	0.236	0.080	0.107	0.169	0.199	0.208	0.285
Contribution weighting	**0.178**$^{\uparrow\diamond}$	**0.190**$^{\uparrow\diamond}$	0.253	**0.146**$^{\uparrow\diamond}$	0.165$^{\uparrow}$	0.198	0.196	0.207	0.285
zero high-norm tokens	0.152	0.168	0.241	0.121$^{\uparrow}$	0.148$^{\uparrow}$	0.186	0.199	0.208	0.285
Mean-map subtraction	0.138	0.165	0.208	0.077$^{\diamond}$	0.087$^{\downarrow\diamond}$	0.144$^{\diamond}$	0.201	0.252$^{\uparrow}$	0.233$^{\downarrow}$
subtract centre Gaussian	0.133	0.168	0.167$^{\downarrow}$	0.056$^{\downarrow}$	0.062$^{\downarrow}$	0.024$^{\downarrow}$	0.200	0.253$^{\uparrow}$	0.232$^{\downarrow}$
Probe relocation	0.041$^{\downarrow}$	0.084$^{\downarrow}$	0.076$^{\downarrow}$	0.027$^{\downarrow\diamond}$	0.050$^{\downarrow}$	0.051$^{\downarrow}$	0.084$^{\downarrow}$	0.143$^{\downarrow}$	0.141$^{\downarrow}$
matched blur	0.095$^{\downarrow}$	0.152	0.181$^{\downarrow}$	−0.008$^{\downarrow}$	0.068$^{\downarrow}$	0.097$^{\downarrow}$	0.189	0.226	0.287
All three corrections	0.059$^{\downarrow}$	0.123$^{\downarrow}$	0.076$^{\downarrow}$	0.079	0.137$^{\uparrow}$	0.085$^{\downarrow}$	0.088$^{\downarrow}$	0.177$^{\downarrow}$	0.090$^{\downarrow}$
+ test-time register	0.152	0.169	0.236	–	–	–	–	–	–
Top-k training (MiTA)	0.100$^{\downarrow}$	0.115$^{\downarrow}$	–	–	–	–	–	–	–
GAE (reference)	0.204	0.234	0.345	0.196	0.213	0.308	0.221	0.234	0.418

Execution test. The 14×14 grid is pooled into 16 overlapping regions. In every layer/head, each region's mean query selects its top-k keys; CLS retains its own set. Sets from an unmodified forward pass restrict every query to its region's set in all 12 layers simultaneously. Top-k sets beat equal-size random sets at every tested k (4–128) in all models, and agreement rises with k (Fig. B.1). The dotted attention-removed baseline alone uses uniform crop ratio 0.875; solid/dashed DeiT curves use 0.9.




Figure B.1: Top-1 agreement on 5,000 ImageNet images with region-selected top-k units (solid), random units (dashed) or attention removed (dotted). Stored 95% intervals are at most ±1.5 percentage points. Dotted curves use crop ratio 0.875 for all models; other curves use each checkpoint's main preprocessing.

Diagnostics per layer. Table B.2 lists the diagnostics plotted in Fig. 2a–c and the uncorrected per-layer ClickMe alignment. Two further details complement the table. First, in layers 9–12, 82–98% of the variance of the mean map is explained by the distance from the grid centre. Second, averaged over layers 9–12, the mean value-vector norm $\|v_j\|$ of high-norm tokens is 0.29 (DeiT-S) and 0.23 (DeiT-B) times the median of the other patches (measured on 11,919 ImageNet-S images using uniform crop ratio 0.875, unlike the main DeiT evaluation at 0.9).

Recovery at the last layer. In the supervised models, single-layer received attention is worse at layer 12 than at the best of layers 8–11 (ClickMe values in Table B.2). Applied to layer 12, contribution weighting recovers 62% and 33% of this drop on enrichment (DeiT-S, DeiT-B), 31% and 45% on ClickMe alignment, and 8% and 29% on deletion. The other two corrections make layer 12 worse.

Differences behind Table B.1. Table B.3 gives the paired differences with their intervals. The values in Table B.1 have 95% intervals of at most ±0.005 on enrichment and ClickMe alignment and ±0.012 on deletion. The model-side differences from DeiT-S received attention are $+0.012$ [0.011, 0.013] on enrichment, $+0.013$ [0.012, 0.013] on ClickMe and 0.000 [-0.005, 0.004] on deletion for the test-time register, and -0.040 [-0.042, -0.039] and -0.042 [-0.044, -0.040] on the first two for top-k training. The paired MiTA enrichment contrast uses 12,118 images valid for both models.

Table B.2: Per-layer diagnostics (Fig. 2a–c) and uncorrected ClickMe alignment (last three columns). S, B, D: DeiT-S, DeiT-B, DINO ViT-S; probe chance: 0.5%. Values are rounded; DINO layers 9–12 have exactly zero high-norm attention on this dataset.

	Specificity: mean-map share (%)			Location: probe accuracy (%)			Contribution: high-norm share (%)			Map quality: ClickMe alignment		
Layer	S	B	D	S	B	D	S	B	D	S	B	D
1	6.8	12.4	11.2	100.0	100.0	99.9	0.0	0.0	0.0	−0.108	−0.111	−0.089
2	21.2	14.0	7.4	100.0	100.0	100.0	0.0	0.0	0.0	0.007	0.041	0.064
3	13.7	15.0	19.7	99.9	100.0	99.9	0.0	0.0	0.0	0.081	0.004	0.056
4	6.9	7.5	14.6	99.0	100.0	99.8	0.0	0.0	0.0	0.132	0.110	0.140
5	7.8	5.8	14.6	97.5	99.9	99.6	0.1	0.0	0.0	0.148	0.130	0.150
6	5.2	6.2	11.9	85.3	99.5	98.9	2.6	0.0	0.0	0.136	0.151	0.167
7	4.4	5.4	12.4	65.0	96.8	95.9	7.4	3.5	0.0	0.147	0.131	0.150
8	4.2	5.4	6.6	43.9	91.8	85.6	9.3	12.9	0.0	0.149	0.118	0.170
9	4.2	5.7	9.5	31.0	83.6	67.4	9.3	21.5	0.0	0.184	0.112	0.198
10	4.3	5.5	15.2	23.1	66.8	50.5	9.1	28.1	0.0	0.171	0.139	0.207
11	4.1	5.8	16.7	19.4	49.2	39.2	5.6	43.5	0.0	0.149	0.120	0.211
12	3.3	5.0	13.6	18.1	31.8	35.7	7.2	22.2	0.0	0.098	0.023	0.179

Table B.3: Paired differences, layers 9–12: mean, 95% image-bootstrap interval and verdict (*h*/*c*/*l*: higher/comparable/lower). Margins: 0.02 (enrichment/ClickMe), 0.05 (deletion); intervals unadjusted. Samples: App. A. Top: descriptive correction–R0 contrasts and the primary combination–R0 contrasts. Bottom: primary correction–control contrasts. Registered negative controls are also discussed in App. A.

Model	Same-ring enrichment	ClickMe alignment	Deletion score
Contribution weighting − received attention			
DeiT-S	0.038 [0.036, 0.039] *h*	0.033 [0.032, 0.034] *h*	0.017 [0.013, 0.021] *c*
DeiT-B	0.065 [0.063, 0.067] *h*	0.058 [0.056, 0.059] *h*	0.029 [0.024, 0.034] *c*
DINO ViT-S	−0.004 [−0.004, −0.003] *c*	−0.001 [−0.001, −0.001] *c*	0.000 [−0.003, 0.004] *c*
Mean-map subtraction − received attention			
DeiT-S	−0.002 [−0.003, −0.002] *c*	0.009 [0.008, 0.010] *c*	−0.028 [−0.034, −0.023] *c*
DeiT-B	−0.003 [−0.004, −0.003] *c*	−0.020 [−0.021, −0.019] *l*	−0.025 [−0.031, −0.019] *c*
DINO ViT-S	0.002 [0.001, 0.003] *c*	0.044 [0.040, 0.048] *h*	−0.052 [−0.059, −0.044] *l*
Probe relocation − received attention			
DeiT-S	−0.099 [−0.101, −0.097] *l*	−0.073 [−0.076, −0.069] *l*	−0.161 [−0.171, −0.150] *l*
DeiT-B	−0.054 [−0.055, −0.052] *l*	−0.057 [−0.059, −0.055] *l*	−0.118 [−0.127, −0.110] *l*
DINO ViT-S	−0.115 [−0.117, −0.113] *l*	−0.064 [−0.067, −0.062] *l*	−0.144 [−0.153, −0.134] *l*
All three corrections − received attention			
DeiT-S	−0.081 [−0.083, −0.079] *l*	−0.034 [−0.038, −0.030] *l*	−0.160 [−0.171, −0.149] *l*
DeiT-B	−0.001 [−0.003, 0.001] *c*	0.030 [0.027, 0.032] *h*	−0.084 [−0.093, −0.076] *l*
DINO ViT-S	−0.111 [−0.114, −0.109] *l*	−0.031 [−0.035, −0.027] *l*	−0.195 [−0.205, −0.184] *l*
Contribution weighting − zero high-norm tokens (its control)			
DeiT-S	0.026 [0.025, 0.027] *h*	0.022 [0.021, 0.023] *h*	0.012 [0.008, 0.016] *c*
DeiT-B	0.025 [0.024, 0.026] *h*	0.017 [0.016, 0.018] *c*	0.013 [0.008, 0.018] *c*
DINO ViT-S	−0.004 [−0.004, −0.003] *c*	−0.001 [−0.001, −0.001] *c*	0.000 [−0.003, 0.004] *c*
Mean-map subtraction − centre-Gaussian subtraction (its control)			
DeiT-S	0.005 [0.004, 0.005] *c*	−0.003 [−0.005, −0.001] *c*	0.040 [0.034, 0.047] *c*
DeiT-B	0.022 [0.021, 0.023] *h*	0.025 [0.020, 0.030] *h*	0.120 [0.109, 0.130] *h*
DINO ViT-S	0.001 [0.001, 0.002] *c*	−0.001 [−0.001, 0.000] *c*	0.001 [−0.003, 0.005] *c*
Probe relocation − matched blur (its control)			
DeiT-S	−0.054 [−0.056, −0.051] *l*	−0.068 [−0.073, −0.064] *l*	−0.105 [−0.116, −0.095] *l*
DeiT-B	0.035 [0.034, 0.036] *h*	−0.018 [−0.020, −0.015] *c*	−0.047 [−0.055, −0.037] *c*
DINO ViT-S	−0.105 [−0.107, −0.102] *l*	−0.083 [−0.085, −0.080] *l*	−0.146 [−0.155, −0.137] *l*

Tests of the contribution account. Norm weighting reduces the relative weight of attention attached to small transformed-value vectors. One consequence was registered (R1); additional checks were post hoc. *No practically meaningful gain in DINO (R1).* In DINO ViT-S, with zero high-norm attention at layers 9–12 on ImageNet-S, every difference from received attention is at most 0.004 in size (Table B.3). *High-norm attention and alignment gain (post hoc).* Across images, gains have a weak positive association with the share of received attention on high-norm tokens: Spearman $+0.075$ [0.057, 0.092] and $+0.132$ [0.113, 0.150] on enrichment (DeiT-S, DeiT-B), $+0.045$ [0.032, 0.060] and $+0.158$ [0.143, 0.173] on ClickMe. *Assigned versus shuffled weights (post hoc).* Against the same weights shuffled among the patches of each head, contribution weighting is higher in all four supervised cells: $+0.038$ [0.037, 0.040] and $+0.073$ [0.071, 0.076] on enrichment, $+0.035$ [0.035, 0.036] and $+0.067$ [0.065, 0.068] on ClickMe. The shuffle control averages seeds 0–4 within each image before bootstrap resampling. Finally, also post hoc, weighting by $\|v_j^h\|$ instead of $\|W_O^h v_j^h\|$ is comparable in every cell (differences -0.010 to 0.000). This comparable verdict does not establish equivalence. C3 aggregates per-head terms related to Kobayashi et al. [19] and shares a norm-weighted component with Zhu et al. [36]; their full analyses and aggregation differ.

B.1 Parameter-randomisation sanity check

The original study included a model-parameter randomisation check [2] on 1,000 fixed-seed ImageNet-S images. Parameters were cumulatively re-initialised from the classifier and final norm through blocks 12–1 to the patch/position embeddings and CLS token. The trained model's probes and mean maps remained fixed. Received attention and its corrections are class-agnostic and therefore do not depend on classifier parameters alone. Table B.4 reports the stored median per-image Spearman correlations between trained and fully randomised maps, with layers 9–12 summed. All five readings meet the registered median < 0.5 criterion; the model-independent centre Gaussian fails as designed. This is a necessary sensitivity check, not proof of prediction faithfulness. The existing summary is reproduced here without rerunning the experiment.

Table B.4: Stored model-randomisation results: median map correlation after full randomisation. The five readings pass the registered < 0.5 criterion in every model.

Reading	DeiT-S	DeiT-B	DINO ViT-S
Received attention	-0.033	0.055	0.071
Mean-map subtraction	0.187	0.366	0.100
Probe relocation	0.063	0.004	-0.002
Contribution weighting	-0.064	0.070	0.114
All three corrections	0.069	0.078	0.025
Centre Gaussian	1.000	1.000	1.000

C Tests of spatial relocation

Relocation lowers every deep-layer cell (Table B.1). Two planned comparisons narrow the problem. Early relocation remains comparable under the registered rule (R1): at layers 1–4 it changes enrichment and ClickMe alignment by at most 0.004 in every model. And in DeiT-S and DINO ViT-S it is lower than a Gaussian matched in mean squared token displacement (Table B.3). The rest of this section is post hoc: Table C.1 lists four explanations that we tested after seeing this result; none meets its specified criterion. Most probability lies near the true patch, and replacing the linear probe with the tested MLP does not restore map quality. This does not exclude all probe-capacity or calibration limitations. The probe targets index decodability rather than input-content provenance; whether this mismatch explains the failed relocation remains untested (Section 4).

Table C.1: Four explanations for probe-relocation failure (post hoc). Model order: DeiT-S, DeiT-B, DINO ViT-S. Cells are the two centre-controlled metrics in the three models; criteria and probe settings are defined in this section.

Explanation	Test (layers 9–12 unless stated)	Result
The probe sends score to distant patches	Share of the probe's error mass more than three patches from the true patch	Small: 2–29% across models and layers. At layer 12, 45%, 66% and 81% of the probability lies in the 3×3 neighbourhood of the true patch
The probe has a fixed position preference	Peak of the probe's mean prediction relative to uniform; its correlation with the mean map	Close to uniform (peak 1.1–1.3 times the uniform value); at most weakly related to the mean map
The linear probe is too weak	Two-layer MLP probe in place of the linear one	Layer-12 accuracy rises by only 1.8, 3.8 and 6.7 points; relocation is still lower than received attention in all six cells
Global tokens are harder to place	Probe accuracy and entropy against a token's similarity to the image's mean token (layers 10–12)	No consistent relation; accuracy falls with globality only in DeiT-B

Probe capacity and explanatory criteria. The tested MLP has a 1,024-unit hidden layer, GELU and a 196-way output. It uses the linear probe's optimiser, epochs, minibatches and standardisation, trained on 1,800 of the original probe-training images with 200 for best-validation-epoch selection; the original 2,000 test images remain separate. Pre-specified post-hoc criteria were: error mass beyond three patches greater than 0.5 at every deep model/layer; fixed preference peak at least twice uniform and mean-map correlation at least 0.5 (with positive lower interval bound) in every deep model/layer; MLP layer-12 accuracy gain above 10 percentage points in some model, with relocation rescued if it is not lower in at least 4/6 alignment comparisons. These tested criteria fail; the finite MLP check cannot exclude all capacity or calibration limitations.

Globality analysis. Excluding high-norm tokens, globality is a token's cosine similarity to the mean of the other retained tokens in the image. Tokens are split into five equal-size rank groups. We relate the group rank to index accuracy and probe entropy, overall and within four equal-count radial groups, at layers 10–12. The post-hoc criterion required negative accuracy and positive entropy associations (overall intervals and within-ring means) in at least two models. No consistent relationship meets this criterion.

D Example maps

The stored gallery holds 24 ClickMe images drawn at random with a fixed seed. Fig. D.1 shows the two with the smallest ClickMe index, and Fig. D.2 the next four. The image-selection rule is unchanged. Received attention and contribution weighting look much alike, while probe relocation spreads the score over many more patches. The gains in Table B.1 are averages of small changes in how each map ranks its patches, which single maps do not show.




Figure D.1: The first two fixed-seed examples, DeiT-S, layers 9–12. Colours show scores min–max normalised within each map; amplitudes are not comparable across panels. These images were not selected for correction gain.




Figure D.2: DeiT-S on four further ClickMe images, layers 9–12; colours are normalised within each map and do not compare amplitudes across panels.

E Exploratory tests of spatial alignment and classifier sensitivity

Deletion endpoints. For each image and method, trapezoidal integration uses the original removal budgets, divided by 196. The probability endpoint integrates the probability of the original top-1 class under least-important-first removal minus most-important-first removal. The KL endpoint uses the reverse difference in divergence from the original prediction, so that larger scores again indicate greater separation. For both endpoints the paired curve difference is zero at budget zero. Results are paired over images. These measures have no registered practical margin.

Uncertainty. Differences are paired by image. Intervals use 1,000 image-bootstrap resamples with seed 0. ClickMe reuses each human map within a batch for its own and another image. Recomputing intervals by sampling the 272 original 64-image batches preserves those dependencies. For C3 relative to zeroing high-norm patches, the resulting ClickMe intervals are [0.021, 0.023] in DeiT-S and [0.016, 0.018] in DeiT-B. All estimates condition on the fixed within-batch pairing and the available checkpoints.

Table E.1: Exploratory endpoint differences (C3 minus comparator). Probability and KL columns give the mean paired area and 95% image-bootstrap interval over the fixed 2,000-image deletion subset. ClickMe uses the original 17,408 images with batch-bootstrap intervals. KL has units of nats times fraction removed.

Model	Comparator	Probability area	KL area	ClickMe
DeiT-S	R0	0.014 [0.012, 0.015]	0.058 [0.050, 0.066]	0.033 [0.032, 0.034]
DeiT-S	Zero high-norm	0.010 [0.009, 0.012]	0.041 [0.033, 0.049]	0.022 [0.021, 0.023]
DeiT-B	R0	0.022 [0.020, 0.024]	0.107 [0.096, 0.118]	0.058 [0.056, 0.059]
DeiT-B	Zero high-norm	0.010 [0.008, 0.012]	0.048 [0.038, 0.058]	0.017 [0.016, 0.018]
DINO	R0	0.000 [−0.001, 0.002]	−0.003 [−0.009, 0.003]	−0.001 [−0.001, −0.001]
DINO	Zero high-norm	0.000 [−0.001, 0.002]	−0.003 [−0.009, 0.003]	−0.001 [−0.001, −0.001]




Figure E.1: C3 minus the zero-high-norm control at each original ImageNet-S deletion budget. The probability panel measures least-important-first minus most-important-first target probability. The KL panel reverses the subtraction to express divergence in the same direction. Horizontal positions use a log scale in one plus the number of removed patches, with model-specific offsets for visibility. Intervals are pointwise 95% paired image-bootstrap intervals over 2,000 images per model. The integrated advantage can coexist with a reversal at a small budget.

E.1 Object geometry and the enrichment scale

For an image with M valid patches and $k > 0$ foreground patches, let ring r contain m_r valid patches of which f_r are foreground. Selecting a patch in this ring contributes $(y - f_r/m_r)/k$ to enrichment, where y is its foreground indicator. Foreground contributions are nonnegative and background contributions are nonpositive. Selecting all k foreground patches therefore attains the maximum

$$E_{\max} = 1 - \frac{1}{k} \sum_{r:m_r>0} \frac{f_r^2}{m_r} \;\le\; 1 - \frac{k}{M}.$$

The inequality follows by Cauchy–Schwarz. It bounds the score itself. The possible change from R0 also depends on R0's starting score. A large raw improvement for small objects can thus reflect properties of both the map and the metric.

Area and centroid displacement. Object area is the share of valid patch slots labelled foreground. Centroid displacement is the distance from their centroid to the grid centre, in patches. For each checkpoint we computed the empirical quartiles on its finite-geometry images, assigning ties to the lower bin. The DeiT area cut points were 0.158, 0.342 and 0.571. DINO's different crop produced different masks. We paired scores within the same supplementary run and resampled images 2,000 times. In DeiT-S and DeiT-B the largest-minus-smallest area quartile differences in the C3 gain were -0.090 and -0.157 for enrichment. Comparing the most off-centre with the most central quartile instead gave $+0.057$ and $+0.095$. Area and centroid displacement covary. Among the smallest objects the latter differences were $+0.041$ [0.028, 0.053] and $+0.047$ [0.028, 0.066]. Some joint bins are small and these are observational contrasts.

Metric sensitivity. After seeing the enrichment gradients we examined patch AUROC under the same quartile cut points. AUROC is the probability that a foreground patch outranks a background patch, counting ties as one half. In the supervised models the gain in AUROC persists across area quartiles (Table E.2). AUROC does not condition on radius, so this comparison changes spatial adjustment as well as how foreground patches are selected. Overall C3-minus-R0 AUROC changes are $+0.028$, $+0.046$ and -0.005 for DeiT-S, DeiT-B and DINO.

Historical sample membership. Archived ImageNet-S files record zero enrichment for all-foreground grids, as the ring formula implies. Counts are 241 such grids for each DeiT and 265 for DINO. An additional 269/275 images, respectively, have zero object area and are excluded from the archived enrichment means. AUROC requires both classes, giving 11,909 DeiT and 11,879 DINO images. Restricting enrichment to that common eligibility changes C3-minus-R0 from 0.03757 to 0.03833 in DeiT-S, 0.06539 to 0.06671 in DeiT-B and -0.00351 to -0.00359 in DINO. The original verdicts use the archived cohort. In two DeiT-S images the original and supplementary R0 exports differ slightly. The stratified comparisons pair both methods from the supplementary export.

Table E.2: Mean C3 minus R0 by foreground-area quartile on ImageNet-S. Q1 contains the smallest objects. Both metrics use the same within-model cut points. AUROC excludes all-foreground crops.

Metric	Model	Q1	Q2	Q3	Q4
Enrichment	DeiT-S	0.092	0.041	0.013	0.002
Enrichment	DeiT-B	0.165	0.060	0.026	0.008
Enrichment	DINO	−0.003	−0.004	−0.005	−0.003
AUROC	DeiT-S	0.024	0.030	0.031	0.026
AUROC	DeiT-B	0.042	0.048	0.048	0.046
AUROC	DINO	0.000	−0.002	−0.006	−0.013

E.2 Independent pet-image controls

The Oxford release provides test filenames and trimaps. We sorted filenames by SHA-256 of the fixed prefix and name (protocol under `experiments/spatial/`), taking the first 384. Images were resized on the short side to 248 pixels with bicubic interpolation and centre-cropped to 224. The masks received the same spatial transform with nearest-neighbour interpolation. Label 3 (boundary) was ignored. A patch counted as foreground when at least half its valid pixels were foreground. One crop contained only foreground. Each image and its adjacent partner in hash order exchanged norm rankings. In each within-ring shuffle all heads shared a permutation for that image and layer. The recipient's sorted values, head scales and marginal distributions were preserved by rank transfer. Norm-only sets each head's received attention to its spatial mean before multiplying by its patch-specific length.

All seven readouts were evaluated on identical masks. Primary intervals used 10,000 paired image-bootstrap draws (seed 2026). A follow-up sensitivity check resampled the 192 donor pairs, weighting by the number of eligible images in each draw. C3 minus donor-rank gives 0.0223 [0.0187, 0.0261] in this check. The captured C3 map and logits were checked against the original implementation on the first batch. Each query–patch pair satisfied the triangle bound within numerical tolerance over the run. Public Oxford images and the model weights are available from their original providers. Individual scores, selected IDs, scripts and protocols accompany the source.

E.3 Last-block CLS value intervention

A second fixed filename hash selected 128 of the 384 images independently of their scores. At block 12 we cached its input and the unmodified logits. For each patch j we held the original CLS attention weights fixed and removed $t_j = \sum_h a^h_{\mathrm{CLS},j} z^h_j$ from the CLS attention output. The shared projection bias stayed in place. The remaining residual, token-wise MLP, final normalisation and classifier were evaluated for each modified CLS. If m is the margin between the original highest and second-highest logits, the response was $|m_{-j} - m|$ for those same classes. This intervention concerns the contextualised token at that slot. Its input evidence can span multiple image regions.

For each image, we correlated the 196 responses with each unmodified layer-12 readout by Spearman correlation. The means over images were 0.696 (all-query R0), 0.705 (all-query C3), 0.730 (CLS attention), 0.747 (CLS sum of head magnitudes) and 0.756 (CLS net magnitude). The paired CLS-only sum versus all-query C3 difference was 0.041 [0.026, 0.057] with 10,000 image-bootstrap resamples. Explicit interventions in full forward passes on four images and three patch indices each agreed with vectorised logits to within 2.4×10^{-6}. The 128-image run took about 3 seconds on the RTX 4060 with inputs cached. The supplied scripts and individual patch responses are under `experiments/cls/`.

Matched mask comparison. After inspecting the classifier intervention we evaluated the saved layer-12 rankings on the same 128 images and masks. All 128 had eligible foreground and background patches. Table 2 reports the three outcomes with equal image weights. Keeping the CLS query fixed, moving from the sum of per-head magnitudes to net magnitude changed margin Spearman by $+0.0092$ [0.0069, 0.0116], enrichment by $+0.0037$ [0.0007, 0.0069] and AUROC by $+0.0002$ [-0.0031, 0.0033]. The target margin uses the direct path queried by the CLS-specific score. These observations describe that layer and intervention. They do not identify the pixels responsible for earlier token representations.

F Key parts of the code

Given the attention a_{ij}^h and values v_j^h of a layer, the readings are:

```
def received_and_contribution(p, v, w_o, prefix=1):
    # p: [B,H,T,T]; v: [B,H,T,d]; w_o: [D,H,d]
    # T includes CLS; values include the value-projection bias.
    gram = torch.einsum('dhe,dhf->hef', w_o, w_o)
    length = torch.einsum('bhne,hef,bhnf->bhn', v, gram, v)
    length = length.clamp_min(0).sqrt()
    received = p.sum(2)  # sum over queries
    s = received.sum(1)[:, prefix:]
    c = (received * length).sum(1)[:, prefix:]
    return s, c

def relocate(s, probs):  # source j to predicted position p
    return torch.einsum('bj,bjp->bp', s, probs)
```

For the independent pet experiment, the following operations compare two weights for the same source patch. Here a has axes (image, head, query, patch), and z contains each head's projected value vector. The implementation processes queries in chunks.

```
# Own lengths versus the same lengths in a donor image's spatial order
length = z.norm(dim=-1)                          # [B, H, 196]
order = donor_length.argsort(dim=-1)
borrowed = torch.empty_like(length).scatter(-1, order, length.sort(-1).values)
received = a.sum(dim=2)
own_map = (received * length).sum(dim=1)
donor_map = (received * borrowed).sum(dim=1)

# Magnitude after summing the head vectors for each query and patch
net_map = sum(torch.einsum('bhij,bhjd->bijd', chunk, z).norm(dim=-1).sum(1)
              for chunk in a.split(32, dim=2))
```

For the final-block intervention we hold the attention matrix fixed. This excerpt from the full-forward check removes one patch's term from the CLS query. The output projection retains its bias and the rest of the model runs normally.

```
# p: [batch, head, query, source]; v: [batch, head, source, head_dim]
head_out = p @ v
head_out[:, :, 0, :] -= p[:, :, 0, source_patch + 1, None] * v[:, :, source_patch + 1, :]
full = head_out.transpose(1, 2).reshape(batch, tokens, -1)
return attn.proj_drop(attn.proj(attn.norm(full)))
```

AI Use Statement. I set the direction of this project, chose a fast-weight perspective for studying ViT attention maps, and organized the paper around three assumptions about how these maps are interpreted. I used AI tools to help search the literature, design follow-up experiments, write code, run experiments, analyze results, and draft and revise the report.