



# Transfer Learning Architectures

This file is meant for personal use by [hhung.inbox@gmail.com](mailto:hhung.inbox@gmail.com) only.  
Sharing or publishing the contents in part or full is liable for legal action.



# VGGNet

This file is meant for personal use by [hhung.inbox@gmail.com](mailto:hhung.inbox@gmail.com) only.  
Sharing or publishing the contents in part or full is liable for legal action.

# VGGNet



- The VGGNet architecture was proposed by Karen Simonyan and Andrew Zisserman, from the Visual Geometry Group (VGG) at the University of Oxford, in 2014. It even finished first runner-up in the ImageNet annual competition (ILSVRC) in 2014.
- VGGNet has two variants: **VGG16** and **VGG19**. Here, 16 and 19 refer to the total number of convolution and fully connected layers present in each variant of the architecture.
- In comparison to previous Deep Learning models for Computer Vision, VGGNet stood out for its **simplicity** and the **standard, repeatable nature** of its blocks. Its main innovation over standard CNNs was simply its **increased depth** (number of layers) - otherwise it utilized the same building blocks - convolution and pooling layers, for feature extraction.

# VGGNet



- VGGNet was the first architecture to standardize **smaller filters**, (a small 3x3 convolutional kernel is used in every layer) but **deeper networks**. The architecture has around 138 million trainable parameters.
- **Why use smaller filters?** A stack of three 3x3 convolutional (stride 1) layers has the same effective region as one 7x7 convolutional layer. Hence, the use of smaller convolution layers depicts more information about the image across each channel, while ensuring that the size of the output is consistent with the size of the input image (with the help of padding). In addition, multiple 3x3 convolutions will have a fewer number of trainable parameters in comparison to a 7x7 convolution, making this idea more computationally efficient as well

This file is meant for personal use by [hhung.inbox@gmail.com](mailto:hhung.inbox@gmail.com) only.  
Sharing or publishing the contents in part or full is liable for legal action.






# The Inception Network

This file is meant for personal use by [hhung.inbox@gmail.com](mailto:hhung.inbox@gmail.com) only.  
Sharing or publishing the contents in part or full is liable for legal action.

# The Inception Network

- While **VGGNet** chooses a standard **3x3** size for the convolutional kernels to simplify the architecture, an important question is, **is that necessarily the best kernel size** for every dataset?
- Choosing the perfect kernel size for the convolution operation can be a difficult endeavor, due to the huge variance in the location of critical information from image to image.



- Choosing the right filter size to extract the information needed from an image is not straightforward, as we see from the three images of cats.
- So in that case, why not have **filters with multiple sizes** operate on the **same input**, and then **aggregate their results** somehow, like an ensemble model?

**This is the core idea behind the Inception Network.**


This file is meant for personal use by hhung.inbox@gmail.com only.

Sharing or publishing the contents in part or full is liable for legal action.

# The Inception Network - Inception Module


- The Inception Network (the winner of ILSVRC 2014), consists of certain specialized repeating blocks, each of which concatenates the outputs from multiple convolutional pathways.
- These blocks are also known as **Inception Modules**, and they represent a key point of difference between the Inception Network and other architectures.

## The Inception Module



# The Inception Network - Inception Module

- Hence rather than choosing between 1x1, 3x3 or 5x5 convolutional filter sizes, **the Inception Module concatenates the feature maps** that are produced from these filters.
- The importance of the Inception module can be recalled by the **Hebbian Principle of Human Learning**, which states that “**Neurons that fire together wire together.**” This means that when creating a new layer in a Deep Learning model, one should always pay attention to the learnings of the previous layer.
- Suppose a layer in our CNN has learned to focus on individual parts of the face. The next layer should then focus on the overall face in the image, and recognize it. **To perform this recognition, the layers should have the appropriate filter sizes for the recognition task of that layer.** **The Inception Network**, unlike other architectures of the time, **provides scope for this idea.**




This file is meant for personal use by hhung.inbox@gmail.com only.  
Sharing or publishing the contents in part or full is liable for legal action.



## The Inception Network - Inception Module

- What happens in the Inception Module is that by providing choices of different filter sizes, **the network itself learns to rely more on larger filter sizes (like 5x5 Convolutions) the deeper we go into the network**, as those larger filter sizes are more appropriate for higher-level feature detection such as recognizing a whole face, as opposed to smaller parts like eyes or ears.

## The Inception Module




This file is meant for personal use by [hhung.inbox@gmail.com](mailto:hhung.inbox@gmail.com) only.  
Sharing or publishing the contents in part or full is liable for legal action.


# The Inception Network - Inception Module

- **The flexibility to make this choice**, which was not provided by other architectures of the time, is what allowed the Inception Module, and ultimately the Inception Network, to **achieve state-of-the-art performance on image prediction tasks**.

The Inception Module




# The Inception Network - Architecture



The actual Inception Network consists of **multiple Inception Layers throughout the architecture**, in addition to the other, more standard building blocks, like Convolution, Pooling and Fully Connected layers.

# The Inception Network - Architecture




Another unique feature of InceptionNet is that at certain Inception Layers (Inception Layers 3 & 6 in this diagram), **outputs are taken at those intermediate layers as well, to create auxiliary classifiers**. The loss function combines the outputs of these auxiliary classifiers with the output of the main chain of the network, as an ensembling technique to reduce error.

# The Inception Network - Architecture


- Prior to the Inception Network, researchers believed that increasing the depth of the network (in terms of the number of layers) was the best way to improve performance. With InceptionNet however, researchers realized that **the width of the network** (the number of feature maps concatenated together at each layer) **was also important in addition to its depth**, as a way to **improve model performance with minimal increase in the model's computational requirements**.
- As seen in the architecture diagram earlier, the Inception Network has three main structural components:
  - **The Inception Module**
  - **The [ Convolution + Max Pooling + LRN ] Module**
  - **The [ Avg Pooling + Convolution + Fully Connected + Softmax ] Module**

# The Inception Network - Convolution + Max Pooling + LRN



- This is the first structural module of InceptionNet after the input image. This module has 3 Convolution layers, 2 Max Pooling layers and **2 LRN (Local Response Normalization) layers**.
- LRN is a non-trainable layer that **square-normalizes each pixel value along its entire depth across all feature maps** (within the local neighbourhood). The main reason for using LRN over **Batch Normalization** was to encourage “**lateral inhibition**”, or **maintaining the contrast values of the neighborhood of an image**, so that the locally maximum pixel values maintain their importance for the next layers.

# The Inception Network - Avg Pooling + Conv + FC + Softmax



- In CNNs, **as the network grows deeper, the chances of the network being subject to the Vanishing Gradient problem increases.**
- To prevent the middle of the Inception Network from dying out, **two auxiliary classifiers were introduced**, consisting of **Avg Pooling, Convolution, Fully Connected and Softmax Layers**. These auxiliary classifiers apply Softmax to the outputs of two inception modules, and compute an auxiliary loss.
- The total loss function of the InceptionNet equals **the weighted sum of the real loss of the main chain and the auxiliary loss.**

# The Inception Network - Higher Computational Efficiency

- The other advantage of the Inception Network is that it has only 5 million parameters.

**In comparison to VGGNet, it has 27 times less parameters.**

- **The increased width of each module (no. of feature maps concatenated), and the use of 1x1 convolutions** in the network architecture is what allows InceptionNet to maintain top performance despite this reduced computational cost.





# Happy Learning !

