Lecture15

Sung-Min Hong (smhong@gist.ac.kr)

Semiconductor Device Simulation Lab.
School of Electrical Engineering and Computer Science
Gwangju Institute of Science and Technology

Current density equation (1)

- Now, instead of just integrating the Boltzmann equation,
  - The velocity is multiplied first.

$$\mathbf{v}\,\frac{\partial f}{\partial t} + \mathbf{v}(\mathbf{v} \cdot \nabla_r f) + \mathbf{v}\left(\frac{1}{\hbar}\mathbf{F} \cdot \nabla_k f\right) = \mathbf{v}\hat{S}$$

  - Then, the resultant equation is integrated.

$$\frac{\partial}{\partial t}\frac{1}{(2\pi)^3}\int_{BZ}\mathbf{v}f\,d\mathbf{k} + \frac{1}{(2\pi)^3}\int_{BZ}\mathbf{v}(\mathbf{v} \cdot \nabla_r f)\,d\mathbf{k} + \frac{1}{(2\pi)^3}\int_{BZ}\mathbf{v}\left(\frac{1}{\hbar}\mathbf{F} \cdot \nabla_k f\right)d\mathbf{k}$$

$$= \frac{1}{(2\pi)^3}\int_{BZ}\mathbf{v}\hat{S}\,d\mathbf{k}$$

Current density equation (2)

- Remember the electron flux.
  - It is readily found that

$$\frac{\partial}{\partial t}\mathbf{F}_n + \frac{1}{(2\pi)^3}\int_{BZ}\mathbf{v}(\mathbf{v}\cdot\nabla_r f)d\mathbf{k} + \frac{1}{(2\pi)^3}\int_{BZ}\mathbf{v}\left(\frac{1}{\hbar}\mathbf{F}\cdot\nabla_k f\right)d\mathbf{k}$$

$$= \frac{1}{(2\pi)^3}\int_{BZ}\mathbf{v}\hat{S}d\mathbf{k}$$

Current density equation (3)

- Consider the third term.
  - For a given direction, x_i,
  $$\frac{1}{(2\pi)^3} \int_{BZ} v_i \left(\frac{1}{\hbar} \mathbf{F} \cdot \nabla_k f \right) d\mathbf{k} = -\mathbf{F} \cdot \frac{1}{(2\pi)^3} \int_{BZ} \frac{1}{\hbar} (\nabla_k v_i) f d\mathbf{k}$$
  - From the definition of the inverse mass, it is now noted that
  $$-\mathbf{F} \cdot \frac{1}{(2\pi)^3} \int_{BZ} \frac{1}{\hbar} (\nabla_k v_i) f d\mathbf{k} = -\sum_j F_j \frac{1}{(2\pi)^3} \int_{BZ} m_{ij}^{-1} f d\mathbf{k}$$

Current density equation (4)

- Effective mass
  - We assume that

$$m_{ij}^{-1} = \frac{1}{m^*}\delta_{ij}$$

  - Then, along the given direction, we have

$$-F_i\frac{1}{m^*}n$$

  - Therefore, in a vector form, the third term becomes

$$-\mathbf{F}\frac{1}{m^*}n$$

Current density equation (5)

- Consider the second term.
  - For a given direction, x_i, it becomes
$$\sum_j \frac{1}{(2\pi)^3} \int_{BZ} v_i v_j \frac{\partial f}{\partial x_j} d\mathbf{k} = \sum_j \frac{1}{(2\pi)^3} \frac{\partial}{\partial x_j} \int_{BZ} v_i v_j f d\mathbf{k}$$

- Collecting the above discussion,
  - For a given direction, x_i, the equation looks like
$$\frac{\partial}{\partial t} F_{n,i} + \sum_j \frac{1}{(2\pi)^3} \frac{\partial}{\partial x_j} \int_{BZ} v_i v_j f d\mathbf{k} - F_i \frac{1}{m^*} n = \frac{1}{(2\pi)^3} \int_{BZ} v_i \hat{S} d\mathbf{k}$$

Current density equation (6)

- Collecting the above discussion,
  - With the momentum relaxation time,

$$\frac{\partial}{\partial t}F_{n,i} + \sum_j \frac{1}{(2\pi)^3}\frac{\partial}{\partial x_j}\int_{BZ} v_i v_j f d\mathbf{k} - F_i \frac{1}{m^*}n = -\frac{F_{n,i}}{\tau}$$

  - We have to calculate a complicated quantity, $v_i v_j$. How?

$$q\tau\frac{\partial}{\partial t}F_{n,i} + q\sum_j \frac{1}{(2\pi)^3}\frac{\partial}{\partial x_j}\int_{BZ} \tau v_i v_j f d\mathbf{k} - F_i \frac{q\tau}{m^*}n = -qF_{n,i}$$

  - Then, the electron diffusion coefficient, D_n, is introduced.

Current density equation (7)

- In a vector form,
  - A simple equation is obtained.

$$q\tau \frac{\partial}{\partial t}\mathbf{F}_n + q\nabla(D_n n) - \mathbf{F}\frac{q\tau}{m^*}n = -q\mathbf{F}_n$$

  - When the steady-state is considered, the current density $\mathbf{J}_n = -q\mathbf{F}_n$ becomes

$$\mathbf{J}_n = +q\mu_n n\mathbf{E} + qD_n\nabla n$$

  - (We neglect the spatial variation of D_n. $\mathbf{F} = -q\mathbf{E}$)