

Remaining TODO: Aggregate the ratings stats and user creation				
Request	Endpoint	Status	Notes	
GET	/search/<query>	Endpoint exists but returns nothing	Foreach show result, includes the url to the show endpoint.	
GET	/show/<show_id>/	Endpoint handles errors and returns data (unverified completeness of response)	Updates recently viewed whenever it's hit. Includes url to latest season endpoint.	
GET	/season/<show_id>/latest/	Endpoint handles errors and returns data (unverified completeness of response)	Includes pagination URLs and URLs to each episode number and the show.	
GET	/season/<show_id>/<season_number>/	Endpoint handles errors and returns data (unverified completeness of response)	Includes pagination URLs and URLs to each episode number and the show.	
GET	/episode/<show_id>/<season_number>/<episode_number>/	Endpoint handles errors and returns data (unverified completeness of response)	Includes URLs to show and season	
GET	/review/<show_id>/<season>/<episode>/<page>/	Endpoint handles errors and returns data (unverified completeness of response)	Page is optional, by default it starts at page 1. Returns empty array with to high paging value. Includes season, episode, show, review and pagination urls	
GET	/review/<review_id>/	Endpoint handles errors and returns data (unverified completeness of response)		
GET	/comment/<review_id>/<page>/	Endpoint handles errors (doesn't alert) and returns data (unverified completeness of response)	Page is optional, by default it starts at page 1. Returns empty array with to high paging value. No error on invalid review id. Includes pagination URL and POST url for parent replies.	
GET	/user/me/reviews/	Endpoint handles errors and returns data (unverified completeness of response)	Authenticates using a query parameter called user_secret Includes urls to reviews.	
GET	/user/me/recently_viewed/	Endpoint handles errors and returns data (unverified completeness of response)	Authenticates using a query parameter called user_secret Includes urls to shows.	
GET	/user/me/favorites/	Endpoint handles errors and returns data (unverified completeness of response)	Authenticates using a query parameter called user_secret. Includes urls to shows.	

GET	/user/me/replies	Endpoint handles errors and returns data (unverified completeness of response)	Authenticates using a query parameter called user_secret. Includes urls to comments and reviews.	
GET	/media/*	Endpoint caches and returns images from the TVDB media api		
POST	/rate/<show_id>/<season>/<episode>/	Endpoint implemented for show ratings and episode ratings. Supports updating if you repost a rating.	Authenticates using a query parameter called user_secret	Takes 0->5 in the rating field
POST	/agree/<review_id>	Endpoint implemented.	Authenticates using a query parameter called user_secret	Takes a 0 or 1 for the agree field.
POST	/review/<show_id>/<season>/<episode>/	Endpoint implemented.	Authenticates using a query parameter called user_secret	
POST	/comment/<review_id>	Endpoint implemented	Authenticates using a query parameter called user_secret	
POST	/favorite/<show_id>/	Endpoint implemented	Authenticates using a query parameter called user_secret	Toggles between favorited/unfavorited
POST	/user/create	Endpoint implemented	Adds a new user account to database. This user is automatically "logged in"	Parameters are email and a "display name"
POST	/user/login	Endpoint implemented	Logins in an existing user. Server returns a user_secret for the user's session (a random, 40-character hex string).	Parameters are email and a "display name". Email must match an existing user account.
POST	/user/update	Endpoint implemented (Currently unused and untested)	Updates user account preferences such as display name and the "allow comments on my reviews" setting. User must be authenticated.	Parameters are email, display name, and "allow comments on my reviews" boolean. Email must match an existing user account. Client may modify display name and the boolean.