

Incident report analysis

Summary	This morning, the company experienced a DDoS attack that compromised the internal network for approximately two hours. The attack included an incoming flood of ICMP packets that overwhelmed the network and prevented normal internal traffic. The incident management team restored services by blocking the attack, stopping all non-critical network services, and enabling critical network functions. Upon further review, the company's cybersecurity team found that the attack entered the company's network through an unconfigured firewall.
Identify	The company was attacked by a high volume of ICMP packets overwhelming the network. This compromised the entire internal network and disrupted traffic.
Protect	The network security team implemented a new firewall rule and an IDS/IPS system in an attempt to limit the rate of incoming ICMP packets and filter out some traffic based on suspicious characteristics.
Detect	The network security team added a source IP address verification on the firewall and network monitoring software in order to check for spoofed IP addresses on incoming ICMP packets and detect abnormal traffic patterns.
Respond	The company has updated their incident response plan to include DDoS procedures. During a similar security event, the cybersecurity team will immediately work to contain the attack by blocking the ICMP traffic in order to prevent further spreading. They will also attempt to recover any critical systems and temporarily stop all non-critical network services. Whenever the team stops the flood of ICMP packets, all network services can be resumed.
Recover	The team will recover from a DDos attack by restoring all network services and

	returning systems to normal operation. Critical services will be brought back online first, followed by non-critical services once stability is confirmed. The team will verify that no residual issues remain, review system performance, and restore any affected configurations. Finally, the company will work to update recovery procedures to ensure fast recovery in a future attack attempt.