

This course material is now made available for public usage.
Special acknowledgement to School of Computing, National University of Singapore
for allowing Steven to prepare and distribute these teaching materials.



CS3233

Competitive Programming

Dr. Steven Halim

Week 02 –
Data Structures & Libraries

Outline

- Mini Contest 1 + Break
- Data Structures With Built-in Libraries + Break
 - Linear Data Structures (CS1010/1st quarter of CS2020)
 - Non Linear Data Structures (CS2010/the remaining part of CS2020)
- Data Structures With Our-Own Libraries
 - Graph
 - Union-Find Disjoint Sets
 - Segment Tree
 - Fenwick Tree
- “Top Coder” Coding Style

Basic knowledge that all ICPC/IOI-ers must have!

LINEAR DATA STRUCTURES WITH BUILT-IN LIBRARIES

Linear DS + Built-In Libraries (1)

1. Static Array, built-in support in C/C++/Java
 2. Resize-able: C++ STL `<vector>`, Java Vector
 - Both are very useful in ICPCs/IOIs
- There are 2 very common operations on Array:
 - Sorting
 - Searching
 - Let's take a look at efficient ways to do them

One of the “fundamental” CS problem

SORTING OUR DATA

Sorting (1)

- Definition:
 - Given unsorted stuffs, sort them... *
- Popular Sorting Algorithms
 - $O(n^2)$ algorithms: Bubble/Selection/Insertion Sort
 - $O(n \log n)$ algorithms: Merge/Quick/Heap Sort
 - Special purpose: Counting/Radix/Bucket Sort
- Reference:
 - http://en.wikipedia.org/wiki/Sorting_algorithm

Sorting (2)

- In ICPC, you can “forget” all these...
 - In general, if you need to sort something..., just use the $O(n \log n)$ sorting library:
 - C++ STL `<algorithm>`: `sort`
 - Java: `Collections.sort` (not discussed in this lecture)
 - Java users: please study sample codes on your own
- In ICPC, sorting is either used as *preliminary step* for more complex algorithm or to *beautify output*
 - Familiarity with sorting libraries is a must!

Sorting (3)

- Sorting routines in C++ STL <algorithm>
 - sort – a bug-free implementation of *introsort**
 - Can sort basic data types (ints, doubles, chars), Abstract Data Types (C++ class), multi-field sorting (≥ 2 criteria)
 - partial_sort – implementation of *heapsort*
 - Can do $O(k \log n)$ sorting, if we just need top-k sorted!
 - stable_sort
 - If you need to have the sorting ‘stable’, keys with same values appear in the same order as in input.

Sorting (4)

- \exists sorting algorithms faster than $O(n \log n)$ e.g.
 - Counting sort (only for special cases^)
 - Counting sort demo:
 - <http://users.cs.cf.ac.uk/C.L.Mumford/tristan/CountPage.html>
 - Example codes provided
 - UVa: [11462](#) (Age Sort)!
- There are others (not discussed today):
 - Radix*
 - Bucket sort, etc

Another “fundamental” CS problem

SEARCHING OUR DATA

Searching in Array

- Two variants:
 - When the array is sorted versus not sorted
- Must do $O(n)$ linear scan if not sorted - trivial
- Can use $O(\log n)$ binary search when sorted
 - PS: must run an $O(n \log n)$ sorting algorithm once
- Binary search is ‘tricky’ to code!
 - Instead, use C++ STL `<algorithm>`: `lower_bound`


Linear DS + Built-In Libraries (2)

3. Linked List, C++ STL `<list>`, Java `LinkedList`
 - Usually not used in ICPCs/IOIs
4. Stack, C++ STL `<stack>`, Java `Stack`
 - Used by default in Recursion, Postfix Calculation
5. Queue, C++ STL `<queue>`, Java `Queue`
 - Used in Breadth First Search, Topological Sort, etc

More efficient data structures

NON-LINEAR DATA STRUCTURES WITH BUILT-IN LIBRARIES


Binary Search Tree (1)



A binary search tree of size 9 and depth 3, with root 8 and leaves 1, 4, 7 and 13

- ADT Table (key \rightarrow data)
- Binary Search Tree (BST)
 - Advertised $O(\log n)$ for insert, search, and delete
 - Requirement: the BST must be **balanced**!
 - AVL tree, Red-Black Tree, etc... *argh*
- Do not worry, just use: C++ STL `<map>`
 - UVa [10295](#) (Hay Points)
 - UVa [10226](#) (Hardwood Species)*


Binary Search Tree (2)



A binary search tree of size 9 and depth 3, with root 8 and leaves 1, 4, 7 and 13

- ADT Table (key exists or not)
- Set (Single Set)
 - C++ STL `<set>`, similar to C++ STL `<map>`
 - `<map>` stores a `pair<key, data>`
 - `<set>` stores just the key
 - Can use `<set>` as vector with “auto-sort” feature


Heap



Example of a full binary max heap

- Heap
 - C++ STL `<algorithm>` has some heap algorithms
 - `partial_sort` uses heapsort
 - C++ STL `<queue>` has `priority_queue` (a heap)
 - Dijkstra and Kruskal's algorithms use priority queue
- But, we rarely see pure heap problems in ICPC
 - Perhaps for something like this:
 - Maintain top-k/bottom-k items given a very large stream of data...

Hash Table



A small phone book as a hash table.

- Hash Table
 - Advertised $O(1)$ for insert, search, and delete, but:
 - The hash function must be good!
 - There is no Hash Table in C++ STL (\exists in Java API)
 - Nevertheless, $O(\log n)$ using `<map>` is usually ok
- Direct Addressing Table (DAT)
 - Rather than hashing, we more frequently use DAT
 - UVa [11340](#) (Newspaper)
 - How about UVa [499](#)?

10 Minutes Break

- More data structures *without* built-in libraries will be discussed in the last part...
 - Many are outside CS1020/2010 syllabus
 - Graph (data structure only)
 - Union-Find Disjoint Sets
 - Segment Tree
 - Fenwick Tree
 - Some are discussed in CS2020 syllabus

[Graph \(data structure only\)](#)

[Union-Find Disjoint Sets](#)


[Segment Tree](#)

[Fenwick Tree](#)

DATA STRUCTURES WITHOUT BUILT-IN LIBRARIES


Graph Data Structures (1)

- Graph is a special data structure
 - Used to model objects and connections...
- Graph Representation:
 - `int AdjacencyMatrix[V][V];`
 - `typedef pair<int, int> ii; typedef vector<ii> vii;`
`vector<vii> AdjacencyList;`




Graph Data Structures (2)

- Graph Representation:
 - `typedef pair<int, int> ii;`
`priority_queue<pair <int, ii > > EdgeList;`
 - `typedef vector<int> vi;`
`int parent;`
`vi children;`




A

	1	2	3	4	5	6	7
1		1	1				
2	1		1	1			
3	1	1			1		
4		1			1		
5			1	1		1	
6					1		1
7						1	



C

1	↔	2
1	↔	3
2	↔	3
2	↔	4
3	↔	5
4	↔	5
5	↔	6
6	↔	7



$p(2) = \text{nil}$
 $c(2) = \{7, 5\}$
 $p(7) = 2$
 $c(7) = \{6\}$
 $p(5) = 2$
 $c(5) = \{9\}$
 $p(6) = 7$
 $c(6) = \text{nil}$
 $p(9) = 5$
 $c(9) = \text{nil}$

Graph Data Structures (3)

- Typical Input:

```
3 // n
0 2 3 // cell[i][j] > 0 implies that
0 0 4 //  $\exists$  an edge between vertex
0 1 0 // i-j with weight cell[i][j]
```

- Adjacency Matrix:

```
#define MAX_N 10 // set size
int G[MAX_N][MAX_N], n;
scanf("%d", &n);
REP (i, 0, n - 1)
    REP (j, 0, n - 1)
        scanf("%d", &G[i][j]);
```

Undirected graph has
symmetric adjacency matrix

- Typical Input:

```
3 // n
2 1 2 2 3 // vertex 0  $\rightarrow$  2 neighbors
1 2 4 // pair (neighbor, weight)
1 3 1
```

- Adjacency List (use STL):

```
vector<vii> G;
int V, t, j, w;
scanf("%d", &V);
REP (i, 0, V - 1) {
    vii Nb;
    scanf("%d", &t);
    while (t--) {
        scanf("%d %d", &j, &w);
        Nb.PB(ii(j, w));
    }
    G.PB(Nb);
}
```


Graph Data Structures (4)

- Adjacency Matrix:
- Pro:
 - Existence of edge $i-j$ can be found in $O(1)$
 - Good for dense graph/
Floyd Warshall's*
- Cons:
 - $O(V)$ to enumerate neighbors of a vertex
 - $O(V^2)$ space
- Adjacency List:
- Pro:
 - $O(k)$ to enumerate k neighbors of a vertex
 - Good for sparse graph/
Dijkstra's*/DFS/BFS
- Cons:
 - $O(k)$ to check the existence of edge $i-j$


Union-Find Disjoint Sets (1)

- Disjoint-Set DS (**Union Find**)
 - Given several disjoint sets initially...
 - **Combine** them when needed!
 - UVa:
 - [459](#) (Graph Connectivity)
 - [793](#) (Network Connections)
 - [10608](#) (Friends)
 - [11503](#) (Virtual Friends)


Overview



Operation Union



Operation Find



Applications

- Kruskal Minimum Spanning Tree algorithm
- Finding Connected Components in Graph
- Both discussed later in Week05-06
- etc

initSet(5)

```
vector<int> pset(1000); // 1000 is just an initial number, it is user-adjustable.
```

```
void initSet(int _size) { pset.resize(_size); REP (i, 0, _size - 1) pset[i] = i; }
```

```
int findSet(int i) { return (pset[i] == i) ? i : (pset[i] = findSet(pset[i])); }
```


```
void unionSet(int i, int j) { pset[findSet(i)] = findSet(j); }
```

```
bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }
```

// note:



```
#define REP(i, a, b) \ // all codes involving REP uses this macro
```

```
for (int i = int(a); i <= int(b); i++)
```




unionSet(A, B)

```
vector<int> pset(1000); // 1000 is just an initial number, it is user-adjustable.  
void initSet(int _size) { pset.resize(_size); REP (i, 0, _size - 1) pset[i] = i; }  
int findSet(int i) { return (pset[i] == i) ? i : (pset[i] = findSet(pset[i])); }  
void unionSet(int i, int j) { pset[findSet(i)] = findSet(j); }  
bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }
```




unionSet(A, C)

```
vector<int> pset(1000); // 1000 is just an initial number, it is user-adjustable.  
void initSet(int _size) { pset.resize(_size); REP (i, 0, _size - 1) pset[i] = i; }  
int findSet(int i) { return (pset[i] == i) ? i : (pset[i] = findSet(pset[i])); }  
void unionSet(int i, int j) { pset[findSet(i)] = findSet(j); }  
bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }
```




Now A, B, C become one set, identified by all three nodes having the same parent ID, directly or indirectly!





unionSet(D, B)

```
vector<int> pset(1000); // 1000 is just an initial number, it is user-adjustable.  
void initSet(int _size) { pset.resize(_size); REP (i, 0, _size - 1) pset[i] = i; }  
int findSet(int i) { return (pset[i] == i) ? i : (pset[i] = findSet(pset[i])); }  
void unionSet(int i, int j) { pset[findSet(i)] = findSet(j); }  
bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }
```



findSet(A)


```
vector<int> pset(1000); // 1000 is just an initial number, it is user-adjustable.  
void initSet(int _size) { pset.resize(_size); REP (i, 0, _size - 1) pset[i] = i; }  
int findSet(int i) { return (pset[i] == i) ? i : (pset[i] = findSet(pset[i])); }  
void unionSet(int i, int j) { pset[findSet(i)] = findSet(j); }  
bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }
```



This is called:
“Path Compression”!

isSameSet(A, E)

```
vector<int> pset(1000); // 1000 is just an initial number, it is user-adjustable.  
void initSet(int _size) { pset.resize(_size); REP (i, 0, _size - 1) pset[i] = i; }  
int findSet(int i) { return (pset[i] == i) ? i : (pset[i] = findSet(pset[i])); }  
void unionSet(int i, int j) { pset[findSet(i)] = findSet(j); }  
bool isSameSet(int i, int j) { return findSet(i) == findSet(j); }
```




Union-Find Disjoint Sets (2)

- Okay, that's the basics...
 - No *union-by-rank* or other detailed analysis...
- Further Reference:
 - **Introductions to Algorithms**, p505-509, ch21.3
 - **Algorithm Design**, p151-157, ch4.6
- No STL for this DS
 - We need to use the library shown previously
 - The code is short anyway

Segment Tree

- TBA



Fenwick Tree

- TBA

Top Coder Coding Style

SUPPLEMENTARY

Top Coder Coding Style (1)

- You may want to follow this coding style (C++)

1. Include all headers 😊

- `#include <vector>`
- `#include <set>`
- `#include <algorithm>`
- `#include <string>`
- `#include <cmath>`
- `#include <queue>`
- `#include <map>`
- `#include <iostream>`
- `#include <list>`
- `#include <deque>`
- `#include <cstdio>`
- `#include <cstdlib>`
- `using namespace std;`

Want More?

Add libraries that you frequently use into this template, e.g.:

`ctype.h`
`string.h`

`etc`

Top Coder Coding Style (2)

2. Use shortcuts for common data types

- `typedef long long ll;`
- `typedef long double ld;`
- `typedef vector<int> vi;`
- `typedef vector<bool> vb;`
- `typedef pair<int,int> ii;`
- `typedef vector<ii> vii;`
- `typedef set<int> si;`

3. Simplify Repetitions/Loops!

- `#define REP(i, a, b) for (int i = int(a); i <= int(b); i++)`
 - `#define REPN(i, n) REP (i, 1, int(n))`
 - `#define REPD(i, a, b) for (int i = int(a); i >= int(b); i--)`
 - `#define TR(c, it) for (vii::iterator it = (c).begin(); it != (c).end(); it++)`
 - `#define TR(c, it) for (typeof((c).begin()) it = (c).begin(); it != (c).end(); it++) // only for UNIX`
- Define your own loops style and stick with it!

Top Coder Coding Style (3)

4. More shortcuts

- `#define PB` `push_back`
- `#define MP` `make_pair`
- `#define SIZE(c)` `(int((c).size()))`
- `#define SHOW(x)` `cerr << #x << " = " << x << endl;`

5. STL/Libraries all the way!

- `isalpha (ctype.h)`
 - `inline bool isletter(char c) { return (c>='A'&&c<='Z') || (c>='a'&&c<='z'); }`
- `abs (math.h)`
 - `inline int abs(int a) { return a >= 0 ? a : -a; }`
- `pow (math.h)`
 - `int power(int a, int b) { int res=1; for (; b>=1; b--) res*=a; return res; }`
- Use STL data structures: `vector`, `stack`, `queue`, `priority_queue`, `map`, `set`, etc
- Use STL algorithms: `sort`, `lower_bound`, `max`, `min`, `max_element`, `min_element`, etc

Top Coder Coding Style (4)

6. Use I/O Redirection

- `int main() {`
- `// freopen("input.txt", "r", stdin); // avoid re-typing the test cases!`
- `// freopen("output.txt", "w", stdout); // but you may want to print to screen directly`
- `scanf and printf as per normal; // I prefer scanf/printf than cin/cout, C style is much easier`
- `}`

7. Use `memset` effectively!

- `#define INF 127 // if using memset, this is the best setting`
- `memset(dist, INF, sizeof(dist)); // useful to initialize shortest path distances, set INF to 127!`
- `memset(dp_memo, -1, sizeof(dp_memo)); // useful to initialize DP memoization table`
- `memset(arr, 0, sizeof(arr)); // useful to clear array of integers`

8. Declare static data structure

- All input size is known, declare data structure size LARGER than needed to avoid silly bugs
- Avoid dynamic data structures that involve pointers, etc

Top Coder Coding Style (5)

- Now our coding tasks are much simpler 😊
- Typing less code = shorter coding time
= better rank in programming contests 😊

Summary

- There are a lot of Data Structures
 - We need the most efficient one for our problem
 - Different DS suits different problem!
- Many of them have **built-in libraries**
- For some others, we have to build **our own**
 - Study these libraries! Do not rebuild them during contests!
- From Week 03 onwards and future ICPCs, use C++ STL and/or Java API and our built-in libraries!
 - Now, your team should be in rank 20-40 (from 60) (still solving ~1-2 problems out of 10, but faster)

Term Assignment Details

- TBA