

Event-Vision SoPC Companion Module for Reactive Drone Control

MVP definition, competitive positioning, and go-to-market for the drone market

PRODUCT	CATEGORY	DIFFERENTIATORS	STATUS
CoreLink companion board	Sense-and-avoid / guidance add-on	Sub-ms latency, HDR, low SWaP	Draft v0.1 — 7 Aug 2026

1. Executive Summary

CoreLink is a low-power companion module that gives existing drones **sub-millisecond reactive perception** by processing an event camera in streaming FPGA fabric. It plugs into the open PX4/ArduPilot ecosystem as a MAVLink/ROS 2 device and emits advisory outputs (brake, avoid, slow-down, capture) — it never directly commands flight controls.

The MVP sells a **determinism and latency advantage**, not a benchmark-win. Against Jetson and Hailo-class NPUs running the same task, CoreLink wins on end-to-end latency determinism, HDR robustness (no motion blur), and watts/J-per-decision; it may lose on raw TOPS/W for a fixed CNN, and the evaluation will say so honestly.

POSITIONING

The buyer is not the drone OEM who wants a generic accelerator. The buyer is an inspection/delivery service provider whose mission fails on blurred, missed, or slow-reacting perception. CoreLink makes the aircraft a better closed-loop observer at a fraction of a GPU's power budget.

2. Market Context

2.1 Target verticals

- **Power-line / utility inspection** — high-contrast scenes (sun, shadows, cable glare) are exactly where frame cameras fail and event cameras excel; reactive braking prevents contact with conductors and structures.
- **Indoor & near-field inspection** (tunnels, tanks, confined space) — low light, high dynamic range, tight maneuvering.
- **Delivery / logistics** — precision landing on marked pads, obstacle braking in cluttered yards.
- **First-response and agriculture** — follow and avoid in unstructured terrain (secondary, later).

2.2 Why now

- Commercial event sensors are now affordable and shipping (Prophesee, Samsung, Sony); the sensing bottleneck moved from sensor availability to processing.
- NPU/GPU latency jitter is a known, unfixable-in-software problem for closed-loop control; the market has not yet seen a companion product that owns the latency argument end-to-end.
- Open flight stacks (PX4/ArduPilot) make a drop-in companion module commercially viable without OEM certification work.

3. MVP Definition

DIMENSION	MVP SCOPE
Sensor	Single commercial event camera (Prophesee/DVS-class) with standard interface to PL.
Processing	Streaming FPGA pipeline: event pre-processing, time-surface accumulation, optical flow, occupancy/obstacle map.
Outputs	MAVLink/ROS 2 advisory messages: brake, avoid, slow-down, capture. Rate-limited and logged.
Safety	Advisory-only. No direct flight-control actuation. CBF safety filter enforces a minimum braking distance guarantee.
Out of scope v1	Autonomous BVLOS, safety certification, direct actuation, multi-sensor SLAM, LiDAR fusion, video encoding, generic CNN benchmarking.
Secondary extension	Event-based precision landing on a marked pad (visual servoing).

3.1 What it is not

- Not a generic FPGA accelerator board sold to OEMs.
- Not a competing autopilot.
- Not an NPU-killer — it does not promise to win TOPS/W for a fixed detector.
- Not a defect-diagnosis product; candidate flags remain reviewable by an operator.

4. Competitive Positioning

The reference comparison is a mission-grade companion computer (Jetson-class) and a low-power NPU (Hailo-class) executing the same perception task at matched accuracy and input rate. The honest win/loss table:

DIMENSION	CORELINK (SOPC)	JETSON-CLASS GPU	HAILO-CLASS NPU
End-to-end latency	Sub-ms, deterministic (p99 ≈ max)	30-100 ms, jittery	5-30 ms, batch-dependent
Latency under load	Constant (streaming)	Degrades with queue occupancy	Degrades with batch/fragmentation
HDR / motion-blur	Event-native (no blur)	Blur + rolling shutter	Frame-camera dependent
Power	Low (SoPC-class)	High	Very low
TOPS/W for fixed CNN	Loses to dedicated NPUs	Loses	Wins
Interface flexibility	Custom I/O, evolving sensor/model without silicon respin	Software-defined	Fixed graph, vendor tooling
Integration effort	HLS/RTL expertise required	Mature SDK	Vendor toolchain

The strategic claim: **deterministic latency and HDR robustness change what closed-loop control can do**. A GPU/NPU cannot win that argument by software tuning. This is the durable wedge; TOPS/W is conceded honestly.

5. Business Model & Go-to-Market

5.1 Entry market

Start with industrial drone **service providers and smaller custom-platform integrators** that already serve utilities and delivery. They fly open PX4/ArduPilot systems, control mission workflow, and feel re-flight/analyst cost directly. Do not begin by selling a generic board to OEMs or targeting vertically-integrated drone manufacturers.

5.2 Offer ladder

OFFER	CUSTOMER	COMMERCIAL PURPOSE
Pilot kit	Inspection service provider / integrator	Dev board or enclosed companion module, integration support, event logs, review export. Paid pilot or co-funded validation.
Retrofit product	Selected open-platform inspection fleets	Ruggedized companion module with supported camera and autopilot interfaces. Hardware margin + per-aircraft software/analytics licence.
OEM / NRE programme	Companion-computer or airframe suppliers	Custom I/O, form factor, bitstream after the core is field-proven. The scale path, not the first revenue path.

5.3 First commercial proof

The first commercial proof is **not a board shipment**. It is a buyer who can show on their own inspection workflow: fewer unusable captures, fewer repeat passes, faster analyst triage, or longer mission endurance. That evidence strengthens both the paper and subsequent design-in sales.

6. MVP Value Metrics

METRIC	MINIMUM THESIS TARGET	COMMERCIAL INTERPRETATION
Latency behavior	Measure mean, p95/p99, observed max at sustained input rate; p99 $\approx$ worst-case bound	A predictable advisory stream matters more than peak FPS
Reaction time	Reduced avoidance reaction time vs frame baseline in HIL	Faster braking/avoidance at same flight envelope
Energy	Report W and J per accepted observation across all three platforms	Supports SWaP and endurance discussions honestly
Usable-data yield	Measurable reduction in rejected/missing target imagery on a held-out mission set	Directly maps to reduced analyst and re-flight cost
Integration effort	Document interfaces, model update path, custom I/O changes	Tests the FPGA reconfigurability argument against real engineering effort

7. Risks and Controls

RISK	CONTROL
No pilot partner found	Require a pilot partner to quantify a baseline re-flight/analyst-time/capture-rejection cost before the hardware phase; if cost is not material, pivot the same co-processor to wind-turbine or confined-space inspection.
Event camera supply / interface	Early validate SPI/MIPI-to-PL path on the target SOM; keep a frame-camera fallback for the software baseline.
HLS/RTL bring-up slips	Mixed HLS+RTL; recorded-data replay keeps software/HIL work unblocked; bench-first gates.
NPU head-to-head loss	Concede TOPS/W; own latency-determinism + HDR + integration flexibility. Evaluation states where it loses.
Regulatory / liability	Advisory-only outputs, no actuation, indoor VLOS only in MVP.

8. Decision Summary

Build the CoreLink MVP: an event-vision SoPC companion module for reactive drone control, targeted first at power-line and confined-space inspection service providers on open flight stacks. The thesis and product share one claim — **sub-millisecond, deterministic perception unlocks control that frame-based GPU/NPU pipelines cannot reach** — which is both publishable and commercially defensible without winning a raw inference benchmark.

Selected evidence to verify before pilot: AMD Kria K26 SOM product brief; commercial event-sensor datasheet (Prophesee/Samsung-class) and PL interface; PX4/MAVLink companion-computer integration docs; relevant event-vision + UAV literature for the related-work section.