


Intro to Neural Networks

Machine Learning for Health Informatics



Anna Saranti

Holzinger Group hci-kdd.org


01.04.2019



Dataset splitting and overfitting (1/5)






Dataset splitting and overfitting (2/5)



Dataset splitting and overfitting (3/5)

- Pretend that part of the data is not seen yet
- The model makes a statement about this set - does this hold?




Dataset splitting and overfitting (4/5)

- <https://scikit-learn.org/stable/>
- `sklearn.model_selection.train_test_split`
- `sklearn.model_selection.StratifiedShuffleSplit`,
`sklearn.model_selection.StratifiedKFold`
- Training and test set should have roughly the same percentage of data in each class
- Beware that shuffling may spread a characteristic that exists in one part of the data in all the folds!

Dataset splitting and overfitting (5/5)

- Overfitting: Model memorizes and does not generalize to unseen data (test set)



Classification Metrics


- **Don't use accuracy!** The ratio of correct predictions) is not enough when the dataset is imbalanced. If a data set contains 90% of samples belonging to a single class, the classifier that by default (no programmed logic) only chooses this class, has 90% accuracy. The classifier is not informative - did not learn anything.
- Confusion matrix - compare the predicted class with the actual class:

		Predicted	
		Negative	Positive
Actual	Negative	TN	FP
	Positive	FN	TP

- Mutual information - measures how many bits the classifier's output conveys about the predicted target.
Helps comparing multi-class classifiers, not directly possible with confusion matrices 2×2 , 4×4 .

Neural Network for Classification (1/5)


One artificial neuron



- Prediction: $\hat{y} = \text{activation}(\sum_i x_i w_i + b) = f(x)$
- Error: $J = y - \hat{y}$


Neural Network for Classification (2/5)

- Learn a non-linear function of the input that approximates the output/target variable
- Architecture is not known, it must be learned as the parameters
- The input must be numeric and has to be scaled





Neural Network for Classification (3/5)

- Various non-linear activation functions (sigmoid, tanh, ReLU)
- Different methods to adapt step-wise the parameters to minimize the error - Bigger steps in the beginning, smaller in the end.
- Different architectures depending on the problem (CNN, RNN)
- Adjust a little the parameters/weights a little according to the error (difference) of the computed with the actual (target) (Back-propagation)



Neural Network for Classification (4/5)



Neural Network for Classification (5/5)

- Repeat until the parameters do not change a lot
- Don't learn too much - don't overfit.
- Check the output of the hidden layers and the values of the weights to discover some patterns

References

Duda, Richard O., Peter E. Hart, and David G. Stork (2012)

Pattern classification [Chapter 6]

John Wiley & Sons

Christopher M. Bishop (2006)

Pattern Recognition and Machine Learning [Chapter 5]

Springer

Aurélien Géron (2017)

Hands-On Machine Learning with Scikit-Learn and TensorFlow

O'Reilly

David J.C. MacKay (2003)

Information Theory, Inference, and Learning Algorithms

Cambridge University Press