

Project Setup Instructions: AsriATS – Applicant Tracking System

Table of Contents:

1. Introduction
2. Prerequisites
3. Cloning the Project
4. Configuration Setup
 - a. Appsettings Configuration
5. Database Setup
6. Folder Structure Setup
 - a. Uploads Folder
7. Running the Application
8. Notable Features and Modifications

1. Introduction

This document outlines the steps required to clone, configure, and modify the **AsriATS** project, a .NET-based Applicant Tracking System (ATS). The instructions cover setting up the development environment, configuring the database, and ensuring proper project modifications for handling file uploads.

2. Prerequisites

Before proceeding, ensure that you have the following installed on your local machine:

- .NET 8 SDK
- [PostgreSQL](#) (Ensure PostgreSQL is running and accessible)
- [Visual Studio 2022](#) or [VS Code](#)
- Entity Framework Core CLI
- Git

3. Cloning the Project

To clone the **AsriATS** project, follow the steps below:

1. Open your terminal or Git Bash.
2. Navigate to the directory where you want to clone the project.
3. Run the following Git command:

```
git clone https://github.com/han4solecode/Asri-ATS-v2.git
```

4. After the repository has been cloned, navigate into the project folder:

```
cd Asri-ATS-v2
```

4. Configuration Setup

Appsettings Configuration:

1. Open the project in your preferred IDE (Visual Studio or VS Code).
2. Locate the `appsettings.json` file in the **AsriATS.WebAPI** project. This file contains database connection strings and other important settings.
3. Modify the following fields to match your local environment:

```
{
  "Logging": {
    "LogLevel": {
      "Default": "Information",
      "Microsoft.AspNetCore": "Warning"
    }
  },
  "AllowedHosts": "*",
  "ConnectionStrings": {
    "DefaultConnection": "Host=localhost; Database=AsriATS;
Username=postgres; Password=123"
  },
  "JWT": {
    "Issuer": "http://localhost:7080",
```

```

    "Audience": "http://localhost:7080",
    "SigningKey":
"Customsecretkeynumber1112223333444555666777888999000"
  },
  "MailSettings": {
    "Host": "smtp.gmail.com",
    "DefaultCredentials": false,
    "Port": 465,
    "Name": "your app name",
    "EmailId": "your email",
    "UserName": "your username",
    "Password": "your password for app",
    "UseSSL": true
  }
}

```

4. Ensure the DefaultConnection is pointing to your PostgreSQL database.

5. Database Setup

The project uses **Entity Framework Core** with PostgreSQL as the database provider.

To set up the database:

1. Open your terminal in the **AsriATS** project folder.
2. You can set as startup project in WebAPI layer and in nuget package manager console you can choose persistence layer to run the migration
3. You can use nuget package manager console to update migration

update-database

4. If you need to generate a new migration in the future, use:

add-migration your-migration-name

6. Folder Structure Setup

Uploads Folder Setup:

The project requires a dedicated folder for storing uploaded files such as resumes, cover letters, and other supporting documents for job applications.

1. Create a new folder named `uploads` in the root directory of the **AsriATS.WebAPI** project.

Example:

```
AsriATS
├── AsriATS.WebAPI
│   └── uploads
```

2. Ensure that the `uploads` folder has appropriate read/write permissions, as files uploaded through the application will be saved here.
3. Update the `appsettings.json` to reflect the path for file uploads if necessary:

7. Running the Application

1. Ensure PostgreSQL is running.
2. Build the solution using :

```
dotnet build
```

3. Run the application:

```
dotnet run --project AsriATS.WebAPI
```

4. The API should be available at <https://localhost:7080> (or another configured port).

8. Notable Features and Modifications

1. File Upload Handling:

- a. The project handles file uploads (e.g., resumes, supporting documents) via API endpoints. Ensure the **uploads** folder exists in the Web API project.
- b. Uploaded files are stored in this folder and managed through services in the application layer.

2. Database Configuration:

- a. The project is configured to use PostgreSQL. Ensure the connection string in `appsettings.json` is properly set before running migrations.

3. Authorization:

- a. Several API methods require authorization based on user roles (e.g., Administrator, Applicant, Recruiter, HR Manager). Ensure you have valid JWT tokens when making requests to protected endpoints.

4. Swagger Documentation:

- a. API documentation is available via Swagger, accessible at <https://localhost:7080/swagger> when the application is running.

5. Reports:

- a. The system includes several PDF report generation endpoints, such as **Overall Recruitment Metrics**, **Approval Time**, and **Demographic Reports**.
- b. These reports are generated via the Polybioz PDF library and can be downloaded through corresponding API routes.

6. Email Templates:

- a. Several API methods are designed to send emails using pre-defined templates. These emails support various use cases, such as notifying applicants about their interview schedule from the HR Manager. The templates ensure consistency and ease of communication for different needs.
- b. If any changes to the email templates are required, they can be easily modified. To do so, navigate to the **Presentation** folder, then proceed to the **Templates** folder, and select the desired template from the **EmailTemplates** folder. The selected template can then be updated as necessary to meet new or adjusted communication requirements.

Troubleshooting

1. Database Connection Issues:

- a. If you encounter issues connecting to the database, verify that PostgreSQL is running and that your connection string in `appsettings.json` is correct.
- 2. File Upload Failures:**
- a. Ensure the uploads folder exists and has the necessary permissions to allow file read/write operations.

These instructions should help you get the **AsriATS** project up and running while ensuring all key components (such as file uploads and database connections) are configured correctly.