

The background of the entire image is a dark blue field filled with a pattern of red dots of varying sizes. These dots are arranged in a way that they form a large, faint, stylized circular shape in the center, creating a sense of depth and movement. The dots are more densely packed in some areas and more sparse in others, giving the pattern a dynamic, almost organic feel.

HUST

ĐẠI HỌC BÁCH KHOA HÀ NỘI
HANOI UNIVERSITY OF SCIENCE AND TECHNOLOGY

ONE LOVE. ONE FUTURE.



ĐẠI HỌC
BÁCH KHOA HÀ NỘI
HANOI UNIVERSITY
OF SCIENCE AND TECHNOLOGY

Machine Learning

IT3190E

Lecture: Probabilistic models – EM algorithm

ONE LOVE. ONE FUTURE.

Contents

- Lecture 1: Introduction to Machine Learning
- Lecture 2: Linear regression
- Lecture 3+4: Clustering
- Lecture 5: Decision tree and Random forest
- Lecture 6: Neural networks
- Lecture 7: Support vector machines
- Lecture 8: Performance evaluation
- **Lecture 9: Probabilistic models**
- Lecture 10: Ensemble learning
- Lecture 11: Reinforcement learning
- Lecture 12: Regularization
- Lecture 13: Discussion on some advanced topics

Difficult situations

- No closed-form solution for the learning/inference problem?
(không tìm được ngay công thức nghiệm)
 - The examples before are easy cases, as we can find solutions in a closed form by using gradient.
 - Many models (e.g., GMM) do not admit a closed-form solution
- No explicit expression of the density/mass function?
(không có công thức tường minh để tính toán)
- Intractable inference (bài toán không khả thi)
 - Inference in many probabilistic models is NP-hard
[Sontag & Roy, 2011; Tosh & Dasgupta, 2019]

Expectation maximization

- The EM algorithm

GMM revisit

- Consider learning GMM, with K Gaussian distributions, from the training data $\mathbf{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_M\}$.
- The density function is $p(\mathbf{x}|\boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi}) = \sum_{k=1}^K \phi_k \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k)$
 - $\boldsymbol{\phi} = (\phi_1, \dots, \phi_K)$ represents the weights of the Gaussians, $P(z = k | \boldsymbol{\phi}) = \phi_k$.
 - Each multivariate Gaussian has density
$$\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k) = \frac{1}{\sqrt{\det(2\pi\boldsymbol{\Sigma}_k)}} \exp\left[-\frac{1}{2}(\mathbf{x} - \boldsymbol{\mu}_k)^T \boldsymbol{\Sigma}_k^{-1}(\mathbf{x} - \boldsymbol{\mu}_k)\right]$$
- MLE tries to maximize the following log-likelihood function

$$L(\boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi}) = \sum_{i=1}^M \log \sum_{k=1}^K \phi_k \mathcal{N}(\mathbf{x}_i | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k)$$

- **We cannot find a closed-form solution!**
- **Naïve gradient decent:** repeat until convergence
 - Optimize $L(\boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi})$ w.r.t $\boldsymbol{\phi}$, when fixing $(\boldsymbol{\mu}, \boldsymbol{\Sigma})$.
 - Optimize $L(\boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi})$ w.r.t $(\boldsymbol{\mu}, \boldsymbol{\Sigma})$, when fixing $\boldsymbol{\phi}$.

Still hard

GMM revisit: K-means

□ GMM: we need to know

- Among K gaussian components, which generates an instance \mathbf{x} ?
the index z of the gaussian component
- The parameters of individual gaussian components: $(\boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k, \phi_k)$

□ K-means:

- Among K clusters, to which an instance \mathbf{x} belongs?
the cluster index z
- The parameters of individual clusters: the mean

□ Idea for GMM?

- $P(z|\mathbf{x}, \boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi})?$
(note $\sum_{k=1}^K P(z = k|\mathbf{x}, \boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi}) = 1$)

(soft assignment)
- Update the parameters of individual gaussians: $(\boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k, \phi_k)$

□ K-means training:

- Step 1: assign each instance \mathbf{x} to the nearest cluster
(the cluster index z for each \mathbf{x})
(hard assignment)
- Step 2: recompute the means of the clusters

GMM: lower bound

□ Idea for GMM?

- Step 1: compute $P(z|x, \mu, \Sigma, \phi)$? (note $\sum_{k=1}^K P(z = k|x, \mu, \Sigma, \phi) = 1$)
- Step 2: Update the parameters of the gaussian components: $\theta = (\mu, \Sigma, \phi)$

- Consider the log-likelihood function

$$L(\theta) = \log P(\mathbf{D}|\theta) = \sum_{i=1}^M \log \sum_{k=1}^K \phi_k \mathcal{N}(\mathbf{x}_i | \mu_k, \Sigma_k)$$

- Too complex if directly using gradient descent
- Note that $\log P(\mathbf{x}|\theta) = \log P(\mathbf{x}, z|\theta) - \log P(z|\mathbf{x}, \theta)$. Therefore

$$\log P(\mathbf{x}|\theta) = \mathbb{E}_{z|x, \theta} \log P(\mathbf{x}, z|\theta) - \mathbb{E}_{z|x, \theta} \log P(z|\mathbf{x}, \theta) \geq \mathbb{E}_{z|x, \theta} \log P(\mathbf{x}, z|\theta)$$

- Maximizing $L(\theta)$ can be done by *maximizing the lower bound*

$$LB(\theta) = \sum_{\mathbf{x} \in \mathbf{D}} \mathbb{E}_{z|x, \theta} \log P(\mathbf{x}, z|\theta) = \sum_{\mathbf{x} \in \mathbf{D}} \sum_z P(z|\mathbf{x}, \theta) \log P(\mathbf{x}, z|\theta)$$

GMM: maximize the lower bound

- Step 1: compute $P(z|\mathbf{x}, \boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi})$? (note $\sum_{k=1}^K P(z = k|\mathbf{x}, \boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi}) = 1$)
- Step 2: Update the parameters of the gaussian components: $\boldsymbol{\theta} = (\boldsymbol{\mu}, \boldsymbol{\Sigma}, \boldsymbol{\phi})$

- Bayes' rule: $P(z|\mathbf{x}, \boldsymbol{\theta}) = P(\mathbf{x}|z, \boldsymbol{\theta})P(z|\boldsymbol{\phi})/P(\mathbf{x}) = \phi_z \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_z, \boldsymbol{\Sigma}_z)/C$, where C is the normalizing constant.

- Meaning that one can compute $P(z|\mathbf{x}, \boldsymbol{\theta})$ if $\boldsymbol{\theta}$ is known
- Denoting $T_{ki} = P(z = k|\mathbf{x}_i, \boldsymbol{\theta})$ for any index $k = \overline{1, K}, i = \overline{1, M}$

- How about $\boldsymbol{\phi}$?

- $\phi_z = P(z|\boldsymbol{\phi}) = P(z|\boldsymbol{\theta}) = \int P(z, \mathbf{x}|\boldsymbol{\theta})d\mathbf{x} = \int P(z|\mathbf{x}, \boldsymbol{\theta})P(\mathbf{x}|\boldsymbol{\theta})d\mathbf{x} = \mathbb{E}_{\mathbf{x}}(P(z|\mathbf{x}, \boldsymbol{\theta})) \approx \frac{1}{M} \sum_{\mathbf{x} \in D} P(z|\mathbf{x}, \boldsymbol{\theta}) = \frac{1}{M} \sum_{i=1}^M T_{zi}$

- Then the lower bound can be maximized w.r.t individual $(\boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k)$:


$$\begin{aligned} LB(\boldsymbol{\theta}) &= \sum_{\mathbf{x} \in D} \sum_z P(z|\mathbf{x}, \boldsymbol{\theta}) \log[P(\mathbf{x}|z, \boldsymbol{\theta})P(z|\boldsymbol{\theta})] \\ &= \sum_{i=1}^M \sum_{k=1}^K T_{ki} \left[-\frac{1}{2} (\mathbf{x}_i - \boldsymbol{\mu}_k)^T \boldsymbol{\Sigma}_k^{-1} (\mathbf{x}_i - \boldsymbol{\mu}_k) - \log \sqrt{\det(2\pi \boldsymbol{\Sigma}_k)} \right] + constant \end{aligned}$$

GMM: EM algorithm


- **Input:** training data $D = \{x_1, x_2, \dots, x_M\}$, $K > 0$
- **Output:** model parameter (μ, Σ, ϕ)
- Initialize $(\mu^{(0)}, \Sigma^{(0)}, \phi^{(0)})$ randomly
 - $\phi^{(0)}$ must be non-negative and sum to 1.
- At iteration t :
 - **E step:** compute $T_{ki} = P(z = k | x_i, \theta^{(t)}) = \phi_k^{(t)} \mathcal{N}(x_i | \mu_k^{(t)}, \Sigma_k^{(t)}) / C$ for any index $k = \overline{1, K}, i = \overline{1, M}$
 - **M step:** update for any k ,
$$\phi_k^{(t+1)} = \frac{1}{M} \sum_{i=1}^M T_{ki}; \mu_k^{(t+1)} = \frac{1}{M\phi_k} \sum_{i=1}^M T_{ki} x_i;$$
$$\Sigma_k^{(t+1)} = \frac{1}{M\phi_k} \sum_{i=1}^M T_{ki} (x_i - \mu_k^{(t+1)}) (x_i - \mu_k^{(t+1)})^T$$
- If not convergence, go to iteration $t + 1$.

GMM: example 1

- We wish to model the height of a person
 - We had collected a dataset from 10 people in Hanoi + 10 people in Sydney
 $\mathbf{D} = \{1.6, 1.7, 1.65, 1.63, 1.75, 1.71, 1.68, 1.72, 1.77, 1.62, 1.75, 1.80, 1.85, 1.65, 1.91, 1.78, 1.88, 1.79, 1.82, 1.81\}$




GMM with
2 components




GMM with
3 components

GMM: example 2

- A GMM is fitted in a 2-dimensional dataset to do clustering.



From initialization



To convergence

https://en.wikipedia.org/wiki/Expectation-maximization_algorithm

GMM: comparison with K-means

□ K-means:


- Step 1: hard assignment
- Step 2: the means
→ similar shape for the clusters?

□ GMM clustering


- Soft assignment of data to the clusters
- Parameters (μ_k, Σ_k, ϕ_k)
→ different shapes for the clusters

Different cluster analysis results on "mouse" data set:


Original Data



k-Means Clustering



EM Clustering



https://en.wikipedia.org/wiki/Expectation-maximization_algorithm

General models

- We can make the EM algorithm in more general cases.
- Consider a model $B(\mathbf{x}, \mathbf{z}; \boldsymbol{\theta})$ with observed variable \mathbf{x} , hidden variable \mathbf{z} , and parameterized by $\boldsymbol{\theta}$
(mô hình có một biến \mathbf{x} quan sát được, biến ẩn \mathbf{z} , và tham số $\boldsymbol{\theta}$)
 - \mathbf{x} depends on \mathbf{z} and $\boldsymbol{\theta}$, while \mathbf{z} may depend on $\boldsymbol{\theta}$
 - Mixture models: each observed data point has a corresponding latent variable, specifying the mixture component which generated the data point
- The learning task is to find a specific model, from the model family parameterized by $\boldsymbol{\theta}$, that maximizes the log-likelihood of training data \mathbf{D} :
$$\boldsymbol{\theta}^* = \operatorname{argmax}_{\boldsymbol{\theta}} \log P(\mathbf{D}|\boldsymbol{\theta})$$
- We assume \mathbf{D} consists of i.i.d samples of \mathbf{x} , the the log-likelihood function can be expressed analytically, $\mathbb{E}_{\mathbf{z}|\mathbf{D},\boldsymbol{\theta}} \log P(\mathbf{D}|\boldsymbol{\theta})$ can be computed easily (hàm log-likelihood có thể viết một cách tường minh)
 - Since there is a latent variable, MLE may not have a close form solution

The Expectation Maximization algorithm

- The Expectation maximization (EM) algorithm was introduced in 1977 by Arthur Dempster, Nan Laird, and Donald Rubin.
- The EM algorithm maximizes the lower bound of the log-likelihood

$$L(\boldsymbol{\theta}; \mathbf{D}) = \log P(\mathbf{D}|\boldsymbol{\theta}) \geq LB(\boldsymbol{\theta}) = \sum_{\mathbf{x} \in \mathbf{D}} \mathbb{E}_{z|\mathbf{x}, \boldsymbol{\theta}} \log P(\mathbf{x}, z|\boldsymbol{\theta})$$


- *Initialization: $\boldsymbol{\theta}^{(0)}, t = 0$*
- *At iteration t :*
 - **E step:** *compute the expectation $Q(\boldsymbol{\theta}|\boldsymbol{\theta}^{(t)}) = LB(\boldsymbol{\theta}^{(t-1)})$*
(tính hàm kỳ vọng Q khi cố định giá trị $\boldsymbol{\theta}^{(t)}$ đã biết ở bước trước)
 - **M step:** *find $\boldsymbol{\theta}^{(t+1)} = \operatorname{argmax}_{\boldsymbol{\theta}} Q(\boldsymbol{\theta}|\boldsymbol{\theta}^{(t)})$*
(tìm điểm $\boldsymbol{\theta}^{(t+1)}$ mà làm cho hàm Q đạt cực đại)
- *If not convergence, go to iteration $t + 1$.*

EM: convergence condition

- Different conditions can be used to check convergence
 - $LB(\theta)$ does not change much between two consecutive iterations
 - θ does not change much between two consecutive iterations
- In practice, we sometimes need to limit the maximum number of iterations

EM: some properties

- The EM algorithm is guaranteed to return a stationary point of the lower bound $LB(\theta)$
(thuật toán EM đảm bảo sẽ hội tụ về một điểm dừng của hàm cận dưới)
 - It may be the local maximum
- Due to maximizing the lower bound, EM does not necessarily return the maximizer of the log-likelihood function
(EM chưa chắc trả về điểm cực đại của hàm log-likelihood)
 - No guarantee exists
 - It can be seen in cases of multimodel, where the log-likelihood function is non-concave
- The Baum-Welch algorithm is the a special case of EM for hidden Markov models




EM, mixture model, and clustering

- *Mixture model*: we assume the data population is composed of K different components (distributions), and each data point is generated from one of those components
 - E.g., Gaussian mixture model, categorical mixture model, Bernoulli mixture model,...
 - The mixture density function can be written as

$$f(\mathbf{x}; \boldsymbol{\theta}, \boldsymbol{\phi}) = \sum_{k=1}^K \phi_k f_k(\mathbf{x} | \boldsymbol{\theta}_k)$$

where $f_k(\mathbf{x} | \boldsymbol{\theta}_k)$ is the density of the k -th component

- We can interpret that a mixture distribution partitions the data space into different regions, each associates with a component
(Một phân bố hỗn hợp tạo ra một cách chia không gian dữ liệu ra thành các vùng khác nhau, mà mỗi vùng tương ứng với 1 thành phần trong hỗn hợp đó)
- Hence, mixture models provide solutions for clustering
- The EM algorithm provides a natural way to learn mixture models



- When the lower bound $LB(\theta)$ does not admit easy computation of the expectation or maximization steps
 - Admixture models, Bayesian mixture models
 - Hierarchical probabilistic models
 - Nonparametric models
- EM finds a point estimate, hence easily gets stuck at a local maximum
- In practice, EM is sensitive with initialization
 - Is it good to use the idea of K-means++ for initialization?
- Sometimes EM converges slowly in practice

Further?

- Variational inference
 - Inference for more general models
- Deep generative models
 - Neural networks + probability theory
- Bayesian neural networks
 - Neural networks + Bayesian inference
- Amortized inference
 - Neural networks for doing Bayesian inference
 - Learning to do inference

Reference

- Blei, David M., Alp Kucukelbir, and Jon D. McAuliffe. "Variational inference: A review for statisticians." *Journal of the American Statistical Association* 112, no. 518 (2017): 859-877.
- Blundell, Charles, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. "Weight Uncertainty in Neural Network." In *International Conference on Machine Learning (ICML)*, pp. 1613-1622. 2015.
- Dempster, A.P.; Laird, N.M.; Rubin, D.B. (1977). "Maximum Likelihood from Incomplete Data via the EM Algorithm". *Journal of the Royal Statistical Society, Series B*. 39 (1): 1-38.
- Gal, Yarin, and Zoubin Ghahramani. "Dropout as a bayesian approximation: Representing model uncertainty in deep learning." In *ICML*, pp. 1050-1059. 2016.
- Ghahramani, Zoubin. "Probabilistic machine learning and artificial intelligence." *Nature* 521, no. 7553 (2015): 452-459.
- Kingma, Diederik P., and Max Welling. "Auto-encoding variational bayes." In *International Conference on Learning Representations (ICLR)*, 2014.
- Jordan, Michael I., and Tom M. Mitchell. "Machine learning: Trends, perspectives, and prospects." *Science* 349, no. 6245 (2015): 255-260.
- Tosh, Christopher, and Sanjoy Dasgupta. "The Relative Complexity of Maximum Likelihood Estimation, MAP Estimation, and Sampling." In *COLT, PMLR* 99:2993-3035, 2019.
- Sontag, David, and Daniel Roy, "Complexity of inference in latent dirichlet allocation" in: *Advances in Neural Information Processing System*, 2011.

A decorative graphic on the left side of the slide. It features a dark blue background with a large, stylized circular pattern composed of many small red dots. The dots are arranged in a way that creates a sense of depth and movement, resembling a spiral or a series of concentric circles that are slightly offset from each other.

HUST

THANK YOU !