Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 43
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer is designing an AWS Lambda function that creates temporary files that are less than 10 MB during invocation. The temporary files will be accessed and modified multiple times during invocation. The developer has no need to save or retrieve these files in the future.
Where should the temporary files be stored?

A. the /tmp directory

B. Amazon Elastic File System (Amazon EFS)

C. Amazon Elastic Block Store (Amazon EBS)

D. Amazon S3

Show Suggested Answer

---

by Untamables at *March 26, 2023, 2:03 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

Untamables Highly Voted 2 years, 6 months ago

Selected Answer: A

A
A Lambda function has access to local storage in the /tmp directory. Each execution environment provides between 512 MB and 10,240 MB, in 1-MB increments, of disk space in the /tmp directory.
https://docs.aws.amazon.com/lambda/latest/dg/foundation-progmodel.html

upvoted 19 times

sumanshu Most Recent 1 year, 3 months ago

Selected Answer: A

A) Correct - AWS Lambda provides a /tmp directory with storage between 51B to 10,240 MB.
https://docs.aws.amazon.com/lambda/latest/dg/configuration-ephemeral-storage.html. The files in this directory are ephemeral and will be deleted after the function execution ends.
B) Eliminated - Temporary files are not required to persist beyond the invocation, and using EFS would increase complexity and cost.

C) Eliminated - Lambda does not directly support EBS volumes

D) Eliminated- While S3 can store temporary data, it is not optimized for high-speed read/write operations during a Lambda invocation. Additionally, the use case specifies that the files do not need to be saved or retrieved later, making S3 an unnecessary overhead.

upvoted 2 times

65703c1 1 year, 4 months ago

Selected Answer: A

A is the correct answer.

upvoted 1 times

Mtho96 2 years, 2 months ago

The correct answer is A
The /tmp directory is the recommended location for storing temporary files within an AWS Lambda function. The /tmp directory provides a writable space with a local storage capacity of 512 MB. It is specifically designed for temporary storage within the Lambda execution environment.

upvoted 4 times