Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 45
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer is writing an AWS Lambda function. The developer wants to log key events that occur while the Lambda function runs. The developer wants to include a unique identifier to associate the events with a specific function invocation. The developer adds the following code to the Lambda function:

```
function handler(event, context) {

}
```

Which solution will meet this requirement?

A. Obtain the request identifier from the AWS request ID field in the context object. Configure the application to write logs to standard output.

B. Obtain the request identifier from the AWS request ID field in the event object. Configure the application to write logs to a file.

C. Obtain the request identifier from the AWS request ID field in the event object. Configure the application to write logs to standard output.

D. Obtain the request identifier from the AWS request ID field in the context object. Configure the application to write logs to a file.

Show Suggested Answer

by March2023 at *March 23, 2023, 11:34 p.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

ninomfr64 Highly Voted 2 years, 1 month ago

Selected Answer: A

Both A and D could work here, as both rely on the context object to get access to execution ID
https://docs.aws.amazon.com/us_en/lambda/latest/dg/python-context.html
While A uses stoud to send log to CloudWatch Log, D writes to a file. D is less specific (where is the file stored? A single file for each execution?) and looks more comples (manage file(s), manage concurrency access to the file ...), thus I'll go for A

upvoted 15 times

Untamables Highly Voted 2 years, 6 months ago

Selected Answer: A

A
https://docs.aws.amazon.com/lambda/latest/dg/nodejs-context.html
https://docs.aws.amazon.com/lambda/latest/dg/nodejs-logging.html
There is no explicit information for the runtime, the code is written in Node.js.

upvoted 8 times

Pupina 2 years, 2 months ago

• https://docs.aws.amazon.com/prescriptive-guidance/latest/implementing-logging-monitoring-cloudwatch/lambda-logging-metrics.html
• Lambda automatically streams standard output and standard error messages from a Lambda function to CloudWatch Logs, without requiring logging drivers.

upvoted 2 times

ProcureSense Most Recent 1 year ago

Selected Answer: A

https://docs.aws.amazon.com/lambda/latest/dg/getting-started.html

upvoted 1 times

sumanshu 1 year, 3 months ago

Selected Answer: A

A) Correct - The context object contains the AWS request ID, which uniquely identifies each function invocation. Writing logs to standard output ensures they are automatically captured by CloudWatch Logs.

B) Eliminated - The event object contains input data passed to the Lambda function but does not include the AWS request ID. Writing logs to a file is not practical in Lambda because the filesystem is ephemeral, and logs stored in files would not persist beyond the function invocation.

upvoted 2 times

65703c1 1 year, 4 months ago

Selected Answer: A

A is the correct answer.

upvoted 1 times

badsati 1 year, 5 months ago

Selected Answer: A

A should work

upvoted 1 times

james2033 1 year, 7 months ago

Selected Answer: A

See getAwsRequestId() at
https://docs.aws.amazon.com/lambda/latest/dg/java-context.html

upvoted 1 times

rimaSamir 1 year, 7 months ago

Tricky question. Sure A and D both can do, but... The question is: why we need to get the request identifier if we will write logs to CloudWatch? So, I will go with answer A.

upvoted 1 times

SD_CS 1 year, 8 months ago

I think it should be A. Also can anyone advise why the two answers are different ?
https://www.examtopics.com/discussions/amazon/view/29007-exam-aws-certified-developer-associate-topic-1-question-26/

upvoted 2 times

KarBiswa 1 year, 9 months ago

The Option A is correct because:
The second argument is the context object. A context object is passed to your function by Lambda at runtime. This object provides methods and properties that provide information about the invocation, function, and runtime environment.
https://docs.aws.amazon.com/lambda/latest/dg/python-handler.html

upvoted 1 times

hsinchang 2 years ago

invocation is in the Context object, and loggging into Standard output, which goes into CloudWatch(more durable, more scalable, etc.), is generally better than using temporary Files

upvoted 1 times

Pupina 2 years, 2 months ago

Selected Answer A:
Handler function
https://docs.aws.amazon.com/lambda/latest/dg/nodejs-handler.html
Context object awsRequestId – The identifier of the invocation request.
https://docs.aws.amazon.com/lambda/latest/dg/nodejs-context.html

upvoted 1 times

rlnd2000 2 years, 3 months ago

Selected Answer: A

In my opinion both options A and D can fulfill the requirement, since there is no requirement about any specific logging and monitoring tool I will go with defaults (A) because, simple is better than complex :)

upvoted 1 times

Prem28 2 years, 4 months ago

Selected Answer: A

The application can write logs to standard output or to a file. Standard output is the default destination for logs. Logs that are written to standard output are sent to Amazon CloudWatch Logs. Logs that are written to a file are stored on the Lambda function's execution environment.

upvoted 5 times

Nagendhar 2 years, 4 months ago

Ans: D

The code snippet provided in the question is obtaining the request identifier from the context.awsRequestId property, which is available in the context object provided to the Lambda function handler. Therefore, the correct option is:

D. Obtain the request identifier from the AWS request ID field in the context object. Configure the application to write logs to a file.

This option meets the requirement of logging key events and including a unique identifier to associate the events with a specific function invocation.

upvoted 1 times

Rpod 2 years, 5 months ago

Selected Answer: D

Why not D ? Writing logs to a file seems more appropriate than stdout

upvoted 3 times

Watascript 2 years, 6 months ago

Selected Answer: A

https://docs.aws.amazon.com/us_en/lambda/latest/dg/python-context.html
https://docs.aws.amazon.com/us_en/lambda/latest/dg/python-logging.html

upvoted 4 times