Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 53
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer is using an AWS Lambda function to generate avatars for profile pictures that are uploaded to an Amazon S3 bucket. The Lambda function is automatically invoked for profile pictures that are saved under the /original/ S3 prefix. The developer notices that some pictures cause the Lambda function to time out. The developer wants to implement a fallback mechanism by using another Lambda function that resizes the profile picture.
Which solution will meet these requirements with the LEAST development effort?

A. Set the image resize Lambda function as a destination of the avatar generator Lambda function for the events that fail processing.

B. Create an Amazon Simple Queue Service (Amazon SQS) queue. Set the SQS queue as a destination with an on failure condition for the avatar generator Lambda function. Configure the image resize Lambda function to poll from the SQS queue.

C. Create an AWS Step Functions state machine that invokes the avatar generator Lambda function and uses the image resize Lambda function as a fallback. Create an Amazon EventBridge rule that matches events from the S3 bucket to invoke the state machine.

D. Create an Amazon Simple Notification Service (Amazon SNS) topic. Set the SNS topic as a destination with an on failure condition for the avatar generator Lambda function. Subscribe the image resize Lambda function to the SNS topic.

Show Suggested Answer

by March2023 at *March 24, 2023, 3:27 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

March2023 Highly Voted 3 years ago

Selected Answer: A

Wouldn't A be the Least Effort

upvoted 14 times

jingle4944 Highly Voted 2 years, 6 months ago

Selected Answer: A

Previously, you needed to write the SQS/SNS/EventBridge handling code within your Lambda function and manage retries and failures yourself.

With Destinations, you can route asynchronous function results as an execution record to a destination resource without writing additional code.

https://aws.amazon.com/ru/blogs/compute/introducing-aws-lambda-destinations/

upvoted 11 times

sumanshu Most Recent 1 year, 3 months ago

Selected Answer: A

AWS Lambda supports Destinations for asynchronous invocations. You can configure a failure destination that triggers a fallback mechanism, such as invoking another Lambda function. This removes the need for additional services like SQS, SNS, or Step Functions, simplifying the architecture.

upvoted 3 times

f271c23 1 year, 3 months ago

Selected Answer: B

Least development effort does not mean incomplete solution. what happens when the number of such issues are high and request needs to be queued. does not sound convincing

upvoted 1 times

lambdaFun 1 year, 5 months ago

A is the correct Answer if we read the question in the last part "The developer wants to implement a fallback mechanism by using another Lambda function"

upvoted 2 times

PrinceMughal 1 year, 9 months ago

Selected Answer: A

I will go with A as it is the simplest solution among other three option

upvoted 1 times

fabiomonta18 1 year, 9 months ago

Selected Answer: B

This seems to be a tricky one. It's true that you can set Lambda destination, but you better set SQS as destination, exactly what the article suggests, go check it. The correct one is B.
https://docs.aws.amazon.com/lambda/latest/dg/invocation-async.html#invocation-async-destinations

upvoted 1 times

65703c1 1 year, 10 months ago

Selected Answer: A

A is the correct answer.

upvoted 1 times

vipyodha 2 years ago

B is right.
A.wrong because
Lambda Function Chaining: While Lambda function chaining is possible, it would require modifying the avatar generation Lambda function to include the resize function as a destination for failed events. This might involve additional coding and potentially more complex error handling within the Lambda function.

upvoted 2 times

Tluszczyk 1 year, 8 months ago

With AWS Lambda destinations you don't need to interact with code to change this

upvoted 2 times

KarBiswa 2 years, 3 months ago

Selected Answer: A

Least development effort no emphasis on orchestration

upvoted 3 times

KarBiswa 2 years, 1 month ago

https://aws.amazon.com/ru/blogs/compute/introducing-aws-lambda-destinations/ this link justifies the answer

upvoted 2 times

fabiomonta18 1 year, 9 months ago

The article says "For each execution status such as Success or Failure you can choose one of four destinations: another Lambda function, SNS, SQS, or EventBridge." It hink for this reason the correct one is B.

upvoted 2 times

fabiomonta18 1 year, 9 months ago

I mean, which destination other then SQS can you set in this case?

upvoted 1 times

Jonalb 2 years, 5 months ago

Selected Answer: A

A. Defina a função Lambda de redimensionamento de imagem como um destino da função Lambda do gerador de avatar para os eventos que falham no processamento

upvoted 1 times

appuNBablu 2 years, 6 months ago

A, because we can map another Lambda function as destination alongside (SQS, SNS, Event Bridge)

upvoted 1 times

ninomfr64 2 years, 7 months ago

Selected Answer: A

A is the easiest option
https://docs.aws.amazon.com/lambda/latest/dg/invocation-async.html#invocation-async-destinations

upvoted 1 times

jayvarma 2 years, 7 months ago

Option B is the right answer. Can someone say why B cannot be the right answer for this question?

Option A fails when there are huge amounts of requests coming to the lambda functions. There is every chance for lambda to throw ProvisionedThrougputExceeded Exception because of the throttling issues. Which is almost the similar reason why Option C will also fail at some point.

However, you could use SNS but it is not the best solution.

Definitely Option B.

upvoted 8 times

backfringe 2 years, 8 months ago

Selected Answer: A

least amount of effort to set up destination on failure events to REsize Lambda

upvoted 1 times

AWSdeveloper08 2 years, 8 months ago

Selected Answer: B

I agree with the explanation for option B. Scalability is the key

upvoted 2 times

umer1998 2 years, 9 months ago

I agree with B because I am considering scalability in my mind if we have thousands/millions of requests at the same time. because of the quota limit, the lambda can fail if we continuously call two functions (step function) together, which may result in another function doing a throttling issue.
If we pass the message to the SQS, our function will never face this issue with throttling.
and since the question asks us to do the least development efforts. Separation of concerns will make development easier.

upvoted 3 times