Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 115
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer needs to build an AWS CloudFormation template that self-populates the AWS Region variable that deploys the CloudFormation template.

What is the MOST operationally efficient way to determine the Region in which the template is being deployed?

A. Use the AWS::Region pseudo parameter.

B. Require the Region as a CloudFormation parameter.

C. Find the Region from the AWS::StackId pseudo parameter by using the Fn::Split intrinsic function.

D. Dynamically import the Region by referencing the relevant parameter in AWS Systems Manager Parameter Store.

Show Suggested Answer

---

by MrTee at *April 22, 2023, 9:55 p.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

MrTee Highly Voted 2 years, 11 months ago

Selected Answer: A

A. Use the AWS::Region pseudo parameter.

upvoted 10 times

sumanshu Most Recent 1 year, 3 months ago

Selected Answer: A

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/mappings-section-structure.html

AWS::Region is a pseudo parameter that automatically provides the Region where the stack is being deployed (e.g., us-east-1 if deploying in the US East Region).

B) Eliminated - Adding a parameter for the Region means users would need to manually specify the Region every time they deploy the template

C) Eliminated - While the stack ID contains the Region as part of its value (e.g., arn:aws:cloudformation:us-east-1:123456789012:stack/MyStack/...), extracting it with Fn::Split is a complicated workaround.

D) Eliminated

upvoted 2 times

albert_kuo 1 year, 6 months ago

Selected Answer: A

Resources:
MyS3Bucket:
Type: "AWS::S3::Bucket"
Properties:
BucketName: !Sub "my-bucket-${AWS::Region}"

upvoted 1 times

65703c1 1 year, 10 months ago

Selected Answer: A

A is the correct answer.

upvoted 1 times

Baba_Eni 2 years, 9 months ago

Selected Answer: A

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/pseudo-parameter-reference.html

upvoted 2 times

Baba_Eni 2 years, 9 months ago

Selected Answer: A

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/pseudo-parameter-reference.htmlhttps://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/pseudo-parameter-reference.html

upvoted 1 times

loctong 2 years, 10 months ago

Selected Answer: A

The AWS::Region pseudo parameter is a built-in CloudFormation parameter that automatically resolves to the AWS Region where the CloudFormation stack is being created. By using this pseudo parameter, you can dynamically access the current Region without requiring any additional configuration or input.

upvoted 4 times