Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 122
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer is developing an application that uses signed requests (Signature Version 4) to call other AWS services. The developer has created a canonical request, has created the string to sign, and has calculated signing information.

Which methods could the developer use to complete a signed request? (Choose two.)

A. Add the signature to an HTTP header that is named Authorization.

B. Add the signature to a session cookie.

C. Add the signature to an HTTP header that is named Authentication.

D. Add the signature to a query string parameter that is named X-Amz-Signature.

E. Add the signature to an HTTP header that is named WWW-Authenticate.

Show Suggested Answer

---

by MrTee at *April 22, 2023, 11:33 p.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

vicvega Highly Voted 2 years, 2 months ago

Header:

Authorization: AWS4-HMAC-SHA256
Credential=AKIAIOSFODNN7EXAMPLE/20220830/us-east-1/ec2/aws4_request,
SignedHeaders=host;x-amz-date,
Signature=calculated-signature

Query String:

https://ec2.amazonaws.com/?
Action=DescribeInstances&
Version=2016-11-15&
X-Amz-Signature=calculated-signature

https://docs.aws.amazon.com/IAM/latest/UserGuide/create-signed-request.html

upvoted 10 times

MrTee Highly Voted 2 years, 5 months ago

Selected Answer: AD

the correct options are A and D.

upvoted 9 times

sumanshu Most Recent 1 year, 3 months ago

Selected Answer: AD

The developer has already performed the necessary steps to generate the signature but needs to know where to place the signature in the request to ensure the request is valid and properly authenticated.

A) Correct - SigV4 officially supports placing the signature in the Authorization header,

C) Eliminated - AWS specifically requires the Authorization header for passing the signature in HTTP headers

D) Correct - SigV4 allows for query string authentication as an alternative to using the Authorization header. This is especially useful for presigned URLs, where the signature and other necessary information are passed in the query string (e.g., X-Amz-Signature)

upvoted 1 times

sumanshu 1 year, 1 month ago

C) Eliminated - The correct header is Authorization, not Authentication

upvoted 1 times

sumanshu 1 year, 1 month ago

E) Eliminated - This is used for different types of authentication (like when a website asks for a username and password), not AWS Signature V4.

upvoted 1 times

65703c1 1 year, 4 months ago

Selected Answer: AD

AD is the correct answer.

upvoted 1 times

SerialiDr 1 year, 8 months ago

Selected Answer: AD

A. Add the signature to an HTTP header that is named Authorization: This is a correct method. In Signature Version 4, the completed signature is typically added to the request's Authorization header. This header includes the signing information along with other necessary components such as the Credential Scope and the Signed Headers.

D. Add the signature to a query string parameter that is named X-Amz-Signature: This is a correct method. In addition to including the signature in the Authorization header, Signature Version 4 also allows for presigned URLs where the signature is part of the query string parameters. The signature is included in the X-Amz-Signature query string parameter.

upvoted 3 times

loctong 2 years, 4 months ago

Selected Answer: AD

Option B,C And E are not correct;

upvoted 1 times

awsdummie 2 years, 4 months ago

Selected Answer: AD

https://docs.aws.amazon.com/IAM/latest/UserGuide/create-signed-request.html

upvoted 2 times