Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 138
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

Users are reporting errors in an application. The application consists of several microservices that are deployed on Amazon Elastic Container Service (Amazon ECS) with AWS Fargate.

Which combination of steps should a developer take to fix the errors? (Choose two.)

A. Deploy AWS X-Ray as a sidecar container to the microservices. Update the task role policy to allow access to the X-Ray API.

B. Deploy AWS X-Ray as a daemonset to the Fargate cluster. Update the service role policy to allow access to the X-Ray API.

C. Instrument the application by using the AWS X-Ray SDK. Update the application to use the PutXrayTrace API call to communicate with the X-Ray API.

D. Instrument the application by using the AWS X-Ray SDK. Update the application to communicate with the X-Ray daemon.

E. Instrument the ECS task to send the stdout and stderr output to Amazon CloudWatch Logs. Update the task role policy to allow the cloudwatch:PullLogs action.

Show Suggested Answer

---

by AWSdeveloper08 at *Aug. 10, 2023, 2:07 p.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

MG1407 Highly Voted 2 years, 7 months ago

AD
A. You can only use X-ray with Fargate as a side car because there is not EC2 image.
D. https://github.com/aws-samples/aws-xray-fargate

upvoted 14 times

lamtany 2 years, 6 months ago

With AWS Fargate, there are no EC2 instances to install the X-Ray daemon onto.

However, the X-Ray daemon is actually provided automatically with Fargate - it runs as an additional container alongside the application containers in the task. So there is no need to deploy it as a sidecar.

When using X-Ray with Fargate, you just need to:

Instrument the application code with the X-Ray SDK
The SDK will communicate with the daemon container provided by Fargate
So you're right that there are no EC2 hosts to install daemons on directly. But Fargate handles running the X-Ray daemon automatically as part of the task, eliminating the need for a sidecar. The SDK can communicate with the daemon container transparently.

upvoted 2 times

Nagasoracle 2 years, 5 months ago

I agree - AD
https://github.com/aws-samples/aws-xray-fargate

upvoted 1 times

e886835 Most Recent 1 year, 1 month ago

Selected Answer: D

AD- The X-Ray SDK is used to enable the application code to send trace data. By integrating the SDK, the application will automatically collect traces of the requests and responses, helping you understand where errors occur within the microservices.

upvoted 1 times

vkovilam 1 year, 9 months ago

A. Deploy AWS X-Ray as a sidecar container to the microservices. Update the task role policy to allow access to the X-Ray API.

D. Instrument the application by using the AWS X-Ray SDK. Update the application to communicate with the X-Ray daemon.

upvoted 1 times

65703c1 1 year, 10 months ago

Selected Answer: A

AD is the correct answer.

upvoted 1 times

Single 2 years ago

Selected Answer: AE

ChatGPT：AE

upvoted 1 times

41eb566 2 years ago

Selected Answer: C

CE
C. Instrument the application by using the AWS X-Ray SDK. Update the application to use the PutXrayTrace API call to communicate with the X-Ray API.

This step involves instrumenting the application code using the AWS X-Ray SDK to generate trace data and communicate it to the X-Ray service for analysis.
E. Instrument the ECS task to send the stdout and stderr output to Amazon CloudWatch Logs. Update the task role policy to allow the cloudwatch:PullLogs action.

upvoted 1 times

rrshah83 2 years, 3 months ago

Selected Answer: A

AC

Fargate cannot have daemon. This rules out B and C. D is distractor.

upvoted 1 times

tqiu654 2 years, 4 months ago

Selected Answer: A

CHatGpt: AD

upvoted 1 times

ShawnWon 2 years, 4 months ago

DE
Option A is incorrect because deploying AWS X-Ray as a sidecar container to the microservices is not the common practice for Fargate deployments. Fargate tasks usually run as a single container, and the application is instrumented to communicate with the X-Ray daemon.

Option B is not applicable because deploying AWS X-Ray as a daemonset is a concept related to Kubernetes, not AWS Fargate.

Option C is incorrect because using the AWS X-Ray SDK involves instrumenting the application, but the suggested approach is to communicate with the X-Ray daemon rather than directly calling the X-Ray API.

upvoted 3 times

Passexam4sure_com 2 years, 5 months ago

Selected Answer: D

Instrument the application by using the AWS X-Ray SDK. Update the application to communicate with the X-Ray daemon

upvoted 1 times

Claire_KMT 2 years, 5 months ago

D. Instrument the application by using the AWS X-Ray SDK. Update the application to communicate with the X-Ray daemon.

E. Instrument the ECS task to send the stdout and stderr output to Amazon CloudWatch Logs. Update the task role policy to allow the cloudwatch:PullLogs action.

upvoted 1 times

fossil123 2 years, 7 months ago

Selected Answer: A

AD is correct.
A - X-Ray container as a "Side car" in ECS/Fargate cluster
D - Instrument the application using the AWS X-Ray SDK to collect telemetry data.

upvoted 3 times

love777 2 years, 7 months ago

Selected Answer: D

D and E
Option D:

Instrumenting the application using the AWS X-Ray SDK is essential for collecting traces and telemetry data. The X-Ray SDK helps you identify bottlenecks, errors, and other issues within your microservices.

Communicating with the X-Ray daemon allows your microservices to send trace data to X-Ray for analysis and visualization. This requires minimal configuration and is efficient for capturing and analyzing traces.

Option E:

Instrumenting the ECS task to send the application's standard output (stdout) and standard error (stderr) logs to Amazon CloudWatch Logs provides visibility into the application's behavior, errors, and issues.

Updating the task role policy to allow the cloudwatch:PullLogs action ensures that the ECS task has the necessary permissions to access and send logs to CloudWatch Logs.

upvoted 3 times

AWSdeveloper08 2 years, 7 months ago

Selected Answer: C

Answer is CE

To diagnose and fix errors in an application deployed on Amazon ECS with AWS Fargate using AWS X-Ray, you should take the following steps:

C. Instrument the application by using the AWS X-Ray SDK. Update the application to use the PutXrayTrace API call to communicate with the X-Ray API.

Instrumenting the application using the AWS X-Ray SDK allows you to capture traces and data about requests as they flow through your application's components.
E. Instrument the ECS task to send the stdout and stderr output to

Amazon CloudWatch Logs. Update the task role policy to allow the cloudwatch:PullLogs action.

This step will help you capture logs from your microservices, which can provide additional insights into the errors and issues occurring within the application.

upvoted 1 times