Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 149
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

An organization is using Amazon CloudFront to ensure that its users experience low-latency access to its web application. The organization has identified a need to encrypt all traffic between users and CloudFront, and all traffic between CloudFront and the web application.

How can these requirements be met? (Choose two.)

A. Use AWS KMS to encrypt traffic between CloudFront and the web application.

B. Set the Origin Protocol Policy to “HTTPS Only”.

C. Set the Origin’s HTTP Port to 443.

D. Set the Viewer Protocol Policy to “HTTPS Only” or “Redirect HTTP to HTTPS”.

E. Enable the CloudFront option Restrict Viewer Access.

Show Suggested Answer

---

by fordiscussionstwo at *Oct. 6, 2023, 1:42 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

SerialiDr Highly Voted 1 year, 8 months ago

Selected Answer: BD

B. Set the Origin Protocol Policy to “HTTPS Only”: This setting ensures that all traffic between CloudFront and the web application (origin) is encrypted. By setting the Origin Protocol Policy to "HTTPS Only," CloudFront will only connect to the origin over HTTPS, ensuring encryption of data in transit.
D. Set the Viewer Protocol Policy to “HTTPS Only” or “Redirect HTTP to HTTPS”: This setting is crucial for ensuring that all traffic between the users (viewers) and CloudFront is encrypted. By setting the Viewer Protocol Policy to "HTTPS Only" or "Redirect HTTP to HTTPS," CloudFront ensures that user requests are either only served over HTTPS or automatically redirected from HTTP to HTTPS.

upvoted 5 times

65703c1 Most Recent 1 year, 4 months ago

Selected Answer: BD

BD is the correct answer.

upvoted 1 times

Jeff1719 1 year, 10 months ago

Selected Answer: BD

BD: Protocol and Viewer protocol policy, see https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/distribution-web-values-specify.html

upvoted 2 times

dilleman 1 year, 11 months ago

Selected Answer: BD

B and D are the correct ones.
B: Setting the Origin Protocol Policy to “HTTPS Only” ensures that CloudFront always uses HTTPS to connect to the origin, which is the web application in this scenario.
D: Setting the Viewer Protocol Policy to “HTTPS Only” ensures that CloudFront will only serve requests over HTTPS. Setting it to “Redirect HTTP to HTTPS” ensures that any HTTP request from viewers is redirected to HTTPS.

upvoted 4 times

Digo30sp 1 year, 12 months ago

Selected Answer: BD

The correct answers are (B) and (D).

To meet the requirement to encrypt all traffic between users and CloudFront, your organization must set the Viewer Protocol Policy to “HTTPS Only” or “Redirect HTTP to HTTPS”. This will force users to use HTTPS to connect to CloudFront.

To meet the requirement to encrypt all traffic between CloudFront and the web application, your organization must set the Origin Protocol Policy to “HTTPS Only”. This will force CloudFront to use HTTPS to connect to the web application.

upvoted 3 times