Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 154
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer maintains applications that store several secrets in AWS Secrets Manager. The applications use secrets that have changed over time. The developer needs to identify required secrets that are still in use. The developer does not want to cause any application downtime.

What should the developer do to meet these requirements?

A. Configure an AWS CloudTrail log file delivery to an Amazon S3 bucket. Create an Amazon CloudWatch alarm for the GetSecretValue Secrets Manager API operation requests.

B. Create a secretsmanager-secret-unused AWS Config managed rule. Create an Amazon EventBridge rule to initiate notifications when the AWS Config managed rule is met.

C. Deactivate the applications secrets and monitor the applications error logs temporarily.

D. Configure AWS X-Ray for the applications. Create a sampling rule to match the GetSecretValue Secrets Manager API operation requests.

Show Suggested Answer

---

by fordiscussionstwo at *Oct. 6, 2023, 1:56 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.

- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

chris_777 Highly Voted 2 years, 5 months ago

Selected Answer: B

I think B is correct
https://docs.aws.amazon.com/config/latest/developerguide/secretsmanager-secret-unused.html

A. could work but requires additional work to identify unused secrets.
C. is too risky and could cause downtime.
D. not the right use case

upvoted 7 times

9d8dd9c Most Recent 1 year, 5 months ago

With option A, if you want to know what secrets are not used anymore for the past 90 days, then you need to wait 90 days, get a list of the ones that are used then minus this from the total list... but option B returns the unused list for the last 90 days directly

upvoted 1 times

MasoudK 1 year, 6 months ago

source copilot: Why Option A is Better:
1. Real-Time Monitoring: By using CloudTrail and CloudWatch, you can monitor GetSecretValue API calls in real-time, providing immediate insights into which secrets are being accessed.
2. Detailed Logging: CloudTrail logs provide detailed information about each API call, including the source IP, user, and timestamp, which can help identify the specific applications or instances accessing the secrets.
3. Customizable Alerts: CloudWatch alarms can be configured to trigger notifications based on specific patterns or thresholds, offering more flexibility and control over monitoring.

upvoted 1 times

MasoudK 1 year, 6 months ago

Why Option B Might Not Be the Best Choice:
1. Rule Limitation: The secretsmanager-secret-unused AWS Config managed rule checks if a secret has not been retrieved for a specified period. However, it might not provide real-time insights into which secrets are currently in use.
2. Delayed Detection: This rule might only detect secrets that have not been used for a while, potentially missing secrets that are infrequently accessed but still required.
3. Lack of Granularity: The rule might not provide detailed information about the specific applications or instances accessing the secrets, making it harder to pinpoint which secrets are actively used.

upvoted 1 times

65703c1 1 year, 10 months ago

Selected Answer: B

B is the correct answer.

upvoted 1 times

KarBiswa 2 years, 1 month ago

Selected Answer: B

We need "secrets that are still in use". "B" secretsmanager-secret-unused returns unused. So we can easily determine the used secrets if it is not falling under this scanner

upvoted 2 times

rimaSamir 2 years, 2 months ago

My choice is "A".
We need "secrets that are still in use". "B" secretsmanager-secret-unused returns unused.

upvoted 1 times

SerialiDr 2 years, 2 months ago

Selected Answer: A

A. Use an AWS Step Functions state machine to monitor API failures. Use the Wait state to delay calling the Lambda function: This is a viable and efficient solution. AWS Step Functions can orchestrate the Lambda function invocations and manage the workflow, including handling API call rate limits. The Wait state can be used to introduce delays between API calls to ensure compliance with the rate limits. This approach also allows for handling errors and retries effectively.

B. Use an Amazon Simple Queue Service (Amazon SQS) queue to hold the API calls. Configure the Lambda function to poll the queue within the API threshold limits: While using SQS to queue API call requests is a good way to manage workload, it adds complexity to the solution. The Lambda function would need to be modified to manage the queue and ensure API calls are made within the threshold limits. This approach might not be as straightforward and efficient as using Step Functions.

upvoted 2 times

tqiu654 2 years, 4 months ago

Selected Answer: A

ChatGPT:A

upvoted 1 times

kaes 2 years, 4 months ago

It's easier to use a built-in solution in AWS Config (check chris_777 answer)

upvoted 1 times

kaes 2 years, 4 months ago

Selected Answer: B

It's easier to use a default built-in solution in AWS Config (check chris_777 answer)

upvoted 1 times

CrescentShared 2 years, 4 months ago

Selected Answer: A

I think A is a more direct way, while B needs an inference after receiving the notification for 'unused'.

upvoted 1 times

LemonGremlin 2 years, 5 months ago

Selected Answer: B

B is correct for this one.

upvoted 1 times

dilleman 2 years, 5 months ago

Selected Answer: A

A is correct. . AWS CloudTrail can track API calls, including the GetSecretValue call for AWS Secrets Manager. By setting up CloudTrail log delivery to an S3 bucket, the developer can analyze which secrets are being accessed. Using CloudWatch to create an alarm for the GetSecretValue API call provides insight into which secrets are actively being retrieved, thus indicating which secrets are in use.

upvoted 2 times

dilleman 2 years, 5 months ago

I think i change my mind to B. B Must be correct..

upvoted 3 times

CrescentShared 2 years, 4 months ago

Why did you change your mind, please? A looks super correct to me.

upvoted 1 times

Digo30sp 2 years, 5 months ago

Selected Answer: B

The correct answer is (B).

Solution (B) is the best option to meet the developer's requirements. It allows the developer to identify necessary secrets that are still in use without causing any application downtime.

upvoted 3 times