Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02

Question #: 158

Topic #: 1

[All AWS Certified Developer - Associate DVA-C02 Questions]

An ecommerce application is running behind an Application Load Balancer. A developer observes some unexpected load on the application during non-peak hours. The developer wants to analyze patterns for the client IP addresses that use the application.

Which HTTP header should the developer use for this analysis?

A. The X-Forwarded-Proto header

B. The X-Forwarded-Host header

C. The X-Forwarded-For header

D. The X-Forwarded-Port header

Show Suggested Answer

---

by fordiscussionstwo at *Oct. 6, 2023, 2:02 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

chris_777 Highly Voted 1 year, 11 months ago

Selected Answer: C

C is correct.

X-Forwarded-Proto: protocol (HTTP/HTTPS)
X-Forwarded-Host: original Host header requested by the client
X-Forwarded-For: original IP address of a client (CORRECT)
X-Forwarded-Port header: original port that the client used to connect

upvoted 9 times

65703c1 Most Recent 1 year, 4 months ago

Selected Answer: C

C is the correct answer.

upvoted 1 times

tapan666 1 year, 11 months ago

Selected Answer: C

C is correct

upvoted 1 times

dilleman 1 year, 11 months ago

Selected Answer: C

C is correct

upvoted 1 times

Cerakoted 1 year, 11 months ago

Selected Answer: C

X-Forwarded-For HTTP header contains the IP address of the original client

upvoted 1 times

Digo30sp 1 year, 12 months ago

Selected Answer: C

The correct answer is (C).

The X-Forwarded-For HTTP header contains the IP address of the original client that made the request. The developer can use this header to analyze patterns for the IP addresses of clients using the application.

upvoted 2 times