Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 239
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer created a web API that receives requests by using an internet-facing Application Load Balancer (ALB) with an HTTPS listener. The developer configures an Amazon Cognito user pool and wants to ensure that every request to the API is authenticated through Amazon Cognito.

What should the developer do to meet this requirement?

A. Add a listener rule to the listener to return a fixed response if the Authorization header is missing. Set the fixed response to 401 Unauthorized.

B. Create an authentication action for the listener rules of the ALSet the rule action type to authenticate-cognito. Set the OnUnauthenticatedRequest field to “deny.”

C. Create an Amazon API Gateway API. Configure all API methods to be forwarded to the ALB endpoint. Create an authorizer of the COGNITO_USER_POOLS type. Configure every API method to use that authorizer.

D. Create a new target group that includes an AWS Lambda function target that validates the Authorization header by using Amazon Cognito. Associate the target group with the listener.

Show Suggested Answer

---

by Claire_KMT at *Oct. 28, 2023, 2:40 p.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

SerialiDr Highly Voted 2 years, 2 months ago

Selected Answer: B

This approach uses the built-in capabilities of the ALB to authenticate requests with Amazon Cognito. By configuring a rule action to authenticate with a Cognito user pool, the ALB can handle authentication before the request is forwarded to the target group. The OnUnauthenticatedRequest setting of "deny" ensures that unauthenticated requests are not allowed access, which aligns with the requirement to authenticate every request.

upvoted 10 times

dostonbekabdullaev Highly Voted 2 years, 2 months ago

Selected Answer: B

https://docs.aws.amazon.com/elasticloadbalancing/latest/application/listener-authenticate-users.html#configure-user-authentication

upvoted 6 times

preachr Most Recent 1 year, 6 months ago

Selected Answer: B

OnUnauthenticatedRequest
The behavior if the user is not authenticated. The following are possible values:

deny - Return an HTTP 401 Unauthorized error.

allow - Allow the request to be forwarded to the target.

authenticate - Redirect the request to the IdP authorization endpoint. This is the default value.

upvoted 1 times

Anandesh 1 year, 8 months ago

Selected Answer: B

https://docs.aws.amazon.com/elasticloadbalancing/latest/application/listener-authenticate-users.html
https://docs.aws.amazon.com/elasticloadbalancing/latest/APIReference/API_AuthenticateCognitoActionConfig.html

upvoted 1 times

tsangckl 1 year, 9 months ago

This appear at 17 Jun exam

upvoted 1 times

65703c1 1 year, 10 months ago

Selected Answer: B

B is the correct answer.

upvoted 1 times

JohnPl 2 years, 2 months ago

Selected Answer: C

https://docs.aws.amazon.com/apigateway/latest/developerguide/apigateway-enable-cognito-user-pool.html

upvoted 1 times

rrshah83 2 years, 3 months ago

Selected Answer: B

https://docs.aws.amazon.com/elasticloadbalancing/latest/application/listener-authenticate-users.html#configure-user-authentication

upvoted 3 times

c9ebec2 2 years, 3 months ago

Selected Answer: C

https://docs.aws.amazon.com/apigateway/latest/developerguide/apigateway-integrate-with-cognito.html

upvoted 2 times

TanTran04 2 years, 3 months ago

Selected Answer: B

https://www.examtopics.com/discussions/amazon/view/88889-exam-aws-certified-developer-associate-topic-1-question-332/

upvoted 3 times

Certified101 2 years, 3 months ago

Selected Answer: C

I think its C - API G would work better ?

upvoted 1 times

Claire_KMT 2 years, 5 months ago

B. Create an authentication action for the listener rules of the ALSet the rule action type to authenticate-cognito. Set the OnUnauthenticatedRequest field to “deny.”

upvoted 2 times