Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 287
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer is creating a serverless application that uses an AWS Lambda function. The developer will use AWS CloudFormation to deploy the application. The application will write logs to Amazon CloudWatch Logs. The developer has created a log group in a CloudFormation template for the application to use. The developer needs to modify the CloudFormation template to make the name of the log group available to the application at runtime.

Which solution will meet this requirement?

A. Use the AWS::Include transform in CloudFormation to provide the log group's name to the application.

B. Pass the log group's name to the application in the user data section of the CloudFormation template.

C. Use the CloudFormation template's Mappings section to specify the log group's name for the application.

D. Pass the log group's Amazon Resource Name (ARN) as an environment variable to the Lambda function.

Show Suggested Answer

by CrescentShared at *Feb. 21, 2024, 6:58 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

albert_kuo 1 year, 6 months ago

Selected Answer: D

Resources:
MyLogGroup:
Type: AWS::Logs::LogGroup
Properties:
LogGroupName: !Sub "/aws/lambda/${AWS::StackName}-log-group"

MyLambdaFunction:
Type: AWS::Lambda::Function
Properties:
FunctionName: MyFunction
Handler: index.handler
Runtime: nodejs14.x
Role: arn:aws:iam::123456789012:role/service-role/MyLambdaRole
Environment:
Variables:
LOG_GROUP_ARN: !GetAtt MyLogGroup.Arn

upvoted 1 times

65703c1 1 year, 10 months ago

Selected Answer: D

D is the correct answer.

upvoted 2 times

Abdullah22 2 years ago

Selected Answer: D

Explanation of why other options are less suitable:

A. AWS::Include transform: While the AWS::Include transform allows importing values from other templates, it's generally used for larger configurations and not ideal for this specific purpose of passing a single value to the application.
B. User data: The user data section in CloudFormation is typically used for one-time configuration scripts and not intended for passing sensitive information like log group names or ARNs, raising security concerns.
C. CloudFormation Mappings: While mappings can store key-value pairs within the template, they are not directly accessible as environment variables within the application code.

upvoted 4 times

SerialiDr 2 years ago

Selected Answer: D

By specifying the log group's ARN as an environment variable in the CloudFormation template for the Lambda function, the developer can easily access this information within the application code at runtime. This method provides a straightforward way to pass dynamic

configuration or resource references to AWS Lambda functions without hardcoding values, thereby maintaining flexibility and ensuring that the application can utilize the correct resources after deployment.

upvoted 2 times

KarBiswa 2 years, 1 month ago

Selected Answer: D

Very nice question totally confusing. D is correct

upvoted 1 times

CrescentShared 2 years, 1 month ago

Selected Answer: D

User data is typically used to pass startup scripts to EC2 instances, not Lambda functions. This would not be the appropriate mechanism for a serverless application using Lambda. The Mappings section in a CloudFormation template is used to define sets of key-value pairs that can be used to specify conditional parameter values based on region or other criteria. It doesn't provide a direct way to make the log group's name available to the Lambda function at runtime.

upvoted 4 times