Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 344
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer is creating a new application for a pet store. The application will manage customer rewards points. The developer will use Amazon DynamoDB to store the data for the application. The developer needs to optimize query performance and limit partition overload before actual performance analysis.

Which option should the developer use for a partition key to meet these requirements?

A. A randomly generated universally unique identifier (UUID)

B. The customer's full name

C. The date when the customer signed up for the rewards program

D. The name of the customer's pet

Show Suggested Answer

---

by KarBiswa at *March 23, 2024, 4:26 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

65703c1 1 year, 10 months ago

Selected Answer: A

A is the correct answer.

upvoted 2 times

trungtd 2 years ago

Selected Answer: A

Think of it as CustomerID

upvoted 3 times

DeaconStJohn 2 years ago

Selected Answer: A

This is the only feasible option for a partition key..

B - Two John Smith's sign up for the programme
C - Both John Smith's signed up on the same day
D - Both John Smith's signed up on the same day with a poodle called Betsy May.

Cant rule it out.

upvoted 2 times

KarBiswa 2 years ago

Selected Answer: C

The start date for the rewards program

upvoted 1 times

tirthyakamaldasgupta 1 year, 7 months ago

Based on my understanding, using the start date as a Partition Key could result in partition overload if a large number of sign-ups occur on the same date. In contrast, choosing a randomly generated UUID as a Partition Key would prevent this issue, as each ID is unique, ensuring even distribution and eliminating the risk of creating a hot partition. Please correct me if my understanding is incorrect, as I am still learning.

upvoted 1 times