Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 353
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer at a company writes an AWS CloudFormation template. The template refers to subnets that were created by a separate AWS CloudFormation template that the company's network team wrote. When the developer attempts to launch the stack for the first time, the launch fails.

Which template coding mistakes could have caused this failure? (Choose two.)

A. The developer's template does not use the Ref intrinsic function to refer to the subnets.

B. The developer's template does not use the ImportValue intrinsic function to refer to the subnets.

C. The Mappings section of the developer's template does not refer to the subnets.

D. The network team's template does not export the subnets in the Outputs section.

E. The network team's template does not export the subnets in the Mappings section.

Show Suggested Answer

---

by mehanizator at *May 5, 2024, 8:01 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

preachr 1 year, 6 months ago

Selected Answer: BD

The intrinsic function Fn::ImportValue returns the value of an output exported by another stack. You typically use this function to create cross-stack references.

upvoted 2 times

KennethNg923 1 year, 7 months ago

Selected Answer: BD

B. When referencing resources from another stack, the ImportValue function should be used. If the developer didn't use this, it would cause a failure when trying to reference the subnets.
D. For a resource to be imported by another stack, it needs to be exported in the Outputs section of the original stack. If the network team didn't export the subnets, they can't be imported by the developer's stack.

upvoted 3 times

65703c1 1 year, 10 months ago

Selected Answer: BD

BD is the correct answer.

upvoted 1 times

Lucky4Life 1 year, 10 months ago

Selected Answer: BD

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference.html

upvoted 3 times

mehanizator 1 year, 11 months ago

Selected Answer: BD

ChatGPT: BD

upvoted 2 times