## Exam AWS Certified Developer - Associate DVA-C02 All Questions

**View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam**

Go to Exam


## EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 431
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

---

A developer is troubleshooting an application. The application includes several AWS Lambda functions that invoke an Amazon API Gateway API. The API Gateway's method request is set up to use an Amazon Cognito authorizer for authentication.

All the Lambda functions pass the user ID as part of the Authorization header to the API Gateway API. The API Gateway API returns a 403 status code for all GET requests.

How should the developer resolve this issue?

A. Modify the client GET request to include a valid API key in the Authorization header.

B. Modify the client GET request to include a valid token in the Authorization header.

C. Update the resource policy for the API Gateway API to allow the execute-api:Invoke action.

D. Modify the client to send an OPTIONS preflight request before the GET request.

Show Suggested Answer

---

by stevesuperdx at *Sept. 26, 2024, 5:18 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.

- Trademarks, certification & product names are used for reference only and belong to Amazon.

## Comments

**Saudis** 1 year, 4 months ago

**Selected Answer: B**

the answer is B

upvoted 1 times

**albert_kuo** 1 year, 5 months ago

**Selected Answer: B**

```
const apiUrl = 'https://api.example.com/my-resource';

const headers = {
'Authorization': `Bearer ${idToken}`, // JWT token
'Content-Type': 'application/json'
};

fetch(apiUrl, { method: 'GET', headers: headers })
.then(response => {
if (!response.ok) {
throw new Error('API request failed');
}
return response.json();
})
.then(data => console.log(data))
.catch(error => console.log('Error:', error));
```

upvoted 1 times

**YUICH** 1 year, 5 months ago

**Selected Answer: B**

the answer is B

upvoted 1 times

**stevesuperdx** 1 year, 6 months ago

Option B is the correct solution, as the client must provide a valid token in the Authorization header for Cognito authorizer to work properly.

upvoted 1 times