Exam AWS Certified Developer - Associate DVA-C02 All Questions

View all questions & answers for the AWS Certified Developer - Associate DVA-C02 exam

Go to Exam

EXAM AWS CERTIFIED DEVELOPER - ASSOCIATE DVA-C02 TOPIC 1 QUESTIO...

Exam question from Amazon's AWS Certified Developer - Associate DVA-C02
Question #: 504
Topic #: 1
[All AWS Certified Developer - Associate DVA-C02 Questions]

A developer is working on a new authorization mechanism for an application. The developer must create an Amazon API Gateway API and must test JSON Web Token (JWT) authorization on the API.

The developer must use the built-in authorizer and must avoid managing the code with custom logic. The developer needs to define an API route that is available at /auth to test the authorizer configuration.

Which solution will meet these requirements?

A. Create a WebSocket API and the /auth route. Configure and attach the JWT authorizer to the API. Deploy the API.

B. Create a WebSocket API and the /auth route. Create and configure an AWS Lambda authorizer. Attach the Lambda authorizer to the API. Deploy the API.

C. Create an HTTP API and the /auth route. Create and configure an AWS Lambda authorizer. Attach the Lambda authorizer to the /auth route. Deploy the API.

D. Create an HTTP API and the /auth route. Configure the JWT authorizer. Attach the JWT authorizer to the /auth route. Deploy the API.

Show Suggested Answer

by Dahlia9524 at *Dec. 10, 2024, 4:35 a.m.*

Disclaimers:
- ExamTopics website is **not** related to, affiliated with, endorsed or authorized by Amazon.
- Trademarks, certification & product names are used for reference only and belong to Amazon.

Comments

e886835 1 year, 1 month ago

Selected Answer: D

To test JWT authorization using the built-in capabilities of Amazon API Gateway, you should create an HTTP API, configure the JWT authorizer, and attach it to the /auth route.

upvoted 1 times

xdeveloper 1 year, 3 months ago

Selected Answer: D

WebSocket APIs in API Gateway do not support the built-in JWT authorizer. This option is invalid.
Lambda authorizers require custom code, which contradicts the requirement to avoid managing custom logic.

upvoted 1 times

ShakthiGCP 1 year, 3 months ago

Selected Answer: D

It narrow downs to C and D . But for C , we need to create a Lambda function , whereas for D - JWT authorizer, it uses the token.

upvoted 1 times

Dahlia9524 1 year, 3 months ago

Selected Answer: D

not needs interactive chat like communication to verify the token. So no web-socket?

upvoted 3 times