

Minimum Edit Distance

Backtrace for Computing Alignments



Computing alignments

- Edit distance isn't sufficient
 - We often need to **align** each character of the two strings to each other
- We do this by keeping a “backtrace”
- Every time we enter a cell, remember where we came from
- When we reach the end,
 - Trace back the path from the upper right corner to read off the alignment



Edit Distance

$$D(i,j) = \min \begin{cases} D(i-1,j) + 1 \\ D(i,j-1) + 1 \\ D(i-1,j-1) + \begin{cases} 2; & \text{if } S_1(i) \neq S_2(j) \\ 0; & \text{if } S_1(i) = S_2(j) \end{cases} \end{cases}$$

N	9									
O	8									
I	7									
T	6									
N	5									
E	4									
T	3									
N	2									
I	1									
#	0	1	2	3	4	5	6	7	8	9
	#	E	X	E	C	U	T	I	O	N



MinEdit with Backtrace

n	9	↓ 8	↙←↓ 9	↙←↓ 10	↙←↓ 11	↙←↓ 12	↓ 11	↓ 10	↓ 9	↙ 8	
o	8	↓ 7	↙←↓ 8	↙←↓ 9	↙←↓ 10	↙←↓ 11	↓ 10	↓ 9	↙ 8	← 9	
i	7	↓ 6	↙←↓ 7	↙←↓ 8	↙←↓ 9	↙←↓ 10	↓ 9	↙ 8	← 9	← 10	
t	6	↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↙←↓ 9	↙ 8	← 9	← 10	←↓ 11	
n	5	↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↙←↓ 9	↙←↓ 10	↙←↓ 11	↙↓ 10	
e	4	↙ 3	← 4	↙← 5	← 6	← 7	←↓ 8	↙←↓ 9	↙←↓ 10	↓ 9	
t	3	↙←↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↙ 7	←↓ 8	↙←↓ 9	↓ 8	
n	2	↙←↓ 3	↙←↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙←↓ 8	↓ 7	↙←↓ 8	↙ 7	
i	1	↙←↓ 2	↙←↓ 3	↙←↓ 4	↙←↓ 5	↙←↓ 6	↙←↓ 7	↙ 6	← 7	← 8	
#	0	1	2	3	4	5	6	7	8	9	
	#	e	x	e	c	u	t	i	o	n	



Adding Backtrace to Minimum Edit Distance

- Base conditions:

$$D(i, 0) = i$$

$$D(0, j) = j$$

Termination:

$D(N, M)$ is distance

- Recurrence Relation:

For each $i = 1 \dots M$


For each $j = 1 \dots N$

$$D(i, j) = \min \begin{cases} D(i-1, j) + 1 & \text{deletion} \\ D(i, j-1) + 1 & \text{insertion} \\ D(i-1, j-1) + \begin{cases} 2; & \text{if } X(i) \neq Y(j) \\ 0; & \text{if } X(i) = Y(j) \end{cases} & \text{substitution} \end{cases}$$

$$\text{ptr}(i, j) = \begin{cases} \text{LEFT} & \text{insertion} \\ \text{DOWN} & \text{deletion} \\ \text{DIAG} & \text{substitution} \end{cases}$$



The Distance Matrix



Every non-decreasing path

from $(0,0)$ to (M, N)

corresponds to
an alignment
of the two sequences

An optimal alignment is composed
of optimal subalignments



Result of Backtrace

- Two strings and their **alignment**:

I	N	T	E	*	N	T	I	O	N
*	E	X	E	C	U	T	I	O	N



Performance

- Time:

$O(nm)$

- Space:

$O(nm)$

- Backtrace

$O(n+m)$

Minimum Edit Distance

Backtrace for Computing Alignments