

Evolution of Hard Negative Mining

Year:	1994	2001	2005	2008	2014	2015	2016	2017	2018	2019	2020	2021
Method	Bootstrap				Without Hard Negative Mining			Bootstrap + New Loss Functions				
Remarks	Bootstrap was widely used to deal with the insufficient computing resources of early time				By simply balancing the weights between object and background classes			Focusing on hard examples Computing power is no longer a problem				

@Face Det. (H. A. Rowley et al-CMUTechRep1995), @Haar Det. (C. P. Papageorgiou et al-ICCV1998), @VJ Det. (P. Viola et al-CVPR2001), @HOG Det. (N. Dalal et al-CVPR2005), @DPM (P. Felzenszwalb et al-CVPR2008, TPAMI2010) ...

@RCNN (R. Girshick et al-CVPR2014), @SPPNet (K. He et al-ECCV2014), @Fast RCNN (R. Girshick-ICCV2015), @Faster RCNN (S. Ren et al-NIPS2015), @YOLO (J. Redmon et al-CVPR2016) ...

@SSD (W. Liu et al-ECCV2016), @FasterPed (L. Zhang et al-ECCV2016), @OHEM (A. Shrivastava et al-CVPR2016), @RetinaNet (T. Y. Lin et al-ICCV2017), @RefineDet (Zhang et al-CVPR18), @FCOS (Z. Tian et al-ICCV2019), @YOLOv4 (A. Bochkovskiy et al-arXiv2020) ...