

Section 1 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock

[See section 3 - peripheral register](#)

Section 2 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock

Section 3 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock

[See section 5 - peripheral register](#)

Section 4 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock

Section 5 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock

[See section 7 - peripheral register](#)

Section 6 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock

Section 7 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock

Section 8 - GPIO and interrupt control

The interrupt flag is set when a rising edge is detected.

Write one to clear the pending interrupt flag.

GPIOA and TIMx_CR1 are memory-mapped registers.

The peripheral clock is divided by the prescaler.

Register address: 0x40020000. Read the status register.

Use volatile for hardware registers accessed by C code.

A pull-up resistor holds the input pin at a high level.

DMA transfers data without repeated CPU intervention.

interrupt register clock