



25 YEARS ANNIVERSARY
SOICT

HA NOI UNIVERSITY OF SCIENCE AND TECHNOLOGY
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

CÁC HỆ THỐNG PHÂN TÁN VÀ ỨNG DỤNG




HA NOI UNIVERSITY OF SCIENCE AND TECHNOLOGY
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

Chapter 5: Consistency and Replication


Problems

3




Content Delivery Network

4



AKAMAI



Outline

6

1. Introduction
2. Data-centric consistency models
3. Client-centric consistency models
4. Replica management
5. Consistency protocols



HA NOI UNIVERSITY OF SCIENCE AND TECHNOLOGY
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

1. Introduction

1.1. Why do we need replication

8

- Reliability
- Performance
- Scalability (?)

 Consistency

1.2. Consistency


9

- Consistency of replicated data
 - ▣ Impossible to propagate the updates immediately
 - ▣ When? How?
- Strong consistency and Weak consistency
- Trade-off between consistency and performance

2. Data-centric consistency models

2.1. Distributed data store


11



Consistency model

12

- A contract between processes and the data store.
- If processes agree to obey certain rules, the store promises to work correctly.
- Range of consistency models
- Major restrictions → easy
- Minor restrictions → difficult



2.2. Continuous consistency


14

- Factors for defining inconsistencies:
 - ▣ Deviation in numerical values
 - ▣ Deviation in staleness (the last time a replica was updated)
 - ▣ Deviation of ordering of update operations
- When the deviation exceeds a given value, Middleware will perform replication operations to bring the deviation back to the limit.


2.3. Conit (consistency unit)

15

Replica A



Replica B




Time:?

Oder:?


Value:?

Size of conit

16




(a)



(b)

- A conit represents a lot of data → bring replica sooner in an inconsistent state
- Conit is very small → overhead related to managing the conit



2.4. Consistent Ordering of Operations

18


- ❑ Concurrent programming
- ❑ Parallel and distributed computing
- ❑ Express the semantics of concurrent accesses when shared resources are replicated
- ❑ Deal with consistently ordering operations on shared, replicated data.

Special notation

19

- Operations on data item x
 - ▣ Reading: $(R_i(x)b)$
 - ▣ Writing: $(W_i(x)a)$
 - ▣ Initial value of data item is NIL

P1:	$W(x)a$		
<hr/>			
P2:		$R(x)NIL$	$R(x)a$



Sequential consistency

21

- Local sequence of operations
- Global sequence of operations
- A model is satisfied the sequential consistency if a global sequence of operations exists so that all local sequence of operations belong to that global sequence (in terms of operation order).
- Hint: All processes see the same order of *writes* operations.

Example


22

P1:	W(x)a		
P2:	W(x)b		
P3:		R(x)b	R(x)a
P4:		R(x)b	R(x)a

(a)

P1:	W(x)a		
P2:	W(x)b		
P3:		R(x)b	R(x)a
P4:		R(x)a	R(x)b

(b)



Causal consistency

24

- A distinction between events that are potentially causally related and those are not.
- *Writes that are potentially causally related must be seen by all processes in the same order. Concurrent writes may be seen in a different order on different machines.*

Causal consistency (cont.)

25

P1:	W(x)a		
P2:		R(x)a	W(x)b
P3:			R(x)b
P4:			R(x)a

(a)

P1:	W(x)a		
P2:			W(x)b
P3:			R(x)b
P4:			R(x)a

(b)

Grouping operations

26

- Sequential and causal consistency are defined at the level of read and write operations → appropriate for the hardware level (shared memory multiprocessor systems) → did not match the granularity as provided by applications.
- At application level: *read* and *write* operations are bracketed by the pair: ENTER_CS and LEAVE_CS

3 conditions

27

- A process does an acquire only after all the guarded shared data have been brought up to date.
- Before updating a shared data item, a process must enter a critical section.
- If a process wants to enter a critical region, it must check with the owner of the synchronization variable guarding to fetch the most recent copies

Example

28

P1: Acq(Lx) W(x)a Acq(Ly) W(y)b Rel(Lx) Rel(Ly)

P2: Acq(Lx) R(x) ■ R(y) ■

P3: Acq(Ly) R(y) ■

3. Client-centric consistency

- 3.1. Eventual consistency
- 3.2. Monotonic reads
- 3.3. Monotonic writes
- 3.4. Read your writes
- 3.5. Writes follow reads


3.1. Eventual Consistency

30

- Consider two services: DNS, WWW
- Very little number of writes (updates), huge number of reads
- No write-write conflict, only the read-write conflicts.
- These systems tolerate a relatively high degree of inconsistency
- If no updates take place for a long time, all replicas will gradually become consistent.

Problem of Eventual Consistency

31



Client-centric consistency

32

- Provide guarantees for a single client concerning the consistency of accesses to a data store by that client.
- No guarantees for concurrent accesses by different clients.
- 4 types:
 - ▣ Monotonic reads
 - ▣ Monotonic writes
 - ▣ Read your writes
 - ▣ Writes follow reads

Notations

33

- L_i : i th local copy
- $x_i[t]$: data item x at L_i , time t
- $WS(x_i[t])$: writes operation at L_i that took place since initialization
- $WS(x_i[t_1]; x_j[t_2])$: All operations $WS(x_i[t_1])$ have been delivered to L_j , before t_2

3.2. Monotonic reads

34

L1:	$WS(x_1)$	$R(x_1)$
<hr/>		
L2:	$WS(x_1; x_2)$	$R(x_2)$

(a)

L1:	$WS(x_1)$	$R(x_1)$
<hr/>		
L2:	$WS(x_2)$	$R(x_2)$

(b)

3.3. Monotonic writes

35

L1: $W(x_1)$ -----

L2: $WS(x_1)$ ----- $W(x_2)$

(a)


L1: $W(x_1)$ -----

L2: ----- $W(x_2)$


(b)

3.4. Read your writes

36



(a)



(b)

3.5. Writes follow reads

37

L1:	WS(x_1)	R(x_1)
<hr/>		
L2:	WS(x_1)	W(x_2)


(a)

L1:	WS(x_1)	R(x_1)
<hr/>		
L2:		W(x_2)

(b)

4. Replica management


- 4.1. Replica server placement
- 4.2. Content replication and placement
- 4.3. Content distribution



4.1. Replica server placement


40

- Problem
 - ▣ N locations for replica placement
 - ▣ Determine K out of N locations
- Solution 1
 - Distance between clients and locations
 - Select one server at a time
- Solution 2: Ignoring the position of clients
 - ▣ Take the topology of the Internet
 - ▣ Sort the ASes
 - Place the server on the router with the largest number of Network interfaces
 - ▣ Continue with the sorted list



4.2. Content replication and placement

42



Permanent replicas

43


- ▣ The initial set of replicas
- ▣ The number of replica is small
- ▣ First kind of distribution
 - Data is replicated across a limited number of servers
 - For each request, it is forwarded to one of the servers (eg. using Round-robin strategy).
- ▣ 2nd kind of distribution: mirroring
 - Client simply chooses one of the various mirror sites.
- ▣ Shared-nothing architecture

Server-initiated Replicas

44

- ▣ Server is active
 - The number of requests increased suddenly
 - Activate other replicas
- ▣ Reduce load for replicas
- ▣ Update the data to a new replica closer to the client


Server-initiated Replicas



Client-initiated Replicas

46

- Caching
 - ▣ Client manages the cache management, decides to update the cache
 - ▣ Erase
 - ▣ Write
 - ▣ Policy caching
- Can share caches between clients



4.3. Content Distribution

48

- State vs. Operations
- Pull vs. Push
- Unicast vs. Multicast

State vs. Operations

49

- Solutions for updating data:
 - ▣ Propagate only a notification of an update
 - Use little network bandwidth.
 - Read-to-write ratio is small
 - ▣ Transferring the modified data
 - Read-to-write ratio is high
 - ▣ Send update operation (active replication)

Pull/Push

50

- Push: server after updating notification data for all clients
 - ▣ Replica activated by server
 - ▣ Ensure high consistency
 - ▣ Weak interaction (eg when client or replica needs to update data)
 - ▣ The server should have a list of all connected clients
- Pull: client when need data will ask server
 - ▣ Usually used for client caches
 - ▣ Suitable for high writes-reads ratio
 - ▣ Increased access time (with cache miss)
- Mixed

Uni vs. multicast

51

- Multicasting:
 - ▣ Appropriate in case 1 replica wants to promote updates to $(N-1)$ other copies in a data store
 - ▣ More efficient and economical than sending $(N-1)$ times
 - ▣ Appropriate for the push-based approach
 - ▣ Not suitable if destination nodes belong to a LAN
- Unicasting:
 - ▣ Appropriate for pull-based

5. Consistency protocols

- 5.1. Continuous consistency
- 5.2. Primary-based protocols
- 5.3. Replicated write
- 5.4. Cache coherence

5.1. Continuous consistency

53

- Bounding numerical deviation
- Bounding staleness deviation
- Bounding ordering deviation

Bounding numerical deviation

54

- Single data item x .
- Each write $W(x)$ has an associated weight that represents the numerical value by which x is updated
- The write's origin: $\text{origin}(W(x))$
- each server S_i keeps log L_i of writes that are performed on its own local copy of x .
- $TW[i,j]$ is the writes executed by S_i that originated from S_j

$$TW[i,j] = \sum \{ \text{weight}(W) \mid \text{origin}(W) = S_j \ \& \ W \in L_i \}$$

- $TW[k,k]$: aggregated writes submitted to S_k

Bounding numerical deviation

55

- Actual value of x

$$v(t) = v(0) + \sum_{k=1}^N TW[k, k]$$

$$v_i = v(0) + \sum_{k=1}^N TW[i, k]$$

$$v_i \leq v(t)$$

- The threshold:

$$v(t) - v_i \leq \delta_i$$

Bounding Staleness Deviation

56

- Can use local time of processes to evaluate
 - ▣ Server S_k has vector clock RVC_k
 - ▣ if $RVC_k[i] = T(i) \Rightarrow S_k$ has seen all operations on S_i at $T(i)$
 - ▣ $T(i)$: local time of server I
 - ▣ When $T(k) - RVC_k[i] > \delta \Rightarrow$ eliminate operations having $T > RVC_k[i]$

Bounding ordering deviation

57

- Each replica has a write queue
- Global order should be considered
- The largest number of write operations are in the queue
- When this number exceeds, the server will stop the execution and will negotiate with other servers in order


5.2. Primary-based protocols

58

- Consistency model => complex
- Developers need simpler models
- Each data item has a primary that is responsible for manipulating operations on that data items
- Fixed-primary (remote-write protocol)
- Local-primary (local write protocol)

Remote-write protocol

59




W1. Write request
W2. Forward request to primary
W3. Tell backups to update
W4. Acknowledge update
W5. Acknowledge write completed

R1. Read request
R2. Response to read

Local-write protocol

60



W1. Write request
W2. Move item x to new primary
W3. Acknowledge write completed
W4. Tell backups to update
W5. Acknowledge update

R1. Read request
R2. Response to read

5.3. Replicated-write protocols

61

1. Active replication
2. Quorum-based protocol

5.3.1. Active replication

62

- A process is responsible for propagating the update operation to all replicas
- Need a total ordered mechanism
 - ▣ logical synchronization of Lamport
 - ▣ Sequencer

5.3.2. Quorum-based protocol

63

- For strong consistency => need to update all replicas
- After updating at a costly cost => not all replicas are read => wasted
- Is there a reduction in the number of replicas that need updating?
- When reading the data
 - ▣ Risk of reading the old data
 - ▣ Read more data in some other replicas => Select the copy with the latest data
- Write Quorum & Read Quorum
 - ▣ $N_R + N_W > N$
 - ▣ $N_W > N/2$

Example of quorum

64

