



1



2



TRƯỜNG ĐẠI HỌC
BÁCH KHOA HÀ NỘI
HANOI UNIVERSITY
OF SCIENCE AND TECHNOLOGY

IT3180 – Introduction to Software Engineering

10 – Models for requirements

ONE LOVE. ONE FUTURE.

3

Models for requirements

Requirement analysis and specification includes selecting the appropriate tool for the particular task

- Models provide a bridge between the client's understanding and the developers'
- A variety of tools and techniques
- There is no correct technique that fits all situations



4

4

Models

A model is a simplification of reality

- We build models so that we can better understand the system we are developing
- We build models of complex system because we cannot comprehend such a system in its entirety



5


5

Example: Model as a Blueprint

1. Requirements

- Shall fit on given piece of land.
- Each room shall have a door.
- Furniture shall fit into living room.
- Bathroom shall have a window.
- Cost shall be in budget.

2. Design



3. System




<http://wikimedia.org>
(CC nc-sa 3.0,
Bobthebuilder82)



6

6

Example (2): Model as a Blueprint



7

7

Principles of Modeling

- The choice of what model to be created has a profound influence on how to resolve a problem
- No single model is sufficient
- Every model can be expressed at **different levels of precision**
- Good models are connected to reality
- Every nontrivial system is best approached through a small set of nearly independent models



8

8

The Unified Modeling Language

- UML is a standard language for modeling software systems
 - Serves as a bridge between the requirements and the implementation
 - Provides a means to specify and document the design of a software system
 - It is intended to be processed and programming language independent, but is particularly suited to object-oriented program development



9

9

Data Flow Models (Data Flow Diagrams – DFDs)

- Goal
 - Represent the flow of information through the system and the activities that process this information
- DFDs provide a graphical representation of the system that aims to be accessible to computer specialist and non-specialist users
- The models enable software engineers, customers and users to work together effectively during the analysis and specification of requirements



10

10

DFD notations

• Processes

- The activities carried out by the system which use and transform information
- Process is denoted as a **rounded rectangle**

• Data-flows

- The data inputs to and outputs from to these activities (**processes**)
- Data flows are notated as **named arrows**

• External entities

- The sources from which information flows into the system and the recipients of information leaving the system
- External entities are notated as **ovals**

• Data stores

- Where information is stored within the system
- Notated as rectangles



11

11

DFD symbols



External entities



Processing steps



Data stores or sources




Data flows



12

12


Example: University Admissions



13

13


Example (2): Assemble Application



14

14

Example (3): Process Completed Application



15

15

Decision Table Model

University Admission Decision

SAT > S1	T	F	F	F	F	F
GPA > G1	-	T	F	F	F	F
SAT between S1 and S2	-	-	T	T	F	F
GPA between G1 and G2	-	-	T	F	T	F
<i>Accept</i>	X	X	X			
<i>Reject</i>				X	X	X

Each column is a separate decision case. The columns are processed from left to right.

Note that the rules are specific and testable.

16

16

Flowchart Models

An informal modeling technique to show the **logic part** of a system and **paths** that data takes through a system



Operation



Decision



Manual operation




Report



17

17

Example: University Admission Assemble Application



18

18

Transition Diagrams

A system is modeled as a set of **states**, S_i


A **transition** is a change from one state to another.

The occurrence of a **condition**, C_i , causes the transition from one state to another

Transition function:

$$f(S_i, C_j) = S_k$$

Example




19

19

Example: Flight Booking System


Finite State Machine



20

20

Example (2) Finite State Machine for Flight Booking System



21

21

Entity Relation Model

A **requirement** and **design methodology** for relational databases

- A database of entities and relations
- Tools for displaying and manipulating entity-relation diagrams
- Tools for manipulating the database


Entity Relationship Models can be used both for **requirement specification** and for the **design specification**



22

22

Entity Relationship Diagram




Note: There are various notations used for entity-relationship diagrams. This is the notation used by Chen (1976).



23

23


Example: IT3180 Project



24

24

Example: Database Schema for Web Data



25

25

Prototyping Requirements

Rapid prototyping is the most comprehensive of all modeling methods

- A method for **specifying requirements** by building a system that **demonstrates** the functionality of key parts of the required system
- Particularly valuable for user interfaces

26

26

Discussion

- **Class** and **object** models are used as a tool for **program design**, not for modeling requirements
- Some documents recommend class and object models for requirements definition, but it is **difficult** to use them without **constraining the system design**
- **Flow charts, finite state machines, entity relationship diagrams** are supported by UML as design models but are equally useful for **requirement modeling**.



27

27

10. Models for Requirements

(end of lecture)

ONE LOVE. ONE FUTURE.

28

28