Architectural Blueprint for Predictive Air Quality Intelligence: Modeling Paradigms, Citizen Exposure Mitigation, and Proactive Urban Ecosystem Regulation

Spatiotemporal Deep Learning and Earth Observation Data Architecture

Modern urban airsheds exhibit non-linear, non-stationary pollutant dispersion patterns governed by complex interactions among localized anthropogenic emissions, regional atmospheric advection, and microclimatic boundary-layer dynamics. Traditional deterministic chemical transport models, such as the Weather Research and Forecasting model coupled with Chemistry (WRF-Chem) or the Community Multiscale Air Quality (CMAQ) modeling system, solve numerical representations of atmospheric thermodynamic and chemical transport equations. While chemically and physically rigorous, these deterministic frameworks suffer from prohibitive computational latency and acute sensitivity to uncertainties in static emission inventories, constraining their operational capacity for sub-kilometer, real-time public health interventions.

Recent advances in computational atmospheric science resolve these spatial and temporal non-linearities through hybrid deep learning architectures, predominantly Spatiotemporal Graph Neural Networks (STGNNs) and Spatiotemporal Graph Convolutional Networks (ST-GCNs). Standard Euclidean convolutional neural networks fail to accurately model irregularly situated urban monitoring stations. In contrast, graph formulations represent an urban sensing topology as an attributed graph \mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{W}), where \mathcal{V} denotes the set of discrete monitoring stations, \mathcal{E} represents relational edges, and \mathbf{W} signifies an adjacency matrix dynamically weighted by geographic distance, local topography, and real-time kinematic wind vectors.

Within these network topologies, spatial correlations across complex cityscapes are extracted via Chebyshev spectral graph convolutions or adaptive graph attention layers, while temporal dependencies are captured using bidirectional Gated Recurrent Units (GRUs), Temporal Convolutional Networks (TCNs), or Informer-based self-attention mechanisms. By interleaving graph spatial operations with temporal attention—exemplified by Attention Temporal Graph Convolutional Networks (A3T-GCN)—the predictive engine dynamically updates spatial edge weights in response to shifting advection vectors, enabling accurate multi-step forecasting across multi-station urban domains.

Data-driven forecasting pipelines achieve operational robustness by coupling ground-level telemetry from Continuous Ambient Air Quality Monitoring Stations (CAAQMS) with spaceborne Earth observation instruments to address spatial sparsity across monitored regions. The TROPOspheric Monitoring Instrument (TROPOMI) aboard the Copernicus Sentinel-5P satellite

provides column densities of critical trace gases including nitrogen dioxide (\text{NO}_2), sulfur dioxide (\text{SO}_2), carbon monoxide (\text{CO}), alongside total aerosol absorption metrics. Specifically, the Ultraviolet Absorbing Aerosol Index (AAI) derived from Sentinel-5P isolates light-absorbing particulates, such as mineral dust and combustion-generated black carbon, by exploiting spectral contrast across ultraviolet wavelengths:
AAI = 100 \left[
\log_{10}\left(\frac{R_{\text{meas}}(\lambda_2)}{R_{\text{meas}}(\lambda_1)}\right) -
\log_{10}\left(\frac{R_{\text{calc}}(\lambda_2,
A_{\text{LER}}(\lambda_2))}{R_{\text{calc}}(\lambda_1, A_{\text{LER}}(\lambda_1))}\right) \right]
where R_{\text{meas}} denotes top-of-atmosphere reflectance measured at wavelengths \lambda_1 = 340\text{ nm} and \lambda_2 = 380\text{ nm}, R_{\text{calc}} denotes modeled Rayleigh-scattering reflectance, and A_{\text{LER}} corresponds to the Lambert-equivalent surface reflectivity. Positive AAI values indicate elevated atmospheric concentrations of absorbing aerosols, providing a reliable observational tracer for tracking transboundary agricultural burning and industrial plumes. Integrating column-integrated satellite Aerosol Optical Depth (AOD) and AAI with planetary boundary layer height (PBLH) data from numerical weather prediction models enables neural feature-fusion layers to estimate vertical particulate stratification and project near-surface \text{PM}_{2.5} loading up to 72 hours in advance.

Forecasting Paradigm	Spatial Formulation	Temporal Dynamics	Computational Latency	Data Integration Strengths	Core Limitations
Deterministic Chemical Transport Models (e.g., WRF-Chem, CMAQ)	Continuous 3D Eulerian / Lagrangian grids	Differential kinetic and mass-flux integrations	High (hours to days across high-performance clusters)	Explicit atmospheric photochemistry and thermodynamic consistency	High sensitivity to outdated emission inventories; prohibitive execution times
Autoregressive and Classical Machine Learning (e.g., ARIMA, XGBoost)	Discrete point-source interpolation	1D time-series sliding windows	Very low (milliseconds)	Efficient ingestion of local CAAQMS time-series streams	Inability to model non-Euclidean spatial cross-correlations or regional advection
Spatiotemporal Graph Neural Networks (e.g., A3T-GCN, ST-GCN, GCN-Informer)	Non-Euclidean dynamic graph topologies	Attention-based GRUs or Informer blocks	Low (sub-second inference post-training)	Seamless fusion of ground monitors, weather vectors, and satellite AOD grids	High dependency on extensive training histories; black-box opacity without explainable AI layers

The end-to-end data pipeline integrates ground-station measurements, meteorological boundary conditions, and spaceborne observations into a unified computational pipeline. Telemetry feeds from CPCB and India-WRIS ground monitors are validated and cross-referenced with synoptic boundary layer parameters—including thermal profiles, wind velocities, and humidity

fields—drawn from global numerical models such as GFS and ECMWF. These multi-source features are fused within an adaptive graph topology alongside column-integrated Sentinel-5P TROPOMI UV absorbing aerosol indices and aerosol optical depth grids. Once ingested, the spatio-temporal graph neural network dynamically reconfigures spatial adjacency weights according to real-time wind advection, executing sub-second multi-step inference to output probabilistic, ward-level air quality forecasts across 12- to 72-hour planning horizons.

Citizen-Centric Interventions and Micro-Exposure Mitigation

Transforming air quality platforms from passive visual dashboards into proactive public health mechanisms requires converting predictive exposure fields into actionable behavioral and automated engineering controls. Standard environmental dashboards report uniform municipal figures that obscure significant micro-scale exposure variations caused by urban surface morphology, localized traffic congestion, and microclimatic boundary-layer fluctuations.

Algorithmic Clean-Air Navigation in Urban Morphologies

Built urban environments operate as complex aerodynamic street canyons, where building height-to-street width ratios (H/W) and building continuity along street fronts (Build-to-Line Ratios, or BTR) control micro-scale ventilation efficiency. In deep symmetric or asymmetric canyons with H/W \ge 1.0, ambient synoptic winds perpendicular to the street axis induce a persistent recirculating aerodynamic vortex within the canyon cavity. This vortex transports ground-level vehicular emissions toward the leeward building facade, establishing substantial concentration differentials between opposing sidewalks. Pedestrian exposure along leeward walkways under perpendicular wind vectors can be double that of windward paths, while high building frontage continuity (\text{BTR} > 0.8) suppresses lateral pollutant dispersion and increases particulate residence time by up to 18%.

To minimize cumulative individual inhalation dosage, predictive navigation architectures must move beyond conventional shortest-distance pathfinding algorithms toward multi-objective exposure minimization models. Total individual pollutant dosage (E) accumulated across an urban route is calculated using the integrated exposure formulation:

$$E = \sum_{i=1}^{N} C_i(\mathbf{x}, t) \cdot V_E(m) \cdot \delta t$$

where C_i(\mathbf{x}, t) represents the predictive micro-scale pollutant concentration at coordinates \mathbf{x} and timestamp t, V_E(m) denotes the minute ventilation volume dictated by the individual's metabolic exertion mode m (such as walking versus high-intensity cycling), and \delta t denotes the traversal residence time across street segment i. By integrating real-time Computational Fluid Dynamics lookup matrices or micro-scale operational street pollution models with topological road networks, algorithmic routing engines direct pedestrians away from stagnant leeward building margins toward well-ventilated windward sidewalks, roadside vegetative screens, or solid physical barriers, which have been shown to reduce localized particle exposure by 17% to 40%.

Dynamic Exposure Scheduling and Building Automation

Predictive atmospheric intelligence allows individuals and facility managers to schedule high-exertion activities outside of diurnal pollution peaks. In continental interior climates,

nocturnal radiational ground cooling forms strong surface-based temperature inversions that suppress vertical mixing between late evening and early morning, confining vehicle exhaust and biomass smoke within a shallow surface layer. As incoming solar insolation warms the urban surface throughout the late morning, convective turbulent mixing deepens the planetary boundary layer, diluting ground-level aerosol concentrations. By modeling boundary-layer expansion trajectories, predictive engines generate activity schedules for vulnerable demographics, including asthmatics, pediatric groups, and the elderly, identifying microclimatic exposure minima for necessary outdoor tasks.

Beyond individual behavioral modification, predictive air quality feeds interface directly with smart building management systems (BMS) through automated IoT industrial control protocols. Standard building HVAC economizers cycle outdoor air intakes based on fixed internal schedules or reactive indoor gas sensors; however, mechanical lag in air handling equipment frequently permits sudden ambient toxic plumes to penetrate indoor spaces before filtration cycles engage. A predictive platform provides automated facilities infrastructure with a 6-to-12-hour operational window, enabling pre-emptive adjustments.

Facility automation systems can pressurize internal building volumes relative to the external atmosphere 60 minutes before an anticipated ground inversion event, creating an outward pressure gradient that prevents fugitive particulate infiltration through facade gaps and entranceways. Automated damper actuators can transition mechanical air handling units from fresh-air intake to full internal recirculation mode prior to the arrival of projected surface plumes, preventing external aerosol spikes from contaminating internal duct networks. Furthermore, high-efficiency particulate air (HEPA) filtration arrays can be cycled dynamically during low-cost electrical intervals to scrub indoor air prior to external stagnation episodes, maintaining indoor air quality standards while reducing peak-hour electrical demand.

Proactive Municipal Governance and Source Apportionment: The Indo-Gangetic Case

Municipal air pollution management across the Indo-Gangetic Plain (IGP), including industrial hubs such as Kanpur, has historically relied on reactive intervention protocols. Under standard Graded Response Action Plans (GRAP), administrative measures—including bans on diesel generator sets, restrictions on heavy vehicle transit, and halting demolition activities—are enacted only after ambient monitors record severe environmental degradation over multi-day periods. This reactive implementation creates an operational lag: administrative deployment and enforcement take 12 to 24 hours, during which calm, stagnant atmospheric conditions continue to accumulate pollutants, exposing urban populations to prolonged toxic episodes.

Source Apportionment Dynamics in Urban Indo-Gangetic Basins

Receptor modeling, optical carbon speciation, and multi-site chemical mass balance analyses conducted across Kanpur demonstrate marked seasonal shifts in the contributions of various pollution sources to ambient particulate loading. Ambient fine particulate matter (\text{PM}_{2.5}) concentrations in Kanpur surge from a summer mean of 78 \pm 23\ \mu\text{g/m}^3 to an extreme winter mean of 238 \pm 96\ \mu\text{g/m}^3, with distinct source signatures characterizing each seasonal regime.

Source Sector	Kanpur Summer Contribution to Ambient \text{PM}_{2.5} (%)	Kanpur Winter Contribution to Ambient \text{PM}_{2.5} (%)	Primary Chemical Fingerprints & Precursor Dynamics	Typical Ground-Level Emission Profiles
Vehicular Exhaust & DG Sets	7.1% – 9.0%	24.5% – 29.9%	Elemental Carbon (EC), Organic Carbon (OC), high ground-level \text{NO}_x	Responsible for up to 78% of ground-level direct urban \text{NO}_x flux
Secondary Inorganic Aerosols (SIA)	9.7% – 15.0%	18.7% – 30.0%	Sulfate (\text{SO}_4^{2-}), Nitrate (\text{NO}_3^-), Ammonium (\text{NH}_4^+)	Formed via regional oxidation of gaseous precursor plumes under high RH
Secondary Organic Aerosols (SOA)	8.7% – 15.5%	16.8% – 17.9%	Complex oxygenated polycyclic aromatic compounds, oxidized NMVOCs	Driven by anthropogenic VOC condensational growth and photochemical aging
Soil, Road, & Construction Dust	21.9% – 28.0%	4.0% – 11.7%	Crustal elements (\text{Si}, \text{Al}, \text{Fe}, \text{Ca}), fugitive coarse particulate fraction	Mechanical shear suspension; silt loads frequently exceeding 2\text{ to }12\ \text{g/m}^2
Biomass & Municipal Solid Waste (MSW) Combustion	12.0% – 14.8%	2.9% – 26.0% (Biomass) + 8.0% – 8.8% (MSW)	Levoglucosan, potassium (\text{K}^+), brown carbon (BrC)	Episodic transboundary stubble burning combined with localized open trash incineration
Industrial Emissions, Coal, & Fly Ash	3.5% – 26.0%	5.2% – 16.0%	Heavy trace elements, arsenic, selenium, primary sulfate particulates	Point-source industrial stacks, fugitive furnace operations, and localized coal use

During winter periods, combustion-derived carbonaceous aerosols (\text{EC} + \text{OC}) and secondary inorganic particles account for roughly 61% of total \text{PM}_{2.5} mass in Kanpur. Ground-level internal combustion sources, including vehicle fleets and decentralized diesel generators, generate up to 29.9% of ambient particulate matter and roughly 78% of primary urban \text{NO}_x, which serves as the critical precursor driving secondary ammonium nitrate formation during cold, humid nights. In contrast, summer conditions exhibit higher fractions of mineral crustal matter derived from soil and road dust (up to 28%), alongside coal and fly ash

emissions suspended by high surface winds.

Algorithmic Transition to Predictive GRAP Interventions

A predictive air quality intelligence framework transforms civic management from a delayed, reactive posture into a data-driven dispatch system. Rather than awaiting post-inversion threshold breaches, multi-variable meteorological machine learning pipelines—leveraging forecast indicators such as horizontal wind stagnation below 1.5\ \t[span_51](start_span)[span_51](end_span)ext{m/s} and nocturnal boundary layer compression—forecast pollution events up to 36 hours in advance. This advance notice allows civic authorities to execute targeted municipal interventions before inversion layers stabilize. Mechanical dust abatement and street cleaning operations can be shifted from daytime hours to late afternoon windows, 4 to 6 hours before thermal inversion descent, directly targeting road corridors where continuous monitoring identifies silt loadings above 2\ \text{g/m}^2. Applying fine-droplet wet suppression and operating regenerative-air vacuum sweepers during this window stabilizes road silt, preventing vehicular turbulence from injecting coarse and fine dust into the evening transition layer.

Simultaneously, municipal transit management platforms can deploy dynamic routing and access restrictions for non-essential commercial vehicles around peripheral bypasses 12 hours prior to severe atmospheric stagnation. Diverting heavy diesel trucks away from narrow, densely settled urban street corridors curtails ground-level \text{NO}_x and black carbon emissions during the early hours of inversion formation, lowering morning concentration peaks.

Industrial emissions management is similarly strengthened through advance notification systems. Operators of brick kilns, secondary metallurgical furnaces, and concrete plants can reschedule high-emission batch production cycles during forecast low-dispersion periods, preventing industrial stack discharges from adding to stagnant local air masses.

Environmental Thermodynamics and Ecological Remediation

The operational benefits of predictive emission abatement extend beyond human exposure management, interrupting destructive thermodynamic feedbacks in the atmosphere and protecting regional ecosystems.

Disrupting the Aerosol-Radiation-Meteorology Feedback Mechanism

High concentrations of atmospheric aerosols—specifically light-absorbing black carbon and light-scattering secondary sulfates and nitrates—alter atmospheric thermodynamics through direct radiative forcing. In the lower atmosphere, these interactions trigger a self-reinforcing positive feedback cycle known as the aerosol-radiation-meteorological feedback loop. Suspended aerosol plumes scatter incoming solar radiation back into space and absorb radiation aloft, resulting in surface cooling alongside localized warming within the upper boundary layer near 925 hPa. This modifies the local thermal lapse rate, suppresses buoyant turbulence, enhances atmospheric stratification, and depresses planetary boundary layer heights by 200 to 400 meters.

The suppression of the planetary boundary layer traps primary pollutants within a restricted mixing volume. At the same time, suppressed vertical mixing and surface cooling reduce the

saturation vapor pressure, elevating relative humidity within the surface boundary layer. Elevated humidity promotes aqueous-phase and heterogeneous chemical reactions on existing aerosol surfaces, accelerating the transformation of precursor gases (SO_2, NO_x, and volatile organic compounds) into secondary inorganic and organic aerosols. Observational and modeling investigations identify a threshold $\text{PM}_{2.5}$ concentration range of 75 to 100 $\mu\text{g/m}^3$ above which this feedback loop becomes self-sustaining, leading to rapid, multi-day accumulations of surface haze.

Targeted, predictive curbs on primary absorbing aerosol emissions interrupt this feedback cycle before the critical stabilization threshold is crossed. Model sensitivity analyses show that mitigating primary black carbon emissions reduces heating in the upper boundary layer, allowing an increase in daytime boundary layer height of over 50 meters and preventing up to 40% of the additional $\text{PM}_{2.5}$ mass generated by the feedback loop during winter stagnation events.

Photochemical Ozone Suppression and Agro-Ecosystem Preservation

Urban centers across the Indo-Gangetic Plain frequently experience complex co-pollutant dynamics involving ground-level ozone (O_3) alongside particulate matter. Tropospheric ozone is a secondary photochemical oxidant produced through the photo-oxidation of volatile organic compounds and carbon monoxide in the presence of nitrogen oxides (NO_x), driven by solar ultraviolet radiation:

$$\text{NO}_2 + h\nu \ (\lambda < 420\text{ nm}) \rightarrow \text{NO} + \text{O}(^3\text{P})$$
$$\text{O}(^3\text{P}) + \text{O}_2 + \text{M} \rightarrow \text{O}_3 + \text{M}$$
$$\text{NO} + \text{O}_3 \rightarrow \text{NO}_2 + \text{O}_2 \quad (\text{Titration})$$

During severe particulate episodes, high aerosol optical depths attenuate solar actinic flux, suppressing photolysis rates and limiting photochemical ozone production. Conversely, indiscriminate reductions in particulate matter without coordinated precursor gas abatement can cause afternoon ozone spikes, as clearing the air allows greater solar radiation to penetrate while reducing aerosol surface area available for scavenging peroxy radicals. Predictive air quality platforms incorporate multi-pollutant chemical sensitivity models to determine whether the regional airshed is in a NO_x-saturated (VOC-limited) or NO_x-sensitive regime, optimizing the timing and composition of industrial and vehicular emission curbs to prevent post-fog ozone surges.

Limiting ground-level ozone exposure provides substantial ecological and agricultural benefits across regional rural-urban interfaces. Ozone enters plant foliage through stomatal pores during daytime gas exchange, generating reactive oxygen species that disrupt chloroplast membranes, reduce ribulose-1,5-bisphosphate carboxylase-oxygenase (rubisco) enzyme activity, inhibit photosynthesis, and accelerate premature leaf death. Crop exposure across the Indo-Gangetic Plain is evaluated using the AOT40 index, defined as the daylight accumulation of hourly ozone concentrations exceeding 40 parts per billion during active photosynthetic intervals ($G_{\text{rad}} > 50\ \text{W/m}^2$):

$$\text{AOT40} = \sum \max(0, [\text{O}_3] - 40\text{ ppb})$$

Across northern India, ambient AOT40 levels regularly exceed the established critical safety threshold of 3,000 $\text{ppb}\cdot\text{h}$ during the critical anthesis and grain filling stages of the winter wheat (*Triticum aestivum*) crop. High-resolution chemical transport simulations quantify relative yield losses for wheat in India between 6.4% and 14.9%, posing a substantial challenge to regional agricultural stability and food security. By forecasting photochemical pollution windows and proactively managing upstream urban transport and industrial emission

fluxes, regional management platforms can lower cumulative AOT40 levels, preventing foliar damage in peri-urban agro-ecosystems and supporting regional crop yields.

AeroWard: Application Architecture and Synthesis of Environmental Factors

The theoretical frameworks and predictive models detailed above culminate in the conceptualization of **AeroWard**, a predictive micro-climate intelligence and civic action dispatch platform. The platform's architecture explicitly integrates the three primary categories of environmental variables driving urban pollution:

1. **Meteorological and Thermodynamic Variables:** AeroWard ingests real-time weather API feeds and Sentinel-5P TROPOMI satellite data to model the meteorological engine of urban smog. By tracking temperature inversions, wind stagnation, and relative humidity, the platform predicts the onset of the aerosol-radiation-meteorological feedback loop. This allows the platform to forecast localized accumulation events 12 to 72 hours in advance, triggering automated building management systems (BMS) to pressurize indoor environments before external plumes infiltrate.
2. **Urban Morphology and Micro-Exposure:** Recognizing that city-wide AQI averages fail to capture localized risks, AeroWard utilizes computational fluid dynamics insights regarding urban "street canyons." Algorithms process building height-to-street width ratios (H/W) and building continuity (Build-to-Line Ratios) to map aerodynamic vortices that trap vehicle exhaust on leeward walkways. The platform's "Clean-Air Routing" module leverages this data to direct pedestrians and cyclists away from stagnant corridors, effectively reducing exposure by up to 40%.
3. **Spatiotemporal Source Apportionment:** Integrating data analogous to high-resolution source apportionment studies (such as those conducted in Kanpur and the wider Indo-Gangetic Plain), the platform attributes impending pollution spikes to specific sources—whether winter biomass burning (up to 26% of \text{PM}_{2.5}) or summer road dust. This diagnostic capability fuels the "Automated Civic Action Dispatcher," which issues targeted municipal directives, such as scheduling road vacuum sweeping ahead of dust accumulation or diverting heavy transit vehicles to mitigate early morning \text{NO}_x emissions. Ultimately, these integrated features protect public health while minimizing ecological damage, such as the severe foliar damage and yield loss inflicted on regional winter wheat crops by ground-level ozone exceeding the 3,000 \text{ppb}\cdot\text{h} AOT40 threshold.

Strategic Synthesis and Implementation Roadmap

Implementing a predictive air quality intelligence framework requires an integrated engineering and environmental policy roadmap. At the foundational data and modeling tier, computational architectures must incorporate dynamic Spatiotemporal Graph Neural Networks that continuously assimilate real-time CAAQMS telemetry, numerical meteorological inputs, and high-resolution Sentinel-5P TROPOMI UV absorbing aerosol indexes. This multi-modal deep learning architecture delivers low-latency, ward-level forecasts that bridge the spatial coverage gaps inherent in physical monitoring networks.

At the human exposure interface, platforms should translate ambient concentration forecasts

into parameterized dosage-minimization algorithms. Incorporating microclimatic street canyon dynamics, aspect ratios, and windward-leeward vortex patterns into algorithmic navigation engines enables individuals to choose lower-exposure travel corridors, while automated API integrations allow smart building management systems to execute pre-emptive HVAC pressurization and filtration cycles ahead of surface-level pollution spikes.
At the municipal and regional policy level, predictive air quality modeling enables an operational transition from reactive emergency measures to predictive Graded Response Action Plans. By forecasting boundary layer compression and atmospheric stagnation 36 hours in advance, municipal agencies can deploy targeted silt suppression over critical corridors, divert heavy freight away from vulnerable street canyons, and modulate industrial batch manufacturing. These coordinated pre-emptive interventions interrupt the positive aerosol-radiation-meteorology feedback loop, preventing extreme stagnation episodes, moderating daytime photochemical ozone formation, and mitigating environmental degradation across downstream agro-ecosystems.

Works cited

1. Spatio-temporal graph neural network for inter-city air quality, https://www.researchgate.net/publication/398088000_Spatio-temporal_graph_neural_network_for_inter-city_air_quality_forecasting 2. A Spatio-Temporal Graph Convolutional Network for Air Quality, https://ideas.repec.org/a/gam/jsusta/v15y2023i9p7624-d1140523.html 3. Improving regional air quality predictions in the Indo-Gangetic Plain, https://www.researchgate.net/publication/343724465_Improving_regional_air_quality_predictions_in_the_Indo-Gangetic_Plain-Case_study_of_an_intensive_pollution_episode_in_November_2017 4. Impacts on Meteorological Parameters and Pollutants by Aerosol, https://www.frontiersin.org/journals/environmental-science/articles/10.3389/fenvs.2022.947894/full 5. Graph Neural Network For Air Quality Prediction, https://theaspd.com/index.php/ijes/article/download/11754/8397/25005 6. Delhi's pollution puzzle: New study to reveal what's changed in a decade, https://m.economictimes.com/news/india/delhis-pollution-puzzle-new-study-to-reveal-whats-changed-in-a-decade/articleshow/135235155.cms 7. A decade on, Delhi-NCR to get new pollution source study with finer grid mapping, https://timesofindia.indiatimes.com/city/delhi/a-decade-on-delhi-ncr-to-get-new-pollution-source-study-with-finer-grid-mapping/articleshow/135217168.cms 8. Spatiotemporal Graph Neural Networks for Air Quality Forecasting, https://www.researchgate.net/publication/408394232_Spatiotemporal_Graph_Neural_Networks_for_Air_Quality_Forecasting_A_Comprehensive_Review_and_Future_Direction 9. Air Quality Prediction with Spatio-Temporal Graph Convolutional, https://africanjournalofbiomedicalresearch.com/index.php/AJBR/article/view/5497 10. Spatio-Temporal Field Neural Networks for Air Quality Inference - arXiv, https://arxiv.org/abs/2403.02354 11. Spatiotemporal PM2.5 forecasting via dynamic geographical Graph, https://www.semanticscholar.org/paper/b7d7f314e456de177e027c7fe0202a5a930a53af 12. Spatio-Temporal Monitoring of Atmospheric Pollutants Using Earth, https://www.mdpi.com/2220-9964/11/5/301 13. Real-Time Source Apportionment and Forecasting for Advance Air, https://www.dpcc.delhigovt.nic.in/uploads/news/819b9fef9cf4a2a574a10d3bbc421cfd.pdf 14. A Review on the Dispersion and Distribution Characteristics ... - MDPI,

https://www.mdpi.com/1996-1073/14/19/6155 15. Optimizing Pedestrian-Friendly Spaces in Xi'an's Residential Streets, https://www.mdpi.com/2073-4433/16/8/947 16. Comprehensive evaluation of an advanced street canyon air, https://www.tandfonline.com/doi/full/10.1080/10962247.2020.1803158 17. A CFD model to obtain human exposure to direct vehicular, https://ic-sd.org/wp-content/uploads/2019/11/Juan_Zavala.pdf 18. A numerical investigation of the impact of low boundary walls on, https://www.researchgate.net/publication/23490349_A_numerical_investigation_of_the_impact_of_low_boundary_walls_on_pedestrian_exposure_to_air_pollutants_in_urban_street_canyons 19. (PDF) A Review on the Dispersion and Distribution Characteristics, https://www.researchgate.net/publication/354875041_A_Review_on_the_Dispersion_and_Distribution_Characteristics_of_Pollutants_in_Street_Canyons_and_Improvement_Measures 20. Using a coupled LES-aerosol radiation model to investigate urban, https://d-nb.info/1207471569/34 21. Roles of Atmospheric Aerosols in Extreme Meteorological Events, https://as.nju.edu.cn/_upload/article/files/59/de/e75d6493402a9bdddf972cb5310/fe9b50d4-a8f3-42f0-ae09-fccb4ef55b5f.pdf 22. Air Quality Management in the Indo-Gangetic Plain and Himalayan, https://iiasa.ac.at/projects/gains-igp-hf 23. Air Quality Analysis for Kanpur, India - UrbanEmissions.Info, https://urbanemissions.info/india-apna/kanpur-india/ 24. Seasonal AQI Variations in Kanpur | PDF | Air Pollution - Scribd, https://www.scribd.com/document/881258864/Project 25. The pollutants in Delhi's air, and why they are hard to trace, https://www.hindustantimes.com/ht-explainers/pollutants-in-delhi-air-why-they-are-hard-to-trace-winter-air-pollution-smog-aqi-caqm-iitm-delhi-govt-curbs-101792987530842.html 26. Indian Institute of Technology, Kanpur (2010) Air Quality ... - SciRP.org, https://www.scirp.org/reference/referencespapers?referenceid=3436811 27. LoPN ok;q nh?kk, https://sustainabledevelopment.in/wp-content/uploads/2020/07/Cleaner-air-initiavtves-WEB.pdf 28. Air Quality Assessment, Trend Analysis, Emission Inventory and, https://home.iitk.ac.in/~mukesh/Publications/2022_IIT%20Kanpur_UPPCB_Final-Report-Kanpur-Source%20Apportionment%20and%20Emission%20Inventory.pdf 29. Aerosol radiative feedback enhances particulate pollution over India, https://www.researchgate.net/publication/367533002_Aerosol_radiative_feedback_enhances_particulate_pollution_over_India_A_process_understanding 30. Aerosol radiative effects and feedbacks on boundary layer, https://pdfs.semanticscholar.org/49fd/faf06073f8fadc9663929143da0a9c3acb84.pdf 31. Weakened Aerosol-PBL Interaction During COVID-19 Lockdown in, https://as.nju.edu.cn/_upload/article/files/59/de/e75d6493402a9bdddf972cb5310/7866ff95-ed76-4bfb-aaf9-632b2c284762.pdf 32. Rising ozone pollution as a threat to wheat yield in India, https://pubs.rsc.org/em/article/28/4/1047/1236792/Rising-ozone-pollution-as-a-threat-to-wheat-yield 33. A synthesis of AOT40-based response functions and critical levels of, https://ouci.dntb.gov.ua/en/works/4rjOKjX4/ 34. First observation-based study on surface O3 trend in Indo-Gangetic, https://www.semanticscholar.org/paper/d3562fb856f2785b6d29aae34b5a1c55bb3597b2 35. Loss of crop yields in India due to surface ozone - ResearchGate, https://www.researchgate.net/publication/318570063_Loss_of_crop_yields_in_India_due_to_surface_ozone_an_estimation_based_on_a_network_of_observations