beginabstract odoabstract endabstract

Execution-aware anytime replanning for multi-UAV missions: when to stop computing under uncertain execution, with validation on PX4 and Gazebo

Cao-Phuc Ha[a], Anh Nguyen Vu Minh[a], Phu-Nguyen Le[b,*]

[a]*Department of Artificial Intelligence, FPT University, Ho Chi Minh City, Vietnam*
[b]*Faculty of Electrical and Electronics Engineering, Vietnam Aerospace University, 104 Nguyen Van Troi Street, Phu Nhuan Ward, Ho Chi Minh City, 700000, Vietnam*

1. Introduction

Teams of unmanned aerial vehicles (UAVs) are used for inspection, delivery and monitoring. During a mission, new tasks may appear, a vehicle may fail, or a deadline may be moved forward. A central planner then repairs the routes of the whole fleet, while some UAVs may already wait for new instructions. Dynamic vehicle routing and multi-robot task allocation offer many methods for this repair [1–3], and metaheuristics such as adaptive large neighbourhood search (ALNS) [4] usually find good plans when enough time is available.

The time given to such a planner is usually fixed in advance, and the same budget is spent on easy and on hard events. This choice may be inefficient for two reasons. Many events leave little room for improvement, and on the others most of the improvement of an anytime search tends to arrive early. In addition, idle UAVs wait while the planner computes, so a later plan is not always a better plan. Anytime algorithms and metareasoning study this question in general terms [5–10]. In replanning, the cost of time is specific to the current plan. It depends on which UAVs are idle, on the slack in their routes and, in practice, on how reliably the plan will be executed.

Execution uncertainty changes this cost. A planner that assumes exact execution prices the delay of a plan with the slack that the plan promises. When UAVs accelerate, meet wind and take longer than expected at a task, a part of this slack is consumed by flight-time errors that the planner does not see. Errors also accumulate along a route between two replanning calls, which raises the question of when to replan at all. Validation is a further difficulty. Results obtained with a kinematic simulator may not hold for vehicles flown by an autopilot, while a physics-based simulation alone cannot provide the number of missions that a statistical comparison of planners requires.

This paper studies when a multi-UAV replanner should stop computing and publish its plan, first with exact execution and then under execution uncertainty. Its contributions are fourfold. The first is AnytimeSwarm, a replanner that repairs the previous plan, improves it with an anytime ALNS whose search trajectory does not depend on the budget, and stops when a learned prediction of the next improvement no longer exceeds a delay cost derived from the slack of the current plan. A proposition shows that this cost bounds the reward that a later publication loses. The second is AnytimeSwarm-R, an execution-aware stopping rule whose delay cost is the expected reward lost under a calibrated model of the finish-time error and of the expected dissemination latency. It reduces exactly to the deterministic cost when the error model is zero. The third is a two-tier evaluation framework. Tier B is a continuous-time kinematic simulator with acceleration limits, wind, speed and service-time errors and stochastic communication latency, drawn with common random numbers [11] so

*Corresponding author.
Email addresses: caophucai@gmail.com (Cao-Phuc Ha), anhnvmse203412@fpt.edu.vn (Anh Nguyen Vu Minh), nguyenlp@vaa.edu.vn (Phu-Nguyen Le)

that every planner faces the same disturbances. Tier C flies the same missions with three PX4 autopilots [12] in Gazebo [13], connected to the planner through ROS 2 [14], after a rescaling that keeps every dimensionless ratio of the decision problem. The fourth is a pre-registered evaluation. All design choices and error models were fixed on development seeds, the configuration was frozen with cryptographic hashes, and the main comparisons were run once on held-out seeds with mission-level paired bootstrap and Holm correction.

The remainder of this paper is organised as follows. Section 2 reviews related work. Section 3 formulates replanning with publication delay and uncertain execution. Section 4 describes AnytimeSwarm and AnytimeSwarm-R. Section 5 presents the evaluation framework and protocol. Section **??** reports the results, Section **??** discusses them together with the limitations of the study, and Section **??** concludes the paper.

2. Related work

Dynamic task allocation and routing. Multi-robot task allocation [1] and dynamic vehicle routing [2, 3] study how tasks can be reassigned when information changes. The planning problem considered here is a prize-collecting routing problem with time windows [15, 16]. Real-time routing has long been limited by the computation available between events. Gendreau et al. parallelised tabu search to fit more optimisation between request arrivals [17], and large neighbourhood search has been adapted to dynamic routing with time windows [18, 19] and to routing with drones [20]. For multi-UAV systems, auction methods such as CBBA [21, 22] reach conflict-free assignments quickly, uncertainty-gated allocation addresses intermittent communication [23], and centralised methods protect valid assignments or repair only affected route segments when events occur [24, 25]. These studies make the search faster or better within a given budget. The present work asks how much of the budget should be used for each event and how this choice depends on uncertain execution.

Uncertainty in routing and allocation. Stochastic vehicle routing models travel and service times or demands as random variables [26]. Scenario-based approaches plan against sampled futures in dynamic settings [27], and chance-constrained task allocation bounds the probability that a team misses its objectives [28]. These methods change the plan itself. AnytimeSwarm-R keeps the planning model and the search unchanged and uses the uncertainty only to price the delay of publishing a plan. The two ideas are complementary, and a risk-aware planner could be combined with the stopping rule studied here.

Metareasoning and anytime algorithms. Anytime algorithms [5, 8] and the rational allocation of computation [6, 7] form the conceptual basis of this work. Hansen and Zilberstein derive a monitoring policy by dynamic programming over a performance profile and a time-dependent utility [9]. Svegliato et al. predict the performance of an anytime algorithm online [10] and learn meta-level control with model-free reinforcement learning [29], and Sung et al. learn when an anytime motion planner should stop [30]. In these studies, the utility of time is usually a given function. In multi-UAV replanning, it follows from the plan at hand, from the vehicles that wait for it and, as studied here, from how reliably the plan will be executed.

Simulation-based validation of multi-UAV planning. Software-in-the-loop simulation with an autopilot and a physics simulator is a common step between algorithm design and flight tests. PX4 [12] runs the same flight stack in simulation and on hardware, Gazebo [13] provides vehicle dynamics and sensors, and ROS 2 [14] connects planners and vehicles. Such setups are rarely used for statistical comparisons of planners, because each mission runs in real time or close to it. The two-tier design of this paper uses the physical tier to validate a fast simulator that carries the statistical burden.

3. Problem formulation

3.1. Replanning snapshot

A central planner is called whenever a replanning trigger fires (Section 3.4). Each UAV keeps the task that it is currently flying to or serving. This committed task determines when and where the UAV becomes available again and how much energy it has left. Each open task has a location, a release time, a deadline by which its service must be completed, a service duration and a reward. A plan assigns an ordered sequence of open tasks to each UAV, and tasks may remain unassigned. The planning problem is therefore a prize-collecting routing problem with time windows [15, 16]. Arrival, start and finish times along a route are computed in the usual way for time windows [15, 31]. A route is feasible if every service ends before its deadline and the UAV returns to the depot with an energy reserve of 10% of its capacity. Flight consumes energy in proportion to the distance, hovering during service consumes energy over time, and waiting consumes no energy. A plan π is evaluated by

$$J(\pi) = \alpha R(\pi) - \gamma E(\pi) - \delta C(\pi), \tag{1}$$

where R is the reward of the tasks served on time, E is the flown distance in kilometres, and C is the number of tasks that move to a different UAV than in the previous plan. The weights are $\alpha = 1$, $\gamma = 0.05$ per kilometre and $\delta = 0.3$. Plan quality is reported in percent of W, the total reward of the open tasks.

3.2. Publication delay

Computation is not free. A plan that is computed for τ milliseconds is released $\kappa\tau$ milliseconds later in mission time. The latency factor κ converts planning time into mission time. The value $\kappa = 1$ corresponds to a planner that runs in real time on the evaluation computer, whereas larger values represent slower on-board processors. A UAV that is already idle must wait for the new plan, so its whole route starts later, and tasks whose deadline can no longer be met are lost. With $J_{\text{eff}}(\pi, \tau)$ as the objective of π after this shift, the net utility of publishing π after τ milliseconds is

$$U(\pi, \tau) = J_{\text{eff}}(\pi, \tau) - \mu W \tau, \tag{2}$$

where μ is the price of one millisecond of computation as a fraction of W. The planner thus chooses both a plan and the moment at which it stops computing.

3.3. Uncertain execution and dissemination

The planner uses a nominal model: straight legs at the cruise speed of each UAV and nominal service durations. The executed mission differs from this model in two ways. First, the finish time of task j is $F_j = f_j + e_j$, where f_j is the nominal finish time computed at publication and e_j is an execution error caused by acceleration, wind, speed tracking and service-time variability. Second, the plan reaches the vehicles after an additional dissemination latency L that is not under the control of the planner. A task yields its reward only if its actual finish time meets its deadline, which may have been tightened in the meantime. Following common practice in dispatching, a UAV skips a task at departure if the nominal estimate from its actual state already misses the deadline, and the task returns to the pool of open tasks. The performance measure of a mission is its utility, the reward of all tasks served on time divided by the total reward of all tasks of the mission.

3.4. Replanning triggers

Three trigger policies are considered. The event trigger replans on task arrivals, UAV failures and deadline changes only. The periodic trigger additionally replans every T seconds of mission time. The deviation trigger additionally replans when the actual finish of a planned task deviates from its planned finish by more than θ seconds. During planning, every UAV finishes its committed task and then waits for the new plan, and events that arrive during planning are queued. These semantics are identical in both simulation tiers.




Figure 1: Overview of AnytimeSwarm: (a) an event changes the mission, (b) the planner repairs and improves the plan, (c) the stopping rule decides when to publish it.

4. Method

AnytimeSwarm consists of a repair module, an anytime search and a stopping rule. Fig. 1 illustrates how the three modules interact during one replanning call. AnytimeSwarm-R differs only in the delay cost used by the stopping rule.

4.1. Feasibility-first repair

The previous plan is first restricted to the open tasks. Each route is then walked once, and a task is kept only if the route up to this task is still feasible, so the result is feasible by construction. Tasks of a failed UAV, removed tasks and new tasks are then inserted with parallel regret-2 insertion [4, 32], and only insertions that increase the objective are made. This feasibility-first repair (FFR) yields a publishable plan within milliseconds and provides the starting point of the search.

4.2. Anytime adaptive large neighbourhood search

The plan is then improved by ALNS [4]. Four destroy operators remove between 10% and 35% of the assigned tasks, and at least two. They select tasks at random, by their contribution to the objective, by relatedness [33] or as a segment of a route. Four repair operators apply greedy or regret-2 insertion, each with and without noise. Operators are chosen by adaptive roulette-wheel selection, and new solutions are accepted by simulated annealing [34]. All intermediate solutions are feasible, so the best plan found so far can be published at any time. The temperature decreases per iteration rather than per unit of time, and all variants use the same random seed. Every stopping rule therefore follows the same search trajectory and differs only in the moment at which it stops.

4.3. Adaptive stopping

Every 5 ms, the stopping rule compares the predicted gain of searching for another $H = 10$ ms with the cost of doing so. With $\widehat{\Delta J}$ as the predicted gain, the search stops at time τ if

$$\widehat{\Delta J} \;\le\; C_{\text{delay}}(\tau) + \mu W H. \tag{3}$$

The gain is predicted from the search history by a Poisson generalised linear model with a log link [35] and a small L_2 penalty. Its eleven features describe the elapsed time, the number of iterations, the recent improvements over 5 ms, over 20 ms and over the second half of the elapsed time, the time since the last improvement, the total improvement over the repaired plan, the unassigned share of the reward, the numbers of tasks and UAVs, and the iteration rate. The target is the improvement in the next 10 ms in percent of W. The model is fitted on 500 ms search trajectories of development scenarios only, and a prediction costs one dot product. The search loop enforces the hard time budget independently of the stopping rule.

4.4. Deterministic delay cost

The delay cost is computed from the best plan found so far. A late start of a route is partly absorbed by the waiting times along it, in the same way as the forward time slack of routing with time windows [31]. The tolerance tol_j of a task is the margin between its finish time and its deadline, plus all waiting times on the route up to this task. A task is lost when the start shift $\sigma_j(\tau)$ of its route exceeds its tolerance. The start shift is zero for a UAV that is still busy, and it equals the waiting time until the publication for an idle UAV. With v_j as the contribution of task j to the objective and $\Lambda(\tau) = \sum_j v_j \mathbb{1}[\sigma_j(\tau) > \mathrm{tol}_j]$, the delay cost of searching H milliseconds longer is $C_{\mathrm{delay}}(\tau) = \Lambda(\tau + H) - \Lambda(\tau)$.

Proposition 1. *For a feasible plan executed exactly, (i) $\Lambda(\tau)$ is the reward lost through missed deadlines if every UAV follows its route, (ii) the loss of the objective is at most $\Lambda(\tau)$ if late tasks are skipped, and (iii) $\Lambda(\tau)$ does not decrease with τ and is zero while all UAVs are busy with their committed tasks. Hence C_{delay} is non-negative and vanishes while no UAV is waiting.*

Proof. A route that starts later by some shift reaches its first task later by the same amount. Each waiting time absorbs part of the delay, so the delay at the end of a task equals the start shift minus all earlier waiting times, if this difference is positive. The task therefore misses its deadline exactly when the start shift exceeds its tolerance. Waiting consumes no energy, which proves (i). If late tasks are skipped, the triangle inequality ensures that every later task is reached no later and with no more energy. All tasks that are on time in (i) remain on time, and the flown distance does not grow. Every assigned task has a positive value, because each reward is at least α and $\delta < \alpha$, which proves (ii). Part (iii) holds because the start shift does not decrease with τ and every tolerance is non-negative in a feasible plan.

4.5. Execution-aware delay cost

Under uncertain execution, task j is lost when $\sigma_j(\tau) + e_j > \mathrm{tol}_j$, where e_j is its finish-time error. AnytimeSwarm-R replaces the indicator in Λ by the probability of this event. The error of task j is modelled as $e_j \sim \mathcal{N}(m(h_j), s(h_j)^2)$, where $h_j = f_j - t_0$ is its lead time, the nominal finish time minus the time of the planning snapshot. The mean and the spread are linear in the lead time,

$$m(h) = b_0 + b_1 h, \qquad s(h) = s_0 + s_1 h, \tag{4}$$

because errors accumulate along a route. The expected dissemination latency $\bar{L}$ is added to the start shift. The expected loss and the execution-aware delay cost are

$$\Lambda_{\mathrm{R}}(\tau) = \sum_j v_j \, \Phi\!\left(\frac{\sigma_j(\tau) + \bar{L} + m(h_j) - \mathrm{tol}_j}{s(h_j)}\right), \qquad C_{\mathrm{R}}(\tau) = \Lambda_{\mathrm{R}}(\tau + H) - \Lambda_{\mathrm{R}}(\tau), \tag{5}$$

where Φ is the standard normal distribution function and the start shift now includes $\bar{L}$ for idle UAVs. Search and predictor are unchanged, and C_{R} replaces C_{delay} in Eq. (3).

Proposition 2. *(i) With $b_0 = b_1 = s_0 = s_1 = 0$ and $\bar{L} = 0$, $\Lambda_{\mathrm{R}} = \Lambda$ and AnytimeSwarm-R takes exactly the decisions of AnytimeSwarm. (ii) $\Lambda_{\mathrm{R}}(\tau)$ does not decrease with τ, so $C_{\mathrm{R}} \geq 0$. (iii) Under the error model, $\Lambda_{\mathrm{R}}(\tau)$ is the expected value of the tasks whose deadline is missed if every UAV follows its route.*

Proof. With zero spread, Φ is read as the indicator of a positive argument, which gives (i). The start shift does not decrease with τ and Φ is non-decreasing, which gives (ii). Part (iii) follows from the proof of Proposition 1, because task j misses its deadline exactly when its delay at the finish, $\sigma_j + e_j$ minus the absorbed waiting time, is positive, and the expectation of the indicator of this event is the probability in Eq. (5).

Table 1: Scenario generator parameters (distances in m, times in s, energy in metres of flight).

Map side / horizon	10 000 / 1 800	Service time	$U[30, 90]$
UAV speed	$U[10, 16]$ m/s	Time-window slack	$U[180, 600]$
Energy capacity	$U[18, 28]$ km	Release delay	$U[0, 120]$
Energy reserve	10% of capacity	Rewards 1, 2, 3, 5	probabilities .4, .3, .2, .1
Hover cost	6 per second	Hotspots	3, std. 600, 50% of tasks
Tasks known at start	50%	Scales (UAVs/tasks)	5/25, 10/50, 20/140, 40/280

The execution-aware cost differs from the deterministic one in two ways. It grows smoothly before a task becomes infeasible, because a task with little remaining slack is already at risk, and it can be positive for a busy UAV through $\bar{L}$. It is also smaller than the deterministic cost for tasks whose tolerance is already consumed by the expected error, because waiting longer cannot lose a task that is likely lost anyway. The parameters of Eq. (4) are fitted on development missions. The mean is estimated by least squares, and the spread by least squares on the absolute residuals scaled by $\sqrt{\pi/2}$, which is less sensitive to the heavy tail of the errors than squared residuals. The latency $\bar{L}$ is the mean of the latency distribution in tier B and the measured mean plan-acceptance latency in tier C.

5. Evaluation framework

5.1. Scenarios

Missions are created by a seeded generator with the parameters in Table 1. The map is a square with a side of 10 km and the depot at its centre, and half of the tasks are clustered around three hotspots. Half of the tasks are known at the start, and the others arrive in batches. Three fleet scales with 5, 10 and 20 UAVs and 25, 50 and 140 tasks are combined with three event profiles. The arrivals profile contains six arrival batches, the failures profile three batches and two UAV failures, and the deadlines profile three batches and four tightened deadlines. A fourth scale with 40 UAVs and 280 tasks is used for scalability only.

5.2. Static snapshots with exact execution

The stopping rules are first compared without execution uncertainty. Each mission is simulated once with a deterministic reference planner, and every replanning call after the start is stored with its previous plan. All methods are evaluated on these snapshots, and regret is measured against the best known objective of each snapshot, which includes a 3 s ALNS run and, for the small and medium scales, the OR-Tools routing solver [36] with guided local search [37]. Because all ALNS variants follow the same search trajectory, whole families of each rule are evaluated exactly offline, with 12 fixed budgets, 10 stagnation patience values and 9 compute prices, and each baseline is compared with AnytimeSwarm at the same mean computation. This benchmark uses its own pre-registered test seeds 2000–2029 (1562 snapshots of 270 missions), and it was reproduced on the final software platform before the execution-aware study (Section **??**).

5.3. Tier B: kinematic execution with disturbances and latency

Tier B executes each published plan in continuous mission time. The duration of a leg follows a trapezoidal speed profile with a horizontal acceleration limit. The cruise airspeed of each (UAV, task) leg deviates from the nominal speed by a multiplicative error, and a constant wind of fixed magnitude and random direction changes the ground speed through the wind triangle. Service durations are multiplied by a random factor. Energy is counted as metres flown through the air plus the hover cost. The planner never sees these disturbances. It receives the state of each UAV as telemetry, and the remaining time of a committed task is estimated with the nominal model from the actual position of the UAV. The dissemination latency of a plan is lognormal, and each message is lost with a given probability and resent after a timeout. Table 2 lists the

Table 2: Disturbance and latency levels of tier B.

Execution	accel. (m/s^2)	speed c.v.	wind (m/s)	service c.v.	Latency	median (s)	$\sigma_{\log}$	loss / timeout
nominal	∞	0	0	0	none	0	–	–
low	3.0	0.03	2	0.05	low	0.2	0.5	–
mid	2.0	0.07	5	0.15	high	2.0	0.8	5% / 5 s
high	1.5	0.12	8	0.25				

disturbance and latency levels. They span a range from mild to severe conditions and are not claimed to represent a particular vehicle.

All random draws use common random numbers [11]. The speed error of a leg depends only on the mission seed, the UAV and the task, the service factor only on the mission seed and the task, the wind only on the mission seed, and the latency only on the mission seed and the event. Two planners that assign the same task to the same UAV therefore experience the same disturbance, independently of the number of replanning calls. With zero disturbance, zero latency and the event trigger, tier B reproduces the discrete-event simulator of the original formulation exactly, which is verified by unit tests.

5.4. Tier C: PX4 software-in-the-loop with Gazebo and ROS 2

Tier C flies missions with three X500 quadrotors, each controlled by its own PX4 v1.17 autopilot in software-in-the-loop mode [12], in Gazebo Harmonic [13], on ROS 2 Jazzy [14] (Fig. 2). A uXRCE-DDS bridge exposes the internal topics of each autopilot to ROS 2. Three nodes form the mission stack. The mission manager runs the scenario timeline, builds the planning snapshot from the fleet state, calls the planner and releases the plan. The executor streams offboard setpoints to every autopilot at 10 Hz, so that PX4 does not leave offboard mode while the planner computes. It flies each leg with a carrot that moves along the straight leg at the commanded ground speed, holds the UAV at the task for the service duration and reports service start, finish and skips. A visualisation node draws tasks, routes and planning decisions in RViz 2 and as coloured pillars in the Gazebo scene. Planning time is measured with a monotonic wall clock, and every mission time is simulation time.

A tier C mission is a tier B scenario with three UAVs and fifteen tasks, which keeps the ratio of five tasks per UAV of the small scale, rescaled by $S_X = 0.1$ in length and $S_T = 0.25$ in time. Speeds are multiplied by S_X/S_T, energy by S_X, the hover cost by S_X/S_T and the distance price by $1/S_X$. Every dimensionless ratio of the decision problem is preserved, so a tier C mission is the same decision problem as its tier B counterpart, flown in a 1 km world in 450 s with cruise speeds of 4–6.4 m/s. A planning delay of τ in tier C corresponds to τ/S_T in tier B, so the latency factors are related by $\kappa_C = S_T\kappa_B$. Disturbances use the same common random numbers as tier B. The commanded ground speed of each leg follows the speed error and the wind triangle, with the wind scaled by S_X/S_T, and the service duration follows the same factor. Acceleration, attitude dynamics, position tracking and communication are those of the simulated vehicles. Gazebo runs in lockstep with PX4 at twice real time, which requires $\kappa_C \geq 2$ so that the emulated planning delay dominates the real one.

5.5. Compared methods

The constructive baseline is regret-2 repair, that is, FFR without search. ALNS is run with the full budget of 250 ms, with a fixed budget of 40 ms, which equals the mean computation of AnytimeSwarm on development data, and with a stagnation rule that stops after 20% of the budget without improvement. AnytimeSwarm is used exactly as frozen after development, without retraining, and an ablation removes its delay cost. AnytimeSwarm-R uses the error model of the execution level of the mission and the expected latency of its latency level. A further ablation sets its error model to zero, so that only the latency term remains, and a sensitivity study uses the error model of another level. For 40 UAVs, the fixed budget matched




Figure 2: Tier C architecture. The planner and the mission timeline run in the mission manager; the executor streams offboard setpoints to three PX4 autopilots that fly X500 quadrotors in Gazebo.

to the computation of AnytimeSwarm on development data is 180 ms. All ALNS variants share operators, parameters, initial plan and seed, and every call has a hard budget of 250 ms.

5.6. Protocol and statistics

Development used seeds 0–9 in tier B and 0–2 in tier C. The predictor was trained on development trajectories, and the compute price $\mu = 10^{-5}$ was selected by a rule stated before any test run. The tier B error models were fitted on 90 development missions per level flown by ALNS with 40 ms, and the tier C models on nine development flights per level. The fitted models are listed in Table 3. The experiment configurations, the error models, the predictor and the experiment code were then frozen with SHA-256 hashes, and the held-out runs checked these hashes before starting. Tier B uses held-out seeds 3000–3029, which gives 270 missions for the three scales and three profiles, and 90 missions for 40 UAVs. Tier C uses held-out seeds 4000–4009 with three profiles, that is, 30 missions per method. The primary tier B matrix crosses two execution levels (low, mid), two latency levels (none, high), two latency factors ($\kappa_B = 10, 50$) and two triggers (event, periodic every 60 s).

The primary hypothesis is that AnytimeSwarm-R serves more reward than ALNS with 40 ms, AnytimeSwarm and the stagnation rule over the primary matrix. For each mission, the utility difference is averaged over the sixteen configurations of the matrix, and the mean over missions is tested with a paired bootstrap [38] of 10 000 resamples. The three comparisons are corrected with the Holm procedure [39]. The same pooled test compares the computation per planning call with that of AnytimeSwarm and the periodic trigger with the event trigger. In tier C, AnytimeSwarm-R is compared with ALNS with 40 ms and with

Table 3: Finish-time error models fitted on development missions: $m(h) = b_0 + b_1 h$, $s(h) = s_0 + s_1 h$ (seconds of the respective tier; n executed tasks).

Tier	Level	n	b_0	b_1	s_0	s_1
B	low	5399	8.91	-0.0044	0.00	0.0904
B	mid	4991	16.84	0.0354	1.58	0.1951
B	high	4253	20.79	0.2923	0.00	0.6389
C	low	90	-1.23	0.0281	1.30	0.0545
C	mid	89	2.36	0.0297	0.00	0.2303

AnytimeSwarm, again with Holm correction, and the same 30 missions are also run in tier B to assess whether tier B ranks the methods as tier C does. All other comparisons are descriptive. A tier C run in which a vehicle does not reach its altitude within 90 s of simulation time is aborted and repeated once with the same seed. The full protocol was written before the held-out runs and is available with the code. Tier B runs four missions in parallel on an Intel Core i7-11800H laptop, with all methods of a configuration run in turn, so that they share the same machine load. All runs use Python 3.12 and pinned package versions. Every plan is checked for feasibility before publication, and a separately written validator that shares no code with the planner found no infeasible plan among 4 779 development plans of all methods.

CRediT authorship contribution statement

Cao-Phuc Ha: Conceptualization, Methodology, Software, Investigation, Formal analysis, Writing – original draft. Anh Nguyen Vu Minh: Software, Validation, Writing – review and editing. Phu-Nguyen Le: Supervision, Methodology, Writing – review and editing.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data and code availability

The planner, both simulation tiers, the experiment configurations with their SHA-256 hashes, the pre-registered protocol, all raw results and the scripts that produce every number, table and figure of this paper will be made available in a public repository upon publication.

Acknowledgements

The authors would like to express their sincere appreciation to the Vietnam Aerospace University for supporting this research during the 2026–2027 academic year.

References

[1] B. P. Gerkey, M. J. Matarić, A formal analysis and taxonomy of task allocation in multi-robot systems, The International Journal of Robotics Research 23 (9) (2004) 939–954. doi:10.1177/0278364904045564.

[2] V. Pillac, M. Gendreau, C. Guéret, A. L. Medaglia, A review of dynamic vehicle routing problems, European Journal of Operational Research 225 (1) (2013) 1–11. doi:10.1016/j.ejor.2012.08.015.

[3] H. N. Psaraftis, M. Wen, C. A. Kontovas, Dynamic vehicle routing problems: Three decades and counting, Networks 67 (1) (2016) 3–31. doi:10.1002/net.21628.

[4] S. Ropke, D. Pisinger, An adaptive large neighborhood search heuristic for the pickup and delivery problem with time windows, Transportation Science 40 (4) (2006) 455–472. doi:10.1287/trsc.1050.0135.

[5] T. Dean, M. Boddy, An analysis of time-dependent planning, in: Proceedings of the Seventh National Conference on Artificial Intelligence (AAAI-88), AAAI Press, 1988, pp. 49–54.

[6] E. J. Horvitz, Reasoning about beliefs and actions under computational resource constraints, in: Proceedings of the Third Workshop on Uncertainty in Artificial Intelligence, AAAI and Association for Uncertainty in Artificial Intelligence, Seattle, WA, 1987.

[7] S. Russell, E. Wefald, Do the Right Thing: Studies in Limited Rationality, MIT Press, Cambridge, MA, 1991. doi:10.7551/mitpress/2474.001.0001.

[8] S. Zilberstein, Using anytime algorithms in intelligent systems, AI Magazine 17 (3) (1996) 73–83. doi:10.1609/aimag.v17i3.1232.

[9] E. A. Hansen, S. Zilberstein, Monitoring and control of anytime algorithms: A dynamic programming approach, Artificial Intelligence 126 (1–2) (2001) 139–157. doi:10.1016/S0004-3702(00)00068-0.

[10] J. Svegliato, K. H. Wray, S. Zilberstein, Meta-level control of anytime algorithms with online performance prediction, in: Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence (IJCAI-18), IJCAI Organization, 2018, pp. 1499–1505. doi:10.24963/ijcai.2018/208.

[11] A. M. Law, Simulation Modeling and Analysis, 5th Edition, McGraw-Hill Education, New York, 2015.

[12] L. Meier, D. Honegger, M. Pollefeys, PX4: A node-based multithreaded open source robotics framework for deeply embedded platforms, in: Proceedings of the IEEE International Conference on Robotics and Automation (ICRA), 2015, pp. 6235–6240. doi:10.1109/ICRA.2015.7140074.

[13] N. Koenig, A. Howard, Design and use paradigms for Gazebo, an open-source multi-robot simulator, in: Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), 2004, pp. 2149–2154. doi:10.1109/IROS.2004.1389727.

[14] S. Macenski, T. Foote, B. Gerkey, C. Lalancette, W. Woodall, Robot operating system 2: Design, architecture, and uses in the wild, Science Robotics 7 (66) (2022) eabm6074. doi:10.1126/scirobotics.abm6074.

[15] M. M. Solomon, Algorithms for the vehicle routing and scheduling problems with time window constraints, Operations Research 35 (2) (1987) 254–265. doi:10.1287/opre.35.2.254.

[16] P. Vansteenwegen, W. Souffriau, D. Van Oudheusden, The orienteering problem: A survey, European Journal of Operational Research 209 (1) (2011) 1–10. doi:10.1016/j.ejor.2010.03.045.

[17] M. Gendreau, F. Guertin, J.-Y. Potvin, É. Taillard, Parallel tabu search for real-time vehicle routing and dispatching, Transportation Science 33 (4) (1999) 381–390. doi:10.1287/trsc.33.4.381.

[18] L. Hong, An improved LNS algorithm for real-time vehicle routing problem with time windows, Computers & Operations Research 39 (2) (2012) 151–163. doi:10.1016/j.cor.2011.03.006.

[19] S. Wang, W. Sun, M. Huang, An adaptive large neighborhood search for the multi-depot dynamic vehicle routing problem with time windows, Computers & Industrial Engineering 191 (2024) 110122. doi:10.1016/j.cie.2024.110122.

[20] D. Sacramento, D. Pisinger, S. Ropke, An adaptive large neighborhood search metaheuristic for the vehicle routing problem with drones, Transportation Research Part C: Emerging Technologies 102 (2019) 289–315. doi:10.1016/j.trc.2019.02.018.

[21] H.-L. Choi, L. Brunet, J. P. How, Consensus-based decentralized auctions for robust task allocation, IEEE Transactions on Robotics 25 (4) (2009) 912–926. doi:10.1109/TRO.2009.2022423.

[22] L. Bertuccelli, H.-L. Choi, P. Cho, J. How, Real-time multi-UAV task assignment in dynamic and uncertain environments, in: AIAA Guidance, Navigation, and Control Conference, American Institute of Aeronautics and Astronautics, 2009, AIAA Paper 2009-5776. doi:10.2514/6.2009-5776.

[23] C. Qian, B. Fu, Uncertainty-gated distributed dynamic task allocation for multi-UAV systems under intermittent communication, Drones 10 (10) (2026) 782. doi:10.3390/drones10100782.

[24] S.-Y. Hwang, S. Oh, J.-C. Lee, S. Lee, J.-H. Lee, H.-J. Hwang, Assignment-preserving replanning for dynamic task allocation in multi-UAV systems, Applied Sciences 16 (19) (2026) 9414. doi:10.3390/app16199414.

[25] Y. Shen, T. Hu, Y. Wan, H. Sun, M. Tan, Edge-responsive local-repair particle swarm optimization for dynamic spatiotemporal task allocation of IoT-connected UAV swarms, IEEE Access 14 (2026) 115169–115190. doi:10.1109/ACCESS.2026.3717031.

[26] M. Gendreau, G. Laporte, R. Séguin, Stochastic vehicle routing, European Journal of Operational Research 88 (1) (1996) 3–12. doi:10.1016/0377-2217(95)00050-X.

[27] R. W. Bent, P. Van Hentenryck, Scenario-based planning for partially dynamic vehicle routing with stochastic customers, Operations Research 52 (6) (2004) 977–987. doi:10.1287/opre.1040.0124.

[28] S. S. Ponda, L. B. Johnson, J. P. How, Distributed chance-constrained task allocation for autonomous multi-agent teams, in: Proceedings of the American Control Conference (ACC), 2012, pp. 4528–4533. doi:10.1109/ACC.2012.6315626.

[29] J. Svegliato, P. Sharma, S. Zilberstein, A model-free approach to meta-level control of anytime algorithms, in: Proceedings of the 2020 IEEE International Conference on Robotics and Automation (ICRA), IEEE, 2020, pp. 11436–11442. doi:10.1109/ICRA40945.2020.9196898.

[30] Y. Sung, L. P. Kaelbling, T. Lozano-Pérez, Learning when to quit: Meta-reasoning for motion planning, in: Proceedings of the 2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), IEEE, 2021, pp. 4692–4699. doi:10.1109/IROS51168.2021.9636864.

[31] M. W. P. Savelsbergh, The vehicle routing problem with time windows: Minimizing route duration, ORSA Journal on Computing 4 (2) (1992) 146–154. doi:10.1287/ijoc.4.2.146.

[32] J.-Y. Potvin, J.-M. Rousseau, A parallel route building algorithm for the vehicle routing and scheduling problem with time windows, European Journal of Operational Research 66 (3) (1993) 331–340. doi:10.1016/0377-2217(93)90221-8.

[33] P. Shaw, Using constraint programming and local search methods to solve vehicle routing problems, in: Principles and Practice of Constraint Programming – CP98, Vol. 1520 of Lecture Notes in Computer Science, Springer, 1998, pp. 417–431. doi:10.1007/3-540-49481-2_30.

[34] S. Kirkpatrick, C. D. Gelatt, M. P. Vecchi, Optimization by simulated annealing, Science 220 (4598) (1983) 671–680. doi:10.1126/science.220.4598.671.

[35] P. McCullagh, J. A. Nelder, Generalized Linear Models, 2nd Edition, Chapman and Hall, London, 1989. doi:10.1007/978-1-4899-3242-6.

[36] L. Perron, V. Furnon, OR-Tools, https://developers.google.com/optimization, version 9.15 (2026).

[37] C. Voudouris, E. Tsang, Guided local search and its application to the traveling salesman problem, European Journal of Operational Research 113 (2) (1999) 469–499. doi:10.1016/S0377-2217(98)00099-X.

[38] B. Efron, R. J. Tibshirani, An Introduction to the Bootstrap, Chapman and Hall, New York, 1993. doi:10.1007/978-1-4899-4541-9.

[39] S. Holm, A simple sequentially rejective multiple test procedure, Scandinavian Journal of Statistics 6 (2) (1979) 65–70.